

WD 1539-1

**J3/16-007
(F2015 Working Document)**

4th January 2016 14:22

This is an internal working document of J3 and WG5.

NOTE: This working document is only available as a PDF file.

This page intentionally left nonblank.

Contents

Foreword	xv
Introduction	xvi
1 Overview	1
1.1 Scope	1
1.2 Normative references	1
1.3 Terms and definitions	2
1.4 Notation, symbols and abbreviated terms	21
1.4.1 Syntax rules	21
1.4.2 Constraints	22
1.4.3 Assumed syntax rules	23
1.4.4 Syntax conventions and characteristics	23
1.4.5 Text conventions	23
1.5 Conformance	23
1.6 Compatibility	25
1.6.1 Previous Fortran standards	25
1.6.2 New intrinsic procedures	25
1.6.3 Fortran 2008 compatibility	25
1.6.4 Fortran 2003 compatibility	25
1.6.5 Fortran 95 compatibility	26
1.6.6 Fortran 90 compatibility	26
1.6.7 FORTRAN 77 compatibility	26
1.7 Deleted and obsolescent features	27
1.7.1 General	27
1.7.2 Nature of deleted features	27
1.7.3 Nature of obsolescent features	27
2 Fortran concepts	29
2.1 High level syntax	29
2.2 Program unit concepts	32
2.2.1 Program units and scoping units	32
2.2.2 Program	32
2.2.3 Procedure	32
2.2.4 Module	33
2.2.5 Submodule	33
2.3 Execution concepts	33
2.3.1 Statement classification	33
2.3.2 Statement order	33
2.3.3 The END statement	34
2.3.4 Program execution	34
2.3.5 Execution sequence	35
2.3.6 Termination of execution	35
2.4 Data concepts	36
2.4.1 Type	36
2.4.2 Data value	36
2.4.3 Data entity	37
2.4.4 Definition of objects and pointers	38

2.4.5	Reference	38
2.4.6	Array	38
2.4.7	Coarray	39
2.4.8	Pointer	39
2.4.9	Allocatable variables	40
2.4.10	Storage	40
2.5	Fundamental concepts	40
2.5.1	Names and designators	40
2.5.2	Statement keyword	40
2.5.3	Other keywords	40
2.5.4	Association	40
2.5.5	Intrinsic	41
2.5.6	Operator	41
2.5.7	Companion processors	41
3	Lexical tokens and source form	43
3.1	Processor character set	43
3.1.1	Characters	43
3.1.2	Letters	43
3.1.3	Digits	43
3.1.4	Underscore	43
3.1.5	Special characters	43
3.1.6	Other characters	44
3.2	Low-level syntax	44
3.2.1	Tokens	44
3.2.2	Names	44
3.2.3	Constants	45
3.2.4	Operators	45
3.2.5	Statement labels	46
3.2.6	Delimiters	46
3.3	Source form	47
3.3.1	Program units, statements, and lines	47
3.3.2	Free source form	47
3.3.3	Fixed source form	48
3.4	Including source text	49
4	Types	51
4.1	Characteristics of types	51
4.1.1	The concept of type	51
4.1.2	Type classification	51
4.1.3	Set of values	51
4.1.4	Constants	51
4.1.5	Operations	51
4.2	Type parameters	52
4.3	Types, type specifiers, and values	52
4.3.1	Relationship of types and values to objects	52
4.3.2	Type specifiers and type compatibility	53
4.4	Intrinsic types	55
4.4.1	Classification and specification	55
4.4.2	Intrinsic operations on intrinsic types	55
4.4.3	Numeric intrinsic types	55
4.4.4	Character type	59
4.4.5	Logical type	62
4.5	Derived types	62
4.5.1	Derived type concepts	62
4.5.2	Derived-type definition	63

4.5.3	Derived-type parameters	66
4.5.4	Components	68
4.5.5	Type-bound procedures	75
4.5.6	Final subroutines	77
4.5.7	Type extension	79
4.5.8	Derived-type values	81
4.5.9	Derived-type specifier	81
4.5.10	Construction of derived-type values	82
4.5.11	Derived-type operations and assignment	84
4.6	Enumerations and enumerators	84
4.7	Binary, octal, and hexadecimal literal constants	86
4.8	Construction of array values	86
5	Attribute declarations and specifications	89
5.1	Attributes of procedures and data objects	89
5.2	Type declaration statement	89
5.3	Automatic data objects	91
5.4	Initialization	91
5.5	Attributes	91
5.5.1	Attribute specification	91
5.5.2	Accessibility attribute	92
5.5.3	ALLOCATABLE attribute	93
5.5.4	ASYNCHRONOUS attribute	93
5.5.5	BIND attribute for data entities	94
5.5.6	CODIMENSION attribute	94
5.5.7	CONTIGUOUS attribute	96
5.5.8	DIMENSION attribute	97
5.5.9	EXTERNAL attribute	100
5.5.10	INTENT attribute	100
5.5.11	INTRINSIC attribute	102
5.5.12	OPTIONAL attribute	103
5.5.13	PARAMETER attribute	103
5.5.14	POINTER attribute	103
5.5.15	PROTECTED attribute	104
5.5.16	SAVE attribute	104
5.5.17	TARGET attribute	105
5.5.18	VALUE attribute	105
5.5.19	VOLATILE attribute	105
5.6	Attribute specification statements	106
5.6.1	Accessibility statement	106
5.6.2	ALLOCATABLE statement	107
5.6.3	ASYNCHRONOUS statement	107
5.6.4	BIND statement	107
5.6.5	CODIMENSION statement	107
5.6.6	CONTIGUOUS statement	108
5.6.7	DATA statement	108
5.6.8	DIMENSION statement	110
5.6.9	INTENT statement	110
5.6.10	OPTIONAL statement	111
5.6.11	PARAMETER statement	111
5.6.12	POINTER statement	111
5.6.13	PROTECTED statement	112
5.6.14	SAVE statement	112
5.6.15	TARGET statement	112
5.6.16	VALUE statement	112
5.6.17	VOLATILE statement	113

5.7	IMPLICIT statement	113
5.8	NAMelist statement	115
5.9	Storage association of data objects	116
5.9.1	EQUIVALENCE statement	116
5.9.2	COMMON statement	118
5.9.3	Restrictions on common and equivalence	120
6	Use of data objects	121
6.1	Designator	121
6.2	Variable	121
6.3	Constants	122
6.4	Scalars	122
6.4.1	Substrings	122
6.4.2	Structure components	122
6.4.3	Coindexed named objects	124
6.4.4	Complex parts	124
6.4.5	Type parameter inquiry	124
6.5	Arrays	125
6.5.1	Order of reference	125
6.5.2	Whole arrays	125
6.5.3	Array elements and array sections	125
6.5.4	Simply contiguous array designators	128
6.6	Image selectors	129
6.7	Dynamic association	130
6.7.1	ALLOCATE statement	130
6.7.2	NULLIFY statement	133
6.7.3	DEALLOCATE statement	134
6.7.4	STAT= specifier	136
6.7.5	ERRMSG= specifier	136
7	Expressions and assignment	137
7.1	Expressions	137
7.1.1	Expression semantics	137
7.1.2	Form of an expression	137
7.1.3	Precedence of operators	141
7.1.4	Evaluation of operations	143
7.1.5	Intrinsic operations	143
7.1.6	Defined operations	150
7.1.7	Evaluation of operands	151
7.1.8	Integrity of parentheses	152
7.1.9	Type, type parameters, and shape of an expression	152
7.1.10	Conformability rules for elemental operations	153
7.1.11	Specification expression	154
7.1.12	Constant expression	155
7.2	Assignment	157
7.2.1	Assignment statement	157
7.2.2	Pointer assignment	161
7.2.3	Masked array assignment – WHERE	165
7.2.4	FORALL	167
8	Execution control	171
8.1	Executable constructs containing blocks	171
8.1.1	Blocks	171
8.1.2	Rules governing blocks	171
8.1.3	ASSOCIATE construct	172
8.1.4	BLOCK construct	173

8.1.5	CRITICAL construct	175
8.1.6	DO construct	176
8.1.7	IF construct and statement	183
8.1.8	SELECT CASE construct	185
8.1.9	SELECT RANK construct	187
8.1.10	SELECT TYPE construct	189
8.1.11	EXIT statement	192
8.2	Branching	192
8.2.1	Branch concepts	192
8.2.2	GO TO statement	193
8.2.3	Computed GO TO statement	193
8.3	CONTINUE statement	193
8.4	STOP and ERROR STOP statements	193
8.5	Image execution control	194
8.5.1	Image control statements	194
8.5.2	Segments	194
8.5.3	SYNC ALL statement	195
8.5.4	SYNC IMAGES statement	196
8.5.5	SYNC MEMORY statement	198
8.5.6	EVENT POST statement	199
8.5.7	EVENT WAIT statement	200
8.5.8	LOCK and UNLOCK statements	200
8.5.9	STAT= and ERRMSG= specifiers in image control statements	202
9	Input/output statements	203
9.1	Input/output concepts	203
9.2	Records	203
9.2.1	Definition of a record	203
9.2.2	Formatted record	203
9.2.3	Unformatted record	203
9.2.4	Endfile record	204
9.3	External files	204
9.3.1	External file concepts	204
9.3.2	File existence	204
9.3.3	File access	205
9.3.4	File position	207
9.3.5	File storage units	208
9.4	Internal files	209
9.5	File connection	209
9.5.1	Referring to a file	209
9.5.2	Connection modes	210
9.5.3	Unit existence	211
9.5.4	Connection of a file to a unit	211
9.5.5	Preconnection	212
9.5.6	OPEN statement	212
9.5.7	CLOSE statement	216
9.6	Data transfer statements	217
9.6.1	Form of input and output statements	217
9.6.2	Control information list	218
9.6.3	Data transfer input/output list	222
9.6.4	Execution of a data transfer input/output statement	225
9.6.5	Termination of data transfer statements	235
9.7	Waiting on pending data transfer	236
9.7.1	Wait operation	236
9.7.2	WAIT statement	236
9.8	File positioning statements	237

9.8.1	Syntax	237
9.8.2	BACKSPACE statement	237
9.8.3	ENDFILE statement	238
9.8.4	REWIND statement	238
9.9	FLUSH statement	239
9.10	File inquiry statement	239
9.10.1	Forms of the INQUIRE statement	239
9.10.2	Inquiry specifiers	240
9.10.3	Inquire by output list	246
9.11	Error, end-of-record, and end-of-file conditions	246
9.11.1	Occurrence of input/output conditions	246
9.11.2	Error conditions and the ERR= specifier	246
9.11.3	End-of-file condition and the END= specifier	247
9.11.4	End-of-record condition and the EOR= specifier	247
9.11.5	IOSTAT= specifier	247
9.11.6	IOMSG= specifier	248
9.12	Restrictions on input/output statements	248
10	Input/output editing	251
10.1	Format specifications	251
10.2	Explicit format specification methods	251
10.2.1	FORMAT statement	251
10.2.2	Character format specification	251
10.3	Form of a format item list	252
10.3.1	Syntax	252
10.3.2	Edit descriptors	252
10.3.3	Fields	254
10.4	Interaction between input/output list and format	254
10.5	Positioning by format control	256
10.6	Decimal symbol	256
10.7	Data edit descriptors	256
10.7.1	Purpose of data edit descriptors	256
10.7.2	Numeric editing	257
10.7.3	Logical editing	264
10.7.4	Character editing	264
10.7.5	Generalized editing	265
10.7.6	User-defined derived-type editing	266
10.8	Control edit descriptors	266
10.8.1	Position edit descriptors	266
10.8.2	Slash editing	267
10.8.3	Colon editing	267
10.8.4	SS, SP, and S editing	268
10.8.5	P editing	268
10.8.6	BN and BZ editing	268
10.8.7	RU, RD, RZ, RN, RC, and RP editing	268
10.8.8	DC and DP editing	269
10.9	Character string edit descriptors	269
10.10	List-directed formatting	269
10.10.1	Purpose of list-directed formatting	269
10.10.2	Values and value separators	269
10.10.3	List-directed input	270
10.10.4	List-directed output	272
10.11	Namelist formatting	273
10.11.1	Purpose of namelist formatting	273
10.11.2	Name-value subsequences	273
10.11.3	Namelist input	274

10.11.4	Namelist output	277
11	Program units	279
11.1	Main program	279
11.2	Modules	279
11.2.1	Module syntax and semantics	279
11.2.2	The USE statement and use association	280
11.2.3	Submodules	283
11.3	Block data program units	283
12	Procedures	285
12.1	Concepts	285
12.2	Procedure classifications	285
12.2.1	Procedure classification by reference	285
12.2.2	Procedure classification by means of definition	285
12.3	Characteristics	286
12.3.1	Characteristics of procedures	286
12.3.2	Characteristics of dummy arguments	286
12.3.3	Characteristics of function results	286
12.4	Procedure interface	287
12.4.1	Interface and abstract interface	287
12.4.2	Implicit and explicit interfaces	287
12.4.3	Specification of the procedure interface	288
12.5	Procedure reference	299
12.5.1	Syntax of a procedure reference	299
12.5.2	Actual arguments, dummy arguments, and argument association	301
12.5.3	Function reference	312
12.5.4	Subroutine reference	312
12.5.5	Resolving named procedure references	312
12.5.6	Resolving type-bound procedure references	315
12.6	Procedure definition	315
12.6.1	Intrinsic procedure definition	315
12.6.2	Procedures defined by subprograms	315
12.6.3	Definition and invocation of procedures by means other than Fortran	321
12.6.4	Statement function	321
12.7	Pure procedures	322
12.8	Elemental procedures	324
12.8.1	Elemental procedure declaration and interface	324
12.8.2	Elemental function actual arguments and results	324
12.8.3	Elemental subroutine actual arguments	324
13	Intrinsic procedures and modules	325
13.1	Classes of intrinsic procedures	325
13.2	Arguments to intrinsic procedures	325
13.2.1	General rules	325
13.2.2	The shape of array arguments	326
13.2.3	Mask arguments	326
13.2.4	DIM arguments and reduction functions	326
13.3	Bit model	326
13.3.1	General	326
13.3.2	Bit sequence comparisons	327
13.3.3	Bit sequences as arguments to INT and REAL	327
13.4	Numeric models	327
13.5	Atomic subroutines	328
13.6	Standard generic intrinsic procedures	329
13.7	Specific names for standard intrinsic functions	334

13.8	Specifications of the standard intrinsic procedures	336
13.8.1	General	336
13.9	Standard intrinsic modules	416
13.9.1	General	416
13.9.2	The ISO_FORTRAN_ENV intrinsic module	416
14	Exceptions and IEEE arithmetic	423
14.1	General	423
14.2	Derived types and constants defined in the modules	424
14.3	The exceptions	424
14.4	The rounding modes	426
14.5	Underflow mode	427
14.6	Halting	427
14.7	The floating-point modes and status	427
14.8	Exceptional values	428
14.9	IEEE arithmetic	428
14.10	Summary of the procedures	429
14.11	Specifications of the procedures	431
14.11.1	General	431
14.12	Examples	453
15	Interoperability with C	457
15.1	General	457
15.2	The ISO_C_BINDING intrinsic module	457
15.2.1	Summary of contents	457
15.2.2	Named constants and derived types in the module	457
15.2.3	Procedures in the module	458
15.3	Interoperability between Fortran and C entities	463
15.3.1	General	463
15.3.2	Interoperability of intrinsic types	463
15.3.3	Interoperability with C pointer types	464
15.3.4	Interoperability of derived types and C struct types	465
15.3.5	Interoperability of scalar variables	466
15.3.6	Interoperability of array variables	466
15.3.7	Interoperability of procedures and procedure interfaces	467
15.4	C descriptors	469
15.5	The source file ISO_Fortran_binding.h	470
15.5.1	Summary of contents	470
15.5.2	The CFI_dim_t structure type	470
15.5.3	The CFI_cdesc_t structure type	470
15.5.4	Macros and typedefs in ISO_Fortran_binding.h	471
15.5.5	Functions declared in ISO_Fortran_binding.h	474
15.6	Restrictions on C descriptors	481
15.7	Restrictions on formal parameters	481
15.8	Restrictions on lifetimes	482
15.9	Interoperation with C global variables	482
15.9.1	General	482
15.9.2	Binding labels for common blocks and variables	483
15.10	Interoperation with C functions	484
15.10.1	Definition and reference of interoperable procedures	484
15.10.2	Binding labels for procedures	484
15.10.3	Exceptions and IEEE arithmetic procedures	485
15.10.4	Asynchronous communication	485
16	Scope, association, and definition	487
16.1	Scopes, identifiers, and entities	487

16.2	Global identifiers	487
16.3	Local identifiers	488
16.3.1	Classes of local identifiers	488
16.3.2	Local identifiers that are the same as common block names	489
16.3.3	Function results	489
16.3.4	Components, type parameters, and bindings	489
16.3.5	Argument keywords	489
16.4	Statement and construct entities	490
16.5	Association	491
16.5.1	Name association	491
16.5.2	Pointer association	495
16.5.3	Storage association	498
16.5.4	Inheritance association	500
16.5.5	Establishing associations	500
16.6	Definition and undefinition of variables	501
16.6.1	Definition of objects and subobjects	501
16.6.2	Variables that are always defined	501
16.6.3	Variables that are initially defined	501
16.6.4	Variables that are initially undefined	502
16.6.5	Events that cause variables to become defined	502
16.6.6	Events that cause variables to become undefined	503
16.6.7	Variable definition context	505
16.6.8	Pointer association context	506
Annex A	(informative) Processor Dependencies	507
A.1	Unspecified Items	507
A.2	Processor Dependencies	507
Annex B	(informative) Deleted and obsolescent features	513
B.1	Deleted features from Fortran 90	513
B.2	Deleted features from Fortran 2008	514
B.3	Obsolescent features	514
B.3.1	General	514
B.3.2	Alternate return	514
B.3.3	Computed GO TO statement	515
B.3.4	Statement functions	515
B.3.5	DATA statements among executables	515
B.3.6	Assumed character length functions	515
B.3.7	Fixed form source	515
B.3.8	CHARACTER* form of CHARACTER declaration	516
B.3.9	ENTRY statements	516
B.3.10	Label DO statement	516
B.3.11	COMMON and EQUIVALENCE statements and the block data program unit	516
B.3.12	Specific names for intrinsic functions	516
B.3.13	FORALL construct and statement	516
Annex C	(informative) Extended notes	517
C.1	Clause 4 notes	517
C.1.1	Selection of the approximation methods (4.4.3.2)	517
C.1.2	Type extension and component accessibility (4.5.2.2, 4.5.4)	517
C.1.3	Generic type-bound procedures (4.5.5)	518
C.1.4	Abstract types (4.5.7.1)	519
C.1.5	Structure constructors and generic names (4.5.10)	520
C.1.6	Final subroutines (4.5.6, 4.5.6.2, 4.5.6.3, 4.5.6.4)	522
C.2	Clause 5 notes: The VOLATILE attribute (5.5.19)	524
C.3	Clause 6 notes	524

C.3.1	Structure components (6.4.2)	524
C.3.2	Allocation with dynamic type (6.7.1)	526
C.4	Clause 7 notes	526
C.4.1	Evaluation of function references (7.1.7)	526
C.4.2	Pointers in expressions (7.1.9.2)	526
C.4.3	Pointers in variable definition contexts (7.2.1.3, 16.6.7)	527
C.5	Clause 8 notes	527
C.5.1	The SELECT CASE construct (8.1.8)	527
C.5.2	Loop control (8.1.6)	527
C.5.3	Examples of DO constructs (8.1.6)	527
C.5.4	Examples of invalid DO constructs (8.1.6)	528
C.5.5	Simple example using events	529
C.6	Clause 9 notes	530
C.6.1	External files (9.3)	530
C.6.2	Nonadvancing input/output (9.3.4.2)	531
C.6.3	OPEN statement (9.5.6)	532
C.6.4	Connection properties (9.5.4)	534
C.6.5	Asynchronous input/output (9.6.2.5)	534
C.7	Clause 10 notes	536
C.7.1	Number of records (10.4, 10.5, 10.8.2)	536
C.7.2	List-directed input (10.10.3)	536
C.8	Clause 11 notes	537
C.8.1	Main program and block data program unit (11.1, 11.3)	537
C.8.2	Dependent compilation (11.2)	537
C.8.3	Examples of the use of modules (11.2.1)	539
C.8.4	Modules with submodules (11.2.3)	545
C.9	Clause 12 notes	550
C.9.1	Portability problems with external procedures (12.4.3.6)	550
C.9.2	Procedures defined by means other than Fortran (12.6.3)	550
C.9.3	Abstract interfaces and procedure pointer components (12.4, 4.5)	550
C.9.4	Pointers and targets as arguments (12.5.2.4, 12.5.2.6, 12.5.2.7)	552
C.9.5	Polymorphic Argument Association (12.5.2.9)	554
C.9.6	Rules ensuring unambiguous generics (12.4.3.5.5)	555
C.10	Clause 13 notes	559
C.10.1	Atomic memory consistency	559
C.10.2	EVENT_QUERY example	561
C.11	Clause 15 notes	562
C.11.1	Runtime environments (15.1)	562
C.11.2	Example of Fortran calling C (15.3)	563
C.11.3	Example of C calling Fortran (15.3)	564
C.11.4	Example of calling C functions with noninteroperable data (15.10)	565
C.11.5	Example of opaque communication between C and Fortran (15.3)	566
C.11.6	Using assumed type to interoperate with C	567
C.11.7	Using assumed-type variables in Fortran	570
C.11.8	Simplifying interfaces for arbitrary rank procedures	571
C.11.9	Processing assumed-shape arrays in C	571
C.11.10	Creating a contiguous copy of an array	573
C.11.11	Changing the attributes of an array	574
C.11.12	Creating an array section in C using CFI_section	575
C.11.13	Use of CFI_setpointer	577
C.11.14	Mapping of MPI interfaces to Fortran	578
C.12	Clause 16 notes : Examples of host association (16.5.1.4)	580
Index	583

List of Tables

1.3	Previous editions of the Fortran International Standard	25
2.1	Requirements on statement ordering	33
2.2	Statements allowed in scoping units	34
3.1	Special characters	44
3.2	Adjacent keywords where separating blanks are optional	47
6.1	Subscript order value	126
7.1	Categories of operations and relative precedence	141
7.2	Type of operands and results for intrinsic operators	144
7.3	Interpretation of the numeric intrinsic operators	145
7.4	Interpretation of the character intrinsic operator //	147
7.5	Interpretation of the logical intrinsic operators	148
7.6	The values of operations involving logical intrinsic operators	148
7.7	Interpretation of the relational intrinsic operators	149
7.8	Type conformance for the intrinsic assignment statement	157
7.9	Numeric conversion and the assignment statement	159
10.1	E and D exponent forms	260
10.2	EN exponent forms	260
10.3	ES exponent forms	261
13.1	Standard generic intrinsic procedure summary	329
13.2	Unrestricted specific intrinsic functions	335
13.3	Restricted specific intrinsic functions	335
13.4	Default BOUNDARY values for EOSHIFT	359
13.5	Characteristics of the result of NULL ()	392
14.1	IEEE_ARITHMETIC module procedure summary	429
14.2	IEEE_EXCEPTIONS module procedure summary	430

15.1 Names of C characters with special semantics	458
15.2 Interoperability between Fortran and C types	463
15.3 ISO_Fortran_binding.h macros for attribute codes	472
15.4 ISO_Fortran_binding.h macros for type codes	472
15.5 ISO_Fortran_binding.h macros for error codes	473

Foreword

- 1 ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and nongovernmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2 International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.
- 3 The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 4 Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.
- 5 ISO/IEC 1539-1 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 22, *Programming languages, their environments and system software interfaces*.
- 6 This fourth edition cancels and replaces the third edition (ISO/IEC 1539-1:2010), which has been technically revised. It also incorporates the Technical Corrigenda ISO/IEC 1539-1:2010/Cor. 1:2012 and ISO/IEC 1539-1:2010/Cor. 2:2013, and the Technical Specification ISO/IEC TS 29113:2012.
- 7 ISO/IEC 1539 consists of the following parts, under the general title *Information technology — Programming languages — Fortran*:
 - 8 — *Part 1: Base language*
 - 9 — *Part 2: Varying length character strings*

Introduction

- 1 This part of ISO/IEC 1539 comprises the specification of the base Fortran language, informally known as Fortran 2015. With the limitations noted in 1.6.4, the syntax and semantics of Fortran 2008 are contained entirely within Fortran 2015. Therefore, any standard-conforming Fortran 2008 program not affected by such limitations is a standard-conforming Fortran 2015 program. New features of Fortran 2015 can be compatibly incorporated into such Fortran 2008 programs, with any exceptions indicated in the text of this part of ISO/IEC 1539.
- 2 Fortran 2015 contains several extensions to Fortran 2008; these are listed below.
 - Data declaration:

Constant properties of an object declared in its *entity-decl* can be used in its *initialization*.
 - Data usage and computation:

Labeled **DO loops** have been redundant since Fortran 90 and are now specified to be **obsolescent**. The **arithmetic IF statement** has been deleted. The **EQUIVALENCE** and **COMMON** statements and the **block data program unit** have been redundant since Fortran 90 and are now specified to be **obsolescent**. The **nonblock DO construct** has been deleted. **FORALL** is now specified to be **obsolescent**. The type and kind of an implied DO variable in an **array constructor** or **DATA statement** can be specified within the constructor or statement. The locality of a variable used in a **DO CONCURRENT construct** can be explicitly specified. The **SELECT RANK construct** provides structured access to the elements of an **assumed-rank array**.
 - Input/output:

The **SIZE= specifier** can be used with advancing input. It is no longer prohibited to open a file on more than one unit. The value assigned by the **RECL= specifier** in an **INQUIRE statement** has been standardized. The **G0.d edit descriptor** can be used for list items of type **Integer**, **Logical**, and **Character**. The **D**, **E**, **EN**, and **ES edit descriptors** can have a field width of zero, analogous to the **F** edit descriptor. The exponent width *e* in a **data edit descriptor** can be zero, analogous to a field width of zero. Floating-point formatted input accepts hexadecimal-significand numbers that conform to ISO/IEC/IEEE 60559:2011. The **EX edit descriptor** provides hexadecimal-significand formatted output conforming to ISO/IEC/IEEE 60559:2011. An error condition occurs if unacceptable characters are presented for logical or numeric editing during execution of a formatted input statement.
 - Execution control:

The stop code in a **STOP** or **ERROR STOP** statement can be nonconstant. Output of the stop code and exception summary from the **STOP** and **ERROR STOP** statements can be controlled.
 - Intrinsic procedures and modules:

In references to the intrinsic functions **ALL**, **ANY**, **FINDLOC**, **IALL**, **IANY**, **IPARITY**, **MAXLOC**, **MAXVAL**, **MINLOC**, **MINVAL**, **NORM2**, **PARITY**, **PRODUCT**, **SUM**, and **THIS_IMAGE**, the **actual argument** for **DIM** can be a present optional **dummy argument**. In a reference of the intrinsic function **CMPLX** with an actual argument of type complex, no keyword is needed for a **KIND** argument. The new intrinsic function **COSHAPE** returns the coshape of a **coarray**. The new intrinsic function **OUT_OF_RANGE** tests whether a numeric value can be safely converted to a different type or kind. The new intrinsic subroutine **RANDOM_INIT** establishes the initial state of the pseudorandom number generator used by **RANDOM_NUMBER**. The new intrinsic function **REDUCE** performs user-specified array reductions. A processor is required to report use of a **nonstandard intrinsic** procedure, use of a **nonstandard intrinsic** module, and use of a non-standard procedure from a **standard intrinsic** module. Integer and logical arguments to intrinsic procedures and intrinsic module procedures that were previously required to be of default kind no longer have that requirement, except for **RANDOM_SEED**. **Specific names for intrinsic functions** are now deemed **obsolescent**. All standard procedures in the intrinsic module **ISO_C_BINDING**, other than **C_F_POINTER**, are now **pure**. The arguments to the intrinsic function **SIGN** can be of different kind. Nonpolymorphic pointer arguments to the intrinsic functions **EXTENDS_TYPE_OF** and **SAME_TYPE_AS** need not have defined pointer association status. The effects of invoking the intrinsic procedures **COMMAND_ARGUMENT_COUNT**, **GET_COMMAND**, and **GET_COMMAND_ARGUMENT**, on **images** other than **image** one, are no longer processor dependent. Access to error messages from the intrinsic subroutines **GET_COMMAND**, **GET_COMMAND_ARGUMENT**, and **GET_ENVIRONMENT_VARIABLE** is provided by an optional **ERRMSG** argument.
 - Program units and procedures:

The **IMPORT statement** can appear in a contained subprogram or **BLOCK construct**, and can restrict access via host association; diagnosis of violation of the **IMPORT restrictions** is required. The **GENERIC statement** can be used to declare generic interfaces. The **ERROR STOP statement** can appear in a **pure subprogram**. The number of procedure arguments is used in **generic resolution**. In a module, the **default accessibility** of entities accessed from another module can be controlled separately from that of entities declared in the using module. An **IMPLICIT NONE statement** can require explicit declaration of the **EXTERNAL attribute** throughout a **scoping unit** and its contained **scoping units**. A defined operation need not specify **INTENT (IN)** for a **dummy argument** with the **VALUE attribute**. A defined assignment need not specify **INTENT (IN)** for the second **dummy argument** if it has the **VALUE attribute**. Procedures, including elemental procedures, can be invoked recursively by default; the **RECURSIVE** keyword is advisory only. The **NON_RECURSIVE** keyword specifies that a procedure is not recursive. A **dummy argument** of a **pure function** is permitted in a variable definition context, if it has the **VALUE attribute**.

- Features previously described by ISO/IEC TS 29113:2012:

A **dummy data object** can **assume its rank** from its **effective argument**. A **dummy data object** can **assume the type** from its **effective argument**, without having the ability to perform type selection. An **interoperable** procedure can have **dummy arguments** that are **assumed-type** and/or **assumed-rank**. An **interoperable** procedure can have **dummy data objects** that are **allocatable**, **assumed-shape**, **optional**, or **pointers**. The **character length** of a **dummy data object** of an **interoperable** procedure can be assumed. The argument to **C_LOC** can be a noninteroperable array. The FPTR argument to **C_F_POINTER** can be a noninteroperable array pointer. The argument to **C_FUNLOC** can be a noninteroperable procedure. The FPTR argument to **C_F_PROCPOINTER** can be a noninteroperable procedure pointer.

- Changes to the intrinsic modules **IEEE_ARITHMETIC**, **IEEE_EXCEPTIONS**, and **IEEE_FEATURES** for conformance with ISO/IEC/IEEE 60559:2011:

There is a new, optional, rounding mode **IEEE_AWAY**. The new type **IEEE_MODES_TYPE** encapsulates all floating-point modes. Features associated with subnormal numbers can be accessed with functions and types named ...**SUBNORMAL**... (the old ...**DENORMAL**... names remain). The standard intrinsic relational operations on IEEE numbers provide the compareSignalingrelation operations. The new function **IEEE_FMA** performs fused multiply-add operations. The function **IEEE_INT** performs rounded conversions to integer type. The new functions **IEEE_MAX_NUM**, **IEEE_MAX_NUM_MAG**, **IEEE_MIN_NUM**, and **IEEE_MIN_NUM_MAG** calculate maximum and minimum numeric values. The new functions **IEEE_NEXT_DOWN** and **IEEE_NEXT_UP** return the adjacent machine numbers. The new functions **IEEE_QUIET_EQ**, **IEEE_QUIET_GE**, **IEEE_QUIET_GT**, **IEEE_QUIET_LE**, **IEEE_QUIET_LT**, and **IEEE_QUIET_NE** perform quiet comparisons. The decimal rounding mode can be inquired and set independently of the binary rounding mode, using the **RADIX** argument to **IEEE_GET_ROUNDING_MODE** and **IEEE_SET_ROUNDING_MODE**. The new function **IEEE_REAL** performs rounded conversions to real type. The function **IEEE_RINT** now has a **ROUND** argument to perform specific rounding. The new function **IEEE_SIGNBIT** tests the sign bit of an IEEE number.

- Features previously described by ISO/IEC TS 18508:2015:

The intrinsic subroutines **ATOMIC_DEFINE** and **ATOMIC_REF** have an optional **STAT** argument. The new intrinsic subroutines **ATOMIC_ADD**, **ATOMIC_AND**, **ATOMIC_CAS**, **ATOMIC_FETCH_ADD**, **ATOMIC_FETCH_AND**, **ATOMIC_FETCH_OR**, **ATOMIC_FETCH_XOR**, **ATOMIC_OR**, and **ATOMIC_XOR** perform atomic operations. The **EVENT POST** and **EVENT WAIT** statements, the intrinsic subroutine **EVENT_QUERY**, and the type **EVENT_TYPE** provide an event facility for one-sided segment ordering.

- 3 This part of ISO/IEC 1539 is organized in 16 clauses, dealing with 8 conceptual areas. These 8 areas, and the clauses in which they are treated, are:

High/low level concepts	Clauses 1, 2, 3
Data concepts	Clauses 4, 5, 6
Computations	Clauses 7, 13, 14
Execution control	Clause 8
Input/output	Clauses 9, 10
Program units	Clauses 11, 12
Interoperability with C	Clause 15
Scoping and association rules	Clause 16

4 It also contains the following nonnormative material:

Processor dependencies	Annex A
Deleted and obsolescent features	Annex B
Extended notes	Annex C
Index	Index

Information technology — Programming languages — Fortran —

Part 1: Base language

1 Overview

1.1 Scope

1 This part of ISO/IEC 1539 specifies the form and establishes the interpretation of programs expressed in the base
2 Fortran language. The purpose of this part of ISO/IEC 1539 is to promote portability, reliability, maintainability,
3 and efficient execution of Fortran programs for use on a variety of computing systems.

4 This part of ISO/IEC 1539 specifies

- the forms that a program written in the Fortran language may take,
- the rules for interpreting the meaning of a program and its data,
- the form of the input data to be processed by such a program, and
- the form of the output data resulting from the use of such a program.

5 Except where stated otherwise, requirements and prohibitions specified by this part of ISO/IEC 1539 apply to
6 programs rather than processors.

7 This part of ISO/IEC 1539 does not specify

- the mechanism by which programs are transformed for use on computing systems,
- the operations required for setup and control of the use of programs on computing systems,
- the method of transcription of programs or their input or output data to or from a storage medium,
- the program and processor behavior when this part of ISO/IEC 1539 fails to establish an interpretation
except for the processor detection and reporting requirements in items (2) to (10) of 1.5,
- the maximum number of [images](#), or the size or complexity of a program and its data that will exceed the
capacity of any particular computing system or the capability of a particular processor,
- the mechanism for determining the number of [images](#) of a program,
- the physical properties of an [image](#) or the relationship between [images](#) and the computational elements of
a computing system,
- the physical properties of the representation of quantities and the method of rounding, approximating, or
computing numeric values on a particular processor, except by reference to ISO/IEC/IEEE 60559:2011
under conditions specified in Clause 14,
- the physical properties of input/output records, files, and units, or
- the physical properties and implementation of storage.

1.2 Normative references

1 The following referenced standards are indispensable for the application of this document. For dated references,
2 only the edition cited applies. For undated references, the latest edition of the referenced document (including
3 any amendments) applies.

1 ISO/IEC 646:1991 (International Reference Version), *Information technology—ISO 7-bit coded character set for*
2 *information interchange*

3 ISO/IEC 9899:2011, *Programming languages—C*

4 ISO/IEC 10646, *Information technology—Universal Multiple-Octet Coded Character Set (UCS)*

5 ISO/IEC/IEEE 60559:2011, *Binary floating-point arithmetic for microprocessor systems*

6 **1.3 Terms and definitions**

7 1 For the purposes of this document, the following terms and definitions apply.

8 **1.3.1**

9 **abstract interface**

10 set of procedure characteristics with dummy argument names ([12.4.1](#))

11 **1.3.2**

12 **actual argument**

13 entity ([R1225](#)) that appears in a [procedure reference](#)

14 **1.3.3**

15 **allocatable**

16 having the [ALLOCATABLE](#) attribute ([5.5.3](#))

17 **1.3.4**

18 **array**

19 set of scalar data, all of the same type and [type parameters](#), whose individual elements are arranged in a
20 rectangular pattern

21 **1.3.4.1**

22 **array element**

23 scalar individual element of an array

24 **1.3.4.2**

25 **array pointer**

26 array with the [POINTER](#) attribute ([5.5.14](#))

27 **1.3.4.3**

28 **array section**

29 array [subobject](#) designated by [array-section](#), and which is itself an array ([6.5.3.3](#))

30 **1.3.4.4**

31 **assumed-shape array**

32 nonallocatable nonpointer [dummy argument](#) array that takes its shape from its [effective argument](#) ([5.5.8.3](#))

33 **1.3.4.5**

34 **assumed-size array**

35 [dummy argument](#) array whose size is assumed from that of its [effective argument](#) ([5.5.8.5](#))

36 **1.3.4.6**

37 **deferred-shape array**

38 [allocatable](#) array or array pointer, declared with a [deferred-shape-spec-list](#) ([5.5.8.4](#))

39 **1.3.4.7**

40 **explicit-shape array**

41 array declared with an [explicit-shape-spec-list](#), which specifies explicit values for the [bounds](#) in each dimension of
42 the array ([5.5.8.2](#))

- 1 **1.3.5**
2 **ASCII character**
3 character whose representation method corresponds to ISO/IEC 646:1991 (International Reference Version)
- 4 **1.3.6**
5 **associate name**
6 name of [construct entity](#) associated with a selector of an ASSOCIATE or SELECT TYPE construct ([8.1.3](#))
- 7 **1.3.7**
8 **associating entity**
9 [\(in a dynamically-established association\)](#) the entity that did not exist prior to the establishment of the association
10 ([16.5.5](#))
- 11 **1.3.8**
12 **association**
13 [inheritance association](#) ([16.5.4](#)), [name association](#) ([16.5.1](#)), [pointer association](#) ([16.5.2](#)), or [storage association](#)
14 ([16.5.3](#)).
- 15 **1.3.8.1**
16 **argument association**
17 association between an [effective argument](#) and a [dummy argument](#) ([12.5.2](#))
- 18 **1.3.8.2**
19 **construct association**
20 association between a selector and an [associate name](#) in an ASSOCIATE or SELECT TYPE construct ([8.1.3](#),
21 [8.1.10](#), [16.5.1.6](#))
- 22 **1.3.8.3**
23 **host association**
24 name association, other than argument association, between entities in a submodule or contained [scoping unit](#)
25 and entities in its host ([16.5.1.4](#))
- 26 **1.3.8.4**
27 **inheritance association**
28 association between the [inherited](#) components of an [extended type](#) and the components of its [parent component](#)
- 29 **1.3.8.5**
30 **linkage association**
31 association between a variable or common block with the [BIND attribute](#) and a C global variable ([15.9](#), [16.5.1.5](#))
- 32 **1.3.8.6**
33 **name association**
34 [argument association](#), [construct association](#), [host association](#), [linkage association](#), or [use association](#) ([16.5.1](#))
- 35 **1.3.8.7**
36 **pointer association**
37 association between a [pointer](#) and an entity with the [TARGET attribute](#) ([16.5.2](#))
- 38 **1.3.8.8**
39 **storage association**
40 association between storage sequences ([16.5.3](#))
- 41 **1.3.8.9**
42 **use association**
43 association between entities in a module and entities in a [scoping unit](#) or construct that references that module,
44 as specified by a [USE statement](#) ([11.2.2](#))

- 1 **1.3.9**
2 **assumed-rank dummy data object**
3 [dummy data object](#) that assumes the rank, shape, and size of its [effective argument](#)
- 4 **1.3.10**
5 **assumed-type**
6 declared with a `TYPE(*)` type specifier ([4.3.2](#))
- 7 **1.3.11**
8 **attribute**
9 property of an entity that determines its uses ([5.1](#))
- 10 **1.3.12**
11 **automatic data object**
12 **automatic object**
13 nondummy [data object](#) with a [type parameter](#) or array [bound](#) that depends on the value of a [specification-expr](#)
14 that is not a [constant expression](#)
- 15 **1.3.13**
16 **base object**
17 `<data-ref>` object designated by the leftmost [part-name](#) ([6.4.2](#))
- 18 **1.3.14**
19 **binding**
20 [type-bound procedure](#) or [final subroutine](#) ([4.5.5](#))
- 21 **1.3.15**
22 **binding name**
23 name given to a specific or generic [type-bound procedure](#) in the type definition ([4.5.5](#))
- 24 **1.3.16**
25 **binding label**
26 default character value specifying the name by which a global entity with the [BIND attribute](#) is known to the
27 [companion processor](#) ([15.10.2](#), [15.9.2](#))
- 28 **1.3.17**
29 **block**
30 sequence of executable constructs formed by the syntactic class [block](#) and which is treated as a unit by the
31 executable constructs described in [8.1](#)
- 32 **1.3.18**
33 **bound**
34 **array bound**
35 limit of a dimension of an [array](#)
- 36 **1.3.19**
37 **branch target statement**
38 [action-stmt](#), [associate-stmt](#), [end-associate-stmt](#), [if-then-stmt](#), [end-if-stmt](#), [select-case-stmt](#), [end-select-stmt](#), [select-](#)
39 [rank-stmt](#), [end-select-rank-stmt](#), [select-type-stmt](#), [end-select-type-stmt](#), [do-stmt](#), [end-do-stmt](#), [block-stmt](#), [end-](#)
40 [block-stmt](#), [critical-stmt](#), [end-critical-stmt](#), [forall-construct-stmt](#), or [where-construct-stmt](#) whose statement label ap-
41 pears as a [label](#) in a [GO TO](#) statement, computed [GO TO](#) statement, [alt-return-spec](#), [END= specifier](#), [EOR= specifier](#),
42 or [ERR= specifier](#) ([8.2.1](#))

1 **1.3.20**2 **C address**

3 value identifying the location of a [data object](#) or procedure either defined by the [companion processor](#) or which
4 might be accessible to the [companion processor](#)

NOTE 1.1

This is the concept that ISO/IEC 9899:2011 calls the address.

5 **1.3.21**6 **C descriptor**

7 C structure of type [CFI_cdesc_t](#) defined in the source file [ISO_Fortran_binding.h](#) ([15.4](#), [15.5](#))

8 **1.3.22**9 **character context**

10 within a character literal constant ([4.4.4](#)) or within a character string edit descriptor ([10.3.2](#))

11 **1.3.23**12 **characteristics**

13 [⟨dummy argument⟩](#) being a [dummy data object](#), [dummy procedure](#), or an asterisk (alternate return indicator)

14 **1.3.24**15 **characteristics**

16 [⟨dummy data object⟩](#) properties listed in [12.3.2.2](#)

17 **1.3.25**18 **characteristics**

19 [⟨dummy procedure or dummy procedure pointer⟩](#) properties listed in [12.3.2.3](#)

20 **1.3.26**21 **characteristics**

22 [⟨function result⟩](#) properties listed in [12.3.3](#)

23 **1.3.27**24 **characteristics**

25 [⟨procedure⟩](#) properties listed in [12.3.1](#)

26 **1.3.28**27 **coarray**

28 [data entity](#) that has nonzero corank ([2.4.7](#))

29 **1.3.29**30 **cobound**

31 bound (limit) of a [codimension](#)

32 **1.3.30**33 **codimension**

34 dimension of the pattern formed by a set of corresponding [coarrays](#)

35 **1.3.31**36 **coindexed object**

37 [data object](#) whose [designator](#) includes an [image-selector](#) ([R624](#), [6.6](#))

38 **1.3.32**39 **collating sequence**

40 one-to-one mapping from a character set into the nonnegative integers ([4.4.4.4](#))

- 1 **1.3.33**
2 **common block**
3 block of physical storage specified by a [COMMON statement](#) (5.9.2)
- 4 **1.3.33.1**
5 **blank common**
6 unnamed common block
- 7 **1.3.34**
8 **companion processor**
9 processor-dependent mechanism by which global data and procedures may be referenced or defined (2.5.7)
- 10 **1.3.35**
11 **component**
12 part of a derived type, or of an object of derived type, defined by a *component-def-stmt* (4.5.4)
- 13 **1.3.35.1**
14 **direct component**
15 one of the components, or one of the direct components of a nonpointer nonallocatable component (4.5.1)
- 16 **1.3.35.2**
17 **parent component**
18 component of an [extended type](#) whose type is that of the [parent type](#) and whose components are [inheritance](#)
19 [associated](#) with the [inherited](#) components of the [parent type](#) (4.5.7.2)
- 20 **1.3.35.3**
21 **potential subobject component**
22 nonpointer component, or potential subobject component of a nonpointer component (4.5.1)
- 23 **1.3.35.4**
24 **subcomponent**
25 *<structure>* [direct component](#) that is a [subobject](#) of the [structure](#) (6.4.2)
- 26 **1.3.35.5**
27 **ultimate component**
28 component that is of [intrinsic type](#), a pointer, or allocatable; or an ultimate component of a nonpointer nonal-
29 locatable component of derived type
- 30 **1.3.36**
31 **component order**
32 ordering of the nonparent components of a derived type that is used for [intrinsic](#) formatted input/output and
33 [structure constructors](#) (where component keywords are not used) (4.5.4.7)
- 34 **1.3.37**
35 **conformable**
36 *<of two data entities>* having the same shape, or one being an array and the other being scalar
- 37 **1.3.38**
38 **connected**
39 relationship between a [unit](#) and a file: each is connected if and only if the [unit](#) refers to the file (9.5.4)
- 40 **1.3.39**
41 **constant**
42 [data object](#) that has a value and which cannot be defined, redefined, or become undefined during execution of a
43 program (3.2.3, 6.3)

1 **1.3.39.1**2 **literal constant**

3 constant that does not have a name (R305, 4.4)

4 **1.3.39.2**5 **named constant**6 named [data object](#) with the [PARAMETER attribute](#) (5.5.13)7 **1.3.40**8 **construct entity**

9 entity whose identifier has the scope of a construct (16.1, 16.4)

10 **1.3.41**11 **constant expression**

12 expression satisfying the requirements specified in 7.1.12, thus ensuring that its value is constant

13 **1.3.42**14 **contiguous**15 \langle array \rangle having array elements in order that are not separated by other data objects, as specified in 5.5.716 **1.3.43**17 **contiguous**18 \langle multi-part data object \rangle that the parts in order are not separated by other data objects19 **1.3.44**20 **corank**21 number of [codimensions](#) of a [coarray](#) (zero for objects that are not coarrays)22 **1.3.45**23 **cosubscript**24 (R625) scalar integer expression in an *image-selector* (R624)25 **1.3.46**26 **data entity**27 [data object](#), result of the evaluation of an expression, or the result of the execution of a function reference28 **1.3.47**29 **data object**30 **object**31 constant (4.1.4), [variable](#) (6), or [subobject](#) of a constant (2.4.3.2.3)32 **1.3.48**33 **decimal symbol**34 character that separates the whole and fractional parts in the decimal representation of a real number in a file
35 (10.6)**1.3.49****declaration**

specification of attributes for various program entities

NOTE 1.2

Often this involves specifying the type of a named [data object](#) or specifying the shape of a named array [object](#).

36 **1.3.50**37 **default initialization**38 mechanism for automatically initializing pointer components to have a defined pointer association status, and
39 nonpointer components to have a particular value (4.5.4.6)

- 1 **1.3.51**
2 **default-initialized**
3 *<subcomponent>* subject to a **default initialization** specified in the type definition for that **component** (4.5.4.6)
- 4 **1.3.52**
5 **definable**
6 capable of **definition** and permitted to become **defined**
- 7 **1.3.53**
8 **defined**
9 *<data object>* has a valid value
- 10 **1.3.54**
11 **defined**
12 *<pointer>* has a pointer association status of associated or **disassociated** (16.5.2.2)
- 13 **1.3.55**
14 **defined assignment**
15 assignment defined by a procedure (7.2.1.4, 12.4.3.5.3)
- 16 **1.3.56**
17 **defined input/output**
18 input/output defined by a procedure and accessed via a *defined-io-generic-spec* (R1209, 9.6.4.8)
- 19 **1.3.57**
20 **defined operation**
21 operation defined by a procedure (7.1.6.1, 12.4.3.5.2)
- 22 **1.3.58**
23 **definition**
24 *<data object>* process by which the data object becomes defined (16.6.5)
- 25 **1.3.59**
26 **definition**
27 *<derived type (4.5.2), enumeration (4.6), or procedure (12.6)>* specification of the type, enumeration, or procedure
- 28 **1.3.60**
29 **descendant**
30 *<module or submodule>* submodule that extends that module or submodule or that extends another descendant
31 thereof
- 32 **1.3.61**
33 **designator**
34 name followed by zero or more component selectors, complex part selectors, array section selectors, array element
35 selectors, image selectors, and substring selectors (6.1)
- 36 **1.3.61.1**
37 **complex part designator**
38 designator that designates the real or imaginary part of a complex **data object**, independently of the other part
39 (6.4.4)

1.3.61.2**object designator****data object designator**

designator for a data object

NOTE 1.3

An object name is a special case of an object designator.

1 **1.3.61.3**2 **procedure designator**

3 designator for a procedure

4 **1.3.62**5 **disassociated**6 <pointer association> pointer association status of not being associated with any target and not being undefined
7 (16.5.2.2)8 **1.3.63**9 **disassociated**

10 <pointer> has a pointer association status of disassociated

11 **1.3.64**12 **dummy argument**13 entity whose identifier appears in a dummy argument list (R1237) in a FUNCTION, SUBROUTINE, ENTRY, or
14 statement function statement, or whose name can be used as an argument keyword in a reference to an intrinsic
15 procedure or a procedure in an intrinsic module16 **1.3.64.1**17 **dummy data object**

18 dummy argument that is a data object

19 **1.3.64.2**20 **dummy function**

21 dummy procedure that is a function

22 **1.3.65**23 **effective argument**

24 entity that is argument-associated with a dummy argument (12.5.2.3)

25 **1.3.66**26 **effective item**

27 scalar object resulting from the application of the rules in 9.6.3 to an input/output list

28 **1.3.67**29 **elemental**30 independent scalar application of an action or operation to elements of an array or corresponding elements of a
31 set of conformable arrays and scalars, or possessing the capability of elemental operation**NOTE 1.4**

Combination of scalar and array operands or arguments combine the scalar operand(s) with each element of the array operand(s).

32 **1.3.67.1**33 **elemental assignment**

34 assignment that operates elementally

- 1 **1.3.67.2**
2 **elemental operation**
3 operation that operates elementally
- 4 **1.3.67.3**
5 **elemental operator**
6 operator in an elemental operation
- 7 **1.3.67.4**
8 **elemental procedure**
9 elemental [intrinsic](#) procedure or procedure defined by an elemental subprogram
- 10 **1.3.67.5**
11 **elemental reference**
12 reference to an elemental procedure with at least one array actual argument
- 13 **1.3.67.6**
14 **elemental subprogram**
15 subprogram with the [ELEMENTAL](#) prefix
- 16 **1.3.68**
17 **END statement**
18 *end-block-data-stmt, end-function-stmt, end-module-stmt, end-mp-subprogram-stmt, end-program-stmt,*
19 *end-submodule-stmt, or end-subroutine-stmt*
- 20 **1.3.69**
21 **explicit initialization**
22 initialization of a data object by a specification statement ([5.4](#), [5.6.7](#))
- 23 **1.3.70**
24 **explicit interface**
25 interface of a procedure that includes all the characteristics of the procedure and names for its dummy arguments
26 except for asterisk dummy arguments ([12.4.2](#))
- 27 **1.3.71**
28 **extent**
29 number of elements in a single dimension of an [array](#)
- 30 **1.3.72**
31 **external file**
32 file that exists in a medium external to the program ([9.3](#))
- 33 **1.3.73**
34 **external unit**
35 **external input/output unit**
36 entity that can be [connected](#) to an [external file](#)
- 37 **1.3.74**
38 **file storage unit**
39 unit of storage in a [stream file](#) or an unformatted [record file](#) ([9.3.5](#))
- 40 **1.3.75**
41 **final subroutine**
42 subroutine whose name appears in a [FINAL statement](#) ([4.5.6](#)) in a type definition, and which can be automatically
43 invoked by the processor when an object of that type is finalized ([4.5.6.2](#))

- 1 **1.3.76**
2 **finalizable**
3 [⟨type⟩](#) has a final subroutine or a nonpointer nonallocatable component of finalizable type
- 4 **1.3.77**
5 **finalizable**
6 [⟨nonpointer data entity⟩](#) of finalizable type
- 7 **1.3.78**
8 **finalization**
9 process of calling [final subroutines](#) when one of the events listed in [4.5.6.3](#) occurs
- 10 **1.3.79**
11 **function**
12 procedure that is invoked by an expression
- 13 **1.3.80**
14 **function result**
15 entity that returns the value of a function
- 16 **1.3.81**
17 **generic identifier**
18 [lexical token](#) that identifies a generic set of procedures, [intrinsic](#) operations, and/or [intrinsic](#) assignments
- 19 **1.3.82**
20 **host instance**
21 [⟨internal procedure, or dummy procedure or procedure pointer associated with an internal procedure⟩](#) instance
22 of the host procedure that supplies the host environment of the [internal procedure](#) ([12.6.2.4](#))
- 23 **1.3.83**
24 **host scoping unit**
25 **host**
26 [scoping unit](#) immediately surrounding another [scoping unit](#), or the [scoping unit](#) extended by a submodule
- 27 **1.3.84**
28 **IEEE infinity**
29 ISO/IEC/IEEE 60559:2011 conformant infinite floating-point value
- 30 **1.3.85**
31 **IEEE NaN**
32 ISO/IEC/IEEE 60559:2011 conformant floating-point datum that does not represent a number
- 33 **1.3.86**
34 **image**
35 instance of a Fortran program ([2.3.4](#))
- 36 **1.3.87**
37 **image index**
38 integer value identifying an [image](#)
- 39 **1.3.88**
40 **image control statement**
41 statement that affects the execution ordering between [images](#) ([8.5](#))
- 42 **1.3.89**
43 **implicit interface**
44 interface of a procedure that includes only the type and type parameters of a function result ([12.4.2](#), [12.4.3.9](#))

1 **1.3.90**
2 **inclusive scope**
3 nonblock [scoping unit](#) plus every [block scoping unit](#) whose [host](#) is that [scoping unit](#) or that is nested within such
4 a [block scoping unit](#)

NOTE 1.5

That is, inclusive scope is the scope as if [BLOCK constructs](#) were not [scoping units](#).

5 **1.3.91**
6 **inherit**
7 [extended type](#) acquire entities ([components](#), [type-bound procedures](#), and [type parameters](#)) through type exten-
8 sion from the parent type

9 **1.3.92**
10 **inquiry function**
11 [intrinsic](#) function, or function in an [intrinsic](#) module, whose result depends on the properties of one or more of
12 its arguments instead of their values

13 **1.3.93**
14 **interface**
15 [procedure](#) name, procedure characteristics, dummy argument names, binding label, and generic identifiers
16 ([12.4.1](#))

17 **1.3.93.1**
18 **generic interface**
19 set of procedure interfaces identified by a [generic identifier](#)

20 **1.3.93.2**
21 **specific interface**
22 [interface](#) identified by a nongeneric name

23 **1.3.94**
24 **interface block**
25 [abstract interface block](#), [generic interface block](#), or [specific interface block](#) ([12.4.3.2](#))

26 **1.3.94.1**
27 **abstract interface block**
28 interface block with the [ABSTRACT](#) keyword; collection of [interface bodies](#) that specify named [abstract interfaces](#)

29 **1.3.94.2**
30 **generic interface block**
31 interface block with a [generic-spec](#); collection of [interface bodies](#) and procedure statements that are to be given
32 that generic identifier

33 **1.3.94.3**
34 **specific interface block**
35 interface block with no [generic-spec](#) or [ABSTRACT](#) keyword; collection of [interface bodies](#) that specify the
36 interfaces of procedures

37 **1.3.95**
38 **interoperable**
39 [Fortran entity](#) equivalent to an entity defined by or definable by the [companion processor](#) ([15.3](#))

- 1 **1.3.96**
2 **intrinsic**
3 type, procedure, module, assignment, operator, or input/output operation defined in this part of ISO/IEC 1539
4 and accessible without further definition or specification, or a procedure or module provided by a processor but
5 not defined in this part of ISO/IEC 1539
- 6 **1.3.96.1**
7 **standard intrinsic**
8 ⟨procedure or module⟩ defined in this part of ISO/IEC 1539 (13)
- 9 **1.3.96.2**
10 **nonstandard intrinsic**
11 ⟨procedure or module⟩ provided by a processor but not defined in this part of ISO/IEC 1539
- 12 **1.3.97**
13 **internal file**
14 character variable that is [connected](#) to an [internal unit](#) (9.4)
- 15 **1.3.98**
16 **internal unit**
17 [input/output unit](#) that is [connected](#) to an [internal file](#) (9.5.4)
- 18 **1.3.99**
19 **ISO 10646 character**
20 character whose representation method corresponds to UCS-4 in ISO/IEC 10646
- 21 **1.3.100**
22 **keyword**
23 statement keyword, argument keyword, type parameter keyword, or component keyword
- 24 **1.3.100.1**
25 **argument keyword**
26 word that identifies the corresponding [dummy argument](#) in an [actual argument](#) list
- 27 **1.3.100.2**
28 **component keyword**
29 word that identifies a [component](#) in a [structure constructor](#)
- 30 **1.3.100.3**
31 **statement keyword**
32 word that is part of the syntax of a statement (2.5.2)
- 33 **1.3.100.4**
34 **type parameter keyword**
35 word that identifies a [type parameter](#) in a type parameter list
- 36 **1.3.101**
37 **lexical token**
38 keyword, name, literal constant other than a complex literal constant, operator, label, delimiter, comma, =, =>,
39 :, ::, ;, or % (3.2)
- 40 **1.3.102**
41 **line**
42 sequence of zero or more characters
- 43 **1.3.103**
44 **main program**
45 [program unit](#) that is not a [subprogram](#), [module](#), [submodule](#), or [block data program unit](#) (11.1)

- 1 **1.3.104**
2 **masked array assignment**
3 [assignment statement](#) in a [WHERE statement](#) or [WHERE construct](#) (7.2.3)
- 4 **1.3.105**
5 **module**
6 [program unit](#) containing (or accessing from other modules) definitions that are to be made accessible to other
7 [program units](#) (11.2)
- 8 **1.3.106**
9 **name**
10 identifier of a program constituent, formed according to the rules given in 3.2.2
- 11 **1.3.107**
12 **NaN**
13 Not a Number, a symbolic floating-point datum (ISO/IEC/IEEE 60559:2011)
- 14 **1.3.108**
15 **operand**
16 data value that is the subject of an operator
- 17 **1.3.109**
18 **operator**
19 [intrinsic-operator](#), [defined-unary-op](#), or [defined-binary-op](#) (R308, R703, R723)
- 20 **1.3.110**
21 **passed-object dummy argument**
22 dummy argument of a [type-bound procedure](#) or procedure pointer component that becomes associated with the
23 object through which the procedure is invoked (4.5.4.5)
- 24 **1.3.111**
25 **pointer**
26 [data pointer](#) (1.3.111.1) or [procedure pointer](#) (1.3.111.2)
- 27 **1.3.111.1**
28 **data pointer**
29 [data entity](#) with the [POINTER attribute](#) (5.5.14)
- 30 **1.3.111.2**
31 **procedure pointer**
32 procedure with the [EXTERNAL](#) and [POINTER](#) attributes (5.5.9, 5.5.14)
- 33 **1.3.111.3**
34 **local procedure pointer**
35 [procedure pointer](#) that is part of a [local variable](#), or a named [procedure pointer](#) that is not a [dummy argument](#)
36 or accessed by use or host association
- 37 **1.3.112**
38 **pointer assignment**
39 association of a pointer with a target, by execution of a [pointer assignment statement](#) (7.2.2) or an [intrinsic](#)
40 [assignment statement](#) (7.2.1.2) for a derived-type object that has the pointer as a subobject
- 41 **1.3.113**
42 **polymorphic**
43 [data entity](#) able to be of differing [dynamic types](#) during program execution (4.3.2.3)

- 1 **1.3.114**
2 **preconnected**
3 <file or [unit](#)> [connected](#) at the beginning of execution of the program (9.5.5)
- 4 **1.3.115**
5 **procedure**
6 entity encapsulating an arbitrary sequence of actions that can be invoked directly during program execution
- 7 **1.3.115.1**
8 **dummy procedure**
9 procedure that is a [dummy argument](#) (12.2.2.3)
- 10 **1.3.115.2**
11 **external procedure**
12 procedure defined by an external subprogram (R203) or by means other than Fortran (12.6.3)
- 13 **1.3.115.3**
14 **internal procedure**
15 procedure defined by an internal subprogram (R212)
- 16 **1.3.115.4**
17 **module procedure**
18 procedure that is defined by a module subprogram (R1108)
- 19 **1.3.115.5**
20 **pure procedure**
21 procedure declared or defined to be pure according to the rules in 12.7
- 22 **1.3.115.6**
23 **type-bound procedure**
24 procedure that is bound to a derived type and referenced via an object of that type (4.5.5)
- 25 **1.3.116**
26 **processor**
27 combination of a computing system and mechanism by which programs are transformed for use on that computing
28 system
- 29 **1.3.117**
30 **processor dependent**
31 not completely specified in this part of ISO/IEC 1539, having methods and semantics determined by the processor
- 32 **1.3.118**
33 **program**
34 set of Fortran [program units](#) and entities defined by means other than Fortran that includes exactly one [main](#)
35 [program](#)
- 36 **1.3.119**
37 **program unit**
38 [main program](#), [external subprogram](#), [module](#), [submodule](#), or [block data program unit](#) (2.2.1)
- 39 **1.3.120**
40 **rank**
41 number of array dimensions of a [data entity](#) (zero for a scalar entity)
- 42 **1.3.121**
43 **record**
44 sequence of values or characters in a file (9.2)

- 1 **1.3.122**
2 **record file**
3 file composed of a sequence of records (9.1)
- 4 **1.3.123**
5 **reference**
6 [data object](#) reference, [procedure](#) reference, or [module](#) reference
- 7 **1.3.123.1**
8 **data object reference**
9 appearance of a [data object designator](#) (6.1) in a context requiring its value at that point during execution
- 10 **1.3.123.2**
11 **function reference**
12 appearance of the [procedure designator](#) for a function, or operator symbol in a context requiring execution of the
13 function during expression evaluation (12.5.3)
- 14 **1.3.123.3**
15 **module reference**
16 appearance of a module name in a [USE statement](#) (11.2.2)
- 17 **1.3.123.4**
18 **procedure reference**
19 appearance of a [procedure designator](#), operator symbol, or assignment symbol in a context requiring execution
20 of the procedure at that point during execution; or occurrence of defined input/output (10.7.6) or derived-type
21 [finalization](#) (4.5.6.2)
- 22 **1.3.124**
23 **saved**
24 having the [SAVE attribute](#) (5.5.16)
- 25 **1.3.125**
26 **scalar**
27 [data entity](#) that can be represented by a single value of the type and that is not an array (6.5)
- 28 **1.3.126**
29 **scoping unit**
30 [BLOCK construct](#), derived-type definition, [interface body](#), [program unit](#), or subprogram, excluding all nested
31 scoping units in it
- 32 **1.3.126.1**
33 **block scoping unit**
34 scoping unit of a [BLOCK construct](#)
- 35 **1.3.127**
36 **sequence**
37 set of elements ordered by a one-to-one correspondence with the numbers 1, 2, to n
- 38 **1.3.128**
39 **sequence structure**
40 [scalar data object](#) of a [sequence type](#) (4.5.2.3)
- 41 **1.3.129**
42 **sequence type**
43 derived type with the [SEQUENCE attribute](#) (4.5.2.3)

1 **1.3.129.1**
2 **character sequence type**
3 sequence type with no [type parameters](#), no [allocatable](#) or [pointer components](#), and whose [components](#) are all
4 default character or of another character sequence type

5 **1.3.129.2**
6 **numeric sequence type**
7 sequence type with no [type parameters](#), no [allocatable](#) or [pointer components](#), and whose [components](#) are all
8 default complex, default integer, default logical, default real, double precision real, or of another numeric sequence
9 type

10 **1.3.130**
11 **shape**
12 array dimensionality of a data entity, represented as a rank-one array whose size is the [rank](#) of the data entity
13 and whose elements are the extents of the data entity

NOTE 1.6

Thus the shape of a scalar data entity is an array with rank one and size zero.

14 **1.3.131**
15 **simply contiguous**
16 [⟨array designator or variable⟩](#) satisfying the conditions specified in [6.5.4](#)

NOTE 1.7

These conditions are simple ones which make it clear that the designator or variable designates a [contiguous](#) array.

17 **1.3.132**
18 **size**
19 [⟨array⟩](#) total number of elements in the array

20 **1.3.133**
21 **specification expression**
22 expression satisfying the requirements specified in [7.1.11](#), thus being suitable for use in specifications

23 **1.3.134**
24 **specific name**
25 name that is not a generic name

26 **1.3.135**
27 **standard-conforming program**
28 program that uses only those forms and relationships described in, and has an interpretation according to, this
29 part of ISO/IEC 1539

30 **1.3.136**
31 **statement**
32 sequence of one or more complete or partial lines satisfying a syntax rule that ends in *-stmt* ([3.3](#))

33 **1.3.136.1**
34 **executable statement**
35 statement that is a member of the syntactic class [executable-construct](#), excluding those in the [block-specification-](#)
36 [part](#) of a [BLOCK construct](#)

37 **1.3.136.2**
38 **nonexecutable statement**
39 statement that is not an [executable statement](#)

- 1 **1.3.137**
2 **statement entity**
3 entity whose identifier has the scope of a statement or part of a statement (16.1, 16.4)
- 4 **1.3.138**
5 **statement label**
6 **label**
7 unsigned positive number of up to five digits that refers to an individual statement (3.2.5)
- 8 **1.3.139**
9 **storage sequence**
10 contiguous sequence of [storage units](#) (16.5.3.2)
- 11 **1.3.140**
12 **storage unit**
13 [character storage unit](#), [numeric storage unit](#), [file storage unit](#), or [unspecified storage unit](#) (16.5.3.2)
- 14 **1.3.140.1**
15 **character storage unit**
16 unit of storage that holds a default character value (16.5.3.2)
- 17 **1.3.140.2**
18 **numeric storage unit**
19 unit of storage that holds a default real, default integer, or default logical value (16.5.3.2)
- 20 **1.3.140.3**
21 **unspecified storage unit**
22 unit of storage that holds a value that is not default character, default real, double precision real, default logical,
23 or default complex (16.5.3.2)
- 24 **1.3.141**
25 **stream file**
26 file composed of a sequence of file storage units (9.1)
- 27 **1.3.142**
28 **structure**
29 [scalar data object](#) of [derived type](#) (4.5)
- 30 **1.3.142.1**
31 **structure component**
32 [component](#) of a structure
- 33 **1.3.142.2**
34 **structure constructor**
35 syntax (*structure-constructor*, 4.5.10) that specifies a structure value or creates such a value
- 36 **1.3.143**
37 **submodule**
38 [program unit](#) that extends a [module](#) or another [submodule](#) (11.2.3)
- 39 **1.3.144**
40 **subobject**
41 portion of [data object](#) that can be referenced, and if it is a [variable](#) defined, independently of any other portion
- 42 **1.3.145**
43 **subprogram**
44 *function-subprogram* (R1229) or *subroutine-subprogram* (R1235)

- 1 **1.3.145.1**
2 **external subprogram**
3 subprogram that is not contained in a [main program](#), [module](#), [submodule](#), or another subprogram
- 4 **1.3.145.2**
5 **internal subprogram**
6 subprogram that is contained in a [main program](#) or another subprogram
- 7 **1.3.145.3**
8 **module subprogram**
9 subprogram that is contained in a [module](#) or [submodule](#) but is not an internal subprogram
- 10 **1.3.146**
11 **subroutine**
12 procedure invoked by a [CALL statement](#), by [defined assignment](#), or by some operations on derived-type entities
- 13 **1.3.146.1**
14 **atomic subroutine**
15 [intrinsic](#) subroutine that performs an action on its ATOM argument atomically
- 16 **1.3.147**
17 **target**
18 entity that is [pointer associated](#) with a [pointer](#) (16.5.2.2), entity on the right-hand-side of a [pointer assignment](#)
19 [statement](#) (R733), or entity with the [TARGET attribute](#) (5.5.17)
- 20 **1.3.148**
21 **transformational function**
22 [intrinsic](#) function, or function in an [intrinsic](#) module, that is neither [elemental](#) nor an [inquiry function](#)
- 23 **1.3.149**
24 **type**
25 **data type**
26 named category of data characterized by a set of values, a syntax for denoting these values, and a set of operations
27 that interpret and manipulate the values (4.1)
- 28 **1.3.149.1**
29 **abstract type**
30 type with the [ABSTRACT attribute](#) (4.5.7.1)
- 31 **1.3.149.2**
32 **declared type**
33 type that a data entity is declared to have, either explicitly or implicitly (4.3.2, 7.1.9)
- 34 **1.3.149.3**
35 **derived type**
36 type defined by a type definition (4.5) or by an [intrinsic](#) module
- 37 **1.3.149.4**
38 **dynamic type**
39 type of a data entity at a particular point during execution of a program (4.3.2.3, 7.1.9)
- 40 **1.3.149.5**
41 **extended type**
42 type with the [EXTENDS attribute](#) (4.5.7.1)
- 43 **1.3.149.6**
44 **extensible type**
45 type that may be extended using the [EXTENDS clause](#) (4.5.7.1)

1 **1.3.149.7**
2 **extension type**
3 ⟨of one type with respect to another⟩ is the same type or is an extended type whose parent type is an extension
4 type of the other type

5 **1.3.149.8**
6 **intrinsic type**
7 type defined by this part of ISO/IEC 1539 that is always accessible (4.4)

8 **1.3.149.9**
9 **numeric type**
10 one of the types integer, real, and complex

11 **1.3.149.10**
12 **parent type**
13 ⟨[extended type](#)⟩ type named in the EXTENDS clause

14 **1.3.149.11**
15 **type compatible**
16 compatibility of the type of one entity with respect to another for purposes such as [argument association](#), [pointer](#)
17 [association](#), and allocation (4.3.2)

18 **1.3.149.12**
19 **type parameter**
20 value used to parameterize a type (4.2)

21 **1.3.149.12.1**
22 **assumed type parameter**
23 [length type parameter](#) that assumes the type parameter value from another entity

NOTE 1.8

The other entity is

- the selector for an [associate name](#),
- the *constant-expr* for a [named constant](#) of type character, or
- the [effective argument](#) for a [dummy argument](#).

24 **1.3.149.12.2**
25 **deferred type parameter**
26 [length type parameter](#) whose value can change during execution of a program and whose *type-param-value* is a
27 colon

28 **1.3.149.12.3**
29 **kind type parameter**
30 type parameter whose value is required to be defaulted or given by a [constant expression](#)

31 **1.3.149.12.4**
32 **length type parameter**
33 type parameter whose value is permitted to be [assumed](#), [deferred](#), or given by a [specification expression](#)

34 **1.3.149.12.5**
35 **type parameter inquiry**
36 syntax (*type-param-inquiry*) that is used to inquire the value of a type parameter of a data object (6.4.5)

37 **1.3.149.12.6**
38 **type parameter order**
39 ordering of the type parameters of a type (4.5.3.2) used for derived-type specifiers (*derived-type-spec*, 4.5.9)

- 1 **1.3.150**
2 **ultimate argument**
3 nondummy entity with which a [dummy argument](#) is associated via a chain of argument associations ([12.5.2.3](#))
- 4 **1.3.151**
5 **undefined**
6 [⟨data object⟩](#) does not have a valid value
- 7 **1.3.152**
8 **undefined**
9 [⟨pointer⟩](#) does not have a pointer association status of associated or [disassociated](#) ([16.5.2.2](#))
- 10 **1.3.153**
11 **unit**
12 **input/output unit**
13 means, specified by an [io-unit](#), for referring to a file ([9.5.1](#))
- 14 **1.3.154**
15 **unlimited polymorphic**
16 able to have any [dynamic type](#) during program execution ([4.3.2.3](#))
- 17 **1.3.155**
18 **unsaved**
19 not having the [SAVE attribute](#) ([5.5.16](#))
- 20 **1.3.156**
21 **variable**
22 [data entity](#) that can be [defined](#) and redefined during execution of a program
- 23 **1.3.156.1**
24 **event variable**
25 scalar variable of type `EVENT_TYPE` ([13.9.2.9](#)) from the intrinsic module `ISO_FORTRAN_ENV`
- 26 **1.3.156.2**
27 **local variable**
28 variable in a [scoping unit](#) that is not a [dummy argument](#) or part thereof, is not a global entity or part thereof,
29 and is not an entity or part of an entity that is accessible outside that [scoping unit](#)
- 30 **1.3.156.3**
31 **lock variable**
32 scalar variable of type `LOCK_TYPE` ([13.9.2.17](#)) from the intrinsic module `ISO_FORTRAN_ENV`
- 33 **1.3.157**
34 **vector subscript**
35 [section-subscript](#) that is an array ([6.5.3.3.2](#))
- 36 **1.3.158**
37 **whole array**
38 array component or array name without further qualification ([6.5.2](#))

39 **1.4 Notation, symbols and abbreviated terms**

40 **1.4.1 Syntax rules**

41 1 Syntax rules describe the forms that Fortran [lexical tokens](#), statements, and constructs may take. These syntax
42 rules are expressed in a variation of Backus-Naur form (BNF) with the following conventions.

- 43
 - Characters from the Fortran character set ([3.1](#)) are interpreted literally as shown, except where otherwise

1 noted.

- 2 • Lower-case italicized letters and words (often hyphenated and abbreviated) represent general syntactic
3 classes for which particular syntactic entities shall be substituted in actual statements.

4 Common abbreviations used in syntactic terms are:

<i>arg</i>	for	argument	<i>attr</i>	for	attribute
<i>decl</i>	for	declaration	<i>def</i>	for	definition
<i>desc</i>	for	descriptor	<i>expr</i>	for	expression
<i>int</i>	for	integer	<i>op</i>	for	operator
<i>spec</i>	for	specifier	<i>stmt</i>	for	statement

- 5 • The syntactic metasympols used are:

is	introduces a syntactic class definition
or	introduces a syntactic class alternative
[]	encloses an optional item
[] ...	encloses an optionally repeated item that may occur zero or more times
■	continues a syntax rule

- 6 • Each syntax rule is given a unique identifying number of the form Rsnn, where s is a one- or two-digit
7 clause number and nn is a two-digit sequence number within that clause. The syntax rules are distributed
8 as appropriate throughout the text, and are referenced by number as needed. Some rules in Clauses 2 and
9 3 are more fully described in later clauses; in such cases, the clause number s is the number of the later
10 clause where the rule is repeated.
- 11 • The syntax rules are not a complete and accurate syntax description of Fortran, and cannot be used to
12 generate a Fortran parser automatically; where a syntax rule is incomplete, it is restricted by corresponding
13 constraints and text.

NOTE 1.9

An example of the use of the syntax rules is:

digit-string **is** *digit* [*digit*] ...

The following are examples of forms for a digit string allowed by the above rule:

digit
digit digit
digit digit digit digit
digit digit digit digit digit digit digit digit

If particular entities are substituted for *digit*, actual digit strings might be:

4
67
1999
10243852

14 1.4.2 Constraints

- 15 1 Each constraint is given a unique identifying number of the form Csnn, where s is a one or two digit clause number
16 and nn is a two or three digit sequence number within that clause.
- 17 2 Often a constraint is associated with a particular syntax rule. Where that is the case, the constraint is annotated
18 with the syntax rule number in parentheses. A constraint that is associated with a syntax rule constitutes part of
19 the definition of the syntax term defined by the rule. It thus applies in all places where the syntax term appears.

1 3 Some constraints are not associated with particular syntax rules. The effect of such a constraint is similar to
2 that of a restriction stated in the text, except that a processor is required to have the capability to detect and
3 report violations of constraints (1.5). In some cases, a broad requirement is stated in text and a subset of the
4 same requirement is also stated as a constraint. This indicates that a standard-conforming program is required to
5 adhere to the broad requirement, but that a standard-conforming processor is required only to have the capability
6 of diagnosing violations of the constraint.

7 1.4.3 Assumed syntax rules

8 1 In order to minimize the number of additional syntax rules and convey appropriate constraint information, the
9 following rules are assumed.

10 R101 *xyz-list* is *xyz* [, *xyz*] ...

11 R102 *xyz-name* is *name*

12 R103 *scalar-xyz* is *xyz*

13 C101 (R103) *scalar-xyz* shall be scalar.

14 2 The letters “*xyz*” stand for any syntactic class phrase. An explicit syntax rule for a term overrides an assumed
15 rule.

16 1.4.4 Syntax conventions and characteristics

17 1 Any syntactic class name ending in “-*stmt*” follows the source form statement rules: it shall be delimited by
18 end-of-line or semicolon, and may be labeled unless it forms part of another statement (such as an **IF** or **WHERE**
19 statement). Conversely, everything considered to be a source form statement is given a “-*stmt*” ending in the
20 syntax rules.

21 2 The rules on statement ordering are described rigorously in the definition of *program-unit* (R202). Expression
22 hierarchy is described rigorously in the definition of *expr* (R722).

23 3 The suffix “-*spec*” is used consistently for specifiers, such as input/output statement specifiers. It also is used for
24 type declaration attribute specifications (for example, “*array-spec*” in R515), and in a few other cases.

25 4 Where reference is made to a type parameter, including the surrounding parentheses, the suffix “-*selector*” is
26 used. See, for example, “*kind-selector*” (R406) and “*length-selector*” (R422).

27 1.4.5 Text conventions

28 1 In descriptive text, an equivalent English word is frequently used in place of a syntactic term. Particular state-
29 ments and attributes are identified in the text by an upper-case keyword, e.g., “END statement”. The descriptions
30 of obsolescent features appear in a smaller type size.

NOTE 1.10

This sentence is an example of the type size used for obsolescent features.

31 1.5 Conformance

32 1 A **program** (2.2.2) is a **standard-conforming program** if it uses only those forms and relationships described
33 herein and if the program has an interpretation according to this part of ISO/IEC 1539. A **program unit** (2.2.1)
34 conforms to this part of ISO/IEC 1539 if it can be included in a **program** in a manner that allows the **program**
35 to be standard conforming.

36 2 A **processor** conforms to this part of ISO/IEC 1539 if:

- 1 (1) it executes any **standard-conforming program** in a manner that fulfills the interpretations herein,
2 subject to any limits that the **processor** may impose on the size and complexity of the **program**;
- 3 (2) it contains the capability to detect and report the use within a submitted **program unit** of a form
4 designated herein as obsolescent, insofar as such use can be detected by reference to the numbered
5 syntax rules and constraints;
- 6 (3) it contains the capability to detect and report the use within a submitted **program unit** of an ad-
7 ditional form or relationship that is not permitted by the numbered syntax rules or constraints,
8 including the deleted features described in Annex B
- 9 (4) it contains the capability to detect and report the use within a submitted **program unit** of an intrinsic
10 type with a **kind type parameter** value not supported by the processor (4.4);
- 11 (5) it contains the capability to detect and report the use within a submitted **program unit** of source
12 form or characters not permitted by Clause 3;
- 13 (6) it contains the capability to detect and report the use within a submitted **program** of name usage
14 not consistent with the scope rules for names, labels, operators, and assignment symbols in Clause
15 16;
- 16 (7) it contains the capability to detect and report the use within a submitted **program unit** of a **non-**
17 **standard intrinsic** procedure (including one with the same name as a **standard intrinsic** procedure
18 but with different requirements);
- 19 (8) it contains the capability to detect and report the use within a submitted **program unit** of a **non-**
20 **standard intrinsic** module;
- 21 (9) it contains the capability to detect and report the use within a submitted **program unit** of a procedure
22 from a **standard intrinsic** module, if the procedure is not defined by this part of ISO/IEC 1539 or
23 the procedure has different requirements from those specified by this part of ISO/IEC 1539; and
- 24 (10) it contains the capability to detect and report the reason for rejecting a submitted **program**.
- 25 3 However, in a format specification that is not part of a **FORMAT statement** (10.2.1), a processor need not detect
26 or report the use of deleted or obsolescent features, or the use of additional forms or relationships.
- 27 4 A standard-conforming processor may allow additional forms and relationships provided that such additions
28 do not conflict with the standard forms and relationships. However, a standard-conforming processor may allow
29 additional intrinsic procedures even though this could cause a conflict with the name of a procedure in a standard-
30 conforming program. If such a conflict occurs and involves the name of an **external procedure**, the processor is
31 permitted to use the intrinsic procedure unless the name has the **EXTERNAL attribute** (5.5.9) where it is used.
32 A standard-conforming program shall not use **nonstandard intrinsic** procedures or modules that have been added
33 by the processor.
- 34 5 Because a standard-conforming program may place demands on a processor that are not within the scope of this
35 part of ISO/IEC 1539 or may include standard items that are not portable, such as **external procedures** defined
36 by means other than Fortran, conformance to this part of ISO/IEC 1539 does not ensure that a program will
37 execute consistently on all or any standard-conforming processors.
- 38 6 The semantics of facilities that are identified as **processor dependent** are not completely specified in this part of
39 ISO/IEC 1539. They shall be provided, with methods or semantics determined by the processor.
- 40 7 The **processor** should be accompanied by documentation that specifies the limits it imposes on the size and com-
41 plexity of a **program** and the means of reporting when these limits are exceeded, that defines the additional forms
42 and relationships it allows, and that defines the means of reporting the use of additional forms and relationships
43 and the use of deleted or obsolescent forms. In this context, the use of a deleted form is the use of an additional
44 form.
- 45 8 The **processor** should be accompanied by documentation that specifies the methods or semantics of processor-
46 dependent facilities.

1.6 Compatibility

1.6.1 Previous Fortran standards

- 1 Table 1.3 lists the previous editions of the Fortran International Standard, along with their informal names.

Table 1.3: Previous editions of the Fortran International Standard

Official designation	Informal name
ISO R 1539-1972	FORTTRAN 66
ISO 1539-1980	FORTTRAN 77
ISO/IEC 1539:1991	Fortran 90
ISO/IEC 1539-1:1997	Fortran 95
ISO/IEC 1539-1:2004	Fortran 2003
ISO/IEC 1539-1:2010	Fortran 2008

1.6.2 New intrinsic procedures

- 1 Each Fortran International Standard since ISO 1539:1980 (FORTTRAN 77), defines more intrinsic procedures than
 2 the previous one. Therefore, a Fortran program conforming to an older standard might have a different inter-
 3 pretation under a newer standard if it invokes an external procedure having the same name as one of the new
 4 standard intrinsic procedures, unless that procedure is specified to have the [EXTERNAL attribute](#).

1.6.3 Fortran 2008 compatibility

- 1 Except as identified in this subclause, this part of ISO/IEC 1539 is an upward compatible to the preceding Fortran
 2 International Standard, ISO/IEC 1539-1:2010 (Fortran 2008). Except for the deleted features noted in Annex
 3 [B.2](#), any standard-conforming Fortran 2008 program remains standard-conforming under this part of ISO/IEC
 4 1539.
 5 Fortran 2008 specifies that the [IOSTAT=](#) variable shall be set to a processor-dependent negative value if the
 6 flush operation is not supported for the unit specified. This part of ISO/IEC 1539 specifies that the processor-
 7 dependent negative integer value must be different from the [named constants](#) [IOSTAT_EOR](#) or [IOSTAT_END](#)
 8 from the intrinsic module [ISO_FORTRAN_ENV](#).

1.6.4 Fortran 2003 compatibility

- 1 Except as identified in this subclause, this part of ISO/IEC 1539 is an upward compatible extension to ISO/IEC
 2 1539-1:2004 (Fortran 2003). Except as identified in this subclause, any standard-conforming Fortran 2003 program
 3 remains standard-conforming under this part of ISO/IEC 1539.
 4 Fortran 2003 permitted a [sequence type](#) to have [type parameters](#); that is not permitted by this part of ISO/IEC
 5 1539.
 6 Fortran 2003 specified that array constructors and structure constructors of [finalizable](#) type are finalized. This
 7 part of ISO/IEC 1539 specifies that these constructors are not finalized.
 8 The form produced by the G edit descriptor for some values and some input/output rounding modes differs from
 9 that specified by Fortran 2003.
 10 Fortran 2003 required an [explicit interface](#) only for a procedure that was actually referenced in the scope, not
 11 merely passed as an [actual argument](#). This part of ISO/IEC 1539 requires an [explicit interface](#) for a procedure
 12 under the conditions listed in [12.4.2.2](#), regardless of whether the procedure is [referenced](#) in the scope.
 13 Fortran 2003 permitted the [function result](#) of a [pure](#) function to be a [polymorphic](#) allocatable variable, and to be
 14 [finalizable](#) by an impure [final subroutine](#). These are not permitted by this part of ISO/IEC 1539.

1 7 Fortran 2003 permitted an **INTENT (OUT)** argument of a **pure** subroutine to be **polymorphic**; that is not
2 permitted by this part of ISO/IEC 1539.

3 **1.6.5 Fortran 95 compatibility**

4 1 Except as identified in this subclause, this part of ISO/IEC 1539 is an upward compatible extension to ISO/IEC
5 1539-1:1997 (Fortran 95). Except as identified in this subclause, any standard-conforming Fortran 95 program
6 remains standard-conforming under this part of ISO/IEC 1539.

7 2 Fortran 95 permitted defined assignment between character strings of the same rank and different kinds. This
8 part of ISO/IEC 1539 does not permit that if both of the different kinds are ASCII, ISO 10646, or default kind.

9 3 The following Fortran 95 features might have different interpretations in this part of ISO/IEC 1539.

- 10 • Earlier Fortran standards had the concept of printing, meaning that column one of formatted output had
11 special meaning for a processor-dependent (possibly empty) set of **external files**. This could be neither
12 detected nor specified by a standard-specified means. The interpretation of the first column is not specified
13 by this part of ISO/IEC 1539.
- 14 • This part of ISO/IEC 1539 specifies a different output format for real zero values in list-directed and
15 namelist output.
- 16 • If the processor distinguishes between positive and negative real zero, this part of ISO/IEC 1539 requires
17 different returned values for **ATAN2(Y,X)** when $X < 0$ and Y is negative real zero and for **LOG(X)** and
18 **SQRT(X)** when X is complex with **REAL(X) < 0** and negative zero imaginary part.
- 19 • This part of ISO/IEC 1539 has fewer restrictions on **constant expressions** than Fortran 95; this might affect
20 whether a variable is considered to be automatic.
- 21 • The form produced by the G edit descriptor with d equal to zero differs from that specified by Fortran 95
22 for some values.

23 **1.6.6 Fortran 90 compatibility**

24 1 Except for the deleted features noted in Annex **B.1**, and except as identified in this subclause, this part of
25 ISO/IEC 1539 is an upward compatible extension to ISO/IEC 1539:1991 (Fortran 90). Any standard-conforming
26 Fortran 90 program that does not use one of the deleted features remains standard-conforming under this part
27 of ISO/IEC 1539.

28 2 The **PAD= specifier** in the **INQUIRE statement** in this part of ISO/IEC 1539 returns the value UNDEFINED if
29 there is no connection or the connection is for unformatted input/output. Fortran 90 specified YES.

30 3 Fortran 90 specified that if the second argument to **MOD** or **MODULO** was zero, the result was processor
31 dependent. This part of ISO/IEC 1539 specifies that the second argument shall not be zero.

32 4 Fortran 90 permitted defined assignment between character strings of the same rank and different kinds. This
33 part of ISO/IEC 1539 does not permit that if both of the different kinds are ASCII, ISO 10646, or default kind.

34 5 The following Fortran 90 features have different interpretations in this part of ISO/IEC 1539:

- 35 • if the processor distinguishes between positive and negative real zero, the result value of the intrinsic function
36 **SIGN** when the second argument is a negative real zero;
- 37 • formatted output of negative real values (when the output value is zero);
- 38 • whether an expression is a **constant expression** (thus whether a variable is considered to be automatic);
- 39 • the G edit descriptor with d equal to zero for some values.

40 **1.6.7 FORTRAN 77 compatibility**

41 1 Except for the deleted features noted in Annex **B.1**, and except as identified in this subclause, this part of
42 ISO/IEC 1539 is an upward compatible extension to ISO 1539:1980 (FORTRAN 77). Any standard-conforming
43 FORTRAN 77 program that does not use one of the deleted features noted in Annex **B.1** and that does not depend

1 on the differences specified here remains standard-conforming under this part of ISO/IEC 1539. This part of
2 ISO/IEC 1539 restricts the behavior for some features that were processor dependent in FORTRAN 77. Therefore,
3 a standard-conforming FORTRAN 77 program that uses one of these processor-dependent features might have
4 a different interpretation under this part of ISO/IEC 1539, yet remain a standard-conforming program. The
5 following FORTRAN 77 features might have different interpretations in this part of ISO/IEC 1539.

- 6 • FORTRAN 77 permitted a processor to supply more precision derived from a default real constant than can
7 be represented in a default real datum when the constant is used to initialize a double precision real data
8 object in a [DATA statement](#). This part of ISO/IEC 1539 does not permit a processor this option.
- 9 • If a named variable that was not in a [common block](#) was initialized in a [DATA statement](#) and did not have the
10 [SAVE attribute](#) specified, FORTRAN 77 left its [SAVE attribute](#) processor dependent. This part of ISO/IEC
11 1539 specifies (5.6.7) that this named variable has the [SAVE attribute](#).
- 12 • FORTRAN 77 specified that the number of characters required by the input list was to be less than or equal
13 to the number of characters in the record during formatted input. This part of ISO/IEC 1539 specifies
14 (9.6.4.5.3) that the input record is logically padded with blanks if there are not enough characters in the
15 record, unless the [PAD= specifier](#) with the value 'NO' is specified in an appropriate [OPEN](#) or [READ](#)
16 statement.
- 17 • A value of 0 for a list item in a formatted [output statement](#) will be formatted in a different form for some
18 G edit descriptors. In addition, this part of ISO/IEC 1539 specifies how rounding of values will affect the
19 output field form, but FORTRAN 77 did not address this issue. Therefore, some FORTRAN 77 processors
20 might produce an output form different from the output form produced by Fortran 2003 processors for
21 certain combinations of values and G edit descriptors.
- 22 • FORTRAN 77 did not permit a processor to distinguish between positive and negative real zero; if the
23 processor does so distinguish, the result will differ for the intrinsic function [SIGN](#) when the second argument
24 is negative real zero, and formatted output of negative real zero will be different.

25 1.7 Deleted and obsolescent features

26 1.7.1 General

- 27 1 This part of ISO/IEC 1539 protects the users' investment in existing software by including all but six of the
28 language elements of Fortran 90 that are not processor dependent. This part of ISO/IEC 1539 identifies two
29 categories of outmoded features. The first category, deleted features, consists of features considered to have been
30 redundant in FORTRAN 77 and largely unused in Fortran 90. Those in the second category, obsolescent features,
31 are considered to have been redundant in Fortran 90 and Fortran 95, but are still frequently used.

32 1.7.2 Nature of deleted features

- 33 1 Better methods existed in FORTRAN 77 for each deleted feature. These features were not included in Fortran 95
34 or Fortran 2003, and are not included in this revision of Fortran.

35 1.7.3 Nature of obsolescent features

- 36 1 Better methods existed in Fortran 90 and Fortran 95 for each obsolescent feature. It is recommended that
37 programmers use these better methods in new programs and convert existing code to these methods.
- 38 2 The obsolescent features are identified in the text of this part of ISO/IEC 1539 by a distinguishing type font
39 (1.4.5).
- 40 3 A future revision of this part of ISO/IEC 1539 might delete an obsolescent feature if its use has become insigni-
41 ficant.

1

(Blank page)

2 Fortran concepts

2.1 High level syntax

- 1 This subclause introduces the syntax associated with [program units](#) and other Fortran concepts above the construct, statement, and expression levels and illustrates their relationships.

NOTE 2.1

Constraints and other information related to the rules that do not begin with R2 appear in the appropriate clause.

5	R201	<i>program</i>	is	<i>program-unit</i>
6				[<i>program-unit</i>] ...
7	R202	<i>program-unit</i>	is	<i>main-program</i>
8			or	<i>external-subprogram</i>
9			or	<i>module</i>
10			or	<i>submodule</i>
11			or	<i>block-data</i>
12	R1101	<i>main-program</i>	is	[<i>program-stmt</i>]
13				[<i>specification-part</i>]
14				[<i>execution-part</i>]
15				[<i>internal-subprogram-part</i>]
16				<i>end-program-stmt</i>
17	R203	<i>external-subprogram</i>	is	<i>function-subprogram</i>
18			or	<i>subroutine-subprogram</i>
19	R1229	<i>function-subprogram</i>	is	<i>function-stmt</i>
20				[<i>specification-part</i>]
21				[<i>execution-part</i>]
22				[<i>internal-subprogram-part</i>]
23				<i>end-function-stmt</i>
24	R1235	<i>subroutine-subprogram</i>	is	<i>subroutine-stmt</i>
25				[<i>specification-part</i>]
26				[<i>execution-part</i>]
27				[<i>internal-subprogram-part</i>]
28				<i>end-subroutine-stmt</i>
29	R1104	<i>module</i>	is	<i>module-stmt</i>
30				[<i>specification-part</i>]
31				[<i>module-subprogram-part</i>]
32				<i>end-module-stmt</i>
33	R1116	<i>submodule</i>	is	<i>submodule-stmt</i>
34				[<i>specification-part</i>]
35				[<i>module-subprogram-part</i>]
36				<i>end-submodule-stmt</i>
37	R1120	<i>block-data</i>	is	<i>block-data-stmt</i>
38				[<i>specification-part</i>]

1			<i>end-block-data-stmt</i>
2	R204	<i>specification-part</i>	is [<i>use-stmt</i>] ...
3			[<i>import-stmt</i>] ...
4			[<i>implicit-part</i>]
5			[<i>declaration-construct</i>] ...
6	R205	<i>implicit-part</i>	is [<i>implicit-part-stmt</i>] ...
7			<i>implicit-stmt</i>
8	R206	<i>implicit-part-stmt</i>	is <i>implicit-stmt</i>
9			or <i>parameter-stmt</i>
10			or <i>format-stmt</i>
11			or <i>entry-stmt</i>
12	R207	<i>declaration-construct</i>	is <i>specification-construct</i>
13			or <i>data-stmt</i>
14			or <i>format-stmt</i>
15			or <i>entry-stmt</i>
16			or <i>stmt-function-stmt</i>
17	R208	<i>specification-construct</i>	is <i>derived-type-def</i>
18			or <i>enum-def</i>
19			or <i>generic-stmt</i>
20			or <i>interface-block</i>
21			or <i>parameter-stmt</i>
22			or <i>procedure-declaration-stmt</i>
23			or <i>other-specification-stmt</i>
24			or <i>type-declaration-stmt</i>
25	R209	<i>execution-part</i>	is <i>executable-construct</i>
26			[<i>execution-part-construct</i>] ...
27	R210	<i>execution-part-construct</i>	is <i>executable-construct</i>
28			or <i>format-stmt</i>
29			or <i>entry-stmt</i>
30			or <i>data-stmt</i>
31	R211	<i>internal-subprogram-part</i>	is <i>contains-stmt</i>
32			[<i>internal-subprogram</i>] ...
33	R212	<i>internal-subprogram</i>	is <i>function-subprogram</i>
34			or <i>subroutine-subprogram</i>
35	R1107	<i>module-subprogram-part</i>	is <i>contains-stmt</i>
36			[<i>module-subprogram</i>] ...
37	R1108	<i>module-subprogram</i>	is <i>function-subprogram</i>
38			or <i>subroutine-subprogram</i>
39			or <i>separate-module-subprogram</i>
40	R1239	<i>separate-module-subprogram</i>	is <i>mp-subprogram-stmt</i>
41			[<i>specification-part</i>]
42			[<i>execution-part</i>]
43			[<i>internal-subprogram-part</i>]
44			<i>end-mp-subprogram-stmt</i>
45	R213	<i>other-specification-stmt</i>	is <i>access-stmt</i>
46			or <i>allocatable-stmt</i>

1		or	<i>asynchronous-stmt</i>
2		or	<i>bind-stmt</i>
3		or	<i>codimension-stmt</i>
4		or	<i>contiguous-stmt</i>
5		or	<i>dimension-stmt</i>
6		or	<i>external-stmt</i>
7		or	<i>intent-stmt</i>
8		or	<i>intrinsic-stmt</i>
9		or	<i>namelist-stmt</i>
10		or	<i>optional-stmt</i>
11		or	<i>pointer-stmt</i>
12		or	<i>protected-stmt</i>
13		or	<i>save-stmt</i>
14		or	<i>target-stmt</i>
15		or	<i>volatile-stmt</i>
16		or	<i>value-stmt</i>
17		or	<i>common-stmt</i>
18		or	<i>equivalence-stmt</i>
19	R214	<i>executable-construct</i>	is <i>action-stmt</i>
20			or <i>associate-construct</i>
21			or <i>block-construct</i>
22			or <i>case-construct</i>
23			or <i>critical-construct</i>
24			or <i>do-construct</i>
25			or <i>if-construct</i>
26			or <i>select-rank-construct</i>
27			or <i>select-type-construct</i>
28			or <i>where-construct</i>
29			or <i>forall-construct</i>
30	R215	<i>action-stmt</i>	is <i>allocate-stmt</i>
31			or <i>assignment-stmt</i>
32			or <i>backspace-stmt</i>
33			or <i>call-stmt</i>
34			or <i>close-stmt</i>
35			or <i>continue-stmt</i>
36			or <i>cycle-stmt</i>
37			or <i>deallocate-stmt</i>
38			or <i>end-function-stmt</i>
39			or <i>end-mp-subprogram-stmt</i>
40			or <i>end-program-stmt</i>
41			or <i>end-subroutine-stmt</i>
42			or <i>endfile-stmt</i>
43			or <i>error-stop-stmt</i>
44			or <i>event-post-stmt</i>
45			or <i>event-wait-stmt</i>
46			or <i>exit-stmt</i>
47			or <i>flush-stmt</i>
48			or <i>goto-stmt</i>
49			or <i>if-stmt</i>
50			or <i>inquire-stmt</i>
51			or <i>lock-stmt</i>
52			or <i>nullify-stmt</i>
53			or <i>open-stmt</i>
54			or <i>pointer-assignment-stmt</i>

1 or *print-stmt*
 2 or *read-stmt*
 3 or *return-stmt*
 4 or *rewind-stmt*
 5 or *stop-stmt*
 6 or *sync-all-stmt*
 7 or *sync-images-stmt*
 8 or *sync-memory-stmt*
 9 or *unlock-stmt*
 10 or *wait-stmt*
 11 or *where-stmt*
 12 or *write-stmt*
 13 or *computed-goto-stmt*
 14 or *forall-stmt*

15 C201 (R209) An *execution-part* shall not contain an *end-function-stmt*, *end-mp-subprogram-stmt*, *end-program-*
 16 *stmt*, or *end-subroutine-stmt*.

17 2.2 Program unit concepts

18 2.2.1 Program units and scoping units

- 19 1 **Program units** are the fundamental components of a Fortran program. A **program unit** is a **main program**, an
 20 **external subprogram**, a **module**, a **submodule**, or a block data program unit.
- 21 2 A **subprogram** is a function subprogram or a subroutine subprogram. A **module** contains definitions that are
 22 to be made accessible to other **program units**. A **submodule** is an extension of a **module**; it may contain the
 23 definitions of procedures declared in a **module** or another **submodule**. A block data program unit is used to specify initial
 24 values for **data objects** in named **common blocks**.
- 25 3 Each type of **program unit** is described in Clause 11 or 12.
- 26 4 A **program unit** consists of a set of nonoverlapping **scoping units**.

NOTE 2.2

The module or submodule containing a **module subprogram** is the **host scoping unit** of the **module subpro-**
gram. The containing **main program** or **subprogram** is the **host scoping unit** of an **internal subprogram**.

An **internal procedure** is local to its **host** in the sense that its name is accessible within the **host scoping**
unit and all its other **internal procedures** but is not accessible elsewhere.

27 2.2.2 Program

- 28 1 A **program** shall consist of exactly one **main program**, any number (including zero) of other kinds of **program units**,
 29 any number (including zero) of **external procedures**, and any number (including zero) of other entities defined by
 30 means other than Fortran. The **main program** shall be defined by a Fortran *main-program program-unit* or by
 31 means other than Fortran, but not both.

32 2.2.3 Procedure

- 33 1 A procedure is either a function or a subroutine. Invocation of a function in an expression causes a value to be
 34 computed which is then used in evaluating the expression.
- 35 2 A procedure that is not pure might change the program state by changing the value of accessible **data objects** or
 36 **procedure pointers**.

1 3 Procedures are described further in Clause 12.

2 **2.2.4 Module**

3 1 A **module** contains (or accesses from other modules) definitions that are to be made accessible to other **program**
 4 **units**. These definitions include **data object declarations**, type definitions, procedure definitions, and **interface**
 5 **blocks**. Modules are further described in Clause 11.

6 **2.2.5 Submodule**

7 1 A **submodule** extends a **module** or another **submodule**.
 8 2 It may provide definitions (12.6) for procedures whose **interfaces** are declared (12.4.3.2) in an ancestor module
 9 or submodule. It may also contain declarations and definitions of other entities, which are accessible in its
 10 **descendants**. An entity declared in a submodule is not accessible by **use association** unless it is a module procedure
 11 whose **interface** is declared in the ancestor module. Submodules are further described in Clause 11.

NOTE 2.3

A submodule has access to entities in its parent module or submodule by **host association**.

12 **2.3 Execution concepts**

13 **2.3.1 Statement classification**

14 1 Each Fortran statement is classified as either an **executable statement** or a **nonexecutable statement**.
 15 2 An **executable statement** is an instruction to perform or control an action. Thus, the executable statements of a
 16 **program unit** determine the behavior of the **program unit**.
 17 3 **Nonexecutable statements** are used to configure the program environment in which actions take place.

18 **2.3.2 Statement order**

Table 2.1: **Requirements on statement ordering**

PROGRAM, FUNCTION, SUBROUTINE, MODULE, SUBMODULE, or BLOCK DATA statement		
USE statements		
IMPORT statements		
FORMAT and ENTRY statements	IMPLICIT NONE	
	PARAMETER statements	IMPLICIT statements
	PARAMETER and DATA statements	Derived-type definitions, interface blocks, type declaration statements, enumeration definitions, procedure declarations, specification statements, and statement function statements
	DATA statements	Executable constructs
CONTAINS statement		
Internal subprograms or module subprograms		

Requirements on statement ordering (cont.)

END statement

1 The syntax rules of subclause 2.1 specify the statement order within [program units](#) and [subprograms](#). These
 2 rules are illustrated in Table 2.1 and Table 2.2. Table 2.1 shows the ordering rules for statements and applies
 3 to all [program units](#), [subprograms](#), and [interface bodies](#). Vertical lines delineate varieties of statements that
 4 may be interspersed and horizontal lines delineate varieties of statements that shall not be interspersed. [Internal](#)
 5 or [module subprograms](#) shall follow a [CONTAINS statement](#). Between [USE](#) and [CONTAINS](#) statements in a
 6 [subprogram](#), nonexecutable statements generally precede executable statements, although the [ENTRY statement](#),
 7 [FORMAT statement](#), and [DATA statement](#) may appear among the executable statements. Table 2.2 shows which
 8 statements are allowed in some kinds of [scoping units](#).

Table 2.2: Statements allowed in scoping units

Statement type	Kind of scoping unit						
	Main program	Module or submodule	Block data	External subprogram	Module subprogram	Internal subprogram	Interface body
USE	Yes	Yes	Yes	Yes	Yes	Yes	Yes
IMPORT	No	No	No	No	No	No	Yes
ENTRY	No	No	No	Yes	Yes	No	No
FORMAT	Yes	No	No	Yes	Yes	Yes	No
Misc. decl.s ¹	Yes	Yes	Yes	Yes	Yes	Yes	Yes
DATA	Yes	Yes	Yes	Yes	Yes	Yes	No
Derived-type	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Interface	Yes	Yes	No	Yes	Yes	Yes	Yes
Executable	Yes	No	No	Yes	Yes	Yes	No
CONTAINS	Yes	Yes	No	Yes	Yes	No	No
Statement function	Yes	No	No	Yes	Yes	Yes	No

(1) Miscellaneous declarations are [PARAMETER statements](#), [IMPLICIT statements](#), [type declaration statements](#), enumeration definitions, [procedure declaration statements](#), and specification statements.

9 2.3.3 The END statement

10 1 Each [program unit](#), [module subprogram](#), and [internal subprogram](#) shall have exactly one [END statement](#). The
 11 [end-program-stmt](#), [end-function-stmt](#), [end-subroutine-stmt](#), and [end-mp-subprogram-stmt](#) statements are execut-
 12 able, and may be [branch target statements](#) (8.2). Executing an [end-program-stmt](#) initiates [normal termination](#).
 13 Executing an [end-function-stmt](#), [end-subroutine-stmt](#), or [end-mp-subprogram-stmt](#) is equivalent to executing a
 14 [return-stmt](#) with no [scalar-int-expr](#).

15 2 The [end-module-stmt](#), [end-submodule-stmt](#), and [end-block-data-stmt](#) statements are nonexecutable.

16 2.3.4 Program execution

17 1 Execution of a program consists of the asynchronous execution of a fixed number (which may be one) of its [images](#).
 18 Each [image](#) has its own execution state, floating-point status (14.7), and set of [data objects](#), [input/output units](#),
 19 and procedure pointers. The [image index](#) that identifies an [image](#) is an integer value in the range one to the
 20 number of [images](#).

NOTE 2.4

Fortran control constructs (8.1, 8.2) control the progress of execution in each *image*. *Image control statements* (8.5.1) affect the relative progress of execution between *images*. *Coarrays* (2.4.7) provide a mechanism for accessing data on one *image* from another *image*.

NOTE 2.5

A processor might allow the number of *images* to be chosen at compile time, link time, or run time. It might be the same as the number of CPUs but this is not required. Compiling for a single *image* might permit the optimizer to eliminate overhead associated with parallel execution. A program that makes assumptions about the exact number of *images* is unlikely to be portable.

2.3.5 Execution sequence

1 Following the creation of a fixed number of instances of the program, execution begins on each *image*. *Image* execution is a sequence, in time, of actions. Actions take place during execution of the statement that performs them (except when explicitly stated otherwise). Segments (8.5.2) executed by a single *image* are totally ordered, and segments executed by separate *images* are partially ordered by *image control statements* (8.5.1).

2 If the program contains a Fortran *main program*, each *image* begins execution with the first executable construct of the *main program*. The execution of a *main program* or *subprogram* involves execution of the executable constructs within its *scoping unit*. When a Fortran procedure is invoked, the *specification expressions* within the *specification-part* of the invoked procedure, if any, are evaluated in a processor dependent order. Thereafter, execution proceeds to the first executable construct appearing within the *scoping unit* of the procedure after the invoked entry point. With the following exceptions, the effect of execution is as if the executable constructs are executed in the order in which they appear in the *main program* or *subprogram* until a *STOP*, *ERROR STOP*, *RETURN*, or *END* statement is executed.

- Execution of a branching statement (8.2) changes the execution sequence. These statements explicitly specify a new starting place for the execution sequence.
- *DO* constructs, *IF* constructs, *SELECT CASE* constructs, *SELECT RANK* constructs, and *SELECT TYPE* constructs contain an internal statement structure and execution of these constructs involves implicit internal transfer of control. See Clause 8 for the detailed semantics of each of these constructs.
- *BLOCK* constructs may contain *specification expressions*; see 8.1.4 for detailed semantics of this construct.
- *END=*, *ERR=*, and *EOR=* specifiers might result in a branch.
- Alternate returns might result in a branch.

2.3.6 Termination of execution

1 Termination of execution of a program is either normal termination or error termination. Normal termination occurs only when all *images* initiate normal termination and occurs in three steps: initiation, synchronization, and completion. In this case, all *images* synchronize execution at the second step so that no *image* starts the completion step until all *images* have finished the initiation step. Error termination occurs when any *image* initiates error termination. Once error termination has been initiated on an *image*, error termination is initiated on all *images* that have not already initiated error termination. Termination of execution of the program occurs when all *images* have terminated execution.

2 Normal termination of execution of an *image* is initiated when a *STOP* statement or *end-program-stmt* is executed. Normal termination of execution of an *image* also may be initiated during execution of a procedure defined by a *companion processor* (ISO/IEC 9899:2011 5.1.2.2.3 and 7.22.4.4). If normal termination of execution is initiated within a Fortran *program unit* and the program incorporates procedures defined by a *companion processor*, the process of execution termination shall include the effect of executing the C `exit()` function (ISO/IEC 9899:2011 7.22.4.4) during the completion step.

3 Error termination of execution of an *image* is initiated if an *ERROR STOP* statement is executed or as specified

1 elsewhere in this part of ISO/IEC 1539. When error termination on an [image](#) has been initiated, the processor
2 should initiate error termination on other [images](#) as quickly as possible.

3 4 If the processor supports the concept of a process exit status, it is recommended that error termination initiated
4 other than by an [ERROR STOP statement](#) supplies a processor-dependent nonzero value as the process exit
5 status.

NOTE 2.6

As well as in the circumstances specified in this part of ISO/IEC 1539, error termination might be initiated by means other than Fortran.

NOTE 2.7

If an [image](#) has initiated normal termination, its data remain available for possible reference or definition by other [images](#) that are still executing.

6 2.4 Data concepts

7 2.4.1 Type

8 1 A [type](#) is a named categorization of data that, together with its [type parameters](#), determines the set of values,
9 syntax for denoting these values, and the set of operations that interpret and manipulate the values. This central
10 concept is described in [4.1](#).

11 2 A [type](#) is either an [intrinsic type](#) or a [derived type](#).

12 2.4.1.1 Intrinsic type

13 1 The [intrinsic types](#) are integer, real, complex, character, and logical. The properties of [intrinsic types](#) are described
14 in [4.4](#).

15 2 All [intrinsic types](#) have a [kind type parameter](#) called KIND, which determines the representation method for the
16 specified type. The [intrinsic type](#) character also has a [length type parameter](#) called LEN, which determines the
17 length of the character string.

18 2.4.1.2 Derived type

19 1 [Derived types](#) may be parameterized. A scalar [object](#) of [derived type](#) is a [structure](#); assignment of structures
20 is defined intrinsically ([7.2.1.3](#)), but there are no [intrinsic](#) operations for structures. For each [derived type](#), a
21 [structure constructor](#) is available to create values ([4.5.10](#)). In addition, [objects](#) of [derived type](#) may be used as
22 procedure arguments and function results, and may appear in input/output lists. If additional operations are
23 needed for a [derived type](#), they shall be defined by procedures ([7.1.6](#)).

24 2 [Derived types](#) are described further in [4.5](#).

25 2.4.2 Data value

26 1 Each [intrinsic type](#) has associated with it a set of values that a datum of that type may take, depending on the
27 values of the type parameters. The values for each [intrinsic type](#) are described in [4.4](#). The values that [objects](#) of
28 a [derived type](#) may assume are determined by the type definition, type parameter values, and the sets of values
29 of its components.

2.4.3 Data entity

2.4.3.1 General

1 A **data entity** has a type and type parameters; it might have a data value (an exception is an undefined variable).
Every **data entity** has a **rank** and is thus either a scalar or an array.

2 A **data entity** that is the result of the execution of a **function reference** is called the function result.

2.4.3.2 Data object

1 A **data object** is either a constant, variable, or a **subobject** of a constant. The type and type parameters of a named **data object** may be specified explicitly (5.2) or implicitly (5.7).

2 **Subobjects** are portions of **data objects** that may be referenced and defined (variables only) independently of the other portions.

3 These include portions of arrays (array elements and array sections), portions of character strings (substrings), portions of complex **objects** (real and imaginary parts), and portions of **structures** (components). **Subobjects** are themselves **data objects**, but **subobjects** are referenced only by **object designators** or **intrinsic** functions. A **subobject** of a variable is a variable. **Subobjects** are described in Clause 6.

4 The following **objects** are referenced by a name:

- a named scalar (a scalar object);
- a named array (an array object).

5 The following **subobjects** are referenced by an **object designator**:

- an array element (a scalar subobject);
- an array section (an array subobject);
- a **complex part designator** (the real or imaginary part of a complex object);
- a structure component (a scalar or an array subobject);
- a substring (a scalar subobject).

2.4.3.2.1 Variable

1 A **variable** can have a value or be undefined; during execution of a program it can be defined and redefined.

2 A **local variable** of a **module**, **submodule**, **main program**, **subprogram**, or **BLOCK construct** is accessible only in that **scoping unit** or construct and in any contained **scoping units** and constructs.

NOTE 2.8

A **subobject** of a **local variable** is also a **local variable**.

A **local variable** cannot be in COMMON or have the **BIND attribute**, because **common blocks** and **variables** with the **BIND attribute** are global entities.

2.4.3.2.2 Constant

1 A constant is either a **named constant** or a **literal constant**.

2 Named constants are defined using the **PARAMETER attribute** (5.5.13, 5.6.11). The syntax of literal constants is described in 4.4.

2.4.3.2.3 Subobject of a constant

1 A **subobject** of a **constant** is a portion of a **constant**.

2 In an **object designator** for a **subobject** of a **constant**, the portion referenced may depend on the value of a **variable**.

NOTE 2.9

For example, given:

```
CHARACTER (LEN = 10), PARAMETER :: DIGITS = '0123456789'
CHARACTER (LEN = 1)           :: DIGIT
INTEGER :: I
...
DIGIT = DIGITS (I:I)
```

DIGITS is a [named constant](#) and DIGITS (I:I) designates a [subobject](#) of the [constant](#) DIGITS.

1 2.4.3.3 Expression

2 1 An expression (7.1) produces a [data entity](#) when evaluated. An expression represents either a [data object reference](#)
 3 or a computation; it is formed from operands, operators, and parentheses. The type, type parameters, value, and
 4 [rank](#) of an expression result are determined by the rules in Clause 7.

5 2.4.3.4 Function reference

6 1 A [function reference](#) produces a [data entity](#) when the function is executed during expression evaluation. The
 7 type, type parameters, and [rank](#) of a function result are determined by the [interface](#) of the function (12.3.3). The
 8 value of a function result is determined by execution of the function.

9 2.4.4 Definition of objects and pointers

10 1 When an [object](#) is given a valid value during program execution, it becomes [defined](#). This is often accomplished
 11 by execution of an [assignment](#) or [input](#) statement. When a variable does not have a predictable value, it is
 12 [undefined](#).

13 2 Similarly, when a pointer is associated with a [target](#) or nullified, its [pointer association](#) status becomes [defined](#).
 14 When the association status of a pointer is not predictable, its [pointer association](#) status is [undefined](#).

15 3 Clause 16 describes the ways in which variables become [defined](#) and [undefined](#) and the association status of
 16 pointers becomes [defined](#) and [undefined](#).

17 2.4.5 Reference

18 1 A [data object](#) is [referenced](#) when its value is required during execution. A procedure is [referenced](#) when it is
 19 executed.

20 2 The appearance of a [data object designator](#) or [procedure designator](#) as an [actual argument](#) does not constitute
 21 a [reference](#) to that [data object](#) or procedure unless such a [reference](#) is necessary to complete the specification of
 22 the [actual argument](#).

23 2.4.6 Array

24 1 An array may have up to fifteen dimensions, and any [extent](#) in any dimension. The [size](#) of an array is the total
 25 number of elements, which is equal to the product of the [extents](#). An array may have zero size. The [shape](#) of an
 26 array is determined by its [rank](#) and its [extent](#) in each dimension, and is represented as a rank-one array whose
 27 elements are the extents. All named arrays shall be declared, and the [rank](#) of a named array is specified in its
 28 declaration. The [rank](#) of a named array, once declared, is constant; the extents may be constant or may vary
 29 during execution.

30 2 Any [intrinsic](#) operation defined for scalar [objects](#) may be applied to [conformable objects](#). Such operations are
 31 performed [elementally](#) to produce a resultant array [conformable](#) with the array operands. If an [elemental](#) operation

1 is intrinsically pure or is implemented by a pure **elemental function** (12.8), the element operations may be
 2 performed simultaneously or in any order.

3 3 A rank-one array may be constructed from scalars and other arrays and may be reshaped into any allowable array
 4 shape (4.8).

5 4 Arrays may be of any type and are described further in 6.5.

6 **2.4.7 Coarray**

7 1 A **coarray** is a **data entity** that has nonzero **corank**; it can be directly referenced or defined by any **image**. It may
 8 be a scalar or an array.

9 2 For each **coarray** on an **image**, there is a corresponding **coarray** with the same type, type parameters, and **bounds**
 10 on every other **image**.

11 3 The set of corresponding **coarrays** on all **images** is arranged in a rectangular pattern. The dimensions of this
 12 pattern are the **codimensions**; the number of **codimensions** is the **corank**. The bounds for each **codimension** are
 13 the **cobounds**.

NOTE 2.10

If the total number of **images** is not a multiple of the product of the sizes of each but the rightmost of the **codimensions**, the rectangular pattern will be incomplete.

14 4 A **coarray** on any **image** can be accessed directly by using **cosubscripts**. On its own **image**, a **coarray** can also be
 15 accessed without use of **cosubscripts**.

16 5 A **subobject** of a **coarray** is a **coarray** if it does not have any **cosubscripts**, **vector subscripts**, **allocatable** component
 17 selection, or pointer component selection.

18 6 For a **coindexed object**, its **cosubscript** list determines the **image index** in the same way that a subscript list
 19 determines the subscript order value for an **array element** (6.5.3.2).

20 7 **Intrinsic** procedures are provided for mapping between an **image index** and a list of **cosubscripts**.

NOTE 2.11

The mechanism for an **image** to reference and define a **coarray** on another **image** might vary according to the hardware. On a shared-memory machine, a **coarray** on an **image** and the corresponding **coarrays** on other **images** could be implemented as a sequence of arrays with evenly spaced starting addresses. On a distributed-memory machine with separate physical memory for each **image**, a processor might store a **coarray** at the same virtual address in each physical memory.

NOTE 2.12

Except in contexts where **coindexed objects** are disallowed, accessing a **coarray** on its own **image** by using a set of **cosubscripts** that specify that **image** has the same effect as accessing it without **cosubscripts**. In particular, the segment ordering rules (8.5.2) apply whether or not **cosubscripts** are used to access the **coarray**.

21 **2.4.8 Pointer**

22 1 A **pointer** has an association status which is either associated, **disassociated**, or undefined (16.5.2.2).

23 2 A **pointer** that is not associated shall not be referenced or defined.

24 3 If a **data pointer** is an **array**, the **rank** is declared, but the **bounds** are determined when it is associated with a
 25 **target**.

1 2.5.5 Intrinsic

2 1 All [intrinsic](#) types, procedures, assignments, and operators may be used in any [scoping unit](#) without further
3 definition or specification. [Intrinsic](#) modules ([13.9](#), [14](#), [15.2](#)) may be accessed by [use association](#).

4 2.5.6 Operator

5 1 This part of ISO/IEC 1539 specifies a number of [intrinsic](#) operators (e.g., the arithmetic operators +, -, *, /,
6 and ** with numeric operands and the logical operators [.AND.](#), [.OR.](#), etc. with logical operands). Additional
7 operators may be defined within a program ([4.5.5](#), [12.4.3.5](#)).

8 2.5.7 Companion processors

9 1 A [processor](#) has one or more [companion processors](#). A [companion processor](#) may be a mechanism that references
10 and defines such entities by a means other than Fortran ([12.6.3](#)), it may be the [Fortran processor](#) itself, or it may
11 be another [Fortran processor](#). If there is more than one [companion processor](#), the means by which the [Fortran](#)
12 [processor](#) selects among them are [processor dependent](#).

13 2 If a [procedure](#) is defined by means of a [companion processor](#) that is not the [Fortran processor](#) itself, this part of
14 ISO/IEC 1539 refers to the C function that defines the [procedure](#), although the [procedure](#) need not be defined
15 by means of the C programming language.

NOTE 2.14

A [companion processor](#) might or might not be a mechanism that conforms to the requirements of ISO/IEC 9899:2011.

For example, a [processor](#) might allow a [procedure](#) defined by some language other than Fortran or C to be invoked if it can be described by a C prototype as defined in 6.7.6.3 of ISO/IEC 9899:2011.

3 Lexical tokens and source form

3.1 Processor character set

3.1.1 Characters

1 The processor character set is processor dependent. Each character in a processor character set is either a control character or a graphic character. The set of graphic characters is further divided into letters (3.1.2), digits (3.1.3), underscore (3.1.4), special characters (3.1.5), and other characters (3.1.6).

2 The letters, digits, underscore, and special characters make up the Fortran character set. Together, the set of letters, digits, and underscore define the syntax class *alphanumeric-character*.

```
R301  alphanumeric-character    is  letter
                                     or  digit
                                     or  underscore
```

3 Except for the currency symbol, the graphics used for the characters shall be as given in 3.1.2, 3.1.3, 3.1.4, and 3.1.5. However, the style of any graphic is not specified.

3.1.2 Letters

1 The twenty-six letters are:

```
2  A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
```

3 The set of letters defines the syntactic class *letter*. The processor character set shall include lower-case and upper-case letters. A lower-case letter is equivalent to the corresponding upper-case letter in *program units* except in a *character context* (1.3.22).

NOTE 3.1

The following statements are equivalent:

```
CALL BIG_COMPLEX_OPERATION (NDATE)
call big_complex_operation (ndate)
Call Big_Complex_Operation (NDate)
```

3.1.3 Digits

1 The ten digits are:

```
2  0 1 2 3 4 5 6 7 8 9
```

3 The ten digits define the syntactic class *digit*.

3.1.4 Underscore

```
R302  underscore                is  _
```

3.1.5 Special characters

1 The special characters are shown in Table 3.1.

Table 3.1: Special characters

Character	Name of character	Character	Name of character
	Blank	;	Semicolon
=	Equals	!	Exclamation point
+	Plus	"	Quotation mark or quote
-	Minus	%	Percent
*	Asterisk	&	Ampersand
/	Slash	~	Tilde
\	Backslash	<	Less than
(Left parenthesis	>	Greater than
)	Right parenthesis	?	Question mark
[Left square bracket	'	Apostrophe
]	Right square bracket	`	Grave accent
{	Left curly bracket	^	Circumflex accent
}	Right curly bracket		Vertical line
,	Comma	\$	Currency symbol
.	Decimal point or period	#	Number sign
:	Colon	@	Commercial at

1 2 Some of the special characters are used for operator symbols, bracketing, and various forms of separating and
2 delimiting other lexical tokens.

3 3.1.6 Other characters

4 1 Additional characters may be representable in the processor, but may appear only in comments (3.3.2.3, 3.3.3.2),
5 character constants (4.4.4), input/output records (9.2.2), and character string edit descriptors (10.3.2).

6 3.2 Low-level syntax

7 3.2.1 Tokens

8 1 The low-level syntax describes the fundamental lexical tokens of a [program unit](#). A [lexical token](#) is a keyword,
9 name, literal constant other than a complex literal constant, operator, statement label, delimiter, comma, =, =>
10 :, ::, ; or %.

11 3.2.2 Names

12 1 [Names](#) are used for various entities such as [variables](#), [program units](#), [dummy arguments](#), [named constants](#), and
13 derived types.

14 R303 *name* is *letter* [*alphanumeric-character*] ...

15 C301 (R303) The maximum length of a *name* is 63 characters.

NOTE 3.2

Examples of names:

```
A1
NAME_LENGTH      (single underscore)
S_P_R_E_A_D__O_U_T (two consecutive underscores)
TRAILER_        (trailing underscore)
```

NOTE 3.3

The word “name” always denotes this particular syntactic form. The word “identifier” is used where entities can be identified by other syntactic forms or by values; its particular meaning depends on the context in which it is used.

1 **3.2.3 Constants**

- 2 R304 *constant* is *literal-constant*
 3 or *named-constant*
- 4 R305 *literal-constant* is *int-literal-constant*
 5 or *real-literal-constant*
 6 or *complex-literal-constant*
 7 or *logical-literal-constant*
 8 or *char-literal-constant*
 9 or *boz-literal-constant*
- 10 R306 *named-constant* is *name*
- 11 R307 *int-constant* is *constant*
- 12 C302 (R307) *int-constant* shall be of type integer.

13 **3.2.4 Operators**

- 14 R308 *intrinsic-operator* is *power-op*
 15 or *mult-op*
 16 or *add-op*
 17 or *concat-op*
 18 or *rel-op*
 19 or *not-op*
 20 or *and-op*
 21 or *or-op*
 22 or *equiv-op*
- 23 R707 *power-op* is **
- 24 R708 *mult-op* is *
 25 or /
- 26 R709 *add-op* is +
 27 or -
- 28 R711 *concat-op* is //
- 29 R713 *rel-op* is .EQ.
 30 or .NE.
 31 or .LT.
 32 or .LE.
 33 or .GT.
 34 or .GE.
 35 or ==
 36 or /=
 37 or <
 38 or <=
 39 or >
 40 or >=

1	R718	<i>not-op</i>	is	.NOT.
2	R719	<i>and-op</i>	is	.AND.
3	R720	<i>or-op</i>	is	.OR.
4	R721	<i>equiv-op</i>	is	.EQV.
5			or	.NEQV.
6	R309	<i>defined-operator</i>	is	<i>defined-unary-op</i>
7			or	<i>defined-binary-op</i>
8			or	<i>extended-intrinsic-op</i>
9	R703	<i>defined-unary-op</i>	is	. letter [letter]
10	R723	<i>defined-binary-op</i>	is	. letter [letter]
11	R310	<i>extended-intrinsic-op</i>	is	<i>intrinsic-operator</i>

3.2.5 Statement labels

1 A **statement label** provides a means of referring to an individual statement.

R311 *label* is *digit [digit [digit [digit [digit]]]]]*

C303 (R311) At least one digit in a *label* shall be nonzero.

2 If a statement is labeled, the statement shall contain a nonblank character. The same statement label shall not be given to more than one statement in its scope. Leading zeros are not significant in distinguishing between statement labels. There are 99999 possible unique statement labels and a processor shall accept any of them as a statement label. However, a processor may have a limit on the total number of unique statement labels in one **program unit**.

NOTE 3.4

For example:

99999

10

010

are all statement labels. The last two are equivalent.

3 Any statement that is not part of another statement, and that is not preceded by a semicolon in fixed form, may begin with a statement label, but the labels are used only in the following ways.

- The label on a **branch target statement** (8.2) is used to identify that statement as the possible destination of a branch.
- The label on a **FORMAT statement** (10.2.1) is used to identify that statement as the format specification for a **data transfer statement** (9.6).
- In some forms of the **DO construct** (8.1.6), the terminal statement of the construct is identified by a label.

3.2.6 Delimiters

1 A **lexical token** that is a delimiter is a (,), /, [,], (/, or /).

3.3 Source form

3.3.1 Program units, statements, and lines

- 1 A Fortran **program unit** is a sequence of one or more **lines**, organized as Fortran statements, comments, and **INCLUDE lines**. A **line** is a sequence of zero or more characters. **Lines** following a **program unit END statement** are not part of that **program unit**. A Fortran **statement** is a sequence of one or more complete or partial **lines**.
- 2 A comment may contain any character that may occur in any **character context**.
- 3 There are two source forms. Subclause 3.3.2 applies only to free form source. Subclause 3.3.3 applies only to fixed source form. Free form and fixed form shall not be mixed in the same program unit. The means for specifying the source form of a **program unit** are processor dependent.

3.3.2 Free source form

3.3.2.1 Free form line length

- 1 In free source form there are no restrictions on where a statement (or portion of a statement) may appear within a **line**. A **line** may contain zero characters. If a **line** consists entirely of characters of default kind (4.4.4), it may contain at most 132 characters. If a **line** contains any character that is not of default kind, the maximum number of characters allowed on the **line** is processor dependent.

3.3.2.2 Blank characters in free form

- 1 In free source form blank characters shall not appear within lexical tokens other than in a **character context** or in a format specification. Blanks may be inserted freely between tokens to improve readability; for example, blanks may occur between the tokens that form a complex literal constant. A sequence of blank characters outside of a **character context** is equivalent to a single blank character.
- 2 A blank shall be used to separate names, constants, or labels from adjacent keywords, names, constants, or labels.

NOTE 3.5

For example, the blanks after REAL, READ, 30, and DO are required in the following:

```
REAL X
READ 10
30 DO K=1,3
```

- 3 One or more blanks shall be used to separate adjacent keywords except in the following cases, where blanks are optional:

Table 3.2: Adjacent keywords where separating blanks are optional

BLOCK DATA	END ENUM	END SELECT
DOUBLE PRECISION	END FILE	END SUBMODULE
ELSE IF	END FORALL	END SUBROUTINE
ELSE WHERE	END FUNCTION	END TYPE
END ASSOCIATE	END IF	END WHERE
END BLOCK	END INTERFACE	GO TO
END BLOCK DATA	END MODULE	IN OUT
END CRITICAL	END PROCEDURE	SELECT CASE
END DO	END PROGRAM	SELECT TYPE

1 3.3.2.3 Free form commentary

- 2 1 The character “!” initiates a comment except where it appears within a [character context](#). The comment extends
3 to the end of the [line](#). If the first nonblank character on a [line](#) is an “!”, the [line](#) is a comment line. [Lines](#)
4 containing only blanks or containing no characters are also comment lines. Comments may appear anywhere in
5 a [program unit](#) and may precede the first statement of a [program unit](#) or may follow the last statement of a
6 [program unit](#). Comments have no effect on the interpretation of the [program unit](#).

NOTE 3.6

This part of ISO/IEC 1539 does not restrict the number of consecutive comment lines.

7 3.3.2.4 Free form statement continuation

- 8 1 The character “&” is used to indicate that the statement is continued on the next [line](#) that is not a comment
9 line. Comment lines cannot be continued; an “&” in a comment has no effect. Comments may occur within a
10 continued statement. When used for continuation, the “&” is not part of the statement. No [line](#) shall contain
11 a single “&” as the only nonblank character or as the only nonblank character before an “!” that initiates a
12 comment.
- 13 2 If a non[character context](#) is to be continued, an “&” shall be the last nonblank character on the [line](#), or the last
14 nonblank character before an “!”. There shall be a later [line](#) that is not a comment; the statement is continued
15 on the next such [line](#). If the first nonblank character on that [line](#) is an “&”, the statement continues at the next
16 character position following that “&”; otherwise, it continues with the first character position of that [line](#).
- 17 3 If a lexical token is split across the end of a [line](#), the first nonblank character on the first following noncomment
18 [line](#) shall be an “&” immediately followed by the successive characters of the split token.
- 19 4 If a [character context](#) is to be continued, an “&” shall be the last nonblank character on the [line](#) and shall not
20 be followed by commentary. There shall be a later [line](#) that is not a comment; an “&” shall be the first nonblank
21 character on the next such [line](#) and the statement continues with the next character following that “&”.

22 3.3.2.5 Free form statement termination

- 23 1 If a statement is not continued, a comment or the end of the [line](#) terminates the statement.
- 24 2 A statement may alternatively be terminated by a “;” character that appears other than in a [character context](#)
25 or in a comment. The “;” is not part of the statement. After a “;” terminator, another statement may appear
26 on the same [line](#), or begin on that [line](#) and be continued. A sequence consisting only of zero or more blanks and
27 one or more “;” terminators, in any order, is equivalent to a single “;” terminator.

28 3.3.2.6 Free form statements

- 29 1 A label may precede any statement not forming part of another statement.

NOTE 3.7

No Fortran statement begins with a digit.

- 30 2 A statement shall not have more than 255 continuation [lines](#).

31 3.3.3 Fixed source form

32 3.3.3.1 General

- 33 1 In fixed source form, there are restrictions on where a statement may appear within a [line](#). If a source [line](#) contains only characters
34 of default kind, it shall contain exactly 72 characters; otherwise, its maximum number of characters is processor dependent.
- 35 2 Except in a [character context](#), blanks are insignificant and may be used freely throughout the program.

1 3.3.3.2 Fixed form commentary

2 1 The character “!” initiates a comment except where it appears within a [character context](#) or in character position 6. The comment
3 extends to the end of the [line](#). If the first nonblank character on a [line](#) is an “!” in any character position other than character
4 position 6, the [line](#) is a comment line. [Lines](#) beginning with a “C” or “*” in character position 1 and lines containing only blanks are
5 also comment lines. Comments may appear anywhere in a [program unit](#) and may precede the first statement of the [program unit](#) or
6 may follow the last statement of a [program unit](#). Comments have no effect on the interpretation of the [program unit](#).

NOTE 3.8

This part of ISO/IEC 1539 does not restrict the number of consecutive comment lines.

7 3.3.3.3 Fixed form statement continuation

8 1 Except within commentary, character position 6 is used to indicate continuation. If character position 6 contains a blank or zero, the
9 [line](#) is the initial [line](#) of a new statement, which begins in character position 7. If character position 6 contains any character other
10 than blank or zero, character positions 7–72 of the [line](#) constitute a continuation of the preceding noncomment [line](#).

NOTE 3.9

An “!” or “;” in character position 6 is interpreted as a continuation indicator unless it appears within commentary indicated
by a “C” or “*” in character position 1 or by an “!” in character positions 1–5.

11 2 Comment lines cannot be continued. Comment lines may occur within a continued statement.

12 3.3.3.4 Fixed form statement termination

13 1 If a statement is not continued, a comment or the end of the [line](#) terminates the statement.

14 2 A statement may alternatively be terminated by a “;” character that appears other than in a [character context](#), in a comment, or in
15 character position 6. The “;” is not part of the statement. After a “;” terminator, another statement may begin on the same [line](#), or
16 begin on that [line](#) and be continued. A “;” shall not appear as the first nonblank character on an initial [line](#). A sequence consisting
17 only of zero or more blanks and one or more “;” terminators, in any order, is equivalent to a single “;” terminator.

18 3.3.3.5 Fixed form statements

19 1 A label, if it appears, shall occur in character positions 1 through 5 of the first [line](#) of a statement; otherwise, positions 1 through
20 5 shall be blank. Blanks may appear anywhere within a label. A statement following a “;” on the same [line](#) shall not be labeled.
21 Character positions 1 through 5 of any continuation [lines](#) shall be blank. A statement shall not have more than 255 continuation
22 [lines](#). The [program unit END statement](#) shall not be continued. A statement whose initial [line](#) appears to be a [program unit END](#)
23 [statement](#) shall not be continued.

24 3.4 Including source text

25 1 Additional text may be incorporated into the source text of a [program unit](#) during processing. This is accomplished
26 with the `INCLUDE`, which has the form

27 2 `INCLUDE char-literal-constant`

28 3 The *char-literal-constant* shall not have a kind type parameter value that is a *named-constant*.

29 4 An `INCLUDE` line is not a Fortran statement.

30 5 An `INCLUDE` line shall appear on a single source [line](#) where a statement may appear; it shall be the only
31 nonblank text on this [line](#) other than an optional trailing comment. Thus, a statement label is not allowed.

32 6 The effect of the `INCLUDE` line is as if the referenced source text physically replaced the `INCLUDE` line prior
33 to program processing. Included text may contain any source text, including additional `INCLUDE` lines; such
34 nested `INCLUDE` lines are similarly replaced with the specified source text. The maximum depth of nesting of
35 any nested `INCLUDE` lines is processor dependent. Inclusion of the source text referenced by an `INCLUDE` line
36 shall not, at any level of nesting, result in inclusion of the same source text.

- 1 7 When an INCLUDE line is resolved, the first included statement [line](#) shall not be a continuation [line](#) and the last
2 included statement [line](#) shall not be continued.
- 3 8 The interpretation of *char-literal-constant* is processor dependent. An example of a possible valid interpretation
4 is that *char-literal-constant* is the name of a file that contains the source text to be included.

NOTE 3.10

In some circumstances, for example where source code is maintained in an INCLUDE file for use in programs whose source form might be either fixed or free, observing the following rules allows the code to be used with either source form.

- Confine statement labels to character positions 1 to 5 and statements to character positions 7 to 72.
- Treat blanks as being significant.
- Use only the exclamation mark (!) to indicate a comment, but do not start the comment in character position 6.
- For continued statements, place an ampersand (&) in both character position 73 of a continued [line](#) and character position 6 of a continuation [line](#).

4 Types

4.1 Characteristics of types

4.1.1 The concept of type

1 Fortran provides an abstract means whereby data can be categorized without relying on a particular physical representation. This abstract means is the concept of type.

2 A type has a name, a set of valid values, a means to denote such values (constants), and a set of operations to manipulate the values.

4.1.2 Type classification

1 A type is either an [intrinsic type](#) or a [derived type](#).

2 This part of ISO/IEC 1539 defines five intrinsic types: integer, real, complex, character, and logical.

3 A derived type is one that is defined by a derived-type definition ([4.5.2](#)) or by an intrinsic module. It shall be used only where it is accessible ([4.5.2.2](#)). An intrinsic type is always accessible.

4.1.3 Set of values

1 For each type, there is a set of valid values. The set of valid values for logical is completely determined by this part of ISO/IEC 1539. The sets of valid values for integer, character, and real are processor dependent. The set of valid values for complex consists of the set of all the combinations of the values of the individual components. The set of valid values for a derived type is as defined in [4.5.8](#).

4.1.4 Constants

1 The syntax for denoting a value indicates the type, type parameters, and the particular value.

2 The syntax for literal constants of each intrinsic type is specified in [4.4](#).

3 A [structure constructor](#) ([4.5.10](#)) that is a [constant expression](#) ([7.1.12](#)) denotes a scalar constant value of derived type. An array constructor ([4.8](#)) that is a [constant expression](#) denotes a constant array value of intrinsic or derived type.

4 A constant value can be named ([5.5.13](#), [5.6.11](#)).

4.1.5 Operations

1 For each of the intrinsic types, a set of operations and corresponding operators is defined intrinsically. These are described in [Clause 7](#). The intrinsic set can be augmented with operations and operators defined by functions with the [OPERATOR](#) interface ([12.4.3.2](#)). Operator definitions are described in [Clauses 7](#) and [12](#).

2 For derived types, there are no intrinsic operations. Operations on derived types can be defined by the program ([4.5.11](#)).

4.2 Type parameters

- 1 A type might be parameterized. In this case, the set of values, the syntax for denoting the values, and the set of operations on the values of the type depend on the values of the parameters.
- 2 A [type parameter](#) is either a [kind type parameter](#) or a [length type parameter](#). All type parameters are of type integer. A [kind type parameter](#) participates in generic resolution ([12.5.5.2](#)), but a [length type parameter](#) does not.
- 3 Each intrinsic type has a [kind type parameter](#) named KIND. The intrinsic character type has a [length type parameter](#) named LEN. A derived type can have type parameters.
- 4 A type parameter value may be specified by a type specification ([4.4](#), [4.5.9](#)).
- R401 *type-param-value* is *scalar-int-expr*
 or *
 or :
- C401 (R401) The *type-param-value* for a kind type parameter shall be a [constant expression](#).
- C402 (R401) A colon shall not be used as a *type-param-value* except in the declaration of an entity or component that has the [POINTER](#) or [ALLOCATABLE](#) attribute.
- 5 A colon as a *type-param-value* specifies a [deferred type parameter](#).
- 6 The values of the [deferred type parameters](#) of an object are determined by successful execution of an [ALLOCATE statement](#) ([6.7.1](#)), execution of an [intrinsic assignment statement](#) ([7.2.1.3](#)), execution of a [pointer assignment statement](#) ([7.2.2](#)), or by [argument association](#) ([12.5.2](#)).

NOTE 4.1

[Deferred type parameters](#) of functions, including function procedure pointers, have no values. Instead, they indicate that those [type parameters](#) of the function result will be determined by execution of the function, if it returns an allocated [allocatable](#) result or an associated pointer result.

- 7 An asterisk as a *type-param-value* specifies that a [length type parameter](#) is an [assumed type parameter](#). It is used for a [dummy argument](#) to assume the type parameter value from the [effective argument](#), for an [associate name](#) in a [SELECT TYPE construct](#) to assume the type parameter value from the corresponding selector, and for a [named constant](#) of type character to assume the character length from the *constant-expr*.

NOTE 4.2

The value of a [kind type parameter](#) is always known at compile time. Some parameterizations that involve multiple representation forms need to be distinguished at compile time for practical implementation and performance. Examples include the multiple precisions of the intrinsic real type and the possible multiple character sets of the intrinsic character type.

The adjective “length” is used for type parameters other than kind type parameters because they often specify a length, as for intrinsic character type. However, they can be used for other purposes. The important difference from kind type parameters is that their values need not be known at compile time and might change during execution.

4.3 Types, type specifiers, and values

4.3.1 Relationship of types and values to objects

- 1 The name of a type serves as a type specifier and may be used to declare objects of that type. A declaration specifies the type of a named object. A data object may be declared explicitly or implicitly. A data object has

1 [attributes](#) in addition to its type. Clause 5 describes the way in which a data object is declared and how its type
2 and other attributes are specified.

3 2 Scalar data of any intrinsic or derived type may be shaped in a rectangular pattern to compose an array of the
4 same type and type parameters. An array object has a type and type parameters just as a scalar object does.

5 3 A variable is a data object. The type and type parameters of a variable determine which values that variable
6 may take. Assignment (7.2) provides one means of defining or redefining the value of a variable of any type.

7 4 The type of a variable determines the operations that may be used to manipulate the variable.

8 4.3.2 Type specifiers and type compatibility

9 4.3.2.1 Type specifier syntax

10 1 A type specifier specifies a type and type parameter values. It is either a [type-spec](#) or a [declaration-type-spec](#).

11 R402 *type-spec* is [intrinsic-type-spec](#)
12 or [derived-type-spec](#)

13 C403 (R402) The [derived-type-spec](#) shall not specify an [abstract type](#) (4.5.7).

14 R403 *declaration-type-spec* is [intrinsic-type-spec](#)
15 or TYPE ([intrinsic-type-spec](#))
16 or TYPE ([derived-type-spec](#))
17 or CLASS ([derived-type-spec](#))
18 or CLASS (*)
19 or TYPE (*)

20 C404 (R403) In a [declaration-type-spec](#), every [type-param-value](#) that is not a colon or an asterisk shall be a
21 [specification-expr](#).

22 C405 (R403) In a [declaration-type-spec](#) that uses the CLASS keyword, [derived-type-spec](#) shall specify an [ex-](#)
23 [tensible type](#) (4.5.7).

24 C406 (R403) TYPE([derived-type-spec](#)) shall not specify an [abstract type](#) (4.5.7).

25 C407 (R402) In TYPE([intrinsic-type-spec](#)) the [intrinsic-type-spec](#) shall not end with a comma.

26 C408 An entity declared with the CLASS keyword shall be a [dummy argument](#) or have the [ALLOCATABLE](#)
27 or [POINTER attribute](#).

28 2 An [intrinsic-type-spec](#) specifies the named intrinsic type and its type parameter values. A [derived-type-spec](#)
29 specifies the named derived type and its type parameter values.

NOTE 4.3

A [type-spec](#) is used in an array constructor, a [SELECT TYPE construct](#), or an [ALLOCATE statement](#).
Elsewhere, a [declaration-type-spec](#) is used.

30 4.3.2.2 TYPE type specifier

31 1 A TYPE type specifier is used to declare entities that are [assumed-type](#), or of an intrinsic or derived type.

32 2 A [derived-type-spec](#) in a TYPE type specifier in a [type declaration statement](#) shall specify a previously defined
33 derived type. If the data entity is a function result, the derived type may be specified in the [FUNCTION](#)
34 [statement](#) provided the derived type is defined within the body of the function or is accessible there by use or
35 [host](#) association. If the derived type is specified in the [FUNCTION statement](#) and is defined within the body
36 of the function, it is as if the [function result](#) were declared with that derived type immediately following the
37 [derived-type-def](#) of the specified derived type.

- 1 3 An entity that is declared using the TYPE(*) type specifier is **assumed-type** and is an **unlimited polymorphic**
 2 entity. Its **dynamic type** and **type parameters** are assumed from its **effective argument**.
- 3 C409 An **assumed-type** entity shall be a **dummy data object** that does not have the **ALLOCATABLE**, **CODI-**
 4 **MENSION**, **INTENT (OUT)**, **POINTER**, or **VALUE** attribute and is not an **explicit-shape** array.
- 5 C410 An **assumed-type** variable name shall not appear in a designator or expression except as an **actual**
 6 **argument** corresponding to a **dummy argument** that is **assumed-type**, or as the first argument to the
 7 **intrinsic** function **IS_CONTIGUOUS**, **LBOUND**, **PRESENT**, **RANK**, **SHAPE**, **SIZE**, or **UBOUND**, or
 8 the function **C_LOC** from the intrinsic module **ISO_C_BINDING**.
- 9 C411 An **assumed-type actual argument** that corresponds to an **assumed-rank dummy argument** shall be
 10 **assumed-shape** or **assumed-rank**.

11 4.3.2.3 CLASS type specifier

- 12 1 The **CLASS** type specifier is used to declare **polymorphic** entities. A **polymorphic** entity is a data entity that is
 13 able to be of differing **dynamic types** during program execution.
- 14 2 The **declared type** of a **polymorphic** entity is the specified type if the **CLASS** type specifier contains a type name.
- 15 3 An entity declared with the **CLASS(*)** specifier is an **unlimited polymorphic** entity. An **unlimited polymorphic**
 16 entity is not declared to have a type. It is not considered to have the same **declared type** as any other entity,
 17 including another **unlimited polymorphic** entity.
- 18 4 A nonpolymorphic entity is **type compatible** only with entities of the same **declared type**. A **polymorphic** entity
 19 that is not an **unlimited polymorphic** entity is **type compatible** with entities of the same **declared type** or any of
 20 its **extensions**. Even though an **unlimited polymorphic** entity is not considered to have a **declared type**, it is **type**
 21 **compatible** with all entities. An entity is **type compatible** with a type if it is **type compatible** with entities of that
 22 type.

NOTE 4.4

Given

```

TYPE TROOT
...
TYPE, EXTENDS(TROOT) :: TEXTENDED
...
CLASS(TROOT) A
CLASS(TEXTENDED) B
...

```

A is **type compatible** with B but B is not **type compatible** with A.

- 23 5 A **polymorphic allocatable** object may be allocated to be of any type with which it is **type compatible**. A
 24 **polymorphic** pointer or **dummy argument** may, during program execution, be associated with objects with which
 25 it is **type compatible**.
- 26 6 The **dynamic type** of an allocated **allocatable polymorphic** object is the type with which it was allocated. The
 27 **dynamic type** of an associated **polymorphic** pointer is the **dynamic type** of its **target**. The **dynamic type** of a
 28 nonallocatable nonpointer **polymorphic dummy argument** is the **dynamic type** of its **effective argument**. The
 29 **dynamic type** of an unallocated **allocatable** object or a **disassociated** pointer is the same as its **declared type**. The
 30 **dynamic type** of an entity identified by an **associate name** (8.1.3) is the **dynamic type** of the selector with which
 31 it is associated. The **dynamic type** of an object that is not **polymorphic** is its **declared type**.

4.4 Intrinsic types

4.4.1 Classification and specification

1 Each intrinsic type is classified as a [numeric type](#) or a nonnumeric type. The [numeric types](#) are integer, real, and complex. The nonnumeric intrinsic types are character and logical.

2 Each intrinsic type has a [kind type parameter](#) named KIND; this [type parameter](#) is of type integer with default kind.

R404 *intrinsic-type-spec* **is** *integer-type-spec*
 or REAL [*kind-selector*]
 or DOUBLE PRECISION
 or COMPLEX [*kind-selector*]
 or CHARACTER [*char-selector*]
 or LOGICAL [*kind-selector*]

R405 *integer-type-spec* **is** INTEGER [*kind-selector*]

R406 *kind-selector* **is** ([KIND =] *scalar-int-constant-expr*)

C412 (R406) The value of *scalar-int-constant-expr* shall be nonnegative and shall specify a representation method that exists on the processor.

4.4.2 Intrinsic operations on intrinsic types

1 Intrinsic numeric operations are defined as specified in [7.1.5.2.1](#) for the numeric intrinsic types. Relational intrinsic operations are defined as specified in [7.1.5.5](#) for numeric and character intrinsic types. The intrinsic concatenation operation is defined as specified in [7.1.5.3](#) for the character type. Logical intrinsic operations are defined as specified in [7.1.5.4](#) for the logical type.

4.4.3 Numeric intrinsic types

4.4.3.1 Integer type

1 The set of values for the integer type is a subset of the mathematical integers. The processor shall provide one or more representation methods that define sets of values for data of type integer. Each such method is characterized by a value for the [kind type parameter](#) KIND. The [kind type parameter](#) of a representation method is returned by the intrinsic function [KIND](#) ([13.8.100](#)). The decimal exponent range of a representation method is returned by the intrinsic function [RANGE](#) ([13.8.150](#)). The intrinsic function [SELECTED_INT_KIND](#) ([13.8.161](#)) returns a kind value based on a specified decimal exponent range requirement. The integer type includes a zero value, which is considered to be neither negative nor positive. The value of a signed integer zero is the same as the value of an unsigned integer zero.

2 The processor shall provide at least one representation method with a decimal exponent range greater than or equal to 18.

3 The type specifier for the integer type uses the keyword INTEGER.

4 The keyword INTEGER with no [kind-selector](#) specifies type integer with default kind; the [kind type parameter](#) value is equal to [KIND](#) (0). The decimal exponent range of default integer shall be at least 5.

5 Any integer value may be represented as a [signed-int-literal-constant](#).

R407 *signed-int-literal-constant* **is** [*sign*] *int-literal-constant*

R408 *int-literal-constant* **is** *digit-string* [*kind-param*]

R409 *kind-param* **is** *digit-string*

1 **or** *scalar-int-constant-name*

2 R410 *signed-digit-string* **is** [*sign*] *digit-string*

3 R411 *digit-string* **is** *digit* [*digit*] ...

4 R412 *sign* **is** +

5 **or** -

6 C413 (R409) A *scalar-int-constant-name* shall be a **named constant** of type integer.

7 C414 (R409) The value of *kind-param* shall be nonnegative.

8 C415 (R408) The value of *kind-param* shall specify a representation method that exists on the processor.

9 6 The optional **kind type parameter** following *digit-string* specifies the **kind type parameter** of the integer constant;
10 if it is does not appear, the constant is default integer.

11 7 An integer constant is interpreted as a decimal value.

NOTE 4.5

Examples of signed integer literal constants are:

```
473
+56
-101
21_2
21_SHORT
1976354279568241_8
```

where SHORT is a scalar integer **named constant**.

4.4.3.2 Real type

13 1 The real type has values that approximate the mathematical real numbers. The processor shall provide two
14 or more approximation methods that define sets of values for data of type real. Each such method has a
15 representation method and is characterized by a value for the **kind type parameter** KIND. The **kind type parameter**
16 of an approximation method is returned by the intrinsic function **KIND** (13.8.100).

17 2 The decimal precision, decimal exponent range, and radix of an approximation method are returned by the
18 intrinsic functions **PRECISION** (13.8.143), **RADIX** (13.8.146) and **RANGE** (13.8.150). The intrinsic function
19 **SELECTED_REAL_KIND** (13.8.162) returns a kind value based on specified precision, range, and radix re-
20 quirements.

NOTE 4.6

See C.1.1 for remarks concerning selection of approximation methods.

21 3 The real type includes a zero value. Processors that distinguish between positive and negative zeros shall treat
22 them as mathematically equivalent

- 23 • in all intrinsic relational operations, and
- 24 • as **actual arguments** to intrinsic procedures other than those for which it is explicitly specified that negative
25 zero is distinguished.

NOTE 4.7

On a processor that distinguishes between 0.0 and -0.0,

NOTE 4.7 (cont.)

```
( X >= 0.0 )
```

evaluates to true if $X = 0.0$ or if $X = -0.0$,

```
( X < 0.0 )
```

evaluates to false for $X = -0.0$.

In order to distinguish between 0.0 and -0.0 , a program can use the intrinsic function `SIGN`. `SIGN(1.0,X)` will return -1.0 if $X < 0.0$ or if the processor distinguishes between 0.0 and -0.0 and X has the value -0.0 .

- 1 4 The type specifier for the real type uses the keyword `REAL`. The keyword `DOUBLE PRECISION` is an alternative
2 specifier for one kind of real type.
- 3 5 If the type keyword `REAL` is used without a [kind type parameter](#), the real type with default real kind is specified
4 and the kind value is `KIND` (0.0). The type specifier `DOUBLE PRECISION` specifies type real with double
5 precision kind; the kind value is `KIND` (0.0D0). The decimal precision of the double precision real approximation
6 method shall be greater than that of the default real method.
- 7 6 The decimal precision of double precision real shall be at least 10, and its decimal exponent range shall be at
8 least 37. It is recommended that the decimal precision of default real be at least 6, and that its decimal exponent
9 range be at least 37.
- 10 R413 *signed-real-literal-constant* is [*sign*] *real-literal-constant*
- 11 R414 *real-literal-constant* is *significand* [*exponent-letter exponent*] [*__ kind-param*]
12 or *digit-string exponent-letter exponent* [*__ kind-param*]
- 13 R415 *significand* is *digit-string* . [*digit-string*]
14 or . *digit-string*
- 15 R416 *exponent-letter* is E
16 or D
- 17 R417 *exponent* is *signed-digit-string*
- 18 C416 (R414) If both *kind-param* and *exponent-letter* appear, *exponent-letter* shall be E.
- 19 C417 (R414) The value of *kind-param* shall specify an approximation method that exists on the processor.
- 20 7 A real literal constant without a [kind type parameter](#) is a default real constant if it is without an exponent part
21 or has exponent letter E, and is a double precision real constant if it has exponent letter D. A real literal constant
22 written with a [kind type parameter](#) is a real constant with the specified [kind type parameter](#).
- 23 8 The exponent represents the power of ten scaling to be applied to the significand or digit string. The meaning of
24 these constants is as in decimal scientific notation.
- 25 9 The significand may be written with more digits than a processor will use to approximate the value of the constant.
26

NOTE 4.8

Examples of signed real literal constants are:

```
-12.78
+1.6E3
2.1
-16.E4_8
```

NOTE 4.8 (cont.)

```

0.45D-4
10.93E7_QUAD
.123
3E4

```

where QUAD is a scalar integer [named constant](#).

1 **4.4.3.3 Complex type**

2 1 The complex type has values that approximate the mathematical complex numbers. The values of a complex
3 type are ordered pairs of real values. The first real value is called the real part, and the second real value is called
4 the imaginary part.

5 2 Each approximation method used to represent data entities of type real shall be available for both the real and
6 imaginary parts of a data entity of type complex. The (default integer) [kind type parameter](#) KIND for a complex
7 entity specifies for both parts the real approximation method characterized by this kind type parameter value.
8 The [kind type parameter](#) of an approximation method is returned by the intrinsic function [KIND \(13.8.100\)](#).

9 3 The type specifier for the complex type uses the keyword COMPLEX. There is no keyword for double precision
10 complex. If the type keyword COMPLEX is used without a [kind type parameter](#), the complex type with default
11 complex kind is specified, the kind value is [KIND \(0.0\)](#), and both parts are default real.

12 R418 *complex-literal-constant* is (*real-part* , *imag-part*)

13 R419 *real-part* is [signed-int-literal-constant](#)
14 or [signed-real-literal-constant](#)
15 or [named-constant](#)

16 R420 *imag-part* is [signed-int-literal-constant](#)
17 or [signed-real-literal-constant](#)
18 or [named-constant](#)

19 C418 (R418) Each [named constant](#) in a complex literal constant shall be of type integer or real.

20 4 If the real part and the imaginary part of a complex literal constant are both real, the [kind type parameter](#) value
21 of the complex literal constant is the [kind type parameter](#) value of the part with the greater decimal precision; if
22 the precisions are the same, it is the [kind type parameter](#) value of one of the parts as determined by the processor.
23 If a part has a [kind type parameter](#) value different from that of the complex literal constant, the part is converted
24 to the approximation method of the complex literal constant.

25 5 If both the real and imaginary parts are integer, they are converted to the default real approximation method
26 and the constant is default complex. If only one of the parts is an integer, it is converted to the approximation
27 method selected for the part that is real and the [kind type parameter](#) value of the complex literal constant is
28 that of the part that is real.

NOTE 4.9

Examples of complex literal constants are:

```

(1.0, -1.0)
(3, 3.1E6)
(4.0_4, 3.6E7_8)
( 0., PI) ! where PI is a previously declared named real constant.

```

4.4.4 Character type

4.4.4.1 Character sets

1 The character type has a set of values composed of character strings. A character string is a sequence of characters, numbered from left to right 1, 2, 3, ... up to the number of characters in the string. The number of characters in the string is called the length of the string. The length is a type parameter; its kind is processor dependent and its value is greater than or equal to zero.

2 The processor shall provide one or more representation methods that define sets of values for data of type character. Each such method is characterized by a value for the (default integer) *kind type parameter* *KIND*. The *kind type parameter* of a representation method is returned by the intrinsic function *KIND* (13.8.100). The intrinsic function *SELECTED_CHAR_KIND* (13.8.160) returns a kind value based on the name of a character type. Any character of a particular representation method representable in the processor may occur in a character string of that representation method.

3 The character set specified in ISO/IEC 646:1991 (International Reference Version) is referred to as the *ASCII character* set and its corresponding representation method is *ASCII character* kind. The character set UCS-4 as specified in ISO/IEC 10646 is referred to as the *ISO 10646 character* set and its corresponding representation method is the *ISO 10646 character* kind.

4.4.4.2 Character type specifier

1 The type specifier for the character type uses the keyword *CHARACTER*.

2 If the type keyword *CHARACTER* is used without a *kind type parameter*, the character type with default character kind is specified and the kind value is *KIND* ('A').

3 The default character kind shall support a character set that includes the characters in the Fortran character set (3.1). By supplying nondefault character kinds, the processor may support additional character sets. The characters available in nondefault character kinds are not specified by this part of ISO/IEC 1539, except that one character in each nondefault character set shall be designated as a blank character to be used as a padding character.

R421 *char-selector* **is** *length-selector*
or (*LEN* = *type-param-value* , ■
 ■ *KIND* = *scalar-int-constant-expr*)
or (*type-param-value* , ■
 ■ [*KIND* =] *scalar-int-constant-expr*)
or (*KIND* = *scalar-int-constant-expr* ■
 ■ [, *LEN* = *type-param-value*])

R422 *length-selector* **is** ([*LEN* =] *type-param-value*)
or * *char-length* [,]

R423 *char-length* **is** (*type-param-value*)
or *int-literal-constant*

C419 (R421) The value of *scalar-int-constant-expr* shall be nonnegative and shall specify a representation method that exists on the processor.

C420 (R423) The *int-literal-constant* shall not include a *kind-param*.

C421 (R423) A *type-param-value* in a *char-length* shall be a colon, asterisk, or *specification-expr*.

C422 (R421 R422 R423) A *type-param-value* of * shall be used only

- to declare a *dummy argument*,
- to declare a *named constant*,

- 1 • in the *type-spec* of an **ALLOCATE** statement wherein each *allocate-object* is a **dummy argument** of
 - 2 type CHARACTER with an assumed character length,
 - 3 • in the *type-spec* or *derived-type-spec* of a **type guard statement** (8.1.10), or
 - 4 • in an external function, to declare the character length parameter of the function result.
- 5 C423 A function name shall not be declared with an asterisk *type-param-value* unless it is of type CHARACTER
- 6 and is the name of a **dummy function** or the name of the result of an external function.
- 7 C424 A function name declared with an asterisk *type-param-value* shall not be an array, a pointer, **elemental**, recursive, or pure.
- 8 C425 (R422) The optional comma in a *length-selector* is permitted only in a *declaration-type-spec* in a *type-declaration-stmt*.
- 9 C426 (R422) The optional comma in a *length-selector* is permitted only if no double-colon separator appears in the *type-*
- 10 *declaration-stmt*.
- 11 C427 (R421) The length specified for a character **statement function** or for a **statement function dummy argument** of type
- 12 character shall be a **constant expression**.
- 13 4 The *char-selector* in a CHARACTER *intrinsic-type-spec* and the * *char-length* in an *entity-decl* or in a *component-*
- 14 *decl* of a type definition specify character length. The * *char-length* in an *entity-decl* or a *component-decl* specifies
- 15 an individual length and overrides the length specified in the *char-selector*, if any. If a * *char-length* is not specified
- 16 in an *entity-decl* or a *component-decl*, the *length-selector* or *type-param-value* specified in the *char-selector* is the
- 17 character length. If the length is not specified in a *char-selector* or a * *char-length*, the length is 1.
- 18 5 If the character length parameter value evaluates to a negative value, the length of character entities declared
- 19 is zero. A character length parameter value of : indicates a **deferred type parameter** (4.2). A *char-length* type
- 20 parameter value of * has the following meanings.
- 21 • If used to declare a **dummy argument** of a procedure, the **dummy argument** assumes its length from its
 - 22 **effective argument**.
 - 23 • If used to declare a **named constant**, the length is that of the constant value.
 - 24 • If used in the *type-spec* of an **ALLOCATE** statement, each *allocate-object* assumes its length from its **effective**
 - 25 **argument**.
 - 26 • If used in the *type-spec* of a **type guard statement**, the **associating entity** assumes its length from the selector.
 - 27 • If used to specify the character length parameter of a function result, any **scoping unit** invoking the function or passing it as
 - 28 an actual argument shall declare the function name with a character length parameter value other than * or access such a
 - 29 definition by **argument**, **host**, or **use** association. When the function is invoked, the length of the **function result** is assumed
 - 30 from the value of this type parameter.

31 4.4.4.3 Character literal constant

32 1 The syntax of a character literal constant is given by R424.

33 R424 *char-literal-constant* **is** [*kind-param* _] ' [*rep-char*] ... '

34 **or** [*kind-param* _] " [*rep-char*] ... "

35 C428 (R424) The value of *kind-param* shall specify a representation method that exists on the processor.

36 2 The optional **kind type parameter** preceding the leading delimiter specifies the **kind type parameter** of the char-

37 acter constant; if it does not appear, the constant is default character.

38 3 For the type character with kind *kind-param*, if it appears, and for default character otherwise, a representable

39 character, *rep-char*, is defined as follows.

- 40 • In free source form, it is any graphic character in the processor-dependent character set.
- 41 • In fixed source form, it is any character in the processor-dependent character set. A processor may restrict the occurrence of
- 42 some or all of the control characters.

- 1 4 The delimiting apostrophes or quotation marks are not part of the value of the character literal constant.
- 2 5 An apostrophe character within a character constant delimited by apostrophes is represented by two consecutive
3 apostrophes (without intervening blanks); in this case, the two apostrophes are counted as one character. Sim-
4 ilarly, a quotation mark character within a character constant delimited by quotation marks is represented by
5 two consecutive quotation marks (without intervening blanks) and the two quotation marks are counted as one
6 character.
- 7 6 A zero-length character literal constant is represented by two consecutive apostrophes (without intervening blanks)
8 or two consecutive quotation marks (without intervening blanks) outside of a [character context](#).

NOTE 4.10

Examples of character literal constants are:

```
"DON'T"
'DON' 'T'
```

both of which have the value DON'T and

```
' ,'
```

which has the zero-length character string as its value.

NOTE 4.11

An example of a nondefault character literal constant, where the processor supports the corresponding character set, is:

```
NIHONGO_ '彼女なしでは何もできない。'
```

where NIHONGO is a [named constant](#) whose value is the kind type parameter for Nihongo (Japanese) characters. This means “Without her, nothing is possible”.

9 **4.4.4.4 Collating sequence**

- 10 1 The processor defines a [collating sequence](#) for the character set of each kind of character. The [collating sequence](#)
11 is an isomorphism between the character set and the set of integers $\{I : 0 \leq I < N\}$, where N is the number of
12 characters in the set. The intrinsic functions [CHAR \(13.8.44\)](#) and [ICHAR \(13.8.88\)](#) provide conversions between
13 the characters and the integers according to this mapping.

NOTE 4.12

For example:

```
ICHAR ( 'X' )
```

returns the integer value of the character 'X' according to the [collating sequence](#) of the processor.

- 14 2 The [collating sequence](#) of the default character kind shall satisfy the following constraints.
- 15 • ICHAR ('A') < ICHAR ('B') < ... < ICHAR ('Z') for the twenty-six upper-case letters.
 - 16 • ICHAR ('0') < ICHAR ('1') < ... < ICHAR ('9') for the ten digits.
 - 17 • ICHAR (' ') < ICHAR ('0') < ICHAR ('9') < ICHAR ('A') or
18 ICHAR (' ') < ICHAR ('A') < ICHAR ('Z') < ICHAR ('0').
 - 19 • ICHAR ('a') < ICHAR ('b') < ... < ICHAR ('z') for the twenty-six lower-case letters.
 - 20 • ICHAR (' ') < ICHAR ('0') < ICHAR ('9') < ICHAR ('a') or
21 ICHAR (' ') < ICHAR ('a') < ICHAR ('z') < ICHAR ('0').

1 3 There are no constraints on the location of any other character in the [collating sequence](#), nor is there any specified
2 [collating sequence](#) relationship between the upper-case and lower-case letters.

3 4 The [collating sequence](#) for the [ASCII character](#) kind is as specified in ISO/IEC 646:1991 (International Reference
4 Version); this [collating sequence](#) is called the ASCII collating sequence in this part of ISO/IEC 1539. The [collating
5 sequence](#) for the [ISO 10646 character](#) kind is as specified in ISO/IEC 10646.

NOTE 4.13

The intrinsic functions [ACHAR](#) (13.8.3) and [IACHAR](#) (13.8.81) provide conversions between characters and corresponding integer values according to the ASCII [collating sequence](#).

6 5 The intrinsic functions [LGT](#), [LGE](#), [LLE](#), and [LLT](#) (13.8.106-13.8.109) provide comparisons between strings based
7 on the ASCII [collating sequence](#). International portability is guaranteed if the set of characters used is limited
8 to the Fortran character set (3.1).

9 4.4.5 Logical type

10 1 The logical type has two values, which represent true and false.

11 2 The processor shall provide one or more representation methods for data of type logical. Each such method
12 is characterized by a value for the (default integer) [kind type parameter](#) KIND. The [kind type parameter](#) of a
13 representation method is returned by the intrinsic function [KIND](#) (13.8.100).

14 3 The type specifier for the logical type uses the keyword LOGICAL.

15 4 The keyword LOGICAL with no [kind-selector](#) specifies type logical with default kind; the [kind type parameter](#)
16 value is equal to [KIND](#) (.FALSE.).

17 R425 *logical-literal-constant* **is** .TRUE. [[_ kind-param](#)]
18 **or** .FALSE. [[_ kind-param](#)]

19 C429 (R425) The value of [kind-param](#) shall specify a representation method that exists on the processor.

20 5 The optional [kind type parameter](#) specifies the [kind type parameter](#) of the logical constant; if it does not appear,
21 the constant has the default logical kind.

22 4.5 Derived types

23 4.5.1 Derived type concepts

24 1 Additional types may be derived from the intrinsic types and other derived types. A type definition defines the
25 name of the type and the names and [attributes](#) of its components and [type-bound procedures](#).

26 2 A derived type may be parameterized by multiple type parameters, each of which is defined to be either a kind
27 or length type parameter and may have a default value.

28 3 The [ultimate components](#) of a derived type are the components that are of intrinsic type or have the [ALLOC-
29 ATABLE](#) or [POINTER attribute](#), plus the [ultimate components](#) of the components that are of derived type and
30 have neither the [ALLOCATABLE](#) nor [POINTER attribute](#).

31 4 The [direct components](#) of a derived type are the components of that type, plus the [direct components](#) of the
32 components that are of derived type and have neither the [ALLOCATABLE](#) nor [POINTER attribute](#).

33 5 The [potential subobject components](#) of a derived type are the nonpointer components of that type together with
34 the [potential subobject components](#) of the nonpointer components that are of derived type. This includes all the
35 components that could be a subobject of an object of the type (6.4.2).

- 1 6 The [components](#), [direct components](#), [potential subobject components](#), and [ultimate components](#) of an object of
 2 derived type are the [components](#), [direct components](#), [potential subobject components](#), and [ultimate components](#)
 3 of its type, respectively.
- 4 7 By default, no [storage sequence](#) is implied by the order of the component definitions. However, a storage order
 5 is implied for a [sequence type](#) (4.5.2.3). If the derived type has the [BIND attribute](#), the [storage sequence](#) is that
 6 required by the [companion processor](#) (2.5.7, 15.3.4).
- 7 8 A scalar entity of derived type is a [structure](#). If a derived type has the [SEQUENCE attribute](#), a scalar entity of
 8 the type is a [sequence structure](#).

NOTE 4.14

The [ultimate components](#) of an object of the derived type `kids` defined below are `name`, `age`, and `other_kids`. The [direct components](#) of such an object are `name`, `age`, `other_kids`, and `oldest_child`.

```

type :: person
  character(len=20) :: name
  integer :: age
end type person

type :: kids
  type(person) :: oldest_child
  type(person), allocatable, dimension(:) :: other_kids
end type kids

```

9 **4.5.2 Derived-type definition**

10 **4.5.2.1 Syntax**

- 11 R426 *derived-type-def* is *derived-type-stmt*
 12 [*type-param-def-stmt*] ...
 13 [*private-or-sequence*] ...
 14 [*component-part*]
 15 [*type-bound-procedure-part*]
 16 *end-type-stmt*
- 17 R427 *derived-type-stmt* is TYPE [[, *type-attr-spec-list*] ::] *type-name* ■
 18 ■ [(*type-param-name-list*)]
- 19 R428 *type-attr-spec* is ABSTRACT
 20 or *access-spec*
 21 or BIND (C)
 22 or EXTENDS (*parent-type-name*)
- 23 C430 (R427) A derived type *type-name* shall not be [DOUBLEPRECISION](#) or the same as the name of any
 24 intrinsic type defined in this part of ISO/IEC 1539.
- 25 C431 (R427) The same *type-attr-spec* shall not appear more than once in a given *derived-type-stmt*.
- 26 C432 (R427) The same *type-param-name* shall not appear more than once in a *derived-type-stmt*.
- 27 C433 (R428) A *parent-type-name* shall be the name of a previously defined [extensible type](#) (4.5.7).
- 28 C434 (R426) If the type definition contains or [inherits](#) (4.5.7.2) a deferred [type-bound procedure](#) (4.5.5), [AB-](#)
 29 [STRACT](#) shall appear.
- 30 C435 (R426) If [ABSTRACT](#) appears, the type shall be [extensible](#).

- 1 C436 (R426) If EXTENDS appears, SEQUENCE shall not appear.
- 2 C437 (R426) If EXTENDS appears and the type being defined has a [coarray ultimate component](#), its [parent](#)
3 [type](#) shall have a [coarray ultimate component](#).
- 4 C438 (R426) If EXTENDS appears and the type being defined has a [potential subobject component](#) of type
5 [EVENT_TYPE](#) or [LOCK_TYPE](#) from the intrinsic module [ISO_FORTRAN_ENV](#), its [parent type](#)
6 shall be [EVENT_TYPE](#) or [LOCK_TYPE](#) or have a [potential subobject component](#) of type [EVENT_](#)
7 [TYPE](#) or [LOCK_TYPE](#).
- 8 R429 *private-or-sequence* is [private-components-stmt](#)
9 or [sequence-stmt](#)
- 10 C439 (R426) The same [private-or-sequence](#) shall not appear more than once in a given [derived-type-def](#).
- 11 R430 *end-type-stmt* is END TYPE [*type-name*]
- 12 C440 (R430) If END TYPE is followed by a *type-name*, the *type-name* shall be the same as that in the
13 corresponding [derived-type-stmt](#).
- 14 1 Derived types with the [BIND attribute](#) are subject to additional constraints as specified in [15.3.4](#).

NOTE 4.15

An example of a derived-type definition is:

```
TYPE PERSON
  INTEGER AGE
  CHARACTER (LEN = 50) NAME
END TYPE PERSON
```

An example of declaring a variable CHAIRMAN of type PERSON is:

```
TYPE (PERSON) :: CHAIRMAN
```

15 **4.5.2.2 Accessibility**

- 16 1 The accessibility of a type name is determined as specified in [5.5.2](#). The accessibility of a type name does not
17 affect, and is not affected by, the accessibility of its [components](#) and [type-bound procedures](#).
- 18 2 If a derived type is defined in the scoping unit of a module, and its name is private in that module, then the type
19 name, and thus the structure constructor ([4.5.10](#)) for the type, are accessible only within that module and its
20 [descendants](#).

NOTE 4.16

An example of a type with a private name is:

```
TYPE, PRIVATE :: AUXILIARY
  LOGICAL :: DIAGNOSTIC
  CHARACTER (LEN = 20) :: MESSAGE
END TYPE AUXILIARY
```

Such a type would be accessible only within the module in which it is defined, and within its [descendants](#).

21 **4.5.2.3 Sequence type**

- 22 R431 *sequence-stmt* is SEQUENCE
- 23 C441 (R426) If SEQUENCE appears, the type shall have at least one component, each data component shall

1 be declared to be of an intrinsic type or of a [sequence type](#), the derived type shall not have any [type](#)
2 [parameter](#), and a [type-bound-procedure-part](#) shall not appear.

3 1 If the SEQUENCE statement appears, the type has the [SEQUENCE attribute](#) and is a [sequence type](#). The order
4 of the component definitions in a [sequence type](#) specifies a [storage sequence](#) for objects of that type. The type
5 is a [numeric sequence type](#) if there are no [pointer](#) or [allocatable components](#), and each [component](#) is default
6 integer, default real, double precision real, default complex, default logical, or of [numeric sequence type](#). The
7 type is a [character sequence type](#) if there are no [pointer](#) or [allocatable](#) components, and each component is default
8 character or of [character sequence type](#).

NOTE 4.17

An example of a [numeric sequence type](#) is:

```
TYPE NUMERIC_SEQ
  SEQUENCE
  INTEGER :: INT_VAL
  REAL    :: REAL_VAL
  LOGICAL :: LOG_VAL
END TYPE NUMERIC_SEQ
```

NOTE 4.18

A structure resolves into a sequence of components. Unless the structure includes a SEQUENCE statement, the use of this terminology in no way implies that these components are stored in this, or any other, order. Nor is there any requirement that [contiguous](#) storage be used. The sequence merely refers to the fact that in writing the definitions there will necessarily be an order in which the components appear, and this will define a sequence of components. This order is of limited significance because a component of an object of derived type will always be accessed by a component name except in the following contexts: the sequence of expressions in a derived-type value constructor, intrinsic assignment, the data values in namelist input data, and the inclusion of the structure in an input/output list of a formatted data transfer, where it is expanded to this sequence of components. Provided the processor adheres to the defined order in these cases, it is otherwise free to organize the storage of the components for any nonsequence structure in memory as best suited to the particular architecture.

9 4.5.2.4 Determination of derived types

- 10 1 Derived-type definitions with the same type name may appear in different [scoping units](#), in which case they might
11 be independent and describe different derived types or they might describe the same type.
- 12 2 Two data entities have the same type if they are declared with reference to the same derived-type definition. Data
13 entities also have the same type if they are declared with reference to different derived-type definitions that specify
14 the same type name, all have the [SEQUENCE attribute](#) or all have the [BIND attribute](#), have no components
15 with [PRIVATE](#) accessibility, and have components that agree in order, name, and attributes. Otherwise, they
16 are of different derived types. A data entity declared using a type with the [SEQUENCE attribute](#) or with the
17 [BIND attribute](#) is not of the same type as an entity of a type that has any components that are [PRIVATE](#).

NOTE 4.19

An example of declaring two entities with reference to the same derived-type definition is:

```
TYPE POINT
  REAL X, Y
END TYPE POINT
TYPE (POINT) :: X1
CALL SUB (X1)
...
CONTAINS
```

NOTE 4.19 (cont.)

```

SUBROUTINE SUB (A)
  TYPE (POINT) :: A
  ...
END SUBROUTINE SUB

```

The definition of derived type POINT is known in subroutine SUB by host association. Because the declarations of X1 and A both reference the same derived-type definition, X1 and A have the same type. X1 and A also would have the same type if the derived-type definition were in a module and both SUB and its containing [program unit](#) referenced the module.

NOTE 4.20

An example of data entities in different [scoping units](#) having the same type is:

```

PROGRAM PGM
  TYPE EMPLOYEE
    SEQUENCE
    INTEGER          ID_NUMBER
    CHARACTER (50) NAME
  END TYPE EMPLOYEE
  TYPE (EMPLOYEE) PROGRAMMER
  CALL SUB (PROGRAMMER)
  ...
END PROGRAM PGM
SUBROUTINE SUB (POSITION)
  TYPE EMPLOYEE
    SEQUENCE
    INTEGER          ID_NUMBER
    CHARACTER (50) NAME
  END TYPE EMPLOYEE
  TYPE (EMPLOYEE) POSITION
  ...
END SUBROUTINE SUB

```

The [actual argument](#) PROGRAMMER and the [dummy argument](#) POSITION have the same type because they are declared with reference to a derived-type definition with the same name, the [SEQUENCE attribute](#), and components that agree in order, name, and [attributes](#).

Suppose the component name ID_NUMBER was ID_NUM in the subroutine. Because all the component names are not identical to the component names in derived type EMPLOYEE in the main program, the [actual argument](#) PROGRAMMER would not be of the same type as the [dummy argument](#) POSITION. Thus, the program would not be standard-conforming.

NOTE 4.21

The requirement that the two types have the same name applies to the *type-names* in the respective derived type definitions, not to local names introduced via renaming in [USE statements](#).

1 **4.5.3 Derived-type parameters**2 **4.5.3.1 Type parameter definition statement**

3 R432 *type-param-def-stmt* is *integer-type-spec, type-param-attr-spec* :: ■
 4 ■ *type-param-decl-list*

5 R433 *type-param-decl* is *type-param-name* [= *scalar-int-constant-expr*]

1 C442 (R432) A *type-param-name* in a *type-param-def-stmt* in a *derived-type-def* shall be one of the *type-param-*
2 *names* in the *derived-type-stmt* of that *derived-type-def*.

3 C443 (R432) Each *type-param-name* in the *derived-type-stmt* in a *derived-type-def* shall appear exactly once as
4 a *type-param-name* in a *type-param-def-stmt* in that *derived-type-def*.

5 R434 *type-param-attr-spec* is KIND
6 or LEN

7 1 The derived type is parameterized if the *derived-type-stmt* has any *type-param-names*.

8 2 Each type parameter is itself of type integer. If its kind selector is omitted, the **kind type parameter** is default
9 integer.

10 3 The *type-param-attr-spec* explicitly specifies whether a type parameter is a kind parameter or a length parameter.

11 4 If a *type-param-decl* has a *scalar-int-constant-expr*, the type parameter has a default value which is specified by
12 the expression. If necessary, the value is converted according to the rules of intrinsic assignment (7.2.1.3) to a
13 value of the same kind as the type parameter.

14 5 A **type parameter** may be used as a primary in a **specification expression** (7.1.11) in the *derived-type-def*. A **kind**
15 **type parameter** may also be used as a primary in a **constant expression** (7.1.12) in the *derived-type-def*.

NOTE 4.22

The following example uses derived-type parameters.

```
TYPE humongous_matrix(k, d)
  INTEGER, KIND :: k = kind(0.0)
  INTEGER(selected_int_kind(12)), LEN :: d
  !-- Specify a nondefault kind for d.
  REAL(k) :: element(d,d)
END TYPE
```

In the following example, *dim* is declared to be a kind parameter, allowing generic overloading of procedures distinguished only by *dim*.

```
TYPE general_point(dim)
  INTEGER, KIND :: dim
  REAL :: coordinates(dim)
END TYPE
```

16 4.5.3.2 Type parameter order

17 1 **Type parameter order** is an ordering of the type parameters of a derived type; it is used for derived-type specifiers.

18 2 The **type parameter order** of a nonextended type is the order of the type parameter list in the derived-type
19 definition. The **type parameter order** of an **extended type** (4.5.7) consists of the **type parameter order** of its
20 **parent type** followed by any additional type parameters in the order of the type parameter list in the derived-type
21 definition.

NOTE 4.23

Given

```
TYPE :: t1(k1,k2)
  INTEGER,KIND :: k1,k2
  REAL(k1) a(k2)
END TYPE
TYPE,EXTENDS(t1) :: t2(k3)
```

NOTE 4.23 (cont.)

```

INTEGER, KIND :: k3
LOGICAL(k3) flag
END TYPE

```

the type parameter order for type t1 is k1 then k2, and the type parameter order for type t2 is k1 then k2 then k3.

4.5.4 Components

4.5.4.1 Component definition statement

R435 *component-part* is [*component-def-stmt*] ...

R436 *component-def-stmt* is *data-component-def-stmt*
or *proc-component-def-stmt*

R437 *data-component-def-stmt* is *declaration-type-spec* [[, *component-attr-spec-list*] ::] ■
■ *component-decl-list*

R438 *component-attr-spec* is *access-spec*
or ALLOCATABLE
or CODIMENSION *lbracket coarray-spec rbracket*
or CONTIGUOUS
or DIMENSION (*component-array-spec*)
or POINTER

R439 *component-decl* is *component-name* [(*component-array-spec*)] ■
■ [*lbracket coarray-spec rbracket*] ■
■ [* *char-length*] [*component-initialization*]

R440 *component-array-spec* is *explicit-shape-spec-list*
or *deferred-shape-spec-list*

C444 (R437) No *component-attr-spec* shall appear more than once in a given *component-def-stmt*.

C445 (R437) If neither the POINTER nor the ALLOCATABLE attribute is specified, the *declaration-type-spec* in the *component-def-stmt* shall specify an intrinsic type or a previously defined derived type.

C446 (R437) If the POINTER or ALLOCATABLE attribute is specified, each *component-array-spec* shall be a *deferred-shape-spec-list*.

C447 (R437) If a *coarray-spec* appears, it shall be a *deferred-coshape-spec-list* and the component shall have the ALLOCATABLE attribute.

C448 (R437) If a *coarray-spec* appears, the component shall not be of type C_PTR or C_FUNPTR from the intrinsic module ISO_C_BINDING (15.3.3).

C449 A data component whose type has a *coarray ultimate component* shall be a nonpointer nonallocatable scalar and shall not be a *coarray*.

C450 (R437) If neither the POINTER nor the ALLOCATABLE attribute is specified, each *component-array-spec* shall be an *explicit-shape-spec-list*.

C451 (R440) Each *bound* in the *explicit-shape-spec* shall be a *specification expression* in which there are no references to specification functions or the intrinsic functions ALLOCATED, ASSOCIATED, EXTENDS_TYPE_OF, PRESENT, or SAME_TYPE_AS, every specification inquiry reference is a *constant ex-*

NOTE 4.26

An example of a derived type definition with an array component is:

```

TYPE LINE
  REAL, DIMENSION (2, 2) :: COORD      !
                                     ! COORD(:,1) has the value of [X1, Y1]
                                     ! COORD(:,2) has the value of [X2, Y2]
  REAL                      :: WIDTH   ! Line width in centimeters
  INTEGER                   :: PATTERN ! 1 for solid, 2 for dash, 3 for dot
END TYPE LINE

```

An example of declaring a variable `LINE_SEGMENT` to be of the type `LINE` is:

```

TYPE (LINE)          :: LINE_SEGMENT

```

The scalar variable `LINE_SEGMENT` has a component that is an array. In this case, the array is a subobject of a scalar. The double colon in the definition for `COORD` is required; the double colon in the definition for `WIDTH` and `PATTERN` is optional.

NOTE 4.27

An example of a derived type definition with an [allocatable](#) component is:

```

TYPE STACK
  INTEGER           :: INDEX
  INTEGER, ALLOCATABLE :: CONTENTS (:)
END TYPE STACK

```

For each scalar variable of type `STACK`, the shape of the component `CONTENTS` is determined by execution of an [ALLOCATE](#) statement or [assignment statement](#), or by [argument association](#).

NOTE 4.28

[Default initialization](#) of an [explicit-shape array](#) component can be specified by a [constant expression](#) consisting of an array constructor (4.8), or of a single scalar that becomes the value of each array element.

1 **4.5.4.3 Coarray components**

- 2 1 A data component is a [coarray](#) if its [component-decl](#) contains a [coarray-spec](#) or its [data-component-def-stmt](#)
3 contains a CODIMENSION clause. If the [component-decl](#) contains a [coarray-spec](#) it specifies the [corank](#); otherwise,
4 the [coarray-spec](#) in the CODIMENSION clause specifies the [corank](#).

NOTE 4.29

An example of a derived type definition with a coarray component is:

```

TYPE GRID_TYPE
  REAL, ALLOCATABLE, CODIMENSION[:, :, :] :: GRID(:, :, :)
END TYPE GRID_TYPE

```

An object of type `grid_type` cannot be an array, an [allocatable](#) object, a [coarray](#), or a [pointer](#).

5 **4.5.4.4 Pointer components**

- 6 1 A component is a pointer (2.4.8) if its [component-attr-spec-list](#) contains the [POINTER](#) attribute. A pointer
7 component may be a data pointer or a procedure pointer.

- 1 *decl-list*.
- 2 C463 (R437) If *component-initialization* appears, every type parameter and *array bound* of the component
3 shall be a colon or *constant expression*.
- 4 C464 (R437) If => appears in *component-initialization*, POINTER shall appear in the *component-attr-spec-*
5 *list*. If = appears in *component-initialization*, neither POINTER nor ALLOCATABLE shall appear in
6 the *component-attr-spec-list*.
- 7 C465 (R443) If *initial-data-target* appears, *component-name* shall be data-pointer-initialization compatible with
8 it.
- 9 C466 (R444) The *designator* shall designate a nonallocatable variable that has the TARGET and SAVE attrib-
10 utes and does not have a *vector subscript*. Every subscript, section subscript, substring starting point,
11 and substring ending point in *designator* shall be a *constant expression*.
- 12 3 If *null-init* appears for a pointer component, that component in any object of the type has an initial association
13 status of *disassociated* (1.3.62) or becomes disassociated as specified in 16.5.2.4.
- 14 4 If *initial-data-target* appears for a data pointer component, that component in any object of the type is initially
15 associated with the *target* or becomes associated with the *target* as specified in 16.5.2.3.
- 16 5 If *initial-proc-target* (12.4.3.7) appears in *proc-decl* for a procedure pointer component, that component in any
17 object of the type is initially associated with the *target* or becomes associated with the *target* as specified in
18 16.5.2.3.
- 19 6 If *constant-expr* appears for a nonpointer component, that component in any object of the type is initially defined
20 (16.6.3) or becomes defined as specified in 16.6.5 with the value determined from *constant-expr*. If necessary,
21 the value is converted according to the rules of intrinsic assignment (7.2.1.3) to a value that agrees in type, type
22 parameters, and shape with the component. If the component is of a type for which *default initialization* is
23 specified for a component, the *default initialization* specified by *constant-expr* overrides the *default initialization*
24 specified for that component. When one *initialization* overrides another it is as if only the overriding *initialization*
25 were specified (see Note 4.33). *Explicit initialization* in a *type declaration statement* (5.2) overrides *default*
26 *initialization* (see Note 4.32). Unlike *explicit initialization*, *default initialization* does not imply that the object
27 has the SAVE attribute.
- 28 7 A *subcomponent* (6.4.2) is *default-initialized* if the type of the object of which it is a component specifies *default*
29 *initialization* for that component, and the *subcomponent* is not a subobject of an object that is *default-initialized*
30 or *explicitly initialized*.
- 31 8 A type has *default initialization* if *component-initialization* is specified for any *direct component* of the type. An
32 object has *default initialization* if it is of a type that has *default initialization*.

NOTE 4.32

It is not required that *initialization* be specified for each component of a derived type. For example:

```

TYPE DATE
  INTEGER DAY
  CHARACTER (LEN = 5) MONTH
  INTEGER :: YEAR = 2008      ! Partial default initialization
END TYPE DATE

```

In the following example, the default initial value for the YEAR component of TODAY is overridden by *explicit initialization* in the *type declaration statement*:

```

TYPE (DATE), PARAMETER :: TODAY = DATE (21, "Feb.", 2009)

```

NOTE 4.33

The default initial value of a component of derived type can be overridden by [default initialization](#) specified in the definition of the type. Continuing the example of Note 4.32:

```
TYPE SINGLE_SCORE
  TYPE (DATE) :: PLAY_DAY = TODAY
  INTEGER SCORE
  TYPE (SINGLE_SCORE), POINTER :: NEXT => NULL ( )
END TYPE SINGLE_SCORE
TYPE (SINGLE_SCORE) SETUP
```

The PLAY_DAY component of SETUP receives its initial value from TODAY, overriding the [initialization](#) for the YEAR component.

NOTE 4.34

Arrays of structures can be declared with elements that are partially or totally initialized by default. Continuing the example of Note 4.33 :

```
TYPE MEMBER (NAME_LEN)
  INTEGER, LEN :: NAME_LEN
  CHARACTER (LEN = NAME_LEN) :: NAME = ''
  INTEGER :: TEAM_NO, HANDICAP = 0
  TYPE (SINGLE_SCORE), POINTER :: HISTORY => NULL ( )
END TYPE MEMBER
TYPE (MEMBER(9)) LEAGUE (36)      ! Array of partially initialized elements
TYPE (MEMBER(9)) :: ORGANIZER = MEMBER (9) ("I. Manage",1,5,NULL ( ))
```

ORGANIZER is [explicitly initialized](#), overriding the [default initialization](#) for an object of type MEMBER.

Allocated objects can also be initialized partially or totally. For example:

```
ALLOCATE (ORGANIZER % HISTORY)   ! A partially initialized object of type
                                ! SINGLE_SCORE is created.
```

NOTE 4.35

A pointer component of a derived type can have as its [target](#) an object of that derived type. The type definition can specify that in objects declared to be of this type, such a pointer is default initialized to [disassociated](#). For example:

```
TYPE NODE
  INTEGER          :: VALUE = 0
  TYPE (NODE), POINTER :: NEXT_NODE => NULL ( )
END TYPE
```

A type such as this can be used to construct linked lists of objects of type NODE. Linked lists can also be constructed using [allocatable](#) components.

NOTE 4.36

A pointer component of a derived type can be default initialized to have an initial [target](#).

```
TYPE NODE
  INTEGER          :: VALUE = 0
  TYPE (NODE), POINTER :: NEXT_NODE => SENTINEL
END TYPE
```

NOTE 4.36 (cont.)

```
TYPE(NODE), SAVE, TARGET :: SENTINEL
```

4.5.4.7 Component order

- 1 **Component order** is an ordering of the nonparent components of a derived type; it is used for intrinsic formatted input/output and **structure constructors** where **component keywords** are not used. **Parent components** are excluded from the **component order** of an **extended type** (4.5.7).
- 2 The **component order** of a nonextended type is the order of the declarations of the components in the derived-type definition. The component order of an **extended type** consists of the **component order** of its **parent type** followed by any additional components in the order of their declarations in the extended derived-type definition.

NOTE 4.37

Given the same type definitions as in Note 4.23, the **component order** of type T1 is just A (there is only one component), and the **component order** of type T2 is A then FLAG. The **parent component** (T1) does not participate in the **component order**.

4.5.4.8 Component accessibility

R445 *private-components-stmt* is PRIVATE

C467 (R445) A *private-components-stmt* is permitted only if the type definition is within the specification part of a module.

- 1 The default accessibility for the components that are declared in a type's *component-part* is private if the type definition contains a *private-components-stmt*, and public otherwise. The accessibility of a component may be explicitly declared by an *access-spec*; otherwise its accessibility is the default for the type definition in which it is declared.
- 2 If a component is private, that component name is accessible only within the module containing the definition, and within its **descendants**.

NOTE 4.38

Type parameters are not components. They are effectively always public.

NOTE 4.39

The accessibility of the components of a type is independent of the accessibility of the type name. It is possible to have all four combinations: a public type name with a public component, a private type name with a private component, a public type name with a private component, and a private type name with a public component.

NOTE 4.40

An example of a public type with private components is:

```
TYPE, PUBLIC :: POINT
  PRIVATE
  REAL :: X, Y
END TYPE POINT
```

Such a type definition can be accessed by use association; however, the components X and Y are accessible only within the module and its **descendants**.

NOTE 4.41

The following example illustrates the use of an individual component *access-spec* to override the default accessibility:

```

TYPE MIXED
  PRIVATE
  INTEGER :: I
  INTEGER, PUBLIC :: J
END TYPE MIXED

TYPE (MIXED) :: M

```

The component M%J is accessible in any *scoping unit* where M is accessible; M%I is accessible only within the module containing the TYPE MIXED definition, and within its *descendants*.

4.5.5 Type-bound procedures

- 1
- 2 R446 *type-bound-procedure-part* **is** *contains-stmt*
- 3 [*binding-private-stmt*]
- 4 [*type-bound-proc-binding*] ...
- 5 R447 *binding-private-stmt* **is** PRIVATE
- 6 C468 (R446) A *binding-private-stmt* is permitted only if the type definition is within the specification part of
- 7 a module.
- 8 R448 *type-bound-proc-binding* **is** *type-bound-procedure-stmt*
- 9 **or** *type-bound-generic-stmt*
- 10 **or** *final-procedure-stmt*
- 11 R449 *type-bound-procedure-stmt* **is** PROCEDURE [[, *binding-attr-list*] ::] *type-bound-proc-decl-list*
- 12 **or** PROCEDURE (*interface-name*), *binding-attr-list* :: *binding-name-list*
- 13 R450 *type-bound-proc-decl* **is** *binding-name* [=> *procedure-name*]
- 14 C469 (R449) If => *procedure-name* appears in a *type-bound-proc-decl*, the double-colon separator shall appear.
- 15 C470 (R449) The *procedure-name* shall be the name of an accessible module procedure or an *external procedure*
- 16 that has an *explicit interface*.
- 17 1 If neither => *procedure-name* nor *interface-name* appears in a *type-bound-proc-decl*, it is as though => *procedure-*
- 18 *name* had appeared with a procedure name the same as the *binding name*.
- 19 R451 *type-bound-generic-stmt* **is** GENERIC [, *access-spec*] :: *generic-spec* => *binding-name-list*
- 20 C471 (R451) Within the *specification-part* of a module, each *type-bound-generic-stmt* shall specify, either im-
- 21 plicitly or explicitly, the same accessibility as every other *type-bound-generic-stmt* with that *generic-spec*
- 22 in the same derived type.
- 23 C472 (R451) Each *binding-name* in *binding-name-list* shall be the name of a specific *binding* of the type.
- 24 C473 (R451) If *generic-spec* is not *generic-name*, each of its specific *bindings* shall have a *passed-object dummy*
- 25 *argument* (4.5.4.5).
- 26 C474 (R451) If *generic-spec* is OPERATOR (*defined-operator*), the *interface* of each *binding* shall be as
- 27 specified in 12.4.3.5.2.
- 28 C475 (R451) If *generic-spec* is ASSIGNMENT (=), the *interface* of each *binding* shall be as specified in

- 1 12.4.3.5.3.
- 2 C476 (R451) If *generic-spec* is *defined-io-generic-spec*, the *interface* of each *binding* shall be as specified in
3 9.6.4.8. The type of the *dtv* argument shall be *type-name*.
- 4 R452 *binding-attr* **is** PASS [(*arg-name*)]
5 **or** NOPASS
6 **or** NON_OVERRIDABLE
7 **or** DEFERRED
8 **or** *access-spec*
- 9 C477 (R452) The same *binding-attr* shall not appear more than once in a given *binding-attr-list*.
- 10 C478 (R449) If the *interface* of the *binding* has no *dummy argument* of the type being defined, **NOPASS** shall
11 appear.
- 12 C479 (R449) If **PASS** (*arg-name*) appears, the *interface* of the *binding* shall have a *dummy argument* named
13 *arg-name*.
- 14 C480 (R452) **PASS** and **NOPASS** shall not both appear in the same *binding-attr-list*.
- 15 C481 (R452) **NON_OVERRIDABLE** and **DEFERRED** shall not both appear in the same *binding-attr-list*.
- 16 C482 (R452) **DEFERRED** shall appear if and only if *interface-name* appears.
- 17 C483 (R449) An overriding *binding* (4.5.7.3) shall have the **DEFERRED** attribute only if the *binding* it over-
18 rides is deferred.
- 19 C484 (R449) A *binding* shall not override an *inherited binding* (4.5.7.2) that has the **NON_OVERRIDABLE**
20 attribute.
- 21 2 A type-bound procedure statement declares one or more specific *type-bound procedures*. A specific *type-bound*
22 *procedure* can have a *passed-object dummy argument* (4.5.4.5). A *type-bound procedure* with the **DEFERRED**
23 *attribute* is a deferred type-bound procedure. The **DEFERRED** keyword shall appear only in the definition of
24 an *abstract type*.
- 25 3 A **GENERIC** statement declares a generic *type-bound procedure*, which is a type-bound *generic interface* for its
26 specific *type-bound procedures*.
- 27 4 A *binding* of a type is a *type-bound procedure* (specific or generic), a *generic type-bound interface*, or a *final*
28 *subroutine*. These are referred to as specific bindings, generic bindings, and final bindings respectively.
- 29 5 A *type-bound procedure* may be identified by a *binding name* in the scope of the type definition. This name is the
30 *binding-name* for a specific *type-bound procedure*, and the *generic-name* for a generic binding whose *generic-spec*
31 is *generic-name*. A final binding, or a generic binding whose *generic-spec* is not *generic-name*, has no *binding*
32 *name*.
- 33 6 The *interface* of a specific *type-bound procedure* is that of the procedure specified by *procedure-name* or the
34 *interface* specified by *interface-name*.

NOTE 4.42

An example of a type and a *type-bound procedure* is:

```

TYPE POINT
  REAL :: X, Y
CONTAINS
  PROCEDURE, PASS :: LENGTH => POINT_LENGTH
END TYPE POINT
...

```

NOTE 4.42 (cont.)

and in the *module-subprogram-part* of the same module:

```
REAL FUNCTION POINT_LENGTH (A, B)
  CLASS (POINT), INTENT (IN) :: A, B
  POINT_LENGTH = SQRT ( (A%X - B%X)**2 + (A%Y - B%Y)**2 )
END FUNCTION POINT_LENGTH
```

- 1 7 The same *generic-spec* may be used in several GENERIC statements within a single derived-type definition. Each
2 additional GENERIC statement with the same *generic-spec* extends the *generic interface*.

NOTE 4.43

Unlike the situation with generic procedure names, a generic *type-bound procedure* name is not permitted to be the same as a specific *type-bound procedure* name in the same type (16.3).

- 3 8 The default accessibility for the *type-bound procedures* of a type is private if the type definition contains a *binding-
4 private-stmt*, and public otherwise. The accessibility of a *type-bound procedure* may be explicitly declared by an
5 *access-spec*; otherwise its accessibility is the default for the type definition in which it is declared.

- 6 9 A public *type-bound procedure* is accessible via any accessible object of the type. A private *type-bound procedure*
7 is accessible only within the module containing the type definition, and within its *descendants*.

NOTE 4.44

The accessibility of a *type-bound procedure* is not affected by a *PRIVATE statement* in the *component-part*; the accessibility of a data component is not affected by a *PRIVATE statement* in the *type-bound-procedure-part*.

8 **4.5.6 Final subroutines**9 **4.5.6.1 FINAL statement**

10 R453 *final-procedure-stmt* is FINAL [::] *final-subroutine-name-list*

11 C485 (R453) A *final-subroutine-name* shall be the name of a module procedure with exactly one *dummy*
12 *argument*. That argument shall be nonoptional and shall be a noncoarray, nonpointer, nonallocatable,
13 nonpolymorphic variable of the derived type being defined. All length type parameters of the *dummy*
14 *argument* shall be assumed. The *dummy argument* shall not have the *INTENT (OUT)* or *VALUE*
15 attribute.

16 C486 (R453) A *final-subroutine-name* shall not be one previously specified as a *final subroutine* for that type.

17 C487 (R453) A *final subroutine* shall not have a *dummy argument* with the same *kind type parameters* and
18 *rank* as the *dummy argument* of another *final subroutine* of that type.

19 1 The FINAL statement specifies that each procedure it names is a *final subroutine*. A *final subroutine* might be
20 executed when a data entity of that type is finalized (4.5.6.2).

21 2 A derived type is *finalizable* if and only if it has a *final subroutine* or a nonpointer, nonallocatable component of
22 *finalizable* type. A nonpointer data entity is *finalizable* if and only if it is of *finalizable* type. No other entity is
23 *finalizable*.

NOTE 4.45

Final subroutines are effectively always “accessible”. They are called for entity *finalization* regardless of the accessibility of the type, its other *type-bound procedures*, or the subroutine name itself.

NOTE 4.46

Final subroutines are not inherited through type extension and cannot be overridden. The final subroutines of the parent type are called after any additional final subroutines of an extended type are called.

1 **4.5.6.2 The finalization process**

- 2 1 Only finalizable entities are finalized. When an entity is finalized, the following steps are carried out in sequence.
- 3 (1) If the dynamic type of the entity has a final subroutine whose dummy argument has the same kind
4 type parameters and rank as the entity being finalized, it is called with the entity as an actual
5 argument. Otherwise, if there is an elemental final subroutine whose dummy argument has the same
6 kind type parameters as the entity being finalized, it is called with the entity as an actual argument.
7 Otherwise, no subroutine is called at this point.
- 8 (2) All finalizable components that appear in the type definition are finalized in a processor-dependent
9 order. If the entity being finalized is an array, each finalizable component of each element of that
10 entity is finalized separately.
- 11 (3) If the entity is of extended type and the parent type is finalizable, the parent component is finalized.
- 12 2 If several entities are to be finalized as a consequence of an event specified in 4.5.6.3, the order in which they
13 are finalized is processor dependent. During this process, execution of a final subroutine for one of these entities
14 shall not reference or define any of the other entities that have already been finalized.
- 15 3 If an object is not finalized, it retains its definition status and does not become undefined.

NOTE 4.47

An implementation might need to ensure that when an event causes more than one coarray to be deallocated, they are deallocated in the same order on all images.

16 **4.5.6.3 When finalization occurs**

- 17 1 When an intrinsic assignment statement is executed (7.2.1.3), if the variable is not an unallocated allocatable
18 variable, it is finalized after evaluation of *expr* and before the definition of the variable. If the variable is an
19 allocated allocatable variable that would be deallocated by intrinsic assignment, the finalization occurs before the
20 deallocation.
- 21 2 When a pointer is deallocated its target is finalized. When an allocatable entity is deallocated, it is finalized
22 unless it is the variable in an intrinsic assignment statement or a component thereof. If an error condition occurs
23 during deallocation, it is processor dependent whether finalization occurs.
- 24 3 A nonpointer, nonallocatable object that is not a dummy argument or function result is finalized immediately
25 before it would become undefined due to execution of a RETURN or END statement (16.6.6, item (3)).
- 26 4 A nonpointer nonallocatable local variable of a BLOCK construct is finalized immediately before it would become
27 undefined due to termination of the BLOCK construct (16.6.6, item (2)).
- 28 5 A nonpointer nonallocatable local variable with LOCAL or LOCAL_INIT locality in a DO CONCURRENT
29 construct is finalized when execution of each iteration completes.
- 30 6 If an executable construct references a nonpointer function, the result is finalized after execution of the innermost
31 executable construct containing the reference.
- 32 7 If a specification expression in a scoping unit references a function, the result is finalized before execution of the
33 executable constructs in the scoping unit.
- 34 8 When a procedure is invoked, a nonpointer, nonallocatable, INTENT (OUT) dummy argument of that procedure
35 is finalized before it becomes undefined. The finalization caused by INTENT (OUT) is considered to occur within
36 the invoked procedure; so for elemental procedures, an INTENT (OUT) argument will be finalized only if a scalar

- 1 or elemental [final subroutine](#) is available, regardless of the rank of the [actual argument](#).
- 2 9 If an object is allocated via pointer allocation and later becomes unreachable due to all pointers associated with
3 that object having their [pointer association](#) status changed, it is processor dependent whether it is finalized. If it
4 is finalized, it is processor dependent as to when the [final subroutines](#) are called.

NOTE 4.48

If [finalization](#) is used for storage management, it often needs to be combined with defined assignment.

5 **4.5.6.4 Entities that are not finalized**

- 6 1 If image execution is [terminated](#), either by an error (e.g. an allocation failure) or by execution of a [stop-stmt](#),
7 [error-stop-stmt](#), or [end-program-stmt](#), entities existing immediately prior to [termination](#) are not finalized.

NOTE 4.49

A nonpointer, nonallocatable object that has the [SAVE attribute](#) is never finalized as a direct consequence of the execution of a [RETURN](#) or [END statement](#).

8 **4.5.7 Type extension**9 **4.5.7.1 Extensible, extended, and abstract types**

- 10 1 A derived type, other than the type [C_PTR](#) or [C_FUNPTR](#) from the intrinsic module [ISO_C_BINDING](#), that
11 does not have the [BIND attribute](#) or the [SEQUENCE attribute](#) is an [extensible type](#).
- 12 2 A type with the [EXTENDS attribute](#) is an [extended type](#); its [parent type](#) is the type named in the [EXTENDS](#)
13 [type-attr-spec](#).

NOTE 4.50

The name of the [parent type](#) might be a local name introduced via renaming in a [USE statement](#).

- 14 3 An [extensible type](#) that does not have the [EXTENDS attribute](#) is an [extension type](#) of itself only. An [extended](#)
15 [type](#) is an [extension](#) of itself and of all types for which its [parent type](#) is an [extension](#).
- 16 4 An [abstract type](#) is a type that has the [ABSTRACT attribute](#).

NOTE 4.51

The [DEFERRED attribute](#) (4.5.5) defers the implementation of a [type-bound procedure](#) to [extensions](#) of the type; it can appear only in an [abstract type](#). The [dynamic type](#) of an object cannot be [abstract](#); therefore, a deferred [type-bound procedure](#) cannot be invoked. An [extension](#) of an [abstract type](#) need not be [abstract](#) if it has no deferred [type-bound procedures](#). A short example of an [abstract type](#) is:

```
TYPE, ABSTRACT :: FILE_HANDLE
CONTAINS
  PROCEDURE(OPEN_FILE), DEFERRED, PASS(HANDLE) :: OPEN
  ...
END TYPE
```

For a more elaborate example see [C.1.4](#).

17 **4.5.7.2 Inheritance**

- 18 1 An [extended type](#) includes all of the type parameters, all of the components, and the nonoverridden (4.5.7.3)
19 [type-bound procedures](#) of its [parent type](#). These are [inherited](#) by the [extended type](#) from the [parent type](#). They
20 retain all of the attributes that they had in the [parent type](#). Additional type parameters, components, and

1 procedure [bindings](#) may be declared in the derived-type definition of the [extended type](#).

NOTE 4.52

Inaccessible components and [bindings](#) of the [parent type](#) are also [inherited](#), but they remain inaccessible in the [extended type](#). Inaccessible entities occur if the type being extended is accessed via [use association](#) and has a private entity.

NOTE 4.53

A derived type is not required to have any components, [bindings](#), or parameters; an [extended type](#) is not required to have more components, [bindings](#), or parameters than its [parent type](#).

2 2 An [extended type](#) has a scalar, nonpointer, nonallocatable, [parent component](#) with the type and type parameters
3 of the [parent type](#). The name of this component is the [parent type](#) name. It has the accessibility of the [parent](#)
4 [type](#). Components of the [parent component](#) are [inheritance associated](#) (16.5.4) with the corresponding components
5 [inherited](#) from the [parent type](#). An ancestor component of a type is the [parent component](#) of the type or an
6 ancestor component of the [parent component](#).

7 3 If a generic [binding](#) specified in a type definition has the same [generic-spec](#) as an [inherited binding](#), it extends
8 the [generic interface](#) and shall satisfy the requirements specified in 12.4.3.5.5.

NOTE 4.54

A component or type parameter declared in an [extended type](#) shall not have the same name as any accessible component or type parameter of its [parent type](#).

NOTE 4.55

Examples:

```

TYPE POINT                                ! A base type
  REAL :: X, Y
END TYPE POINT

TYPE, EXTENDS(POINT) :: COLOR_POINT      ! An extension of TYPE(POINT)
  ! Components X and Y, and component name POINT, inherited from parent
  INTEGER :: COLOR
END TYPE COLOR_POINT

```

9 **4.5.7.3 Type-bound procedure overriding**

10 1 If a specific [type-bound procedure](#) specified in a type definition has the same [binding name](#) as an accessible
11 [type-bound procedure](#) from the [parent type](#) then the [binding](#) specified in the type definition overrides the one
12 from the [parent type](#).

13 2 The overriding and overridden [type-bound procedures](#) shall satisfy the following conditions.

- 14 • Either both shall have a [passed-object dummy argument](#) or neither shall.
- 15 • If the overridden [type-bound procedure](#) is pure then the overriding one shall also be pure.
- 16 • Either both shall be [elemental](#) or neither shall.
- 17 • They shall have the same number of [dummy arguments](#).
- 18 • [Passed-object dummy arguments](#), if any, shall correspond by name and position.
- 19 • [Dummy arguments](#) that correspond by position shall have the same names and [characteristics](#), except for
20 the type of the [passed-object dummy arguments](#).
- 21 • Either both shall be subroutines or both shall be functions having the same result [characteristics](#) (12.3.3).
- 22 • If the overridden [type-bound procedure](#) is [PUBLIC](#) then the overriding one shall not be [PRIVATE](#).

- 1 3 A [binding](#) of a type and a [binding](#) of an [extension](#) of that type correspond if the latter [binding](#) is the same [binding](#)
2 as the former, overrides a corresponding [binding](#), or is an [inherited](#) corresponding [binding](#).

NOTE 4.56

The following is an example of procedure overriding, expanding on the example in Note [4.42](#).

```
TYPE, EXTENDS (POINT) :: POINT_3D
  REAL :: Z
CONTAINS
  PROCEDURE, PASS :: LENGTH => POINT_3D_LENGTH
END TYPE POINT_3D
...
```

and in the *module-subprogram-part* of the same module:

```
REAL FUNCTION POINT_3D_LENGTH ( A, B )
  CLASS (POINT_3D), INTENT (IN) :: A
  CLASS (POINT), INTENT (IN) :: B
  SELECT TYPE(B)
    CLASS IS(POINT_3D)
      POINT_3D_LENGTH = SQRT( (A%X-B%X)**2 + (A%Y-B%Y)**2 + (A%Z-B%Z)**2 )
      RETURN
    END SELECT
  PRINT *, 'In POINT_3D_LENGTH, dynamic type of argument is incorrect.'
  STOP
END FUNCTION POINT_3D_LENGTH
```

3 4.5.8 Derived-type values

- 4 1 The component value of
- 5 • a pointer component is its [pointer association](#),
 - 6 • an [allocatable](#) component is its allocation status and, if it is allocated, its [dynamic type](#) and type parameters,
7 [bounds](#) and value, and
 - 8 • a nonpointer nonallocatable component is its value.
- 9 2 The set of values of a particular derived type consists of all possible sequences of the component values of its
10 components.

11 4.5.9 Derived-type specifier

- 12 1 A derived-type specifier is used in several contexts to specify a particular derived type and type parameters.
- 13 R454 *derived-type-spec* is *type-name* [(*type-param-spec-list*)]
- 14 R455 *type-param-spec* is [*keyword* =] *type-param-value*
- 15 C488 (R454) *type-name* shall be the name of an accessible derived type.
- 16 C489 (R454) *type-param-spec-list* shall appear only if the type is parameterized.
- 17 C490 (R454) There shall be at most one *type-param-spec* corresponding to each parameter of the type. If a
18 type parameter does not have a default value, there shall be a *type-param-spec* corresponding to that
19 type parameter.
- 20 C491 (R455) The *keyword*= may be omitted from a *type-param-spec* only if the *keyword*= has been omitted
21 from each preceding *type-param-spec* in the *type-param-spec-list*.

- 1 C492 (R455) Each *keyword* shall be the name of a parameter of the type.
- 2 C493 (R455) An asterisk may be used as a *type-param-value* in a *type-param-spec* only in the declaration of a
3 *dummy argument* or *associate name* or in the allocation of a *dummy argument*.
- 4 2 Type parameter values that do not have *type parameter keywords* specified correspond to type parameters in type
5 parameter order (4.5.3.2). If a *type parameter keyword* appears, the value corresponds to the type parameter
6 named by the keyword. If necessary, the value is converted according to the rules of intrinsic assignment (7.2.1.3)
7 to a value of the same kind as the type parameter.
- 8 3 The value of a type parameter for which no *type-param-value* has been specified is its default value.

9 4.5.10 Construction of derived-type values

- 10 1 A derived-type definition implicitly defines a corresponding *structure constructor* that allows construction of
11 scalar values of that derived type. The type and type parameters of a constructed value are specified by a derived
12 type specifier.
- 13 R456 *structure-constructor* is *derived-type-spec* ([*component-spec-list*])
- 14 R457 *component-spec* is [*keyword* =] *component-data-source*
- 15 R458 *component-data-source* is *expr*
16 or *data-target*
17 or *proc-target*
- 18 C494 (R456) The *derived-type-spec* shall not specify an *abstract type* (4.5.7).
- 19 C495 (R456) At most one *component-spec* shall be provided for a component.
- 20 C496 (R456) If a *component-spec* is provided for an ancestor component, a *component-spec* shall not be provided
21 for any component that is *inheritance associated* with a *subcomponent* of that ancestor component.
- 22 C497 (R456) A *component-spec* shall be provided for a nonallocatable component unless it has *default initializ-*
23 *ation* or is *inheritance associated* with a *subcomponent* of another component for which a *component-spec*
24 is provided.
- 25 C498 (R457) The *keyword=* may be omitted from a *component-spec* only if the *keyword=* has been omitted
26 from each preceding *component-spec* in the constructor.
- 27 C499 (R457) Each *keyword* shall be the name of a component of the type.
- 28 C4100 (R456) The type name and all components of the type for which a *component-spec* appears shall be
29 accessible in the *scoping unit* containing the *structure constructor*.
- 30 C4101 (R456) If *derived-type-spec* is a type name that is the same as a generic name, the *component-spec-list*
31 shall not be a valid *actual-arg-spec-list* for a function reference that is resolvable as a generic reference to
32 that name (12.5.5.2).
- 33 C4102 (R458) A *data-target* shall correspond to a data pointer component; a *proc-target* shall correspond to a
34 procedure pointer component.
- 35 C4103 (R458) A *data-target* shall have the same *rank* as its corresponding component.

NOTE 4.57

The form 'name(...)' is interpreted as a generic *function-reference* if possible; it is interpreted as a *structure-constructor* only if it cannot be interpreted as a generic *function-reference*.

- 36 2 In the absence of a *component keyword*, each *component-data-source* is assigned to the corresponding component

- 1 in [component order](#) (4.5.4.7). If a [component keyword](#) appears, the *expr* is assigned to the component named
 2 by the keyword. For a nonpointer component, the [declared type](#) and type parameters of the component and
 3 *expr* shall conform in the same way as for a [variable](#) and *expr* in an [intrinsic assignment statement](#) (7.2.1.2), as
 4 specified in Table 7.8. If necessary, each value of intrinsic type is converted according to the rules of intrinsic
 5 assignment (7.2.1.3) to a value that agrees in type and type parameters with the corresponding component of
 6 the derived type. For a nonpointer nonallocatable component, the shape of the expression shall conform with the
 7 shape of the component.
- 8 3 If a component with [default initialization](#) has no corresponding [component-data-source](#), then the [default initial-](#)
 9 [ization](#) is applied to that component. If an [allocatable](#) component has no corresponding [component-data-source](#),
 10 then that component has an allocation status of unallocated.

NOTE 4.58

Because no [parent components](#) appear in the defined [component ordering](#), a value for a [parent component](#) can be specified only with a [component keyword](#). Examples of equivalent values using types defined in Note 4.55:

```
! Create values with components x = 1.0, y = 2.0, color = 3.
TYPE(POINT) :: PV = POINT(1.0, 2.0)      ! Assume components of TYPE(POINT)
                                           ! are accessible here.
...
COLOR_POINT( point=point(1,2), color=3) ! Value for parent component
COLOR_POINT( point=PV, color=3)         ! Available even if TYPE(point)
                                           ! has private components
COLOR_POINT( 1, 2, 3)                   ! All components of TYPE(point)
                                           ! need to be accessible.
```

- 11 4 A [structure constructor](#) shall not appear before the referenced type is defined.

NOTE 4.59

This example illustrates a derived-type constant expression using a derived type defined in Note 4.15:

```
PERSON (21, 'JOHN SMITH')
```

This could also be written as

```
PERSON (NAME = 'JOHN SMITH', AGE = 21)
```

NOTE 4.60

An example constructor using the derived type GENERAL_POINT defined in Note 4.22 is

```
general_point(dim=3) ( [ 1., 2., 3. ] )
```

- 12 5 For a pointer component, the corresponding [component-data-source](#) shall be an allowable [data-target](#) or [proc-](#)
 13 [target](#) for such a pointer in a [pointer assignment statement](#) (7.2.2). If the component data source is a pointer,
 14 the association of the component is that of the pointer; otherwise, the component is [pointer associated](#) with the
 15 component data source.

NOTE 4.61

For example, if the variable TEXT were declared (5.2) to be

```
CHARACTER, DIMENSION (1:400), TARGET :: TEXT
```

and BIBLIO were declared using the derived-type definition REFERENCE in Note 4.30

NOTE 4.61 (cont.)

```
TYPE (REFERENCE) :: BIBLIO
```

the statement

```
BIBLIO = REFERENCE (1, 1987, 1, "This is the title of the referenced &
&paper", SYNOPSIS=TEXT)
```

is valid and associates the pointer component SYNOPSIS of the object BIBLIO with the [target](#) object TEXT. The keyword SYNOPSIS is required because the fifth component of the type REFERENCE is a procedure pointer component, not a data pointer component of type character. It is not necessary to specify a [proc-target](#) for the procedure pointer component because it has [default initialization](#).

- 6 If a component of a derived type is [allocatable](#), the corresponding constructor expression shall either be a reference to the intrinsic function NULL with no arguments, an [allocatable](#) entity of the same [rank](#), or shall evaluate to an entity of the same [rank](#). If the expression is a reference to the intrinsic function NULL, the corresponding component of the constructor has a status of unallocated. If the expression is an [allocatable](#) entity, the corresponding component of the constructor has the same allocation status as that [allocatable](#) entity and, if it is allocated, the same [dynamic type](#), [bounds](#), and value; if a length parameter of the component is [deferred](#), its value is the same as the corresponding parameter of the expression. Otherwise the corresponding component of the constructor has an allocation status of allocated and has the same [bounds](#) and value as the expression.

NOTE 4.62

When the constructor is an [actual argument](#), the allocation status of the [allocatable](#) component is available through the associated [dummy argument](#).

9 4.5.11 Derived-type operations and assignment

- 1 Intrinsic assignment of derived-type entities is described in [7.2.1](#). This part of ISO/IEC 1539 does not specify any intrinsic operations on derived-type entities. Any operation on derived-type entities or defined assignment ([7.2.1.4](#)) for derived-type entities shall be defined explicitly by a function or a subroutine, and a [generic interface](#) ([4.5.5](#), [12.4.3.2](#)).

14 4.6 Enumerations and enumerators

- 1 An enumeration is a set of enumerators. An enumerator is a named integer constant. An enumeration definition specifies the enumeration and its set of enumerators of the corresponding integer kind.

```
R459  enum-def          is  enum-def-stmt
                             enumerator-def-stmt
                             [ enumerator-def-stmt ] ...
                             end-enum-stmt
```

```
R460  enum-def-stmt    is  ENUM, BIND(C)
```

```
R461  enumerator-def-stmt is  ENUMERATOR [ :: ] enumerator-list
```

```
R462  enumerator      is  named-constant [ = scalar-int-constant-expr ]
```

```
R463  end-enum-stmt   is  END ENUM
```

C4104 (R461) If = appears in an [enumerator](#), a double-colon separator shall appear before the [enumerator-list](#).

- 2 For an enumeration, the kind is selected such that an integer type with that kind is [interoperable](#) ([15.3.2](#)) with the corresponding C enumeration type. The corresponding C enumeration type is the type that would be declared by a C enumeration specifier ([6.7.2.2](#) of ISO/IEC 9899:2011) that specified C enumeration constants with the

- 1 same values as those specified by the *enum-def*, in the same order as specified by the *enum-def*.
- 2 3 The *companion processor* (2.5.7) shall be one that uses the same representation for the types declared by all C
- 3 enumeration specifiers that specify the same values in the same order.

NOTE 4.63

If a *companion processor* uses an unsigned type to represent a given enumeration type, the Fortran processor will use the signed integer type of the same width for the enumeration, even though some of the values of the enumerators cannot be represented in this signed integer type. The types of any such enumerators will be *interoperable* with the type declared in the C enumeration.

NOTE 4.64

ISO/IEC 9899:2011 guarantees the enumeration constants fit in a C int (6.7.2.2 of ISO/IEC 9899:2011). Therefore, the Fortran processor can evaluate all enumerator values using the integer type with kind parameter C_INT, and then determine the kind parameter of the integer type that is *interoperable* with the corresponding C enumerated type.

NOTE 4.65

ISO/IEC 9899:2011 specifies that two enumeration types are compatible only if they specify enumeration constants with the same names and same values in the same order. This part of ISO/IEC 1539 further requires that a C processor that is to be a *companion processor* of a Fortran processor use the same representation for two enumeration types if they both specify enumeration constants with the same values in the same order, even if the names are different.

- 4 4 An enumerator is treated as if it were explicitly declared with the *PARAMETER attribute*. The enumerator is
- 5 defined in accordance with the rules of intrinsic assignment (7.2) with the value determined as follows.
- 6 (1) If *scalar-int-constant-expr* is specified, the value of the enumerator is the result of *scalar-int-constant-*
- 7 *expr*.
- 8 (2) If *scalar-int-constant-expr* is not specified and the enumerator is the first enumerator in *enum-def*,
- 9 the enumerator has the value 0.
- 10 (3) If *scalar-int-constant-expr* is not specified and the enumerator is not the first enumerator in *enum-*
- 11 *def*, its value is the result of adding 1 to the value of the enumerator that immediately precedes it
- 12 in the *enum-def*.

NOTE 4.66

Example of an enumeration definition:

```
ENUM, BIND(C)
  ENUMERATOR :: RED = 4, BLUE = 9
  ENUMERATOR YELLOW
END ENUM
```

The *kind type parameter* for this enumeration is processor dependent, but the processor is required to select a kind sufficient to represent the values 4, 9, and 10, which are the values of its enumerators. The following declaration might be equivalent to the above enumeration definition.

```
INTEGER(SELECTED_INT_KIND(2)), PARAMETER :: RED = 4, BLUE = 9, YELLOW = 10
```

An entity of the same *kind type parameter* value can be declared using the intrinsic function *KIND* with one of the enumerators as its argument, for example

```
INTEGER(KIND(RED)) :: X
```

NOTE 4.67

There is no difference in the effect of declaring the enumerators in multiple ENUMERATOR statements or in a single ENUMERATOR statement. The order in which the enumerators in an enumeration definition are declared is significant, but the number of ENUMERATOR statements is not.

4.7 Binary, octal, and hexadecimal literal constants

- 1 A binary, octal, or hexadecimal constant (*boz-literal-constant*) is a sequence of digits that represents an ordered sequence of bits. Such a constant has no type.

R464 *boz-literal-constant* **is** *binary-constant*
 or *octal-constant*
 or *hex-constant*

R465 *binary-constant* **is** B ' *digit* [*digit*] ... '
 or B " *digit* [*digit*] ... "

C4105 (R465) *digit* shall have one of the values 0 or 1.

R466 *octal-constant* **is** O ' *digit* [*digit*] ... '
 or O " *digit* [*digit*] ... "

C4106 (R466) *digit* shall have one of the values 0 through 7.

R467 *hex-constant* **is** Z ' *hex-digit* [*hex-digit*] ... '
 or Z " *hex-digit* [*hex-digit*] ... "

R468 *hex-digit* **is** *digit*
 or A
 or B
 or C
 or D
 or E
 or F

- 2 The *hex-digits* A through F represent the numbers ten through fifteen, respectively; they may be represented by their lower-case equivalents. Each digit of a *boz-literal-constant* represents a sequence of bits, according to its numerical interpretation, using the model of 13.3, with *z* equal to one for binary constants, three for octal constants or four for hexadecimal constants. A *boz-literal-constant* represents a sequence of bits that consists of the concatenation of the sequences of bits represented by its digits, in the order the digits are specified. The positions of bits in the sequence are numbered from right to left, with the position of the rightmost bit being zero. The length of a sequence of bits is the number of bits in the sequence. The processor shall allow the position of the leftmost nonzero bit to be at least $z - 1$, where *z* is the maximum value that could result from invoking the intrinsic function `STORAGE_SIZE` (13.8.175) with an argument that is a real or integer scalar of any kind supported by the processor.

C4107 (R464) A *boz-literal-constant* shall appear only as a *data-stmt-constant* in a `DATA statement`, or where explicitly allowed in subclause 13.8 as an actual argument of an *intrinsic* procedure.

4.8 Construction of array values

- 1 An array constructor constructs a rank-one array value from a sequence of scalar values, array values, and implied DO loops.

R469 *array-constructor* **is** (/ *ac-spec* /)
 or *lbracket ac-spec rbracket*

- 1 R470 *ac-spec* is *type-spec* ::
2 or [*type-spec* ::] *ac-value-list*
- 3 R471 *lbracket* is [
4 R472 *rbracket* is]
- 5 R473 *ac-value* is *expr*
6 or *ac-implied-do*
- 7 R474 *ac-implied-do* is (*ac-value-list* , *ac-implied-do-control*)
- 8 R475 *ac-implied-do-control* is [*integer-type-spec* ::] *ac-do-variable* = *scalar-int-expr* , ■
9 ■ *scalar-int-expr* [, *scalar-int-expr*]
- 10 R476 *ac-do-variable* is *do-variable*
- 11 C4108 (R470) If *type-spec* is omitted, each *ac-value* expression in the *array-constructor* shall have the same
12 declared type and kind type parameters.
- 13 C4109 (R470) If *type-spec* specifies an intrinsic type, each *ac-value* expression in the *array-constructor* shall be
14 of an intrinsic type that is in type conformance with a variable of type *type-spec* as specified in Table 7.8.
- 15 C4110 (R470) If *type-spec* specifies a derived type, the declared type of each *ac-value* expression in the *array-
16 constructor* shall be that derived type and shall have the same kind type parameter values as specified
17 by *type-spec*.
- 18 C4111 (R473) An *ac-value* shall not be unlimited polymorphic.
- 19 C4112 (R473) The declared type of an *ac-value* shall not be abstract.
- 20 C4113 (R474) The *ac-do-variable* of an *ac-implied-do* that is in another *ac-implied-do* shall not appear as the
21 *ac-do-variable* of the containing *ac-implied-do*.
- 22 2 If *type-spec* is omitted, corresponding length type parameters of the declared type of each *ac-value* expression
23 shall have the same value; in this case, the declared type and type parameters of the array constructor are those
24 of the *ac-value* expressions.
- 25 3 If *type-spec* appears, it specifies the declared type and type parameters of the array constructor. Each *ac-value*
26 expression in the *array-constructor* shall be compatible with intrinsic assignment to a variable of this type and
27 type parameters. Each value is converted to the type and type parameters of the *array-constructor* in accordance
28 with the rules of intrinsic assignment (7.2.1.3).
- 29 4 The dynamic type of an array constructor is the same as its declared type.
- 30 5 The character length of an *ac-value* in an *ac-implied-do* whose iteration count is zero shall not depend on the
31 value of the *ac-do-variable* and shall not depend on the value of an expression that is not a constant expression.
- 32 6 If an *ac-value* is a scalar expression, its value specifies an element of the array constructor. If an *ac-value* is
33 an array expression, the values of the elements of the expression, in array element order (6.5.3.2), specify the
34 corresponding sequence of elements of the array constructor. If an *ac-value* is an *ac-implied-do*, it is expanded to
35 form a sequence of elements under the control of the *ac-do-variable*, as in the DO construct (8.1.6.4).
- 36 7 For an *ac-implied-do*, the loop initialization and execution is the same as for a DO construct.
- 37 8 An empty sequence forms a zero-sized array.

NOTE 4.68

A one-dimensional array can be reshaped into any allowable array shape using the intrinsic function [RE-SHAPE](#) (13.8.155). An example is:

NOTE 4.68 (cont.)

```
X = (/ 3.2, 4.01, 6.5 /)
Y = RESHAPE (SOURCE = [ 2.0, [ 4.5, 4.5 ], X ], SHAPE = [ 3, 2 ])
```

This results in Y having the 3×2 array of values:

```
2.0  3.2
4.5  4.01
4.5  6.5
```

NOTE 4.69

Examples of array constructors containing an implied DO are:

```
(/ (I, I = 1, 1075) /)
```

and

```
[ 3.6, (3.6 / I, I = 1, N) ]
```

NOTE 4.70

Using the type definition for PERSON in Note 4.15, an example of the construction of a derived-type array value is:

```
[ PERSON (40, 'SMITH'), PERSON (20, 'JONES') ]
```

NOTE 4.71

Using the type definition for LINE in Note 4.26, an example of the construction of a derived-type scalar value with a rank-2 array component is:

```
LINE (RESHAPE ( [ 0.0, 0.0, 1.0, 2.0 ], [ 2, 2 ] ), 0.1, 1)
```

The intrinsic function [RESHAPE](#) is used to construct a value that represents a solid line from (0, 0) to (1, 2) of width 0.1 centimeters.

NOTE 4.72

Examples of zero-size array constructors are:

```
[ INTEGER :: ]
[ ( I, I = 1, 0) ]
```

NOTE 4.73

An example of an array constructor that specifies a length type parameter:

```
[ CHARACTER(LEN=7) :: 'Takata', 'Tanaka', 'Hayashi' ]
```

In this constructor, without the type specification, it would have been necessary to specify all of the constants with the same character length.

5 Attribute declarations and specifications

5.1 Attributes of procedures and data objects

- 1 Every data object has a type and **rank** and may have type parameters and other properties that determine the uses of the object. Collectively, these properties are the **attributes** of the object. The type of a named data object is either specified explicitly in a type declaration statement or determined implicitly by the first letter of its name (5.7). All of its **attributes** may be specified in a type declaration statement or individually in separate specification statements.
- 2 A function has a type and **rank** and may have type parameters and other **attributes** that determine the uses of the function. The type, **rank**, and type parameters are the same as those of the **function result**.
- 3 A subroutine does not have a type, **rank**, or type parameters, but may have other **attributes** that determine the uses of the subroutine.

5.2 Type declaration statement

R501 *type-declaration-stmt* **is** *declaration-type-spec* [[, *attr-spec*] ... ::] *entity-decl-list*

- 1 The type declaration statement specifies the type of the entities in the entity declaration list. The type and type parameters are those specified by *declaration-type-spec*, except that the character length type parameter may be overridden for an entity by the appearance of * *char-length* in its *entity-decl*.

R502 *attr-spec* **is** *access-spec*
 or ALLOCATABLE
 or ASYNCHRONOUS
 or CODIMENSION *lbracket coarray-spec rbracket*
 or CONTIGUOUS
 or DIMENSION (*array-spec*)
 or EXTERNAL
 or INTENT (*intent-spec*)
 or INTRINSIC
 or *language-binding-spec*
 or OPTIONAL
 or PARAMETER
 or POINTER
 or PROTECTED
 or SAVE
 or TARGET
 or VALUE
 or VOLATILE

C501 (R501) The same *attr-spec* shall not appear more than once in a given *type-declaration-stmt*.

C502 (R501) If a *language-binding-spec* with a NAME= specifier appears, the *entity-decl-list* shall consist of a single *entity-decl*.

C503 (R501) If a *language-binding-spec* is specified, the *entity-decl-list* shall not contain any procedure names.

- 2 The type declaration statement also specifies the **attributes** whose keywords appear in the *attr-spec*, except that

1 the **DIMENSION** attribute may be specified or overridden for an entity by the appearance of *array-spec* in its
 2 *entity-decl*, and the **CODIMENSION** attribute may be specified or overridden for an entity by the appearance of
 3 *coarray-spec* in its *entity-decl*.

4 R503 *entity-decl* is *object-name* [(*array-spec*)] ■
 5 ■ [*lbracket coarray-spec rbracket*] ■
 6 ■ [* *char-length*] [*initialization*]
 7 or *function-name* [* *char-length*]

8 C504 (R503) If the entity is not of type character, * *char-length* shall not appear.

9 C505 (R501) If *initialization* appears, a double-colon separator shall appear before the *entity-decl-list*.

10 C506 (R501) If the PARAMETER keyword appears, *initialization* shall appear in each *entity-decl*.

11 C507 (R503) An *initialization* shall not appear if *object-name* is a **dummy argument**, a function result, an object
 12 in a named **common block** unless the type declaration is in a block data program unit, an object in **blank common**, an
 13 **allocatable** variable, or an automatic object.

14 C508 (R503) The *function-name* shall be the name of an external function, an intrinsic function, a **dummy**
 15 **function**, a **procedure pointer**, or a statement function.

16 R504 *object-name* is *name*

17 C509 (R504) The *object-name* shall be the name of a data object.

18 R505 *initialization* is = *constant-expr*
 19 or => *null-init*
 20 or => *initial-data-target*

21 R506 *null-init* is *function-reference*

22 C510 (R503) If => appears in *initialization*, the entity shall have the **POINTER** attribute. If = appears in
 23 *initialization*, the entity shall not have the **POINTER** attribute.

24 C511 (R503) If *initial-data-target* appears, *object-name* shall be data-pointer-initialization compatible with it
 25 (4.5.4.6).

26 C512 (R506) The *function-reference* shall be a reference to the intrinsic function **NULL** with no arguments.

27 3 A name that identifies a specific intrinsic function has a type as specified in 13.7. An explicit type declaration statement is not
 28 required; however, it is permitted. Specifying a type for a generic intrinsic function name in a type declaration
 29 statement has no effect.

30 4 If *initialization* appears for a nonpointer entity,

- 31 • its type and **type parameters** shall conform as specified for intrinsic assignment (7.2.1.2);
- 32 • if the entity has implied shape, the rank of *initialization* shall be the same as the rank of the entity;
- 33 • if the entity does not have implied shape, *initialization* shall either be scalar or have the same shape as the
 34 entity.

NOTE 5.1

Examples of type declaration statements:

```

REAL A (10)
LOGICAL, DIMENSION (5, 5) :: MASK1, MASK2
COMPLEX :: CUBE_ROOT = (-0.5, 0.866)
INTEGER, PARAMETER :: SHORT = SELECTED_INT_KIND (4)
INTEGER (SHORT) K      ! Range at least -9999 to 9999.
```

NOTE 5.1 (cont.)

```

REAL (KIND (0.0D0)) B1
REAL (KIND = 2) B2
COMPLEX (KIND = KIND (0.0D0)) :: C
CHARACTER (LEN = 10, KIND = 2) TEXT2
CHARACTER CHAR, STRING *20
TYPE (PERSON) :: CHAIRMAN
TYPE(NODE), POINTER :: HEAD => NULL ( )
TYPE (humongous_matrix (k=8, d=1000)) :: MAT

```

(The last line above uses a type definition from Note 4.22.)

5.3 Automatic data objects

1 An [automatic data object](#) is a [nondummy data object](#) with a [type parameter](#) or [array bound](#) that depends on the value of a [specification-expr](#) that is not a [constant expression](#).

C513 An [automatic object](#) shall not have the [SAVE attribute](#).

2 If a type parameter in a [declaration-type-spec](#) or in a [char-length](#) in an [entity-decl](#) for a [local variable](#) of a subprogram or [BLOCK construct](#) is defined by an expression that is not a [constant expression](#), the type parameter value is established on entry to a procedure defined by the subprogram, or on execution of the [BLOCK statement](#), and is not affected by any redefinition or undefinition of the variables in the expression during execution of the procedure or [BLOCK construct](#).

5.4 Initialization

1 The appearance of [initialization](#) in an [entity-decl](#) for an entity without the [PARAMETER attribute](#) specifies that the entity is a variable with [explicit initialization](#). [Explicit initialization](#) alternatively may be specified in a [DATA statement](#) unless the variable is of a derived type for which [default initialization](#) is specified. If [initialization](#) is [= constant-expr](#), the variable is initially defined with the value specified by the [constant-expr](#); if necessary, the value is converted according to the rules of intrinsic assignment (7.2.1.3) to a value that agrees in type, type parameters, and shape with the variable. A variable, or part of a variable, shall not be [explicitly initialized](#) more than once in a program. If the variable is an array, it shall have its shape specified in either the type declaration statement or a previous attribute specification statement in the same [scoping unit](#).

2 If [null-init](#) appears, the initial association status of the object is [disassociated](#). If [initial-data-target](#) appears, the object is initially associated with the [target](#).

3 [Explicit initialization](#) of a variable that is not in a [common block](#) implies the [SAVE attribute](#), which may be confirmed by explicit specification.

5.5 Attributes

5.5.1 Attribute specification

1 An [attribute](#) may be explicitly specified by an [attr-spec](#) in a [type declaration statement](#) or by an attribute specification statement (5.6). The following constraints apply to [attributes](#).

C514 An entity shall not be explicitly given any [attribute](#) more than once in a [scoping unit](#).

C515 An [array-spec](#) for a nonallocatable nonpointer function result shall be an [explicit-shape-spec-list](#).

1 C516 The `ALLOCATABLE` or `POINTER` attribute shall not be specified for a `default-initialized dummy`
 2 `argument` of a procedure that has a `proc-language-binding-spec`.

3 5.5.2 Accessibility attribute

4 1 The accessibility attribute specifies the accessibility of an entity via a particular identifier.

5 R507 `access-spec` is `PUBLIC`
 6 or `PRIVATE`

7 C517 An `access-spec` shall appear only in the `specification-part` of a module.

8 2 An `access-spec` in a type declaration statement specifies the accessibility of the names of all the entities declared
 9 by that statement. An `access-spec` in a `derived-type-stmt` specifies the accessibility of the derived type name.
 10 Accessibility can also be specified by an `access-stmt`.

11 3 An identifier that is specified in a module or is accessible in a module by use association has either the `PUBLIC`
 12 `attribute` or `PRIVATE attribute`. An identifier whose accessibility is not explicitly specified and that is declared
 13 in the module has the default accessibility for that module (5.6.1). An identifier that is not declared in the module
 14 but which is accessible by use association is `PRIVATE` if and only if the default accessibility for each module via
 15 which it is accessed is `PRIVATE`, and `PUBLIC` otherwise.

Unresolved Technical Issue 013

Accessibility ambiguity

```
Module m1
  Real x
End Module
Module m2
  Use m1
  Private m1
  Asynchronous x
End Module
```

According to 5.6.1, the “default accessibility” of X in M2 is `PRIVATE`. But according to the second sentence of the paragraph above, the accessibility of X in M2 is the default accessibility in M2, which is `PUBLIC`.

Which is it?

Unresolved Technical Issue 014

Another accessibility ambiguity

```
Module m1
  Real,Public :: x
  Private
End Module
Module m2
  Use m1
  Private
  Public x
End Module
Module m3
  Use m2
  ! Hello X
End Module
```

Unresolved Technical Issue 014 (cont.)

X is accessed via module m2 (with default PRIVATE accessibility) and m1 (with default PRIVATE accessibility). Therefore by the third sentence in the paragraph above, the accessibility of X in m3 is PRIVATE. This is clearly wrong.

There are two points here:

1. The third sentence should not be talking about the default accessibility of a module; PRIVATE module-name makes all the entities accessed via that module default-private, it does not change what the default accessibility of that module is.
2. It needs to avoid recursing, it is only the accessibility statements in the module in question that affect accessibility of entities, not any modules that lie between the module in question and the ultimate module that defined the entity.

- 1 4 The default accessibility attribute for a module is PUBLIC unless it has been changed by a PRIVATE statement.
 2 Only an identifier that has the PUBLIC attribute in that module is available to be accessed from that module
 3 by use association.

NOTE 5.2

In order for an identifier to be accessed by [use association](#), it must have the [PUBLIC attribute](#) in the module from which it is accessed. It can nonetheless have the [PRIVATE attribute](#) in a module in which it is accessed by [use association](#), and therefore not be available for [use association](#) from that module.

NOTE 5.3

An example of an accessibility specification is:

```
REAL, PRIVATE :: X, Y, Z
```

4 5.5.3 ALLOCATABLE attribute

- 5 1 An entity with the [ALLOCATABLE attribute](#) is a variable for which space is allocated by an [ALLOCATE](#)
 6 [statement](#) (6.7.1) or by an [intrinsic assignment statement](#) (7.2.1.2).

7 5.5.4 ASYNCHRONOUS attribute

- 8 1 An entity with the [ASYNCHRONOUS attribute](#) is a variable that may be subject to asynchronous input/output
 9 or asynchronous communication.

- 10 2 The [base object](#) of a variable shall have the [ASYNCHRONOUS attribute](#) in a [scoping unit](#) if

- 11 • the variable appears in an executable statement or [specification expression](#) in that [scoping unit](#) and
- 12 • any statement of the [scoping unit](#) is executed while the variable is a pending input/output storage sequence
 13 affector (9.6.2.5) or a pending communication affector (15.10.4).

- 14 3 Use of a variable in an asynchronous data transfer statement can imply the [ASYNCHRONOUS attribute](#); see
 15 subclause 9.6.2.5.

- 16 4 An object with the [ASYNCHRONOUS attribute](#) may be associated with an object that does not have the
 17 [ASYNCHRONOUS attribute](#), including by [use](#) (11.2.2) or [host](#) association (16.5.1.4). If an object that is not a
 18 [local variable](#) of a [BLOCK construct](#) is specified to have the [ASYNCHRONOUS attribute](#) in the [specification-](#)
 19 [part](#) of the construct, the object has the attribute within the construct even if it does not have the attribute
 20 outside the construct. If an object has the [ASYNCHRONOUS attribute](#), then all of its subobjects also have the
 21 [ASYNCHRONOUS attribute](#).

NOTE 5.6

A [coarray](#) is permitted to be of a derived type with pointer or [allocatable](#) components. The [target](#) of such a pointer component is always on the same [image](#) as the pointer.

NOTE 5.7

This requirement for the [SAVE attribute](#) has the effect that [automatic coarrays](#) are not permitted; for example, the [coarray](#) WORK in the following code fragment is not valid.

```
SUBROUTINE SOLVE3(N,A,B)
INTEGER :: N
REAL    :: A(N) [*], B(N)
REAL    :: WORK(N) [*]    ! Not permitted
```

If this were permitted, it would require an implicit synchronization on entry to the procedure.

[Explicit-shape coarrays](#) that are declared in a subprogram and are not [dummy arguments](#) are required to have the [SAVE attribute](#) because otherwise they might be implemented as if they were [automatic coarrays](#).

NOTE 5.8

Examples of CODIMENSION attribute specifications are:

```
REAL W(100,100)[0:2,*]           ! Explicit-shape coarray
REAL, CODIMENSION[*] :: X       ! Scalar coarray
REAL, CODIMENSION[3,*] :: Y(:)  ! Assumed-shape coarray
REAL, CODIMENSION[:,ALLOCATABLE] :: Z(:,,:) ! Allocatable coarray
```

1 5.5.6.2 Allocatable coarray

2 1 A [coarray](#) with the [ALLOCATABLE attribute](#) has a specified [corank](#), but its [cobounds](#) are determined by
3 allocation or [argument association](#).

4 R510 *deferred-coshape-spec* is :

5 C528 A [coarray](#) with the [ALLOCATABLE attribute](#) shall have a [coarray-spec](#) that is a *deferred-coshape-spec-*
6 *list*.

7 2 The [corank](#) of an [allocatable coarray](#) is equal to the number of colons in its *deferred-coshape-spec-list*.

8 3 The [cobounds](#) of an unallocated [allocatable coarray](#) are undefined. No part of such a [coarray](#) shall be referenced
9 or defined; however, the [coarray](#) may appear as an argument to an intrinsic [inquiry function](#) as specified in 13.1.

10 4 The [cobounds](#) of an allocated [allocatable coarray](#) are those specified when the [coarray](#) is allocated.

11 5 The [cobounds](#) of an [allocatable coarray](#) are unaffected by any subsequent redefinition or undefinition of the
12 variables on which the [cobounds](#)' expressions depend.

13 5.5.6.3 Explicit-coshape coarray

14 1 An explicit-coshape coarray is a named [coarray](#) that has its [corank](#) and [cobounds](#) declared by an *explicit-coshape-*
15 *spec*.

16 R511 *explicit-coshape-spec* is $\left[\left[\textit{lower-cobound} : \right] \textit{upper-cobound}, \dots \right] \blacksquare$
17 $\blacksquare \left[\textit{lower-cobound} : \right]^*$

18 C529 A nonallocatable [coarray](#) shall have a [coarray-spec](#) that is an *explicit-coshape-spec*.

19 2 The [corank](#) is equal to one plus the number of *upper-cobounds*.

- 1 R512 *lower-cobound* is *specification-expr*
 2 R513 *upper-cobound* is *specification-expr*
 3 C530 (R511) A *lower-cobound* or *upper-cobound* that is not a *constant expression* shall appear only in a sub-
 4 program, *BLOCK construct*, or *interface body*.

- 5 3 If an explicit-coshape *coarray* is a *local variable* of a subprogram or *BLOCK construct* and has *cobounds* that are
 6 not *constant expressions*, the *cobounds* are determined on entry to a procedure defined by the subprogram, or
 7 on execution of the *BLOCK statement*, by evaluating the *cobounds* expressions. The *cobounds* of such a *coarray*
 8 are unaffected by the redefinition or undefinition of any variable during execution of the procedure or *BLOCK*
 9 *construct*.
 10 4 The values of each *lower-cobound* and *upper-cobound* determine the *cobounds* of the *coarray* along a particular
 11 *codimension*. The *cosubscript* range of the *coarray* in that *codimension* is the set of integer values between and
 12 including the lower and upper *cobounds*. If the lower *cobound* is omitted, the default value is 1. The upper
 13 *cobound* shall not be less than the lower *cobound*.

14 5.5.7 CONTIGUOUS attribute

- 15 C531 An entity with the *CONTIGUOUS attribute* shall be an *array pointer*, an *assumed-shape array*, or an
 16 *assumed-rank dummy data object*.

- 17 1 The *CONTIGUOUS attribute* specifies that an *assumed-shape array* is contiguous, that an *array pointer* can
 18 only be *pointer associated* with a *contiguous target*, or that an *assumed-rank dummy data object* is contiguous.

- 19 2 An object is *contiguous* if it is

- 20 (1) an object with the *CONTIGUOUS attribute*,
 21 (2) a nonpointer whole array that is not *assumed-shape*,
 22 (3) an *assumed-shape array* that is argument associated with an array that is contiguous,
 23 (4) an *assumed-rank dummy data object* whose *effective argument* is contiguous,
 24 (5) an array allocated by an *ALLOCATE statement*,
 25 (6) a *pointer associated* with a contiguous *target*, or
 26 (7) a nonzero-sized *array section* (6.5.3) provided that
 27 (a) its *base object* is *contiguous*,
 28 (b) it does not have a *vector subscript*,
 29 (c) the array element ordering of the elements of the section is the same as the array element
 30 ordering of those elements of the *base object*,
 31 (d) in the array element ordering of the *base object*, every element of the *base object* that is not
 32 an element of the section either precedes every element of the section or follows every element
 33 of the section,
 34 (e) if the array is of type character and a *substring-range* appears, the *substring-range* specifies all
 35 of the characters of the *parent-string* (6.4.1),
 36 (f) only its final *part-ref* has nonzero *rank*, and
 37 (g) it is not the real or imaginary part (6.4.4) of an array of type complex.

- 38 3 An object is not contiguous if it is an array subobject, and

- 39 • the object has two or more elements,
 40 • the elements of the object in array element order are not consecutive in the elements of the *base object*,
 41 • the object is not of type character with length zero, and
 42 • the object is not of a derived type that has no *ultimate components* other than zero-sized arrays and
 43 characters with length zero.

- 1 4 It is processor dependent whether any other object is contiguous.

NOTE 5.9

If a derived type has only one component that is not zero-sized, it is processor dependent whether a structure component of a contiguous array of that type is contiguous. That is, the derived type might contain padding on some processors.

NOTE 5.10

The **CONTIGUOUS** attribute makes it easier for a processor to enable optimizations that depend on the memory layout of the object occupying a contiguous block of memory. Examples of **CONTIGUOUS** attribute specifications are:

```
REAL, POINTER, CONTIGUOUS      :: SPTR(:)
REAL, CONTIGUOUS, DIMENSION(:, :) :: D
```

2 5.5.8 DIMENSION attribute

3 5.5.8.1 General

- 4 1 The **DIMENSION** attribute specifies that an entity is **assumed-rank** or an array. An **assumed-rank dummy data**
 5 **object** has the rank, shape, and size of its **effective argument**; otherwise, the **rank** or **rank** and shape is specified
 6 by its **array-spec**.

```
7 R514 dimension-spec          is DIMENSION ( array-spec )
8 R515 array-spec              is explicit-shape-spec-list
9                               or assumed-shape-spec-list
10                              or deferred-shape-spec-list
11                              or assumed-size-spec
12                              or implied-shape-spec
13                              or implied-shape-or-assumed-size-spec
14                              or assumed-rank-spec
```

NOTE 5.11

The maximum **rank** of an entity is fifteen minus the **corank**.

NOTE 5.12

Examples of **DIMENSION** attribute specifications are:

```
SUBROUTINE EX (N, A, B)
  REAL, DIMENSION (N, 10) :: W      ! Automatic explicit-shape array
  REAL A (:), B (0:)              ! Assumed-shape arrays
  REAL, POINTER :: D (:, :)        ! Array pointer
  REAL, DIMENSION (:), POINTER :: P ! Array pointer
  REAL, ALLOCATABLE, DIMENSION (:) :: E ! Allocatable array
  REAL, PARAMETER :: V(0:*) = [0.1, 1.1] ! Implied-shape array
```

15 5.5.8.2 Explicit-shape array

```
16 R516 explicit-shape-spec      is [ lower-bound : ] upper-bound
17 R517 lower-bound              is specification-expr
18 R518 upper-bound              is specification-expr
```

1 C532 (R516) An *explicit-shape-spec* whose **bounds** are not **constant expressions** shall appear only in a subpro-
 2 gram, derived type definition, **BLOCK construct**, or **interface body**.

3 1 An **explicit-shape array** is an array whose shape is explicitly declared by an *explicit-shape-spec-list*. The **rank** is
 4 equal to the number of *explicit-shape-specs*.

5 2 An **explicit-shape array** that is a named local variable of a subprogram or **BLOCK construct** may have **bounds**
 6 that are not **constant expressions**. The **bounds**, and hence shape, are determined on entry to a procedure defined
 7 by the subprogram, or on execution of the **BLOCK statement**, by evaluating the bounds' expressions. The
 8 **bounds** of such an array are unaffected by the redefinition or undefinition of any variable during execution of the
 9 procedure or **BLOCK construct**.

10 3 The values of each *lower-bound* and *upper-bound* determine the bounds of the array along a particular dimension
 11 and hence the extent of the array in that dimension. If *lower-bound* appears it specifies the lower bound; otherwise
 12 the lower bound is 1. The value of a lower bound or an upper bound may be positive, negative, or zero. The
 13 subscript range of the array in that dimension is the set of integer values between and including the lower and
 14 upper bounds, provided the upper bound is not less than the lower bound. If the upper bound is less than the
 15 lower bound, the range is empty, the extent in that dimension is zero, and the array is of zero size.

16 5.5.8.3 Assumed-shape array

17 1 An **assumed-shape array** is a nonallocatable nonpointer **dummy argument** array that takes its shape from its
 18 **effective argument**.

19 R519 *assumed-shape-spec* is [*lower-bound*] :

20 2 The **rank** is equal to the number of colons in the *assumed-shape-spec-list*.

21 3 The extent of a dimension of an **assumed-shape array dummy argument** is the extent of the corresponding
 22 dimension of its **effective argument**. If the lower bound value is d and the extent of the corresponding dimension
 23 of its **effective argument** is s , then the value of the upper bound is $s + d - 1$. If *lower-bound* appears it specifies
 24 the lower bound; otherwise the lower bound is 1.

25 5.5.8.4 Deferred-shape array

26 1 A **deferred-shape array** is an **allocatable** array or an **array pointer**. (An **allocatable** array has the **ALLOCATABLE**
 27 **attribute**; an **array pointer** has the **POINTER attribute**.)

28 R520 *deferred-shape-spec* is :

29 C533 An array with the **POINTER** or **ALLOCATABLE attribute** shall have an *array-spec* that is a *deferred-*
 30 *shape-spec-list*.

31 2 The **rank** is equal to the number of colons in the *deferred-shape-spec-list*.

32 3 The size, bounds, and shape of an unallocated **allocatable** array or a **disassociated array pointer** are undefined.
 33 No part of such an array shall be referenced or defined; however, the array may appear as an argument to an
 34 intrinsic **inquiry function** as specified in 13.1.

35 4 The bounds of each dimension of an allocated **allocatable** array are those specified when the array is allocated
 36 or, if it is a **dummy argument**, when it is argument associated with an allocated **effective argument**.

37 5 The bounds of each dimension of an associated **array pointer**, and hence its shape, may be specified

- 38 • in an **ALLOCATE statement** (6.7.1) when the **target** is allocated,
- 39 • by pointer assignment (7.2.2), or
- 40 • if it is a **dummy argument**, by **argument association** with a nonpointer **actual argument** or an associated
 41 pointer **effective argument**.

1 6 The bounds of an [array pointer](#) or [allocatable](#) array are unaffected by any subsequent redefinition or undefinition
2 of variables on which the bounds' expressions depend.

3 5.5.8.5 Assumed-size array

4 1 An [assumed-size array](#) is a [dummy argument](#) array whose size is assumed from that of its [effective argument](#), or
5 the associate name of a [RANK \(* \)](#) block in a [SELECT RANK construct](#). The [rank](#) and extents may differ for
6 the [effective](#) and [dummy](#) arguments; only the size of the [effective argument](#) is assumed by the [dummy argument](#).
7 A [dummy argument](#) is declared to be an [assumed-size array](#) by an [assumed-size-spec](#) or an [implied-shape-or-](#)
8 [assumed-size-spec](#).

9 R521 *assumed-implied-spec* is [*lower-bound* :] *

10 R522 *assumed-size-spec* is *explicit-shape-spec-list*, *assumed-implied-spec*

11 C534 An object whose array bounds are specified by an [assumed-size-spec](#) shall be a [dummy data object](#).

12 C535 An [assumed-size array](#) with the [INTENT \(OUT\)](#) attribute shall not be [polymorphic](#), [finalizable](#), of a
13 type with an [allocatable ultimate component](#), or of a type for which [default initialization](#) is specified.

14 R523 *implied-shape-or-assumed-size-spec* is assumed-implied-spec

15 C536 An object whose array bounds are specified by an [implied-shape-or-assumed-size-spec](#) shall be a dummy
16 data object or a named constant.

17 2 The size of an [assumed-size array](#) is determined as follows.

- 18 • If the [effective argument](#) associated with the [assumed-size](#) dummy array is an array of any type other than
19 default character, the size is that of the [effective argument](#).
- 20 • If the [actual argument](#) corresponding to the [assumed-size](#) dummy array is an array element of any type
21 other than default character with a subscript order value of r ([6.5.3.2](#)) in an array of size x , the size of the
22 dummy array is $x - r + 1$.
- 23 • If the [actual argument](#) is a default character array, default character array element, or a default character
24 array element substring ([6.4.1](#)), and if it begins at [character storage unit](#) t of an array with c [character](#)
25 [storage units](#), the size of the dummy array is $\text{MAX}(\text{INT}((c - t + 1)/e), 0)$, where e is the length of an
26 element in the dummy character array.
- 27 • If the [actual argument](#) is a default character scalar that is not an array element or array element substring
28 [designator](#), the size of the dummy array is $\text{MAX}(\text{INT}(l/e), 0)$, where e is the length of an element in the
29 dummy character array and l is the length of the [actual argument](#).

30 3 The [rank](#) is equal to one plus the number of [explicit-shape-specs](#).

31 4 An [assumed-size array](#) has no upper bound in its last dimension and therefore has no extent in its last dimension
32 and no shape. An [assumed-size array](#) shall not appear in a context that requires its shape.

33 5 If a list of [explicit-shape-specs](#) appears, it specifies the bounds of the first [rank](#)–1 dimensions. If [lower-bound](#)
34 appears it specifies the lower bound of the last dimension; otherwise that lower bound is 1. An [assumed-size](#)
35 [array](#) may be subscripted or sectioned ([6.5.3.3](#)). The upper bound shall not be omitted from a subscript triplet
36 in the last dimension.

37 6 If an [assumed-size array](#) has bounds that are not [constant expressions](#), the bounds are determined on entry to
38 the procedure. The bounds of such an array are unaffected by the redefinition or undefinition of any variable
39 during execution of the procedure.

40 5.5.8.6 Implied-shape array

41 1 An implied-shape array is a [named constant](#) that takes its shape from the [constant-expr](#) in its declaration. A
42 named constant is declared to be an implied-shape array with an [array-spec](#) that is an [implied-shape-or-assumed-](#)

1 *size-spec* or an *implied-shape-spec*.

2 R524 *implied-shape-spec* is *assumed-implied-spec*, *assumed-implied-spec-list*

3 C537 An implied-shape array shall be a **named constant**.

4 2 The **rank** of an implied-shape array is the number of *assumed-implied-specs* in its *array-spec*.

5 3 The extent of each dimension of an implied-shape array is the same as the extent of the corresponding dimension
6 of the *constant-expr*. The lower bound of each dimension is *lower-bound*, if it appears, and 1 otherwise; the upper
7 bound is one less than the sum of the lower bound and the extent.

8 **5.5.8.7 Assumed-rank entity**

9 1 An assumed-rank entity is a **dummy data object** whose **rank** is assumed from its **effective argument**, or the associate
10 name of a **RANK DEFAULT** block in a **SELECT RANK construct**; this rank can be zero. An assumed-rank
11 entity is declared with an *array-spec* that is an *assumed-rank-spec*.

12 R525 *assumed-rank-spec* is ..

13 C538 An assumed-rank entity shall be a **dummy data object** that does not have the **CODIMENSION** or **VALUE**
14 attribute.

15 C539 An assumed-rank variable name shall not appear in a **designator** or expression except as an **actual**
16 **argument** that corresponds to a **dummy argument** that is assumed-rank, the argument of the function
17 **C_LOC** from the intrinsic module **ISO_C_BINDING** (15.2.3.6), the first **dummy argument** of an **intrinsic**
18 **inquiry function**, or the selector of a **SELECT RANK statement**.

19 C540 If an **assumed-size** or nonallocatable nonpointer assumed-rank array is an **actual argument** that corres-
20 ponds to a **dummy argument** that is an **INTENT (OUT)** assumed-rank array, it shall not be **polymorphic**,
21 **finalizable**, of a type with an **allocatable ultimate component**, or of a type for which **default initialization**
22 is specified.

23 **5.5.9 EXTERNAL attribute**

24 1 The **EXTERNAL attribute** specifies that an entity is an **external procedure**, **dummy procedure**, **procedure pointer**,
25 or block data subprogram.

26 C541 An entity shall not have both the **EXTERNAL attribute** and the **INTRINSIC attribute**.

27 C542 In an external subprogram, the **EXTERNAL attribute** shall not be specified for a procedure defined by
28 the subprogram.

29 2 If an **external procedure** or **dummy procedure** is used as an **actual argument** or is the **target** of a **procedure pointer**
30 **assignment**, it shall be declared to have the **EXTERNAL attribute**.

31 3 A procedure that has both the **EXTERNAL** and **POINTER** attributes is a **procedure pointer**.

NOTE 5.13

The **EXTERNAL attribute** can be specified in a **type declaration statement**, by an **interface body** (12.4.3.2),
by an **EXTERNAL statement** (12.4.3.6), or by a **procedure declaration statement** (12.4.3.7).

32 **5.5.10 INTENT attribute**

33 1 The **INTENT attribute** specifies the intended use of a **dummy argument**. An **INTENT (IN)** **dummy argument**
34 is suitable for receiving data from the invoking **scoping unit**, an **INTENT (OUT)** **dummy argument** is suitable
35 for returning data to the invoking **scoping unit**, and an **INTENT (INOUT)** **dummy argument** is suitable for use
36 both to receive data from and to return data to the invoking **scoping unit**.

- 1 R526 *intent-spec* **is** IN
 2 **or** OUT
 3 **or** INOUT
- 4 C543 An entity with the **INTENT** attribute shall be a **dummy data object** or a dummy procedure pointer.
- 5 C544 (R526) A nonpointer object with the **INTENT (IN)** attribute shall not appear in a variable definition
 6 context (16.6.7).
- 7 C545 A pointer with the **INTENT (IN)** attribute shall not appear in a pointer association context (16.6.8).
- 8 C546 An **INTENT (OUT)** **dummy argument** of a nonintrinsic procedure shall not be an **allocatable coarray** or
 9 have a **subobject** that is an **allocatable coarray**.
- 10 C547 An entity with the **INTENT (OUT)** attribute shall not be of, or have a **subcomponent** of, type **EVENT_-**
 11 **TYPE** (13.9.2.9) or **LOCK_TYPE** (13.9.2.17) from the intrinsic module **ISO_FORTRAN_ENV**.
- 12 2 The **INTENT (IN)** attribute for a nonpointer **dummy argument** specifies that it shall neither be defined nor
 13 become undefined during the invocation and execution of the procedure. The **INTENT (IN)** attribute for a
 14 pointer **dummy argument** specifies that during the invocation and execution of the procedure its association shall
 15 not be changed except that it may become undefined if the **target** is deallocated other than through the pointer
 16 (16.5.2.5).
- 17 3 The **INTENT (OUT)** attribute for a nonpointer **dummy argument** specifies that the **dummy argument** becomes
 18 undefined on invocation of the procedure, except for any subcomponents that are **default-initialized** (4.5.4.6). Any
 19 **actual argument** that corresponds to such a **dummy argument** shall be **definable**. The **INTENT (OUT)** attribute
 20 for a pointer **dummy argument** specifies that on invocation of the procedure the **pointer association** status of the
 21 **dummy argument** becomes undefined. Any **actual argument** that corresponds to such a pointer dummy shall be
 22 a pointer variable. Any undefinition or definition implied by association of an **actual argument** with an **INTENT**
 23 **(OUT)** **dummy argument** shall not affect any other entity within the statement that invokes the procedure.
- 24 4 The **INTENT (INOUT)** attribute for a nonpointer **dummy argument** specifies that any **actual argument** that
 25 corresponds to the **dummy argument** shall be **definable**. The **INTENT (INOUT)** attribute for a pointer **dummy**
 26 **argument** specifies that any **actual argument** that corresponds to the **dummy argument** shall be a pointer variable.

NOTE 5.14

The **INTENT** attribute for an **allocatable dummy argument** applies to both the allocation status and the definition status. An **actual argument** that corresponds to an **INTENT (OUT)** **allocatable dummy argument** is deallocated on procedure invocation (6.7.3.2). To avoid this deallocation for coarrays, **INTENT (OUT)** is not allowed for a **dummy argument** that is an **allocatable coarray** or has a **subobject** that is an **allocatable coarray**.

- 27 5 If no **INTENT** attribute is specified for a **dummy argument**, its use is subject to the limitations of its **effective**
 28 **argument** (12.5.2).
- 29 6 If an object has an **INTENT** attribute, then all of its **subobjects** have the same **INTENT** attribute.

NOTE 5.15

An example of **INTENT** specification is:

```
SUBROUTINE MOVE (FROM, TO)
  USE PERSON_MODULE
  TYPE (PERSON), INTENT (IN) :: FROM
  TYPE (PERSON), INTENT (OUT) :: TO
```

NOTE 5.16

If a **dummy argument** is a derived-type object with a pointer component, then the pointer as a pointer is a subobject of the **dummy argument**, but the **target** of the pointer is not. Therefore, the restrictions on subobjects of the **dummy argument** apply to the pointer in contexts where it is used as a pointer, but not in contexts where it is dereferenced to indicate its **target**. For example, if X is a **dummy argument** of derived type with an integer pointer component P, and X is **INTENT (IN)**, then the statement

```
X%P => NEW_TARGET
```

is prohibited, but

```
X%P = 0
```

is allowed (provided that X%P is associated with a **definable target**).

Similarly, the **INTENT** restrictions on pointer **dummy arguments** apply only to the association of the **dummy argument**; they do not restrict the operations allowed on its **target**.

NOTE 5.17

Argument intent specifications serve several purposes in addition to documenting the intended use of **dummy arguments**. A processor can check whether an **INTENT (IN) dummy argument** is used in a way that could redefine it. A slightly more sophisticated processor could check to see whether an **INTENT (OUT) dummy argument** could possibly be referenced before it is defined. If the procedure's **interface** is explicit, the processor can also verify that **actual arguments** corresponding to **INTENT (OUT)** or **INTENT (INOUT) dummy arguments** are **definable**. A more sophisticated processor could use this information to optimize the translation of the referencing **scoping unit** by taking advantage of the fact that **actual arguments** corresponding to **INTENT (IN) dummy arguments** will not be changed and that any prior value of an **actual argument** corresponding to an **INTENT (OUT) dummy argument** will not be referenced and could thus be discarded.

INTENT (OUT) means that the value of the argument after invoking the procedure is entirely the result of executing that procedure. If an argument might not be redefined and it is desired to have the argument retain its value in that case, **INTENT (OUT)** cannot be used because it would cause the argument to become undefined; however, **INTENT (INOUT)** can be used, even if there is no explicit reference to the value of the dummy argument.

INTENT (INOUT) is not equivalent to omitting the **INTENT attribute**. The **actual argument** corresponding to an **INTENT (INOUT) dummy argument** is always required to be **definable**, while an **actual argument** corresponding to a **dummy argument** without an **INTENT attribute** need be **definable** only if the **dummy argument** is actually redefined.

1 5.5.11 INTRINSIC attribute

2 1 The **INTRINSIC attribute** specifies that the entity is an intrinsic procedure. The procedure name may be a
3 generic name (13.6), a **specific name** (13.7), or both.

4 2 If the **specific name** of an intrinsic procedure (13.7) is used as an **actual argument**, the name shall be explicitly specified to have the
5 **INTRINSIC attribute**. Note that a specific intrinsic procedure listed in Table 13.3 is not permitted to be used as an **actual argument**
6 (C1240).

7 C548 If the generic name of an intrinsic procedure is explicitly declared to have the **INTRINSIC attribute**,
8 and it is also the generic name of one or more **generic interfaces** (12.4.3.2) accessible in the same **scoping**
9 **unit**, the procedures in the interfaces and the generic intrinsic procedure shall all be functions or all be
10 subroutines.

5.5.12 OPTIONAL attribute

- 1 The **OPTIONAL attribute** specifies that the **dummy argument** need not have a corresponding **actual argument** in a **reference** to the procedure (12.5.2.12).

C549 An entity with the **OPTIONAL attribute** shall be a **dummy argument**.

NOTE 5.18

The intrinsic function **PRESENT** (13.8.144) can be used to determine whether an optional **dummy argument** has a corresponding **actual argument**.

5.5.13 PARAMETER attribute

- 1 The **PARAMETER attribute** specifies that an entity is a **named constant**. The entity has the value specified by its **constant-expr**, converted, if necessary, to the type, type parameters and shape of the entity.

C550 An entity with the **PARAMETER attribute** shall not be a **variable**, a **coarray**, or a **procedure**.

C551 An expression that specifies a **length type parameter** or array bound of a named constant shall be a constant expression.

- 2 A **named constant** shall not be referenced unless it has been defined previously; it may be defined previously in the same statement.

NOTE 5.19

Examples of declarations with a **PARAMETER attribute** are:

```
REAL, PARAMETER :: ONE = 1.0, Y = 4.1 / 3.0
INTEGER, DIMENSION (3), PARAMETER :: ORDER = (/ 1, 2, 3 /)
TYPE(NODE), PARAMETER :: DEFAULT = NODE(0, NULL ( ))
```

5.5.14 POINTER attribute

- 1 Entities with the **POINTER attribute** can be associated with different data objects or procedures during execution of a program. A pointer is either a data pointer or a procedure pointer. Procedure pointers are described in 12.4.3.7.

C552 An entity with the **POINTER attribute** shall not have the **ALLOCATABLE**, **INTRINSIC**, or **TARGET** attribute, and shall not be a **coarray**.

C553 A procedure with the **POINTER attribute** shall have the **EXTERNAL attribute**.

- 2 A data pointer shall not be referenced unless it is **pointer associated** with a **target** object that is defined. A data pointer shall not be defined unless it is **pointer associated** with a **target** object that is **definable**.

- 3 If a data pointer is associated, the values of its **deferred type parameters** are the same as the values of the corresponding type parameters of its **target**.

- 4 A **procedure pointer** shall not be referenced unless it is **pointer associated** with a **target** procedure.

NOTE 5.20

Examples of **POINTER attribute** specifications are:

```
TYPE (NODE), POINTER :: CURRENT, TAIL
REAL, DIMENSION (:, :), POINTER :: IN, OUT, SWAP
```

5.5.15 PROTECTED attribute

- 1 The **PROTECTED attribute** imposes limitations on the usage of module entities.
- C554 The **PROTECTED attribute** shall be specified only in the specification part of a module.
- C555 An entity with the **PROTECTED attribute** shall be a procedure pointer or variable.
- C556 An entity with the **PROTECTED attribute** shall not be in a **common block**.
- C557 A nonpointer object that has the **PROTECTED attribute** and is accessed by **use association** shall not appear in a variable definition context (16.6.7) or as the *data-target* or *proc-target* in a *pointer-assignment-stmt*.
- C558 A pointer that has the **PROTECTED attribute** and is accessed by **use association** shall not appear in a pointer association context (16.6.8).
- 2 Other than within the module in which an entity is given the **PROTECTED attribute**, or within any of its **descendants**,
- if it is a nonpointer object, it is not **definable**, and
 - if it is a pointer, its association status shall not be changed except that it may become undefined if its **target** is deallocated other than through the pointer (16.5.2.5) or if its **target** becomes undefined by execution of a **RETURN** or **END** statement.
- 3 If an object has the **PROTECTED attribute**, all of its subobjects have the **PROTECTED attribute**.

NOTE 5.21

An example of the **PROTECTED attribute**:

```

MODULE temperature
  REAL, PROTECTED :: temp_c, temp_f
CONTAINS
  SUBROUTINE set_temperature_c(c)
    REAL, INTENT(IN) :: c
    temp_c = c
    temp_f = temp_c*(9.0/5.0) + 32
  END SUBROUTINE
END MODULE

```

The **PROTECTED attribute** ensures that the variables `temp_c` and `temp_f` cannot be modified other than via the `set_temperature_c` procedure, thus keeping them consistent with each other.

5.5.16 SAVE attribute

- 1 The **SAVE attribute** specifies that a local variable of a **program unit** or subprogram retains its association status, allocation status, definition status, and value after execution of a **RETURN** or **END** statement unless it is a pointer and its **target** becomes undefined (16.5.2.5(6)). If it is a local variable of a subprogram it is shared by all instances (12.6.2.4) of the subprogram.
- 2 The **SAVE attribute** specifies that a local variable of a **BLOCK construct** retains its association status, allocation status, definition status, and value after termination of the construct unless it is a pointer and its **target** becomes undefined (16.5.2.5(7)). If the **BLOCK construct** is within a subprogram the variable is shared by all instances (12.6.2.4) of the subprogram.
- 3 Giving a **common block** the **SAVE attribute** confers the attribute on all entities in the **common block**.
- C559 An entity with the **SAVE attribute** shall be a **common block**, variable, or procedure pointer.

1 C560 The **SAVE attribute** shall not be specified for a **dummy argument**, a function result, an **automatic data**
2 **object**, or an object that is in a **common block**.

3 4 A variable, **common block**, or procedure pointer declared in the **scoping unit** of a main program, module, or
4 submodule implicitly has the **SAVE attribute**, which may be confirmed by explicit specification. If a **common block**
5 has the **SAVE attribute** in any other kind of **scoping unit**, it shall have the **SAVE attribute** in every **scoping unit** that is not of a
6 main program, module, or submodule.

7 5.5.17 TARGET attribute

8 1 The **TARGET attribute** specifies that a data object may have a **pointer associated** with it (7.2.2). An object
9 without the **TARGET attribute** shall not have a **pointer associated** with it.

10 C561 An entity with the **TARGET attribute** shall be a variable.

11 C562 An entity with the **TARGET attribute** shall not have the **POINTER attribute**.

12 2 If an object has the **TARGET attribute**, then all of its nonpointer subobjects also have the **TARGET attribute**.

NOTE 5.22

In addition to variables explicitly declared to have the **TARGET attribute**, the objects created by allocation of pointers (6.7.1.4) have the **TARGET attribute**.

NOTE 5.23

Examples of **TARGET attribute** specifications are:

```
TYPE (NODE), TARGET :: HEAD
REAL, DIMENSION (1000, 1000), TARGET :: A, B
```

NOTE 5.24

Every **object designator** that starts from an object with the **TARGET attribute** will have either the **TARGET** or **POINTER** attribute. If pointers are involved, the **designator** might not necessarily be a subobject of the original object, but because a pointer can point only to an entity with the **TARGET attribute**, there is no way to end up at a nonpointer that does not have the **TARGET attribute**.

13 5.5.18 VALUE attribute

14 1 The **VALUE attribute** specifies a type of **argument association** (12.5.2.4) for a **dummy argument**.

15 C563 An entity with the **VALUE attribute** shall be a **dummy data object**. It shall not be an **assumed-size**
16 **array**, a **coarray**, or a variable with a **coarray ultimate component**.

17 C564 An entity with the **VALUE attribute** shall not have the **ALLOCATABLE**, **INTENT (INOUT)**, **INTENT**
18 **(OUT)**, **POINTER**, or **VOLATILE** attributes.

19 5.5.19 VOLATILE attribute

20 1 The **VOLATILE attribute** specifies that an object may be referenced, defined, or become undefined, by means
21 not specified by the program. A pointer with the **VOLATILE attribute** may additionally have its association
22 status, **dynamic type** and type parameters, and array bounds changed by means not specified by the program.
23 An **allocatable** object with the **VOLATILE attribute** may additionally have its allocation status, **dynamic type**
24 and type parameters, and array bounds changed by means not specified by the program.

25 C565 An entity with the **VOLATILE attribute** shall be a variable that is not an **INTENT (IN) dummy argu-**
26 **ment**.

- 1 C566 The **VOLATILE attribute** shall not be specified for a **coarray** that is accessed by use (11.2.2) or host
2 (16.5.1.4) association.
- 3 C567 Within a **BLOCK construct** (8.1.4), the **VOLATILE attribute** shall not be specified for a **coarray** that is
4 not a **construct entity** (16.4) of that construct.
- 5 2 A noncoarray object that has the **VOLATILE attribute** may be associated with an object that does not have
6 the **VOLATILE attribute**, including by **use** (11.2.2) or **host** association (16.5.1.4). If an object that is not a
7 **local variable** of a **BLOCK construct** is specified to have the **VOLATILE attribute** in the *specification-part* of
8 the construct, the object has the attribute within the construct even if it does not have the attribute outside the
9 construct. The relationship between **coarrays**, the **VOLATILE attribute**, and **argument association** is described
10 in 12.5.2.8. The relationship between **coarrays**, the **VOLATILE attribute**, and **pointer association** is
11 described in 7.2.2.3.
- 12 3 A pointer should have the **VOLATILE attribute** if its target has the **VOLATILE attribute**. If, by means not
13 specified by the program, the target is referenced, defined, or becomes undefined, the pointer shall have the
14 **VOLATILE attribute**. All members of an EQUIVALENCE group should have the **VOLATILE attribute** if any member has the
15 **VOLATILE attribute**.
- 16 4 If an object has the **VOLATILE attribute**, then all of its subobjects also have the **VOLATILE attribute**.
- 17 5 The Fortran processor should use the most recent definition of a volatile object each time its value is required.
18 When a volatile object is defined by means of Fortran, it should make that definition available to the non-Fortran
19 parts of the program as soon as possible.

20 5.6 Attribute specification statements

21 5.6.1 Accessibility statement

- 22 R527 *access-stmt* is *access-spec* [[*::*] *access-id-list*]
- 23 R528 *access-id* is *access-name*
24 or *generic-spec*
- 25 C568 (R527) An *access-stmt* shall appear only in the *specification-part* of a module. Only one accessibility
26 statement with an omitted *access-id-list* is permitted in the *specification-part* of a module.
- 27 C569 (R528) Each *access-name* shall be the name of a module, variable, procedure, derived type, **named**
28 **constant**, or namelist group.
- 29 C570 A module whose name appears in an *access-stmt* shall be referenced by a **USE statement** in the **scoping**
30 **unit** that contains the *access-stmt*.
- 31 C571 The name of a module shall appear at most once in all of the *access-stmts* in a module.
- 32 1 An *access-stmt* with an *access-id-list* specifies the **accessibility attribute**, **PUBLIC** or **PRIVATE**, of each *access-id*
33 in the list that is not a module name. Appearance of a module name in an *access-stmt* specifies the default
34 accessibility of the identifiers of entities accessed from that module. An *access-stmt* without an *access-id* list
35 specifies the default accessibility of the identifiers of entities declared in the module, and of entities accessed from
36 a module whose name does not appear in any *access-stmt* in the module. If an identifier is accessed from another
37 module and also declared locally, it has the default accessibility of a locally declared identifier. The statement
38 **PUBLIC**
39 specifies a default of public accessibility. The statement
40 **PRIVATE**
41 specifies a default of private accessibility. If no such statement appears in a module, the default is public
42 accessibility.

NOTE 5.25

Examples of accessibility statements are:

```
MODULE EX
  PRIVATE
  PUBLIC :: A, B, C, ASSIGNMENT (=), OPERATOR (+)
```

NOTE 5.26

The following is an example of using an accessibility statement on a module name.

```
MODULE m2
  USE m1
  ! We want to use the types and procedures in m1, but we only want to
  ! re-export m_type and our own procedures.
  PRIVATE m1
  PUBLIC m_type
  ... definitions for our own entities and module procedures.
END MODULE
```

1 **5.6.2 ALLOCATABLE statement**2 R529 *allocatable-stmt* is ALLOCATABLE [::] *allocatable-decl-list*3 R530 *allocatable-decl* is *object-name* [(*array-spec*)] ■
4 ■ [*lbracket coarray-spec rbracket*]5 1 The ALLOCATABLE statement specifies the **ALLOCATABLE attribute** (5.5.3) for a list of objects.**NOTE 5.27**

An example of an ALLOCATABLE statement is:

```
REAL A, B (:), SCALAR
ALLOCATABLE :: A (:, :), B, SCALAR
```

6 **5.6.3 ASYNCHRONOUS statement**7 R531 *asynchronous-stmt* is ASYNCHRONOUS [::] *object-name-list*8 1 The ASYNCHRONOUS statement specifies the **ASYNCHRONOUS attribute** (5.5.4) for a list of objects.9 **5.6.4 BIND statement**10 R532 *bind-stmt* is *language-binding-spec* [::] *bind-entity-list*11 R533 *bind-entity* is *entity-name*
12 or / *common-block-name* /13 C572 (R532) If the *language-binding-spec* has a **NAME= specifier**, the *bind-entity-list* shall consist of a single
14 *bind-entity*.15 1 The BIND statement specifies the **BIND attribute** for a list of variables and **common blocks**.16 **5.6.5 CODIMENSION statement**17 R534 *codimension-stmt* is CODIMENSION [::] *codimension-decl-list*

1 R535 *codimension-decl* is *coarray-name lbracket coarray-spec rbracket*

2 1 The CODIMENSION statement specifies the [CODIMENSION attribute \(5.5.6\)](#) for a list of objects.

NOTE 5.28

An example of a CODIMENSION statement is:

```
CODIMENSION a[*], b[3,*], c[:]
```

3 5.6.6 CONTIGUOUS statement

4 R536 *contiguous-stmt* is CONTIGUOUS [::] *object-name-list*

5 1 The CONTIGUOUS statement specifies the [CONTIGUOUS attribute \(5.5.7\)](#) for a list of objects.

6 5.6.7 DATA statement

7 R537 *data-stmt* is DATA *data-stmt-set* [[,] *data-stmt-set*] ...

8 1 The DATA statement specifies [explicit initialization \(5.4\)](#).

9 2 If a nonpointer variable has [default initialization](#), it shall not appear in a *data-stmt-object-list*.

10 3 A variable that appears in a DATA statement and has not been typed previously may appear in a subsequent type
11 declaration only if that declaration confirms the implicit typing. An array name, [array section](#), or array element
12 that appears in a DATA statement shall have had its array properties established by a previous specification
13 statement.

14 4 Except for variables in named [common blocks](#), a named variable has the [SAVE attribute](#) if any part of it is initialized
15 in a DATA statement, and this may be confirmed by explicit specification.

16 R538 *data-stmt-set* is *data-stmt-object-list* / *data-stmt-value-list* /

17 R539 *data-stmt-object* is *variable*
18 or *data-implied-do*

19 R540 *data-implied-do* is (*data-i-do-object-list* , [*integer-type-spec* ::] *data-i-do-variable* = ■
20 ■ *scalar-int-constant-expr* , ■
21 ■ *scalar-int-constant-expr* ■
22 ■ [, *scalar-int-constant-expr*])

23 R541 *data-i-do-object* is *array-element*
24 or *scalar-structure-component*
25 or *data-implied-do*

26 R542 *data-i-do-variable* is *do-variable*

27 C573 A *data-stmt-object* or *data-i-do-object* shall not be a [coindexed](#) variable.

28 C574 (R539) A *data-stmt-object* that is a *variable* shall be a *designator*. Each subscript, section subscript,
29 substring starting point, and substring ending point in the variable shall be a [constant expression](#).

30 C575 (R539) A variable whose *designator* appears as a *data-stmt-object* or a *data-i-do-object* shall not be a
31 [dummy argument](#), accessed by use or [host](#) association, in a named [common block](#) unless the DATA statement is
32 in a block data program unit, in [blank common](#), a function name, a function result name, an [automatic object](#),
33 or an [allocatable](#) variable.

34 C576 (R539) A *data-i-do-object* or a *variable* that appears as a *data-stmt-object* shall not be an [object designator](#)
35 in which a pointer appears other than as the entire rightmost *part-ref*.

- 1 C577 (R541) The *array-element* shall be a variable.
- 2 C578 (R541) The *scalar-structure-component* shall be a variable.
- 3 C579 (R541) The *scalar-structure-component* shall contain at least one *part-ref* that contains a *subscript-list*.
- 4 C580 (R541) In an *array-element* or *scalar-structure-component* that is a *data-i-do-object*, any subscript shall
5 be a *constant expression*, and any primary within that subscript that is a *data-i-do-variable* shall be a
6 DO variable of this *data-implied-do* or of a containing *data-implied-do*.
- 7 R543 *data-stmt-value* is [*data-stmt-repeat* *] *data-stmt-constant*
- 8 R544 *data-stmt-repeat* is *scalar-int-constant*
9 or *scalar-int-constant-subobject*
- 10 C581 (R544) The *data-stmt-repeat* shall be positive or zero. If the *data-stmt-repeat* is a *named constant*, it
11 shall have been defined previously.
- 12 R545 *data-stmt-constant* is *scalar-constant*
13 or *scalar-constant-subobject*
14 or *signed-int-literal-constant*
15 or *signed-real-literal-constant*
16 or *null-init*
17 or *initial-data-target*
18 or *structure-constructor*
- 19 C582 (R545) If a DATA statement constant value is a *named constant* or a *structure constructor*, the *named*
20 *constant* or derived type shall have been defined previously.
- 21 C583 (R545) If a *data-stmt-constant* is a *structure-constructor*, it shall be a *constant expression*.
- 22 R546 *int-constant-subobject* is *constant-subobject*
- 23 C584 (R546) *int-constant-subobject* shall be of type integer.
- 24 R547 *constant-subobject* is *designator*
- 25 C585 (R547) *constant-subobject* shall be a subobject of a constant.
- 26 C586 (R547) Any subscript, substring starting point, or substring ending point shall be a *constant expression*.
- 27 5 The *data-stmt-object-list* is expanded to form a sequence of pointers and scalar variables, referred to as “sequence
28 of variables” in subsequent text. A nonpointer array whose unqualified name appears as a *data-stmt-object* or
29 *data-i-do-object* is equivalent to a complete sequence of its array elements in array element order (6.5.3.2). An
30 *array section* is equivalent to the sequence of its array elements in array element order. A *data-implied-do* is
31 expanded to form a sequence of array elements and *structure components*, under the control of the *data-i-do-*
32 *variable*, as in the DO construct (8.1.6.4).
- 33 6 The *data-stmt-value-list* is expanded to form a sequence of *data-stmt-constants*. A *data-stmt-repeat* indicates the
34 number of times the following *data-stmt-constant* is to be included in the sequence; omission of a *data-stmt-repeat*
35 has the effect of a repeat factor of 1.
- 36 7 A zero-sized array or a *data-implied-do* with an iteration count of zero contributes no variables to the expanded
37 sequence of variables, but a zero-length scalar character variable does contribute a variable to the expanded
38 sequence. A *data-stmt-constant* with a repeat factor of zero contributes no *data-stmt-constants* to the expanded
39 sequence of scalar *data-stmt-constants*.
- 40 8 The expanded sequences of variables and *data-stmt-constants* are in one-to-one correspondence. Each *data-stmt-*
41 *constant* specifies the initial value, initial data *target*, or *null-init* for the corresponding variable. The lengths of
42 the two expanded sequences shall be the same.

- 1 9 A *data-stmt-constant* shall be *null-init* or *initial-data-target* if and only if the corresponding *data-stmt-object* has
 2 the **POINTER** attribute. If *data-stmt-constant* is *null-init*, the initial association status of the corresponding data
 3 statement object is *disassociated*. If *data-stmt-constant* is *initial-data-target* the corresponding data statement
 4 object shall be data-pointer-initialization compatible (4.5.4.6) with the initial data **target**; the data statement
 5 object is initially associated with the **target**.
- 6 10 A *data-stmt-constant* other than *boz-literal-constant*, *null-init*, or *initial-data-target* shall be compatible with its
 7 corresponding variable according to the rules of intrinsic assignment (7.2.1.2). The variable is initially defined
 8 with the value specified by the *data-stmt-constant*; if necessary, the value is converted according to the rules of
 9 intrinsic assignment (7.2.1.3) to a value that agrees in type, type parameters, and shape with the variable.
- 10 11 If a *data-stmt-constant* is a *boz-literal-constant*, the corresponding variable shall be of type integer. The *boz-*
 11 *literal-constant* is treated as if it were converted by the intrinsic function **INT** (13.8.92) to type integer with the
 12 kind type parameter of the variable.

NOTE 5.29

Examples of DATA statements are:

```
CHARACTER (LEN = 10) NAME
INTEGER, DIMENSION (0:9) :: MILES
REAL, DIMENSION (100, 100) :: SKEW
TYPE (NODE), POINTER :: HEAD_OF_LIST
TYPE (PERSON) MYNAME, YOURNAME
DATA NAME / 'JOHN DOE' /, MILES / 10 * 0 /
DATA ((SKEW (K, J), J = 1, K), K = 1, 100) / 5050 * 0.0 /
DATA ((SKEW (K, J), J = K + 1, 100), K = 1, 99) / 4950 * 1.0 /
DATA HEAD_OF_LIST / NULL() /
DATA MYNAME / PERSON (21, 'JOHN SMITH') /
DATA YOURNAME % AGE, YOURNAME % NAME / 35, 'FRED BROWN' /
```

The character variable NAME is initialized with the value JOHN DOE with padding on the right because the length of the constant is less than the length of the variable. All ten elements of the integer array MILES are initialized to zero. The two-dimensional array SKEW is initialized so that the lower triangle of SKEW is zero and the strict upper triangle is one. The structures MYNAME and YOURNAME are declared using the derived type PERSON from Note 4.15. The pointer HEAD_OF_LIST is declared using the derived type NODE from Note 4.35; it is initially *disassociated*. MYNAME is initialized by a **structure constructor**. YOURNAME is initialized by supplying a separate value for each component.

13 5.6.8 DIMENSION statement

14 R548 *dimension-stmt* is DIMENSION [::] *array-name* (*array-spec*) ■
 15 ■ [, *array-name* (*array-spec*)] ...

- 16 1 The DIMENSION statement specifies the **DIMENSION** attribute (5.5.8) for a list of objects.

NOTE 5.30

An example of a DIMENSION statement is:

```
DIMENSION A (10), B (10, 70), C (:)
```

17 5.6.9 INTENT statement

18 R549 *intent-stmt* is INTENT (*intent-spec*) [::] *dummy-arg-name-list*

- 19 1 The INTENT statement specifies the **INTENT** attribute (5.5.10) for the **dummy arguments** in the list.

NOTE 5.31

An example of an INTENT statement is:

```
SUBROUTINE EX (A, B)
  INTENT (INOUT) :: A, B
```

5.6.10 OPTIONAL statement

R550 *optional-stmt* is OPTIONAL [::] *dummy-arg-name-list*

- 1 The OPTIONAL statement specifies the **OPTIONAL attribute** (5.5.12) for the **dummy arguments** in the list.

NOTE 5.32

An example of an OPTIONAL statement is:

```
SUBROUTINE EX (A, B)
  OPTIONAL :: B
```

5.6.11 PARAMETER statement

- 1 The PARAMETER statement specifies the **PARAMETER attribute** (5.5.13) and the values for the **named constants** in the list.

R551 *parameter-stmt* is PARAMETER (*named-constant-def-list*)

R552 *named-constant-def* is *named-constant* = *constant-expr*

- 2 If a **named constant** is defined by a PARAMETER statement, it shall not be subsequently declared to have a type or type parameter value that differs from the type and type parameters it would have if declared implicitly (5.7). A named array constant defined by a PARAMETER statement shall have its **rank** specified in a prior specification statement.
- 3 The constant expression that corresponds to a named constant shall have type and **type parameters** that conform with the named constant as specified for intrinsic assignment (7.2.1.2). If the named constant has implied shape, the expression shall have the same rank as the named constant; otherwise, the expression shall either be scalar or have the same shape as the named constant.
- 4 The value of each **named constant** is that specified by the corresponding **constant expression**; if necessary, the value is converted according to the rules of intrinsic assignment (7.2.1.3) to a value that agrees in type, type parameters, and shape with the **named constant**.

NOTE 5.33

An example of a PARAMETER statement is:

```
PARAMETER (MODULUS = MOD (28, 3), NUMBER_OF_SENATORS = 100)
```

5.6.12 POINTER statement

R553 *pointer-stmt* is POINTER [::] *pointer-decl-list*

R554 *pointer-decl* is *object-name* [(*deferred-shape-spec-list*)]
or *proc-entity-name*

C587 A *proc-entity-name* shall have the **EXTERNAL attribute**.

- 1 The POINTER statement specifies the **POINTER attribute** (5.5.14) for a list of entities.

NOTE 5.34

An example of a POINTER statement is:

```
TYPE (NODE) :: CURRENT
POINTER :: CURRENT, A (:, :)
```

5.6.13 PROTECTED statement

R555 *protected-stmt* is PROTECTED [::] *entity-name-list*

- 1 The PROTECTED statement specifies the [PROTECTED attribute \(5.5.15\)](#) for a list of entities.

5.6.14 SAVE statement

R556 *save-stmt* is SAVE [[::] *saved-entity-list*]

R557 *saved-entity* is *object-name*
or *proc-pointer-name*
or / *common-block-name* /

R558 *proc-pointer-name* is *name*

C588 (R556) If a SAVE statement with an omitted saved entity list appears in a [scoping unit](#), no other appearance of the SAVE *attr-spec* or SAVE statement is permitted in that [scoping unit](#).

C589 A *proc-pointer-name* shall be the name of a procedure pointer.

- 1 A SAVE statement with a saved entity list specifies the [SAVE attribute \(5.5.16\)](#) for a list of entities. A SAVE statement without a saved entity list is treated as though it contained the names of all allowed items in the same [scoping unit](#).

NOTE 5.35

An example of a SAVE statement is:

```
SAVE A, B, C, / BLOCKA /, D
```

5.6.15 TARGET statement

R559 *target-stmt* is TARGET [::] *target-decl-list*

R560 *target-decl* is *object-name* [(*array-spec*)] ■
■ [*lbracket coarray-spec rbracket*]

- 1 The TARGET statement specifies the [TARGET attribute \(5.5.17\)](#) for a list of objects.

NOTE 5.36

An example of a TARGET statement is:

```
TARGET :: A (1000, 1000), B
```

5.6.16 VALUE statement

R561 *value-stmt* is VALUE [::] *dummy-arg-name-list*

- 1 The VALUE statement specifies the [VALUE attribute \(5.5.18\)](#) for a list of [dummy arguments](#).

5.6.17 VOLATILE statement

R562 *volatile-stmt* is VOLATILE [::] *object-name-list*

- 1 The VOLATILE statement specifies the VOLATILE attribute (5.5.19) for a list of objects.

5.7 IMPLICIT statement

- 1 In a [scoping unit](#), an IMPLICIT statement specifies a type, and possibly type parameters, for all implicitly typed data entities whose names begin with one of the letters specified in the statement. Alternatively, it may indicate that no implicit typing rules are to apply in a particular [scoping unit](#).

R563 *implicit-stmt* is IMPLICIT *implicit-spec-list*
or IMPLICIT NONE [([*implicit-none-spec-list*])]

R564 *implicit-spec* is *declaration-type-spec* (*letter-spec-list*)

R565 *letter-spec* is *letter* [– *letter*]

R566 *implicit-none-spec* is EXTERNAL
or TYPE

C590 (R563) If IMPLICIT NONE is specified in a [scoping unit](#), it shall precede any [PARAMETER statements](#) that appear in the [scoping unit](#). No more than one IMPLICIT NONE statement shall appear in a [scoping unit](#).

C591 If an IMPLICIT NONE statement in a [scoping unit](#) has an *implicit-none-spec* of TYPE or has no *implicit-none-spec-list*, there shall be no other IMPLICIT statements in the [scoping unit](#).

C592 (R565) If the minus and second *letter* appear, the second letter shall follow the first letter alphabetically.

C593 If IMPLICIT NONE with an *implicit-none-spec* of EXTERNAL appears within a [scoping unit](#), the name of an [external](#) or [dummy](#) procedure in that [scoping unit](#) or in a contained [subprogram](#) or [BLOCK construct](#) shall be explicitly declared to have the [EXTERNAL attribute](#).

- 2 A *letter-spec* consisting of two *letters* separated by a minus is equivalent to writing a list containing all of the letters in alphabetical order in the alphabetic sequence from the first letter through the second letter. For example, A–C is equivalent to A, B, C. The same letter shall not appear as a single letter, or be included in a range of letters, more than once in all of the IMPLICIT statements in a [scoping unit](#).

- 3 In each [scoping unit](#), there is a mapping, which may be null, between each of the letters A, B, ..., Z and a type (and type parameters). An IMPLICIT statement specifies the mapping for the letters in its *letter-spec-list*. IMPLICIT NONE with an *implicit-none-spec* of TYPE or with no *implicit-none-spec-list* specifies the null mapping for all the letters. If a mapping is not specified for a letter, the default for a [program unit](#) or an [interface body](#) is default integer if the letter is I, J, ..., or N and default real otherwise, and the default for a [BLOCK construct](#), [internal subprogram](#), or [module subprogram](#) is the mapping in the [host scoping unit](#).

- 4 Any data entity that is not explicitly declared by a [type declaration statement](#), is not an intrinsic function, is not a [component](#), and is not accessed by [use](#) or [host](#) association is declared implicitly to be of the type (and type parameters) mapped from the first letter of its name, provided the mapping is not null. The mapping for the first letter of the data entity shall either have been established by a prior IMPLICIT statement or be the default mapping for the letter. The data entity is treated as if it were declared in an explicit type declaration; if the outermost [inclusive scope](#) in which it appears is not a type definition, it is declared in that scope, otherwise it is declared in the host of that scope. An explicit type specification in a [FUNCTION statement](#) overrides an IMPLICIT statement for the [result](#) of that function.

NOTE 5.37

The following are examples of the use of IMPLICIT statements:

```

MODULE EXAMPLE_MODULE
  IMPLICIT NONE
  ...
  INTERFACE
    FUNCTION FUN (I)      ! Not all data entities need to
      INTEGER FUN        ! be declared explicitly
    END FUNCTION FUN
  END INTERFACE
CONTAINS
  FUNCTION JFUN (J)      ! All data entities need to
    INTEGER JFUN, J     ! be declared explicitly.
    ...
  END FUNCTION JFUN
END MODULE EXAMPLE_MODULE
SUBROUTINE SUB
  IMPLICIT COMPLEX (C)
  C = (3.0, 2.0)        ! C is implicitly declared COMPLEX
  ...
CONTAINS
  SUBROUTINE SUB1
    IMPLICIT INTEGER (A, C)
    C = (0.0, 0.0)      ! C is host associated and of
                       ! type complex
    Z = 1.0             ! Z is implicitly declared REAL
    A = 2               ! A is implicitly declared INTEGER
    CC = 1              ! CC is implicitly declared INTEGER
    ...
  END SUBROUTINE SUB1
  SUBROUTINE SUB2
    Z = 2.0             ! Z is implicitly declared REAL and
                       ! is different from the variable of
                       ! the same name in SUB1
    ...
  END SUBROUTINE SUB2
  SUBROUTINE SUB3
    USE EXAMPLE_MODULE ! Accesses integer function FUN
                       ! by use association
    Q = FUN (K)        ! Q is implicitly declared REAL and
    ...                ! K is implicitly declared INTEGER
  END SUBROUTINE SUB3
END SUBROUTINE SUB

```

NOTE 5.38

The following is an example of a mapping to a derived type that is inaccessible in the local scope:

```

PROGRAM MAIN
  IMPLICIT TYPE(BLOB) (A)
  TYPE BLOB
    INTEGER :: I
  END TYPE BLOB
  TYPE(BLOB) :: B

```

NOTE 5.38 (cont.)

```

CALL STEVE
CONTAINS
SUBROUTINE STEVE
  INTEGER :: BLOB
  ..
  AA = B
  ..
END SUBROUTINE STEVE
END PROGRAM MAIN

```

In the subroutine STEVE, it is not possible to explicitly declare a variable to be of type BLOB because BLOB has been given a different meaning, but implicit mapping for the letter A still maps to type BLOB, so AA is of type BLOB.

NOTE 5.39

Implicit typing is not affected by [BLOCK constructs](#). For example, in

```

SUBROUTINE S(N)
  ...
  IF (N>0) THEN
    BLOCK
      NSQP = CEILING(SQRT(DBLE(N)))
    END BLOCK
  END IF
  ...
  IF (N>0) THEN
    BLOCK
      PRINT *,NSQP
    END BLOCK
  END IF
END SUBROUTINE

```

even if the only two appearances of NSQP are within the [BLOCK constructs](#), the scope of NSQP is the whole subroutine S.

NOTE 5.40

In the subprogram

```

SUBROUTINE EXAMPLE (X, Y)
  IMPLICIT NONE (EXTERNAL)
  REAL, EXTERNAL :: G
  REAL :: X, Y
  X = F (Y)           ! Invalid: F lacks the EXTERNAL attribute.
  X = G (Y)           ! Valid: G has the EXTERNAL attribute.
END SUBROUTINE

```

the referenced function F needs to have the [EXTERNAL attribute \(5.5.9\)](#).

1 5.8 NAMELIST statement

- 2 1 A NAMELIST statement specifies a group of named data objects, which may be referred to by a single name for
3 the purpose of data transfer ([9.6](#), [10.11](#)).

- 1 R567 *namelist-stmt* is NAMELIST ■
 2 ■ / *namelist-group-name* / *namelist-group-object-list* ■
 3 ■ [[,] / *namelist-group-name* / ■
 4 ■ *namelist-group-object-list*] ...
- 5 C594 (R567) The *namelist-group-name* shall not be a name accessed by [use association](#).
- 6 R568 *namelist-group-object* is *variable-name*
- 7 C595 (R568) A *namelist-group-object* shall not be an [assumed-size array](#).
- 8 C596 (R567) A *namelist-group-object* shall not have the [PRIVATE attribute](#) if the *namelist-group-name* has
 9 the [PUBLIC attribute](#).
- 10 2 The order in which the variables are specified in the NAMELIST statement determines the order in which the
 11 values appear on output.
- 12 3 Any *namelist-group-name* may occur more than once in the NAMELIST statements in a [scoping unit](#). The
 13 *namelist-group-object-list* following each successive appearance of the same *namelist-group-name* in a [scoping](#)
 14 [unit](#) is treated as a continuation of the list for that *namelist-group-name*.
- 15 4 A namelist group object may be a member of more than one namelist group.
- 16 5 A namelist group object shall either be accessed by use or host association or shall have its [declared type](#), [kind](#)
 17 [type parameters](#) of the [declared type](#), and [rank](#) specified by previous specification statements or the procedure
 18 heading in the same [scoping unit](#) or by the [implicit typing rules](#) in effect for the [scoping unit](#). If a namelist group
 19 object is typed by the [implicit typing rules](#), its appearance in any subsequent [type declaration statement](#) shall
 20 confirm the implied type and [type parameters](#).

NOTE 5.41

An example of a NAMELIST statement is:

```
NAMELIST /NLIST/ A, B, C
```

21 5.9 Storage association of data objects

22 5.9.1 EQUIVALENCE statement

23 5.9.1.1 General

- 24 1 An EQUIVALENCE statement is used to specify the sharing of [storage units](#) by two or more objects in a [scoping unit](#). This causes
 25 [storage association](#) (16.5.3) of the objects that share the [storage units](#).
- 26 2 If the equivalenced objects have differing type or type parameters, the EQUIVALENCE statement does not cause type conversion or
 27 imply mathematical equivalence. If a scalar and an array are equivalenced, the scalar does not have array properties and the array
 28 does not have the properties of a scalar.
- 29 R569 *equivalence-stmt* is EQUIVALENCE *equivalence-set-list*
- 30 R570 *equivalence-set* is (*equivalence-object* , *equivalence-object-list*)
- 31 R571 *equivalence-object* is *variable-name*
 32 or *array-element*
 33 or *substring*
- 34 C597 (R571) An *equivalence-object* shall not be a [designator](#) with a [base object](#) that is a [dummy argument](#), a [function result](#), a
 35 pointer, an [allocatable](#) variable, a derived-type object that has an [allocatable](#) or pointer [ultimate component](#), an object of
 36 a nonsequence derived type, an [automatic object](#), a [coarray](#), a variable with the [BIND attribute](#), a variable in a [common](#)
 37 [block](#) that has the [BIND attribute](#), or a [named constant](#).
- 38 C598 (R571) An *equivalence-object* shall not be a [designator](#) that has more than one [part-ref](#).

- 1 C599 (R571) An *equivalence-object* shall not have the **TARGET** attribute.
- 2 C5100 (R571) Each subscript or substring range expression in an *equivalence-object* shall be an integer **constant expression** (7.1.12).
- 3 C5101 (R570) If an *equivalence-object* is default integer, default real, double precision real, default complex, default logical, or of
4 **numeric sequence type**, all of the objects in the equivalence set shall be of these types and kinds.
- 5 C5102 (R570) If an *equivalence-object* is default character or of **character sequence type**, all of the objects in the equivalence set
6 shall be of these types and kinds.
- 7 C5103 (R570) If an *equivalence-object* is of a **sequence type** that is not a **numeric sequence** or **character sequence** type, all of the
8 objects in the equivalence set shall be of the same type with the same type parameter values.
- 9 C5104 (R570) If an *equivalence-object* is of an intrinsic type but is not default integer, default real, double precision real, default
10 complex, default logical, or default character, all of the objects in the equivalence set shall be of the same type with the
11 same kind type parameter value.
- 12 C5105 (R571) If an *equivalence-object* has the **PROTECTED** attribute, all of the objects in the equivalence set shall have the
13 **PROTECTED** attribute.
- 14 C5106 (R571) The name of an *equivalence-object* shall not be a name made accessible by **use association**.
- 15 C5107 (R571) A *substring* shall not have length zero.

NOTE 5.42

The EQUIVALENCE statement allows the equivalencing of sequence structures and the equivalencing of objects of intrinsic type with nondefault type parameters, but there are strict rules regarding the appearance of these objects in an EQUIVALENCE statement.

A structure that appears in an EQUIVALENCE statement shall be a sequence structure. If a sequence structure is not of **numeric sequence type** or of **character sequence type**, it shall be equivalenced only to objects of the same type with the same type parameter values.

A structure of a **numeric sequence type** shall be equivalenced only to another structure of a **numeric sequence type**, an object that is default integer, default real, double precision real, default complex, or default logical type such that components of the structure ultimately become associated only with objects of these types and kinds.

A structure of a **character sequence type** shall be equivalenced only to a default character object or another structure of a **character sequence type**.

An object of intrinsic type with nondefault kind type parameters shall not be equivalenced to objects of different type or kind type parameters.

Further rules on the interaction of EQUIVALENCE statements and **default initialization** are given in 16.5.3.4.

16 **5.9.1.2 Equivalence association**

- 17 1 An EQUIVALENCE statement specifies that the **storage sequences** (16.5.3.2) of the data objects specified in an *equivalence-set* are
18 storage associated. All of the nonzero-sized sequences in the *equivalence-set*, if any, have the same first **storage unit**, and all of
19 the zero-sized sequences in the *equivalence-set*, if any, are storage associated with one another and with the first **storage unit** of
20 any nonzero-sized sequences. This causes the **storage association** of the data objects in the *equivalence-set* and may cause **storage**
21 **association** of other data objects.
- 22 2 If any data object in an *equivalence-set* has the **SAVE** attribute, all other objects in the *equivalence-set* have the **SAVE** attribute;
23 this may be confirmed by explicit specification.

24 **5.9.1.3 Equivalence of default character objects**

- 25 1 A default character data object shall not be equivalenced to an object that is not default character and not of a **character sequence**
26 **type**. The lengths of equivalenced default character objects need not be the same.
- 27 2 An EQUIVALENCE statement specifies that the **storage sequences** of all the default character data objects specified in an *equivalence-*
28 *set* are storage associated. All of the nonzero-sized sequences in the *equivalence-set*, if any, have the same first **character storage unit**,
29 and all of the zero-sized sequences in the *equivalence-set*, if any, are storage associated with one another and with the first **character**
30 **storage unit** of any nonzero-sized sequences. This causes the **storage association** of the data objects in the *equivalence-set* and may
31 cause **storage association** of other data objects.

NOTE 5.43

For example, using the declarations:

```
CHARACTER (LEN = 4) :: A, B
CHARACTER (LEN = 3) :: C (2)
EQUIVALENCE (A, C (1)), (B, C (2))
```

the association of A, B, and C can be illustrated graphically as:

```

  1      2      3      4      5      6      7
|---  --- A  ---  ---|
|---  C(1) ---| |---  C(2) ---|
```

1 5.9.1.4 Array names and array element designators

2 1 For a nonzero-sized array, the use of the array name unqualified by a subscript list as an *equivalence-object* has the same effect as
3 using an array element *designator* that identifies the first element of the array.

4 5.9.1.5 Restrictions on EQUIVALENCE statements

5 1 An EQUIVALENCE statement shall not specify that the same *storage unit* is to occur more than once in a *storage sequence*.

6 2 An EQUIVALENCE statement shall not specify that consecutive *storage units* are to be nonconsecutive.

7 5.9.2 COMMON statement

8 5.9.2.1 General

9 1 The COMMON statement specifies blocks of physical storage, called *common blocks*, that can be accessed by any of the *scoping*
10 *units* in a program. Thus, the COMMON statement provides a global data facility based on *storage association* (16.5.3).

11 2 A *common block* that does not have a name is called *blank common*.

```
12 R572  common-stmt                is  COMMON ■
13                                     ■ [ / [ common-block-name ] / ] common-block-object-list ■
14                                     ■ [ [ , ] / [ common-block-name ] / ■
15                                     ■ common-block-object-list ] ...
```

```
16 R573  common-block-object        is  variable-name [ ( array-spec ) ]
```

17 C5108 (R573) An *array-spec* in a *common-block-object* shall be an *explicit-shape-spec-list*.

18 C5109 (R573) Only one appearance of a given *variable-name* is permitted in all *common-block-object-lists* within a *scoping unit*.

19 C5110 (R573) A *common-block-object* shall not be a *dummy argument*, a *function result*, an *allocatable* variable, a derived-type
20 object with an *ultimate component* that is *allocatable*, a *procedure pointer*, an *automatic object*, a variable with the *BIND*
21 *attribute*, an *unlimited polymorphic* pointer, or a *coarray*.

22 C5111 (R573) If a *common-block-object* is of a derived type, the type shall have the *BIND attribute* or the *SEQUENCE attribute*
23 and it shall have no *default initialization*.

24 C5112 (R573) A *variable-name* shall not be a name made accessible by *use association*.

25 3 In each COMMON statement, the data objects whose names appear in a common block object list following a *common block* name
26 are declared to be in that *common block*. If the first *common block* name is omitted, all data objects whose names appear in the
27 first common block object list are specified to be in *blank common*. Alternatively, the appearance of two slashes with no *common*
28 *block* name between them declares the data objects whose names appear in the common block object list that follows to be in *blank*
29 *common*.

30 4 Any *common block* name or an omitted *common block* name for *blank common* may occur more than once in one or more COMMON
31 statements in a *scoping unit*. The common block list following each successive appearance of the same common block name in a
32 *scoping unit* is treated as a continuation of the list for that common block name. Similarly, each blank common block object list in
33 a *scoping unit* is treated as a continuation of *blank common*.

34 5 The form *variable-name* (*array-spec*) specifies the *DIMENSION attribute* for that variable.

- 1 6 If derived-type objects of **numeric sequence type** or **character sequence type** (4.5.2.3) appear in **common**, it is as if the individual
2 components were enumerated directly in the common list.

3 5.9.2.2 Common block storage sequence

- 4 1 For each **common block** in a **scoping unit**, a common block **storage sequence** is formed as follows:
- 5 (1) A **storage sequence** is formed consisting of the sequence of **storage units** in the **storage sequences** (16.5.3.2) of all data
6 objects in the common block object lists for the **common block**. The order of the **storage sequences** is the same as the
7 order of the appearance of the common block object lists in the **scoping unit**.
 - 8 (2) The **storage sequence** formed in (1) is extended to include all **storage units** of any **storage sequence** associated with it
9 by equivalence association. The **sequence** shall be extended only by adding **storage units** beyond the last **storage unit**.
10 Data objects associated with an entity in a **common block** are considered to be in that **common block**.
- 11 2 Only COMMON statements and EQUIVALENCE statements appearing in the **scoping unit** contribute to common block **storage**
12 **sequences** formed in that **scoping unit**.

13 5.9.2.3 Size of a common block

- 14 1 The size of a common block is the size of its common block **storage sequence**, including any extensions of the **sequence** resulting from
15 equivalence association.

16 5.9.2.4 Common association

- 17 1 Within a program, the common block **storage sequences** of all nonzero-sized **common blocks** with the same name have the same first
18 **storage unit**, and the common block **storage sequences** of all zero-sized **common blocks** with the same name are storage associated
19 with one another. Within a program, the common block **storage sequences** of all nonzero-sized **blank common** blocks have the same
20 first **storage unit** and the **storage sequences** of all zero-sized **blank common** blocks are associated with one another and with the first
21 **storage unit** of any nonzero-sized **blank common** blocks. This results in the association of objects in different **scoping units**. Use or
22 **host** association may cause these associated objects to be accessible in the same **scoping unit**.
- 23 2 A nonpointer object that is default integer, default real, double precision real, default complex, default logical, or of **numeric sequence**
24 **type** shall be associated only with nonpointer objects of these types and kinds.
- 25 3 A nonpointer object that is default character or of **character sequence type** shall be associated only with nonpointer objects of these
26 types and kinds.
- 27 4 A nonpointer object of a derived type that is not a **numeric sequence** or **character sequence type** shall be associated only with
28 nonpointer objects of the same type with the same type parameter values.
- 29 5 A nonpointer object of intrinsic type but which is not default integer, default real, double precision real, default complex, default
30 logical, or default character shall be associated only with nonpointer objects of the same type and type parameters.
- 31 6 A data pointer shall be storage associated only with data pointers of the same type and **rank**. Data pointers that are storage
32 associated shall have **deferred** the same type parameters; corresponding nondeferred **type parameters** shall have the same value.
- 33 7 An object with the **TARGET attribute** shall be storage associated only with another object that has the **TARGET attribute** and the
34 same type and type parameters.

NOTE 5.44

A **common block** is permitted to contain sequences of different **storage units**, provided each **scoping unit** that accesses the **common block** specifies an identical sequence of **storage units** for the **common block**. For example, this allows a single **common block** to contain both **numeric** and **character storage units**.

Association in different **scoping units** between objects of default type, objects of double precision real type, and sequence structures is permitted according to the rules for equivalence objects (5.9.1).

35 5.9.2.5 Differences between named common and blank common

- 36 1 A **blank common** block has the same properties as a named **common block**, except for the following.
- 37 • Execution of a **RETURN** or **END** statement might cause data objects in a named **common block** to become undefined unless
38 the **common block** has the **SAVE attribute**, but never causes data objects in **blank common** to become undefined (16.6.6).
 - 39 • Named **common blocks** of the same name shall be of the same size in all **scoping units** of a program in which they appear, but
40 **blank common** blocks may be of different sizes.
 - 41 • A data object in a named **common block** may be initially defined by means of a **DATA statement** or **type declaration statement**
42 in a **block data program unit** (11.3), but objects in **blank common** shall not be initially defined.

1 **5.9.3 Restrictions on common and equivalence**

- 2 1 An **EQUIVALENCE statement** shall not cause the **storage sequences** of two different **common blocks** to be associated.
- 3 2 Equivalence association shall not cause a derived-type object with **default initialization** to be associated with an object in a **common**
- 4 **block**.
- 5 3 Equivalence association shall not cause a common block **storage sequence** to be extended by adding **storage units** preceding the first
- 6 **storage unit** of the first object specified in a COMMON statement for the **common block**.

6 Use of data objects

6.1 Designator

R601 *designator* is *object-name*
 or *array-element*
 or *array-section*
 or *coindexed-named-object*
 or *complex-part-designator*
 or *structure-component*
 or *substring*

1 The appearance of a *data object designator* in a context that requires its value is termed a reference.

6.2 Variable

R602 *variable* is *designator*
 or *function-reference*

C601 (R602) *designator* shall not be a constant or a subobject of a constant.

C602 (R602) *function-reference* shall have a data pointer result.

- 1 A variable is either the data object denoted by *designator* or the *target* of the pointer resulting from the evaluation of *function-reference*; this pointer shall be associated.
- 2 A reference is permitted only if the variable is defined. A reference to a data pointer is permitted only if the pointer is associated with a *target* object that is defined. A variable becomes defined with a value when events described in 16.6.5 occur.

R603 *variable-name* is *name*

C603 (R603) *variable-name* shall be the name of a variable.

R604 *logical-variable* is *variable*

C604 (R604) *logical-variable* shall be of type logical.

R605 *char-variable* is *variable*

C605 (R605) *char-variable* shall be of type character.

R606 *default-char-variable* is *variable*

C606 (R606) *default-char-variable* shall be default character.

R607 *int-variable* is *variable*

C607 (R607) *int-variable* shall be of type integer.

NOTE 6.1

For example, given the declarations:

```
CHARACTER (10) A, B (10)
```

NOTE 6.1 (cont.)

TYPE (PERSON) P ! See Note 4.15

then A, B, B (1), B (1:5), P % AGE, and A (1:1) are all variables.

6.3 Constants

- 1 A constant (3.2.3) is a literal constant or a [named constant](#). A literal constant is a scalar denoted by a syntactic form, which indicates its type, type parameters, and value. A [named constant](#) is a constant that has a name; the name has the [PARAMETER attribute](#) (5.5.13, 5.6.11). A reference to a constant is always permitted; redefinition of a constant is never permitted.

6.4 Scalars**6.4.1 Substrings**

- 1 A substring is a [contiguous](#) portion of a character string (4.4.4).

R608 *substring* is *parent-string* (*substring-range*)

R609 *parent-string* is *scalar-variable-name*
 or *array-element*
 or *coindexed-named-object*
 or *scalar-structure-component*
 or *scalar-constant*

R610 *substring-range* is [*scalar-int-expr*] : [*scalar-int-expr*]

C608 (R609) *parent-string* shall be of type character.

- 2 The value of the first *scalar-int-expr* in *substring-range* is the starting point of the substring and the value of the second one is the ending point of the substring. The length of a substring is the number of characters in the substring and is $\text{MAX}(l - f + 1, 0)$, where f and l are the starting and ending points, respectively.
- 3 Let the characters in the parent string be numbered 1, 2, 3, ..., n , where n is the length of the parent string. Then the characters in the substring are those from the parent string from the starting point and proceeding in sequence up to and including the ending point. If the starting point is greater than the ending point, the substring has length zero; otherwise, both the starting point and the ending point shall be within the range 1, 2, ..., n . If the starting point is not specified, the default value is 1. If the ending point is not specified, the default value is n .

NOTE 6.2

Examples of character substrings are:

B(1)(1:5)	array element as parent string
P%NAME(1:1)	structure component as parent string
ID(4:9)	scalar variable name as parent string
'0123456789'(N:N)	character constant as parent string

6.4.2 Structure components

- 1 A [structure component](#) is part of an object of derived type; it may be referenced by an [object designator](#). A [structure component](#) may be a scalar or an array.

R611 *data-ref* is *part-ref* [% *part-ref*] ...

- 1 R612 *part-ref* is *part-name* [(*section-subscript-list*)] [*image-selector*]
- 2 C609 (R611) Each *part-name* except the rightmost shall be of derived type.
- 3 C610 (R611) Each *part-name* except the leftmost shall be the name of a component of the **declared type** of the
4 preceding *part-name*.
- 5 C611 (R611) If the rightmost *part-name* is of **abstract type**, *data-ref* shall be **polymorphic**.
- 6 C612 (R611) The leftmost *part-name* shall be the name of a data object.
- 7 C613 (R612) If a *section-subscript-list* appears, the number of *section-subscripts* shall equal the **rank** of *part-*
8 *name*.
- 9 C614 (R612) If *image-selector* appears, the number of *cosubscripts* shall be equal to the **corank** of *part-name*.
- 10 C615 (R612) If *image-selector* appears and *part-name* is an array, *section-subscript-list* shall appear.
- 11 C616 (R611) If *image-selector* appears, *data-ref* shall not be of type **C_PTR** or **C_FUNPTR** from the intrinsic
12 module **ISO_C_BINDING** (15.3.3).
- 13 C617 (R611) Except as an **actual argument** to an intrinsic **inquiry function** or as the *designator* in a type
14 parameter inquiry, a *data-ref* shall not be a **polymorphic** subobject of a **coindexed object** and shall not
15 be a **coindexed object** that has a **polymorphic allocatable** subcomponent.
- 16 2 The **rank** of a *part-ref* of the form *part-name* is the **rank** of *part-name*. The **rank** of a *part-ref* that has a section
17 subscript list is the number of subscript triplets and **vector subscripts** in the list.
- 18 C618 (R611) There shall not be more than one *part-ref* with nonzero **rank**. A *part-name* to the right of a
19 *part-ref* with nonzero **rank** shall not have the **ALLOCATABLE** or **POINTER** attribute.
- 20 3 The **rank** of a *data-ref* is the **rank** of the *part-ref* with nonzero **rank**, if any; otherwise, the **rank** is zero. The **base**
21 **object** of a *data-ref* is the data object whose name is the leftmost part name.
- 22 4 The type and type parameters, if any, of a *data-ref* are those of the rightmost part name.
- 23 5 A *data-ref* with more than one *part-ref* is a subobject of its **base object** if none of the *part-names*, except for
24 possibly the rightmost, is a pointer. If the rightmost *part-name* is the only pointer, then the *data-ref* is a subobject
25 of its **base object** in contexts that pertain to its **pointer association** status but not in any other contexts.

NOTE 6.3

If X is an object of derived type with a pointer component P, then the pointer X%P is a subobject of X when considered as a pointer – that is in contexts where it is not dereferenced.

However the **target** of X%P is not a subobject of X. Thus, in contexts where X%P is dereferenced to refer to the **target**, it is not a subobject of X.

- 26 R613 *structure-component* is *data-ref*
- 27 C619 (R613) There shall be more than one *part-ref* and the rightmost *part-ref* shall not have a *section-subscript-*
28 *list*.
- 29 6 A **structure component** shall be neither referenced nor defined before the declaration of the **base object**. A
30 **structure component** is a pointer only if the rightmost part name is defined to have the **POINTER** attribute.

NOTE 6.4

Examples of structure components are:

SCALAR_PARENT%SCALAR_FIELD scalar component of scalar parent

NOTE 6.4 (cont.)

ARRAY_PARENT(J)%SCALAR_FIELD	component of array element parent
ARRAY_PARENT(1:N)%SCALAR_FIELD	component of array section parent

For a more elaborate example see [C.3.1](#).

NOTE 6.5

The syntax rules are structured such that a *data-ref* that ends in a component name without a following subscript list is a structure component, even when other component names in the *data-ref* are followed by a subscript list. A *data-ref* that ends in a component name with a following subscript list is either an array element or an *array section*. A *data-ref* of nonzero *rank* that ends with a *substring-range* is an *array section*. A *data-ref* of zero *rank* that ends with a *substring-range* is a substring.

6.4.3 Coindexed named objects

1 A *coindexed-named-object* is a named scalar coarray variable followed by an image selector.

2 R614 *coindexed-named-object* is *data-ref*

3 C620 (R614) The *data-ref* shall contain exactly one *part-ref*. The *part-ref* shall contain an *image-selector*.
4 The *part-name* shall be the name of a scalar coarray.

6.4.4 Complex parts

5 R615 *complex-part-designator* is *designator* % RE
6 or *designator* % IM

7 C621 (R615) The *designator* shall be of complex type.

8 1 If *complex-part-designator* is *designator*%RE it designates the real part of *designator*. If it is *designator*%IM
9 it designates the imaginary part of *designator*. The type of a *complex-part-designator* is real, and its kind and
10 shape are those of the *designator*.
11
12

NOTE 6.6

The following are examples of *complex part designators*:

impedance%re	!-- Same value as REAL(impedance)
fft%im	!-- Same value as AIMAG(fft)
x%im = 0.0	!-- Sets the imaginary part of X to zero

6.4.5 Type parameter inquiry

13 1 A *type parameter inquiry* is used to inquire about a type parameter of a data object. It applies to both intrinsic
14 and derived types.
15

16 R616 *type-param-inquiry* is *designator* % *type-param-name*

17 C622 (R616) The *type-param-name* shall be the name of a type parameter of the *declared type* of the object
18 designated by the *designator*.

19 2 A *deferred type parameter* of a pointer that is not associated or of an unallocated *allocatable* variable shall not
20 be inquired about.

NOTE 6.7

A *type-param-inquiry* has a syntax like that of a *structure component* reference, but it does not have the same semantics. It is not a variable and thus can never be assigned to. It can be used only as a primary in an expression. It is scalar even if *designator* is an array.

The intrinsic type parameters can also be inquired about by using the intrinsic functions *KIND* and *LEN*.

NOTE 6.8

The following are examples of type parameter inquiries:

```

a%kind      !-- A is real.  Same value as KIND(a).
s%len       !-- S is character.  Same value as LEN(s).
b(10)%kind  !-- Inquiry about an array element.
p%dim       !-- P is of the derived type general_point.

```

See Note 4.22 for the definition of the *general_point* type used in the last example above.

6.5 Arrays**6.5.1 Order of reference**

- 1 No order of reference to the elements of an array is indicated by the appearance of the array *designator*, except where array element ordering (6.5.3.2) is specified.

6.5.2 Whole arrays

- 1 A *whole array* is a named array or a structure component whose final *part-ref* is an array component name; no subscript list is appended.
- 2 The appearance of a *whole array* variable in an executable construct specifies all the elements of the array (2.4.6). The appearance of a *whole array designator* in a nonexecutable statement specifies the entire array except for the appearance of a *whole array designator* in an equivalence set (5.9.1.4). An *assumed-size array* (5.5.8.5) is permitted to appear as a *whole array* in an executable construct or *specification expression* only as an *actual argument* in a *procedure reference* that does not require the shape.

6.5.3 Array elements and array sections**6.5.3.1 Syntax**

R617 *array-element* is *data-ref*

C623 (R617) Every *part-ref* shall have *rank* zero and the last *part-ref* shall contain a *subscript-list*.

R618 *array-section* is *data-ref* [(*substring-range*)]
or *complex-part-designator*

C624 (R618) Exactly one *part-ref* shall have nonzero *rank*, and either the final *part-ref* shall have a *section-subscript-list* with nonzero *rank*, another *part-ref* shall have nonzero *rank*, or the *complex-part-designator* shall be an array.

C625 (R618) If a *substring-range* appears, the rightmost *part-name* shall be of type character.

R619 *subscript* is *scalar-int-expr*

R620 *section-subscript* is *subscript*
or *subscript-triplet*

or *vector-subscript*

R621 *subscript-triplet* is [*subscript*] : [*subscript*] [: *stride*]

R622 *stride* is *scalar-int-expr*

R623 *vector-subscript* is *int-expr*

C626 (R623) A *vector-subscript* shall be an integer array expression of rank one.

C627 (R621) The second subscript shall not be omitted from a *subscript-triplet* in the last dimension of an assumed-size array.

1 An array element is a scalar. An *array section* is an array. If a *substring-range* appears in an *array-section*, each element is the designated substring of the corresponding element of the *array section*.

2 The value of a subscript in an array element shall be within the bounds for its dimension.

NOTE 6.9

For example, with the declarations:

```
REAL A (10, 10)
CHARACTER (LEN = 10) B (5, 5, 5)
```

A (1, 2) is an array element, A (1:N:2, M) is a rank-one *array section*, and B (:, :, :) (2:3) is an array of shape (5, 5, 5) whose elements are substrings of length 2 of the corresponding elements of B.

NOTE 6.10

Unless otherwise specified, an array element or *array section* does not have an attribute of the *whole array*. In particular, an array element or an *array section* does not have the *POINTER* or *ALLOCATABLE* attribute.

NOTE 6.11

Examples of array elements and array sections are:

```
ARRAY_A(1:N:2)%ARRAY_B(I, J)%STRING(K)(:)    array section
SCALAR_PARENT%ARRAY_FIELD(J)                array element
SCALAR_PARENT%ARRAY_FIELD(1:N)              array section
SCALAR_PARENT%ARRAY_FIELD(1:N)%SCALAR_FIELD array section
```

6.5.3.2 Array element order

1 The elements of an array form a sequence known as the array element order. The position of an array element in this sequence is determined by the subscript order value of the subscript list designating the element. The subscript order value is computed from the formulas in Table 6.1.

Table 6.1: Subscript order value

Rank	Subscript bounds	Subscript list	Subscript order value
1	$j_1:k_1$	s_1	$1 + (s_1 - j_1)$
2	$j_1:k_1, j_2:k_2$	s_1, s_2	$1 + (s_1 - j_1)$ $+ (s_2 - j_2) \times d_1$
3	$j_1:k_1, j_2:k_2, j_3:k_3$	s_1, s_2, s_3	$1 + (s_1 - j_1)$ $+ (s_2 - j_2) \times d_1$ $+ (s_3 - j_3) \times d_2 \times d_1$
.	.	.	.
.	.	.	.

Subscript order value (cont.)

Rank	Subscript bounds	Subscript list	Subscript order value
.	.	.	.
15	$j_1:k_1, \dots, j_{15}:k_{15}$	s_1, \dots, s_{15}	$1 + (s_1 - j_1)$ $+ (s_2 - j_2) \times d_1$ $+ (s_3 - j_3) \times d_2 \times d_1$ $+ \dots$ $+ (s_{15} - j_{15}) \times d_{14}$ $\times d_{13} \times \dots \times d_1$
Notes for Table 6.1:			
1) $d_i = \max(k_i - j_i + 1, 0)$ is the size of the i th dimension.			
2) If the size of the array is nonzero, $j_i \leq s_i \leq k_i$ for all $i = 1, 2, \dots, 15$.			

1 **6.5.3.3 Array sections**

- 2 1 In an *array-section* having a *section-subscript-list*, each *subscript-triplet* and *vector-subscript* in the section sub-
- 3 script list indicates a sequence of subscripts, which may be empty. Each subscript in such a sequence shall be
- 4 within the bounds for its dimension unless the sequence is empty. The *array section* is the set of elements from
- 5 the array determined by all possible subscript lists obtainable from the single subscripts or sequences of subscripts
- 6 specified by each section subscript.
- 7 2 In an *array-section* with no *section-subscript-list*, the *rank* and shape of the array is the *rank* and shape of the
- 8 *part-ref* with nonzero *rank*; otherwise, the *rank* of the *array section* is the number of subscript triplets and *vector*
- 9 *subscripts* in the section subscript list. The shape is the rank-one array whose i th element is the number of
- 10 integer values in the sequence indicated by the i th subscript triplet or *vector subscript*. If any of these sequences
- 11 is empty, the *array section* has size zero. The subscript order of the elements of an *array section* is that of the
- 12 array data object that the *array section* represents.

13 **6.5.3.3.1 Subscript triplet**

- 14 1 A subscript triplet designates a regular sequence of subscripts consisting of zero or more subscript values. The
- 15 *stride* in the subscript triplet specifies the increment between the subscript values. The subscripts and stride of a
- 16 subscript triplet are optional. An omitted first subscript in a subscript triplet is equivalent to a subscript whose
- 17 value is the lower bound for the array and an omitted second subscript is equivalent to the upper bound. An
- 18 omitted stride is equivalent to a stride of 1.
- 19 2 The stride shall not be zero.
- 20 3 When the stride is positive, the subscripts specified by a triplet form a regularly spaced sequence of integers
- 21 beginning with the first subscript and proceeding in increments of the stride to the largest such integer not
- 22 greater than the second subscript; the sequence is empty if the first subscript is greater than the second.

NOTE 6.12

For example, suppose an array is declared as A (5, 4, 3). The section A (3 : 5, 2, 1 : 2) is the array of shape (3, 2):

A (3, 2, 1)	A (3, 2, 2)
A (4, 2, 1)	A (4, 2, 2)
A (5, 2, 1)	A (5, 2, 2)

- 23 4 When the stride is negative, the sequence begins with the first subscript and proceeds in increments of the stride
- 24 down to the smallest such integer equal to or greater than the second subscript; the sequence is empty if the
- 25 second subscript is greater than the first.

NOTE 6.13

For example, if an array is declared B (10), the section B (9 : 1 : -2) is the array of shape (5) whose elements are B (9), B (7), B (5), B (3), and B (1), in that order.

NOTE 6.14

A subscript in a subscript triplet need not be within the declared bounds for that dimension if all values used in selecting the array elements are within the declared bounds.

For example, if an array is declared as B (10), the **array section** B (3 : 11 : 7) is the array of shape (2) consisting of the elements B (3) and B (10), in that order.

1 **6.5.3.3.2 Vector subscript**

- 2 1 A **vector subscript** designates a sequence of subscripts corresponding to the values of the elements of the expression.
 3 Each element of the expression shall be defined.
- 4 2 An **array section** with a **vector subscript** shall not be **finalized** by a nonelemental **final subroutine**.
- 5 3 If a **vector subscript** has two or more elements with the same value, an **array section** with that **vector subscript**
 6 is not **definable** and shall not be **defined** or become **undefined**.

NOTE 6.15

For example, suppose Z is a two-dimensional array of shape [5, 7] and U and V are one-dimensional arrays of shape (3) and (4), respectively. Assume the values of U and V are:

U = [1, 3, 2]

V = [2, 1, 1, 3]

Then Z (3, V) consists of elements from the third row of Z in the order:

Z (3, 2) Z (3, 1) Z (3, 1) Z (3, 3)

and Z (U, 2) consists of the column elements:

Z (1, 2) Z (3, 2) Z (2, 2)

and Z (U, V) consists of the elements:

Z (1, 2) Z (1, 1) Z (1, 1) Z (1, 3)

Z (3, 2) Z (3, 1) Z (3, 1) Z (3, 3)

Z (2, 2) Z (2, 1) Z (2, 1) Z (2, 3)

Because Z (3, V) and Z (U, V) contain duplicate elements from Z, the sections Z (3, V) and Z (U, V) shall not be redefined as sections.

7 **6.5.4 Simply contiguous array designators**

- 8 1 A **section-subscript-list** specifies a **simply contiguous** section if and only if it does not have a **vector subscript** and
- 9 • all but the last **subscript-triplet** is a colon,
 10 • the last **subscript-triplet** does not have a **stride**, and
 11 • no **subscript-triplet** is preceded by a **section-subscript** that is a **subscript**.
- 12 2 An array designator is **simply contiguous** if and only if it is
- 13 • an **object-name** that has the **CONTIGUOUS** attribute,

- 1 • an *object-name* that is not a *pointer*, not *assumed-shape*, and not *assumed-rank*,
 2 • a *structure-component* whose final *part-name* is an array and that either has the *CONTIGUOUS* attribute
 3 or is not a pointer, or
 4 • an *array section*
 5 – that is not a *complex-part-designator*,
 6 – that does not have a *substring-range*,
 7 – whose final *part-ref* has nonzero *rank*,
 8 – whose rightmost *part-name* has the *CONTIGUOUS* attribute or is neither *assumed-shape* nor a pointer,
 9 and
 10 – which either does not have a *section-subscript-list*, or has a *section-subscript-list* which specifies a
 11 *simply contiguous* section.
- 12 3 An array *variable* is *simply contiguous* if and only if it is a *simply contiguous* array designator or a reference to
 13 a function that returns a pointer with the *CONTIGUOUS* attribute.

NOTE 6.16

Array sections that are *simply contiguous* include column, plane, cube, and hypercube subobjects of a *simply contiguous* base object, for example:

```

ARRAY1 (10:20, 3)    ! passes part of the third column of ARRAY1.
X3D (:, i:j, 2)     ! passes part of the second plane of X3D (or the whole
                   ! plane if i==LBOUND(X3D,2) and j==UBOUND(X3D,2)).
Y5D (:, :, :, :, 7) ! passes the seventh hypercube of Y5D.
```

All *simply contiguous* designators designate *contiguous* objects.

14 6.6 Image selectors

- 15 1 An image selector determines the *image index* for a *coindexed* object.
- 16 R624 *image-selector* **is** *lbracket cosubscript-list rbracket*
- 17 R625 *cosubscript* **is** *scalar-int-expr*
- 18 2 The number of *cosubscripts* shall be equal to the *corank* of the object. The value of a *cosubscript* in an image
 19 selector shall be within the *cobounds* for its *codimension*. Taking account of the *cobounds*, the *cosubscript* list in
 20 an image selector determines the *image index* in the same way that a subscript list in an array element determines
 21 the subscript order value (6.5.3.2), taking account of the bounds. An image selector shall specify an *image index*
 22 value that is not greater than the number of *images*.

NOTE 6.17

For example, if there are 16 *images* and the *coarray* A is declared

```
REAL :: A(10)[5,*]
```

A(:)[1,4] is valid because it specifies *image* 16, but A(:)[2,4] is invalid because it specifies *image* 17.

6.7 Dynamic association

6.7.1 ALLOCATE statement

6.7.1.1 Form of the ALLOCATE statement

1 The ALLOCATE statement dynamically creates pointer *targets* and *allocatable* variables.

R626 *allocate-stmt* is ALLOCATE ([*type-spec* ::] *allocation-list* ■
■ [, *alloc-opt-list*])

R627 *alloc-opt* is ERRMSG = *errmsg-variable*
or MOLD = *source-expr*
or SOURCE = *source-expr*
or STAT = *stat-variable*

R628 *stat-variable* is *scalar-int-variable*

R629 *errmsg-variable* is *scalar-default-char-variable*

R630 *source-expr* is *expr*

R631 *allocation* is *allocate-object* [(*allocate-shape-spec-list*)] ■
■ [*lbracket allocate-coarray-spec rbracket*]

R632 *allocate-object* is *variable-name*
or *structure-component*

R633 *allocate-shape-spec* is [*lower-bound-expr* :] *upper-bound-expr*

R634 *lower-bound-expr* is *scalar-int-expr*

R635 *upper-bound-expr* is *scalar-int-expr*

R636 *allocate-coarray-spec* is [*allocate-coshape-spec-list* ,] [*lower-bound-expr* :] *

R637 *allocate-coshape-spec* is [*lower-bound-expr* :] *upper-bound-expr*

C628 (R632) Each *allocate-object* shall be a data pointer or an *allocatable* variable.

C629 (R626) If any *allocate-object* has a deferred type parameter, is unlimited polymorphic, or is of abstract type, either *type-spec* or *source-expr* shall appear.

C630 (R626) If *type-spec* appears, it shall specify a type with which each *allocate-object* is type compatible.

C631 (R626) A *type-param-value* in a *type-spec* shall be an asterisk if and only if each *allocate-object* is a dummy argument for which the corresponding type parameter is assumed.

C632 (R626) If *type-spec* appears, the kind type parameter values of each *allocate-object* shall be the same as the corresponding type parameter values of the *type-spec*.

C633 (R626) If an *allocate-object* is an array, either *allocate-shape-spec-list* shall appear in its *allocation*, or *source-expr* shall appear in the ALLOCATE statement and have the same rank as the *allocate-object*.

C634 (R631) If *allocate-object* is scalar, *allocate-shape-spec-list* shall not appear.

C635 (R631) An *allocate-coarray-spec* shall appear if and only if the *allocate-object* is a *coarray*.

C636 (R631) The number of *allocate-shape-specs* in an *allocate-shape-spec-list* shall be the same as the rank of the *allocate-object*. The number of *allocate-coshape-specs* in an *allocate-coarray-spec* shall be one less than the *corank* of the *allocate-object*.

- 1 C637 (R627) No *alloc-opt* shall appear more than once in a given *alloc-opt-list*.
- 2 C638 (R626) At most one of *source-expr* and *type-spec* shall appear.
- 3 C639 (R626) Each *allocate-object* shall be *type compatible* (4.3.2.3) with *source-expr*. If SOURCE= appears,
4 *source-expr* shall be a scalar or have the same *rank* as each *allocate-object*.
- 5 C640 (R626) If *source-expr* appears, the *kind type parameters* of each *allocate-object* shall have the same values
6 as the corresponding *type parameters* of *source-expr*.
- 7 C641 (R626) *type-spec* shall not specify a type that has a *coarray ultimate component*.
- 8 C642 (R626) If an *allocate-object* is a *coarray*, *type-spec* shall not specify the type C_PTR or C_FUNPTR
9 from the intrinsic module ISO_C_BINDING.
- 10 C643 (R626) The *declared type* of *source-expr* shall not be C_PTR or C_FUNPTR from the intrinsic module
11 ISO_C_BINDING, or EVENT_TYPE or LOCK_TYPE from the intrinsic module ISO_FORTRAN_
12 ENV, or have a subcomponent of type EVENT_TYPE or LOCK_TYPE, if an *allocate-object* is a
13 *coarray*.
- 14 C644 (R630) The *declared type* of *source-expr* shall not have a *coarray ultimate component*.
- 15 C645 (R632) An *allocate-object* shall not be a coindexed object.

NOTE 6.18

If a *coarray* is of a derived type that has an *allocatable* component, the component shall be allocated by its own *image*:

```

TYPE(SOMETHING), ALLOCATABLE :: T[:]
...
ALLOCATE(T[*])           ! Allowed - implies synchronization
ALLOCATE(T%AA(N))       ! Allowed - allocated by its own image
ALLOCATE(T[Q]%AA(N))    ! Not allowed, because it is not
                        ! necessarily executed on image Q.

```

- 16 2 An *allocate-object* or a bound or type parameter of an *allocate-object* shall not depend on the value of *stat-variable*,
17 the value of *errmsg-variable*, or on the value, bounds, length type parameters, allocation status, or association
18 status of any *allocate-object* in the same ALLOCATE statement.
- 19 3 *source-expr* shall not be allocated within the ALLOCATE statement in which it appears; nor shall it depend on
20 the value, bounds, *deferred type parameters*, allocation status, or association status of any *allocate-object* in that
21 statement.
- 22 4 If an *allocate-object* is a *coarray*, the ALLOCATE statement shall not have a *source-expr* with a *dynamic type*
23 of C_PTR or C_FUNPTR from the intrinsic module ISO_C_BINDING, or EVENT_TYPE or LOCK_
24 TYPE from the intrinsic module ISO_FORTRAN_ENV, or which has a *subcomponent* whose *dynamic type*
25 is EVENT_TYPE or LOCK_TYPE.
- 26 5 If *type-spec* is specified, each *allocate-object* is allocated with the specified *dynamic type* and type parameter
27 values; if *source-expr* is specified, each *allocate-object* is allocated with the *dynamic type* and type parameter
28 values of *source-expr*; otherwise, each *allocate-object* is allocated with its *dynamic type* the same as its *declared*
29 *type*.
- 30 6 If *type-spec* appears and the value of a type parameter it specifies differs from the value of the corresponding
31 nondeferred type parameter specified in the declaration of any *allocate-object*, an error condition occurs. If the
32 value of a nondeferred length type parameter of an *allocate-object* differs from the value of the corresponding type
33 parameter of *source-expr*, an error condition occurs.

- 1 7 If a *type-param-value* in a *type-spec* in an ALLOCATE statement is an asterisk, it denotes the current value of
 2 that assumed type parameter. If it is an expression, subsequent redefinition or undefinition of any entity in the
 3 expression does not affect the type parameter value.

NOTE 6.19

An example of an ALLOCATE statement is:

```
ALLOCATE (X (N), B (-3 : M, 0:9), STAT = IERR_ALLOC)
```

4 6.7.1.2 Execution of an ALLOCATE statement

- 5 1 When an ALLOCATE statement is executed for an array for which *allocate-shape-spec-list* is specified, the values
 6 of the lower bound and upper bound expressions determine the bounds of the array. Subsequent redefinition
 7 or undefinition of any entities in the bound expressions do not affect the array bounds. If the lower bound is
 8 omitted, the default value is 1. If the upper bound is less than the lower bound, the extent in that dimension is
 9 zero and the array has zero size.
- 10 2 When an ALLOCATE statement is executed for a *coarray*, the values of the lower *cobound* and upper *cobound*
 11 expressions determine the *cobounds* of the *coarray*. Subsequent redefinition or undefinition of any entities in the
 12 *cobound* expressions do not affect the *cobounds*. If the lower *cobound* is omitted, the default value is 1. The
 13 upper *cobound* shall not be less than the lower *cobound*.
- 14 3 If an *allocation* specifies a *coarray*, its *dynamic type* and the values of corresponding type parameters shall be
 15 the same on every *image*. The values of corresponding bounds and corresponding *cobounds* shall be the same on
 16 every *image*. If the *coarray* is a *dummy argument*, its *ultimate argument* (12.5.2.3) shall be the same *coarray* on
 17 every *image*.
- 18 4 When an ALLOCATE statement is executed for which an *allocate-object* is a *coarray*, there is an implicit syn-
 19 chronization of all *images*. On each *image*, execution of the segment (8.5.2) following the statement is delayed
 20 until all other *images* have executed the same statement the same number of times.

NOTE 6.20

When an *image* executes an ALLOCATE statement, communication is not necessarily involved apart from any required for synchronization. The *image* allocates its *coarray* and records how the corresponding *coarrays* on other *images* are to be addressed. The processor is not required to detect violations of the rule that the bounds are the same on all *images*, nor is it responsible for detecting or resolving deadlock problems (such as two *images* waiting on different ALLOCATE statements).

- 21 5 If *source-expr* is a pointer, it shall be associated with a *target*. If *source-expr* is *allocatable*, it shall be allocated.
- 22 6 When an ALLOCATE statement is executed for an array with no *allocate-shape-spec-list*, the bounds of *source-*
 23 *expr* determine the bounds of the array. Subsequent changes to the bounds of *source-expr* do not affect the array
 24 bounds.
- 25 7 If SOURCE= appears, *source-expr* shall be *conformable* with *allocation*. If the value of a nondeferred *length*
 26 *type parameter* of *allocate-object* is different from the value of the corresponding *type parameter* of *source-expr*,
 27 an error condition occurs. If an *allocate-object* is not *polymorphic* and the *source-expr* is *polymorphic* with
 28 a *dynamic type* that differs from its *declared type*, the value provided for that *allocate-object* is the ancestor
 29 component of the *source-expr* that has the type of the *allocate-object*; otherwise the value provided is the value
 30 of the *source-expr*. On successful allocation, if *allocate-object* and *source-expr* have the same *rank* the value of
 31 *allocate-object* becomes the value provided, otherwise the value of each element of *allocate-object* becomes the
 32 value provided. The *source-expr* is evaluated exactly once for each execution of an ALLOCATE statement.
- 33 8 If MOLD= appears and *source-expr* is a variable, its value need not be defined.
- 34 9 The set of error conditions for an ALLOCATE statement is processor dependent. If an error condition occurs
 35 during execution of an ALLOCATE statement that does not contain the STAT= specifier, *error termination* is

1 initiated. The `STAT=` specifier is described in 6.7.4. The `ERRMSG=` specifier is described in 6.7.5.

2 6.7.1.3 Allocation of allocatable variables

3 1 The allocation status of an `allocatable` entity is one of the following at any time.

- 4 • The status of an `allocatable` variable becomes “allocated” if it is allocated by an `ALLOCATE` statement, if
5 it is allocated during assignment, or if it is given that status by the intrinsic subroutine `MOVE_ALLOC`
6 (13.8.129). An `allocatable` variable with this status may be referenced, defined, or deallocated; allocating
7 it causes an error condition in the `ALLOCATE` statement. The intrinsic function `ALLOCATED` (13.8.11)
8 returns true for such a variable.
- 9 • An `allocatable` variable has a status of “unallocated” if it is not allocated. The status of an `allocatable`
10 variable becomes unallocated if it is deallocated (6.7.3) or if it is given that status by the intrinsic subroutine
11 `MOVE_ALLOC`. An `allocatable` variable with this status shall not be referenced or defined. It shall not
12 be supplied as an `actual argument` corresponding to a nonallocatable `dummy argument`, except to certain
13 intrinsic `inquiry functions`. It may be allocated with the `ALLOCATE` statement. Deallocating it causes an
14 error condition in the `DEALLOCATE` statement. The intrinsic function `ALLOCATED` (13.8.11) returns
15 false for such a variable.

16 2 At the beginning of execution of a program, `allocatable` variables are unallocated.

17 3 When the allocation status of an `allocatable` variable changes, the allocation status of any associated `allocat-`
18 `able` variable changes accordingly. Allocation of an `allocatable` variable establishes values for the `deferred type`
19 `parameters` of all associated `allocatable` variables.

20 4 An `unsaved allocatable local variable` of a procedure has a status of unallocated at the beginning of each invocation
21 of the procedure. An `unsaved local variable` of a construct has a status of unallocated at the beginning of each
22 execution of the construct.

23 5 When an object of derived type is created by an `ALLOCATE` statement, any `allocatable ultimate components`
24 have an allocation status of unallocated unless the `SOURCE=` specifier appears and the corresponding component
25 of the `source-expr` is allocated.

26 6 If the evaluation of a function would change the allocation status of a variable and if a reference to the function
27 appears in an expression in which the value of the function is not needed to determine the value of the expression,
28 the allocation status of the variable after evaluation of the expression is processor dependent.

29 6.7.1.4 Allocation of pointer targets

30 1 Allocation of a `pointer` creates an object that implicitly has the `TARGET` attribute. Following successful execution
31 of an `ALLOCATE` statement for a `pointer`, the `pointer` is associated with the `target` and may be used to reference
32 or define the `target`. Additional `pointers` may become associated with the `pointer target` or a part of the `pointer`
33 `target` by `pointer assignment`. It is not an error to allocate a `pointer` that is already associated with a `target`.
34 In this case, a new `pointer target` is created as required by the attributes of the `pointer` and any array bounds,
35 type, and type parameters specified by the `ALLOCATE` statement. The `pointer` is then associated with this
36 new `target`. Any previous association of the `pointer` with a `target` is broken. If the previous `target` had been
37 created by allocation, it becomes inaccessible unless other `pointers` are associated with it. The intrinsic function
38 `ASSOCIATED` (13.8.16) may be used to determine whether a `pointer` that does not have undefined association
39 status is associated.

40 2 At the beginning of execution of a function whose result is a `pointer`, the association status of the result `pointer`
41 is undefined. Before such a function returns, it shall either associate a `target` with this `pointer` or cause the
42 association status of this `pointer` to become `disassociated`.

43 6.7.2 NULLIFY statement

44 1 The `NULLIFY` statement causes `pointers` to be `disassociated`.

1 R638 *nullify-stmt* is NULLIFY (*pointer-object-list*)

2 R639 *pointer-object* is *variable-name*
 3 or *structure-component*
 4 or *proc-pointer-name*

5 C646 (R639) Each *pointer-object* shall have the POINTER attribute.

6 2 A *pointer-object* shall not depend on the value, bounds, or association status of another *pointer-object* in the
 7 same NULLIFY statement.

NOTE 6.21

When a NULLIFY statement is applied to a polymorphic pointer (4.3.2.3), its dynamic type becomes the declared type.

8 6.7.3 DEALLOCATE statement

9 6.7.3.1 Form of the DEALLOCATE statement

10 1 The DEALLOCATE statement causes allocatable variables to be deallocated; it causes pointer targets to be
 11 deallocated and the pointers to be disassociated.

12 R640 *deallocate-stmt* is DEALLOCATE (*allocate-object-list* [, *dealloc-opt-list*])

13 R641 *dealloc-opt* is STAT = *stat-variable*
 14 or ERRMSG = *errmsg-variable*

15 C647 (R641) No *dealloc-opt* shall appear more than once in a given *dealloc-opt-list*.

16 2 An *allocate-object* shall not depend on the value, bounds, allocation status, or association status of another
 17 *allocate-object* in the same DEALLOCATE statement; it also shall not depend on the value of the *stat-variable*
 18 or *errmsg-variable* in the same DEALLOCATE statement.

19 3 The set of error conditions for a DEALLOCATE statement is processor dependent. If an error condition occurs
 20 during execution of a DEALLOCATE statement that does not contain the STAT= specifier, error termination is
 21 initiated. The STAT= specifier is described in 6.7.4. The ERRMSG= specifier is described in 6.7.5.

22 4 When more than one allocated object is deallocated by execution of a DEALLOCATE statement, the order of
 23 deallocation is processor dependent.

NOTE 6.22

An example of a DEALLOCATE statement is:

```
DEALLOCATE (X, B)
```

24 6.7.3.2 Deallocation of allocatable variables

25 1 Deallocating an unallocated allocatable variable causes an error condition in the DEALLOCATE statement.
 26 Deallocating an allocatable variable with the TARGET attribute causes the pointer association status of any
 27 pointer associated with it to become undefined. An allocatable variable shall not be deallocated if it or any
 28 subobject of it is argument associated with a dummy argument or construct associated with an associate name.

29 2 When the execution of a procedure is terminated by execution of a RETURN or END statement, an unsaved
 30 allocatable local variable of the procedure retains its allocation and definition status if it is a function result or a
 31 subobject thereof; otherwise, if it is allocated it will be deallocated.

32 3 When a BLOCK construct terminates, any unsaved allocated allocatable local variable of the construct is deal-
 33 located.

- 1 4 If an executable construct references a function whose result is [allocatable](#) or has an [allocatable](#) subobject, and
 2 the function reference is executed, an [allocatable](#) result and any allocated [allocatable](#) subobject of the result is
 3 deallocated after execution of the innermost executable construct containing the reference.
- 4 5 If a function whose result is [allocatable](#) or has an [allocatable](#) subobject is referenced in the specification part of a
 5 [scoping unit](#), and the function reference is executed, an [allocatable](#) result and any allocated [allocatable](#) subobject
 6 of the result is deallocated before execution of the executable constructs of the [scoping unit](#).
- 7 6 When a procedure is invoked, any allocated [allocatable](#) object that is an [actual argument](#) corresponding to an
 8 [INTENT \(OUT\) allocatable dummy argument](#) is deallocated; any allocated [allocatable](#) object that is a subobject
 9 of an [actual argument](#) corresponding to an [INTENT \(OUT\) dummy argument](#) is deallocated. If a Fortran proced-
 10 ure that has an [INTENT \(OUT\) allocatable dummy argument](#) is invoked by a C function and the corresponding
 11 argument in the C function call is a [C descriptor](#) that describes an allocated [allocatable](#) variable, the variable
 12 is deallocated on entry to the Fortran procedure. If a C function is invoked from a Fortran procedure via an
 13 interface with an [INTENT \(OUT\) allocatable dummy argument](#) and the corresponding [actual argument](#) in the
 14 reference to the C function is an allocated [allocatable](#) variable, the variable is deallocated on invocation (before
 15 execution of the C function begins).
- 16 7 When an [intrinsic assignment statement \(7.2.1.3\)](#) is executed, any noncoarray allocated [allocatable](#) subobject of
 17 the variable is deallocated before the assignment takes place.
- 18 8 When a variable of derived type is deallocated, any allocated [allocatable](#) subobject is deallocated. If an error
 19 condition occurs during deallocation, it is [processor dependent](#) whether an allocated [allocatable subobject](#) is
 20 deallocated.
- 21 9 If an [allocatable](#) component is a subobject of a [finalizable](#) object, that object is finalized before the component is
 22 automatically deallocated.
- 23 10 When a statement that deallocates a [coarray](#) is executed, there is an implicit synchronization of all [images](#).
 24 On each [image](#), execution of the segment [\(8.5.2\)](#) following the statement is delayed until all other [images](#) have
 25 executed the same statement the same number of times. If an [allocate-object](#) is a [coarray dummy argument](#), its
 26 [ultimate argument \(12.5.2.3\)](#) shall be the same [coarray](#) on every [image](#).
- 27 11 The effect of automatic deallocation is the same as that of a DEALLOCATE statement without a [dealloc-opt-list](#).

NOTE 6.23

In the following example:

```
SUBROUTINE PROCESS
  REAL, ALLOCATABLE :: TEMP(:)
  REAL, ALLOCATABLE, SAVE :: X(:)
  ...
END SUBROUTINE PROCESS
```

on return from subroutine PROCESS, the allocation status of X is preserved because X has the [SAVE attribute](#). TEMP does not have the [SAVE attribute](#), so it will be deallocated if it was allocated. On the next invocation of PROCESS, TEMP will have an allocation status of unallocated.

NOTE 6.24

For example, executing a [RETURN](#), [END](#), or [END BLOCK](#) statement, or deallocating an object that has an [allocatable subobject](#), can cause deallocation of a [coarray](#), and thus an implicit synchronization of all [images](#).

28 **6.7.3.3 Deallocation of pointer targets**

- 29 1 If a pointer appears in a DEALLOCATE statement, its association status shall be defined. Deallocating a pointer
 30 that is [disassociated](#) or whose [target](#) was not created by an ALLOCATE statement causes an error condition

1 in the DEALLOCATE statement. If a pointer is associated with an [allocatable](#) entity, the pointer shall not be
2 deallocated. A [pointer](#) shall not be deallocated if its [target](#) or any [subobject](#) thereof is [argument associated](#) with
3 a [dummy argument](#) or [construct associated](#) with an [associate name](#).

4 2 If a pointer appears in a DEALLOCATE statement, it shall be associated with the whole of an object that was
5 created by allocation. The pointer shall have the same [dynamic type](#) and type parameters as the allocated object,
6 and if the allocated object is an array the pointer shall be an array whose elements are the same as those of the
7 allocated object in array element order. Deallocating a pointer [target](#) causes the pointer association status of any
8 other pointer that is associated with the [target](#) or a portion of the [target](#) to become undefined.

9 **6.7.4 STAT= specifier**

10 1 The [stat-variable](#) shall not be allocated or deallocated within the [ALLOCATE](#) or [DEALLOCATE](#) statement
11 in which it appears; nor shall it depend on the value, [bounds](#), [deferred type parameters](#), allocation status, or
12 association status of any [allocate-object](#) in that statement.

13 2 If the STAT= specifier appears, successful execution of the [ALLOCATE](#) or [DEALLOCATE](#) statement causes the
14 [stat-variable](#) to become defined with a value of zero.

15 3 If an [ALLOCATE](#) or [DEALLOCATE](#) statement with a [coarray allocate-object](#) is executed when one or more [im-](#)
16 [ages](#) has initiated [normal termination](#) of execution, the [stat-variable](#) becomes defined with the processor-dependent
17 positive integer value of the constant [STAT_STOPPED_IMAGE](#) from the intrinsic module [ISO_FORTRAN_-](#)
18 [ENV \(13.9.2\)](#). If any other error condition occurs during execution of the [ALLOCATE](#) or [DEALLOCATE](#)
19 statement, the [stat-variable](#) becomes defined with a processor-dependent positive integer value different from
20 [STAT_STOPPED_IMAGE](#). In either case, each [allocate-object](#) has a processor-dependent status:

- 21 • each [allocate-object](#) that was successfully allocated shall have an allocation status of allocated or a [pointer](#)
22 [association](#) status of associated;
- 23 • each [allocate-object](#) that was successfully deallocated shall have an allocation status of unallocated or a
24 [pointer association](#) status of [disassociated](#);
- 25 • each [allocate-object](#) that was not successfully allocated or deallocated shall retain its previous allocation
26 status or [pointer association](#) status.

NOTE 6.25

The status of objects that were not successfully allocated or deallocated can be individually checked with the intrinsic functions [ALLOCATED](#) or [ASSOCIATED](#).

27 **6.7.5 ERRMSG= specifier**

28 1 The [errmsg-variable](#) shall not be allocated or deallocated within the [ALLOCATE](#) or [DEALLOCATE](#) statement
29 in which it appears; nor shall it depend on the value, [bounds](#), [deferred type parameters](#), allocation status, or
30 association status of any [allocate-object](#) in that statement.

31 2 If an error condition occurs during execution of an [ALLOCATE](#) or [DEALLOCATE](#) statement, the [errmsg-variable](#)
32 is assigned an explanatory message, as if by [intrinsic assignment](#). If no such condition occurs, the definition status
33 and value of [errmsg-variable](#) are unchanged.

7 Expressions and assignment

7.1 Expressions

7.1.1 Expression semantics

- 1 An expression represents either a data object reference or a computation, and its value is either a scalar or an array. Evaluation of an expression produces a value, which has a type, type parameters (if appropriate), and a shape (7.1.9). The *corank* of an expression that is not a variable is zero.

7.1.2 Form of an expression

7.1.2.1 Overall expression syntax

- 1 An expression is formed from operands, operators, and parentheses. An operand is either a scalar or an array. An operation is either intrinsic (7.1.5) or defined (7.1.6). More complicated expressions can be formed using operands which are themselves expressions.
- 2 An expression is defined in terms of several categories: primary, level-1 expression, level-2 expression, level-3 expression, level-4 expression, and level-5 expression.
- 3 These categories are related to the different operator precedence levels and, in general, are defined in terms of other categories. The simplest form of each expression category is a *primary*.

7.1.2.2 Primary

R701 *primary* is *constant*
 or *designator*
 or *array-constructor*
 or *structure-constructor*
 or *function-reference*
 or *type-param-inquiry*
 or *type-param-name*
 or (*expr*)

C701 (R701) The *type-param-name* shall be the name of a type parameter.

C702 (R701) The *designator* shall not be a whole *assumed-size array*.

C703 (R701) The *expr* shall not be a function reference that returns a procedure pointer.

NOTE 7.1

Examples of a *primary* are:

<u>Example</u>	<u>Syntactic class</u>
1.0	<i>constant</i>
'ABCDEFGHIJKLMNQRSTUWXYZ' (I:I)	<i>designator</i>
[1.0, 2.0]	<i>array-constructor</i>
PERSON ('Jones', 12)	<i>structure-constructor</i>
F (X, Y)	<i>function-reference</i>
X%KIND	<i>type-param-inquiry</i>
KIND	<i>type-param-name</i>
(S + T)	(<i>expr</i>)

1 7.1.2.3 Level-1 expressions

2 1 Defined unary operators have the highest operator precedence (Table 7.1). Level-1 expressions are primaries
3 optionally operated on by defined unary operators:

4 R702 *level-1-expr* is [*defined-unary-op*] *primary*

5 R703 *defined-unary-op* is . *letter* [*letter*]

6 C704 (R703) A *defined-unary-op* shall not contain more than 63 letters and shall not be the same as any
7 *intrinsic-operator* or *logical-literal-constant*.

NOTE 7.2

Simple examples of a level-1 expression are:

<u>Example</u>	<u>Syntactic class</u>
A	<i>primary</i> (R701)
. INVERSE. B	<i>level-1-expr</i> (R702)

A more complicated example of a level-1 expression is:

. INVERSE. (A + B)

8 7.1.2.4 Level-2 expressions

9 1 Level-2 expressions are level-1 expressions optionally involving the numeric operators *power-op*, *mult-op*, and
10 *add-op*.

11 R704 *mult-operand* is *level-1-expr* [*power-op mult-operand*]

12 R705 *add-operand* is [*add-operand mult-op*] *mult-operand*

13 R706 *level-2-expr* is [[*level-2-expr*] *add-op*] *add-operand*

14 R707 *power-op* is **

15 R708 *mult-op* is *
16 or /

17 R709 *add-op* is +
18 or -

NOTE 7.3

Simple examples of a level-2 expression are:

<u>Example</u>	<u>Syntactic class</u>	<u>Remarks</u>
A	<i>level-1-expr</i>	A is a <i>primary</i> . (R702)
B ** C	<i>mult-operand</i>	B is a <i>level-1-expr</i> , ** is a <i>power-op</i> , and C is a <i>mult-operand</i> . (R704)
D * E	<i>add-operand</i>	D is an <i>add-operand</i> , * is a <i>mult-op</i> , and E is a <i>mult-operand</i> . (R705)
+1	<i>level-2-expr</i>	+ is an <i>add-op</i> and 1 is an <i>add-operand</i> . (R706)
F - I	<i>level-2-expr</i>	F is a <i>level-2-expr</i> , - is an <i>add-op</i> , and I is an <i>add-operand</i> . (R706)

NOTE 7.3 (cont.)

A more complicated example of a level-2 expression is:

- A + D * E + B ** C

1 **7.1.2.5 Level-3 expressions**

2 1 Level-3 expressions are level-2 expressions optionally involving the character operator *concat-op*.

3 R710 *level-3-expr* **is** [*level-3-expr concat-op*] *level-2-expr*

4 R711 *concat-op* **is** //

NOTE 7.4

Simple examples of a level-3 expression are:

<u>Example</u>	<u>Syntactic class</u>
A	<i>level-2-expr</i> (R706)
B // C	<i>level-3-expr</i> (R710)

A more complicated example of a level-3 expression is:

X // Y // 'ABCD'

5 **7.1.2.6 Level-4 expressions**

6 1 Level-4 expressions are level-3 expressions optionally involving the relational operators *rel-op*.

7 R712 *level-4-expr* **is** [*level-3-expr rel-op*] *level-3-expr*

8 R713 *rel-op* **is** .EQ.
9 **or** .NE.
10 **or** .LT.
11 **or** .LE.
12 **or** .GT.
13 **or** .GE.
14 **or** ==
15 **or** /=
16 **or** <
17 **or** <=
18 **or** >
19 **or** >=

NOTE 7.5

Simple examples of a level-4 expression are:

<u>Example</u>	<u>Syntactic class</u>
A	<i>level-3-expr</i> (R710)
B == C	<i>level-4-expr</i> (R712)
D < E	<i>level-4-expr</i> (R712)

A more complicated example of a level-4 expression is:

(A + B) /= C

1 **7.1.2.7 Level-5 expressions**

2 1 Level-5 expressions are level-4 expressions optionally involving the logical operators *not-op*, *and-op*, *or-op*, and
3 *equiv-op*.

4	R714	<i>and-operand</i>	is	[<i>not-op</i>] <i>level-4-expr</i>
5	R715	<i>or-operand</i>	is	[<i>or-operand and-op</i>] <i>and-operand</i>
6	R716	<i>equiv-operand</i>	is	[<i>equiv-operand or-op</i>] <i>or-operand</i>
7	R717	<i>level-5-expr</i>	is	[<i>level-5-expr equiv-op</i>] <i>equiv-operand</i>
8	R718	<i>not-op</i>	is	.NOT.
9	R719	<i>and-op</i>	is	.AND.
10	R720	<i>or-op</i>	is	.OR.
11	R721	<i>equiv-op</i>	is	.EQV.
12			or	.NEQV.

NOTE 7.6

Simple examples of a level-5 expression are:

<u>Example</u>	<u>Syntactic class</u>
A	<i>level-4-expr</i> (R712)
.NOT. B	<i>and-operand</i> (R714)
C .AND. D	<i>or-operand</i> (R715)
E .OR. F	<i>equiv-operand</i> (R716)
G .EQV. H	<i>level-5-expr</i> (R717)
S .NEQV. T	<i>level-5-expr</i> (R717)

A more complicated example of a level-5 expression is:

A .AND. B .EQV. .NOT. C

13 **7.1.2.8 General form of an expression**

14 1 Expressions are level-5 expressions optionally involving defined binary operators. Defined binary operators have
15 the lowest operator precedence (Table 7.1).

16 R722 *expr* is [*expr defined-binary-op*] *level-5-expr*

17 R723 *defined-binary-op* is . *letter* [*letter*]

18 C705 (R723) A *defined-binary-op* shall not contain more than 63 letters and shall not be the same as any
19 *intrinsic-operator* or *logical-literal-constant*.

NOTE 7.7

Simple examples of an expression are:

<u>Example</u>	<u>Syntactic class</u>
A	<i>level-5-expr</i> (R717)
B.UNION.C	<i>expr</i> (R722)

NOTE 7.7 (cont.)

More complicated examples of an expression are:

```
(B .INTERSECT. C) .UNION. (X - Y)
A + B == C * D
.INVERSE. (A + B)
A + B .AND. C * D
E // G == H (1:10)
```

7.1.3 Precedence of operators

1 There is a precedence among the intrinsic and extension operations corresponding to the form of expressions
 2 specified in 7.1.2, which determines the order in which the operands are combined unless the order is changed by
 3 the use of parentheses. This precedence order is summarized in Table 7.1.
 4

Table 7.1: Categories of operations and relative precedence

Category of operation	Operators	Precedence
Extension	<i>defined-unary-op</i>	Highest
Numeric	**	.
Numeric	*, /	.
Numeric	unary +, -	.
Numeric	binary +, -	.
Character	//	.
Relational	.EQ., .NE., .LT., .LE., .GT., .GE., ==, /=, <, <=, >, >=	.
Logical	.NOT.	.
Logical	.AND.	.
Logical	.OR.	.
Logical	.EQV., .NEQV.	.
Extension	<i>defined-binary-op</i>	Lowest

5 2 The precedence of a *defined operation* is that of its operator.

NOTE 7.8

For example, in the expression

```
-A ** 2
```

the exponentiation operator (**) has precedence over the negation operator (-); therefore, the operands of the exponentiation operator are combined to form an expression that is used as the operand of the negation operator. The interpretation of the above expression is the same as the interpretation of the expression

```
-(A ** 2)
```

6 3 The general form of an expression (7.1.2) also establishes a precedence among operators in the same syntactic class.
 7 This precedence determines the order in which the operands are to be combined in determining the interpretation
 8 of the expression unless the order is changed by the use of parentheses.

NOTE 7.9

In interpreting a *level-2-expr* containing two or more binary operators + or -, each operand (*add-operand*) is combined from left to right. Similarly, the same left-to-right interpretation for a *mult-operand* in *add-operand*, as well as for other kinds of expressions, is a consequence of the general form. However, for interpreting a *mult-operand* expression when two or more exponentiation operators ** combine *level-1-expr* operands, each *level-1-expr* is combined from right to left.

NOTE 7.9 (cont.)

For example, the expressions

```
2.1 + 3.4 + 4.9
2.1 * 3.4 * 4.9
2.1 / 3.4 / 4.9
2 ** 3 ** 4
'AB' // 'CD' // 'EF'
```

have the same interpretations as the expressions

```
(2.1 + 3.4) + 4.9
(2.1 * 3.4) * 4.9
(2.1 / 3.4) / 4.9
2 ** (3 ** 4)
('AB' // 'CD') // 'EF'
```

As a consequence of the general form (7.1.2), only the first *add-operand* of a *level-2-expr* can be preceded by the identity (+) or negation (-) operator. These formation rules do not permit expressions containing two consecutive numeric operators, such as $A ** -B$ or $A + -B$. However, expressions such as $A ** (-B)$ and $A + (-B)$ are permitted. The rules do allow a binary operator or an intrinsic unary operator to be followed by a defined unary operator, such as:

```
A * .INVERSE. B
- .INVERSE. (B)
```

As another example, in the expression

```
A .OR. B .AND. C
```

the general form implies a higher precedence for the *.AND.* operator than for the *.OR.* operator; therefore, the interpretation of the above expression is the same as the interpretation of the expression

```
A .OR. (B .AND. C)
```

NOTE 7.10

An expression can contain more than one category of operator. The logical expression

```
L .OR. A + B >= C
```

where A, B, and C are of type real, and L is of type logical, contains a numeric operator, a relational operator, and a logical operator. This expression would be interpreted the same as the expression

```
L .OR. ((A + B) >= C)
```

NOTE 7.11

If

- the operator **** is extended to type logical,
- the operator *.STARSTAR.* is defined to duplicate the function of **** on type real,
- *.MINUS.* is defined to duplicate the unary operator *-*, and
- L1 and L2 are type logical and X and Y are type real,

then in precedence: L1 **** L2 is higher than X * Y; X * Y is higher than X *.STARSTAR.* Y; and *.MINUS.* X is higher than -X.

7.1.4 Evaluation of operations

- 1 An intrinsic operation requires the values of its operands.
- 2 Execution of a function reference in the logical expression in an **IF statement** (8.1.7.4), the mask expression in a **WHERE statement** (7.2.3.1), or the *concurrent-limits* and *concurrent-steps* in a **FORALL statement** (7.2.4) is permitted to define variables in the subsidiary *action-stmt*, *where-assignment-stmt*, or *forall-assignment-stmt* respectively. Except in those cases:
- the evaluation of a function reference shall neither affect nor be affected by the evaluation of any other entity within the statement;
 - if a function reference causes definition or undefinition of an **actual argument** of the function, that argument or any associated entities shall not appear elsewhere in the same statement.

NOTE 7.12

For example, the statements

```
A (I) = F (I)
Y = G (X) + X
```

are prohibited if the reference to F defines or undefines I or the reference to G defines or undefines X.

However, in the statements

```
IF (F (X)) A = X
WHERE (G (X)) B = X
```

the reference to F and/or the reference to G can define X.

- 3 The appearance of an array constructor requires the evaluation of each *scalar-int-expr* of the *ac-implied-do-control* in any *ac-implied-do* it may contain.
- 4 When an **elemental** binary operation is applied to a scalar and an array or to two arrays of the same shape, the operation is performed element-by-element on corresponding array elements of the array operands.

NOTE 7.13

For example, the array expression

```
A + B
```

produces an array of the same shape as A and B. The individual array elements of the result have the values of the first element of A added to the first element of B, the second element of A added to the second element of B, etc.

- 5 When an **elemental** unary operator operates on an array operand, the operation is performed element-by-element, and the result is the same shape as the operand. If an **elemental operation** is intrinsically pure or is implemented by a pure **elemental** function (12.8), the element operations may be performed simultaneously or in any order.

7.1.5 Intrinsic operations

7.1.5.1 Intrinsic operation classification

- 1 An intrinsic operation is either a unary or binary operation. An intrinsic unary operation is an operation of the form *intrinsic-operator* x_2 where x_2 is of an intrinsic type (4.4) listed in Table 7.2 for the unary intrinsic operator.
- 2 An intrinsic binary operation is an operation of the form x_1 *intrinsic-operator* x_2 where x_1 and x_2 are **conformable** and of the intrinsic types (4.4) listed in Table 7.2 for the binary intrinsic operator.

- 1 3 A numeric intrinsic operation is an intrinsic operation for which the *intrinsic-operator* is a numeric operator (+, 2 -, *, /, or **). A numeric intrinsic operator is the operator in a numeric intrinsic operation.
- 3 4 The character intrinsic operation is the intrinsic operation for which the *intrinsic-operator* is (//) and both 4 operands are of type character with the same *kind type parameter*. The character intrinsic operator is the 5 operator in a character intrinsic operation.
- 6 5 A logical intrinsic operation is an intrinsic operation for which the *intrinsic-operator* is *.AND.*, *.OR.*, *.NOT.*, 7 *.EQV.*, or *.NEQV.* and both operands are of type logical. A logical intrinsic operator is the operator in a logical 8 intrinsic operation.
- 9 6 A relational intrinsic operator is an *intrinsic-operator* that is *.EQ.*, *.NE.*, *.GT.*, *.GE.*, *.LT.*, *.LE.*, *==*, */=*, *>*, 10 *>=*, *<*, or *<=*. A relational intrinsic operation is an intrinsic operation for which the *intrinsic-operator* is a 11 relational intrinsic operator. A numeric relational intrinsic operation is a relational intrinsic operation for which 12 both operands are of *numeric type*. A character relational intrinsic operation is a relational intrinsic operation for 13 which both operands are of type character. The *kind type parameters* of the operands of a character relational 14 intrinsic operation shall be the same.
- 15 7 The interpretations defined in subclause 7.1.5 apply to both scalars and arrays; the interpretation for arrays is 16 obtained by applying the interpretation for scalars element by element.

NOTE 7.14

For example, if X is of type real, J is of type integer, and INT is the real-to-integer intrinsic conversion function, the expression INT (X + J) is an integer expression and X + J is a real expression.

Table 7.2: **Type of operands and results for intrinsic operators**

Intrinsic operator <i>op</i>	Type of x_1	Type of x_2	Type of $[x_1] op x_2$
Unary +, -		I, R, Z	I, R, Z
Binary +, -, *, /, **	I	I, R, Z	I, R, Z
	R	I, R, Z	R, R, Z
	Z	I, R, Z	Z, Z, Z
//	C	C	C
<i>.EQ.</i> , <i>.NE.</i> , <i>==</i> , <i>/=</i>	I	I, R, Z	L, L, L
	R	I, R, Z	L, L, L
	Z	I, R, Z	L, L, L
	C	C	L
<i>.GT.</i> , <i>.GE.</i> , <i>.LT.</i> , <i>.LE.</i> <i>></i> , <i>>=</i> , <i><</i> , <i><=</i>	I	I, R	L, L
	R	I, R	L, L
	C	C	L
<i>.NOT.</i>		L	L
<i>.AND.</i> , <i>.OR.</i> , <i>.EQV.</i> , <i>.NEQV.</i>	L	L	L
Note: The symbols I, R, Z, C, and L stand for the types integer, real, complex, character, and logical, respectively. Where more than one type for x_2 is given, the type of the result of the operation is given in the same relative position in the next column.			

17 **7.1.5.2 Numeric intrinsic operations**18 **7.1.5.2.1 Interpretation of numeric intrinsic operations**

- 19 1 The two operands of numeric intrinsic binary operations may be of different *numeric types* or different *kind type* 20 *parameters*. Except for a value raised to an integer power, if the operands have different types or *kind type* 21 *parameters*, the effect is as if each operand that differs in type or *kind type parameter* from those of the result is 22 converted to the type and *kind type parameter* of the result before the operation is performed. When a value of

- 1 type real or complex is raised to an integer power, the integer operand need not be converted.
- 2 2 A numeric operation is used to express a numeric computation. Evaluation of a numeric operation produces a
3 numeric value. The permitted data types for operands of the numeric intrinsic operations are specified in 7.1.5.1.
- 4 3 The numeric operators and their interpretation in an expression are given in Table 7.3, where x_1 denotes the
5 operand to the left of the operator and x_2 denotes the operand to the right of the operator.

Table 7.3: Interpretation of the numeric intrinsic operators

Operator	Representing	Use of operator	Interpretation
**	Exponentiation	$x_1 ** x_2$	Raise x_1 to the power x_2
/	Division	x_1 / x_2	Divide x_1 by x_2
*	Multiplication	$x_1 * x_2$	Multiply x_1 by x_2
-	Subtraction	$x_1 - x_2$	Subtract x_2 from x_1
-	Negation	$- x_2$	Negate x_2
+	Addition	$x_1 + x_2$	Add x_1 and x_2
+	Identity	$+ x_2$	Same as x_2

- 6 4 The interpretation of a division operation depends on the types of the operands (7.1.5.2.2).
- 7 5 If x_1 and x_2 are of type integer and x_2 has a negative value, the interpretation of $x_1 ** x_2$ is the same as the
8 interpretation of $1/(x_1 ** \text{ABS}(x_2))$, which is subject to the rules of integer division (7.1.5.2.2).

NOTE 7.15

For example, $2 ** (-3)$ has the value of $1/(2 ** 3)$, which is zero.

9 **7.1.5.2.2 Integer division**

- 10 1 One operand of type integer may be divided by another operand of type integer. Although the mathematical
11 quotient of two integers is not necessarily an integer, Table 7.2 specifies that an expression involving the division
12 operator with two operands of type integer is interpreted as an expression of type integer. The result of such an
13 operation is the integer closest to the mathematical quotient and between zero and the mathematical quotient
14 inclusively.

NOTE 7.16

For example, the expression $(-8) / 3$ has the value (-2) .

15 **7.1.5.2.3 Complex exponentiation**

- 16 1 In the case of a complex value raised to a complex power, the value of the operation $x_1 ** x_2$ is the principal
17 value of $x_1^{x_2}$.

18 **7.1.5.2.4 Evaluation of numeric intrinsic operations**

- 19 1 The execution of any numeric operation whose result is not defined by the arithmetic used by the processor is
20 prohibited. Raising a negative-valued primary of type real to a real power is prohibited.
- 21 2 Once the interpretation of a numeric intrinsic operation is established, the processor may evaluate any mathem-
22 atically equivalent expression, provided that the integrity of parentheses is not violated.
- 23 3 Two expressions of a **numeric type** are mathematically equivalent if, for all possible values of their primaries, their
24 mathematical values are equal. However, mathematically equivalent expressions of **numeric type** may produce
25 different computational results.

NOTE 7.17

Any difference between the values of the expressions $(1./3.)*3.$ and $1.$ is a computational difference, not a mathematical difference. The difference between the values of the expressions $5/2$ and $5./2.$ is a mathematical difference, not a computational difference.

The mathematical definition of integer division is given in [7.1.5.2.2](#).

NOTE 7.18

The following are examples of expressions with allowable alternative forms that can be used by the processor in the evaluation of those expressions. A, B, and C represent arbitrary real or complex operands; I and J represent arbitrary integer operands; and X, Y, and Z represent arbitrary operands of [numeric type](#).

<u>Expression</u>	<u>Allowable alternative form</u>
$X + Y$	$Y + X$
$X * Y$	$Y * X$
$-X + Y$	$Y - X$
$X + Y + Z$	$X + (Y + Z)$
$X - Y + Z$	$X - (Y - Z)$
$X * A / Z$	$X * (A / Z)$
$X * Y - X * Z$	$X * (Y - Z)$
$A / B / C$	$A / (B * C)$
$A / 5.0$	$0.2 * A$

The following are examples of expressions with forbidden alternative forms that cannot be used by a processor in the evaluation of those expressions.

<u>Expression</u>	<u>Forbidden alternative form</u>
$I / 2$	$0.5 * I$
$X * I / J$	$X * (I / J)$
$I / J / A$	$I / (J * A)$
$(X + Y) + Z$	$X + (Y + Z)$
$(X * Y) - (X * Z)$	$X * (Y - Z)$
$X * (Y - Z)$	$X * Y - X * Z$

NOTE 7.19

In addition to the parentheses required to establish the desired interpretation, parentheses can be included to restrict the alternative forms that can be used by the processor in the actual evaluation of the expression. This is useful for controlling the magnitude and accuracy of intermediate values developed during the evaluation of an expression.

For example, in the expression

$$A + (B - C)$$

the parenthesized expression $(B - C)$ is evaluated and then added to A.

The inclusion of parentheses could change the mathematical value of an expression. For example, the two expressions

$$A * I / J$$

$$A * (I / J)$$

could have different mathematical values if I and J are of type integer.

NOTE 7.20

Each operand in a numeric intrinsic operation has a type that can depend on the order of evaluation used by the processor.

For example, in the evaluation of the expression

$$Z + R + I$$

where Z, R, and I represent data objects of complex, real, and integer type, respectively, the type of the operand that is added to I could be either complex or real, depending on which pair of operands (Z and R, R and I, or Z and I) is added first.

1 **7.1.5.3 Character intrinsic operation**2 **7.1.5.3.1 Interpretation of the character intrinsic operation**

3 1 The character intrinsic operator // is used to concatenate two operands of type character with the same [kind](#)
4 [type parameter](#). Evaluation of the character intrinsic operation produces a result of type character.

5 2 The interpretation of the character intrinsic operator // when used to form an expression is given in Table 7.4,
6 where x_1 denotes the operand to the left of the operator and x_2 denotes the operand to the right of the operator.

Table 7.4: **Interpretation of the character intrinsic operator //**

Operator	Representing	Use of operator	Interpretation
//	Concatenation	$x_1 // x_2$	Concatenate x_1 with x_2

7 3 The result of the character intrinsic operation // is a character string whose value is the value of x_1 concatenated
8 on the right with the value of x_2 and whose length is the sum of the lengths of x_1 and x_2 . Parentheses used to
9 specify the order of evaluation have no effect on the value of a character expression.

NOTE 7.21

For example, the value of ('AB' // 'CDE') // 'F' is the string 'ABCDEF'. Also, the value of 'AB' // ('CDE' // 'F') is the string 'ABCDEF'.

10 **7.1.5.3.2 Evaluation of the character intrinsic operation**

11 1 A processor is only required to evaluate as much of the character intrinsic operation as is required by the context
12 in which the expression appears.

NOTE 7.22

For example, the statements

```
CHARACTER (LEN = 2) C1, C2, C3, CF
C1 = C2 // CF (C3)
```

do not require the function CF to be evaluated, because only the value of C2 is needed to determine the value of C1 because C1 and C2 both have a length of 2.

13 **7.1.5.4 Logical intrinsic operations**14 **7.1.5.4.1 Interpretation of logical intrinsic operations**

15 1 A logical operation is used to express a logical computation. Evaluation of a logical operation produces a result
16 of type logical. The permitted types for operands of the logical intrinsic operations are specified in [7.1.5.1](#).

1 2 The logical operators and their interpretation when used to form an expression are given in Table 7.5, where x_1
 2 denotes the operand to the left of the operator and x_2 denotes the operand to the right of the operator.

Table 7.5: Interpretation of the logical intrinsic operators

Operator	Representing	Use of operator	Interpretation
.NOT.	Logical negation	.NOT. x_2	True if x_2 is false
.AND.	Logical conjunction	x_1 .AND. x_2	True if x_1 and x_2 are both true
.OR.	Logical inclusive disjunction	x_1 .OR. x_2	True if x_1 and/or x_2 is true
.EQV.	Logical equivalence	x_1 .EQV. x_2	True if both x_1 and x_2 are true or both are false
.NEQV.	Logical nonequivalence	x_1 .NEQV. x_2	True if either x_1 or x_2 is true, but not both

3 3 The values of the logical intrinsic operations are shown in Table 7.6.

Table 7.6: The values of operations involving logical intrinsic operators

x_1	x_2	.NOT. x_2	x_1 .AND. x_2	x_1 .OR. x_2	x_1 .EQV. x_2	x_1 .NEQV. x_2
true	true	false	true	true	true	false
true	false	true	false	true	false	true
false	true	false	false	true	false	true
false	false	true	false	false	true	false

4 **7.1.5.4.2 Evaluation of logical intrinsic operations**

5 1 Once the interpretation of a logical intrinsic operation is established, the processor may evaluate any other
 6 expression that is logically equivalent, provided that the integrity of parentheses in any expression is not violated.

NOTE 7.23

For example, for the variables L1, L2, and L3 of type logical, the processor could choose to evaluate the expression

L1 .AND. L2 .AND. L3

as

L1 .AND. (L2 .AND. L3)

7 2 Two expressions of type logical are logically equivalent if their values are equal for all possible values of their
 8 primaries.

9 **7.1.5.5 Relational intrinsic operations**

10 **7.1.5.5.1 Interpretation of relational intrinsic operations**

11 1 A relational intrinsic operation is used to compare values of two operands using the relational intrinsic operators
 12 .LT., .LE., .GT., .GE., .EQ., .NE., <, <=, >, >=, ==, and /=. The permitted types for operands of the
 13 relational intrinsic operators are specified in 7.1.5.1.

14 2 The operators <, <=, >, >=, ==, and /= always have the same interpretations as the operators .LT., .LE.,
 15 .GT., .GE., .EQ., and .NE., respectively.

NOTE 7.24

As shown in Table 7.2, a relational intrinsic operator cannot be used to compare the value of an expression of a numeric type with one of type character or logical. Also, two operands of type logical cannot be

NOTE 7.24 (cont.)

compared, a complex operand can be compared with another numeric operand only when the operator is `.EQ.`, `.NE.`, `==`, or `/=`, and two character operands cannot be compared unless they have the same `kind type parameter` value.

- 1 3 Evaluation of a relational intrinsic operation produces a default logical result.
- 2 4 The interpretation of the relational intrinsic operators is given in Table 7.7, where x_1 denotes the operand to the
- 3 left of the operator and x_2 denotes the operand to the right of the operator.

Table 7.7: **Interpretation of the relational intrinsic operators**

Operator	Representing	Use of operator	Interpretation
<code>.LT.</code>	Less than	x_1 <code>.LT.</code> x_2	x_1 less than x_2
<code><</code>	Less than	$x_1 < x_2$	x_1 less than x_2
<code>.LE.</code>	Less than or equal to	x_1 <code>.LE.</code> x_2	x_1 less than or equal to x_2
<code><=</code>	Less than or equal to	$x_1 <= x_2$	x_1 less than or equal to x_2
<code>.GT.</code>	Greater than	x_1 <code>.GT.</code> x_2	x_1 greater than x_2
<code>></code>	Greater than	$x_1 > x_2$	x_1 greater than x_2
<code>.GE.</code>	Greater than or equal to	x_1 <code>.GE.</code> x_2	x_1 greater than or equal to x_2
<code>>=</code>	Greater than or equal to	$x_1 >= x_2$	x_1 greater than or equal to x_2
<code>.EQ.</code>	Equal to	x_1 <code>.EQ.</code> x_2	x_1 equal to x_2
<code>==</code>	Equal to	$x_1 == x_2$	x_1 equal to x_2
<code>.NE.</code>	Not equal to	x_1 <code>.NE.</code> x_2	x_1 not equal to x_2
<code>/=</code>	Not equal to	$x_1 /= x_2$	x_1 not equal to x_2

- 4 5 A numeric relational intrinsic operation is interpreted as having the logical value true if and only if the values of
- 5 the operands satisfy the relation specified by the operator.
- 6 6 In the numeric relational operation
- 7 x_1 *rel-op* x_2
- 8 7 if the types or `kind type parameters` of x_1 and x_2 differ, their values are converted to the type and `kind type`
- 9 `parameter` of the expression $x_1 + x_2$ before evaluation.
- 10 8 A character relational intrinsic operation is interpreted as having the logical value true if and only if the values
- 11 of the operands satisfy the relation specified by the operator.
- 12 9 For a character relational intrinsic operation, the operands are compared one character at a time in order,
- 13 beginning with the first character of each character operand. If the operands are of unequal length, the shorter
- 14 operand is treated as if it were extended on the right with blanks to the length of the longer operand. If both
- 15 x_1 and x_2 are of zero length, x_1 is equal to x_2 ; if every character of x_1 is the same as the character in the
- 16 corresponding position in x_2 , x_1 is equal to x_2 . Otherwise, at the first position where the character operands
- 17 differ, the character operand x_1 is considered to be less than x_2 if the character value of x_1 at this position
- 18 precedes the value of x_2 in the `collating sequence` (1.3.32); x_1 is greater than x_2 if the character value of x_1 at
- 19 this position follows the value of x_2 in the `collating sequence`.

NOTE 7.25

The `collating sequence` depends partially on the processor; however, the result of the use of the operators `.EQ.`, `.NE.`, `==`, and `/=` does not depend on the `collating sequence`.

For nondefault character kinds, the blank padding character is processor dependent.

1 7.1.5.5.2 Evaluation of relational intrinsic operations

2 1 Once the interpretation of a relational intrinsic operation is established, the processor may evaluate any other
3 expression that is relationally equivalent, provided that the integrity of parentheses in any expression is not
4 violated.

5 2 Two relational intrinsic operations are relationally equivalent if their logical values are equal for all possible values
6 of their primaries.

7 7.1.6 Defined operations

8 7.1.6.1 Definitions

9 1 A **defined operation** is either a unary operation or a binary operation. A unary **defined operation** is an operation
10 that has the form *defined-unary-op* x_2 or *intrinsic-operator* x_2 and that is defined by a function and a **generic**
11 **interface** (4.5.5, 12.4.3.5).

12 2 A function defines the unary operation *op* x_2 if

- 13 (1) the function is specified with a **FUNCTION** (12.6.2.2) or **ENTRY** (12.6.2.6) statement that specifies one
14 **dummy argument** d_2 ,
- 15 (2) either
 - 16 (a) a **generic interface** (12.4.3.2) provides the function with a *generic-spec* of **OPERATOR** (*op*),
17 or
 - 18 (b) there is a generic **binding** (4.5.5) in the **declared type** of x_2 with a *generic-spec* of **OPER-**
19 **ATOR** (*op*) and there is a corresponding **binding** to the function in the **dynamic type** of x_2 ,
- 20 (3) the type of d_2 is compatible with the **dynamic type** of x_2 ,
- 21 (4) the type parameters, if any, of d_2 match the corresponding type parameters of x_2 , and
- 22 (5) either
 - 23 (a) the **rank** of x_2 matches that of d_2 or
 - 24 (b) the function is **elemental** and there is no other function that defines the operation.

25 3 If d_2 is an array, the shape of x_2 shall match the shape of d_2 .

26 4 A binary **defined operation** is an operation that has the form x_1 *defined-binary-op* x_2 or x_1 *intrinsic-operator* x_2
27 and that is defined by a function and a **generic interface**.

28 5 A function defines the binary operation x_1 *op* x_2 if

- 29 (1) the function is specified with a **FUNCTION** (12.6.2.2) or **ENTRY** (12.6.2.6) statement that specifies
30 two **dummy arguments**, d_1 and d_2 ,
- 31 (2) either
 - 32 (a) a **generic interface** (12.4.3.2) provides the function with a *generic-spec* of **OPERATOR** (*op*),
33 or
 - 34 (b) there is a generic **binding** (4.5.5) in the **declared type** of x_1 or x_2 with a *generic-spec* of
35 **OPERATOR** (*op*) and there is a corresponding **binding** to the function in the **dynamic type**
36 of x_1 or x_2 , respectively,
- 37 (3) the types of d_1 and d_2 are compatible with the **dynamic types** of x_1 and x_2 , respectively,
- 38 (4) the type parameters, if any, of d_1 and d_2 match the corresponding type parameters of x_1 and x_2 ,
39 respectively, and
- 40 (5) either
 - 41 (a) the **ranks** of x_1 and x_2 match those of d_1 and d_2 or
 - 42 (b) the function is **elemental**, x_1 and x_2 are **conformable**, and there is no other function that defines
43 the operation.

- 1 6 If d_1 or d_2 is an array, the shapes of x_1 and x_2 shall match the shapes of d_1 and d_2 , respectively.

NOTE 7.26

An intrinsic operator can be used as the operator in a [defined operation](#). In such a case, the generic properties of the operator are extended.

2 **7.1.6.2 Interpretation of a defined operation**

- 3 1 The interpretation of a [defined operation](#) is provided by the function that defines the operation.
 4 2 The operators $<$, $<=$, $>$, $>=$, $==$, and $/=$ always have the same interpretations as the operators [.LT.](#), [.LE.](#),
 5 [.GT.](#), [.GE.](#), [.EQ.](#), and [.NE.](#), respectively.

6 **7.1.6.3 Evaluation of a defined operation**

- 7 1 Once the interpretation of a [defined operation](#) is established, the processor may evaluate any other expression
 8 that is equivalent, provided that the integrity of parentheses is not violated.
 9 2 Two expressions of derived type are equivalent if their values are equal for all possible values of their primaries.

10 **7.1.7 Evaluation of operands**

- 11 1 It is not necessary for a processor to evaluate all of the operands of an expression, or to evaluate entirely each
 12 operand, if the value of the expression can be determined otherwise.

NOTE 7.27

This principle is most often applicable to logical expressions, zero-sized arrays, and zero-length strings, but it applies to all expressions.

For example, in evaluating the expression

$$X > Y \text{ .OR. } L(Z)$$

where X , Y , and Z are real and L is a function of type logical, the function reference $L(Z)$ need not be evaluated if X is greater than Y . Similarly, in the array expression

$$W(Z) + A$$

where A is of size zero and W is a function, the function reference $W(Z)$ need not be evaluated.

- 13 2 If a statement contains a function reference in a part of an expression that need not be evaluated, all entities that
 14 would have become defined in the execution of that reference become undefined at the completion of evaluation
 15 of the expression containing the function reference.

NOTE 7.28

In the examples in [Note 7.27](#), if L or W defines its argument, evaluation of the expressions under the specified conditions causes Z to become undefined, no matter whether or not $L(Z)$ or $W(Z)$ is evaluated.

- 16 3 If a statement contains a function reference in a part of an expression that need not be evaluated, no invocation
 17 of that function in that part of the expression shall execute an [image control statement](#) other than [CRITICAL](#)
 18 or [END CRITICAL](#).

NOTE 7.29

This restriction is intended to avoid inadvertent deadlock caused by optimization.

7.1.8 Integrity of parentheses

- 1 The rules for evaluation specified in subclause 7.1.5 state certain conditions under which a processor may evaluate an expression that is different from the one specified by applying the rules given in 7.1.2 and rules for interpretation specified in subclause 7.1.5. However, any expression in parentheses shall be treated as a data entity.

NOTE 7.30

For example, in evaluating the expression $A + (B - C)$ where A , B , and C are of **numeric types**, the difference of B and C shall be evaluated before the addition operation is performed; the processor shall not evaluate the mathematically equivalent expression $(A + B) - C$.

7.1.9 Type, type parameters, and shape of an expression

7.1.9.1 General

- 1 The type, type parameters, and shape of an expression depend on the operators and on the types, type parameters, and shapes of the primaries used in the expression, and are determined recursively from the syntactic form of the expression. The type of an expression is one of the intrinsic types (4.4) or a derived type (4.5).
- 2 If an expression is a **polymorphic** primary or **defined operation**, the type parameters and the **declared** and **dynamic** types of the expression are the same as those of the primary or **defined operation**. Otherwise the type parameters and **dynamic type** of the expression are the same as its **declared type** and type parameters; they are referred to simply as the type and type parameters of the expression.

R724 *logical-expr* is *expr*

C706 (R724) *logical-expr* shall be of type logical.

R725 *default-char-expr* is *expr*

C707 (R725) *default-char-expr* shall be default character.

R726 *int-expr* is *expr*

C708 (R726) *int-expr* shall be of type integer.

R727 *numeric-expr* is *expr*

C709 (R727) *numeric-expr* shall be of type integer, real, or complex.

7.1.9.2 Type, type parameters, and shape of a primary

- 1 The type, type parameters, and shape of a primary are determined according to whether the primary is a constant, variable, array constructor, **structure constructor**, function reference, **type parameter inquiry**, type parameter name, or parenthesized expression. If a primary is a constant, its type, type parameters, and shape are those of the constant. If it is a **structure constructor**, it is scalar and its type and type parameters are as described in 4.5.10. If it is an array constructor, its type, type parameters, and shape are as described in 4.8. If it is a variable or function reference, its type, type parameters, and shape are those of the variable (5.2, 5.5) or the function reference (12.5.3), respectively. If the function reference is generic (12.4.3.2, 13.6) then its type, type parameters, and shape are those of the specific function referenced, which is determined by the types, type parameters, and **ranks** of its **actual arguments** as specified in 12.5.5.2. If it is a **type parameter inquiry** or type parameter name, it is a scalar integer with the kind of the type parameter.
- 2 If a primary is a parenthesized expression, its type, type parameters, and shape are those of the expression.
- 3 The associated **target** object is referenced if a pointer appears as
- a primary in an intrinsic or **defined operation**,
 - the *expr* of a parenthesized primary, or

- the only primary on the right-hand side of an [intrinsic assignment statement](#).

4 The type, type parameters, and shape of the primary are those of the [target](#). If the pointer is not associated with a [target](#), it may appear as a primary only as an [actual argument](#) in a reference to a procedure whose corresponding [dummy argument](#) is declared to be a pointer, or as the target in a [pointer assignment statement](#).

5 A [disassociated array pointer](#) or an unallocated [allocatable](#) array has no shape but does have [rank](#). The type, type parameters, and [rank](#) of the result of the intrinsic function [NULL](#) (13.8.136) depend on context.

7.1.9.3 Type, type parameters, and shape of the result of an operation

1 The type of the result of an intrinsic operation $[x_1] \text{ op } x_2$ is specified by Table 7.2. The shape of the result of an intrinsic operation is the shape of x_2 if op is unary or if x_1 is scalar, and is the shape of x_1 otherwise.

2 The type, type parameters, and shape of the result of a defined operation $[x_1] \text{ op } x_2$ are specified by the function defining the operation (7.1.6).

3 An expression of an intrinsic type has a [kind type parameter](#). An expression of type character also has a character length parameter.

4 The type parameters of the result of an intrinsic operation are as follows.

- For an expression $x_1 // x_2$ where $//$ is the character intrinsic operator and x_1 and x_2 are of type character, the character length parameter is the sum of the lengths of the operands and the [kind type parameter](#) is the [kind type parameter](#) of x_1 , which shall be the same as the [kind type parameter](#) of x_2 .
- For an expression $\text{op } x_2$ where op is an intrinsic unary operator and x_2 is of type integer, real, complex, or logical, the [kind type parameter](#) of the expression is that of the operand.
- For an expression $x_1 \text{ op } x_2$ where op is a numeric intrinsic binary operator with one operand of type integer and the other of type real or complex, the [kind type parameter](#) of the expression is that of the real or complex operand.
- For an expression $x_1 \text{ op } x_2$ where op is a numeric intrinsic binary operator with both operands of the same type and [kind type parameters](#), or with one real and one complex with the same [kind type parameters](#), the [kind type parameter](#) of the expression is identical to that of each operand. In the case where both operands are integer with different [kind type parameters](#), the [kind type parameter](#) of the expression is that of the operand with the greater decimal exponent range if the decimal exponent ranges are different; if the decimal exponent ranges are the same, the [kind type parameter](#) of the expression is processor dependent, but it is the same as that of one of the operands. In the case where both operands are any of type real or complex with different [kind type parameters](#), the [kind type parameter](#) of the expression is that of the operand with the greater decimal precision if the decimal precisions are different; if the decimal precisions are the same, the [kind type parameter](#) of the expression is processor dependent, but it is the same as that of one of the operands.
- For an expression $x_1 \text{ op } x_2$ where op is a logical intrinsic binary operator with both operands of the same [kind type parameter](#), the [kind type parameter](#) of the expression is identical to that of each operand. In the case where both operands are of type logical with different [kind type parameters](#), the [kind type parameter](#) of the expression is processor dependent, but it is the same as that of one of the operands.
- For an expression $x_1 \text{ op } x_2$ where op is a relational intrinsic operator, the expression has the default logical [kind type parameter](#).

7.1.10 Conformability rules for elemental operations

1 An [elemental operation](#) is an intrinsic operation or a [defined operation](#) for which the function is [elemental](#) (12.8).

2 For all [elemental](#) binary operations, the two operands shall be conformable. In the case where one is a scalar and the other an array, the scalar is treated as if it were an array of the same shape as the array operand with every element, if any, of the array equal to the value of the scalar.

7.1.11 Specification expression

1 A **specification expression** is an expression with limitations that make it suitable for use in specifications such as length type parameters (C404) and array bounds (R517, R518). A *specification-expr* shall be a **constant expression** unless it is in an **interface body** (12.4.3.2), the specification part of a subprogram or **BLOCK construct**, a derived type definition, or the *declaration-type-spec* of a **FUNCTION statement** (12.6.2.2).

R728 *specification-expr* **is** *scalar-int-expr*

C710 (R728) The *scalar-int-expr* shall be a restricted expression.

2 A restricted expression is an expression in which each operation is intrinsic or defined by a specification function and each primary is

- (1) a constant or subobject of a constant,
- (2) an **object designator** with a **base object** that is a **dummy argument** that has neither the **OPTIONAL** nor the **INTENT (OUT)** attribute,
- (3) an **object designator** with a **base object** that is in a **common block**,
- (4) an **object designator** with a **base object** that is made accessible by use or **host** association,
- (5) an **object designator** with a **base object** that is a **local variable** of the procedure containing the **BLOCK construct** in which the restricted expression appears,
- (6) an **object designator** with a **base object** that is a **local variable** of an outer **BLOCK construct** containing the **BLOCK construct** in which the restricted expression appears,
- (7) an array constructor where each element and each *scalar-int-expr* of each *ac-implied-do-control* is a restricted expression,
- (8) a **structure constructor** where each component is a restricted expression,
- (9) a specification inquiry where each **designator** or argument is
 - (a) a restricted expression or
 - (b) a variable that is not an optional dummy argument, and whose properties inquired about are not
 - (i) dependent on the upper bound of the last dimension of an **assumed-size array**,
 - (ii) deferred, or
 - (iii) defined by an expression that is not a restricted expression,
- (10) a specification inquiry that is a constant expression,
- (11) a reference to the intrinsic function **PRESENT**,
- (12) a reference to any other standard intrinsic function where each argument is a restricted expression,
- (13) a reference to a specification function where each argument is a restricted expression,
- (14) a type parameter of the derived type being defined,
- (15) an *ac-do-variable* within an array constructor where each *scalar-int-expr* of the corresponding *ac-implied-do-control* is a restricted expression, or
- (16) a restricted expression enclosed in parentheses,

3 where each subscript, section subscript, substring starting point, substring ending point, and type parameter value is a restricted expression, and where any **final subroutine** that is invoked is pure.

4 A specification inquiry is a reference to

- (1) an intrinsic **inquiry function** other than **PRESENT**,
- (2) a **type parameter inquiry** (6.4.5),
- (3) an **inquiry function** from the intrinsic modules **IEEE_ARITHMETIC** and **IEEE_EXCEPTIONS** (14.10),
- (4) the function **C_SIZEOF** from the intrinsic module **ISO_C_BINDING** (15.2.3.7), or
- (5) the **COMPILER_VERSION** or **COMPILER_OPTIONS** function from the intrinsic module **ISO_FORTRAN_ENV** (13.9.2.6, 13.9.2.7).

- 1 5 A function is a specification function if it is a pure function, is not a standard intrinsic function, is not an internal
2 function, is not a statement function, and does not have a **dummy procedure** argument.
- 3 6 Evaluation of a **specification expression** shall not directly or indirectly cause a procedure defined by the subpro-
4 gram in which it appears to be invoked.

NOTE 7.31

Specification functions are nonintrinsic functions that can be used in specification expressions to determine the attributes of data objects. The requirement that they be pure ensures that they cannot have side effects that could affect other objects being declared in the same *specification-part*. The requirement that they not be internal ensures that they cannot inquire, via **host association**, about other objects being declared in the same *specification-part*. The prohibition against recursion avoids the creation of a new instance of a procedure while construction of one is in progress.

- 5 7 A variable in a **specification expression** shall have its type and type parameters, if any, specified by a previous
6 declaration in the same **scoping unit**, by the implicit typing rules in effect for the **scoping unit**, or by **host** or **use**
7 association. If a variable in a **specification expression** is typed by the implicit typing rules, its appearance in any
8 subsequent **type declaration statement** shall confirm the implied type and type parameters.
- 9 8 If a **specification expression** includes a specification inquiry that depends on a type parameter or an array bound
10 of an entity specified in the same *specification-part*, the type parameter or array bound shall be specified in a prior
11 specification of the *specification-part*. The prior specification may be to the left of the specification inquiry in the
12 same statement, but shall not be within the same *entity-decl*. If a **specification expression** includes a reference to
13 the value of an element of an array specified in the same *specification-part*, the array shall be completely specified
14 in prior declarations.
- 15 9 A generic entity referenced in a **specification expression** in the *specification-part* of a **scoping unit** shall have no
16 specific procedures defined in the **scoping unit**, or its **host scoping unit**, subsequent to the **specification expression**.

NOTE 7.32

The following are examples of **specification expressions**:

```
LBOUND (B, 1) + 5 ! B is an assumed-shape dummy array
M + LEN (C)      ! M and C are dummy arguments
2 * PRECISION (A) ! A is a real variable made accessible
                  ! by a USE statement
```

17 **7.1.12 Constant expression**

- 18 1 A **constant expression** is an expression with limitations that make it suitable for use as a **kind type parameter**,
19 initializer, or **named constant**. It is an expression in which each operation is intrinsic, and each primary is
- 20 (1) a constant or subobject of a constant,
21 (2) an array constructor where each element and each *scalar-int-expr* of each *ac-implied-do-control* is a
22 **constant expression**,
23 (3) a **structure constructor** where each *component-spec* corresponding to
24 (a) an **allocatable** component is a reference to the intrinsic function **NULL**,
25 (b) a pointer component is an initialization target or a reference to the intrinsic function **NULL**,
26 and
27 (c) any other component is a **constant expression**,
- 28 (4) a specification inquiry where each **designator** or argument is
29 (a) a **constant expression** or
30 (b) a variable whose properties inquired about are not

- (i) assumed,
- (ii) deferred, or
- (iii) defined by an expression that is not a [constant expression](#),

- (5) a reference to an [elemental](#) standard intrinsic function, where each argument is a [constant expression](#),
- (6) a reference to a [transformational](#) standard intrinsic function other than [COMMAND_ARGUMENT_COUNT](#), [NULL](#), [NUM_IMAGES](#), [THIS_IMAGE](#), or [TRANSFER](#), where each argument is a [constant expression](#),
- (7) a reference to the intrinsic function [NULL](#) that does not have an argument with a type parameter that is assumed or is defined by an expression that is not a [constant expression](#),
- (8) a reference to the intrinsic function [TRANSFER](#) where each argument is a [constant expression](#) and each [ultimate pointer](#) component of the [SOURCE](#) argument is [disassociated](#),
- (9) a reference to the [transformational](#) function [IEEE_SELECTED_REAL_KIND](#) from the intrinsic module [IEEE_ARITHMETIC](#)(14), where each argument is a [constant expression](#),
- (10) a previously declared [kind type parameter](#) of the derived type being defined,
- (11) a [data-i-do-variable](#) within a [data-implied-do](#),
- (12) an [ac-do-variable](#) within an array constructor where each [scalar-int-expr](#) of the corresponding [ac-implied-do-control](#) is a [constant expression](#), or
- (13) a [constant expression](#) enclosed in parentheses,

and where each subscript, section subscript, substring starting point, substring ending point, and type parameter value is a [constant expression](#).

R729 *constant-expr* is *expr*

C711 (R729) *constant-expr* shall be a [constant expression](#).

R730 *default-char-constant-expr* is *default-char-expr*

C712 (R730) *default-char-constant-expr* shall be a [constant expression](#).

R731 *int-constant-expr* is *int-expr*

C713 (R731) *int-constant-expr* shall be a [constant expression](#).

- 2 If a [constant expression](#) includes a specification inquiry that depends on a type parameter or an array bound of an entity specified in the same [specification-part](#), the type parameter or array bound shall be specified in a prior specification of the [specification-part](#). The prior specification may be to the left of the specification inquiry in the same statement, but shall not be within the same [entity-decl](#) unless the specification inquiry appears within an [initialization](#).
- 3 A generic entity referenced in a [constant expression](#) in the [specification-part](#) of a [scoping unit](#) shall have no specific procedures defined in that [scoping unit](#), or its [host scoping unit](#), subsequent to the [constant expression](#).

NOTE 7.33

The following are examples of [constant expressions](#):

```

3
-3 + 4
'AB'
'AB' // 'CD'
('AB' // 'CD') // 'EF'
SIZE (A)
DIGITS (X) + 4
4.0 * atan(1.0)
ceiling(number_of_decimal_digits / log10(radix(0.0)))

```

NOTE 7.33 (cont.)

where A is an [explicit-shape array](#) with constant bounds and X is default real.

7.2 Assignment

7.2.1 Assignment statement

7.2.1.1 General form

R732 *assignment-stmt* is *variable* = *expr*

C714 (R732) The *variable* shall not be a whole [assumed-size array](#).

NOTE 7.34

Examples of an assignment statement are:

```
A = 3.5 + X * Y
I = INT (A)
```

1 An [assignment-stmt](#) shall meet the requirements of either a [defined assignment](#) statement or an intrinsic assignment statement.

7.2.1.2 Intrinsic assignment statement

1 An intrinsic assignment statement is an assignment statement that is not a [defined assignment](#) statement (7.2.1.4). In an intrinsic assignment statement,

- (1) if the variable is [polymorphic](#) it shall be [allocatable](#) and not a [coarray](#),
- (2) if *expr* is an array then the variable shall also be an array,
- (3) the variable and *expr* shall be [conformable](#) unless the variable is an [allocatable](#) array that has the same [rank](#) as *expr* and is not a [coarray](#),
- (4) if the variable is [polymorphic](#) it shall be [type compatible](#) with *expr*; otherwise the [declared types](#) of the variable and *expr* shall conform as specified in Table 7.8,
- (5) if the variable is of type character and of [ISO 10646](#), [ASCII](#), or default character kind, *expr* shall be of [ISO 10646](#), [ASCII](#), or default character kind,
- (6) otherwise if the variable is of type character *expr* shall have the same [kind type parameter](#),
- (7) if the variable is of derived type each [kind type parameter](#) of the variable shall have the same value as the corresponding [kind type parameter](#) of *expr*, and
- (8) if the variable is of derived type each length type parameter of the variable shall have the same value as the corresponding type parameter of *expr* unless the variable is [allocatable](#), is not a [coarray](#), and its corresponding [type parameter](#) is [deferred](#).

Table 7.8: **Type conformance for the intrinsic assignment statement**

Type of the variable	Type of <i>expr</i>
integer	integer, real, complex
real	integer, real, complex
complex	integer, real, complex
character	character
logical	logical
derived type	same derived type as the variable

2 If the variable in an intrinsic assignment statement is a [coindexed object](#),

- 1 • the variable shall not be *polymorphic*,
- 2 • the variable shall not have an *allocatable* ultimate component,
- 3 • the variable shall be *conformable* with *expr*, and
- 4 • each *deferred length type parameter* of the variable shall have the same value as the corresponding type
- 5 parameter of *expr*.

- 6 3 If the variable is a pointer, it shall be associated with a *definable target* such that the type, type parameters, and
- 7 shape of the *target* and *expr* conform.

8 7.2.1.3 Interpretation of intrinsic assignments

9 1 Execution of an intrinsic assignment causes, in effect, the evaluation of the expression *expr* and all expressions

10 within *variable* (7.1), the possible conversion of *expr* to the type and type parameters of the variable (Table 7.9),

11 and the definition of the variable with the resulting value. The execution of the assignment shall have the same

12 effect as if the evaluation of *expr* and the evaluation of all expressions in *variable* occurred before any portion of

13 the variable is defined by the assignment. The evaluation of expressions within *variable* shall neither affect nor

14 be affected by the evaluation of *expr*.

15 2 If the variable is a pointer, the value of *expr* is assigned to the *target* of the variable.

16 3 If the variable is an unallocated *allocatable* array, *expr* shall have the same *rank*. If the variable is an allocated

17 *allocatable* variable, it is deallocated if *expr* is an array of different shape, any of the corresponding length type

18 parameter values of the variable and *expr* differ, or the variable is *polymorphic* and the *dynamic type* of the

19 variable and *expr* differ. If the variable is or becomes an unallocated *allocatable* variable, it is then allocated with

- 20 • the same *dynamic type* as *expr* if the variable is *polymorphic*,
- 21 • each *deferred type parameter* equal to the corresponding type parameter of *expr*,
- 22 • the same bounds as before if the variable is an array and *expr* is scalar, and
- 23 • the shape of *expr* with each lower bound equal to the corresponding element of `LBOUND (expr)` if *expr* is
- 24 an array.

NOTE 7.35

For example, given the declaration

```
CHARACTER(:), ALLOCATABLE :: NAME
```

then after the assignment statement

```
NAME = 'Dr. ' // FIRST_NAME // ' ' // SURNAME
```

NAME will have the length `LEN(FIRST_NAME)+LEN(SURNAME)+5`, even if it had previously been unallocated, or allocated with a different length. However, for the assignment statement

```
NAME(:) = 'Dr. ' // FIRST_NAME // ' ' // SURNAME
```

NAME must already be allocated at the time of the assignment; the assigned value is truncated or blank padded to the previously allocated length of NAME.

- 25 4 Both *variable* and *expr* may contain references to any portion of the variable.

NOTE 7.36

For example, in the character intrinsic assignment statement:

```
STRING (2:5) = STRING (1:4)
```


NOTE 7.36 (cont.)

the assignment of the first character of `STRING` to the second character does not affect the evaluation of `STRING(1:4)`. If the value of `STRING` prior to the assignment was `'ABCDEF'`, the value following the assignment is `'AABCDF'`.

- 1 5 If *expr* is a scalar and the variable is an array, the *expr* is treated as if it were an array of the same shape as the
 2 variable with every element of the array equal to the scalar value of *expr*.
- 3 6 If the variable is an array, the assignment is performed element-by-element on corresponding array elements of
 4 the variable and *expr*.

NOTE 7.37

For example, if `A` and `B` are arrays of the same shape, the array intrinsic assignment

```
A = B
```

assigns the corresponding elements of `B` to those of `A`; that is, the first element of `B` is assigned to the first element of `A`, the second element of `B` is assigned to the second element of `A`, etc.

If `C` is an allocatable array of rank 1, then

```
C = PACK(ARRAY, ARRAY>0)
```

will cause `C` to contain all the positive elements of `ARRAY` in array element order; if `C` is not allocated or is allocated with the wrong size, it will be re-allocated to be of the correct size to hold the result of `PACK`.

- 5 7 The processor may perform the element-by-element assignment in any order.

NOTE 7.38

For example, the following program segment results in the values of the elements of array `X` being reversed:

```
REAL X (10)
...
X (1:10) = X (10:1:-1)
```

- 6 8 For an intrinsic assignment statement where the variable is of numeric type, the *expr* can have a different numeric
 7 type or kind type parameter, in which case the value of *expr* is converted to the type and kind type parameter
 8 of the variable according to the rules of Table 7.9.

Table 7.9: **Numeric conversion and the assignment statement**

Type of the variable	Value Assigned
integer	<code>INT (expr, KIND = KIND (variable))</code>
real	<code>REAL (expr, KIND = KIND (variable))</code>
complex	<code>CMPLX (expr, KIND = KIND (variable))</code>
Note: <code>INT</code> , <code>REAL</code> , <code>CMPLX</code> , and <code>KIND</code> are the generic names of functions defined in 13.8.	

- 9 9 For an intrinsic assignment statement where the variable is of type logical, the *expr* can have a different kind
 10 type parameter, in which case the value of *expr* is converted to the kind type parameter of the variable.
- 11 10 For an intrinsic assignment statement where the variable is of type character, the *expr* can have a different
 12 character length parameter in which case the conversion of *expr* to the length of the variable is as follows.
- 13 (1) If the length of the variable is less than that of *expr*, the value of *expr* is truncated from the right
 14 until it is the same length as the variable.

- 1 (2) If the length of the variable is greater than that of *expr*, the value of *expr* is extended on the right
2 with blanks until it is the same length as the variable.

- 3 11 For an intrinsic assignment statement where the variable is of type character, if *expr* has a different **kind type para-**
4 **meter**, each character *c* in *expr* is converted to the **kind type parameter** of the variable by **ACHAR (IACHAR(*c*),**
5 **KIND (*variable*))**.

NOTE 7.39

For nondefault character kinds, the blank padding character is processor dependent. When assigning a character expression to a variable of a different kind, each character of the expression that is not representable in the kind of the variable is replaced by a processor-dependent character.

- 6 12 For an intrinsic assignment of the type **C_PTR** or **C_FUNPTR** from the intrinsic module **ISO_C_BINDING**,
7 the variable becomes undefined if the variable and *expr* are not on the same **image**.

NOTE 7.40

An intrinsic assignment statement for a variable of type **C_PTR** or **C_FUNPTR** is not permitted to involve a **coindexed object**, see **C614**, which prevents inappropriate copying from one **image** to another. However, such copying can occur as an intrinsic assignment for a component in a derived-type assignment.

- 8 13 An intrinsic assignment where the variable is of derived type is performed as if each component of the vari-
9 able were assigned from the corresponding component of *expr* using **pointer assignment (7.2.2)** for each pointer
10 component, **defined assignment** for each nonpointer nonallocatable component of a type that has a **type-bound**
11 **defined assignment** consistent with the component, intrinsic assignment for each other nonpointer nonallocatable
12 component, and intrinsic assignment for each allocated **coarray** component. For unallocated **coarray** components,
13 the corresponding component of the variable shall be unallocated. For a noncoarray **allocatable** component the
14 following sequence of operations is applied.

- 15 (1) If the component of the variable is allocated, it is deallocated.
16 (2) If the component of the value of *expr* is allocated, the corresponding component of the variable is
17 allocated with the same **dynamic type** and type parameters as the component of the value of *expr*.
18 If it is an array, it is allocated with the same bounds. The value of the component of the value of
19 *expr* is then assigned to the corresponding component of the variable using **defined assignment** if the
20 **declared type** of the component has a **type-bound defined assignment** consistent with the component,
21 and intrinsic assignment for the **dynamic type** of that component otherwise.

- 22 14 The processor may perform the component-by-component assignment in any order or by any means that has the
23 same effect.

NOTE 7.41

For an example of a derived-type intrinsic assignment statement, if C and D are of the same derived type with a pointer component P and nonpointer components S, T, U, and V of type integer, logical, character, and another derived type, respectively, the intrinsic

$$C = D$$

pointer assigns D%P to C%P. It assigns D%S to C%S, D%T to C%T, and D%U to C%U using intrinsic assignment. It assigns D%V to C%V using **defined assignment** if objects of that type have a compatible **type-bound defined assignment**, and intrinsic assignment otherwise.

NOTE 7.42

If an **allocatable** component of *expr* is unallocated, the corresponding component of the variable has an allocation status of unallocated after execution of the assignment.

1 7.2.1.4 Defined assignment statement

- 2 1 A **defined assignment** statement is an assignment statement that is defined by a subroutine and a **generic interface** (4.5.5, 12.4.3.5.3) that specifies **ASSIGNMENT** (=).
- 3
- 4 2 A subroutine defines the **defined assignment** $x_1 = x_2$ if
- 5 (1) the subroutine is specified with a **SUBROUTINE** (12.6.2.3) or **ENTRY** (12.6.2.6) statement that specifies
 - 6 two **dummy arguments**, d_1 and d_2 ,
 - 7 (2) either
 - 8 (a) a **generic interface** (12.4.3.2) provides the subroutine with a *generic-spec* of **ASSIGNMENT** (=),
 - 9 or
 - 10 (b) there is a **generic binding** (4.5.5) in the **declared type** of x_1 or x_2 with a *generic-spec* of
 - 11 **ASSIGNMENT** (=) and there is a corresponding **binding** to the subroutine in the **dynamic**
 - 12 **type** of x_1 or x_2 , respectively,
 - 13 (3) the types of d_1 and d_2 are compatible with the **dynamic types** of x_1 and x_2 , respectively,
 - 14 (4) the type parameters, if any, of d_1 and d_2 match the corresponding type parameters of x_1 and x_2 ,
 - 15 respectively, and
 - 16 (5) either
 - 17 (a) the **ranks** of x_1 and x_2 match those of d_1 and d_2 or
 - 18 (b) the subroutine is **elemental**, x_1 and x_2 are **conformable**, and there is no other subroutine that
 - 19 defines the assignment.
- 20 3 If d_1 or d_2 is an array, the shapes of x_1 and x_2 shall match the shapes of d_1 and d_2 , respectively.

21 7.2.1.5 Interpretation of defined assignment statements

- 22 1 The interpretation of a **defined assignment** is provided by the subroutine that defines it.
- 23 2 If the **defined assignment** is an **elemental assignment** and the variable in the assignment is an array, the **defined**
- 24 **assignment** is performed element-by-element, on corresponding elements of the variable and *expr*. If *expr* is a
- 25 scalar, it is treated as if it were an array of the same shape as the variable with every element of the array equal
- 26 to the scalar value of *expr*.

NOTE 7.43

The rules of **defined assignment** (12.4.3.5.3), procedure references (12.5), subroutine references (12.5.4), and **elemental** subroutine arguments (12.8.3) ensure that the **defined assignment** has the same effect as if the evaluation of all operations in x_2 and x_1 occurs before any portion of x_1 is defined. If an **elemental assignment** is defined by a pure **elemental** subroutine, the element assignments can be performed simultaneously or in any order.

27 7.2.2 Pointer assignment

28 7.2.2.1 General

- 29 1 **Pointer assignment** causes a pointer to become associated with a **target** or causes its **pointer association** status
- 30 to become **disassociated** or undefined. Any previous association between the pointer and a **target** is broken.
- 31 2 **Pointer assignment** for a pointer component of a structure may also take place by execution of a derived-type
- 32 **intrinsic assignment statement** (7.2.1.3).

33 7.2.2.2 Syntax of the pointer assignment statement

34 R733 *pointer-assignment-stmt* is *data-pointer-object* [(*bounds-spec-list*)] => *data-target*

35 or *data-pointer-object* (*bounds-remapping-list*) => *data-target*

36 or *proc-pointer-object* => *proc-target*

- 1 R734 *data-pointer-object* **is** *variable-name*
 2 **or** *scalar-variable* % *data-pointer-component-name*
- 3 C715 (R733) If *data-target* is not **unlimited polymorphic**, *data-pointer-object* shall be **type compatible** (4.3.2.3)
 4 with it and the corresponding **kind type parameters** shall be equal.
- 5 C716 (R733) If *data-target* is **unlimited polymorphic**, *data-pointer-object* shall be **unlimited polymorphic**, or of
 6 a type with the **BIND attribute** or the **SEQUENCE attribute**.
- 7 C717 (R733) If *bounds-spec-list* is specified, the number of *bounds-specs* shall equal the **rank** of *data-pointer-*
 8 *object*.
- 9 C718 (R733) If *bounds-remapping-list* is specified, the number of *bounds-remappings* shall equal the **rank** of
 10 *data-pointer-object*.
- 11 C719 (R733) If *bounds-remapping-list* is not specified, the **ranks** of *data-pointer-object* and *data-target* shall be
 12 the same.
- 13 C720 (R733) A coarray *data-target* shall have the **VOLATILE attribute** if and only if the *data-pointer-object*
 14 has the **VOLATILE attribute**.
- 15 C721 (R734) A *variable-name* shall have the **POINTER attribute**.
- 16 C722 (R734) A *scalar-variable* shall be a *data-ref*.
- 17 C723 (R734) A *data-pointer-component-name* shall be the name of a component of *scalar-variable* that is a
 18 data pointer.
- 19 C724 (R734) A *data-pointer-object* shall not be a **coindexed object**.
- 20 R735 *bounds-spec* **is** *lower-bound-expr* :
- 21 R736 *bounds-remapping* **is** *lower-bound-expr* : *upper-bound-expr*
- 22 R737 *data-target* **is** *expr*
- 23 C725 (R737) The *expr* shall be a *designator* that designates a variable with either the **TARGET** or **POINTER**
 24 attribute and is not an array section with a vector subscript, or it shall be a reference to a function that
 25 returns a data pointer.
- 26 C726 (R737) A *data-target* shall not be a **coindexed object**.

NOTE 7.44

A data pointer and its **target** are always on the same **image**. A **coarray** can be of a derived type with pointer or **allocatable subcomponents**. For example, if PTR is a pointer component, Z[P]%PTR is a reference to the **target** of component PTR of Z on **image** P. This **target** is on **image** P and its association with Z[P]%PTR must have been established by the execution of an **ALLOCATE statement** or a **pointer assignment** on **image** P.

- 27 R738 *proc-pointer-object* **is** *proc-pointer-name*
 28 **or** *proc-component-ref*
- 29 R739 *proc-component-ref* **is** *scalar-variable* % *procedure-component-name*
- 30 C727 (R739) The *scalar-variable* shall be a *data-ref* that is not a **coindexed object**.
- 31 C728 (R739) The *procedure-component-name* shall be the name of a procedure pointer component of the **de-**
 32 **clared type** of *scalar-variable*.
- 33 R740 *proc-target* **is** *expr*

1 or *procedure-name*
 2 or *proc-component-ref*

3 C729 (R740) An *expr* shall be a reference to a function whose result is a procedure pointer.

4 C730 (R740) A *procedure-name* shall be the name of an **internal**, **module**, or **dummy** procedure, a **procedure**
 5 **pointer**, a **specific** intrinsic function listed in Table 13.2, or an **external procedure** that is accessed by **use** or **host**
 6 association, referenced in the **scoping unit** as a procedure, or that has the **EXTERNAL** attribute.

7 C731 (R740) The *proc-target* shall not be a nonintrinsic **elemental procedure**.

8 1 In a pointer assignment statement, *data-pointer-object* or *proc-pointer-object* denotes the pointer object and
 9 *data-target* or *proc-target* denotes the pointer target.

10 2 For pointer assignment performed by a derived-type **intrinsic assignment statement**, the pointer object is the
 11 pointer component of the variable and the pointer target is the corresponding component of *expr*.

12 7.2.2.3 Data pointer assignment

13 1 If the pointer object is not polymorphic (4.3.2.3) and the pointer target is **polymorphic** with **dynamic type** that
 14 differs from its **declared type**, the assignment target is the ancestor component of the pointer target that has the
 15 type of the pointer object. Otherwise, the assignment target is the pointer target.

16 2 If the pointer target is not a pointer, the pointer object becomes **pointer associated** with the assignment target;
 17 if the pointer target is a pointer with a target that is not on the same **image**, the **pointer association** status of the
 18 pointer object becomes undefined. Otherwise, the **pointer association** status of the pointer object becomes that
 19 of the pointer target; if the pointer target is associated with an object, the pointer object becomes associated
 20 with the assignment target. If the pointer target is **allocatable**, it shall be allocated.

NOTE 7.45

A **pointer assignment statement** is not permitted to involve a **coindexed** pointer or target, see C724 and C726. This prevents a pointer assignment statement from associating a pointer with a target on another **image**. If such an association would otherwise be implied, the association status of the pointer becomes undefined. For example, a derived-type intrinsic assignment where the variable and *expr* are on different images and the variable has an ultimate pointer component.

21 3 If the pointer object is **polymorphic**, it assumes the **dynamic type** of the pointer target. If the pointer object is
 22 of a type with the **BIND** attribute or the **SEQUENCE** attribute, the **dynamic type** of the pointer target shall be
 23 that type.

24 4 If the pointer target is a **disassociated** pointer, all nondeferred type parameters of the **declared type** of the pointer
 25 object that correspond to nondeferred type parameters of the pointer target shall have the same values as the
 26 corresponding type parameters of the pointer target.

27 5 Otherwise, all nondeferred type parameters of the **declared type** of the pointer object shall have the same values
 28 as the corresponding type parameters of the pointer target.

29 6 If the pointer object has nondeferred type parameters that correspond to **deferred type parameters** of the pointer
 30 target, the pointer target shall not be a pointer with undefined association status.

31 7 If the pointer object has the **CONTIGUOUS** attribute, the pointer target shall be **contiguous**.

32 8 If the target of a pointer is a **coarray**, the pointer shall have the **VOLATILE** attribute if and only if the **coarray**
 33 has the **VOLATILE** attribute.

34 9 If *bounds-remapping-list* appears, it specifies the upper and lower **bounds** of each dimension of the pointer,
 35 and thus the **extents**; the pointer target shall be **simply contiguous** (6.5.4) or of **rank** one, and shall not be a
 36 **disassociated** or **undefined** pointer. The number of elements of the pointer target shall not be less than the

1 number implied by the *bounds-remapping-list*. The elements of the pointer object are associated with those of
 2 the pointer *target*, in array element order; if the pointer target has more elements than specified for the pointer
 3 object, the remaining elements are not associated with the pointer object.

4 10 If no *bounds-remapping-list* appears, the extent of a dimension of the pointer object is the extent of the corres-
 5 ponding dimension of the pointer target. If *bounds-spec-list* appears, it specifies the lower bounds; otherwise,
 6 the lower bound of each dimension is the result of the intrinsic function `LBOUND` (13.8.101) applied to the
 7 corresponding dimension of the pointer target. The upper bound of each dimension is one less than the sum of
 8 the lower bound and the extent.

9 7.2.2.4 Procedure pointer assignment

10 1 If the pointer target is not a pointer, the pointer object becomes *pointer associated* with the pointer target.
 11 Otherwise, the *pointer association* status of the pointer object becomes that of the pointer target; if the pointer
 12 target is associated with a procedure, the pointer object becomes associated with the same procedure.

13 2 The *host instance* (12.6.2.4) of an associated *procedure pointer* is the *host instance* of its target.

14 3 If the pointer object has an *explicit interface*, its *characteristics* shall be the same as the pointer target except
 15 that the pointer target may be pure even if the pointer object is not pure and the pointer target may be an
 16 *elemental* intrinsic procedure even if the pointer object is not *elemental*.

17 4 If the *characteristics* of the pointer object or the pointer target are such that an *explicit interface* is required,
 18 both the pointer object and the pointer target shall have an *explicit interface*.

19 5 If the pointer object has an *implicit interface* and is explicitly typed or referenced as a function, the pointer target
 20 shall be a function. If the pointer object has an *implicit interface* and is referenced as a subroutine, the pointer
 21 target shall be a subroutine.

22 6 If the pointer object is a function with an *implicit interface*, the pointer target shall be a function with the same
 23 type; corresponding type parameters shall have the same value.

24 7 If *procedure-name* is a specific procedure name that is also a generic name, only the specific procedure is associated
 25 with the pointer object.

26 7.2.2.5 Examples

NOTE 7.46

The following are examples of pointer assignment statements. (See Note 12.18 for declarations of P and BESSEL.)

```

NEW_NODE % LEFT => CURRENT_NODE
SIMPLE_NAME => TARGET_STRUCTURE % SUBSTRUCT % COMPONENT
PTR => NULL ( )
ROW => MAT2D (N, :)
WINDOW => MAT2D (I-1:I+1, J-1:J+1)
POINTER_OBJECT => POINTER_FUNCTION (ARG_1, ARG_2)
EVERY_OTHER => VECTOR (1:N:2)
WINDOW2 (0:, 0:) => MAT2D (ML:MU, NL:NU)
! P is a procedure pointer and BESSEL is a procedure with a
! compatible interface.
P => BESSEL

! Likewise for a structure component.
STRUCT % COMPONENT => BESSEL

```

NOTE 7.47

It is possible to obtain different-rank views of parts of an object by specifying upper bounds in pointer assignment statements. This requires that the object be either [rank](#) one or [contiguous](#). Consider the following example, in which a matrix is under consideration. The matrix is stored as a rank-one object in MYDATA because its diagonal is needed for some reason – the diagonal cannot be gotten as a single object from a rank-two representation. The matrix is represented as a rank-two view of MYDATA.

```
real, target :: MYDATA ( NR*NC )      ! An automatic array
real, pointer :: MATRIX ( :, : )      ! A rank-two view of MYDATA
real, pointer :: VIEW_DIAG ( : )
MATRIX( 1:NR, 1:NC ) => MYDATA       ! The MATRIX view of the data
VIEW_DIAG => MYDATA( 1::NR+1 )       ! The diagonal of MATRIX
```

Rows, columns, or blocks of the matrix can be accessed as sections of MATRIX.

[Rank](#) remapping can be applied to CONTIGUOUS arrays, for example:

```
REAL, CONTIGUOUS, POINTER :: A(:)
REAL, CONTIGUOUS, TARGET :: B(:, :) ! Dummy argument
A(1:SIZE(B)) => B                    ! Linear view of a rank-2 array
```

1 7.2.3 Masked array assignment – WHERE

2 7.2.3.1 General form of the masked array assignment

3 1 A [masked array assignment](#) is either a WHERE statement or a WHERE construct. It is used to mask the
4 evaluation of expressions and assignment of values in array assignment statements, according to the value of a
5 logical array expression.

6 R741 *where-stmt* is WHERE (*mask-expr*) *where-assignment-stmt*

7 R742 *where-construct* is *where-construct-stmt*
8 [*where-body-construct*] ...
9 [*masked-elsewhere-stmt*
10 [*where-body-construct*] ...] ...
11 [*elsewhere-stmt*
12 [*where-body-construct*] ...]
13 *end-where-stmt*

14 R743 *where-construct-stmt* is [*where-construct-name*:] WHERE (*mask-expr*)

15 R744 *where-body-construct* is *where-assignment-stmt*
16 or *where-stmt*
17 or *where-construct*

18 R745 *where-assignment-stmt* is *assignment-stmt*

19 R746 *mask-expr* is *logical-expr*

20 R747 *masked-elsewhere-stmt* is ELSEWHERE (*mask-expr*) [*where-construct-name*]

21 R748 *elsewhere-stmt* is ELSEWHERE [*where-construct-name*]

22 R749 *end-where-stmt* is END WHERE [*where-construct-name*]

23 C732 (R745) A *where-assignment-stmt* that is a [defined assignment](#) shall be [elemental](#).

24 C733 (R742) If the *where-construct-stmt* is identified by a *where-construct-name*, the corresponding *end-where-*

1 *stmt* shall specify the same *where-construct-name*. If the *where-construct-stmt* is not identified by a
 2 *where-construct-name*, the corresponding *end-where-stmt* shall not specify a *where-construct-name*. If
 3 an *elsewhere-stmt* or a *masked-elsewhere-stmt* is identified by a *where-construct-name*, the corresponding
 4 *where-construct-stmt* shall specify the same *where-construct-name*.

5 C734 (R744) A statement that is part of a *where-body-construct* shall not be a *branch target statement*.

6 2 If a *where-construct* contains a *where-stmt*, a *masked-elsewhere-stmt*, or another *where-construct* then each *mask-*
 7 *expr* within the *where-construct* shall have the same shape. In each *where-assignment-stmt*, the *mask-expr* and
 8 the variable being defined shall be arrays of the same shape.

NOTE 7.48

Examples of a masked array assignment are:

```
WHERE (TEMP > 100.0) TEMP = TEMP - REDUCE_TEMP
WHERE (PRESSURE <= 1.0)
  PRESSURE = PRESSURE + INC_PRESSURE
  TEMP = TEMP - 5.0
ELSEWHERE
  RAINING = .TRUE.
END WHERE
```

9 7.2.3.2 Interpretation of masked array assignments

10 1 When a WHERE statement or a *where-construct-stmt* is executed, a control mask is established. In addition,
 11 when a WHERE construct statement is executed, a pending control mask is established. If the statement does
 12 not appear as part of a *where-body-construct*, the *mask-expr* of the statement is evaluated, and the control mask is
 13 established to be the value of *mask-expr*. The pending control mask is established to have the value *.NOT. mask-*
 14 *expr* upon execution of a WHERE construct statement that does not appear as part of a *where-body-construct*.
 15 The *mask-expr* is evaluated only once.

16 2 Each statement in a WHERE construct is executed in sequence.

17 3 Upon execution of a *masked-elsewhere-stmt*, the following actions take place in sequence.

- 18 (1) The control mask m_c is established to have the value of the pending control mask.
- 19 (2) The pending control mask is established to have the value m_c *.AND. (.NOT. mask-expr)*.
- 20 (3) The control mask m_c is established to have the value m_c *.AND. mask-expr*.

21 4 The *mask-expr* is evaluated at most once.

22 5 Upon execution of an ELSEWHERE statement, the control mask is established to have the value of the pending
 23 control mask. No new pending control mask value is established.

24 6 Upon execution of an ENDWHERE statement, the control mask and pending control mask are established to
 25 have the values they had prior to the execution of the corresponding WHERE construct statement. Following
 26 the execution of a WHERE statement that appears as a *where-body-construct*, the control mask is established to
 27 have the value it had prior to the execution of the WHERE statement.

NOTE 7.49

The establishment of control masks and the pending control mask is illustrated with the following example:

```
WHERE(cond1)          ! Statement 1
. . .
ELSEWHERE(cond2)     ! Statement 2
. . .
ELSEWHERE            ! Statement 3
```


NOTE 7.49 (cont.)

```

. . .
END WHERE

```

Following execution of statement 1, the control mask has the value `cond1` and the pending control mask has the value `.NOT. cond1`. Following execution of statement 2, the control mask has the value `(.NOT. cond1) .AND. cond2` and the pending control mask has the value `(.NOT. cond1) .AND. (.NOT. cond2)`. Following execution of statement 3, the control mask has the value `(.NOT. cond1) .AND. (.NOT. cond2)`. The false condition values are propagated through the execution of the masked ELSEWHERE statement.

- 1 7 Upon execution of a WHERE construct statement that is part of a *where-body-construct*, the pending control
2 mask is established to have the value m_c *.AND.* *(.NOT. mask-expr)*. The control mask is then established to
3 have the value m_c *.AND.* *mask-expr*. The *mask-expr* is evaluated at most once.
- 4 8 Upon execution of a WHERE statement that is part of a *where-body-construct*, the control mask is established
5 to have the value m_c *.AND.* *mask-expr*. The pending control mask is not altered.
- 6 9 If a *nonelemental* function reference occurs in the *expr* or *variable* of a *where-assignment-stmt* or in a *mask-expr*,
7 the function is evaluated without any masked control; that is, all of its argument expressions are fully evaluated
8 and the function is fully evaluated. If the result is an array and the reference is not within the argument list
9 of a *nonelemental* function, elements corresponding to true values in the control mask are selected for use in
10 evaluating the *expr*, variable or *mask-expr*.
- 11 10 If an *elemental operation* or function reference occurs in the *expr* or *variable* of a *where-assignment-stmt* or in a
12 *mask-expr*, and is not within the argument list of a *nonelemental* function reference, the operation is performed
13 or the function is evaluated only for the elements corresponding to true values of the control mask.
- 14 11 If an array constructor appears in a *where-assignment-stmt* or in a *mask-expr*, the array constructor is evaluated
15 without any masked control and then the *where-assignment-stmt* is executed or the *mask-expr* is evaluated.
- 16 12 When a *where-assignment-stmt* is executed, the values of *expr* that correspond to true values of the control mask
17 are assigned to the corresponding elements of the variable.
- 18 13 The value of the control mask is established by the execution of a WHERE statement, a WHERE construct
19 statement, an ELSEWHERE statement, a masked ELSEWHERE statement, or an ENDWHERE statement.
20 Subsequent changes to the value of entities in a *mask-expr* have no effect on the value of the control mask. The
21 execution of a function reference in the mask expression of a WHERE statement is permitted to affect entities in
22 the assignment statement.

NOTE 7.50

Examples of function references in masked array assignments are:

```

WHERE (A > 0.0)
  A = LOG (A)           ! LOG is invoked only for positive elements.
  A = A / SUM (LOG (A)) ! LOG is invoked for all elements
                       ! because SUM is transformational
END WHERE

```

23 7.2.4 FORALL

24 7.2.4.1 Form of the FORALL Construct

- 25 1 The FORALL construct allows multiple assignments, masked array (WHERE) assignments, and nested FORALL constructs and
26 statements to be controlled by a single *concurrent-control-list* and *scalar-mask-expr*.

27 R750 *forall-construct* is *forall-construct-stmt*

1 *[forall-body-construct] ...*
 2 *end-forall-stmt*

3 R751 *forall-construct-stmt* is *[forall-construct-name :] FORALL concurrent-header*

4 R752 *forall-body-construct* is *forall-assignment-stmt*
 5 or *where-stmt*
 6 or *where-construct*
 7 or *forall-construct*
 8 or *forall-stmt*

9 R753 *forall-assignment-stmt* is *assignment-stmt*
 10 or *pointer-assignment-stmt*

11 R754 *end-forall-stmt* is END FORALL *[forall-construct-name]*

12 C735 (R754) If the *forall-construct-stmt* has a *forall-construct-name*, the *end-forall-stmt* shall have the same *forall-construct-*
 13 *name*. If the *end-forall-stmt* has a *forall-construct-name*, the *forall-construct-stmt* shall have the same *forall-construct-*
 14 *name*.

15 C736 (R752) A statement in a *forall-body-construct* shall not define an *index-name* of the *forall-construct*.

16 C737 (R752) Any procedure referenced in a *forall-body-construct*, including one referenced by a defined operation, assignment,
 17 or *finalization*, shall be a *pure procedure*.

18 C738 (R752) A *forall-body-construct* shall not be a branch target.

19 2 The scope and attributes of an *index-name* in a *concurrent-header* in a FORALL construct or statement are described in 16.4.

20 7.2.4.2 Execution of the FORALL construct

21 7.2.4.2.1 Execution stages

22 1 There are three stages in the execution of a FORALL construct:
 23 (1) determination of the values for *index-name* variables,
 24 (2) evaluation of the *scalar-mask-expr*, and
 25 (3) execution of the FORALL body constructs.

26 7.2.4.2.2 Determination of the values for index variables

27 1 The values of the index variables are determined as they are for the DO CONCURRENT statement (8.1.6.4.2).

28 7.2.4.2.3 Evaluation of the mask expression

29 1 The mask expression is evaluated as it is for the DO CONCURRENT statement (8.1.6.4.2).

30 7.2.4.2.4 Execution of the FORALL body constructs

31 1 The *forall-body-constructs* are executed in the order in which they appear. Each construct is executed for all active combinations of
 32 the *index-name* values with the following interpretation:

33 2 Execution of a *forall-assignment-stmt* that is an *assignment-stmt* causes the evaluation of *expr* and all expressions within *variable*
 34 for all active combinations of *index-name* values. These evaluations may be done in any order. After all these evaluations have been
 35 performed, each *expr* value is assigned to the corresponding *variable*. The assignments may occur in any order.

36 3 Execution of a *forall-assignment-stmt* that is a *pointer-assignment-stmt* causes the evaluation of all expressions within *data-target*
 37 and *data-pointer-object* or *proc-target* and *proc-pointer-object*, the determination of any pointers within *data-pointer-object* or *proc-*
 38 *pointer-object*, and the determination of the *target* for all active combinations of *index-name* values. These evaluations may be done
 39 in any order. After all these evaluations have been performed, each *data-pointer-object* or *proc-pointer-object* is associated with the
 40 corresponding *target*. These associations may occur in any order.

1 4 In a *forall-assignment-stmt*, a *defined assignment* subroutine shall not reference any *variable* that becomes defined by the statement.

NOTE 7.51

If a variable defined in an assignment statement within a FORALL construct is referenced in a later statement in that construct, the later statement uses the value(s) computed in the preceding assignment statement, not the value(s) the variable had prior to execution of the FORALL.

2 5 Each statement in a *where-construct* (7.2.3) within a *forall-construct* is executed in sequence. When a *where-stmt*, *where-construct-stmt* or *masked-elsewhere-stmt* is executed, the statement's *mask-expr* is evaluated for all active combinations of *index-name* values as determined by the outer *forall-constructs*, masked by any control mask corresponding to outer *where-constructs*. Any *where-assignment-stmt* is executed for all active combinations of *index-name* values, masked by the control mask in effect for the *where-assignment-stmt*.

7 6 Execution of a *forall-stmt* or *forall-construct* causes the evaluation of the *concurrent-limit* and *concurrent-step* expressions in the *concurrent-control-list* for all active combinations of the *index-name* values of the outer FORALL construct. The set of combinations of *index-name* values for the inner FORALL is the union of the sets defined by these limits and steps for each active combination of the outer *index-name* values; it also includes the outer *index-name* values. The *scalar-mask-expr* is then evaluated for all combinations of the *index-name* values of the inner construct to produce a set of active combinations for the inner construct. If there is no *scalar-mask-expr*, it is as if it appeared with the value true. Each statement in the inner FORALL is then executed for each active combination of the *index-name* values.

14 7.2.4.3 The FORALL statement

15 1 The FORALL statement allows a single assignment statement or *pointer assignment statement* to be controlled by a set of index values and an optional mask expression.

17 R755 *forall-stmt* is FORALL *concurrent-header forall-assignment-stmt*

18 2 A FORALL statement is equivalent to a FORALL construct containing a single *forall-body-construct* that is a *forall-assignment-stmt*.

19 3 The scope of an *index-name* in a *forall-stmt* is the statement itself (16.4).

20 7.2.4.4 Restrictions on FORALL constructs and statements

21 1 A many-to-one assignment is more than one assignment to the same object, or association of more than one *target* with the same pointer, whether the object is referenced directly or indirectly through a pointer. A many-to-one assignment shall not occur within a single statement in a FORALL construct or statement. It is possible to assign or pointer-assign to the same object in different *assignment* or *pointer assignment* statements in a FORALL construct.

NOTE 7.52

The appearance of each *index-name* in the identification of the left-hand side of an assignment statement is helpful in eliminating many-to-one assignments, but it is not sufficient to guarantee there will be none. For example, the following is allowed

```
FORALL (I = 1:10)
  A (INDEX (I)) = B(I)
END FORALL
```

if and only if INDEX(1:10) contains no repeated values.

25 2 Within the scope of a FORALL construct, a nested FORALL statement or FORALL construct shall not have the same *index-name*. The *concurrent-header* expressions within a nested FORALL may depend on the values of outer *index-name* variables.

1

(Blank page)

8 Execution control

8.1 Executable constructs containing blocks

8.1.1 Blocks

1 The following are executable constructs that contain blocks:

- 2 • ASSOCIATE construct;
- 3 • BLOCK construct;
- 4 • CRITICAL construct;
- 5 • DO construct;
- 6 • IF construct;
- 7 • SELECT CASE construct;
- 8 • SELECT RANK construct;
- 9 • SELECT TYPE construct.

R801 *block* is [*execution-part-construct*] ...

2 Executable constructs may be used to control which blocks of a program are executed or how many times a block is executed. Blocks are always bounded by statements that are particular to the construct in which they are embedded.

NOTE 8.1

An example of a construct containing a block is:

```
IF (A > 0.0) THEN
  B = SQRT (A) ! These two statements
  C = LOG (A) ! form a block.
END IF
```

8.1.2 Rules governing blocks

8.1.2.1 Control flow in blocks

1 Transfer of control to the interior of a block from outside the block is prohibited, except for the return from a procedure invoked within the block. Transfers within a block and transfers from the interior of a block to outside the block may occur.

2 Subroutine and function references ([12.5.3](#), [12.5.4](#)) may appear in a block.

8.1.2.2 Execution of a block

1 Execution of a block begins with the execution of the first executable construct in the block.

2 Execution of the block is completed when

- execution of the last executable construct in the block completes without branching to a statement within the block,
- a branch ([8.2](#)) within the block that has a branch target outside the block occurs,
- a RETURN statement within the block is executed, or

- an [EXIT statement](#) or [CYCLE statement](#) statement that belongs to a construct that contains the block is executed.

NOTE 8.2

The action that takes place at the terminal boundary depends on the particular construct and on the block within that construct.

8.1.3 ASSOCIATE construct**8.1.3.1 Purpose and form of the ASSOCIATE construct**

- 1 The ASSOCIATE construct associates named entities with expressions or variables during the execution of its block. These named [construct entities](#) (16.4) are [associating entities](#) (16.5.1.6). The names are [associate names](#).

R802 *associate-construct* is *associate-stmt*
block
end-associate-stmt

R803 *associate-stmt* is [*associate-construct-name* :] ASSOCIATE ■
■ (*association-list*)

R804 *association* is *associate-name* => *selector*

R805 *selector* is *expr*
or *variable*

C801 (R804) If *selector* is not a *variable* or is a *variable* that has a [vector subscript](#), *associate-name* shall not appear in a variable definition context (16.6.7).

C802 (R804) An *associate-name* shall not be the same as another *associate-name* in the same *associate-stmt*.

C803 (R805) *variable* shall not be a [coindexed object](#).

C804 (R805) *expr* shall not be a variable.

C805 (R805) *expr* shall not be a [designator](#) of a procedure pointer or a function reference that returns a procedure pointer.

R806 *end-associate-stmt* is END ASSOCIATE [*associate-construct-name*]

C806 (R806) If the *associate-stmt* of an *associate-construct* specifies an *associate-construct-name*, the corresponding *end-associate-stmt* shall specify the same *associate-construct-name*. If the *associate-stmt* of an *associate-construct* does not specify an *associate-construct-name*, the corresponding *end-associate-stmt* shall not specify an *associate-construct-name*.

8.1.3.2 Execution of the ASSOCIATE construct

- 1 Execution of an ASSOCIATE construct causes evaluation of every expression within every *selector* that is a variable designator and evaluation of every other *selector*, followed by execution of its block. During execution of that block each [associate name](#) identifies an entity which is associated (16.5.1.6) with the corresponding selector. The [associating entity](#) assumes the [declared type](#) and type parameters of the selector. If and only if the selector is [polymorphic](#), the [associating entity](#) is [polymorphic](#).

- 2 The other attributes of the [associating entity](#) are described in 8.1.3.3.

- 3 It is permissible to branch to an *end-associate-stmt* only from within its ASSOCIATE construct.

8.1.3.3 Other attributes of associate names

- 1 Within an ASSOCIATE or SELECT TYPE construct, each **associating entity** has the same **rank** as its associated selector. The lower bound of each dimension is the result of the intrinsic function **LBOUND** (13.8.101) applied to the corresponding dimension of **selector**. The upper bound of each dimension is one less than the sum of the lower bound and the extent. The **associating entity** has the **ASYNCHRONOUS** or **VOLATILE** attribute if and only if the selector is a variable and has the attribute. The **associating entity** has the **TARGET** attribute if and only if the selector is a variable and has either the **TARGET** or **POINTER** attribute.
- 2 Within an ASSOCIATE, SELECT RANK, or SELECT TYPE construct, each **associating entity** has the same **corank** as its associated selector. If the selector is a **coarray**, the **cobounds** of each **codimension** of the **associating entity** are the same as those of the selector. If the **associating entity** is **polymorphic**, it assumes the **dynamic type** and **type parameter** values of the selector. If the selector has the **OPTIONAL** attribute, it shall be present. The **associating entity** is **contiguous** if and only if the selector is **contiguous**.
- 3 The **associating entity** itself is a variable, but if the selector is not a **definable** variable, the **associating entity** is not **definable** and shall not be **defined** or become **undefined**. If the selector is not permitted to appear in a variable definition context (16.6.7), the **associate name** shall not appear in a variable definition context.

8.1.3.4 Examples of the ASSOCIATE construct

NOTE 8.3

The following example illustrates an association with an expression.

```
ASSOCIATE ( Z => EXP(-(X**2+Y**2)) * COS(THETA) )
  PRINT *, A+Z, A-Z
END ASSOCIATE
```

The following example illustrates an association with a derived-type variable.

```
ASSOCIATE ( XC => AX%B(I,J)%C )
  XC%DV = XC%DV + PRODUCT(XC%EV(1:N))
END ASSOCIATE
```

The following example illustrates association with an **array section**.

```
ASSOCIATE ( ARRAY => AX%B(I,:)%C )
  ARRAY(N)%EV = ARRAY(N-1)%EV
END ASSOCIATE
```

The following example illustrates multiple associations.

```
ASSOCIATE ( W => RESULT(I,J)%W, ZX => AX%B(I,J)%D, ZY => AY%B(I,J)%D )
  W = ZX*X + ZY*Y
END ASSOCIATE
```

8.1.4 BLOCK construct

- 1 The **BLOCK** construct is an executable construct that may contain declarations.

R807	<i>block-construct</i>	is	<i>block-stmt</i> [<i>block-specification-part</i>] <i>block</i> <i>end-block-stmt</i>
R808	<i>block-stmt</i>	is	[<i>block-construct-name</i> :] BLOCK

- 1 R809 *block-specification-part* is [*use-stmt*]...
 2 [*import-stmt*] ...
 3 [*implicit-part*]
 4 [[*declaration-construct*] ...
 5 *specification-construct*]
- 6 R810 *end-block-stmt* is END BLOCK [*block-construct-name*]
- 7 C807 (R807) A *block-specification-part* shall not contain a COMMON, EQUIVALENCE, INTENT, NAMELIST,
 8 OPTIONAL, statement function, or VALUE statement.
- 9 C808 (R807) A SAVE statement in a BLOCK construct shall contain a *saved-entity-list* that does not specify a
 10 *common-block-name*.
- 11 C809 (R807) If the *block-stmt* of a *block-construct* specifies a *block-construct-name*, the corresponding *end-block-*
 12 *stmt* shall specify the same *block-construct-name*. If the *block-stmt* does not specify a *block-construct-*
 13 *name*, the corresponding *end-block-stmt* shall not specify a *block-construct-name*.
- 14 2 Except for the ASYNCHRONOUS and VOLATILE statements, specifications in a BLOCK construct declare
 15 construct entities whose scope is that of the BLOCK construct (16.4). The appearance of the name of an object
 16 that is not a construct entity in an ASYNCHRONOUS or VOLATILE statement in a BLOCK construct specifies
 17 that the object has the attribute within the construct even if it does not have the attribute outside the construct.
- 18 3 Execution of a BLOCK construct causes evaluation of the specification expressions within its specification part
 19 in a processor-dependent order, followed by execution of its block.

NOTE 8.4

The following is an example of a BLOCK construct.

```

IF (swapxy) THEN
  BLOCK
    REAL(KIND(x)) tmp
    tmp = x
    x = y
    y = tmp
  END BLOCK
END IF

```

Actions on a variable local to a BLOCK construct do not affect any variable of the same name outside the construct. For example,

```

F = 254E-2
BLOCK
  REAL F
  F = 39.37
END BLOCK
! F is still equal to 254E-2.

```

A SAVE statement outside a BLOCK construct does not affect variables local to the BLOCK construct, because a SAVE statement affects variables in its scoping unit rather than in its inclusive scope. For example,

```

SUBROUTINE S
  ...
  SAVE
  ...
  BLOCK

```


NOTE 8.4 (cont.)

```

REAL X           ! Not saved.
REAL,SAVE :: Y(100) ! SAVE attribute is allowed.
Z = 3           ! Implicitly declared in S, thus saved.
...
END BLOCK
...
END SUBROUTINE

```

1 **8.1.5 CRITICAL construct**

2 1 A CRITICAL construct limits execution of a block to one [image](#) at a time.

3 R811 *critical-construct* is *critical-stmt*
4 *block*
5 *end-critical-stmt*

6 R812 *critical-stmt* is [*critical-construct-name* :] CRITICAL

7 R813 *end-critical-stmt* is END CRITICAL [*critical-construct-name*]

8 C810 (R811) If the *critical-stmt* of a *critical-construct* specifies a *critical-construct-name*, the corresponding
9 *end-critical-stmt* shall specify the same *critical-construct-name*. If the *critical-stmt* of a *critical-construct*
10 does not specify a *critical-construct-name*, the corresponding *end-critical-stmt* shall not specify a *critical-*
11 *construct-name*.

12 C811 (R811) The *block* of a *critical-construct* shall not contain a [RETURN statement](#) or an [image control](#)
13 [statement](#).

14 C812 A branch (8.2) within a [CRITICAL construct](#) shall not have a branch target that is outside the construct.

15 2 Execution of the CRITICAL construct is completed when execution of its block is completed. A procedure
16 invoked, directly or indirectly, from a CRITICAL construct shall not execute an [image control statement](#).

17 3 The processor shall ensure that once an [image](#) has commenced executing *block*, no other [image](#) shall commence
18 executing *block* until this [image](#) has completed executing *block*. The [image](#) shall not execute an [image control](#)
19 [statement](#) during the execution of *block*. The sequence of executed statements is therefore a segment (8.5.2). If
20 [image](#) T is the next to execute the construct after [image](#) M, the segment on [image](#) M precedes the segment on
21 [image](#) T.

NOTE 8.5

If more than one [image](#) executes the block of a CRITICAL construct, its execution by one [image](#) always either precedes or succeeds its execution by another [image](#). Typically no other statement ordering is needed. Consider the following example:

```

CRITICAL
  GLOBAL_COUNTER[1] = GLOBAL_COUNTER[1] + 1
END CRITICAL

```

The definition of GLOBAL_COUNTER [1] by a particular [image](#) will always precede the reference to the same variable by the next [image](#) to execute the block.

NOTE 8.6

The following example permits a large number of jobs to be shared among the [images](#):

```

INTEGER :: NUM_JOBS[*], JOB

```

NOTE 8.6 (cont.)

```

IF (THIS_IMAGE() == 1) READ(*,*) NUM_JOBS
SYNC ALL
DO
  CRITICAL
    JOB = NUM_JOBS[1]
    NUM_JOBS[1] = JOB - 1
  END CRITICAL
  IF (JOB > 0) THEN
    ! Work on JOB
  ELSE
    EXIT
  END IF
END DO
SYNC ALL

```

1 **8.1.6 DO construct**2 **8.1.6.1 Purpose and form of the DO construct**

3 1 The DO construct specifies the repeated execution of a sequence of executable constructs. Such a repeated
4 sequence is called a loop.

5 2 The number of iterations of a loop can be determined at the beginning of execution of the DO construct, or can
6 be left indefinite (“DO forever” or DO WHILE). The execution order of the iterations can be left indeterminate
7 (DO CONCURRENT); except in this case, the loop can be terminated immediately (8.1.6.4.5). An iteration of
8 the loop can be curtailed by executing a [CYCLE statement](#) (8.1.6.4.4).

9 3 There are three phases in the execution of a DO construct: initiation of the loop, execution of each iteration of
10 the loop, and termination of the loop.

11 4 The scope and attributes of an *index-name* in a *concurrent-header* (DO CONCURRENT) are described in 16.4.

12 **8.1.6.2 Form of the DO construct**

13 R814 *do-construct* is *do-stmt*
14 *block*
15 *end-do*

16 R815 *do-stmt* is *nonlabel-do-stmt*
17 or *label-do-stmt*

18 R816 *label-do-stmt* is [*do-construct-name* :] DO *label* [*loop-control*]

19 R817 *nonlabel-do-stmt* is [*do-construct-name* :] DO [*loop-control*]

20 R818 *loop-control* is [,] *do-variable* = *scalar-int-expr*, *scalar-int-expr* ■
21 ■ [, *scalar-int-expr*]
22 or [,] WHILE (*scalar-logical-expr*)
23 or [,] CONCURRENT *concurrent-header* *concurrent-locality*

24 R819 *do-variable* is *scalar-int-variable-name*

25 C813 (R819) The *do-variable* shall be a variable of type integer.

26 R820 *concurrent-header* is ([*integer-type-spec* ::] *concurrent-control-list* [, *scalar-mask-expr*])

- 1 R821 *concurrent-control* is *index-name* = *concurrent-limit* : *concurrent-limit* [: *concurrent-step*]
- 2 R822 *concurrent-limit* is *scalar-int-expr*
- 3 R823 *concurrent-step* is *scalar-int-expr*
- 4 R824 *concurrent-locality* is [*locality-spec*]...
- 5 R825 *locality-spec* is LOCAL (*variable-name-list*)
6 or LOCAL_INIT (*variable-name-list*)
7 or SHARED (*variable-name-list*)
8 or DEFAULT (NONE)
- 9 C814 (R820) Any procedure referenced in the *scalar-mask-expr*, including one referenced by a *defined operation*,
10 shall be a *pure procedure* (12.7).
- 11 C815 (R821) The *index-name* shall be a named scalar variable of type integer.
- 12 C816 (R821) A *concurrent-limit* or *concurrent-step* in a *concurrent-control* shall not contain a reference to any
13 *index-name* in the *concurrent-control-list* in which it appears.
- 14 C817 A *variable-name* in a *locality-spec* shall be the name of a variable in the innermost executable construct
15 or *scoping unit* that includes the DO CONCURRENT statement.
- 16 C818 A *variable-name* in a *locality-spec* shall not be the same as an *index-name* in the *concurrent-header* of
17 the same DO CONCURRENT statement.
- 18 C819 The name of a variable shall not appear in more than one *variable-name-list*, or more than once in a
19 *variable-name-list*, in a *locality-spec*.
- 20 C820 A *variable-name* that has LOCAL or LOCAL_INIT locality shall not have the INTENT (IN) or OP-
21 TIONAL attributes, and shall not be a *coarray* or an *assumed-size array*.
- 22 C821 A variable that is referenced by the *scalar-mask-expr* of a *concurrent-header* or by any *concurrent-limit*
23 or *concurrent-step* in that *concurrent-header* shall not appear in a LOCAL *locality-spec* in the same DO
24 CONCURRENT statement.
- 25 C822 If the *locality-spec* DEFAULT (NONE) appears in a DO CONCURRENT statement, a variable that
26 appears in the *block* of the construct and is not an *index-name* of that construct shall have its locality
27 explicitly specified.
- 28 R826 *end-do* is *end-do-stmt*
29 or *continue-stmt*
- 30 R827 *end-do-stmt* is END DO [*do-construct-name*]
- 31 C823 (R814) If the *do-stmt* of a *do-construct* specifies a *do-construct-name*, the corresponding *end-do* shall be
32 an *end-do-stmt* specifying the same *do-construct-name*. If the *do-stmt* of a *do-construct* does not specify
33 a *do-construct-name*, the corresponding *end-do* shall not specify a *do-construct-name*.
- 34 C824 (R814) If the *do-stmt* is a *nonlabel-do-stmt*, the corresponding *end-do* shall be an *end-do-stmt*.
- 35 C825 (R814) If the *do-stmt* is a *label-do-stmt*, the corresponding *end-do* shall be identified with the same *label*.
- 36 1 It is permissible to branch to an *end-do* only from within its DO construct.

37 8.1.6.3 Active and inactive DO constructs

- 38 1 A DO construct is either active or inactive. Initially inactive, a DO construct becomes active only when its DO
39 *statement* is executed.

1 2 Once active, the DO construct becomes inactive only when it terminates (8.1.6.4.5).

2 8.1.6.4 Execution of a DO construct

3 8.1.6.4.1 Loop initiation

4 1 When the DO statement is executed, the DO construct becomes active. If *loop-control* is

5 $[,] \textit{do-variable} = \textit{scalar-int-expr}_1 , \textit{scalar-int-expr}_2 [, \textit{scalar-int-expr}_3]$

6 the following steps are performed in sequence.

- 7 (1) The initial parameter m_1 , the terminal parameter m_2 , and the incrementation parameter m_3 are
8 of type integer with the same kind type parameter as the *do-variable*. Their values are established
9 by evaluating *scalar-int-expr*₁, *scalar-int-expr*₂, and *scalar-int-expr*₃, respectively, including, if ne-
10 cessary, conversion to the kind type parameter of the *do-variable* according to the rules for numeric
11 conversion (Table 7.9). If *scalar-int-expr*₃ does not appear, m_3 has the value 1. The value of m_3
12 shall not be zero.
- 13 (2) The DO variable becomes defined with the value of the initial parameter m_1 .
- 14 (3) The iteration count is established and is the value of the expression $(m_2 - m_1 + m_3)/m_3$, unless that
15 value is negative, in which case the iteration count is 0.

NOTE 8.7

The iteration count is zero whenever:

$$m_1 > m_2 \text{ and } m_3 > 0, \text{ or} \\ m_1 < m_2 \text{ and } m_3 < 0.$$

16 2 If *loop-control* is omitted, no iteration count is calculated. The effect is as if a large positive iteration count,
17 impossible to decrement to zero, were established. If *loop-control* is $[,]$ WHILE (*scalar-logical-expr*), the effect
18 is as if *loop-control* were omitted and the following statement inserted as the first statement of the *block*:

19 IF (.NOT. (*scalar-logical-expr*)) EXIT

20 3 For a DO CONCURRENT construct, the values of the index variables for the iterations of the construct are
21 determined by the rules in 8.1.6.4.2.

22 4 At the completion of the execution of the DO statement, the execution cycle begins.

23 8.1.6.4.2 DO CONCURRENT loop control

24 1 The *concurrent-limit* and *concurrent-step* expressions in the *concurrent-control-list* are evaluated. These ex-
25 pressions may be evaluated in any order. The set of values that a particular *index-name* variable assumes is
26 determined as follows.

- 27 (1) The lower bound m_1 , the upper bound m_2 , and the step m_3 are of type integer with the same kind type
28 parameter as the *index-name*. Their values are established by evaluating the first *concurrent-limit*,
29 the second *concurrent-limit*, and the *concurrent-step* expressions, respectively, including, if necessary,
30 conversion to the kind type parameter of the *index-name* according to the rules for numeric conversion
31 (Table 7.9). If *concurrent-step* does not appear, m_3 has the value 1. The value m_3 shall not be zero.
- 32 (2) Let the value of *max* be $(m_2 - m_1 + m_3)/m_3$. If $max \leq 0$ for some *index-name*, the execution of the
33 construct is complete. Otherwise, the set of values for the *index-name* is

$$34 \quad m_1 + (k - 1) \times m_3 \quad \text{where } k = 1, 2, \dots, \textit{max}.$$

35 2 The set of combinations of *index-name* values is the Cartesian product of the sets defined by each triplet specific-
36 ation. An *index-name* becomes defined when this set is evaluated.

37 3 The *scalar-mask-expr*, if any, is evaluated for each combination of *index-name* values. If there is no *scalar-*
38 *mask-expr*, it is as if it appeared with the value true. The *index-name* variables may be primaries in the

1 *scalar-mask-expr*.

2 4 The set of active combinations of *index-name* values is the subset of all possible combinations for which the
3 *scalar-mask-expr* has the value true.

NOTE 8.8

The *index-name* variables can appear in the mask, for example

```
DO CONCURRENT (I=1:10, J=1:10, A(I) > 0.0 .AND. B(J) < 1.0)
. . .
```

4 8.1.6.4.3 The execution cycle

5 1 The execution cycle of a DO construct that is not a DO CONCURRENT construct consists of the following steps
6 performed in sequence repeatedly until termination.

- 7 (1) The iteration count, if any, is tested. If it is zero, the loop terminates and the DO construct becomes
8 inactive. If *loop-control* is [,] WHILE (*scalar-logical-expr*), the *scalar-logical-expr* is evaluated; if
9 the value of this expression is false, the loop terminates and the DO construct becomes inactive.
- 10 (2) The *block* of the loop is executed.
- 11 (3) The iteration count, if any, is decremented by one. The DO variable, if any, is incremented by the
12 value of the incrementation parameter m_3 .

13 2 Except for the incrementation of the DO variable that occurs in step (3), the DO variable shall neither be redefined
14 nor become undefined while the DO construct is active.

15 3 The *block* of a DO CONCURRENT construct is executed for every active combination of the *index-name* values.
16 Each execution of the *block* is an iteration. The executions may occur in any order.

17 8.1.6.4.4 CYCLE statement

18 1 Execution of a loop iteration can be curtailed by executing a CYCLE statement that belongs to the construct.

19 R828 *cycle-stmt* is CYCLE [*do-construct-name*]

20 C826 If a *do-construct-name* appears on a CYCLE statement, the CYCLE statement shall be within that
21 *do-construct*; otherwise, it shall be within at least one *do-construct*.

22 C827 A *cycle-stmt* shall not appear within a CRITICAL or DO CONCURRENT construct if it belongs to an
23 outer construct.

24 2 A CYCLE statement belongs to a particular DO construct. If the CYCLE statement contains a DO construct
25 name, it belongs to that DO construct; otherwise, it belongs to the innermost DO construct in which it appears.

26 3 Execution of a CYCLE statement that belongs to a DO construct that is not a DO CONCURRENT construct
27 causes immediate progression to step (3) of the execution cycle of the DO construct to which it belongs.

28 4 Execution of a CYCLE statement that belongs to a DO CONCURRENT construct completes execution of that
29 iteration of the construct.

30 5 In a DO construct, a transfer of control to the *end-do* has the same effect as execution of a CYCLE statement
31 belonging to that construct.

32 8.1.6.4.5 Loop termination

33 1 For a DO construct that is not a DO CONCURRENT construct, the loop terminates, and the DO construct
34 becomes inactive, when any of the following occurs.

- 1 • The iteration count is determined to be zero or the *scalar-logical-expr* is false, when tested during step (1)
 - 2 of the above execution cycle.
 - 3 • An **EXIT statement** that belongs to the DO construct is executed.
 - 4 • An **EXIT** or **CYCLE** statement that belongs to an outer construct and is within the DO construct is
 - 5 executed.
 - 6 • A branch occurs within the DO construct and the **branch target statement** is outside the construct.
 - 7 • A **RETURN statement** within the DO construct is executed.
- 8 2 For a DO CONCURRENT construct, the loop terminates, and the DO construct becomes inactive when all of
- 9 the iterations have completed execution.
- 10 3 When a DO construct becomes inactive, the DO variable, if any, of the DO construct retains its last defined
- 11 value.

12 **8.1.6.5 Additional semantics for DO CONCURRENT constructs**

- 13 C828 A **RETURN statement** shall not appear within a DO CONCURRENT construct.
- 14 C829 An **image control statement** shall not appear within a DO CONCURRENT construct.
- 15 C830 A branch (8.2) within a DO CONCURRENT construct shall not have a branch target that is outside
- 16 the construct.
- 17 C831 A reference to an impure procedure shall not appear within a DO CONCURRENT construct.
- 18 C832 A reference to the procedure **IEEE_GET_FLAG**, **IEEE_SET_HALTING_MODE**, or **IEEE_GET_-**
- 19 **HALTING_MODE** from the intrinsic module **IEEE_EXCEPTIONS**, shall not appear within a DO
- 20 **CONCURRENT** construct.
- 21 1 The locality of a variable that appears in a DO CONCURRENT construct is **LOCAL**, **LOCAL_INIT**, **SHARED**,
- 22 or unspecified.

Unresolved Technical Issue 015

Attributes wrong for LOCAL and LOCAL_INIT.

Note: This refers to the paragraph following the UTI.

A LOCAL or LOCAL_INIT entity cannot have

- BIND(C) because that would give it the same binding-label as the outer variable, making it the same variable and not a construct entity at all;
- INTENT because it is not a dummy argument or part thereof;
- PROTECTED because it is not a module variable (should be disallowed anyway since INTENT(IN) is disallowed);
- VALUE because it is not a dummy argument;
- SAVE (!!!) for reasons that are hopefully obvious.

Working through the rest of the attributes:

- type and type parameters is obviously desirable;
- bounds (not just shape) is obviously desirable;
- ALLOCATABLE is workable (though the implementation effort is way out of proportion to the usefulness);
- come to think of it, if the variable is finalisable it would need to be finalised at the end of each iteration — if we are to allow it to be of finalisable type (which seems pretty useless), this should be stated in normative text;

Unresolved Technical Issue 015 (cont.)

- why do we want to allow ASYNCHRONOUS — if we do, we should state in normative text that it shall not have any pending i/o at the end of an iteration (which makes it useless, so maybe just disallow ASYNCHRONOUS?);
- CONTIGUOUS ok;
- EXTERNAL and INTRINSIC irrelevant;
- POINTER ok;
- TARGET seems problematic, since any pointer associated with it will go undefined at the end of an iteration, i.e. it is an open invitation to dangling pointers without providing any useful functionality to counterbalance the high likelihood of error — if we allow TARGET we should state the effect on associated pointers in normative text;
- VOLATILE seems pointless — not actually a burden on implementors, but it's hard to see how it can have any significant use.

The text here should list the attributes that the local entity does get from the outer entity, and state that it has no other attributes, just like we do for the other construct entities.

For PROTECTED, we should disallow for consistency with INTENT(IN). For ASYNCHRONOUS, finalisable type, and TARGET, we should consider disallowing, on grounds of unreasonable implementation effort or error likelihood for little if any utility. Maybe VOLATILE also ought to be reconsidered.

- 1 2 A variable that has LOCAL or LOCAL_INIT locality is a construct entity with the same attributes as the variable
 2 with the same name in the innermost executable construct or [scoping unit](#) that includes the DO CONCURRENT
 3 construct, and the outside variable is inaccessible by that name within the construct. At the beginning of
 4 execution of each iteration,
- 5 • if a variable with LOCAL locality is allocatable it is unallocated, if it is a pointer it has undefined pointer
 6 association status, and otherwise it is undefined except for any subobjects that are default-initialized;
 - 7 • a variable with LOCAL_INIT locality has the allocation, pointer association, and definition status of the
 8 outside variable with that name; the outside variable shall not be an undefined pointer or a nonallocatable
 9 nonpointer variable that is undefined.
- 10 When execution of that iteration completes, an allocatable variable with LOCAL or LOCAL_INIT locality will
 11 be automatically deallocated.
- 12 3 If a variable has SHARED locality, appearances of the variable within the DO CONCURRENT construct refer
 13 to the variable in the innermost executable construct or [scoping unit](#) that includes the DO CONCURRENT
 14 construct. If it is defined or becomes undefined during any iteration, it shall not be referenced, defined, or
 15 become undefined during any other iteration. If it is allocated or deallocated during an iteration it shall not
 16 have its allocation or association status, dynamic type, array bounds, shape, or a deferred type parameter value
 17 inquired about in any other iteration.
- 18 4 If a variable has unspecified locality,
- 19 • if it is referenced in an iteration it shall either be previously defined during that iteration, or shall not be
 20 defined or become undefined during any other iteration; if it is defined or becomes undefined by more than
 21 one iteration it becomes undefined when the loop terminates;
 - 22 • if it is a pointer and is used in an iteration other than as the pointer in pointer assignment, allocation,
 23 or nullification, it shall either be previously [pointer associated](#) during that iteration or shall not have its
 24 [pointer association](#) changed during any iteration;
 - 25 • if it is a pointer whose [pointer association](#) is changed in more than one iteration, it has an association status
 26 of undefined when the construct terminates;
 - 27 • if it is [allocatable](#) and is allocated in more than one iteration, it shall have an allocation status of unallocated
 28 at the end of every iteration;
 - 29 • if it is [allocatable](#) and is referenced, defined, deallocated, or has its allocation status, dynamic type, or a
 30 deferred type parameter value inquired about, in any iteration, it shall either be previously allocated in

- 1 that iteration or shall not be allocated or deallocated in any other iteration.
- 2 5 If data are written to a file record or position in one iteration, that record or position in that file shall not be
- 3 read from or written to in a different iteration. If records are written to a file connected for sequential access by
- 4 more than one iteration, the ordering of records written by different iterations is processor dependent.

NOTE 8.9

The restrictions on referencing variables defined in an iteration of a DO CONCURRENT construct apply to any procedure invoked within the loop.

NOTE 8.10

The restrictions on the statements in a DO CONCURRENT construct are designed to ensure there are no data dependencies between iterations of the loop. This permits code optimizations that might otherwise be difficult or impossible because they would depend on properties of the program not visible to the compiler.

5 **8.1.6.6 Examples of DO constructs****NOTE 8.11**

The following program fragment computes a tensor product of two arrays:

```
DO I = 1, M
  DO J = 1, N
    C (I, J) = DOT_PRODUCT (A (I, J, :), B(:, I, J))
  END DO
END DO
```

NOTE 8.12

The following program fragment contains a DO construct that uses the **WHILE** form of *loop-control*. The loop will continue to execute until an end-of-file or input/output error is encountered, at which point the **DO statement** terminates the loop. When a negative value of X is read, the program skips immediately to the next **READ statement**, bypassing most of the *block* of the loop.

```
READ (IUN, '(1X, G14.7)', IOSTAT = IOS) X
DO WHILE (IOS == 0)
  IF (X >= 0.) THEN
    CALL SUBA (X)
    CALL SUBB (X)
    ...
    CALL SUBZ (X)
  ENDIF
  READ (IUN, '(1X, G14.7)', IOSTAT = IOS) X
END DO
```

NOTE 8.13

The following example behaves exactly the same as the one in Note 8.12. However, the **READ statement** has been moved to the interior of the loop, so that only one **READ statement** is needed. Also, a **CYCLE statement** has been used to avoid an extra level of **IF** nesting.

```
DO      ! A "DO WHILE + 1/2" loop
  READ (IUN, '(1X, G14.7)', IOSTAT = IOS) X
  IF (IOS /= 0) EXIT
  IF (X < 0.) CYCLE
  CALL SUBA (X)
```


NOTE 8.13 (cont.)

```

CALL SUBB (X)
. . .
CALL SUBZ (X)
END DO

```

NOTE 8.14

The following example illustrates a case in which the user knows that there are no repeated values in the index array IND. The DO CONCURRENT construct makes it easier for the processor to generate vector gather/scatter code, unroll the loop, or parallelize the code for this loop, potentially improving performance.

```

INTEGER :: A(N),IND(N)

DO CONCURRENT (I=1:M)
  A(IND(I)) = I
END DO

```

NOTE 8.15

The following code demonstrates the use of the [LOCAL](#) clause so that the X inside the [DO CONCURRENT construct](#) is a temporary variable, and will not affect the X outside the construct.

```

X = 1.0
DO CONCURRENT (I=1:10) LOCAL (X)
  IF (A (I) > 0) THEN
    X = SQRT (A (I))
    A (I) = A (I) - X**2
  END IF
  B (I) = B (I) - A (I)
END DO
PRINT *, X
! Always prints 1.0.

```

NOTE 8.16

Additional examples of DO constructs are in [C.5.3](#).

1 **8.1.7 IF construct and statement**

2 **8.1.7.1 Purpose and form of the IF construct**

3 1 The IF construct selects for execution at most one of its constituent blocks. The selection is based on a sequence
4 of logical expressions.

```

5 R829 if-construct is if-then-stmt
6 block
7 [ else-if-stmt
8 block ] ...
9 [ else-stmt
10 block ]
11 end-if-stmt

12 R830 if-then-stmt is [ if-construct-name : ] IF ( scalar-logical-expr ) THEN
13 R831 else-if-stmt is ELSE IF ( scalar-logical-expr ) THEN [ if-construct-name ]
14 R832 else-stmt is ELSE [ if-construct-name ]

```

1 R833 *end-if-stmt* is END IF [*if-construct-name*]

2 C833 (R829) If the *if-then-stmt* of an *if-construct* specifies an *if-construct-name*, the corresponding *end-if-*
 3 *stmt* shall specify the same *if-construct-name*. If the *if-then-stmt* of an *if-construct* does not specify an
 4 *if-construct-name*, the corresponding *end-if-stmt* shall not specify an *if-construct-name*. If an *else-if-*
 5 *stmt* or *else-stmt* specifies an *if-construct-name*, the corresponding *if-then-stmt* shall specify the same
 6 *if-construct-name*.

7 8.1.7.2 Execution of an IF construct

8 1 At most one of the blocks in the IF construct is executed. If there is an ELSE statement in the construct,
 9 exactly one of the blocks in the construct is executed. The scalar logical expressions are evaluated in the order
 10 of their appearance in the construct until a true value is found or an ELSE statement or END IF statement is
 11 encountered. If a true value or an ELSE statement is found, the block immediately following is executed and this
 12 completes the execution of the construct. The scalar logical expressions in any remaining ELSE IF statements of
 13 the IF construct are not evaluated. If none of the evaluated expressions is true and there is no ELSE statement,
 14 the execution of the construct is completed without the execution of any block within the construct.

15 2 It is permissible to branch to an END IF statement only from within its IF construct. Execution of an END IF
 16 statement has no effect.

17 8.1.7.3 Examples of IF constructs

NOTE 8.17

```

IF (CVAR == 'RESET') THEN
  I = 0; J = 0; K = 0
END IF
PROOF_DONE: IF (PROP) THEN
  WRITE (3, '( 'QED' )')
  STOP
ELSE
  PROP = NEXTPROP
END IF PROOF_DONE
IF (A > 0) THEN
  B = C/A
  IF (B > 0) THEN
    D = 1.0
  END IF
ELSE IF (C > 0) THEN
  B = A/C
  D = -1.0
ELSE
  B = ABS (MAX (A, C))
  D = 0
END IF

```

18 8.1.7.4 IF statement

19 1 The IF statement controls the execution of a single action statement based on a single logical expression.

20 R834 *if-stmt* is IF (*scalar-logical-expr*) *action-stmt*

21 C834 (R834) The *action-stmt* in the *if-stmt* shall not be an *end-function-stmt*, *end-mp-subprogram-stmt*, *end-*
 22 *program-stmt*, *end-subroutine-stmt*, or *if-stmt*.

- 1 2 Execution of an IF statement causes evaluation of the scalar logical expression. If the value of the expression is
 2 true, the action statement is executed. If the value is false, the action statement is not executed.
- 3 3 The execution of a function reference in the scalar logical expression may affect entities in the action statement.

NOTE 8.18

An example of an IF statement is:

```
IF ( A > 0.0 ) A = LOG ( A )
```

8.1.8 SELECT CASE construct**8.1.8.1 Purpose and form of the SELECT CASE construct**

- 6 1 The SELECT CASE construct selects for execution at most one of its constituent blocks. The selection is based
 7 on the value of an expression.

8 R835 *case-construct* is *select-case-stmt*
 9 [*case-stmt*
 10 *block*] ...
 11 *end-select-stmt*

12 R836 *select-case-stmt* is [*case-construct-name* :] SELECT CASE (*case-expr*)

13 R837 *case-stmt* is CASE *case-selector* [*case-construct-name*]

14 R838 *end-select-stmt* is END SELECT [*case-construct-name*]

15 C835 (R835) If the *select-case-stmt* of a *case-construct* specifies a *case-construct-name*, the corresponding *end-*
 16 *select-stmt* shall specify the same *case-construct-name*. If the *select-case-stmt* of a *case-construct* does
 17 not specify a *case-construct-name*, the corresponding *end-select-stmt* shall not specify a *case-construct-*
 18 *name*. If a *case-stmt* specifies a *case-construct-name*, the corresponding *select-case-stmt* shall specify the
 19 same *case-construct-name*.

20 R839 *case-expr* is *scalar-expr*

21 C836 *case-expr* shall be of type character, integer, or logical.

22 R840 *case-selector* is (*case-value-range-list*)
 23 or DEFAULT

24 C837 (R835) No more than one of the selectors of one of the CASE statements shall be DEFAULT.

25 R841 *case-value-range* is *case-value*
 26 or *case-value* :
 27 or : *case-value*
 28 or *case-value* : *case-value*

29 R842 *case-value* is *scalar-constant-expr*

30 C838 (R835) For a given *case-construct*, each *case-value* shall be of the same type as *case-expr*. For character
 31 type, the *kind type parameters* shall be the same; character length differences are allowed.

32 C839 (R835) A *case-value-range* using a colon shall not be used if *case-expr* is of type logical.

33 C840 (R835) For a given *case-construct*, there shall be no possible value of the *case-expr* that matches more
 34 than one *case-value-range*.

1 8.1.8.2 Execution of a SELECT CASE construct

2 1 The execution of the SELECT CASE statement causes the case expression to be evaluated. For a case value
3 range list, a match occurs if the case expression value matches any of the case value ranges in the list. For a case
4 expression with a value of *c*, a match is determined as follows.

- 5 (1) If the case value range contains a single value *v* without a colon, a match occurs for type logical if
6 the expression *c* .EQV. *v* is true, and a match occurs for type integer or character if the expression
7 *c* == *v* is true.
- 8 (2) If the case value range is of the form *low* : *high*, a match occurs if the expression *low* <= *c* .AND.
9 *c* <= *high* is true.
- 10 (3) If the case value range is of the form *low* :, a match occurs if the expression *low* <= *c* is true.
- 11 (4) If the case value range is of the form : *high*, a match occurs if the expression *c* <= *high* is true.
- 12 (5) If no other selector matches and a DEFAULT selector appears, it matches the case index.
- 13 (6) If no other selector matches and the DEFAULT selector does not appear, there is no match.

14 2 The block following the CASE statement containing the matching selector, if any, is executed. This completes
15 execution of the construct.

16 3 It is permissible to branch to an *end-select-stmt* only from within its SELECT CASE construct.

17 8.1.8.3 Examples of SELECT CASE constructs

NOTE 8.19

An integer signum function:

```
INTEGER FUNCTION SIGNUM (N)
SELECT CASE (N)
CASE (:-1)
    SIGNUM = -1
CASE (0)
    SIGNUM = 0
CASE (1:)
    SIGNUM = 1
END SELECT
END
```

NOTE 8.20

A code fragment to check for balanced parentheses:

```
CHARACTER (80) :: LINE
...
LEVEL = 0
SCAN_LINE: DO I = 1, 80
    CHECK_PARENS: SELECT CASE (LINE (I:I))
        CASE ('(')
            LEVEL = LEVEL + 1
        CASE (')')
            LEVEL = LEVEL - 1
            IF (LEVEL < 0) THEN
                PRINT *, 'UNEXPECTED RIGHT PARENTHESIS'
                EXIT SCAN_LINE
            END IF
        CASE DEFAULT
            ! Ignore all other characters
```



```

1      SUBROUTINE process(x)
2          REAL x(..)
3          !
4          SELECT RANK(x)
5              RANK (0)
6                  x = 0
7              RANK (2)
8                  IF (SIZE(x,2)>=2) x(:,2) = 2
9              RANK DEFAULT
10             Print *, 'I did not expect rank', RANK(y), 'shape', SHAPE(y)
11             ERROR STOP 'process bad arg'
12         END SELECT

```

13 2 The following example shows how to process [assumed-size arrays](#), including how to use [sequence association](#) if
14 you want to do multi-dimensional processing of an [assumed-size array](#).

```

15         SELECT RANK (y => x)
16         RANK (*)
17             IF (RANK(x)==2) THEN
18                 ! Special code for the rank two case.
19                 CALL sequence_assoc_2(y, LBOUND(x,1), UBOUND(x,1), LBOUND(x,2))
20             ELSE
21                 ! We just do all the other ranks in array element order.
22                 i = 1
23                 DO
24                     IF (y(i)==0) Exit
25                     y(i) = -y(i)
26                     i = i + 1
27                 END DO
28             END IF
29         END SELECT
30         ...
31     CONTAINS
32         ...
33         SUBROUTINE sequence_assoc_2(a, lb1, ub1, lb2)
34             REAL a(lb1:ub1,lb2:*)
35             j = lb2
36         outer: DO
37             DO i=lb1,ub1
38                 IF (a(i,j)==0) EXIT outer
39                 a(i,j) = a(i,j)**2
40             END DO
41             j = j + 1
42             IF (ANY(a(:,j))==0) EXIT
43             j = j + 1
44         END DO outer
45     END SUBROUTINE

```

46 8.1.10 SELECT TYPE construct

47 8.1.10.1 Purpose and form of the SELECT TYPE construct

48 1 The SELECT TYPE construct selects for execution at most one of its constituent blocks. The selection is based
49 on the [dynamic type](#) of an expression. A [name](#) is associated with the expression or variable ([16.4](#), [16.5.1.6](#)), in
50 the same way as for the ASSOCIATE construct.

- 1 R847 *select-type-construct* is *select-type-stmt*
 2 [*type-guard-stmt*
 3 *block*] ...
 4 *end-select-type-stmt*
- 5 R848 *select-type-stmt* is [*select-construct-name* :] SELECT TYPE ■
 6 ■ ([*associate-name* =>] *selector*)
- 7 C848 (R848) If *selector* is not a named *variable*, *associate-name* => shall appear.
- 8 C849 (R848) If *selector* is not a *variable* or is a *variable* that has a *vector subscript*, *associate-name* shall not
 9 appear in a variable definition context (16.6.7).
- 10 C850 (R848) The *selector* in a *select-type-stmt* shall be *polymorphic*.
- 11 R849 *type-guard-stmt* is TYPE IS (*type-spec*) [*select-construct-name*]
 12 or CLASS IS (*derived-type-spec*) [*select-construct-name*]
 13 or CLASS DEFAULT [*select-construct-name*]
- 14 C851 (R849) The *type-spec* or *derived-type-spec* shall specify that each length type parameter is assumed.
- 15 C852 (R849) The *type-spec* or *derived-type-spec* shall not specify a type with the *BIND* attribute or the *SE-*
 16 *QUENCE* attribute.
- 17 C853 (R847) If *selector* is not *unlimited polymorphic*, each TYPE IS or CLASS IS *type-guard-stmt* shall specify
 18 an *extension* of the *declared type* of *selector*.
- 19 C854 (R847) For a given *select-type-construct*, the same type and *kind type parameter* values shall not be
 20 specified in more than one TYPE IS *type-guard-stmt* and shall not be specified in more than one CLASS
 21 IS *type-guard-stmt*.
- 22 C855 (R847) For a given *select-type-construct*, there shall be at most one CLASS DEFAULT *type-guard-stmt*.
- 23 R850 *end-select-type-stmt* is END SELECT [*select-construct-name*]
- 24 C856 (R847) If the *select-type-stmt* of a *select-type-construct* specifies a *select-construct-name*, the correspond-
 25 ing *end-select-type-stmt* shall specify the same *select-construct-name*. If the *select-type-stmt* of a *select-*
 26 *type-construct* does not specify a *select-construct-name*, the corresponding *end-select-type-stmt* shall not
 27 specify a *select-construct-name*. If a *type-guard-stmt* specifies a *select-construct-name*, the corresponding
 28 *select-type-stmt* shall specify the same *select-construct-name*.
- 29 2 The *associate name* of a SELECT TYPE construct is the *associate-name* if specified; otherwise it is the *name*
 30 that constitutes the *selector*.

31 8.1.10.2 Execution of the SELECT TYPE construct

- 32 1 Execution of a SELECT TYPE construct causes evaluation of every expression within a selector that is a variable
 33 designator, or evaluation of a selector that is not a variable designator.
- 34 2 A SELECT TYPE construct selects at most one block to be executed. During execution of that block, the
 35 *associate name* identifies an entity which is associated (16.5.1.6) with the selector.
- 36 3 A TYPE IS type guard statement matches the selector if the *dynamic type* and *kind type parameter* values of
 37 the selector are the same as those specified by the statement. A CLASS IS type guard statement matches the
 38 selector if the *dynamic type* of the selector is an *extension* of the type specified by the statement and the *kind*
 39 *type parameter* values specified by the statement are the same as the corresponding type parameter values of the
 40 *dynamic type* of the selector.
- 41 4 The block to be executed is selected as follows.

- 1 (1) If a TYPE IS type guard statement matches the selector, the block following that statement is
2 executed.
- 3 (2) Otherwise, if exactly one CLASS IS type guard statement matches the selector, the block following
4 that statement is executed.
- 5 (3) Otherwise, if several CLASS IS type guard statements match the selector, one of these statements
6 must specify a type that is an [extension](#) of all the types specified in the others; the block following
7 that statement is executed.
- 8 (4) Otherwise, if there is a CLASS DEFAULT type guard statement, the block following that statement
9 is executed.
- 10 (5) Otherwise, no block is executed.

NOTE 8.23

This algorithm does not examine the type guard statements in source text order when it looks for a match; it selects the most particular type guard when there are several potential matches.

- 11 5 Within the block following a TYPE IS type guard statement, the [associating entity](#) ([16.5.5](#)) is not polymorphic
12 ([4.3.2.3](#)), has the type named in the type guard statement, and has the type parameter values of the selector.
- 13 6 Within the block following a CLASS IS type guard statement, the [associating entity](#) is [polymorphic](#) and has the
14 [declared type](#) named in the type guard statement. The type parameter values of the [associating entity](#) are the
15 corresponding type parameter values of the selector.
- 16 7 Within the block following a CLASS DEFAULT type guard statement, the [associating entity](#) is [polymorphic](#) and
17 has the same [declared type](#) as the selector. The type parameter values of the [associating entity](#) are those of the
18 [declared type](#) of the selector.

NOTE 8.24

If the [declared type](#) of the [selector](#) is T, specifying CLASS DEFAULT has the same effect as specifying CLASS IS (T).

- 19 8 The other attributes of the [associating entity](#) are described in [8.1.3.3](#).
- 20 9 It is permissible to branch to an [end-select-type-stmt](#) only from within its SELECT TYPE construct.

8.1.10.3 Examples of the SELECT TYPE construct**NOTE 8.25**

```

TYPE POINT
  REAL :: X, Y
END TYPE POINT
TYPE, EXTENDS(POINT) :: POINT_3D
  REAL :: Z
END TYPE POINT_3D
TYPE, EXTENDS(POINT) :: COLOR_POINT
  INTEGER :: COLOR
END TYPE COLOR_POINT

TYPE(POINT), TARGET :: P
TYPE(POINT_3D), TARGET :: P3
TYPE(COLOR_POINT), TARGET :: C
CLASS(POINT), POINTER :: P_OR_C
P_OR_C => C
SELECT TYPE ( A => P_OR_C )
CLASS IS ( POINT )

```

NOTE 8.25 (cont.)

```

! "CLASS ( POINT ) :: A" implied here
PRINT *, A%X, A%Y ! This block gets executed
TYPE IS ( POINT_3D )
! "TYPE ( POINT_3D ) :: A" implied here
PRINT *, A%X, A%Y, A%Z
END SELECT

```

NOTE 8.26

The following example illustrates the omission of *associate-name*. It uses the declarations from Note 8.25.

```

P_OR_C => P3
SELECT TYPE ( P_OR_C )
CLASS IS ( POINT )
! "CLASS ( POINT ) :: P_OR_C" implied here
PRINT *, P_OR_C%X, P_OR_C%Y
TYPE IS ( POINT_3D )
! "TYPE ( POINT_3D ) :: P_OR_C" implied here
PRINT *, P_OR_C%X, P_OR_C%Y, P_OR_C%Z ! This block gets executed
END SELECT

```

1 **8.1.11 EXIT statement**

2 1 The EXIT statement provides one way of terminating a loop, or completing execution of another construct.

3 R851 *exit-stmt* is EXIT [*construct-name*]

4 C857 If a *construct-name* appears on an EXIT statement, the EXIT statement shall be within that construct;
5 otherwise, it shall be within at least one *do-construct*.

6 2 An EXIT statement belongs to a particular construct. If a construct name appears, the EXIT statement belongs
7 to that construct; otherwise, it belongs to the innermost *DO construct* in which it appears.

8 C858 An *exit-stmt* shall not appear within a **CRITICAL** or **DO CONCURRENT** construct if it belongs to that
9 construct or an outer construct.

10 3 When an EXIT statement that belongs to a *DO construct* is executed, it terminates the loop (8.1.6.4.5) and
11 any active loops contained within the terminated loop. When an EXIT statement that belongs to a non-DO
12 construct is executed, it terminates any active loops contained within that construct, and completes execution of
13 that construct.

14 **8.2 Branching**15 **8.2.1 Branch concepts**

16 1 Branching is used to alter the normal execution sequence. A branch causes a transfer of control from one
17 statement to a labeled *branch target statement* in the same *inclusive scope*. Branching may be caused by a **GO**
18 **TO statement**, a *computed GO TO statement*, a **CALL statement** that has an *alt-return-spec*, or an input/output statement
19 that has an **END=**, **EOR=**, or **ERR=** specifier. Although procedure references and control constructs can cause
20 transfer of control, they are not branches. A *branch target statement* is an *action-stmt*, *associate-stmt*, *end-*
21 *associate-stmt*, *if-then-stmt*, *end-if-stmt*, *select-case-stmt*, *end-select-stmt*, *select-rank-stmt*, *end-select-rank-stmt*,
22 *select-type-stmt*, *end-select-type-stmt*, *do-stmt*, *end-do-stmt*, *block-stmt*, *end-block-stmt*, *critical-stmt*, *end-critical-*
23 *stmt*, *forall-construct-stmt*, *forall-stmt*, or *where-construct-stmt*.

8.2.2 GO TO statement

R852 *goto-stmt* is GO TO *label*

C859 (R852) The *label* shall be the statement label of a [branch target statement](#) that appears in the same [inclusive scope](#) as the *goto-stmt*.

1 Execution of a GO TO statement causes a branch to the [branch target statement](#) identified by the label.

8.2.3 Computed GO TO statement

R853 *computed-goto-stmt* is GO TO (*label-list*) [,] *scalar-int-expr*

C860 (R853) Each *label* in *label-list* shall be the statement label of a [branch target statement](#) that appears in the same [inclusive scope](#) as the *computed-goto-stmt*.

1 Execution of a computed GO TO statement causes evaluation of the scalar integer expression. If this value is i such that $1 \leq i \leq n$ where n is the number of labels in *label-list*, a branch occurs to the [branch target statement](#) identified by the i^{th} label in the list of labels. If i is less than 1 or greater than n , the execution sequence continues as though a [CONTINUE statement](#) were executed.

8.3 CONTINUE statement

1 Execution of a CONTINUE statement has no effect.

R854 *continue-stmt* is CONTINUE

8.4 STOP and ERROR STOP statements

R855 *stop-stmt* is STOP [*stop-code*] [, QUIET = *scalar-logical-expr*]

R856 *error-stop-stmt* is ERROR STOP [*stop-code*] [, QUIET = *scalar-logical-expr*]

R857 *stop-code* is *scalar-default-char-expr*
or *scalar-int-expr*

C861 (R857) The *scalar-int-expr* shall be of default kind.

1 Execution of a STOP statement initiates [normal termination](#) of execution. Execution of an ERROR STOP statement initiates [error termination](#) of execution.

2 When an [image](#) is terminated by a STOP or ERROR STOP statement, its stop code, if any, is made available in a processor-dependent manner. If the *stop-code* is an integer, it is recommended that the value be used as the process exit status, if the processor supports that concept. If the *stop-code* in a STOP statement is of type character or does not appear, or if an [end-program-stmt](#) is executed, it is recommended that the value zero be supplied as the process exit status, if the processor supports that concept. If the *stop-code* in an ERROR STOP statement is of type character or does not appear, or if an [end-program-stmt](#) is executed, it is recommended that a processor-dependent nonzero value be supplied as the process exit status, if the processor supports that concept.

3 If QUIET= is omitted or the *scalar-logical-expr* has the value false:

- if any exception (14) is signaling on that [image](#), the processor shall issue a warning indicating which exceptions are signaling, and this warning shall be on the [unit](#) identified by the named constant [ERROR_UNIT](#) from the intrinsic module [ISO_FORTRAN_ENV](#) (13.9.2.8);
- if a stop code is specified, it is recommended that it be made available by formatted output to the same [unit](#).

4 If QUIET= appears and the *scalar-logical-expr* has the value true, no output of signaling exceptions or stop code shall be produced.

NOTE 8.27

When normal termination occurs on more than one **image**, it is expected that a processor-dependent summary of any stop codes and signaling exceptions will be made available.

NOTE 8.28

If the integer *stop-code* is used as the process exit status, the processor might be able to interpret only values within a limited range, or only a limited portion of the integer value (for example, only the least-significant 8 bits).

8.5 Image execution control

8.5.1 Image control statements

1 The execution sequence on each **image** is specified in 2.3.5.

2 Execution of an **image control statement** divides the execution sequence on an **image** into segments. Each of the following is an **image control statement**:

- **SYNC ALL** statement;
- **SYNC IMAGES** statement;
- **SYNC MEMORY** statement;
- **ALLOCATE** or **DEALLOCATE** statement that has a *coarray allocate-object*;
- **CRITICAL** or **END CRITICAL** (8.1.5);
- **EVENT POST** or **EVENT WAIT** statement;
- **LOCK** or **UNLOCK** statement;
- any statement that completes execution of a block or procedure and which results in the implicit deallocation of a *coarray*;
- a **CALL** statement that references the intrinsic subroutine **MOVE_ALLOC** with *coarray* arguments;
- **STOP** statement;
- **END** statement of a main program.

3 All image control statements except **CRITICAL**, **END CRITICAL**, **EVENT POST**, **EVENT WAIT**, **LOCK**, and **UNLOCK** include the effect of executing a **SYNC MEMORY** statement (8.5.5).

4 During an execution of a statement that invokes more than one procedure, at most one invocation shall cause execution of an **image control statement** other than **CRITICAL** or **END CRITICAL**.

8.5.2 Segments

1 On each **image**, the sequence of statements executed before the first execution of an **image control statement**, between the execution of two **image control statements**, or after the last execution of an **image control statement** is a segment. The segment executed immediately before the execution of an **image control statement** includes the evaluation of all expressions within the statement.

2 By execution of **image control statements** or user-defined ordering (8.5.5), the program can ensure that the execution of the i^{th} segment on **image** P, P_i , either precedes or succeeds the execution of the j^{th} segment on another **image** Q, Q_j . If the program does not ensure this, segments P_i and Q_j are unordered; depending on the relative execution speeds of the **images**, some or all of the execution of the segment P_i may take place at the same time as some or all of the execution of the segment Q_j .

3 A *coarray* may be referenced or defined by execution of an **atomic subroutine** during the execution of a segment that is unordered relative to the execution of a segment in which the *coarray* is referenced or defined by execution

1 of an **atomic subroutine**. An **event variable** may be referenced or defined during the execution of a segment that
 2 is unordered relative to the execution of another segment in which that **event variable** is defined. Otherwise,

- 3 • if a variable is defined on an **image** in a segment, it shall not be referenced, defined, or become undefined
 4 in a segment on another **image** unless the segments are ordered,
- 5 • if the allocation of an **allocatable** subobject of a **coarray** or the **pointer association** of a pointer subobject
 6 of a **coarray** is changed on an **image** in a segment, that subobject shall not be referenced or defined in a
 7 segment on another **image** unless the segments are ordered, and
- 8 • if a procedure invocation on **image** P is in execution in segments P_i, P_{i+1}, \dots, P_k and defines a noncoarray
 9 **dummy argument**, the **effective argument** shall not be referenced, defined, or become undefined on another
 10 **image** Q in a segment Q_j unless Q_j precedes P_i or succeeds P_k .

NOTE 8.29

The set of all segments on all **images** is partially ordered: the segment P_i precedes segment Q_j if and only if there is a sequence of segments starting with P_i and ending with Q_j such that each segment of the sequence precedes the next either because they are consecutive segments on the same **image** or because of the execution of **image control statements**.

NOTE 8.30

If the segments S_1, S_2, \dots, S_k on the distinct **images** P_1, P_2, \dots, P_k are all unordered with respect to each other, it is expected that the processor will ensure that each of these **images** is provided with an equitable share of resources for executing its segment.

NOTE 8.31

Because of the restrictions on references and definitions in unordered segments, the processor can apply code motion optimizations within a segment as if it were the only **image** in execution, provided calls to **atomic subroutines** are not involved.

NOTE 8.32

The model upon which the interpretation of a program is based is that there is a permanent memory location for each **coarray** and that all **images** can access it.

In practice, apart from executions of **atomic subroutines**, the processor could make a copy of a nonvolatile **coarray** on an **image** (in cache or a register, for example) and, as an optimization, defer copying a changed value back to the permanent memory location while it is still being used. Since the variable is not volatile, it is safe to defer this transfer until the end of the segment and thereafter to reload from permanent memory any **coarray** that was not defined within the segment. It might not be safe to defer these actions beyond the end of the segment since another **image** might reference the variable then.

The value of the ATOM argument of an **atomic subroutine** might be accessed or modified by another concurrently executing **image**. Therefore, execution of an **atomic subroutine** that references the ATOM argument cannot rely on a local copy, but instead always gets its value from its permanent memory location. Execution of an **atomic subroutine** that defines the ATOM argument does not complete until the value of its ATOM argument has been sent to its permanent memory location.

NOTE 8.33

The incorrect sequencing of **image control statements** can suspend execution indefinitely. For example, one **image** might be executing a **SYNC ALL statement** while another is executing an **ALLOCATE statement** for a **coarray**.

8.5.3 SYNC ALL statement

R858 *sync-all-stmt* is SYNC ALL [([*sync-stat-list*])]

1 R859 *sync-stat* is STAT = *stat-variable*
 2 or ERRMSG = *errmsg-variable*

3 C862 No specifier shall appear more than once in a given *sync-stat-list*.

4 1 The STAT= and ERRMSG= specifiers for *image control statements* are described in 8.5.9.

5 2 Execution of a SYNC ALL statement performs a synchronization of all *images*. Execution on an *image*, M, of
 6 the segment following the SYNC ALL statement is delayed until each other *image* has executed a SYNC ALL
 7 statement as many times as has *image* M. The segments that executed before the SYNC ALL statement on an
 8 *image* precede the segments that execute after the SYNC ALL statement on another *image*.

NOTE 8.34

The processor might have special hardware or employ an optimized algorithm to make the SYNC ALL statement execute efficiently.

Here is a simple example of its use. *Image* 1 reads data and broadcasts it to other *images*:

```
REAL :: P[*]
...
SYNC ALL
IF (THIS_IMAGE()==1) THEN
  READ (*,*) P
  DO I = 2, NUM_IMAGES()
    P[I] = P
  END DO
END IF
SYNC ALL
```

9 8.5.4 SYNC IMAGES statement

10 R860 *sync-images-stmt* is SYNC IMAGES (*image-set* [, *sync-stat-list*])

11 R861 *image-set* is *int-expr*
 12 or *

13 C863 An *image-set* that is an *int-expr* shall be scalar or of *rank* one.

14 1 If *image-set* is an array expression, the value of each element shall be positive and not greater than the number
 15 of *images*, and there shall be no repeated values.

16 2 If *image-set* is a scalar expression, its value shall be positive and not greater than the number of *images*.

17 3 An *image-set* that is an asterisk specifies all *images*.

18 4 Execution of a SYNC IMAGES statement performs a synchronization of the *image* with each of the other *images*
 19 in the *image-set*. Executions of SYNC IMAGES statements on *images* M and T correspond if the number of
 20 times *image* M has executed a SYNC IMAGES statement with T in its *image* set is the same as the number of
 21 times *image* T has executed a SYNC IMAGES statement with M in its *image* set. The segments that executed
 22 before the SYNC IMAGES statement on either *image* precede the segments that execute after the corresponding
 23 SYNC IMAGES statement on the other *image*.

NOTE 8.35

A SYNC IMAGES statement that specifies the single *image index* value THIS_IMAGE () in its *image* set is allowed. This simplifies writing programs for an arbitrary number of *images* by allowing correct execution in the limiting case of the number of *images* being equal to one.

NOTE 8.36

In a program that uses `SYNC ALL` as its only synchronization mechanism, every `SYNC ALL` statement could be replaced by a `SYNC IMAGES (*)` statement, but `SYNC ALL` might give better performance.

`SYNC IMAGES` statements are not required to specify the entire `image` set, or even the same `image` set, on all `images` participating in the synchronization. In the following example, `image 1` will wait for each of the other `images` to complete its use of the data. The other `images` wait for `image 1` to set up the data, but do not wait on any other `image`.

```
IF (THIS_IMAGE() == 1) then
  ! Set up coarray data needed by all other images
  SYNC IMAGES(*)
ELSE
  SYNC IMAGES(1)
  ! Use the data set up by image 1
END IF
```

When the following example runs on five or more `images`, each `image` synchronizes with both of its neighbors, in a circular fashion.

```
INTEGER :: up, down
...
IF (NUM_IMAGES()>1) THEN
  up = THIS_IMAGE()+1; IF (up>NUM_IMAGES()) up = 1
  down = THIS_IMAGE()-1; IF (down==0) down = NUM_IMAGES()
  SYNC IMAGES ( (/ up, down /) )
END IF
```

This might appear to have the same effect as `SYNC ALL` but there is no ordering between the preceding and succeeding segments on non-adjacent `images`. For example, the segment preceding the `SYNC IMAGES` statement on `image 3` will be ordered before those succeeding it on `images 2` and `4`, but not those on `images 1` and `5`.

NOTE 8.37

In the following example, each `image` synchronizes with its neighbor.

```
INTEGER :: ME, NE, STEP, NSTEPS
NE = NUM_IMAGES()
ME = THIS_IMAGE()
  ! Initial calculation
SYNC ALL
DO STEP = 1, NSTEPS
  IF (ME > 1) SYNC IMAGES(ME-1)
  ! Perform calculation
  IF (ME < NE) SYNC IMAGES(ME+1)
END DO
SYNC ALL
```

The calculation starts on `image 1` since all the others will be waiting on `SYNC IMAGES (ME-1)`. When this is done, `image 2` can start and `image 1` can perform its second calculation. This continues until they are all executing different steps at the same time. Eventually, `image 1` will finish and then the others will finish one by one.

8.5.5 SYNC MEMORY statement

1 Execution of a SYNC MEMORY statement ends one segment and begins another; those two segments can be ordered by a user-defined way with respect to segments on other **images**.

R862 *sync-memory-stmt* is SYNC MEMORY [([*sync-stat-list*])]

2 If, by execution of statements on **image** P,

- a variable X on **image** Q is defined, referenced, becomes undefined, or has its allocation status, **pointer association** status, array bounds, **dynamic type**, or type parameters changed or inquired about by execution of a statement,
- that statement precedes a successful execution of a SYNC MEMORY statement, and
- a variable Y on **image** Q is defined, referenced, becomes undefined, or has its allocation status, **pointer association** status, array bounds, **dynamic type**, or type parameters changed or inquired about by execution of a statement that succeeds execution of that SYNC MEMORY statement,

then the action regarding X on **image** Q precedes the action regarding Y on **image** Q.

3 User-defined ordering of segment P_i on **image** P to precede segment Q_j on **image** Q occurs when

- **image** P executes an **image control statement** that ends segment P_i , and then executes statements that initiate a cooperative synchronization between **images** P and Q, and
- **image** Q executes statements that complete the cooperative synchronization between **images** P and Q and then executes an **image control statement** that begins segment Q_j .

4 Execution of the cooperative synchronization between **images** P and Q shall include a dependency that forces execution on **image** P of the statements that initiate the synchronization to precede the execution on **image** Q of the statements that complete the synchronization. The mechanisms available for creating such a dependency are processor dependent.

NOTE 8.38

SYNC MEMORY usually suppresses compiler optimizations that might reorder memory operations across the segment boundary defined by the SYNC MEMORY statement and ensures that all memory operations initiated in the preceding segments in its **image** complete before any memory operations in the subsequent segment in its **image** are initiated. It needs to do this unless it can establish that failure to do so could not alter processing on another **image**.

NOTE 8.39

SYNC MEMORY can be used to implement specialized schemes for segment ordering, such as the spin-wait loop. For example:

```

USE, INTRINSIC :: ISO_FORTRAN_ENV
LOGICAL(ATOMICAL_KIND), SAVE :: LOCKED[*] = .TRUE.
LOGICAL :: VAL
INTEGER :: IAM, P, Q
...
IAM = THIS_IMAGE()
IF (IAM == P) THEN
    SYNC MEMORY
    CALL ATOMIC_DEFINE (LOCKED[Q], .FALSE.)
ELSE IF (IAM == Q) THEN
    VAL = .TRUE.
    DO WHILE (VAL)
    CALL ATOMIC_REF (VAL, LOCKED)

```

! Segment P_i
! A
! Segment P_{i+1}
! Segment Q_{j-1}

NOTE 8.39 (cont.)

```

END DO
  SYNC MEMORY                ! B
                              ! Segment  $Q_j$ 
END IF

```

The **DO WHILE** loop does not complete until VAL is defined with the value false. This is the cooperative synchronization that provides the dependency that **image** Q does not complete segment Q_{j-1} until the **CALL statement** in segment P_{i+1} completes. This ensures that the execution of segment P_i on **image** P precedes execution of segment Q_j on **image** Q.

The first SYNC MEMORY statement (A) ensures that the compiler does not reorder the following statement (segment P_{i+1}) with the previous statements, since the lock is supposed to be freed only after the work in segment P_i has been completed.

The second SYNC MEMORY statement (B) marks the beginning of a new segment, informing the compiler that the values of **coarrays** referenced in that segment might have been changed by other **images** in preceding segments, so need to be loaded from memory.

NOTE 8.40

As a second example, the user might have access to an **external procedure** that performs synchronization between **images**. That library procedure might not be aware of the mechanisms used by the processor to manage remote data references and definitions, and therefore not, by itself, be able to ensure the correct memory state before and after its reference. The SYNC MEMORY statement provides the needed memory ordering that enables the safe use of the external synchronization routine. For example:

```

INTEGER :: IAM
REAL    :: X[*]

IAM = THIS_IMAGE()
IF (IAM == 1) X = 1.0
SYNC MEMORY
CALL EXTERNAL_SYNC()
SYNC MEMORY
IF (IAM == 2) WRITE(*,*) X[1]

```

where executing the subroutine EXTERNAL_SYNC has an **image** synchronization effect similar to executing a **SYNC ALL statement**.

8.5.6 EVENT POST statement

1 The EVENT POST statement posts an event.

3 R863 *event-post-stmt* is EVENT POST (*event-variable* [, *sync-stat-list*])

4 R864 *event-variable* is scalar-variable

5 C864 (R864) An *event-variable* shall be of type **EVENT_TYPE** from the intrinsic module **ISO_FORTRAN_**
6 **ENV(13.9.2)**.

7 2 Successful execution of an EVENT POST statement atomically increments the count of the **event variable** by
8 one. If an error condition occurs during execution of an EVENT POST statement, the value of the count of the
9 **event variable** is processor dependent. The completion of an EVENT POST statement does not depend on the
10 execution of a corresponding **EVENT WAIT statement**.

8.5.7 EVENT WAIT statement

1 The EVENT WAIT statement waits until an event is posted.

R865 *event-wait-stmt* is EVENT WAIT (*event-variable* [, *event-wait-spec-list*])

R866 *event-wait-spec* is *until-spec*
or *sync-stat*

R867 *until-spec* is UNTIL_COUNT = *scalar-int-expr*

C865 (R865) The *event-variable* in an *event-wait-stmt* shall not be coindexed.

C866 (R865) No specifier shall appear more than once in an *event-wait-spec-list*.

2 Execution of an EVENT WAIT statement consists of the following sequence of actions:

1. if the UNTIL_COUNT= specifier does not appear, the threshold value is set to one; otherwise, the threshold value is set to the maximum of the value of the *scalar-int-expr* and one;
2. the executing image waits until the count of the *event variable* is greater than or equal to the threshold value or an error condition occurs;
3. if no error condition occurs, the count of the *event variable* is atomically decremented by the threshold value.

3 If an error occurs during execution of an EVENT WAIT statement, the value of the count of its *event variable* is processor dependent.

4 An **EVENT POST statement** execution is initially unsatisfied. Successful execution of an EVENT WAIT statement with a threshold of *k* satisfies the first *k* unsatisfied **EVENT POST statement** executions for that *event variable*. This EVENT WAIT statement execution causes the segment following the EVENT WAIT statement execution to succeed the segments preceding those *k* **EVENT POST statement** executions.

8.5.8 LOCK and UNLOCK statements

R868 *lock-stmt* is LOCK (*lock-variable* [, *lock-stat-list*])

R869 *lock-stat* is ACQUIRED_LOCK = *scalar-logical-variable*
or *sync-stat*

C867 No specifier shall appear more than once in a given *lock-stat-list*.

R870 *unlock-stmt* is UNLOCK (*lock-variable* [, *sync-stat-list*])

R871 *lock-variable* is *scalar-variable*

C868 (R871) A *lock-variable* shall be of type LOCK_TYPE from the intrinsic module ISO_FORTRAN_ENV (13.9.2.17).

1 A lock variable is unlocked if and only if the value of each component is the same as its default value. If it has any other value, it is locked. A lock variable is locked by an *image* if it was locked by execution of a LOCK statement on that *image* and has not been subsequently unlocked by execution of an UNLOCK statement on the same *image*.

2 Successful execution of a LOCK statement without an ACQUIRED_LOCK= specifier causes the lock variable to become locked by that *image*. If the lock variable is already locked by another *image*, that LOCK statement causes the lock variable to become locked after the other *image* causes the lock variable to become unlocked.

- 1 3 If the lock variable is unlocked, successful execution of a LOCK statement with an ACQUIRED_LOCK= specifier
 2 causes the lock variable to become locked by that `image` and the scalar logical variable to become defined with the
 3 value true. If the lock variable is already locked by a different `image`, successful execution of a LOCK statement
 4 with an ACQUIRED_LOCK= specifier leaves the lock variable unchanged and causes the scalar logical variable
 5 to become defined with the value false.
- 6 4 Successful execution of an UNLOCK statement causes the lock variable to become unlocked.
- 7 5 During execution of the program, the value of a lock variable changes through a sequence of locked and unlocked
 8 states due to the execution of LOCK and UNLOCK statements. If a lock variable becomes unlocked by execution
 9 of an UNLOCK statement on `image M` and next becomes locked by execution of a LOCK statement on `image T`,
 10 the segments preceding the UNLOCK statement on `image M` precede the segments following the LOCK statement
 11 on `image T`. Execution of a LOCK statement that does not cause the lock variable to become locked does not
 12 affect segment ordering.
- 13 6 An error condition occurs if the lock variable in a LOCK statement is already locked by the executing `image`.
 14 An error condition occurs if the lock variable in an UNLOCK statement is not already locked by the executing
 15 `image`. If an error condition occurs during execution of a LOCK or UNLOCK statement, the value of the lock
 16 variable is not changed and the value of the ACQUIRED_LOCK variable, if any, is not changed.

NOTE 8.41

A lock variable is effectively defined atomically by a LOCK or UNLOCK statement. If LOCK statements on two `images` both attempt to acquire a lock, one will succeed and the other will either fail if an ACQUIRED_LOCK= specifier appears, or will wait until the lock is later released if an ACQUIRED_LOCK= specifier does not appear.

NOTE 8.42

An `image` might wait for a LOCK statement to successfully complete for a long period of time if other `images` frequently lock and unlock the same lock variable. This situation might result from executing LOCK statements with ACQUIRED_LOCK= specifiers inside a spin loop.

NOTE 8.43

The following example illustrates the use of LOCK and UNLOCK statements to manage a work queue:

```
USE, INTRINSIC :: ISO_FORTRAN_ENV

TYPE(LOCK_TYPE) :: queue_lock[*] ! Lock on each image to manage its work queue
INTEGER :: work_queue_size[*]
TYPE(Task) :: work_queue(100)[*] ! List of tasks to perform

TYPE(Task) :: job ! Current task working on
INTEGER :: me

me = THIS_IMAGE()
DO
  ! Process the next item in your work queue

  LOCK (queue_lock) ! New segment A starts
  ! This segment A is ordered with respect to
  ! segment B executed by image me-1 below because of lock exclusion
  IF (work_queue_size>0) THEN
    ! Fetch the next job from the queue
    job = work_queue(work_queue_size)
    work_queue_size = work_queue_size-1
  END IF
```

NOTE 8.43 (cont.)

```

UNLOCK (queue_lock) ! Segment ends
... ! Actually process the task

! Add a new task on neighbors queue:
LOCK(queue_lock[me+1]) ! Starts segment B
! This segment B is ordered with respect to
! segment A executed by image me+1 above because of lock exclusion
IF (work_queue_size[me+1]<SIZE(work_queue)) THEN
    work_queue_size[me+1] = work_queue_size[me+1]+1
    work_queue(work_queue_size[me+1])[me+1] = job
END IF
UNLOCK (queue_lock[me+1]) ! Ends segment B

END DO

```

1 8.5.9 STAT= and ERRMSG= specifiers in image control statements

- 2 1 If the STAT= specifier appears, successful execution of the LOCK, SYNC ALL, SYNC IMAGES, SYNC MEMORY,
3 or UNLOCK statement causes the specified variable to become defined with the value zero.
- 4 2 If the STAT= specifier appears in a SYNC ALL or SYNC IMAGES statement and execution of one of these
5 statements involves synchronization with an image that has initiated normal termination, the variable becomes
6 defined with the value of the constant STAT_STOPPED_IMAGE (13.9.2.25) in the intrinsic module ISO_
7 FORTRAN_ENV(13.9.2), and the effect of executing the statement is otherwise the same as that of executing
8 the SYNC MEMORY statement. If any other error condition occurs during execution of one of these statements,
9 the variable becomes defined with a processor-dependent positive integer value that is different from the value of
10 STAT_STOPPED_IMAGE.
- 11 3 If the STAT= specifier appears in a LOCK statement and the lock variable is locked by the executing image,
12 the specified variable becomes defined with the value of STAT_LOCKED (13.9.2.23). If the STAT= specifier
13 appears in an UNLOCK statement and the lock variable has the value unlocked, the variable specified by the
14 STAT= specifier becomes defined with the value of STAT_UNLOCKED (13.9.2.26). If the STAT= specifier
15 appears in an UNLOCK statement and the lock variable is locked by a different image, the specified variable
16 becomes defined with the value STAT_LOCKED_OTHER_IMAGE (13.9.2.24). The named constants STAT_
17 LOCKED, STAT_UNLOCKED, and STAT_LOCKED_OTHER_IMAGE are defined in the intrinsic module
18 ISO_FORTRAN_ENV. If any other error condition occurs during execution of a LOCK or UNLOCK statement,
19 the specified variable becomes defined with a positive integer value that is different from STAT_LOCKED,
20 STAT_UNLOCKED, and STAT_LOCKED_OTHER_IMAGE.
- 21 4 If an error condition occurs during execution of an EVENT POST, EVENT WAIT, LOCK, SYNC ALL, SYNC
22 IMAGES, SYNC MEMORY, or UNLOCK statement that does not contain the STAT= specifier, error termination
23 is initiated.
- 24 5 If an ERRMSG= specifier appears in an EVENT POST, EVENT WAIT, LOCK, SYNC ALL, SYNC IMAGES,
25 SYNC MEMORY, or UNLOCK statement, and an error condition occurs during execution of that statement, the
26 specified variable is assigned an explanatory message as if by intrinsic assignment. If no such condition occurs,
27 the definition status and value of the specified variable are unchanged.
- 28 6 The set of error conditions that can occur in an image control statement is processor dependent.

NOTE 8.44

A processor might detect communication failure between images and treat it as an error condition. A processor might also treat an invalid set of images in a SYNC IMAGES statement as an error condition.

9 Input/output statements

9.1 Input/output concepts

- 1 **Input statements** provide the means of transferring data from external media to internal storage or from an **internal file** to internal storage. This process is called reading. **Output statements** provide the means of transferring data from internal storage to external media or from internal storage to an **internal file**. This process is called writing. Some **input/output statements** specify that editing of the data is to be performed.
- 2 In addition to the statements that transfer data, there are auxiliary input/output statements to manipulate the external medium, or to describe or inquire about the properties of the connection to the external medium.
- 3 The input/output statements are the **BACKSPACE**, **CLOSE**, **ENDFILE**, **FLUSH**, **INQUIRE**, **OPEN**, **PRINT**, **READ**, **REWIND**, **WAIT**, and **WRITE** statements.
- 4 A file is composed of either a sequence of **file storage units** (9.3.5) or a sequence of records, which provide an extra level of organization to the file. A file composed of records is called a **record file**. A file composed of **file storage units** is called a **stream file**. A processor may allow a file to be viewed both as a **record file** and as a **stream file**; in this case the relationship between the **file storage units** when viewed as a **stream file** and the records when viewed as a **record file** is processor dependent.
- 5 A file is either an **external file** (9.3) or an **internal file** (9.4).

9.2 Records

9.2.1 Definition of a record

- 1 A **record** is a sequence of values or a sequence of characters. For example, a line on a terminal is usually considered to be a record. However, a record does not necessarily correspond to a physical entity. There are three kinds of records:
 - (1) formatted;
 - (2) unformatted;
 - (3) endfile.

NOTE 9.1

What is called a “record” in Fortran is commonly called a “logical record”. There is no concept in Fortran of a “physical record.”

9.2.2 Formatted record

- 1 A formatted record consists of a sequence of characters that are representable in the processor; however, a processor may prohibit some control characters (3.1.1) from appearing in a formatted record. The length of a formatted record is measured in characters and depends primarily on the number of characters put into the record when it is written. However, it may depend on the processor and the external medium. The length may be zero. Formatted records shall be read or written only by **formatted input/output statements**.

9.2.3 Unformatted record

- 1 An unformatted record consists of a sequence of values in a processor-dependent form and may contain data of any type or may contain no data. The length of an unformatted record is measured in **file storage units**

1 (9.3.5) and depends on the output list (9.6.3) used when it is written, as well as on the processor and the external
2 medium. The length may be zero. Unformatted records may be read or written only by [unformatted input/output](#)
3 [statements](#).

4 9.2.4 Endfile record

5 1 An endfile record is written explicitly by the [ENDFILE statement](#); the file shall be [connected](#) for sequential
6 access. An endfile record is written implicitly to a file [connected](#) for sequential access when the most recent [data](#)
7 [transfer statement](#) referring to the file is an [output statement](#), no intervening [file positioning statement](#) referring
8 to the file has been executed, and

- 9 • a [REWIND](#) or [BACKSPACE](#) statement references the [unit](#) to which the file is [connected](#), or
- 10 • the [unit](#) is closed, either explicitly by a [CLOSE statement](#), implicitly by [normal termination](#), or implicitly
11 by another [OPEN statement](#) for the same [unit](#).

12 2 An endfile record may occur only as the last record of a file. An endfile record does not have a length property.

NOTE 9.2

An endfile record does not necessarily have any physical embodiment. The processor can use a record count or any other means to register the position of the file at the time an [ENDFILE statement](#) is executed, so that it can take appropriate action when that position is reached again during a read operation. The endfile record, however it is implemented, is considered to exist for the [BACKSPACE statement](#) (9.8.2).

13 9.3 External files

14 9.3.1 External file concepts

15 1 An [external file](#) is any file that exists in a medium external to the program.

16 2 At any given time, there is a processor-dependent set of allowed access methods, a processor-dependent set of
17 allowed forms, a processor-dependent set of allowed actions, and a processor-dependent set of allowed record
18 lengths for a file.

NOTE 9.3

For example, the processor-dependent set of allowed actions for a printer would likely include the write action, but not the read action.

19 3 A file may have a name; a file that has a name is called a named file. The name of a named file is represented by
20 a character string value. The set of allowable names for a file is processor dependent. Whether a named file on
21 one [image](#) is the same as a file with the same name on another [image](#) is processor dependent.

NOTE 9.4

If different files are needed on each [image](#), using a different file name on each [image](#) will improve portability of the code. One technique is to incorporate the [image index](#) as part of the name.

22 4 An [external file](#) that is [connected](#) to a [unit](#) has a position property (9.3.4).

NOTE 9.5

For more explanatory information on [external files](#), see C.6.1.

23 9.3.2 File existence

24 1 At any given time, there is a processor-dependent set of [external files](#) that exist for a program. A file may be
25 known to the processor, yet not exist for a program at a particular time.

1 2 To create a file means to cause a file to exist that did not exist previously. To delete a file means to terminate
2 the existence of the file.

3 3 All input/output statements may refer to files that exist. A **CLOSE**, **ENDFILE**, **FLUSH**, **INQUIRE**, **OPEN**,
4 **PRINT**, **REWIND**, or **WRITE** statement is permitted to refer to a file that does not exist. No other input/output
5 statement shall refer to a file that does not exist. Execution of a **WRITE**, **PRINT**, or **ENDFILE** statement
6 referring to a **preconnected** file that does not exist creates the file. This file is a different file from one **preconnected**
7 on any other **image**.

8 **9.3.3 File access**

9 **9.3.3.1 File access methods**

10 1 There are three methods of accessing the data of an **external file**: sequential, direct, and stream. Some files may
11 have more than one allowed access method; other files may be restricted to one access method.

NOTE 9.6

For example, a processor might provide only sequential access to a file on magnetic tape. Thus, the set of allowed access methods depends on the file and the processor.

12 2 The method of accessing a file is determined when the file is **connected** to a **unit** (9.5.4) or when the file is created
13 if the file is **preconnected** (9.5.5).

14 **9.3.3.2 Sequential access**

15 1 Sequential access is a method of accessing the records of an external **record file** in order.

16 2 While **connected** for sequential access, an **external file** has the following properties.

- 17 • The order of the records is the order in which they were written if the direct access method is not a member
18 of the set of allowed access methods for the file. If the direct access method is also a member of the set of
19 allowed access methods for the file, the order of the records is the same as that specified for direct access.
20 In this case, the first record accessible by sequential access is the record whose record number is 1 for direct
21 access. The second record accessible by sequential access is the record whose record number is 2 for direct
22 access, etc. A record that has not been written since the file was created shall not be read.
- 23 • The records of the file are either all formatted or all unformatted, except that the last record of the file may
24 be an endfile record. Unless the previous reference to the file was an **output statement**, the last record, if
25 any, of the file shall be an endfile record.
- 26 • The records of the file shall be read or written only by sequential access **data transfer statements**.

27 **9.3.3.3 Direct access**

28 1 Direct access is a method of accessing the records of an external **record file** in arbitrary order.

29 2 While **connected** for direct access, an **external file** has the following properties.

- 30 • Each record of the file is uniquely identified by a positive integer called the record number. The record
31 number of a record is specified when the record is written. Once established, the record number of a record
32 can never be changed. The order of the records is the order of their record numbers.
- 33 • The records of the file are either all formatted or all unformatted. If the sequential access method is also a
34 member of the set of allowed access methods for the file, its endfile record, if any, is not considered to be
35 part of the file while it is **connected** for direct access. If the sequential access method is not a member of
36 the set of allowed access methods for the file, the file shall not contain an endfile record.
- 37 • The records of the file shall be read or written only by direct access **data transfer statements**.
- 38 • All records of the file have the same length.

- 1 • Records need not be read or written in the order of their record numbers. Any record may be written
2 into the file while it is **connected** to a **unit**. For example, it is permissible to write record 3, even though
3 records 1 and 2 have not been written. Any record may be read from the file while it is **connected** to a
4 **unit**, provided that the record has been written since the file was created, and if a **READ statement** for this
5 connection is permitted.
- 6 • The records of the file shall not be read or written using list-directed formatting (10.10), namelist formatting
7 (10.11), or a nonadvancing **data transfer statement** (9.3.4.2).

NOTE 9.7

A record cannot be deleted; however, a record can be rewritten.

9.3.3.4 Stream access

- 8 1 Stream access is a method of accessing the **file storage units** (9.3.5) of an external **stream file**.
- 9 2 The properties of an **external file connected** for stream access depend on whether the connection is for unformatted
10 or formatted access. While connected for stream access, the **file storage units** of the file shall be read or written
11 only by stream access **data transfer statements**.
12
- 13 3 While **connected** for unformatted stream access, an **external file** has the following properties.
 - 14 • Each **file storage unit** in the file is uniquely identified by a positive integer called the position. The first **file**
15 **storage unit** in the file is at position 1. The position of each subsequent **file storage unit** is one greater than
16 that of its preceding **file storage unit**.
 - 17 • If it is possible to position the file, the **file storage units** need not be read or written in order of their position.
18 For example, it might be permissible to write the **file storage unit** at position 3, even though the **file storage**
19 **units** at positions 1 and 2 have not been written. Any **file storage unit** may be read from the file while it is
20 **connected** to a **unit**, provided that the **file storage unit** has been written since the file was created, and if a
21 **READ statement** for this connection is permitted.
- 22 4 While **connected** for formatted stream access, an **external file** has the following properties.
 - 23 • Some **file storage units** of the file may contain record markers; this imposes a record structure on the file
24 in addition to its stream structure. There might or might not be a record marker at the end of the file. If
25 there is no record marker at the end of the file, the final record is incomplete.
 - 26 • No maximum length (9.5.6.15) is applicable to these records.
 - 27 • Writing an empty record with no record marker has no effect.
 - 28 • Each **file storage unit** in the file is uniquely identified by a positive integer called the position. The first **file**
29 **storage unit** in the file is at position 1. The relationship between positions of successive **file storage units** is
30 processor dependent; not all positive integers need correspond to valid positions.
 - 31 • If it is possible to position the file, the file position can be set to a position that was previously identified
32 by the **POS= specifier** in an **INQUIRE statement**.
 - 33 • A processor may prohibit some control characters (3.1.1) from appearing in a formatted **stream file**.

NOTE 9.8

Because the record structure is determined from the record markers that are stored in the file itself, an incomplete record at the end of the file is necessarily not empty.

NOTE 9.9

There might be some character positions in the file that do not correspond to characters written; this is because on some processors a record marker could be written to the file as a carriage-return/line-feed or other sequence. The means of determining the position in a file **connected** for stream access is via the **POS= specifier** in an **INQUIRE statement** (9.10.2.22).

9.3.4 File position

9.3.4.1 General

- 1 Execution of certain input/output statements affects the position of an [external file](#). Certain circumstances can cause the position of a file to become indeterminate.
- 2 The initial point of a file is the position just before the first record or [file storage unit](#). The terminal point is the position just after the last record or [file storage unit](#). If there are no records or [file storage units](#) in the file, the initial point and the terminal point are the same position.
- 3 If a [record file](#) is positioned within a record, that record is the current record; otherwise, there is no current record.
- 4 Let n be the number of records in the file. If $1 < i \leq n$ and a file is positioned within the i th record or between the $(i - 1)$ th record and the i th record, the $(i - 1)$ th record is the preceding record. If $n \geq 1$ and the file is positioned at its terminal point, the preceding record is the n th and last record. If $n = 0$ or if a file is positioned at its initial point or within the first record, there is no preceding record.
- 5 If $1 \leq i < n$ and a file is positioned within the i th record or between the i th and $(i + 1)$ th record, the $(i + 1)$ th record is the next record. If $n \geq 1$ and the file is positioned at its initial point, the first record is the next record. If $n = 0$ or if a file is positioned at its terminal point or within the n th (last) record, there is no next record.
- 6 For a file [connected](#) for stream access, the file position is either between two [file storage units](#), at the initial point of the file, at the terminal point of the file, or undefined.

9.3.4.2 Advancing and nonadvancing input/output

- 1 An advancing input/output statement always positions a [record file](#) after the last record read or written, unless there is an error condition.
- 2 A nonadvancing input/output statement may position a [record file](#) at a character position within the current record, or a subsequent record ([10.8.2](#)). Using nonadvancing input/output, it is possible to read or write a record of the file by a sequence of [data transfer statements](#), each accessing a portion of the record. It is also possible to read variable-length records and be notified of their lengths. If a nonadvancing [output statement](#) leaves a file positioned within a current record and no further [output statement](#) is executed for the file before it is closed or a [BACKSPACE](#), [ENDFILE](#), or [REWIND](#) statement is executed for it, the effect is as if the [output statement](#) were the corresponding advancing [output statement](#).

9.3.4.3 File position prior to data transfer

- 1 The positioning of the file prior to data transfer depends on the method of access: sequential, direct, or stream.
- 2 For sequential access on input, if there is a current record, the file position is not changed. Otherwise, the file is positioned at the beginning of the next record and this record becomes the current record. Input shall not occur if there is no next record or if there is a current record and the last [data transfer statement](#) accessing the file performed output.
- 3 If the file contains an endfile record, the file shall not be positioned after the endfile record prior to data transfer. However, a [REWIND](#) or [BACKSPACE](#) statement may be used to reposition the file.
- 4 For sequential access on output, if there is a current record, the file position is not changed and the current record becomes the last record of the file. Otherwise, a new record is created as the next record of the file; this new record becomes the last and current record of the file and the file is positioned at the beginning of this record.
- 5 For direct access, the file is positioned at the beginning of the record specified by the [REC= specifier](#). This record becomes the current record.
- 6 For stream access, the file is positioned immediately before the [file storage unit](#) specified by the [POS= specifier](#);

1 if there is no `POS= specifier`, the file position is not changed.

2 7 File positioning for child `data transfer statements` is described in 9.6.4.8.

3 **9.3.4.4 File position after data transfer**

4 1 If an error condition (9.11) occurred, the position of the file is indeterminate. If no error condition occurred, but
5 an end-of-file condition (9.11) occurred as a result of reading an endfile record, the file is positioned after the
6 endfile record.

7 2 For unformatted stream input/output, if no error condition occurred, the file position is not changed. For
8 unformatted stream output, if the file position exceeds the previous terminal point of the file, the terminal point
9 is set to the file position.

NOTE 9.10

An unformatted stream `output statement` with a `POS= specifier` and an empty output list can have the effect of extending the terminal point of a file without actually writing any data.

10 3 For formatted stream input, if an end-of-file condition occurred, the file position is not changed.

11 4 For nonadvancing input, if no error condition or end-of-file condition occurred, but an end-of-record condition
12 (9.11) occurred, the file is positioned after the record just read. If no error condition, end-of-file condition, or
13 end-of-record condition occurred in a nonadvancing `input statement`, the file position is not changed. If no error
14 condition occurred in a nonadvancing `output statement`, the file position is not changed.

15 5 In all other cases, the file is positioned after the record just read or written and that record becomes the preceding
16 record.

17 6 For a formatted stream `output statement`, if no error condition occurred, the terminal point of the file is set to
18 the next position after the highest-numbered position to which a datum was transferred by the statement.

NOTE 9.11

The highest-numbered position might not be the current one if the output involved a T, TL, TR, or X edit descriptor (10.8.1) and the statement is a nonadvancing `output statement`.

19 **9.3.5 File storage units**

20 1 A `file storage unit` is the basic unit of storage in a `stream file` or an unformatted `record file`. It is the unit of file
21 position for stream access, the unit of record length for unformatted files, and the unit of file size for all `external`
22 `files`.

23 2 Every value in a `stream file` or an unformatted `record file` shall occupy an integer number of `file storage units`; if
24 the `stream` or `record` file is unformatted, this number shall be the same for all scalar values of the same type and
25 type parameters. The number of `file storage units` required for an item of a given type and type parameters may
26 be determined using the `IOLength= specifier` of the `INQUIRE statement` (9.10.3).

27 3 For a file `connected` for unformatted stream access, the processor shall not have alignment restrictions that prevent
28 a value of any type from being stored at any positive integer file position.

29 4 The number of bits in a `file storage unit` is given by the constant `FILE_STORAGE_SIZE` (13.9.2.10) defined in
30 the intrinsic module `ISO_FORTRAN_ENV`. It is recommended that the `file storage unit` be an 8-bit octet where
31 this choice is practical.

NOTE 9.12

The requirement that every data value occupy an integer number of `file storage units` implies that data items inherently smaller than a `file storage unit` will require padding. This suggests that the `file storage unit` be small to avoid wasted space. Ideally, the file storage unit would be chosen such that padding is

- 1 C902 (R903) The *char-variable* shall be default character, [ASCII character](#), or [ISO 10646 character](#).
- 2 2 A [unit](#) is either an [external unit](#) or an [internal unit](#). An [external unit](#) is used to refer to an [external file](#)
 3 and is specified by an asterisk or a *file-unit-number*. The value of *file-unit-number* shall be nonnegative, equal
 4 to one of the [named constants](#) `INPUT_UNIT`, `OUTPUT_UNIT`, or `ERROR_UNIT` of the intrinsic module
 5 `ISO_FORTRAN_ENV` (13.9.2), the `unit` argument of an active [defined input/output](#) procedure (9.6.4.8), or a
 6 `NEWUNIT` value (9.5.6.12). An [internal unit](#) is used to refer to an [internal file](#) and is specified by an *internal-*
 7 *file-variable* or a *file-unit-number* whose value is equal to the `unit` argument of an active [defined input/output](#)
 8 procedure. The value of a *file-unit-number* shall identify a valid [unit](#).
- 9 3 The [external unit](#) identified by a particular value of a *scalar-int-expr* is the same [external unit](#) in all [program](#)
 10 [units](#) of the program.

NOTE 9.13

In the example:

```
SUBROUTINE A
  READ (6) X
  ...
SUBROUTINE B
  N = 6
  REWIND N
```

the value 6 used in both [program units](#) identifies the same [external unit](#).

- 11 4 In a [READ statement](#), an *io-unit* that is an asterisk identifies an [external unit](#) that is [preconnected](#) for sequential
 12 formatted input on [image 1](#) only (9.6.4.3). This [unit](#) is also identified by the value of the [named constant](#)
 13 `INPUT_UNIT` of the intrinsic module `ISO_FORTRAN_ENV` (13.9.2.11). In a [WRITE statement](#), an *io-unit*
 14 that is an asterisk identifies an [external unit](#) that is [preconnected](#) for sequential formatted output. This [unit](#) is also
 15 identified by the value of the [named constant](#) `OUTPUT_UNIT` of the intrinsic module `ISO_FORTRAN_ENV`
 16 (13.9.2.20).
- 17 5 This part of ISO/IEC 1539 identifies a processor-dependent [external unit](#) for the purpose of error reporting. This
 18 [unit](#) shall be [preconnected](#) for sequential formatted output. The processor may define this to be the same as the
 19 output [unit](#) identified by an asterisk. This [unit](#) is also identified by a unit number defined by the [named constant](#)
 20 `ERROR_UNIT` of the intrinsic module `ISO_FORTRAN_ENV`.

NOTE 9.14

Even though `OUTPUT_UNIT` is connected to a separate file on each [image](#), it is expected that the processor could merge the sequences of records from these files into a single sequence of records that is sent to the physical device associated with this [unit](#), such as the user's terminal. If `ERROR_UNIT` is associated with the same physical device, the sequences of records from files connected to `ERROR_UNIT` on each of the [images](#) could be merged into the same sequence generated from the `OUTPUT_UNIT` files. Otherwise, it is expected that the sequence of records in the files connected to `ERROR_UNIT` on each [image](#) could be merged into a single sequence of records that is sent to the physical device associated with `ERROR_UNIT`.

21 9.5.2 Connection modes

- 22 1 A connection for formatted input/output has several changeable modes: these are the blank interpretation mode
 23 (10.8.6), delimiter mode (10.10.4, 10.11.4.2), sign mode (10.8.4), decimal edit mode (10.8.8), input/output round-
 24 ing mode (10.7.2.3.8), pad mode (9.6.4.5.3), and scale factor (10.8.5). A connection for unformatted input/output
 25 has no changeable modes.
- 26 2 Values for the modes of a connection are established when the connection is initiated. If the connection is initiated
 27 by an [OPEN statement](#), the values are as specified, either explicitly or implicitly, by the [OPEN statement](#). If the
 28 connection is initiated other than by an [OPEN statement](#) (that is, if the file is an [internal file](#) or [preconnected file](#))

1 the values established are those that would be implied by an initial **OPEN statement** without the corresponding
2 keywords.

3 3 The scale factor cannot be explicitly specified in an **OPEN statement**; it is implicitly 0.

4 4 The modes of a connection to an **external file** may be changed by a subsequent **OPEN statement** that modifies
5 the connection.

6 5 The modes of a connection may be temporarily changed by a corresponding keyword specifier in a **data transfer**
7 **statement** or by an edit descriptor. Keyword specifiers take effect at the beginning of execution of the **data**
8 **transfer statement**. Edit descriptors take effect when they are encountered in format processing. When a **data**
9 **transfer statement** terminates, the values for the modes are reset to the values in effect immediately before the
10 **data transfer statement** was executed.

11 9.5.3 Unit existence

12 1 At any given time, there is a processor-dependent set of **external units** that exist for an **image**.

13 2 All input/output statements are permitted to refer to **units** that exist. The **CLOSE**, **INQUIRE**, and **WAIT**
14 statements are also permitted to refer to **units** that do not exist. No other input/output statement shall refer to
15 a **unit** that does not exist.

16 9.5.4 Connection of a file to a unit

17 1 An **external unit** has a property of being **connected** or not connected. If **connected**, it refers to an **external file**. An
18 **external unit** may become **connected** by **preconnection** or by the execution of an **OPEN statement**. The property
19 of connection is symmetric; the unit is **connected** to a file if and only if the file is **connected** to the **unit**.

20 2 Every input/output statement except an **OPEN**, **CLOSE**, **INQUIRE**, or **WAIT** statement shall refer to a **unit**
21 that is **connected** to a file and thereby make use of or affect that file.

22 3 A file may be **connected** and not exist (9.3.2).

NOTE 9.15

An example is a **preconnected external file** that has not yet been written.

23 4 A **unit** shall not be **connected** to more than one file at the same time. However, means are provided to change
24 the status of an **external unit** and to connect a **unit** to a different file. It is processor dependent whether a file
25 can be **connected** to more than one **unit** at the same time.

26 5 This part of ISO/IEC 1539 defines means of portable interoperation with C. C streams are described in 7.21.2 of
27 ISO/IEC 9899:2011. Whether a **unit** can be **connected** to a file that is also **connected** to a C stream is processor
28 dependent. If a **unit** is **connected** to a file that is also **connected** to a C stream, the results of performing
29 input/output operations on such a file are processor dependent. It is processor dependent whether the files
30 **connected** to the **units** **INPUT_UNIT**, **OUTPUT_UNIT**, and **ERROR_UNIT** correspond to the predefined C
31 text streams standard input, standard output, and standard error. If a main program or procedure defined by
32 means of Fortran and a main program or procedure defined by means other than Fortran perform input/output
33 operations on the same **external file**, the results are processor dependent. A main program or procedure defined by
34 means of Fortran and a main program or procedure defined by means other than Fortran can perform input/output
35 operations on different **external files** without interference.

36 6 After an **external unit** has been disconnected by the execution of a **CLOSE statement**, it may be **connected** again
37 within the same program to the same file or to a different file. After an **external file** has been disconnected by
38 the execution of a **CLOSE statement**, it may be **connected** again within the same program to the same **unit** or
39 to a different **unit**.

NOTE 9.16

The only means of referencing a file that has been disconnected is by the appearance of its name in an **OPEN** or **INQUIRE** statement. There might be no means of reconnecting an unnamed file once it is disconnected.

1 7 An **internal unit** is always **connected** to the **internal file** designated by the variable that identifies the **unit**.

NOTE 9.17

For more explanatory information on file connection properties, see **C.6.4**.

2 **9.5.5 Preconnection**

3 1 Preconnection means that the **unit** is **connected** to a file at the beginning of execution of the program and therefore
4 it may be specified in input/output statements without the prior execution of an **OPEN statement**.

5 **9.5.6 OPEN statement**

6 **9.5.6.1 General**

7 1 An **OPEN statement** initiates or modifies the connection between an **external file** and a specified **unit**. The **OPEN**
8 statement may be used to connect an existing file to a **unit**, create a file that is **preconnected**, create a file and
9 connect it to a **unit**, or change certain modes of a connection between a file and a **unit**.

10 2 An **external unit** may be **connected** by an **OPEN statement** in the main program or any subprogram.

11 3 If the file to be **connected** to the **unit** does not exist but is the same as the file to which the **unit** is **preconnected**,
12 the modes specified by an **OPEN statement** become a part of the connection.

13 4 If the file to be **connected** to the **unit** is not the same as the file to which the **unit** is **connected**, the effect is as
14 if a **CLOSE statement** without a **STATUS= specifier** had been executed for the **unit** immediately prior to the
15 execution of an **OPEN statement**.

16 5 If a **unit** is **connected** to a file that exists, execution of an **OPEN statement** for that **unit** is permitted. If the
17 **FILE= specifier** is not included in such an **OPEN statement**, the file to be **connected** to the **unit** is the same as
18 the file to which the **unit** is already **connected**.

19 6 If the file to be **connected** to the **unit** is the same as the file to which the **unit** is **connected**, a new connection is not
20 established and values for any changeable modes (**9.5.2**) specified come into effect for the established connection;
21 the current file position is unaffected. Before any effect on changeable modes, a wait operation is performed for
22 any pending asynchronous data transfer operations for the specified **unit**. If the **POSITION= specifier** appears
23 in such an **OPEN statement**, the value specified shall not disagree with the current position of the file. If the
24 **STATUS= specifier** is included in such an **OPEN statement**, it shall be specified with the value **OLD**. Other than
25 **ERR=**, **IOSTAT=**, and **IOMSG=**, and the changeable modes, the values of all other specifiers in such an **OPEN**
26 statement shall not differ from those in effect for the established connection.

27 7 A **STATUS= specifier** with a value of **OLD** is always allowed when the file to be **connected** to the **unit** is the same
28 as the file to which the **unit** is **connected**. In this case, if the status of the file was **SCRATCH** before execution of
29 the **OPEN statement**, the file will still be deleted when the **unit** is closed, and the file is still considered to have
30 a status of **SCRATCH**.

31 8 If a file is already **connected** to a **unit**, an **OPEN statement** for that file with a different **unit** shall not be executed.

32 **9.5.6.2 Syntax**

33 R904 *open-stmt* is OPEN (*connect-spec-list*)

34 R905 *connect-spec* is [UNIT =] *file-unit-number*
35 or ACCESS = *scalar-default-char-expr*

- 1 or ACTION = *scalar-default-char-expr*
 2 or ASYNCHRONOUS = *scalar-default-char-expr*
 3 or BLANK = *scalar-default-char-expr*
 4 or DECIMAL = *scalar-default-char-expr*
 5 or DELIM = *scalar-default-char-expr*
 6 or ENCODING = *scalar-default-char-expr*
 7 or ERR = *label*
 8 or FILE = *file-name-expr*
 9 or FORM = *scalar-default-char-expr*
 10 or IOMSG = *iomsg-variable*
 11 or IOSTAT = *scalar-int-variable*
 12 or NEWUNIT = *scalar-int-variable*
 13 or PAD = *scalar-default-char-expr*
 14 or POSITION = *scalar-default-char-expr*
 15 or RECL = *scalar-int-expr*
 16 or ROUND = *scalar-default-char-expr*
 17 or SIGN = *scalar-default-char-expr*
 18 or STATUS = *scalar-default-char-expr*
- 19 R906 *file-name-expr* is *scalar-default-char-expr*
- 20 R907 *iomsg-variable* is *scalar-default-char-variable*
- 21 C903 No specifier shall appear more than once in a given *connect-spec-list*.
- 22 C904 (R904) If the **NEWUNIT= specifier** does not appear, a *file-unit-number* shall be specified; if the optional
 23 characters UNIT= are omitted, the *file-unit-number* shall be the first item in the *connect-spec-list*.
- 24 C905 (R904) If a **NEWUNIT= specifier** appears, a *file-unit-number* shall not appear.
- 25 C906 (R904) The *label* used in the **ERR= specifier** shall be the statement label of a **branch target statement**
 26 that appears in the same **inclusive scope** as the OPEN statement.
- 27 1 If the **STATUS= specifier** has the value NEW or REPLACE, the **FILE= specifier** shall appear. If the **STATUS=**
 28 **specifier** has the value SCRATCH, the **FILE= specifier** shall not appear. If the **STATUS= specifier** has the value
 29 OLD, the **FILE= specifier** shall appear unless the **unit** is **connected** and the file **connected** to the **unit** exists.
- 30 2 If the **NEWUNIT= specifier** appears in an OPEN statement, either the **FILE= specifier** shall appear, or the
 31 **STATUS= specifier** shall appear with a value of SCRATCH. The **unit** identified by a NEWUNIT value shall not
 32 be **preconnected**.
- 33 3 A specifier that requires a *scalar-default-char-expr* may have a limited list of character values. These values are
 34 listed for each such specifier. Any trailing blanks are ignored. The value specified is without regard to case. Some
 35 specifiers have a default value if the specifier is omitted.
- 36 4 The **IOSTAT=**, **ERR=**, and **IOMSG=** specifiers are described in 9.11.

NOTE 9.18

An example of an OPEN statement is:

```
OPEN (10, FILE = 'employee.names', ACTION = 'READ', PAD = 'YES')
```

NOTE 9.19

For more explanatory information on the OPEN statement, see C.6.3.

1 9.5.6.3 ACCESS= specifier in the OPEN statement

2 1 The *scalar-default-char-expr* shall evaluate to SEQUENTIAL, DIRECT, or STREAM. The ACCESS= specifier
3 specifies the access method for the connection of the file as being sequential, direct, or stream. If this specifier is
4 omitted, the default value is SEQUENTIAL. For an existing file, the specified access method shall be included in
5 the set of allowed access methods for the file. For a new file, the processor creates the file with a set of allowed
6 access methods that includes the specified method.

7 9.5.6.4 ACTION= specifier in the OPEN statement

8 1 The *scalar-default-char-expr* shall evaluate to READ, WRITE, or READWRITE. READ specifies that the
9 WRITE, PRINT, and ENDFILE statements shall not refer to this connection. WRITE specifies that READ
10 statements shall not refer to this connection. READWRITE permits any input/output statements to refer to this
11 connection. If this specifier is omitted, the default value is processor dependent. If READWRITE is included in
12 the set of allowable actions for a file, both READ and WRITE also shall be included in the set of allowed actions
13 for that file. For an existing file, the specified action shall be included in the set of allowed actions for the file.
14 For a new file, the processor creates the file with a set of allowed actions that includes the specified action.

15 9.5.6.5 ASYNCHRONOUS= specifier in the OPEN statement

16 1 The *scalar-default-char-expr* shall evaluate to YES or NO. If YES is specified, asynchronous input/output on
17 the *unit* is allowed. If NO is specified, asynchronous input/output on the *unit* is not allowed. If this specifier is
18 omitted, the default value is NO.

19 9.5.6.6 BLANK= specifier in the OPEN statement

20 1 The *scalar-default-char-expr* shall evaluate to NULL or ZERO. The BLANK= specifier is permitted only for a
21 connection for formatted input/output. It specifies the blank interpretation mode (10.8.6, 9.6.2.6) for input for
22 this connection. This mode has no effect on output. It is a changeable mode (9.5.2). If this specifier is omitted
23 in an OPEN statement that initiates a connection, the default value is NULL.

24 9.5.6.7 DECIMAL= specifier in the OPEN statement

25 1 The *scalar-default-char-expr* shall evaluate to COMMA or POINT. The DECIMAL= specifier is permitted only
26 for a connection for formatted input/output. It specifies the decimal edit mode (10.6, 10.8.8, 9.6.2.7) for this
27 connection. This is a changeable mode (9.5.2). If this specifier is omitted in an OPEN statement that initiates a
28 connection, the default value is POINT.

29 9.5.6.8 DELIM= specifier in the OPEN statement

30 1 The *scalar-default-char-expr* shall evaluate to APOSTROPHE, QUOTE, or NONE. The DELIM= specifier is
31 permitted only for a connection for formatted input/output. It specifies the delimiter mode (9.6.2.8) for list-
32 directed (10.10.4) and namelist (10.11.4.2) output for the connection. This mode has no effect on input. It is
33 a changeable mode (9.5.2). If this specifier is omitted in an OPEN statement that initiates a connection, the
34 default value is NONE.

35 9.5.6.9 ENCODING= specifier in the OPEN statement

36 1 The *scalar-default-char-expr* shall evaluate to UTF-8 or DEFAULT. The ENCODING= specifier is permitted
37 only for a connection for formatted input/output. The value UTF-8 specifies that the encoding form of the file
38 is UTF-8 as specified in ISO/IEC 10646. Such a file is called a Unicode file, and all characters therein are of ISO
39 10646 character kind. The value UTF-8 shall not be specified if the processor does not support the ISO 10646
40 character kind. The value DEFAULT specifies that the encoding form of the file is processor dependent. If this
41 specifier is omitted in an OPEN statement that initiates a connection, the default value is DEFAULT.

1 9.5.6.10 FILE= specifier in the OPEN statement

2 1 The value of the FILE= specifier is the name of the file to be [connected](#) to the specified [unit](#). Any trailing blanks
3 are ignored. The *file-name-expr* shall be a name that is allowed by the processor. If this specifier is omitted and
4 the [unit](#) is not connected to a file, the STATUS= specifier shall be specified with a value of SCRATCH; in this
5 case, the connection is made to a processor-dependent file. The interpretation of case is processor dependent.

6 9.5.6.11 FORM= specifier in the OPEN statement

7 1 The *scalar-default-char-expr* shall evaluate to FORMATTED or UNFORMATTED. The FORM= specifier de-
8 termines whether the file is being connected for formatted or unformatted input/output. If this specifier is
9 omitted, the default value is UNFORMATTED if the file is being connected for direct access or stream access,
10 and the default value is FORMATTED if the file is being connected for sequential access. For an existing file,
11 the specified form shall be included in the set of allowed forms for the file. For a new file, the processor creates
12 the file with a set of allowed forms that includes the specified form.

13 9.5.6.12 NEWUNIT= specifier in the OPEN statement

14 1 The variable is defined with a processor determined NEWUNIT value if no error occurs during the execution of
15 the OPEN statement. If an error occurs, the processor shall not change the value of the variable.

16 2 A NEWUNIT value is a negative number, and shall not be equal to -1 , any of the [named constants](#) [ERROR_](#)
17 [UNIT](#), [INPUT_UNIT](#), or [OUTPUT_UNIT](#) from the intrinsic module [ISO_FORTRAN_ENV \(13.9.2\)](#), any value
18 used by the processor for the [unit](#) argument to a [defined input/output](#) procedure, nor any previous NEWUNIT
19 value that identifies a file that is [connected](#).

20 9.5.6.13 PAD= specifier in the OPEN statement

21 1 The *scalar-default-char-expr* shall evaluate to YES or NO. The PAD= specifier is permitted only for a connection
22 for formatted input/output. It specifies the pad mode ([9.6.4.5.3](#), [9.6.2.10](#)) for input for this connection. This
23 mode has no effect on output. It is a changeable mode ([9.5.2](#)). If this specifier is omitted in an OPEN statement
24 that initiates a connection, the default value is YES.

25 9.5.6.14 POSITION= specifier in the OPEN statement

26 1 The *scalar-default-char-expr* shall evaluate to ASIS, REWIND, or APPEND. The connection shall be for sequen-
27 tial or stream access. A new file is positioned at its initial point. REWIND positions an existing file at its initial
28 point. APPEND positions an existing file such that the endfile record is the next record, if it has one. If an
29 existing file does not have an endfile record, APPEND positions the file at its terminal point. ASIS leaves the
30 position unchanged if the file exists and already is [connected](#). If the file exists but is not connected, the position
31 resulting from ASIS is processor dependent. If this specifier is omitted, the default value is ASIS.

32 9.5.6.15 RECL= specifier in the OPEN statement

33 1 The value of the RECL= specifier shall be positive. It specifies the length of each record in a file being connected
34 for direct access, or specifies the maximum length of a record in a file being connected for sequential access. This
35 specifier shall not appear when a file is being connected for stream access. This specifier shall appear when a
36 file is being connected for direct access. If this specifier is omitted when a file is being connected for sequential
37 access, the default value is processor dependent. If the file is being connected for formatted input/output, the
38 length is the number of characters for all records that contain only characters of default kind. When a record
39 contains any nondefault characters, the effect of the RECL= specifier is processor dependent. If the file is being
40 connected for unformatted input/output, the length is measured in [file storage units](#). For an existing file, the
41 value of the RECL= specifier shall be included in the set of allowed record lengths for the file. For a new file, the
42 processor creates the file with a set of allowed record lengths that includes the specified value.

1 9.5.6.16 ROUND= specifier in the OPEN statement

- 2 1 The *scalar-default-char-expr* shall evaluate to one of UP, DOWN, ZERO, NEAREST, COMPATIBLE, or PRO-
3 CESSOR_DEFINED. The ROUND= specifier is permitted only for a connection for formatted input/output. It
4 specifies the input/output rounding mode (10.7.2.3.8, 9.6.2.13) for this connection. This is a changeable mode
5 (9.5.2). If this specifier is omitted in an OPEN statement that initiates a connection, the input/output rounding
6 mode is processor dependent; it shall be one of the above modes.

NOTE 9.20

A processor is free to select any input/output rounding mode for the default mode. The mode might correspond to UP, DOWN, ZERO, NEAREST, or COMPATIBLE; or it might be a completely different input/output rounding mode.

7 9.5.6.17 SIGN= specifier in the OPEN statement

- 8 1 The *scalar-default-char-expr* shall evaluate to one of PLUS, SUPPRESS, or PROCESSOR_DEFINED. The
9 SIGN= specifier is permitted only for a connection for formatted input/output. It specifies the sign mode
10 (10.8.4, 9.6.2.14) for this connection. This is a changeable mode (9.5.2). If this specifier is omitted in an OPEN
11 statement that initiates a connection, the default value is PROCESSOR_DEFINED.

12 9.5.6.18 STATUS= specifier in the OPEN statement

- 13 1 The *scalar-default-char-expr* shall evaluate to OLD, NEW, SCRATCH, REPLACE, or UNKNOWN. If OLD is
14 specified, the file shall exist. If NEW is specified, the file shall not exist.
- 15 2 Successful execution of an OPEN statement with NEW specified creates the file and changes the status to OLD.
16 If REPLACE is specified and the file does not already exist, the file is created and the status is changed to OLD.
17 If REPLACE is specified and the file does exist, the file is deleted, a new file is created with the same name, and
18 the status is changed to OLD. If SCRATCH is specified, the file is created and connected to the specified [unit](#)
19 for use by the program but is deleted at the execution of a [CLOSE statement](#) referring to the same [unit](#) or at
20 the [normal termination](#) of the program.

NOTE 9.21

SCRATCH shall not be specified with a named file.

- 21 3 If UNKNOWN is specified, the status is processor dependent. If this specifier is omitted, the default value is
22 UNKNOWN.

23 9.5.7 CLOSE statement

24 9.5.7.1 General

- 25 1 The CLOSE statement is used to terminate the connection of a specified [unit](#) to an [external file](#).
- 26 2 Execution of a CLOSE statement for a [unit](#) may occur in any [program unit](#) of a program and need not occur in
27 the same [program unit](#) as the execution of an [OPEN statement](#) referring to that [unit](#).
- 28 3 Execution of a CLOSE statement performs a wait operation for any pending asynchronous data transfer operations
29 for the specified [unit](#).
- 30 4 Execution of a CLOSE statement specifying a [unit](#) that does not exist, exists but is connected to a file that does
31 not exist, or has no file [connected](#) to it, is permitted and affects no file or [unit](#).
- 32 5 After a [unit](#) has been disconnected by execution of a CLOSE statement, it may be [connected](#) again within the
33 same program, either to the same file or to a different file. After a named file has been disconnected by execution
34 of a CLOSE statement, it may be [connected](#) again within the same program, either to the same [unit](#) or to a
35 different [unit](#), provided that the file still exists.

- 1 6 During the completion step (2.3.6) of normal termination, all units that are connected are closed. Each unit is
 2 closed with status KEEP unless the file status prior to termination of execution was SCRATCH, in which case
 3 the unit is closed with status DELETE.

NOTE 9.22

The effect is as though a CLOSE statement without a STATUS= specifier were executed on each connected unit.

4 **9.5.7.2 Syntax**

- 5 R908 *close-stmt* is CLOSE (*close-spec-list*)
- 6 R909 *close-spec* is [UNIT =] *file-unit-number*
 7 or IOSTAT = *scalar-int-variable*
 8 or IOMSG = *iomsg-variable*
 9 or ERR = *label*
 10 or STATUS = *scalar-default-char-expr*
- 11 C907 No specifier shall appear more than once in a given *close-spec-list*.
- 12 C908 A *file-unit-number* shall be specified in a *close-spec-list*; if the optional characters UNIT= are omitted,
 13 the *file-unit-number* shall be the first item in the *close-spec-list*.
- 14 C909 (R909) The *label* used in the ERR= specifier shall be the statement label of a branch target statement
 15 that appears in the same inclusive scope as the CLOSE statement.
- 16 1 The *scalar-default-char-expr* has a limited list of character values. Any trailing blanks are ignored. The value
 17 specified is without regard to case.
- 18 2 The IOSTAT=, ERR=, and IOMSG= specifiers are described in 9.11.

NOTE 9.23

An example of a CLOSE statement is:

```
CLOSE (10, STATUS = 'KEEP')
```

19 **9.5.7.3 STATUS= specifier in the CLOSE statement**

- 20 1 The *scalar-default-char-expr* shall evaluate to KEEP or DELETE. The STATUS= specifier determines the dis-
 21 position of the file that is connected to the specified unit. KEEP shall not be specified for a file whose status prior
 22 to execution of a CLOSE statement is SCRATCH. If KEEP is specified for a file that exists, the file continues
 23 to exist after the execution of a CLOSE statement. If KEEP is specified for a file that does not exist, the file
 24 will not exist after the execution of a CLOSE statement. If DELETE is specified, the file will not exist after the
 25 execution of a CLOSE statement. If this specifier is omitted, the default value is KEEP, unless the file status
 26 prior to execution of the CLOSE statement is SCRATCH, in which case the default value is DELETE.

27 **9.6 Data transfer statements**28 **9.6.1 Form of input and output statements**

- 29 1 The READ statement is the data transfer input statement. The WRITE statement and the PRINT statement
 30 are the data transfer output statements.

31 R910 *read-stmt* is READ (*io-control-spec-list*) [*input-item-list*]
 32 or READ *format* [, *input-item-list*]

33 R911 *write-stmt* is WRITE (*io-control-spec-list*) [*output-item-list*]

1 R912 *print-stmt* is PRINT *format* [, *output-item-list*]

NOTE 9.24

Examples of data transfer statements are:

```

READ (6, *) SIZE
READ 10, A, B
WRITE (6, 10) A, S, J
PRINT 10, A, S, J
10 FORMAT (2E16.3, I5)

```

2 9.6.2 Control information list

3 9.6.2.1 Syntax

4 1 A control information list is an *io-control-spec-list*. It governs data transfer.

5 R913 *io-control-spec* is [UNIT =] *io-unit*
6 or [FMT =] *format*
7 or [NML =] *namelist-group-name*
8 or ADVANCE = *scalar-default-char-expr*
9 or ASYNCHRONOUS = *scalar-default-char-constant-expr*
10 or BLANK = *scalar-default-char-expr*
11 or DECIMAL = *scalar-default-char-expr*
12 or DELIM = *scalar-default-char-expr*
13 or END = *label*
14 or EOR = *label*
15 or ERR = *label*
16 or ID = *id-variable*
17 or IOMSG = *iomsg-variable*
18 or IOSTAT = *scalar-int-variable*
19 or PAD = *scalar-default-char-expr*
20 or POS = *scalar-int-expr*
21 or REC = *scalar-int-expr*
22 or ROUND = *scalar-default-char-expr*
23 or SIGN = *scalar-default-char-expr*
24 or SIZE = *scalar-int-variable*

25 R914 *id-variable* is *scalar-int-variable*

26 C910 No specifier shall appear more than once in a given *io-control-spec-list*.

27 C911 An *io-unit* shall be specified in an *io-control-spec-list*; if the optional characters UNIT= are omitted, the
28 *io-unit* shall be the first item in the *io-control-spec-list*.

29 C912 (R913) A DELIM= or SIGN= specifier shall not appear in a *read-stmt*.

30 C913 (R913) A BLANK=, PAD=, END=, EOR=, or SIZE= specifier shall not appear in a *write-stmt*.

31 C914 (R913) The *label* in the ERR=, EOR=, or END= specifier shall be the statement label of a *branch target*
32 *statement* that appears in the same *inclusive scope* as the data transfer statement.

33 C915 (R913) A *namelist-group-name* shall be the name of a namelist group.

34 C916 (R913) A *namelist-group-name* shall not appear if a REC= specifier, *format*, *input-item-list*, or an *output-*
35 *item-list* appears in the data transfer statement.

36 C917 (R913) If *format* appears without a preceding FMT=, it shall be the second item in the *io-control-spec-list*

- 1 and the first item shall be *io-unit*.
- 2 C918 (R913) If *namelist-group-name* appears without a preceding NML=, it shall be the second item in the
3 *io-control-spec-list* and the first item shall be *io-unit*.
- 4 C919 (R913) If *io-unit* is not a *file-unit-number*, the *io-control-spec-list* shall not contain a REC= specifier or
5 a POS= specifier.
- 6 C920 (R913) If the REC= specifier appears, an END= specifier shall not appear, and the *format*, if any, shall
7 not be an asterisk.
- 8 C921 (R913) An ADVANCE= specifier may appear only in a formatted sequential or stream data transfer
9 statement with explicit format specification (10.2) whose *io-control-spec-list* does not contain an *internal-*
10 *file-variable* as the *io-unit*.
- 11 C922 (R913) If an EOR= specifier appears, an ADVANCE= specifier also shall appear.
- 12 C923 (R913) The *scalar-default-char-constant-expr* in an ASYNCHRONOUS= specifier shall have the value
13 YES or NO.
- 14 C924 (R913) An ASYNCHRONOUS= specifier with a value YES shall not appear unless *io-unit* is a *file-unit-*
15 *number*.
- 16 C925 (R913) If an ID= specifier appears, an ASYNCHRONOUS= specifier with the value YES shall also
17 appear.
- 18 C926 (R913) If a POS= specifier appears, the *io-control-spec-list* shall not contain a REC= specifier.
- 19 C927 (R913) If a DECIMAL=, BLANK=, PAD=, SIGN=, or ROUND= specifier appears, a *format* or
20 *namelist-group-name* shall also appear.
- 21 C928 (R913) If a DELIM= specifier appears, either *format* shall be an asterisk or *namelist-group-name* shall
22 appear.
- 23 C929 (R914) The *scalar-int-variable* shall have a decimal exponent range no smaller than that of default integer.
- 24 2 If an EOR= specifier appears, an ADVANCE= specifier with the value NO shall also appear.
- 25 3 If the data transfer statement contains a *format* or *namelist-group-name*, the statement is a formatted in-
26 put/output statement; otherwise, it is an unformatted input/output statement.
- 27 4 The ADVANCE=, ASYNCHRONOUS=, DECIMAL=, BLANK=, DELIM=, PAD=, SIGN=, and ROUND=
28 specifiers have a limited list of character values. Any trailing blanks are ignored. The values specified are without
29 regard to case.
- 30 5 The IOSTAT=, ERR=, EOR=, END=, and IOMSG= specifiers are described in 9.11.

NOTE 9.25

An example of a READ statement is:

```
READ (IOSTAT = IOS, UNIT = 6, FMT = '(10F8.2)') A, B
```

9.6.2.2 Format specification in a data transfer statement

- 32 1 The *format* specifier supplies a format specification or specifies list-directed formatting for a formatted in-
33 put/output statement.
- 34 R915 *format* is *default-char-expr*
35 or *label*

1 4 If a variable is used in an asynchronous data transfer statement as

- 2 • an item in an input/output list,
- 3 • a group object in a namelist, or
- 4 • a SIZE= specifier,

5 the [base object](#) of the [data-ref](#) is implicitly given the [ASYNCHRONOUS](#) attribute in the [scoping unit](#) of the data
6 transfer statement. This attribute may be confirmed by explicit declaration.

7 5 When an asynchronous input/output statement is executed, the set of [storage units](#) specified by the item list or
8 NML= specifier, plus the [storage units](#) specified by the SIZE= specifier, is defined to be the pending input/output
9 storage sequence for the data transfer operation.

NOTE 9.28

A pending input/output storage sequence is not necessarily a [contiguous](#) set of [storage units](#).

10 6 A pending input/output storage sequence affector is a variable of which any part is associated with a [storage unit](#)
11 in a pending input/output storage sequence.

9.6.2.6 BLANK= specifier in a data transfer statement

13 1 The [scalar-default-char-expr](#) shall evaluate to NULL or ZERO. The BLANK= specifier temporarily changes
14 (9.5.2) the blank interpretation mode (10.8.6, 9.5.6.6) for the connection. If the specifier is omitted, the mode is
15 not changed.

9.6.2.7 DECIMAL= specifier in a data transfer statement

17 1 The [scalar-default-char-expr](#) shall evaluate to COMMA or POINT. The DECIMAL= specifier temporarily changes
18 (9.5.2) the decimal edit mode (10.6, 10.8.8, 9.5.6.7) for the connection. If the specifier is omitted, the mode is
19 not changed.

9.6.2.8 DELIM= specifier in a data transfer statement

21 1 The [scalar-default-char-expr](#) shall evaluate to APOSTROPHE, QUOTE, or NONE. The DELIM= specifier tem-
22 porarily changes (9.5.2) the delimiter mode (10.10.4, 10.11.4.2, 9.5.6.8) for the connection. If the specifier is
23 omitted, the mode is not changed.

9.6.2.9 ID= specifier in a data transfer statement

25 1 Successful execution of an asynchronous data transfer statement containing an ID= specifier causes the variable
26 specified in the ID= specifier to become defined with a processor determined value. If this value is zero, the
27 data transfer operation has been completed. A nonzero value is referred to as the identifier of the data transfer
28 operation. This identifier is different from the identifier of any other pending data transfer operation for this [unit](#).
29 It can be used in a subsequent [WAIT](#) or [INQUIRE](#) statement to identify the particular data transfer operation.

30 2 If an error occurs during the execution of a data transfer statement containing an ID= specifier, the variable
31 specified in the ID= specifier becomes undefined.

32 3 A child data transfer statement shall not specify the ID= specifier.

9.6.2.10 PAD= specifier in a data transfer statement

34 1 The [scalar-default-char-expr](#) shall evaluate to YES or NO. The PAD= specifier temporarily changes (9.5.2) the
35 pad mode (9.6.4.5.3, 9.5.6.13) for the connection. If the specifier is omitted, the mode is not changed.

9.6.2.11 POS= specifier in a data transfer statement

- 1 The POS= specifier specifies the file position in [file storage units](#). This specifier may appear in a data transfer statement only if the statement specifies a [unit connected](#) for stream access. A child data transfer statement shall not specify this specifier.
- 2 A processor may prohibit the use of POS= with particular files that do not have the properties necessary to support random positioning. A processor may also prohibit positioning a particular file to any position prior to its current file position if the file does not have the properties necessary to support such positioning.

NOTE 9.29

A [unit](#) that is [connected](#) to a device or data stream might not be positionable.

- 3 If the file is [connected](#) for formatted stream access, the file position specified by POS= shall be equal to either 1 (the beginning of the file) or a value previously returned by a [POS= specifier](#) in an [INQUIRE statement](#) for the file.

9.6.2.12 REC= specifier in a data transfer statement

- 1 The REC= specifier specifies the number of the record that is to be read or written. This specifier may appear only in a data transfer statement that specifies a [unit connected](#) for direct access; it shall not appear in a child data transfer statement. If the [io-control-spec-list](#) contains a REC= specifier, the statement is a direct access data transfer statement. A child data transfer statement is a direct access data transfer statement if the parent is a direct access data transfer statement. Any other data transfer statement is a sequential access data transfer statement or a stream access data transfer statement, depending on whether the file connection is for sequential access or stream access.

9.6.2.13 ROUND= specifier in a data transfer statement

- 1 The [scalar-default-char-expr](#) shall evaluate to UP, DOWN, ZERO, NEAREST, COMPATIBLE or PROCESSOR_ _DEFINED. The ROUND= specifier temporarily changes (9.5.2) the input/output rounding mode (10.7.2.3.8, 9.5.6.16) for the connection. If the specifier is omitted, the mode is not changed.

9.6.2.14 SIGN= specifier in a data transfer statement

- 1 The [scalar-default-char-expr](#) shall evaluate to PLUS, SUPPRESS, or PROCESSOR_ _DEFINED. The SIGN= specifier temporarily changes (9.5.2) the sign mode (10.8.4, 9.5.6.17) for the connection. If the specifier is omitted, the mode is not changed.

9.6.2.15 SIZE= specifier in a data transfer statement

- 1 The SIZE= specifier in an [input statement](#) causes the variable specified to become [defined](#) with the count of the characters transferred from the file by data edit descriptors during the input operation. Blanks inserted as padding are not counted.
- 2 For a synchronous [input statement](#), this definition occurs when execution of the statement completes. For an asynchronous [input statement](#), this definition occurs when the corresponding wait operation is performed.

9.6.3 Data transfer input/output list

- 1 An input/output list specifies the entities whose values are transferred by a data transfer statement.

R916 *input-item* is *variable*
 or *io-implied-do*

R917 *output-item* is *expr*
 or *io-implied-do*

- 1 R918 *io-implied-do* is (*io-implied-do-object-list* , *io-implied-do-control*)
- 2 R919 *io-implied-do-object* is *input-item*
- 3 or *output-item*
- 4 R920 *io-implied-do-control* is *do-variable* = *scalar-int-expr* , ■
- 5 ■ *scalar-int-expr* [, *scalar-int-expr*]
- 6 C931 (R916) A variable that is an *input-item* shall not be a whole *assumed-size* array.
- 7 C932 (R919) In an *input-item-list*, an *io-implied-do-object* shall be an *input-item*. In an *output-item-list*, an
- 8 *io-implied-do-object* shall be an *output-item*.
- 9 C933 (R917) An expression that is an *output-item* shall not have a value that is a procedure pointer.
- 10 2 An *input-item* shall not appear as, nor be associated with, the *do-variable* of any *io-implied-do* that contains the
- 11 *input-item*.

NOTE 9.30

A constant, an expression involving operators or function references that does not have a pointer result, or an expression enclosed in parentheses shall not appear as an input list item.

- 12 3 If an input item is a pointer, it shall be associated with a *definable target* and data are transferred from the file to
- 13 the associated *target*. If an output item is a pointer, it shall be associated with a *target* and data are transferred
- 14 from the *target* to the file.

NOTE 9.31

Data transfers always involve the movement of values between a file and internal storage. A pointer as such cannot be read or written. Therefore, a pointer shall not appear as an item in an input/output list unless it is associated with a *target* that can receive a value (input) or can deliver a value (output).

- 15 4 If an input item or an output item is *allocatable*, it shall be allocated.
- 16 5 A list item shall not be *polymorphic* unless it is processed by a *defined input/output* procedure (9.6.4.8).
- 17 6 The *do-variable* of an *io-implied-do* that is in another *io-implied-do* shall not appear as, nor be associated with,
- 18 the *do-variable* of the containing *io-implied-do*.
- 19 7 The following rules describing whether to expand an input/output list item are re-applied to each expanded list
- 20 item until none of the rules apply.
- 21 • If an array appears as an input/output list item, it is treated as if the elements, if any, were specified in
- 22 array element order (6.5.3.2). However, no element of that array may affect the value of any expression in
- 23 the *input-item*, nor may any element appear more than once in an *input-item*.

NOTE 9.32

For example:

```

INTEGER A (100), J (100)
...
READ *, A (A)                ! Not allowed
READ *, A (LBOUND (A, 1) : UBOUND (A, 1)) ! Allowed
READ *, A (J)                ! Allowed if no two elements
                                !   of J have the same value
A(1) = 1; A(10) = 10
READ *, A (A (1) : A (10))    ! Not allowed

```

- 1 • If a list item of derived type in an unformatted input/output statement is not processed by a [defined input/output](#) procedure (9.6.4.8), and if any subobject of that list item would be processed by a [defined input/output](#) procedure, the list item is treated as if all of the components of the object were specified in the list in [component order](#) (4.5.4.7); those components shall be accessible in the [scoping unit](#) containing the data transfer statement and shall not be pointers or [allocatable](#).
- 2
- 3
- 4
- 5
- 6 • An effective item of derived type in an unformatted input/output statement is treated as a single value in a processor-dependent form unless the list item or a subobject thereof is processed by a [defined input/output](#) procedure (9.6.4.8).
- 7
- 8

NOTE 9.33

The appearance of a derived-type object as an input/output list item in an unformatted input/output statement is not equivalent to the list of its components.

Unformatted input/output involving derived-type list items forms the single exception to the rule that the appearance of an aggregate list item (such as an array) is equivalent to the appearance of its expanded list of component parts. This exception permits the processor greater latitude in improving efficiency or in matching the processor-dependent sequence of values for a derived-type object to similar sequences for aggregate objects used by means other than Fortran. However, formatted input/output of all list items and unformatted input/output of list items other than those of derived types adhere to the above rule.

- 9 • If a list item of derived type in a formatted input/output statement is not processed by a [defined input/output](#) procedure, that list item is treated as if all of the components of the list item were specified in the list in [component order](#); those components shall be accessible in the [scoping unit](#) containing the input/output statement and shall not be pointers or [allocatable](#).
- 10
- 11
- 12
- 13 • If a derived-type list item is not processed by a [defined input/output](#) procedure and is not treated as a list of its individual components, all the subcomponents of that list item shall be accessible in the [scoping unit](#) containing the data transfer statement and shall not be pointers or [allocatable](#).
- 14
- 15
- 16 • For an *io-implied-do*, the loop initialization and execution are the same as for a [DO construct](#) (8.1.6.4).

NOTE 9.34

An example of an output list with an implied DO is:

```
WRITE (LP, FMT = '(10F8.2)') (LOG (A (I)), I = 1, N + 9, K), G
```

- 17 8 The scalar objects resulting when a data transfer statement's list items are expanded according to the rules in this subclause for handling array and derived-type list items are called [effective items](#). Zero-sized arrays and *io-implied-dos* with an iteration count of zero do not contribute to the list of [effective items](#). A scalar character item of zero length is an [effective item](#).
- 18
- 19
- 20

NOTE 9.35

In a formatted input/output statement, edit descriptors are associated with [effective items](#), which are always scalar. The rules in 9.6.3 determine the set of [effective items](#) corresponding to each actual list item in the statement. These rules might have to be applied repetitively until all of the [effective items](#) are scalar items.

- 21 9 An input/output list shall not contain an effective item of nondefault character kind if the data transfer statement specifies an [internal file](#) of default character kind. An input/output list shall not contain an effective item that is nondefault character except for [ISO 10646](#) or [ASCII character](#) if the data transfer statement specifies an [internal file](#) of [ISO 10646 character](#) kind. An input/output list shall not contain an effective item of type character of any kind other than [ASCII](#) if the data transfer statement specifies an [ASCII character internal file](#).
- 22
- 23
- 24
- 25

9.6.4 Execution of a data transfer input/output statement

9.6.4.1 Data transfer sequence of operations

1 Execution of a WRITE or PRINT statement for a file that does not exist creates the file unless an error condition occurs.

2 The effect of executing a synchronous data transfer statement shall be as if the following operations were performed in the order specified.

- (1) Determine the direction of data transfer.
- (2) Identify the **unit**.
- (3) Perform a wait operation for all pending input/output operations for the **unit**. If an error, end-of-file, or end-of-record condition occurs during any of the wait operations, steps 4 through 8 are skipped.
- (4) Establish the format if one is specified.
- (5) If the statement is not a child data transfer statement (9.6.4.8),
 - (a) position the file prior to data transfer (9.3.4.3), and
 - (b) for formatted data transfer, set the left tab limit (10.8.1.2).
- (6) Transfer data between the file and the entities specified by the input/output list (if any) or namelist, possibly mediated by **defined input/output** procedures (9.6.4.8).
- (7) Determine whether an error, end-of-file, or end-of-record condition has occurred.
- (8) Position the file after data transfer (9.3.4.4) unless the statement is a child data transfer statement (9.6.4.8).
- (9) Cause any variable specified in a SIZE= specifier to become defined.
- (10) If an error, end-of-file, or end-of-record condition occurred, processing continues as specified in 9.11; otherwise, any variable specified in an IOSTAT= specifier is assigned the value zero.

3 The effect of executing an asynchronous data transfer statement shall be as if the following operations were performed in the order specified.

- (1) Determine the direction of data transfer.
- (2) Identify the **unit**.
- (3) Optionally, perform wait operations for one or more pending input/output operations for the **unit**. If an error, end-of-file, or end-of-record condition occurs during any of the wait operations, steps 4 through 9 are skipped.
- (4) Establish the format if one is specified.
- (5) Position the file prior to data transfer (9.3.4.3) and, for formatted data transfer, set the left tab limit (10.8.1.2).
- (6) Establish the set of **storage units** identified by the input/output list. For an **input statement**, this might require some or all of the data in the file to be read if an input variable is used as a *scalar-int-expr* in an *io-implied-do-control* in the input/output list, as a *subscript*, *substring-range*, *stride*, or is otherwise referenced.
- (7) Initiate an asynchronous data transfer between the file and the entities specified by the input/output list (if any) or namelist. The asynchronous data transfer may complete (and an error, end-of-file, or end-of-record condition may occur) during the execution of this data transfer statement or during a later wait operation.
- (8) Determine whether an error, end-of-file, or end-of-record condition has occurred. The conditions may occur during the execution of this data transfer statement or during the corresponding wait operation, but not both.
- (9) Position the file as if the data transfer had finished (9.3.4.4).
- (10) Cause any variable specified in a SIZE= specifier to become undefined.
- (11) If an error, end-of-file, or end-of-record condition occurred, processing continues as specified in 9.11; otherwise, any variable specified in an IOSTAT= specifier is assigned the value zero.

- 1 4 For an asynchronous data transfer statement, the data transfers may occur during execution of the statement,
 2 during execution of the corresponding wait operation, or anywhere between. The data transfer operation is
 3 considered to be pending until a corresponding wait operation is performed.
- 4 5 For asynchronous output, a pending input/output storage sequence affector (9.6.2.5) shall not be redefined,
 5 become undefined, or have its [pointer association](#) status changed.
- 6 6 For asynchronous input, a pending input/output storage sequence affector shall not be referenced, become defined,
 7 become undefined, become associated with a [dummy argument](#) that has the [VALUE attribute](#), or have its [pointer
 8 association](#) status changed.
- 9 7 Error, end-of-file, and end-of-record conditions in an asynchronous data transfer operation may occur during
 10 execution of either the data transfer statement or the corresponding wait operation. If an ID= specifier does not
 11 appear in the initiating data transfer statement, the conditions may occur during the execution of any subsequent
 12 data transfer or wait operation for the same [unit](#). When a condition occurs for a previously executed asynchronous
 13 data transfer statement, a wait operation is performed for all pending data transfer operations on that [unit](#). When
 14 a condition occurs during a subsequent statement, any actions specified by IOSTAT=, IOMSG=, ERR=, END=,
 15 and EOR= specifiers for that statement are taken.
- 16 8 If execution of the program is terminated during execution of an [output statement](#), the contents of the file become
 17 undefined.

NOTE 9.36

Because end-of-file and error conditions for asynchronous data transfer statements without an ID= specifier can be reported by the processor during the execution of a subsequent data transfer statement, it might be impossible for the user to determine which data transfer statement caused the condition. Reliably detecting which [input statement](#) caused an end-of-file condition requires that all asynchronous [input statements](#) for the [unit](#) include an ID= specifier.

18 **9.6.4.2 Direction of data transfer**

- 19 1 Execution of a READ statement causes values to be transferred from a file to the entities specified by the input
 20 list, if any, or specified within the file itself for namelist input. Execution of a WRITE or PRINT statement
 21 causes values to be transferred to a file from the entities specified by the output list and format specification, if
 22 any, or by the *namelist-group-name* for namelist output.

23 **9.6.4.3 Identifying a unit**

- 24 1 A data transfer statement that contains an input/output control list includes a UNIT= specifier that identifies
 25 an [external](#) or [internal](#) unit. A READ statement that does not contain an input/output control list specifies a
 26 particular processor-dependent [unit](#), which is the same as the [unit](#) identified by * in a [READ statement](#) that
 27 contains an input/output control list (9.5.1) and is the same as the [unit](#) identified by the value of the [named
 28 constant](#) INPUT_UNIT of the intrinsic module ISO_FORTRAN_ENV (13.9.2.11). The [PRINT statement](#)
 29 specifies some other processor-dependent [unit](#), which is the same as the [unit](#) identified by * in a [WRITE statement](#)
 30 and is the same as the [unit](#) identified by the value of the [named constant](#) OUTPUT_UNIT of the intrinsic module
 31 ISO_FORTRAN_ENV (13.9.2.20). Thus, each data transfer statement identifies an [external](#) or [internal](#) unit.
- 32 2 The [unit](#) identified by an unformatted data transfer statement shall be an [external unit](#).
- 33 3 The [unit](#) identified by a data transfer statement shall be [connected](#) to a file when execution of the statement
 34 begins.

NOTE 9.37

The [unit](#) could be [preconnected](#).

9.6.4.4 Establishing a format

- 1 If the input/output control list contains * as a format, list-directed formatting is established. If *namelist-group-name* appears, namelist formatting is established. If no *format* or *namelist-group-name* is specified, unformatted data transfer is established. Otherwise, the format specified by *format* is established.
- 2 For output to an *internal file*, a format specification that is in the file or is associated with the file shall not be specified.
- 3 An input list item, or an entity associated with it, shall not contain any portion of an established format specification.

9.6.4.5 Data transfer

9.6.4.5.1 General

- 1 Data are transferred between the file and the entities specified by the input/output list or namelist. The list items are processed in the order of the input/output list for all data transfer statements except namelist data transfer statements. The list items for a namelist *input statement* are processed in the order of the entities specified within the input records. The list items for a namelist *output statement* are processed in the order in which the variables are specified in the *namelist-group-object-list*. *Effective items* are derived from the input/output list items as described in 9.6.3.
- 2 All values needed to determine which entities are specified by an input/output list item are determined at the beginning of the processing of that item.
- 3 All values are transmitted to or from the entities specified by a list item prior to the processing of any succeeding list item for all data transfer statements.

NOTE 9.38

In the example

```
READ (N) N, X (N)
```

the old value of N identifies the *unit*, but the new value of N is the subscript of X.

- 4 All values following the *name=* part of the namelist entity (10.11) within the input records are transmitted to the matching entity specified in the *namelist-group-object-list* prior to processing any succeeding entity within the input record for namelist *input statements*. If an entity is specified more than once within the input record during a namelist *input statement*, the last occurrence of the entity specifies the value or values to be used for that entity.
- 5 If the input/output item is a pointer, data are transferred between the file and the associated *target*.
- 6 If an *internal file* has been specified, an input/output list item shall not be in the file or associated with the file.
- 7 During the execution of an *output statement* that specifies an *internal file*, no part of that *internal file* shall be referenced, defined, or become undefined as the result of evaluating any output list item.
- 8 During the execution of an *input statement* that specifies an *internal file*, no part of that *internal file* shall be defined or become undefined as the result of transferring a value to any input list item.
- 9 A DO variable becomes defined and its iteration count established at the beginning of processing of the *io-implied-do-object-list* an *io-implied-do*.
- 10 On output, every entity whose value is to be transferred shall be defined.

9.6.4.5.2 Unformatted data transfer

- 1 If the file is not [connected](#) for unformatted input/output, unformatted data transfer is prohibited.
- 2 During unformatted data transfer, data are transferred without editing between the file and the entities specified by the input/output list. If the file is [connected](#) for sequential or direct access, exactly one record is read or written.
- 3 A value in the file is stored in a [contiguous](#) sequence of [file storage units](#), beginning with the [file storage unit](#) immediately following the current file position.
- 4 After each value is transferred, the current file position is moved to a point immediately after the last [file storage unit](#) of the value.
- 5 On input from a file [connected](#) for sequential or direct access, the number of [file storage units](#) required by the input list shall be less than or equal to the number of [file storage units](#) in the record.
- 6 On input, if the [file storage units](#) transferred do not contain a value with the same type and type parameters as the input list entity, then the resulting value of the entity is processor dependent except in the following cases.
 - A complex entity may correspond to two real values with the same [kind type parameter](#) as the complex entity.
 - A default character list entity of length *n* may correspond to *n* default characters stored in the file, regardless of the length parameters of the entities that were written to these [storage units](#) of the file. If the file is [connected](#) for stream input, the characters may have been written by formatted stream output.
- 7 On output to a file [connected](#) for unformatted direct access, the output list shall not specify more values than can fit into the record. If the file is [connected](#) for direct access and the values specified by the output list do not fill the record, the remainder of the record is undefined.
- 8 If the file is [connected](#) for unformatted sequential access, the record is created with a length sufficient to hold the values from the output list. This length shall be one of the set of allowed record lengths for the file and shall not exceed the value specified in the [RECL= specifier](#), if any, of the [OPEN statement](#) that established the connection.

9.6.4.5.3 Formatted data transfer

- 1 If the file is not [connected](#) for formatted input/output, formatted data transfer is prohibited.
- 2 During formatted data transfer, data are transferred with editing between the file and the entities specified by the input/output list or by the *namelist-group-name*. Format control is initiated and editing is performed as described in [Clause 10](#).
- 3 The current record and possibly additional records are read or written.
- 4 During advancing input when the pad mode has the value NO, the input list and format specification shall not require more characters from the record than the record contains.
- 5 During advancing input when the pad mode has the value YES, blank characters are supplied by the processor if the input list and format specification require more characters from the record than the record contains.
- 6 During nonadvancing input when the pad mode has the value NO, an end-of-record condition ([9.11](#)) occurs if the input list and format specification require more characters from the record than the record contains, and the record is complete ([9.3.3.4](#)). If the record is incomplete, an end-of-file condition occurs instead of an end-of-record condition.
- 7 During nonadvancing input when the pad mode has the value YES, blank characters are supplied by the processor if an [effective item](#) and its corresponding data edit descriptors require more characters from the record than the record contains. If the record is incomplete, an end-of-file condition occurs; otherwise, an end-of-record condition

1 occurs.

2 8 If the file is [connected](#) for direct access, the record number is increased by one as each succeeding record is read
3 or written.

4 9 On output, if the file is [connected](#) for direct access or is an internal file and the characters specified by the output
5 list and format do not fill a record, blank characters are added to fill the record.

6 10 On output, the output list and format specification shall not specify more characters for a record than have been
7 specified by a [RECL= specifier](#) in the [OPEN statement](#) or the record length of an [internal file](#).

8 **9.6.4.6 List-directed formatting**

9 1 If list-directed formatting has been established, editing is performed as described in [10.10](#).

10 **9.6.4.7 Namelist formatting**

11 1 If namelist formatting has been established, editing is performed as described in [10.11](#).

12 2 Every [allocatable namelist-group-object](#) in the namelist group shall be allocated and every [namelist-group-object](#)
13 that is a pointer shall be associated with a [target](#). If a [namelist-group-object](#) is [polymorphic](#) or has an [ultimate](#)
14 [component](#) that is [allocatable](#) or a pointer, that object shall be processed by a [defined input/output](#) procedure
15 ([9.6.4.8](#)).

16 **9.6.4.8 Defined input/output**

17 **9.6.4.8.1 General**

18 1 [Defined input/output](#) allows a program to override the default handling of derived-type objects and values in
19 data transfer statements described in [9.6.3](#).

20 2 A [defined input/output](#) procedure is a procedure accessible by a [defined-io-generic-spec](#) ([12.4.3.2](#)). A particular
21 [defined input/output](#) procedure is selected as described in [9.6.4.8.4](#).

22 **9.6.4.8.2 Executing defined input/output data transfers**

23 1 If a [defined input/output](#) procedure is selected for an effective item as specified in [9.6.4.8.4](#), the processor shall
24 call the selected [defined input/output](#) procedure for that item. The [defined input/output](#) procedure controls the
25 actual data transfer operations for the derived-type list item.

26 2 A data transfer statement that includes a derived-type list item and that causes a [defined input/output](#) procedure
27 to be invoked is called a parent data transfer statement. A data transfer statement that is executed while a parent
28 data transfer statement is being processed and that specifies the [unit](#) passed into a [defined input/output](#) procedure
29 is called a child data transfer statement.

NOTE 9.39

A [defined input/output](#) procedure will usually contain child data transfer statements that read values from or write values to the current record or at the current file position. The effect of executing the [defined input/output](#) procedure is similar to that of substituting the list items from any child data transfer statements into the parent data transfer statement's list items, along with similar substitutions in the format specification.

NOTE 9.40

A particular execution of a READ, WRITE or PRINT statement can be both a parent and a child data transfer statement. A [defined input/output](#) procedure can indirectly call itself or another [defined input/output](#) procedure by executing a child data transfer statement containing a list item of derived type,

NOTE 9.40 (cont.)

where a matching [interface](#) is accessible for that derived type. If a [defined input/output](#) procedure calls itself indirectly in this manner, it cannot be declared `NON_RECURSIVE`.

1 3 A child data transfer statement is processed differently from a nonchild data transfer statement in the following
2 ways.

- 3 • Executing a child data transfer statement does not position the file prior to data transfer.
- 4 • An unformatted child data transfer statement does not position the file after data transfer is complete.
- 5 • Any `ADVANCE= specifier` in a child input/output statement is ignored.

6 9.6.4.8.3 Defined input/output procedures

7 1 For a particular derived type and a particular set of [kind type parameter](#) values, there are four possible sets of
8 [characteristics](#) for [defined input/output](#) procedures; one each for formatted input, formatted output, unformatted
9 input, and unformatted output. The user need not supply all four procedures. The procedures are specified
10 to be used for derived-type input/output by [interface blocks](#) (12.4.3.2) or by generic [bindings](#) (4.5.5), with a
11 [defined-io-generic-spec](#) (R1209). The [defined-io-generic-specs](#) for these procedures are `READ (FORMATTED)`,
12 `READ (UNFORMATTED)`, `WRITE (FORMATTED)`, and `WRITE (UNFORMATTED)`, for formatted input,
13 unformatted input, formatted output, and unformatted output respectively.

14 2 In the four [interfaces](#), which specify the [characteristics](#) of [defined input/output](#) procedures, the following syntax
15 term is used:

```
16 R921  dtv-type-spec                is  TYPE( derived-type-spec )
17                                     or  CLASS( derived-type-spec )
```

18 C934 (R921) If *derived-type-spec* specifies an [extensible type](#), the `CLASS` keyword shall be used; otherwise, the
19 `TYPE` keyword shall be used.

20 C935 (R921) All length type parameters of *derived-type-spec* shall be assumed.

21 3 If the [defined-io-generic-spec](#) is `READ (FORMATTED)`, the [characteristics](#) shall be the same as those specified
22 by the following [interface](#):

```
23 4      SUBROUTINE my_read_routine_formatted                &
24                                     (dtv,                &
25                                     unit,                &
26                                     iotype, v_list,      &
27                                     iostat, iomsg)
28
29      ! the derived-type variable
30      dtv-type-spec, INTENT(INOUT) :: dtv
31      INTEGER, INTENT(IN) :: unit ! unit number
32      ! the edit descriptor string
33      CHARACTER (LEN=*), INTENT(IN) :: iotype
34      INTEGER, INTENT(IN) :: v_list(:)
35      INTEGER, INTENT(OUT) :: iostat
36      CHARACTER (LEN=*), INTENT(INOUT) :: iomsg
37      END
```

37 5 If the [defined-io-generic-spec](#) is `READ (UNFORMATTED)`, the [characteristics](#) shall be the same as those specified
38 by the following [interface](#):

```
39 6      SUBROUTINE my_read_routine_unformatted            &
40                                     (dtv,                &
```



```

1          unit,                                &
2          iostat, iomsg)
3      ! the derived-type variable
4      dtv-type-spec, INTENT(INOUT) :: dtv
5      INTEGER, INTENT(IN) :: unit
6      INTEGER, INTENT(OUT) :: iostat
7      CHARACTER (LEN=*), INTENT(INOUT) :: iomsg
8  END

```

9 7 If the *defined-io-generic-spec* is **WRITE (FORMATTED)**, the *characteristics* shall be the same as those specified
10 by the following *interface*:

```

11 8      SUBROUTINE my_write_routine_formatted      &
12          (dtv,                                  &
13          unit,                                  &
14          iotype, v_list,                       &
15          iostat, iomsg)
16      ! the derived-type value/variable
17      dtv-type-spec, INTENT(IN) :: dtv
18      INTEGER, INTENT(IN) :: unit
19      ! the edit descriptor string
20      CHARACTER (LEN=*), INTENT(IN) :: iotype
21      INTEGER, INTENT(IN) :: v_list(:)
22      INTEGER, INTENT(OUT) :: iostat
23      CHARACTER (LEN=*), INTENT(INOUT) :: iomsg
24  END

```

25 9 If the *defined-io-generic-spec* is **WRITE (UNFORMATTED)**, the *characteristics* shall be the same as those
26 specified by the following *interface*:

```

27 10     SUBROUTINE my_write_routine_unformatted  &
28         (dtv,                                  &
29         unit,                                  &
30         iostat, iomsg)
31     ! the derived-type value/variable
32     dtv-type-spec, INTENT(IN) :: dtv
33     INTEGER, INTENT(IN) :: unit
34     INTEGER, INTENT(OUT) :: iostat
35     CHARACTER (LEN=*), INTENT(INOUT) :: iomsg
36  END

```

37 11 The actual specific procedure names (the *my_..._routine_...* procedure names above) are not significant. In
38 the discussion here and elsewhere, the *dummy arguments* in these *interfaces* are referred to by the names given
39 above; the names are, however, arbitrary.

40 12 When a *defined input/output* procedure is invoked, the processor shall pass a *unit* argument that has a value as
41 follows.

- 42 • If the parent data transfer statement uses a *file-unit-number*, the value of the *unit* argument shall be that
43 of the *file-unit-number*.
- 44 • If the parent data transfer statement is a **WRITE statement** with an asterisk *unit* or a **PRINT statement**,
45 the *unit* argument shall have the same value as the *named constant* **OUTPUT_UNIT** of the intrinsic
46 module **ISO_FORTRAN_ENV(13.9.2)**.

- 1 • If the parent data transfer statement is a **READ statement** with an asterisk **unit** or a **READ statement**
 2 without an *io-control-spec-list*, the **unit** argument shall have the same value as the **INPUT_UNIT** named
 3 constant of the intrinsic module **ISO_FORTRAN_ENV**(13.9.2).
 4 • Otherwise the parent data transfer statement must access an **internal file**, in which case the **unit** argument
 5 shall have a processor-dependent negative value.

NOTE 9.41

The **unit** argument passed to a **defined input/output** procedure will be negative when the parent data transfer statement specified an **internal unit**, or specified an **external unit** that is a **NEWUNIT** value. When an **internal unit** is used with the **INQUIRE statement**, an error condition will occur, and any variable specified in an **IOSTAT= specifier** will be assigned the value **IOSTAT_INQUIRE_INTERNAL_UNIT** from the intrinsic module **ISO_FORTRAN_ENV**(13.9.2).

- 6 13 For formatted data transfer, the processor shall pass an **iotype** argument that has the value
 7 • “LISTDIRECTED” if the parent data transfer statement specified list directed formatting,
 8 • “NAMELIST” if the parent data transfer statement specified namelist formatting, or
 9 • “DT” concatenated with the *char-literal-constant*, if any, of the DT edit descriptor in the format specification
 10 of the parent data transfer statement.
- 11 14 If the parent data transfer statement is an **input statement**, the **dtv dummy argument** is argument associated
 12 with the **effective item** that caused the **defined input** procedure to be invoked, as if the **effective item** were an
 13 **actual argument** in this **procedure reference** (2.4.5).
- 14 15 If the parent data transfer statement is an **output statement**, the processor shall provide the value of the **effective**
 15 **item** in the **dtv dummy argument**.
- 16 16 If the *v-list* of the edit descriptor appears in the parent data transfer statement, the processor shall provide the
 17 values from it in the **v_list dummy argument**, with the same number of elements in the same order as *v-list*.
 18 If there is no *v-list* in the edit descriptor or if the data transfer statement specifies list-directed or namelist
 19 formatting, the processor shall provide **v_list** as a zero-sized array.

NOTE 9.42

The user’s procedure might choose to interpret an element of the **v_list** argument as a field width, but this is not required. If it does, it would be appropriate to fill an output field with “*”s if the width is too small.

- 20 17 The **iostat** argument is used to report whether an error, end-of-record, or end-of-file condition (9.11) occurs.
 21 If an error condition occurs, the **defined input/output** procedure shall assign a positive value to the **iostat**
 22 argument. Otherwise, if an end-of-file condition occurs, the **defined input** procedure shall assign the value of the
 23 **named constant IOSTAT_END** (13.9.2.14) to the **iostat** argument. Otherwise, if an end-of-record condition
 24 occurs, the **defined input** procedure shall assign the value of the **named constant IOSTAT_EOR** (13.9.2.15) to
 25 **iostat**. Otherwise, the **defined input/output** procedure shall assign the value zero to the **iostat** argument.
- 26 18 If the **defined input/output** procedure returns a nonzero value for the **iostat** argument, the procedure shall also
 27 return an explanatory message in the **iomsg** argument. Otherwise, the procedure shall not change the value of
 28 the **iomsg** argument.

NOTE 9.43

The values of the **iostat** and **iomsg** arguments set in a **defined input/output** procedure need not be passed to all of the parent data transfer statements.

- 29 19 If the **iostat** argument of the **defined input/output** procedure has a nonzero value when that procedure returns,
 30 and the processor therefore **terminates execution** of the program as described in 9.11, the processor shall make
 31 the value of the **iomsg** argument available in a processor-dependent manner.

- 1 20 While a parent **READ** statement is active, an input/output statement shall not read from any **external unit** other
 2 than the one specified by the **unit dummy argument** and shall not perform output to any **external unit**.
- 3 21 While a parent **WRITE** or **PRINT** statement is active, an input/output statement shall not perform output to
 4 any **external unit** other than the one specified by the **unit dummy argument** and shall not read from any **external**
 5 **unit**.
- 6 22 While a parent data transfer statement is active, a data transfer statement that specifies an **internal file** is
 7 permitted.
- 8 23 **OPEN**, **CLOSE**, **BACKSPACE**, **ENDFILE**, and **REWIND** statements shall not be executed while a parent data
 9 transfer statement is active.
- 10 24 A **defined input/output** procedure may use a format specification with a **DT edit descriptor** for handling a
 11 component of the derived type that is itself of a derived type. A child data transfer statement that is a list
 12 directed or namelist input/output statement may contain a list item of derived type.
- 13 25 Because a child data transfer statement does not position the file prior to data transfer, the child data transfer
 14 statement starts transferring data from where the file was positioned by the parent data transfer statement's
 15 most recently processed **effective item** or edit descriptor. This is not necessarily at the beginning of a record.
- 16 26 The edit descriptors **T** and **TL** used on **unit** by a child data transfer statement shall not cause the file to be
 17 positioned before the file position at the time the **defined input/output** procedure was invoked.

NOTE 9.44

A **defined input/output** procedure could use **INQUIRE** to determine the settings of **BLANK=**, **PAD=**, **ROUND=**, **DECIMAL=**, and **DELIM=** for an **external unit**. The **INQUIRE** statement provides values as specified in 9.10.

- 18 27 Neither a parent nor child data transfer statement shall be asynchronous.
- 19 28 A **defined input/output** procedure, and any procedures invoked therefrom, shall not define, nor cause to become
 20 undefined, any **storage unit** referenced by any input/output list item, the corresponding format, or any specifier
 21 in any active parent data transfer statement, except through the **dtv** argument.

NOTE 9.45

A child data transfer statement shall not specify the **ID=**, **POS=**, or **REC=** specifiers in an input/output control list.

NOTE 9.46

A simple example of derived type formatted output follows. The derived type variable **chairman** has two components. The type and an associated write formatted procedure are defined in a module so as to be accessible from wherever they might be needed. It would also be possible to check that **iotype** indeed has the value 'DT' and to set **iostat** and **iomsg** accordingly.

```

MODULE p

  TYPE :: person
    CHARACTER (LEN=20) :: name
    INTEGER :: age
  CONTAINS
    PROCEDURE,PRIVATE :: pwf
    GENERIC             :: WRITE(FORMATTED) => pwf
  END TYPE person

CONTAINS

```

NOTE 9.46 (cont.)

```

SUBROUTINE pwf (dtv,unit,iotype,vlist,iostat,iomsg)
! argument definitions
  CLASS(person), INTENT(IN) :: dtv
  INTEGER, INTENT(IN) :: unit
  CHARACTER (LEN=*), INTENT(IN) :: iotype
  INTEGER, INTENT(IN) :: vlist(:)
  INTEGER, INTENT(OUT) :: iostat
  CHARACTER (LEN=*), INTENT(INOUT) :: iomsg
! local variable
  CHARACTER (LEN=9) :: pfmt

! vlist(1) and (2) are to be used as the field widths of the two
! components of the derived type variable. First set up the format to
! be used for output.
  WRITE(pfmt,'(A,I2,A,I2,A)' ) '(A', vlist(1), ',I', vlist(2), ' )'

! now the basic output statement
  WRITE(unit, FMT=pfmt, IOSTAT=iostat) dtv%name, dtv%age

END SUBROUTINE pwf

END MODULE p

PROGRAM committee
  USE p
  INTEGER id, members
  TYPE (person) :: chairman
  ...
  WRITE(6, FMT="(I2, DT (15,6), I5)" ) id, chairman, members
! this writes a record with four fields, with lengths 2, 15, 6, 5
! respectively

END PROGRAM

```

NOTE 9.47

In the following example, the variables of the derived type `node` form a linked list, with a single value at each node. The subroutine `pwf` is used to write the values in the list, one per line.

```

MODULE p

  TYPE node
    INTEGER :: value = 0
    TYPE (NODE), POINTER :: next_node => NULL ( )
  CONTAINS
    PROCEDURE,PRIVATE :: pwf
    GENERIC :: WRITE(FORMATTED) => pwf
  END TYPE node

CONTAINS

  SUBROUTINE pwf (dtv,unit,iotype,vlist,iostat,iomsg)
! Write the chain of values, each on a separate line in I9 format.
  CLASS(node), INTENT(IN) :: dtv

```

NOTE 9.47 (cont.)

```

INTEGER, INTENT(IN) :: unit
CHARACTER (LEN=*), INTENT(IN) :: iotype
INTEGER, INTENT(IN) :: vlist(:)
INTEGER, INTENT(OUT) :: iostat
CHARACTER (LEN=*), INTENT(INOUT) :: iomsg

WRITE(unit,'(i9 /)', IOSTAT = iostat) dtv%value
IF(iostat/=0) RETURN
IF(ASSOCIATED(dtv%next_node)) WRITE(unit,'(dt)', IOSTAT=iostat) dtv%next_node
END SUBROUTINE pwf

END MODULE p

```

1 **9.6.4.8.4 Resolving defined input/output procedure references**

2 1 A suitable [generic interface](#) for [defined input/output](#) of an [effective item](#) is one that has a [defined-io-generic-spec](#)
3 that is appropriate to the direction (read or write) and form (formatted or unformatted) of the data transfer
4 as specified in [9.6.4.8.3](#), and has a [specific interface](#) whose `dtv` argument is compatible with the [effective item](#)
5 according to the rules for argument association in [12.5.2.4](#).

6 2 When an [effective item](#) ([9.6.3](#)) that is of derived type is encountered during a data transfer, [defined input/output](#)
7 occurs if both of the following conditions are true.

8 (1) The circumstances of the input/output are such that [defined input/output](#) is permitted; that is,
9 either

10 (a) the transfer was initiated by a list-directed, namelist, or unformatted input/output statement,
11 or

12 (b) a format specification is supplied for the data transfer statement, and the edit descriptor
13 corresponding to the [effective item](#) is a DT edit descriptor.

14 (2) A suitable [defined input/output](#) procedure is available; that is, either

15 (a) the [declared type](#) of the [effective item](#) has a suitable generic [type-bound procedure](#), or

16 (b) a suitable [generic interface](#) is accessible.

17 3 If (2a) is true, the procedure referenced is determined as for explicit [type-bound procedure](#) references ([12.5](#)); that
18 is, the [binding](#) with the appropriate [specific interface](#) is located in the [declared type](#) of the [effective item](#), and the
19 corresponding [binding](#) in the [dynamic type](#) of the [effective item](#) is selected.

20 4 If (2a) is false and (2b) is true, the reference is to the procedure identified by the appropriate [specific interface](#)
21 in the [interface block](#).

22 **9.6.5 Termination of data transfer statements**

23 1 Termination of a data transfer statement occurs when

24 • format processing encounters a colon or data edit descriptor and there are no remaining elements in the
25 [input-item-list](#) or [output-item-list](#),

26 • unformatted or list-directed data transfer exhausts the [input-item-list](#) or [output-item-list](#),

27 • namelist output exhausts the [namelist-group-object-list](#),

28 • an error condition occurs,

29 • an end-of-file condition occurs,

30 • a slash (/) is encountered as a value separator ([10.10](#), [10.11](#)) in the record being read during list-directed
31 or namelist input, or

32 • an end-of-record condition occurs during execution of a nonadvancing input statement ([9.11](#)).

9.7 Waiting on pending data transfer

9.7.1 Wait operation

- 1 Execution of an asynchronous [data transfer statement](#) in which neither an error, end-of-record, nor end-of-file condition occurs initiates a pending data transfer operation. There may be multiple pending data transfer operations for the same or multiple [units](#) simultaneously. A pending data transfer operation remains pending until a corresponding wait operation is performed. A wait operation may be performed by a [BACKSPACE](#), [CLOSE](#), [ENDFILE](#), [FLUSH](#), [INQUIRE](#), [PRINT](#), [READ](#), [REWIND](#), [WAIT](#), or [WRITE](#) statement.
- 2 A wait operation completes the processing of a pending data transfer operation. Each wait operation completes only a single data transfer operation, although a single statement may perform multiple wait operations.
- 3 If the actual data transfer is not yet complete, the wait operation first waits for its completion. If the data transfer operation is an input operation that completed without error, the [storage units](#) of the input/output storage sequence then become defined with the values as described in [9.6.2.15](#) and [9.6.4.5](#).
- 4 If any error, end-of-file, or end-of-record conditions occur, the applicable actions specified by the [IOSTAT=](#), [IOMSG=](#), [ERR=](#), [END=](#), and [EOR=](#) specifiers of the statement that performs the wait operation are taken.
- 5 If an error or end-of-file condition occurs during a wait operation for a [unit](#), the processor performs a wait operation for all pending data transfer operations for that [unit](#).

NOTE 9.48

Error, end-of-file, and end-of-record conditions can be raised either during the [data transfer statement](#) that initiates asynchronous input/output, a subsequent asynchronous [data transfer statement](#) for the same [unit](#), or during the wait operation. If such conditions are raised during a [data transfer statement](#), they trigger actions according to the [IOSTAT=](#), [ERR=](#), [END=](#), and [EOR=](#) specifiers of that statement; if they are raised during the wait operation, the actions are in accordance with the specifiers of the statement that performs the wait operation.

- 6 After completion of the wait operation, the data transfer operation and its input/output storage sequence are no longer considered to be pending.

9.7.2 WAIT statement

- 1 A WAIT statement performs a wait operation for specified pending asynchronous data transfer operations.

R922 *wait-stmt* **is** WAIT (*wait-spec-list*)

R923 *wait-spec* **is** [UNIT =] *file-unit-number*
or END = *label*
or EOR = *label*
or ERR = *label*
or ID = *scalar-int-expr*
or IOMSG = *iomsg-variable*
or IOSTAT = *scalar-int-variable*

C936 No specifier shall appear more than once in a given *wait-spec-list*.

C937 A *file-unit-number* shall be specified in a *wait-spec-list*; if the optional characters UNIT= are omitted, the *file-unit-number* shall be the first item in the *wait-spec-list*.

C938 (R923) The *label* in the [ERR=](#), [EOR=](#), or [END=](#) specifier shall be the statement label of a [branch target statement](#) that appears in the same [inclusive scope](#) as the WAIT statement.

- 2 The [IOSTAT=](#), [ERR=](#), [EOR=](#), [END=](#), and [IOMSG=](#) specifiers are described in [9.11](#).

- 1 3 The value of the expression specified in the ID= specifier shall be zero or the identifier of a pending data transfer
 2 operation for the specified **unit**. If the ID= specifier appears, a wait operation for the specified data transfer
 3 operation, if any, is performed. If the ID= specifier is omitted, wait operations for all pending data transfers for
 4 the specified **unit** are performed.
- 5 4 Execution of a WAIT statement specifying a **unit** that does not exist, has no file connected to it, or is not open
 6 for asynchronous input/output is permitted, provided that the WAIT statement has no ID= specifier; such a
 7 WAIT statement does not cause an error or end-of-file condition to occur.

NOTE 9.49

An **EOR= specifier** has no effect if the pending data transfer operation is not a nonadvancing read. An **END= specifier** has no effect if the pending data transfer operation is not a READ.

8 9.8 File positioning statements

9 9.8.1 Syntax

10 R924 *backspace-stmt* is BACKSPACE *file-unit-number*
 11 or BACKSPACE (*position-spec-list*)

12 R925 *endfile-stmt* is ENDFILE *file-unit-number*
 13 or ENDFILE (*position-spec-list*)

14 R926 *rewind-stmt* is REWIND *file-unit-number*
 15 or REWIND (*position-spec-list*)

- 16 1 A **unit** that is connected for direct access shall not be referred to by a BACKSPACE, ENDFILE, or REWIND
 17 statement. A **unit** that is connected for unformatted stream access shall not be referred to by a BACKSPACE
 18 statement. A **unit** that is connected with an ACTION= specifier having the value READ shall not be referred
 19 to by an ENDFILE statement.

20 R927 *position-spec* is [UNIT =] *file-unit-number*
 21 or IOMSG = *iomsg-variable*
 22 or IOSTAT = *scalar-int-variable*
 23 or ERR = *label*

24 C939 No specifier shall appear more than once in a given *position-spec-list*.

25 C940 A *file-unit-number* shall be specified in a *position-spec-list*; if the optional characters UNIT= are omitted,
 26 the *file-unit-number* shall be the first item in the *position-spec-list*.

27 C941 (R927) The *label* in the **ERR= specifier** shall be the statement label of a **branch target statement** that
 28 appears in the same **inclusive scope** as the file positioning statement.

- 29 2 The **IOSTAT=**, **ERR=**, and **IOMSG=** specifiers are described in 9.11.

- 30 3 Execution of a file positioning statement performs a wait operation for all pending asynchronous data transfer
 31 operations for the specified **unit**.

32 9.8.2 BACKSPACE statement

- 33 1 Execution of a BACKSPACE statement causes the file connected to the specified **unit** to be positioned before
 34 the current record if there is a current record, or before the preceding record if there is no current record. If the
 35 file is at its initial point, the position of the file is not changed.

NOTE 9.50

If the preceding record is an endfile record, the file is positioned before the endfile record.

- 1 2 If a BACKSPACE statement causes the implicit writing of an endfile record, the file is positioned before the
- 2 record that precedes the endfile record.
- 3 3 Backspacing a file that is connected but does not exist is prohibited.
- 4 4 Backspacing over records written using list-directed or namelist formatting is prohibited.

NOTE 9.51

An example of a BACKSPACE statement is:

```
BACKSPACE (10, IOSTAT = N)
```

9.8.3 ENDFILE statement

- 5
- 6 1 Execution of an ENDFILE statement for a file connected for sequential access writes an endfile record as the next
- 7 record of the file. The file is then positioned after the endfile record, which becomes the last record of the file.
- 8 If the file also may be connected for direct access, only those records before the endfile record are considered to
- 9 have been written. Thus, only those records may be read during subsequent direct access connections to the file.
- 10 2 After execution of an ENDFILE statement for a file connected for sequential access, a BACKSPACE or REWIND
- 11 statement shall be used to reposition the file prior to execution of any data transfer input/output statement or
- 12 ENDFILE statement.
- 13 3 Execution of an ENDFILE statement for a file connected for stream access causes the terminal point of the file
- 14 to become equal to the current file position. Only file storage units before the current position are considered
- 15 to have been written; thus only those file storage units may be subsequently read. Subsequent stream output
- 16 statements may be used to write further data to the file.
- 17 4 Execution of an ENDFILE statement for a file that is connected but does not exist creates the file; if the file is
- 18 connected for sequential access, it is created prior to writing the endfile record.

NOTE 9.52

An example of an ENDFILE statement is:

```
ENDFILE K
```

9.8.4 REWIND statement

- 19
- 20 1 Execution of a REWIND statement causes the specified file to be positioned at its initial point.

NOTE 9.53

If the file is already positioned at its initial point, execution of this statement has no effect on the position of the file.

- 21 2 Execution of a REWIND statement for a file that is connected but does not exist is permitted and has no effect
- 22 on any file.

NOTE 9.54

An example of a REWIND statement is:

```
REWIND 10
```


9.9 FLUSH statement

R928 *flush-stmt* is FLUSH *file-unit-number*
or FLUSH (*flush-spec-list*)

R929 *flush-spec* is [UNIT =] *file-unit-number*
or IOSTAT = *scalar-int-variable*
or IOMSG = *iomsg-variable*
or ERR = *label*

C942 No specifier shall appear more than once in a given *flush-spec-list*.

C943 A *file-unit-number* shall be specified in a *flush-spec-list*; if the optional characters UNIT= are omitted from the unit specifier, the *file-unit-number* shall be the first item in the *flush-spec-list*.

C944 (R929) The *label* in the ERR= specifier shall be the statement label of a **branch target statement** that appears in the same **inclusive scope** as the FLUSH statement.

1 The IOSTAT=, IOMSG= and ERR= specifiers are described in 9.11.

2 Execution of a FLUSH statement causes data written to an **external file** to be available to other processes, or causes data placed in an **external file** by means other than Fortran to be available to a **READ statement**. These actions are processor dependent.

3 Execution of a FLUSH statement for a file that is connected but does not exist is permitted and has no effect on any file. A FLUSH statement has no effect on file position.

4 Execution of a FLUSH statement performs a wait operation for all pending asynchronous data transfer operations for the specified **unit**.

NOTE 9.55

Because this part of ISO/IEC 1539 does not specify the mechanism of file storage, the exact meaning of the flush operation is not precisely defined. It is expected that the flush operation will make all data written to a file available to other processes or devices, or make data recently added to a file by other processes or devices available to the program via a subsequent read operation. This is commonly called “flushing input/output buffers”.

NOTE 9.56

An example of a FLUSH statement is:

```
FLUSH (10, IOSTAT = N)
```

9.10 File inquiry statement

9.10.1 Forms of the INQUIRE statement

1 The INQUIRE statement can be used to inquire about properties of a particular named file, of the connection to a particular **unit**, or the number of file storage units required for an output list. There are three forms of the INQUIRE statement: inquire by file, which uses the FILE= specifier, inquire by **unit**, which uses the UNIT= specifier, and inquire by output list, which uses only the **IOLength= specifier**. Assignments to specifier variables are performed as if by **intrinsic assignment**.

2 For inquiry by **unit**, the **unit** specified need not exist or be connected to a file. If it is connected to a file, the inquiry is being made about the connection and about the file connected.

3 An INQUIRE statement may be executed before, while, or after a file is connected to a **unit**. All values assigned

1 by an INQUIRE statement are those that are current at the time the statement is executed.

2 R930 *inquire-stmt* is INQUIRE (*inquire-spec-list*)
 3 or INQUIRE (IOLENGTH = *scalar-int-variable*) ■
 4 ■ *output-item-list*

NOTE 9.57

Examples of INQUIRE statements are:

```
INQUIRE (IOLENGTH = IOL) A (1:N)
INQUIRE (UNIT = JOAN, OPENED = LOG_01, NAMED = LOG_02, &
  FORM = CHAR_VAR, IOSTAT = IOS)
```

9.10.2 Inquiry specifiers

9.10.2.1 Syntax

- 1 Unless constrained, the following inquiry specifiers may be used in either of the inquire by file or inquire by unit
 8 forms of the INQUIRE statement.

9 R931 *inquire-spec* is [UNIT =] *file-unit-number*
 10 or FILE = *file-name-expr*
 11 or ACCESS = *scalar-default-char-variable*
 12 or ACTION = *scalar-default-char-variable*
 13 or ASYNCHRONOUS = *scalar-default-char-variable*
 14 or BLANK = *scalar-default-char-variable*
 15 or DECIMAL = *scalar-default-char-variable*
 16 or DELIM = *scalar-default-char-variable*
 17 or DIRECT = *scalar-default-char-variable*
 18 or ENCODING = *scalar-default-char-variable*
 19 or ERR = *label*
 20 or EXIST = *scalar-logical-variable*
 21 or FORM = *scalar-default-char-variable*
 22 or FORMATTED = *scalar-default-char-variable*
 23 or ID = *scalar-int-expr*
 24 or IOMSG = *iomsg-variable*
 25 or IOSTAT = *scalar-int-variable*
 26 or NAME = *scalar-default-char-variable*
 27 or NAMED = *scalar-logical-variable*
 28 or NEXTREC = *scalar-int-variable*
 29 or NUMBER = *scalar-int-variable*
 30 or OPENED = *scalar-logical-variable*
 31 or PAD = *scalar-default-char-variable*
 32 or PENDING = *scalar-logical-variable*
 33 or POS = *scalar-int-variable*
 34 or POSITION = *scalar-default-char-variable*
 35 or READ = *scalar-default-char-variable*
 36 or READWRITE = *scalar-default-char-variable*
 37 or RECL = *scalar-int-variable*
 38 or ROUND = *scalar-default-char-variable*
 39 or SEQUENTIAL = *scalar-default-char-variable*
 40 or SIGN = *scalar-default-char-variable*
 41 or SIZE = *scalar-int-variable*
 42 or STREAM = *scalar-default-char-variable*
 43 or UNFORMATTED = *scalar-default-char-variable*
 44 or WRITE = *scalar-default-char-variable*

- 1 C945 No specifier shall appear more than once in a given *inquire-spec-list*.
- 2 C946 An *inquire-spec-list* shall contain one **FILE= specifier** or one *file-unit-number*, but not both.
- 3 C947 In the inquire by unit form of the INQUIRE statement, if the optional characters UNIT= are omitted,
4 the *file-unit-number* shall be the first item in the *inquire-spec-list*.
- 5 C948 If an **ID= specifier** appears in an *inquire-spec-list*, a **PENDING= specifier** shall also appear.
- 6 C949 (R929) The *label* in the **ERR= specifier** shall be the statement label of a **branch target statement** that
7 appears in the same **inclusive scope** as the INQUIRE statement.
- 8 2 If *file-unit-number* identifies an **internal unit** (9.6.4.8.3), an error condition occurs.
- 9 3 When a returned value of a specifier other than the **NAME= specifier** is of type character, the value returned is
10 in upper case.
- 11 4 If an error condition occurs during execution of an INQUIRE statement, all of the inquiry specifier variables
12 become undefined, except for variables in the **IOSTAT=** and **IOMSG=** specifiers (if any).
- 13 5 The **IOSTAT=**, **ERR=**, and **IOMSG=** specifiers are described in 9.11.

14 9.10.2.2 FILE= specifier in the INQUIRE statement

- 15 1 The value of the *file-name-expr* in the **FILE=** specifier specifies the name of the file being inquired about. The
16 named file need not exist or be connected to a **unit**. The value of the *file-name-expr* shall be of a form acceptable
17 to the processor as a file name. Any trailing blanks are ignored. The interpretation of case is processor dependent.

18 9.10.2.3 ACCESS= specifier in the INQUIRE statement

- 19 1 The *scalar-default-char-variable* in the **ACCESS=** specifier is assigned the value SEQUENTIAL if the connection
20 is for sequential access, DIRECT if the connection is for direct access, or STREAM if the connection is for stream
21 access. If there is no connection, it is assigned the value UNDEFINED.

22 9.10.2.4 ACTION= specifier in the INQUIRE statement

- 23 1 The *scalar-default-char-variable* in the **ACTION=** specifier is assigned the value READ if the connection is for
24 input only, WRITE if the connection is for output only, and READWRITE if the connection is for both input
25 and output. If there is no connection, the *scalar-default-char-variable* is assigned the value UNDEFINED.

26 9.10.2.5 ASYNCHRONOUS= specifier in the INQUIRE statement

- 27 1 The *scalar-default-char-variable* in the **ASYNCHRONOUS=** specifier is assigned the value YES if the connection
28 allows asynchronous input/output; it is assigned the value NO if the connection does not allow asynchronous
29 input/output. If there is no connection, the *scalar-default-char-variable* is assigned the value UNDEFINED.

30 9.10.2.6 BLANK= specifier in the INQUIRE statement

- 31 1 The *scalar-default-char-variable* in the **BLANK=** specifier is assigned the value ZERO or NULL, corresponding
32 to the blank interpretation mode in effect for a connection for formatted input/output. If there is no connection,
33 or if the connection is not for formatted input/output, the *scalar-default-char-variable* is assigned the value
34 UNDEFINED.

35 9.10.2.7 DECIMAL= specifier in the INQUIRE statement

- 36 1 The *scalar-default-char-variable* in the **DECIMAL=** specifier is assigned the value COMMA or POINT, corres-
37 ponding to the decimal edit mode in effect for a connection for formatted input/output. If there is no connection,
38 or if the connection is not for formatted input/output, the *scalar-default-char-variable* is assigned the value
39 UNDEFINED.

1 9.10.2.8 DELIM= specifier in the INQUIRE statement

2 1 The *scalar-default-char-variable* in the DELIM= specifier is assigned the value APOSTROPHE, QUOTE, or
3 NONE, corresponding to the delimiter mode in effect for a connection for formatted input/output. If there is no
4 connection or if the connection is not for formatted input/output, the *scalar-default-char-variable* is assigned the
5 value UNDEFINED.

6 9.10.2.9 DIRECT= specifier in the INQUIRE statement

7 1 The *scalar-default-char-variable* in the DIRECT= specifier is assigned the value YES if DIRECT is included in
8 the set of allowed access methods for the file, NO if DIRECT is not included in the set of allowed access methods
9 for the file, and UNKNOWN if the processor is unable to determine whether DIRECT is included in the set of
10 allowed access methods for the file or if the *unit* identified by *file-unit-number* is not connected to a file.

11 9.10.2.10 ENCODING= specifier in the INQUIRE statement

12 1 The *scalar-default-char-variable* in the ENCODING= specifier is assigned the value UTF-8 if the connection is
13 for formatted input/output with an encoding form of UTF-8, and is assigned the value UNDEFINED if the
14 connection is for unformatted input/output. If there is no connection, it is assigned the value UTF-8 if the
15 processor is able to determine that the encoding form of the file is UTF-8; if the processor is unable to determine
16 the encoding form of the file or if the *unit* identified by *file-unit-number* is not connected to a file, the variable is
17 assigned the value UNKNOWN.

NOTE 9.58

The value assigned could be something other than UTF-8, UNDEFINED, or UNKNOWN if the processor supports other specific encoding forms (e.g. UTF-16BE).

18 9.10.2.11 EXIST= specifier in the INQUIRE statement

19 1 Execution of an INQUIRE by file statement causes the *scalar-logical-variable* in the EXIST= specifier to be
20 assigned the value true if there exists a file with the specified name; otherwise, false is assigned. Execution of an
21 INQUIRE by unit statement causes true to be assigned if the specified *unit* exists; otherwise, false is assigned.

22 9.10.2.12 FORM= specifier in the INQUIRE statement

23 1 The *scalar-default-char-variable* in the FORM= specifier is assigned the value FORMATTED if the connection
24 is for formatted input/output, and is assigned the value UNFORMATTED if the connection is for unformatted
25 input/output. If there is no connection, it is assigned the value UNDEFINED.

26 9.10.2.13 FORMATTED= specifier in the INQUIRE statement

27 1 The *scalar-default-char-variable* in the FORMATTED= specifier is assigned the value YES if FORMATTED is
28 included in the set of allowed forms for the file, NO if FORMATTED is not included in the set of allowed forms
29 for the file, and UNKNOWN if the processor is unable to determine whether FORMATTED is included in the
30 set of allowed forms for the file or if the *unit* identified by *file-unit-number* is not connected to a file.

31 9.10.2.14 ID= specifier in the INQUIRE statement

32 1 The value of the expression specified in the ID= specifier shall be the identifier of a pending data transfer operation
33 for the specified *unit*. This specifier interacts with the PENDING= specifier (9.10.2.21).

34 9.10.2.15 NAME= specifier in the INQUIRE statement

35 1 The *scalar-default-char-variable* in the NAME= specifier is assigned the value of the name of the file if the file
36 has a name; otherwise, it becomes undefined. The value assigned shall be suitable for use as the value of the
37 *file-name-expr* in the FILE= specifier in an OPEN statement.

NOTE 9.59

If this specifier appears in an INQUIRE by file statement, its value is not necessarily the same as the name given in the FILE= specifier.

The processor could assign a file name qualified by a user identification, device, directory, or other relevant information.

1 2 The case of the characters assigned to *scalar-default-char-variable* is processor dependent.

9.10.2.16 NAMED= specifier in the INQUIRE statement

3 1 The *scalar-logical-variable* in the NAMED= specifier is assigned the value true if the file has a name; otherwise,
4 it is assigned the value false.

9.10.2.17 NEXTREC= specifier in the INQUIRE statement

6 1 The *scalar-int-variable* in the NEXTREC= specifier is assigned the value $n + 1$, where n is the record number of
7 the last record read from or written to the connection for direct access. If there is a connection but no records have
8 been read or written since the connection, the *scalar-int-variable* is assigned the value 1. If there is no connection,
9 the connection is not for direct access, or the position is indeterminate because of a previous error condition, the
10 *scalar-int-variable* becomes undefined. If there are pending data transfer operations for the specified **unit**, the
11 value assigned is computed as if all the pending data transfers had already completed.

9.10.2.18 NUMBER= specifier in the INQUIRE statement

13 1 Execution of an INQUIRE by file statement causes the *scalar-int-variable* in the NUMBER= specifier to be
14 assigned the value of the **external unit** number of the unit that is connected to the file. If there is no **unit**
15 connected to the file, the value -1 is assigned. Execution of an INQUIRE by **unit** statement causes the *scalar-*
16 *int-variable* to be assigned the value of *file-unit-number*.

9.10.2.19 OPENED= specifier in the INQUIRE statement

18 1 Execution of an INQUIRE by file statement causes the *scalar-logical-variable* in the OPENED= specifier to be
19 assigned the value true if the file specified is connected to a **unit**; otherwise, false is assigned. Execution of an
20 INQUIRE by **unit** statement causes the *scalar-logical-variable* to be assigned the value true if the specified **unit**
21 is connected to a file; otherwise, false is assigned.

9.10.2.20 PAD= specifier in the INQUIRE statement

23 1 The *scalar-default-char-variable* in the PAD= specifier is assigned the value YES or NO, corresponding to the
24 pad mode in effect for a connection for formatted input/output. If there is no connection or if the connection is
25 not for formatted input/output, the *scalar-default-char-variable* is assigned the value UNDEFINED.

9.10.2.21 PENDING= specifier in the INQUIRE statement

27 1 The PENDING= specifier is used to determine whether previously pending asynchronous data transfers are
28 complete. A data transfer operation is previously pending if it is pending at the beginning of execution of the
29 INQUIRE statement.

30 2 If an ID= specifier appears and the specified data transfer operation is complete, then the variable specified in
31 the PENDING= specifier is assigned the value false and the INQUIRE statement performs the wait operation
32 for the specified data transfer.

33 3 If the ID= specifier is omitted and all previously pending data transfer operations for the specified **unit** are
34 complete, then the variable specified in the PENDING= specifier is assigned the value false and the INQUIRE
35 statement performs wait operations for all previously pending data transfers for the specified **unit**.

- 1 4 In all other cases, the variable specified in the PENDING= specifier is assigned the value true, no wait operations
 2 are performed, and the previously pending data transfers remain pending after the execution of the INQUIRE
 3 statement.

NOTE 9.60

The processor has considerable flexibility in defining when it considers a transfer to be complete. Any of the following approaches could be used:

- The INQUIRE statement could consider an asynchronous data transfer to be incomplete until after the corresponding wait operation. In this case PENDING= would always return true unless there were no previously pending data transfers for the [unit](#).
- The INQUIRE statement could wait for all specified data transfers to complete and then always return false for PENDING=.
- The INQUIRE statement could actually test the state of the specified data transfer operations.

4 9.10.2.22 POS= specifier in the INQUIRE statement

- 5 1 The *scalar-int-variable* in the POS= specifier is assigned the number of the [file storage unit](#) immediately following
 6 the current position of a file connected for stream access. If the file is positioned at its terminal position, the
 7 variable is assigned a value one greater than the number of the highest-numbered [file storage unit](#) in the file. If
 8 there is no connection, the file is not connected for stream access, or if the position of the file is indeterminate
 9 because of previous error conditions, the variable becomes undefined.

10 9.10.2.23 POSITION= specifier in the INQUIRE statement

- 11 1 The *scalar-default-char-variable* in the POSITION= specifier is assigned the value REWIND if the connection
 12 was opened for positioning at its initial point, APPEND if the connection was opened for positioning before its
 13 endfile record or at its terminal point, and ASIS if the connection was opened without changing its position.
 14 If there is no connection or if the file is connected for direct access, the *scalar-default-char-variable* is assigned
 15 the value UNDEFINED. If the file has been repositioned since the connection, the *scalar-default-char-variable*
 16 is assigned a processor-dependent value, which shall not be REWIND unless the file is positioned at its initial
 17 point and shall not be APPEND unless the file is positioned so that its endfile record is the next record or at its
 18 terminal point if it has no endfile record.

19 9.10.2.24 READ= specifier in the INQUIRE statement

- 20 1 The *scalar-default-char-variable* in the READ= specifier is assigned the value YES if READ is included in the
 21 set of allowed actions for the file, NO if READ is not included in the set of allowed actions for the file, and
 22 UNKNOWN if the processor is unable to determine whether READ is included in the set of allowed actions for
 23 the file or if the [unit](#) identified by *file-unit-number* is not connected to a file.

24 9.10.2.25 READWRITE= specifier in the INQUIRE statement

- 25 1 The *scalar-default-char-variable* in the READWRITE= specifier is assigned the value YES if READWRITE is
 26 included in the set of allowed actions for the file, NO if READWRITE is not included in the set of allowed actions
 27 for the file, and UNKNOWN if the processor is unable to determine whether READWRITE is included in the
 28 set of allowed actions for the file or if the [unit](#) identified by *file-unit-number* is not connected to a file.

29 9.10.2.26 RECL= specifier in the INQUIRE statement

- 30 1 The *scalar-int-variable* in the RECL= specifier is assigned the value of the record length of a connection for direct
 31 access, or the value of the maximum record length of a connection for sequential access. If the connection is for
 32 formatted input/output, the length is the number of characters for all records that contain only characters of
 33 default kind. If the connection is for unformatted input/output, the length is measured in [file storage units](#). If
 34 there is no connection, the *scalar-int-variable* is assigned the value -1, and if the connection is for stream access,
 35 the *scalar-int-variable* is assigned the value -2.

1 **9.10.2.27 ROUND= specifier in the INQUIRE statement**

2 1 The *scalar-default-char-variable* in the ROUND= specifier is assigned the value UP, DOWN, ZERO, NEAREST,
3 COMPATIBLE, or PROCESSOR_DEFINED, corresponding to the input/output rounding mode in effect for
4 a connection for formatted input/output. If there is no connection or if the connection is not for formatted
5 input/output, the *scalar-default-char-variable* is assigned the value UNDEFINED. The processor shall return the
6 value PROCESSOR_DEFINED only if the behavior of the input/output rounding mode is different from that
7 of the UP, DOWN, ZERO, NEAREST, and COMPATIBLE modes.

8 **9.10.2.28 SEQUENTIAL= specifier in the INQUIRE statement**

9 1 The *scalar-default-char-variable* in the SEQUENTIAL= specifier is assigned the value YES if SEQUENTIAL is
10 included in the set of allowed access methods for the file, NO if SEQUENTIAL is not included in the set of allowed
11 access methods for the file, and UNKNOWN if the processor is unable to determine whether SEQUENTIAL is
12 included in the set of allowed access methods for the file or if the *unit* identified by *file-unit-number* is not
13 connected to a file.

14 **9.10.2.29 SIGN= specifier in the INQUIRE statement**

15 1 The *scalar-default-char-variable* in the SIGN= specifier is assigned the value PLUS, SUPPRESS, or PRO-
16 CESSOR_DEFINED, corresponding to the sign mode in effect for a connection for formatted input/output.
17 If there is no connection, or if the connection is not for formatted input/output, the *scalar-default-char-variable*
18 is assigned the value UNDEFINED.

19 **9.10.2.30 SIZE= specifier in the INQUIRE statement**

20 1 The *scalar-int-variable* in the SIZE= specifier is assigned the size of the file in *file storage units*. If the file size
21 cannot be determined or if the *unit* identified by *file-unit-number* is not connected to a file, the variable is assigned
22 the value -1 .
23 2 For a file that may be connected for stream access, the file size is the number of the highest-numbered *file storage*
24 *unit* in the file.
25 3 For a file that may be connected for sequential or direct access, the file size may be different from the number of
26 *storage units* implied by the data in the records; the exact relationship is processor dependent.

27 **9.10.2.31 STREAM= specifier in the INQUIRE statement**

28 1 The *scalar-default-char-variable* in the STREAM= specifier is assigned the value YES if STREAM is included in
29 the set of allowed access methods for the file, NO if STREAM is not included in the set of allowed access methods
30 for the file, and UNKNOWN if the processor is unable to determine whether STREAM is included in the set of
31 allowed access methods for the file or if the *unit* identified by *file-unit-number* is not connected to a file.

32 **9.10.2.32 UNFORMATTED= specifier in the INQUIRE statement**

33 1 The *scalar-default-char-variable* in the UNFORMATTED= specifier is assigned the value YES if UNFORMAT-
34 TED is included in the set of allowed forms for the file, NO if UNFORMATTED is not included in the set of
35 allowed forms for the file, and UNKNOWN if the processor is unable to determine whether UNFORMATTED is
36 included in the set of allowed forms for the file or if the *unit* identified by *file-unit-number* is not connected to a
37 file.

38 **9.10.2.33 WRITE= specifier in the INQUIRE statement**

39 1 The *scalar-default-char-variable* in the WRITE= specifier is assigned the value YES if WRITE is included in the
40 set of allowed actions for the file, NO if WRITE is not included in the set of allowed actions for the file, and
41 UNKNOWN if the processor is unable to determine whether WRITE is included in the set of allowed actions for
42 the file or if the *unit* identified by *file-unit-number* is not connected to a file.

9.10.3 Inquire by output list

- 1 The *scalar-int-variable* in the IOLENGTH= specifier is assigned the processor-dependent number of **file storage units** that would be required to store the data of the output list in an unformatted file. The value shall be suitable as a **RECL= specifier** in an **OPEN statement** that connects a file for unformatted direct access if data will be read from or written to the file using data transfer statements with an input/output list that specifies transfer of a sequence of objects having the same types, type parameters, and extents, in the same order as the output list in the INQUIRE statement.
- 2 The output list in an INQUIRE statement shall not contain any derived-type list items that require a **defined input/output** procedure as described in subclause 9.6.3. If a derived-type list item appears in the output list, the value returned for the IOLENGTH= specifier assumes that no **defined input/output** procedure will be invoked.

9.11 Error, end-of-record, and end-of-file conditions

9.11.1 Occurrence of input/output conditions

- 1 The set of input/output error conditions is processor dependent. Except as otherwise specified, when an error condition occurs or is detected is processor dependent.
- 2 An end-of-record condition occurs when a nonadvancing **input statement** attempts to transfer data from a position beyond the end of the current record, unless the file is a **stream file** and the current record is at the end of the file (an end-of-file condition occurs instead).
- 3 An end-of-file condition occurs when
 - an endfile record is encountered during the reading of a file connected for sequential access,
 - an attempt is made to read a record beyond the end of an **internal file**, or
 - an attempt is made to read beyond the end of a **stream file**.
- 4 An end-of-file condition may occur at the beginning of execution of an **input statement**. An end-of-file condition also may occur during execution of a formatted **input statement** when more than one record is required by the interaction of the input list and the format. An end-of-file condition also may occur during execution of a stream **input statement**.

9.11.2 Error conditions and the ERR= specifier

- 1 If an error condition occurs during execution of an input/output statement, the position of the file becomes indeterminate.
- 2 If an error condition occurs during execution of an input/output statement that contains neither an ERR= nor IOSTAT= specifier, **error termination** is initiated. If an error condition occurs during execution of an input/output statement that contains either an ERR= specifier or an IOSTAT= specifier then:
 - (1) processing of the input/output list, if any, terminates;
 - (2) if the statement is a **data transfer statement** or the error occurs during a wait operation, all *do-variables* in the statement that initiated the transfer become undefined;
 - (3) if an **IOSTAT= specifier** appears, the *scalar-int-variable* in the **IOSTAT= specifier** becomes defined as specified in 9.11.5;
 - (4) if an **IOMSG= specifier** appears, the *iomsg-variable* becomes defined as specified in 9.11.6;
 - (5) if the statement is a **READ statement** and it contains a **SIZE= specifier**, the *scalar-int-variable* in the **SIZE= specifier** becomes defined as specified in 9.6.2.15;
 - (6) if the statement is a **READ statement** or the error condition occurs in a wait operation for a transfer initiated by a **READ statement**, all input items or namelist group objects in the statement that initiated the transfer become undefined;

- 1 (7) if an ERR= specifier appears, a branch to the statement labeled by the *label* in the ERR= specifier
 2 occurs.

3 9.11.3 End-of-file condition and the END= specifier

4 1 If an end-of-file condition occurs during execution of an input/output statement that contains neither an END=
 5 specifier nor an IOSTAT= specifier, **error termination** is initiated. If an end-of-file condition occurs during
 6 execution of an input/output statement that contains either an END= specifier or an IOSTAT= specifier, and
 7 an error condition does not occur then:

- 8 (1) processing of the input list, if any, terminates;
 9 (2) if the statement is a **data transfer statement** or the end-of-file condition occurs during a wait operation,
 10 all *do-variables* in the statement that initiated the transfer become undefined;
 11 (3) if the statement is an **input statement** or the end-of-file condition occurs during a wait operation
 12 for a transfer initiated by an **input statement**, all input list items or namelist group objects in the
 13 statement that initiated the transfer become undefined;
 14 (4) if the file specified in the **input statement** is an external record file, it is positioned after the endfile
 15 record;
 16 (5) if an **IOSTAT= specifier** appears, the *scalar-int-variable* in the **IOSTAT= specifier** becomes defined
 17 as specified in 9.11.5;
 18 (6) if an **IOMSG= specifier** appears, the *iomsg-variable* becomes defined as specified in 9.11.6;
 19 (7) if an END= specifier appears, a branch to the statement labeled by the *label* in the END= specifier
 20 occurs.

21 9.11.4 End-of-record condition and the EOR= specifier

22 1 If an end-of-record condition occurs during execution of an input/output statement that contains neither an
 23 EOR= specifier nor an IOSTAT= specifier, **error termination** is initiated. If an end-of-record condition occurs
 24 during execution of an input/output statement that contains either an EOR= specifier or an IOSTAT= specifier,
 25 and an error condition does not occur then:

- 26 (1) if the pad mode has the value
 27 (a) YES, the record is padded with blanks to satisfy the **effective item** (9.6.4.5.3) and corresponding
 28 data edit descriptors that require more characters than the record contains,
 29 (b) NO, the input list item becomes undefined;
 30 (2) processing of the input list, if any, terminates;
 31 (3) if the statement is a **data transfer statement** or the end-of-record condition occurs during a wait
 32 operation, all *do-variables* in the statement that initiated the transfer become undefined;
 33 (4) the file specified in the input statement is positioned after the current record;
 34 (5) if an **IOSTAT= specifier** appears, the *scalar-int-variable* in the **IOSTAT= specifier** becomes defined
 35 as specified in 9.11.5;
 36 (6) if an **IOMSG= specifier** appears, the *iomsg-variable* becomes defined as specified in 9.11.6;
 37 (7) if a **SIZE= specifier** appears, the *scalar-int-variable* in the **SIZE= specifier** becomes defined as spe-
 38 cified in (9.6.2.15);
 39 (8) if an **EOR= specifier** appears, a branch to the statement labeled by the *label* in the **EOR= specifier**
 40 occurs.

41 9.11.5 IOSTAT= specifier

42 1 Execution of an input/output statement containing the IOSTAT= specifier causes the *scalar-int-variable* in the
 43 IOSTAT= specifier to become defined with

- 44 • a zero value if neither an error condition, an end-of-file condition, nor an end-of-record condition occurs,

- 1 • the processor-dependent positive integer value of the constant `IOSTAT_INQUIRE_INTERNAL_UNIT`
- 2 from the intrinsic module `ISO_FORTRAN_ENV`(13.9.2) if a `unit` number in an `INQUIRE` statement
- 3 identifies an `internal file`,
- 4 • a processor-dependent positive integer value different from `IOSTAT_INQUIRE_INTERNAL_UNIT` if any
- 5 other error condition occurs,
- 6 • the processor-dependent negative integer value of the constant `IOSTAT_END` (13.9.2.14) from the intrinsic
- 7 module `ISO_FORTRAN_ENV` if an end-of-file condition occurs and no error condition occurs,
- 8 • the processor-dependent negative integer value of the constant `IOSTAT_EOR` (13.9.2.15) from the intrinsic
- 9 module `ISO_FORTRAN_ENV` if an end-of-record condition occurs and no error condition or end-of-file
- 10 condition occurs, or
- 11 • a processor-dependent negative integer value different from `IOSTAT_EOR` and `IOSTAT_END`, if the IO-
- 12 STAT= specifier appears in a `FLUSH` statement and the processor does not support the flush operation for
- 13 the specified unit.

NOTE 9.61

An end-of-file condition can occur only for sequential or stream input and an end-of-record condition can occur only for nonadvancing input.

For example,

```

READ (FMT = "(E8.3)", UNIT = 3, IOSTAT = IOSS) X
IF (IOSS < 0) THEN
  ! Perform end-of-file processing on the file connected to unit 3.
  CALL END_PROCESSING
ELSE IF (IOSS > 0) THEN
  ! Perform error processing
  CALL ERROR_PROCESSING
END IF

```

9.11.6 IOMSG= specifier

- 1 If an error, end-of-file, or end-of-record condition occurs during execution of an input/output statement, *iomsg-variable* is assigned an explanatory message as if by `intrinsic assignment`. If no such condition occurs, the definition status and value of *iomsg-variable* are unchanged.

9.12 Restrictions on input/output statements

- 1 If a `unit`, or a file connected to a `unit`, does not have all of the properties required for the execution of certain input/output statements, those statements shall not refer to the `unit`.
- 2 An input/output statement that is executed while another input/output statement is being executed is a recursive input/output statement. A recursive input/output statement shall not identify an `external unit` that is identified by another input/output statement being executed except that a child `data transfer statement` may identify its parent `data transfer statement external unit`.
- 3 An input/output statement shall not cause the value of any established format specification to be modified.
- 4 A recursive input/output statement shall not modify the value of any `internal unit` except that a recursive `WRITE` statement may modify the `internal unit` identified by that recursive `WRITE` statement.
- 5 The value of a specifier in an input/output statement shall not depend on the definition or evaluation of any other specifier in the *io-control-spec-list* or *inquire-spec-list* in that statement. The value of an *internal-file-variable* or of a `FMT=`, `ID=`, `IOMSG=`, `IOSTAT=`, or `SIZE=` specifier shall not depend on the value of any *input-item* or *io-implied-do do-variable* in the same statement.

- 1 6 The value of any subscript or substring bound of a variable that appears in a specifier in an input/output
2 statement shall not depend on any *input-item*, *io-implied-do do-variable*, or on the definition or evaluation of any
3 other specifier in the *io-control-spec-list* or *inquire-spec-list* in that statement.
- 4 7 In a *data transfer statement*, the variable specified in an *IOSTAT=*, *IOMSG=*, or *SIZE=* specifier, if any, shall
5 not be associated with any entity in the data transfer input/output list (9.6.3) or *namelist-group-object-list*, nor
6 with a *do-variable* of an *io-implied-do* in the data transfer input/output list.
- 7 8 In a *data transfer statement*, if a variable specified in an *IOSTAT=*, *IOMSG=*, or *SIZE=* specifier is an array
8 element reference, its subscript values shall not be affected by the data transfer, the *io-implied-do* processing, or
9 the definition or evaluation of any other specifier in the *io-control-spec-list*.
- 10 9 A variable that may become defined or undefined as a result of its use in a specifier in an *INQUIRE statement*,
11 or any associated entity, shall not appear in another specifier in the same *INQUIRE statement*.

NOTE 9.62

Restrictions on the evaluation of expressions (7.1.4) prohibit certain side effects.

1

(Blank page)

10 Input/output editing

10.1 Format specifications

- 1 A format used in conjunction with a [data transfer statement](#) provides information that directs the editing between the internal representation of data and the characters of a sequence of formatted records.
- 2 A *format* ([9.6.2.2](#)) in a [data transfer statement](#) may refer to a [FORMAT statement](#) or to a character expression that contains a format specification. A format specification provides explicit editing information. The *format* alternatively may be an asterisk (*), which indicates list-directed formatting ([10.10](#)). Namelist formatting ([10.11](#)) may be indicated by specifying a *namelist-group-name* instead of a *format*.

10.2 Explicit format specification methods

10.2.1 FORMAT statement

R1001 *format-stmt* is FORMAT *format-specification*

R1002 *format-specification* is ([*format-items*])
or ([*format-items*,] *unlimited-format-item*)

C1001 (R1001) The *format-stmt* shall be labeled.

- 1 Blank characters may precede the initial left parenthesis of the format specification. Additional blank characters may appear at any point within the format specification, with no effect on the interpretation of the format specification, except within a character string edit descriptor ([10.9](#)).

NOTE 10.1

Examples of FORMAT statements are:

```
5      FORMAT (1PE12.4, I10)
9      FORMAT (I12, /, ' Dates: ', 2 (2I3, I5))
```

10.2.2 Character format specification

- 1 A character expression used as a *format* in a formatted input/output statement shall evaluate to a character string whose leading part is a valid format specification.

NOTE 10.2

The format specification begins with a left parenthesis and ends with a right parenthesis.

- 2 All character positions up to and including the final right parenthesis of the format specification shall be defined at the time the [data transfer statement](#) is executed, and shall not become redefined or undefined during the execution of the statement. Character positions, if any, following the right parenthesis that ends the format specification need not be defined and may contain any character data with no effect on the interpretation of the format specification.
- 3 If the *format* is a character array, it is treated as if all of the elements of the array were specified in array element order and were concatenated. However, if a *format* is a character array element, the format specification shall be entirely within that array element.

NOTE 10.3

If a character constant is used as a *format* in *data transfer statement*, care shall be taken that the value of the character constant is a valid format specification. In particular, if a format specification delimited by apostrophes contains a character constant edit descriptor delimited with apostrophes, two apostrophes shall be written to delimit the edit descriptor and four apostrophes shall be written for each apostrophe that occurs within the edit descriptor. For example, the text:

```
2 ISN'T 3
```

can be written by various combinations of *output statements* and format specifications:

```
WRITE (6, 100) 2, 3
100 FORMAT (1X, I1, 1X, 'ISN'T', 1X, I1)
WRITE (6, '(1X, I1, 1X, ''ISN''''T'', 1X, I1)') 2, 3
WRITE (6, '(A)') ' 2 ISN'T 3'
```

Doubling of internal apostrophes usually can be avoided by using quotation marks to delimit the format specification and doubling of internal quotation marks usually can be avoided by using apostrophes as delimiters.

10.3 Form of a format item list**10.3.1 Syntax**

R1003 *format-items* is *format-item* [[,] *format-item*] ...

R1004 *format-item* is [*r*] *data-edit-desc*
 or *control-edit-desc*
 or *char-string-edit-desc*
 or [*r*] (*format-items*)

R1005 *unlimited-format-item* is * (*format-items*)

R1006 *r* is *int-literal-constant*

C1002 (R1003) The optional comma shall not be omitted except

- between a P edit descriptor and an immediately following F, E, EN, ES, D, or G edit descriptor (10.8.5), possibly preceded by a repeat specification,
- before a slash edit descriptor when the optional repeat specification does not appear (10.8.2),
- after a slash edit descriptor, or
- before or after a colon edit descriptor (10.8.3)

C1003 (R1005) An *unlimited-format-item* shall contain at least one data edit descriptor.

C1004 (R1006) *r* shall be positive.

C1005 (R1006) A kind parameter shall not be specified for *r*.

1 The integer literal constant *r* is called a repeat specification.

10.3.2 Edit descriptors

1 An edit descriptor is a data edit descriptor (*data-edit-desc*), control edit descriptor (*control-edit-desc*), or character string edit descriptor (*char-string-edit-desc*).

- 1 R1007 *data-edit-desc* is I *w* [. *m*]
 2 or B *w* [. *m*]
 3 or O *w* [. *m*]
 4 or Z *w* [. *m*]
 5 or F *w* . *d*
 6 or E *w* . *d* [E *e*]
 7 or EN *w* . *d* [E *e*]
 8 or ES *w* . *d* [E *e*]
 9 or EX *w* . *d* [E *e*]
 10 or G *w* [. *d* [E *e*]]
 11 or L *w*
 12 or A [*w*]
 13 or D *w* . *d*
 14 or DT [*char-literal-constant*] [(*v-list*)]
- 15 R1008 *w* is *int-literal-constant*
- 16 R1009 *m* is *int-literal-constant*
- 17 R1010 *d* is *int-literal-constant*
- 18 R1011 *e* is *int-literal-constant*
- 19 R1012 *v* is *signed-int-literal-constant*
- 20 C1006 (R1008) *w* shall be zero or positive for the I, B, O, Z, D, E, EN, ES, EX, F, and G edit descriptors. *w*
 21 shall be positive for all other edit descriptors.
- 22 C1007 (R1007) For the G edit descriptor, *d* shall be specified if *w* is not zero.
- 23 C1008 (R1007) For the G edit descriptor, *e* shall not be specified if *w* is zero.
- 24 C1009 (R1007) A kind parameter shall not be specified for the *char-literal-constant* in the DT edit descriptor,
 25 or for *w*, *m*, *d*, *e*, and *v*.
- 26 2 An I, B, O, Z, F, E, EN, ES, EX, G, L, A, D, or DT edit descriptor indicates the manner of editing.
- 27 R1013 *control-edit-desc* is *position-edit-desc*
 28 or [*r*] /
 29 or :
 30 or *sign-edit-desc*
 31 or *k* P
 32 or *blank-interp-edit-desc*
 33 or *round-edit-desc*
 34 or *decimal-edit-desc*
- 35 R1014 *k* is *signed-int-literal-constant*
- 36 C1010 (R1014) A kind parameter shall not be specified for *k*.
- 37 3 In *k* P, *k* is called the scale factor.
- 38 R1015 *position-edit-desc* is T *n*
 39 or TL *n*
 40 or TR *n*
 41 or *n* X
- 42 R1016 *n* is *int-literal-constant*
- 43 C1011 (R1016) *n* shall be positive.

1 C1012 (R1016) A kind parameter shall not be specified for *n*.

2 R1017 *sign-edit-desc* is SS
3 or SP
4 or S

5 R1018 *blank-interp-edit-desc* is BN
6 or BZ

7 R1019 *round-edit-desc* is RU
8 or RD
9 or RZ
10 or RN
11 or RC
12 or RP

13 R1020 *decimal-edit-desc* is DC
14 or DP

15 4 A T, TL, TR, X, slash, colon, SS, SP, S, P, BN, BZ, RU, RD, RZ, RN, RC, RP, DC, or DP edit descriptor
16 indicates the manner of editing.

17 R1021 *char-string-edit-desc* is *char-literal-constant*

18 C1013 (R1021) A kind parameter shall not be specified for the *char-literal-constant*.

19 5 Each *rep-char* in a character string edit descriptor shall be capable of representation by the processor.

20 6 A character string edit descriptor provides constant data to be output, and is not valid for input.

21 7 The edit descriptors are without regard to case except within a character string edit descriptor.

22 10.3.3 Fields

23 1 A field is a part of a record that is read on input or written on output when format control encounters a data
24 edit descriptor or a character string edit descriptor. The field width is the size in characters of the field.

25 10.4 Interaction between input/output list and format

26 1 The start of formatted data transfer using a format specification initiates format control (9.6.4.5.3). Each action
27 of format control depends on information jointly provided by the next edit descriptor in the format specification
28 and the next *effective item* in the input/output list, if one exists.

29 2 If an input/output list specifies at least one *effective item*, at least one data edit descriptor shall exist in the
30 format specification.

NOTE 10.4

An empty format specification of the form () can be used only if the input/output list has no *effective item* (9.6.4.5). A zero length character item is an *effective item*, but a zero sized array and an implied DO list with an iteration count of zero is not.

31 3 A format specification is interpreted from left to right. The exceptions are format items preceded by a repeat
32 specification *r*, and format reversion (described below).

33 4 A format item preceded by a repeat specification is processed as a list of *r* items, each identical to the format
34 item but without the repeat specification and separated by commas.

NOTE 10.5

An omitted repeat specification is treated in the same way as a repeat specification whose value is one.

- 1 5 To each data edit descriptor interpreted in a format specification, there corresponds one **effective item** specified by
 2 the input/output list (9.6.3), except that an input/output list item of type complex requires the interpretation of
 3 two F, E, EN, ES, D, or G edit descriptors. For each control edit descriptor or character edit descriptor, there is
 4 no corresponding item specified by the input/output list, and format control communicates information directly
 5 with the record.
- 6 6 Whenever format control encounters a data edit descriptor in a format specification, it determines whether
 7 there is a corresponding **effective item** specified by the input/output list. If there is such an item, it transmits
 8 appropriately edited information between the item and the record, and then format control proceeds. If there is
 9 no such item, format control terminates.
- 10 7 If format control encounters a colon edit descriptor in a format specification and another effective item is not
 11 specified, format control terminates.
- 12 8 If format control encounters the rightmost parenthesis of an unlimited format item, control reverts to the leftmost
 13 parenthesis of that unlimited format item. This reversion of format control has no effect on the changeable modes
 14 (9.5.2).
- 15 9 If format control encounters the rightmost parenthesis of a complete format specification and another effective
 16 item is not specified, format control terminates. However, if another effective item is specified, format control
 17 then reverts to the beginning of the format item terminated by the last preceding right parenthesis that is not
 18 part of a DT edit descriptor. If there is no such preceding right parenthesis, format control reverts to the first
 19 left parenthesis of the format specification. If any reversion occurs, the reused portion of the format specification
 20 shall contain at least one data edit descriptor. If format control reverts to a parenthesis that is preceded by a
 21 repeat specification, the repeat specification is reused. Reversion of format control, of itself, has no effect on
 22 the **changeable modes**. The file is positioned in a manner identical to the way it is positioned when a slash edit
 23 descriptor is processed (10.8.2).

NOTE 10.6

Example: The format specification:

```
10 FORMAT (1X, 2(F10.3, I5))
```

with an output list of

```
WRITE (10,10) 10.1, 3, 4.7, 1, 12.4, 5, 5.2, 6
```

produces the same output as the format specification:

```
10 FORMAT (1X, F10.3, I5, F10.3, I5/F10.3, I5, F10.3, I5)
```

NOTE 10.7

The effect of an **unlimited-format-item** is as if its enclosed list were preceded by a very large repeat count. There is no file positioning implied by **unlimited-format-item** reversion. This can be used to write what is commonly called a comma separated value record.

For example,

```
WRITE( 10, '( "IARRAY =", *( I0, :, ",") )') IARRAY
```

produces a single record with a header and a comma separated list of integer values.

10.5 Positioning by format control

- 1 After each data edit descriptor or character string edit descriptor is processed, the file is positioned after the last character read or written in the current record.
- 2 After each T, TL, TR, or X edit descriptor is processed, the file is positioned as described in 10.8.1.1. After each slash edit descriptor is processed, the file is positioned as described in 10.8.2.
- 3 During formatted stream output, processing of an A edit descriptor can cause file positioning to occur (10.7.4).
- 4 If format control reverts as described in 10.4, the file is positioned in a manner identical to the way it is positioned when a slash edit descriptor is processed (10.8.2).
- 5 During a read operation, any unprocessed characters of the current record are skipped whenever the next record is read.

10.6 Decimal symbol

- 1 The [decimal symbol](#) is the character that separates the whole and fractional parts in the decimal representation of a real number in an internal or [external](#) file. When the decimal edit mode is POINT, the [decimal symbol](#) is a decimal point. When the decimal edit mode is COMMA, the [decimal symbol](#) is a comma.
- 2 If the decimal edit mode is COMMA during list-directed input/output, the character used as a value separator is a semicolon in place of a comma.

10.7 Data edit descriptors

10.7.1 Purpose of data edit descriptors

- 1 Data edit descriptors cause the conversion of data to or from its internal representation; during formatted stream output, the A data edit descriptor may also cause file positioning. On input, the specified variable becomes defined unless an error condition, an end-of-file condition, or an end-of-record condition occurs. On output, the specified expression is evaluated.
- 2 During input from a Unicode file,
 - characters in the record that correspond to an [ASCII character](#) variable shall have a position in the [ISO 10646 character collating sequence](#) of 127 or less, and
 - characters in the record that correspond to a default character variable shall be representable as default characters.
- 3 During input from a non-Unicode file,
 - characters in the record that correspond to a character variable shall have the kind of the character variable, and
 - characters in the record that correspond to a numeric or logical variable shall be default characters.
- 4 During output to a Unicode file, all characters transmitted to the record are of [ISO 10646 character](#) kind. If a character input/output list item or character string edit descriptor contains a character that is not representable as an [ISO 10646 character](#), the result is processor dependent.
- 5 During output to a non-Unicode file, characters transmitted to the record as a result of processing a character string edit descriptor or as a result of evaluating a numeric, logical, or default character data entity, are of default kind.

10.7.2 Numeric editing

10.7.2.1 General rules

1 The I, B, O, Z, F, E, EN, ES, EX, D, and G edit descriptors may be used to specify the input/output of integer, real, and complex data. The following general rules apply.

- (1) On input, leading blanks are not significant. When the input field is not an IEEE exceptional specification or hexadecimal-significand number (10.7.2.3.2), the interpretation of blanks, other than leading blanks, is determined by the blank interpretation mode (10.8.6). Plus signs may be omitted. A field containing only blanks is considered to be zero.
- (2) On input, with F, E, EN, ES, EX, D, and G editing, a [decimal symbol](#) appearing in the input field overrides the portion of an edit descriptor that specifies the [decimal symbol](#) location. The input field may have more digits than the processor uses to approximate the value of the datum.
- (3) On output with I, F, E, EN, ES, EX, D, and G editing, the representation of a positive or zero internal value in the field may be prefixed with a plus sign, as controlled by the S, SP, and SS edit descriptors or the processor. The representation of a negative internal value in the field shall be prefixed with a minus sign.
- (4) On output, the representation is right justified in the field. If the number of characters produced by the editing is smaller than the field width, leading blanks are inserted in the field.
- (5) On output, if an exponent exceeds its specified or implied width using the E, EN, ES, EX, D, or G edit descriptor, or the number of characters produced exceeds the field width, the processor shall fill the entire field of width *w* with asterisks. However, the processor shall not produce asterisks if the field width is not exceeded when optional characters are omitted.

NOTE 10.8

When the sign mode is PLUS, a plus sign is not optional.

- (6) On output, with I, B, O, Z, D, E, EN, ES, EX, F, and G editing, the specified value of the field width *w* may be zero. In such cases, the processor selects the smallest positive actual field width that does not result in a field filled with asterisks. The specified value of *w* shall not be zero on input.
- (7) On output of a real zero value, the digits in the exponent field shall all be zero.

10.7.2.2 Integer editing

1 The *Iw* and *Iw.m* edit descriptors indicate that the field to be edited occupies *w* positions, except when *w* is zero. When *w* is zero, the processor selects the field width. On input, *w* shall not be zero. The specified input/output list item shall be of type integer. The G, B, O, and Z edit descriptor also may be used to edit integer data (10.7.5.2.1, 10.7.2.4).

2 On input, *m* has no effect.

3 In the standard form of the input field for the I edit descriptor, the character string is a *signed-digit-string* (R410), except for the interpretation of blanks. If the input field does not have the standard form and is not acceptable to the processor, an error condition occurs.

4 The output field for the *Iw* edit descriptor consists of zero or more leading blanks followed by a minus sign if the internal value is negative, or an optional plus sign otherwise, followed by the magnitude of the internal value as a *digit-string* without leading zeros.

NOTE 10.9

A *digit-string* always consists of at least one digit.

5 The output field for the *Iw.m* edit descriptor is the same as for the *Iw* edit descriptor, except that the *digit-string* consists of at least *m* digits. If necessary, sufficient leading zeros are included to achieve the minimum of *m* digits. The value of *m* shall not exceed the value of *w*, except when *w* is zero. If *m* is zero and the internal value is zero,

1 the output field consists of only blank characters, regardless of the sign control in effect. When m and w are both
2 zero, and the internal value is zero, one blank character is produced.

3 10.7.2.3 Real and complex editing

4 10.7.2.3.1 General

5 1 The F, E, EN, ES, and D edit descriptors specify the editing of real and complex data. An input/output list
6 item corresponding to an F, E, EN, ES, or D edit descriptor shall be real or complex. The G, B, O, and Z edit
7 descriptors also may be used to edit real and complex data (10.7.5.2.2, 10.7.2.4).

8 10.7.2.3.2 F editing

9 1 The F $w.d$ edit descriptor indicates that the field occupies w positions, except when w is zero in which case the
10 processor selects the field width. The fractional part of the field consists of d digits. On input, w shall not be
11 zero.

12 2 A lower-case letter is equivalent to the corresponding upper-case letter in an IEEE exceptional specification or
13 the exponent in a numeric input field.

14 3 The standard form of the input field is an IEEE exceptional specification, a hexadecimal-significant number, or
15 consists of a mantissa optionally followed by an exponent. The form of the mantissa is an optional sign, followed
16 by a string of one or more digits optionally containing a decimal symbol, including any blanks interpreted as
17 zeros. The d has no effect on input if the input field contains a decimal symbol. If the decimal symbol is omitted,
18 the rightmost d digits of the string, with leading zeros assumed if necessary, are interpreted as the fractional part
19 of the value represented. The string of digits may contain more digits than a processor uses to approximate the
20 value. The form of the exponent is one of the following:

- 21 • a *sign* followed by a *digit-string*;
- 22 • the letter E followed by zero or more blanks, followed by a *signed-digit-string*;
- 23 • the letter D followed by zero or more blanks, followed by a *signed-digit-string*.

24 4 An exponent containing a D is processed identically to an exponent containing an E.

NOTE 10.10

If the input field does not contain an exponent, the effect is as if the basic form were followed by an exponent with a value of $-k$, where k is the established scale factor (10.8.5).

25 5 An input field that is an IEEE exceptional specification consists of optional blanks, followed by either

- 26 • an optional sign, followed by the string 'INF' or the string 'INFINITY', or
- 27 • an optional sign, followed by the string 'NAN', optionally followed by zero or more alphanumeric characters
28 enclosed in parentheses,

29 optionally followed by blanks.

30 6 The value specified by 'INF' or 'INFINITY' is an IEEE infinity; this form shall not be used if the processor does
31 not support IEEE infinities for the input variable. The value specified by 'NAN' is an IEEE NaN; this form shall
32 not be used if the processor does not support IEEE NaNs for the input variable. The NaN value is a quiet NaN if
33 the only nonblank characters in the field are 'NAN' or 'NAN()'; otherwise, the NaN value is processor dependent.
34 The interpretation of a sign in a NaN input field is processor dependent.

35 7 An input field that is a hexadecimal-significant number consists of an optional sign, followed by the hexadecimal
36 indicator which is the digit 0 immediately followed by the letter X, followed by a hexadecimal significant followed
37 by a hexadecimal exponent. A hexadecimal significant is a string of one or more hexadecimal characters optionally
38 containing a decimal symbol. The decimal symbol indicates the position of the hexadecimal point; if no decimal
39 symbol appears, the hexadecimal point implicitly follows the last hexadecimal symbol. A hexadecimal exponent

- 1 is the letter P followed by a (decimal) *signed-digit-string*. Embedded blanks are not permitted in a hexadecimal-
 2 significand number. The value is equal to the significand multiplied by two raised to the power of the exponent,
 3 negated if the optional sign is minus.
- 4 8 If the input field does not have one of the standard forms, and is not acceptable to the processor, an error
 5 condition occurs.
- 6 9 For an internal value that is an IEEE infinity, the output field consists of blanks, if necessary, followed by a minus
 7 sign for negative infinity or an optional plus sign otherwise, followed by the letters 'Inf' or 'Infinity', right justified
 8 within the field. The minimum field width required for output of the form 'Inf' is 3 if no sign is produced, and
 9 4 otherwise. The minimum field width required for output of the form 'Infinity' is 8 if no sign is produced, and
 10 9 otherwise. If w is greater than or equal to the minimum required for the form 'Infinity', the form 'Infinity' is
 11 output. If w is zero or w is less than the minimum required for the form 'Infinity' and greater than or equal to
 12 the minimum required for the form 'Inf', the form 'Inf' is output. Otherwise (w is greater than zero but less than
 13 the minimum required for any form), the field is filled with asterisks.
- 14 10 For an internal value that is an IEEE NaN, the output field consists of blanks, if necessary, followed by the
 15 letters 'NaN' and optionally followed by one to $w-5$ alphanumeric processor-dependent characters enclosed in
 16 parentheses, right justified within the field. If w is greater than zero and less than 3, the field is filled with
 17 asterisks. If w is zero, the output field is 'NaN'.

NOTE 10.11

The processor-dependent characters following 'NaN' might convey additional information about that particular NaN.

- 18 11 For an internal value that is neither an IEEE infinity nor a NaN, the output field consists of blanks, if necessary,
 19 followed by a minus sign if the internal value is negative, or an optional plus sign otherwise, followed by a string
 20 of digits that contains a *decimal symbol* and represents the magnitude of the internal value, as modified by the
 21 established scale factor and rounded (10.7.2.3.8) to d fractional digits. Leading zeros are not permitted except
 22 for an optional zero immediately to the left of the *decimal symbol* if the magnitude of the value in the output
 23 field is less than one. The optional zero shall appear if there would otherwise be no digits in the output field.

10.7.2.3.3 E and D editing

- 24 1 The $Ew.d$, $Dw.d$, and $Ew.d Ee$ edit descriptors indicate that the external field occupies w positions, except when
 25 w is zero in which case the processor selects the field width. The fractional part of the field contains d digits,
 26 unless a scale factor greater than one is in effect. If e is positive the exponent part contains e digits, otherwise it
 27 contains the minimum number of digits required to represent the exponent value. The e has no effect on input.
 28
- 29 2 The form and interpretation of the input field is the same as for $Fw.d$ editing (10.7.2.3.2).
- 30 3 For an internal value that is an IEEE infinity or NaN, the form of the output field is the same as for $Fw.d$.
- 31 4 For an internal value that is neither an IEEE infinity nor a NaN, the form of the output field for a scale factor
 32 of zero is
 33
$$[\pm] [0].x_1x_2 \dots x_d exp$$

 34 where:
- 35 • \pm signifies a plus sign or a minus sign;
 - 36 • $.$ signifies a *decimal symbol* (10.6);
 - 37 • $x_1x_2 \dots x_d$ are the d most significant digits of the internal value after rounding (10.7.2.3.8);
 - 38 • exp is a decimal exponent having one of the forms specified in table 10.1.

Table 10.1: **E and D exponent forms**

Edit Descriptor	Absolute Value of Exponent	Form of Exponent ¹
<i>Ew.d</i>	$ exp \leq 99$	$E\pm z_1 z_2$ or $\pm 0z_1 z_2$
	$99 < exp \leq 999$	$\pm z_1 z_2 z_3$
<i>Ew.d Ee</i> with $e > 0$	$ exp \leq 10^e - 1$	$E\pm z_1 z_2 \dots z_e$
<i>Ew.d E0</i>	any	$E\pm z_1 z_2 \dots z_s$
<i>Dw.d</i>	$ exp \leq 99$	$D\pm z_1 z_2$ or $E\pm z_1 z_2$ or $\pm 0z_1 z_2$
	$99 < exp \leq 999$	$\pm z_1 z_2 z_3$

(1) where each z is a digit, and s is the minimum number of digits required to represent the exponent.

- 1 5 The sign in the exponent is produced. A plus sign is produced if the exponent value is zero.
- 2 6 The scale factor k controls the decimal normalization (10.3.2, 10.8.5). If $-d < k \leq 0$, the output field contains
- 3 exactly $|k|$ leading zeros and $d - |k|$ significant digits after the decimal symbol. If $0 < k < d + 2$, the output field
- 4 contains exactly k significant digits to the left of the decimal symbol and $d - k + 1$ significant digits to the right
- 5 of the decimal symbol. Other values of k are not permitted.

6 **10.7.2.3.4 EN editing**

- 7 1 The EN edit descriptor produces an output field in the form of a real number in engineering notation such that
- 8 the decimal exponent is divisible by three and the absolute value of the significand (R415) is greater than or
- 9 equal to 1 and less than 1000, except when the output value is zero. The scale factor has no effect on output.
- 10 2 The forms of the edit descriptor are *ENw.d* and *ENw.d Ee* indicating that the external field occupies w positions,
- 11 except when w is zero in which case the processor selects the field width. The fractional part of the field contains
- 12 d digits. If e is positive the exponent part contains e digits, otherwise it contains the minimum number of digits
- 13 required to represent the exponent value.
- 14 3 The form and interpretation of the input field is the same as for *Fw.d* editing (10.7.2.3.2).
- 15 4 For an internal value that is an IEEE infinity or NaN, the form of the output field is the same as for *Fw.d*.
- 16 5 For an internal value that is neither an IEEE infinity nor a NaN, the form of the output field is
- 17 $[\pm] yyy . x_1 x_2 \dots x_d exp$
- 18 where:
 - 19 • \pm signifies a plus sign or a minus sign;
 - 20 • yyy are the 1 to 3 decimal digits representative of the most significant digits of the internal value after
 - 21 rounding (10.7.2.3.8);
 - 22 • yyy is an integer such that $1 \leq yyy < 1000$ or, if the output value is zero, $yyy = 0$;
 - 23 • $.$ signifies a decimal symbol (10.6);
 - 24 • $x_1 x_2 \dots x_d$ are the d next most significant digits of the internal value after rounding;
 - 25 • exp is a decimal exponent, divisible by three, having one of the forms specified in table 10.2.

Table 10.2: **EN exponent forms**

Edit Descriptor	Absolute Value of Exponent	Form of Exponent ¹
<i>ENw.d</i>	$ exp \leq 99$	$E\pm z_1 z_2$ or $\pm 0z_1 z_2$
	$99 < exp \leq 999$	$\pm z_1 z_2 z_3$
<i>ENw.d Ee</i> with $e > 0$	$ exp \leq 10^e - 1$	$E\pm z_1 z_2 \dots z_e$
<i>ENw.d E0</i>	any	$E\pm z_1 z_2 \dots z_s$

EN exponent forms (cont.)

Edit Descriptor	Absolute Value of Exponent	Form of Exponent ¹
(1) where each z is a digit, and s is the minimum number of digits required to represent the exponent.		

6 The sign in the exponent is produced. A plus sign is produced if the exponent value is zero.

NOTE 10.12

Examples:

Internal Value	Output field Using SS, EN12.3
6.421	6.421E+00
-.5	-500.000E-03
.00217	2.170E-03
4721.3	4.721E+03

10.7.2.3.5 ES editing

1 The ES edit descriptor produces an output field in the form of a real number in scientific notation such that the absolute value of the significand (R415) is greater than or equal to 1 and less than 10, except when the output value is zero. The scale factor has no effect on output.

2 The forms of the edit descriptor are $ESw.d$ and $ESw.d Ee$ indicating that the external field occupies w positions, except when w is zero in which case the processor selects the field width. The fractional part of the field contains d digits. If e is positive the exponent part contains e digits, otherwise it contains the minimum number of digits required to represent the exponent value.

3 The form and interpretation of the input field is the same as for $Fw.d$ editing (10.7.2.3.2).

4 For an internal value that is an IEEE infinity or NaN, the form of the output field is the same as for $Fw.d$.

5 For an internal value that is neither an IEEE infinity nor a NaN, the form of the output field is $[\pm] y . x_1x_2 \dots x_d exp$ where:

- \pm signifies a plus sign or a minus sign;
- y is a decimal digit representative of the most significant digit of the internal value after rounding (10.7.2.3.8);
- $.$ signifies a decimal symbol (10.6);
- $x_1x_2 \dots x_d$ are the d next most significant digits of the internal value after rounding;
- exp is a decimal exponent having one of the forms specified in table 10.3.

Table 10.3: ES exponent forms

Edit Descriptor	Absolute Value of Exponent	Form of Exponent ¹
$ESw.d$	$ exp \leq 99$	$E\pm z_1z_2$ or $\pm 0z_1z_2$
	$99 < exp \leq 999$	$\pm z_1z_2z_3$
$ESw.d Ee$ with $e > 0$	$ exp \leq 10^e - 1$	$E\pm z_1z_2 \dots z_e$
$ESw.d E0$	any	$E\pm z_1z_2 \dots z_s$
(1) where each z is a digit, and s is the minimum number of digits required to represent the exponent.		

1 6 The sign in the exponent is produced. A plus sign is produced if the exponent value is zero.

NOTE 10.13

Examples:

Internal Value	Output field Using SS, ES12.3
6.421	6.421E+00
-.5	-5.000E-01
.00217	2.170E-03
4721.3	4.721E+03

2 **10.7.2.3.6 EX editing**

3 1 The EX edit descriptor produces an output field in the form of a hexadecimal-significand number.

4 2 The EX $w.d$ and EX $w.dEe$ edit descriptors indicate that the external field occupies w positions, except when w
5 is zero in which case the processor selects the field width. The fractional part of the field contains d hexadecimal
6 digits, except when d is zero in which case the processor selects the number of hexadecimal digits to be the
7 minimum required so that the output field is equal to the internal value; d shall not be zero if the radix of the
8 internal value is not a power of two. The hexadecimal point, represented by a decimal symbol, appears after
9 the first hexadecimal digit. For the form EX $w.d$, and for EX $w.dE0$, the exponent part contains the minimum
10 number of digits needed to represent the exponent; otherwise the exponent contains e digits. The e has no effect
11 on input. The scale factor has no effect on output.

12 3 The form and interpretation of the input field is the same as for F $w.d$ editing (10.7.2.3.2).

13 4 For an internal value that is an IEEE infinity or NaN, the form of the output field is the same as for F $w.d$.

14 5 For an internal value that is neither an IEEE infinity nor a NaN, the form of the output field is

15 $[\pm] x_0 . x_1 x_2 \dots exp$

16 where:

- 17 • \pm signifies a plus sign or a minus sign;
- 18 • $.$ signifies a decimal symbol (10.6);
- 19 • $x_0 x_1 x_2 \dots$ are the most significant hexadecimal digits of the internal value, after rounding if d is not zero
20 (10.7.2.3.8);
- 21 • exp is a binary exponent expressed as a decimal integer; for EX $w.d$ and EX $w.dE0$, the form is P $\pm z_1 \dots z_n$,
22 where n is the minimum number of digits needed to represent exp , and for EX $w.dEe$ with e greater than
23 zero the form is P $\pm z_1 \dots z_e$.

24 6 The sign in the exponent is produced. A plus sign is produced if the exponent value is zero.

NOTE 10.14

Examples:

Internal value	Edit descriptor	Possible output with SS in effect
1.375	EX0.1	0X1.6P+0
-15.625	EX14.4E3	-0X1.F400P+003
1048580.0	EX0.0	0X1.00003P+20

25 **10.7.2.3.7 Complex editing**

26 1 A complex datum consists of a pair of separate real data. The editing of a scalar datum of complex type is
27 specified by two edit descriptors each of which specifies the editing of real data. The first edit descriptor specifies
28 the editing for the real part; the second specifies it for the imaginary part. The two edit descriptors may be
29 different. Control and character string edit descriptors may be processed between the edit descriptor for the real
30 part and the edit descriptor for the imaginary part.

10.7.2.3.8 Input/output rounding mode

- 1 The input/output rounding mode can be specified by an **OPEN statement** (9.5.2), a **data transfer statement** (9.6.2.13), or an edit descriptor (10.8.7).
- 2 In what follows, the term “decimal value” means the exact decimal number as given by the character string, while the term “internal value” means the number actually stored in the processor. For example, in dealing with the decimal constant 0.1, the decimal value is the mathematical quantity 1/10, which has no exact representation in binary form. Formatted output of real data involves conversion from an internal value to a decimal value; formatted input involves conversion from a decimal value to an internal value.
- 3 When the input/output rounding mode is UP, the value resulting from conversion shall be the smallest representable value that is greater than or equal to the original value. When the input/output rounding mode is DOWN, the value resulting from conversion shall be the largest representable value that is less than or equal to the original value. When the input/output rounding mode is ZERO, the value resulting from conversion shall be the value closest to the original value and no greater in magnitude than the original value. When the input/output rounding mode is NEAREST, the value resulting from conversion shall be the closer of the two nearest representable values if one is closer than the other. If the two nearest representable values are equidistant from the original value, it is processor dependent which one of them is chosen. When the input/output rounding mode is COMPATIBLE, the value resulting from conversion shall be the closer of the two nearest representable values or the value away from zero if halfway between them. When the input/output rounding mode is PROCESSOR_DEFINED, rounding during conversion shall be a processor-dependent default mode, which may correspond to one of the other modes.
- 4 On processors that support IEEE rounding on conversions (14.4), NEAREST shall correspond to round to nearest, as specified in ISO/IEC/IEEE 60559:2011.

NOTE 10.15

On processors that support IEEE rounding on conversions, the input/output rounding modes COMPATIBLE and NEAREST will produce the same results except when the datum is halfway between the two representable values. In that case, NEAREST will pick the even value, but COMPATIBLE will pick the value away from zero. The input/output rounding modes UP, DOWN, and ZERO have the same effect as those specified in ISO/IEC/IEEE 60559:2011 for round toward $+\infty$, round toward $-\infty$, and round toward 0, respectively.

10.7.2.4 B, O, and Z editing

- 1 The **Bw**, **Bw.m**, **Ow**, **Ow.m**, **w**, and **Zw.m** edit descriptors indicate that the field to be edited occupies *w* positions, except when *w* is zero. When *w* is zero, the processor selects the field width. On input, *w* shall not be zero. The corresponding input/output list item shall be of type integer, real, or complex.
- 2 On input, *m* has no effect.
- 3 In the standard form of the input field for the B, O, and Z edit descriptors the character string consists of binary, octal, or hexadecimal digits (as in R465, R466, R467) in the respective input field. The lower-case hexadecimal digits a through f in a hexadecimal input field are equivalent to the corresponding upper-case hexadecimal digits. If the input field does not have the standard form, and is not acceptable to the processor, an error condition occurs.
- 4 The value is INT (X) if the input list item is of type integer and REAL (X) if the input list item is of type real or complex, where X is a *boz-literal-constant* that specifies the same bit sequence as the digits of the input field.
- 5 The output field for the **Bw**, **Ow**, and **Zw** descriptors consists of zero or more leading blanks followed by the internal value in a form identical to the digits of a binary, octal, or hexadecimal constant, respectively, that specifies the same bit sequence but without leading zero bits.

NOTE 10.16

A binary, octal, or hexadecimal constant always consists of at least one digit or hexadecimal digit.

1 R1022 *hex-digit-string* is *hex-digit* [*hex-digit*] ...

2 6 The output field for the *Bw.m*, *Ow.m*, and *Zw.m* edit descriptor is the same as for the *Bw*, *Ow*, and *Zw* edit
3 descriptor, except that the *digit-string* or *hex-digit-string* consists of at least *m* digits. If necessary, sufficient
4 leading zeros are included to achieve the minimum of *m* digits. The value of *m* shall not exceed the value of *w*,
5 except when *w* is zero. If *m* is zero and the internal value consists of all zero bits, the output field consists of
6 only blank characters. When *m* and *w* are both zero, and the internal value consists of all zero bits, one blank
7 character is produced.

8 10.7.3 Logical editing

- 9 1 The *Lw* edit descriptor indicates that the field occupies *w* positions. The specified input/output list item shall
10 be of type logical. The *G* edit descriptor also may be used to edit logical data (10.7.5.3).
- 11 2 The standard form of the input field consists of optional blanks, optionally followed by a period, followed by a *T*
12 for true or *F* for false. The *T* or *F* may be followed by additional characters in the field, which are ignored. If the
13 input field does not have the standard form, and is not acceptable to the processor, an error condition occurs.
- 14 3 A lower-case letter is equivalent to the corresponding upper-case letter in a logical input field.

NOTE 10.17

The logical constants *.TRUE.* and *.FALSE.* are acceptable input forms.

- 15 4 The output field consists of *w*−1 blanks followed by a *T* or *F*, depending on whether the internal value is true or
16 false, respectively.

17 10.7.4 Character editing

- 18 1 The *A[w]* edit descriptor is used with an input/output list item of type character. The *G* edit descriptor also may
19 be used to edit character data (10.7.5.4). The kind type parameter of all characters transferred and converted
20 under control of one *A* or *G* edit descriptor is implied by the kind of the corresponding list item.
- 21 2 If a field width *w* is specified with the *A* edit descriptor, the field consists of *w* characters. If a field width *w* is
22 not specified with the *A* edit descriptor, the number of characters in the field is the length of the corresponding
23 list item, regardless of the value of the kind type parameter.
- 24 3 Let *len* be the length of the input/output list item. If the specified field width *w* for an *A* edit descriptor
25 corresponding to an input item is greater than or equal to *len*, the rightmost *len* characters will be taken from the
26 input field. If the specified field width *w* is less than *len*, the *w* characters will appear left justified with *len*−*w*
27 trailing blanks in the internal value.
- 28 4 If the specified field width *w* for an *A* edit descriptor corresponding to an output item is greater than *len*, the
29 output field will consist of *w*−*len* blanks followed by the *len* characters from the internal value. If the specified
30 field width *w* is less than or equal to *len*, the output field will consist of the leftmost *w* characters from the internal
31 value.

NOTE 10.18

For nondefault character kinds, the blank padding character is processor dependent.

- 32 5 If the file is connected for stream access, the output may be split across more than one record if it contains
33 newline characters. A newline character is a nonblank character returned by the intrinsic function *NEW_LINE*.
34 Beginning with the first character of the output field, each character that is not a newline is written to the current
35 record in successive positions; each newline character causes file positioning at that point as if by slash editing

1 (the current record is terminated at that point, a new empty record is created following the current record, this
 2 new record becomes the last and current record of the file, and the file is positioned at the beginning of this new
 3 record).

NOTE 10.19

If the intrinsic function `NEW_LINE` returns a blank character for a particular character kind, then the processor does not support using a character of that kind to cause record termination in a formatted stream file.

4 10.7.5 Generalized editing

5 10.7.5.1 Overview

6 1 The `Gw`, `Gw.d` and `Gw.d Ee` edit descriptors are used with an input/output list item of any intrinsic type. When
 7 `w` is nonzero, these edit descriptors indicate that the external field occupies `w` positions. For real or complex
 8 data the fractional part consists of a maximum of `d` digits and the exponent part consists of `e` digits. When these
 9 edit descriptors are used to specify the input/output of integer, logical, or character data, `d` and `e` have no effect.
 10 When `w` is zero the processor selects the field width. On input, `w` shall not be zero.

11 10.7.5.2 Generalized numeric editing

12 1 When used to specify the input/output of integer, real, and complex data, the `Gw`, `Gw.d` and `Gw.d Ee` edit
 13 descriptors follow the general rules for numeric editing (10.7.2).

NOTE 10.20

The `Gw.d Ee` edit descriptor follows any additional rules for the `Ew.d Ee` edit descriptor.

14 10.7.5.2.1 Generalized integer editing

15 1 When used to specify the input/output of integer data, the `Gw.d` and `Gw.d Ee` edit descriptors follow the rules
 16 for the `Iw` edit descriptor (10.7.2.2), except that `w` shall not be zero. When used to specify the output of integer
 17 data, the `G0` and `G0.d` edit descriptors follow the rules for the `I0` edit descriptor.

18 10.7.5.2.2 Generalized real and complex editing

- 19 1 The form and interpretation of the input field is the same as for `Fw.d` editing (10.7.2.3.2).
- 20 2 If `d` is zero, `kPEw.0` or `kPEw.0Ee` editing is used for `Gw.0` editing or `Gw.0Ee` editing respectively.
- 21 3 When used to specify the output of real or complex data that is not an IEEE infinity or NaN, the `G0` and `G0.d`
 22 edit descriptors follow the rules for the `Gw.dEe` edit descriptor, except that any leading or trailing blanks are
 23 removed. Reasonable processor-dependent values of `w`, `d` (if not specified), and `e` are used with each output value.
- 24 4 For an internal value that is an IEEE infinity or NaN, the form of the output field for the `Gw.d` and `Gw.d Ee`
 25 edit descriptors is the same as for `Fw.d`, and the form of the output field for the `G0` and `G0.d` edit descriptors is
 26 the same as for `F0.0`.
- 27 5 Otherwise, the method of representation in the output field depends on the magnitude of the internal value
 28 being edited. If the internal value is zero, let s be one. If the internal value is a number other than zero, let N
 29 be the decimal value that is the result of converting the internal value to `d` significant digits according to the
 30 input/output rounding mode and let s be the integer such that $10^{s-1} \leq |N| < 10^s$. If $s < 0$ or $s > d$, `kPEw.d` or
 31 `kPEw.dEe` editing is used for `Gw.d` editing or `Gw.dEe` editing respectively, where k is the scale factor (10.8.5).
 32 If $0 \leq s \leq d$, the scale factor has no effect and `F(w-n).(d-s),n('b')` editing is used where b is a blank and n is
 33 4 for `Gw.d` editing, $e+2$ for `Gw.dEe` editing if $e > 0$, and 4 for `Gw.dE0` editing.
- 34 6 The value of $w-n$ shall be positive.

NOTE 10.21

The scale factor has no effect on output unless the magnitude of the datum to be edited is outside the range that permits effective use of F editing.

1 **10.7.5.3 Generalized logical editing**

2 1 When used to specify the input/output of logical data, the *Gw.d* and *Gw.d Ee* edit descriptors follow the rules for
 3 the *Lw* edit descriptor (10.7.3). When used to specify the output of logical data, the *G0* and *G0.d* edit descriptors
 4 follow the rules for the *L1* edit descriptor.

5 **10.7.5.4 Generalized character editing**

6 1 When used to specify the input/output of character data, the *Gw.d* and *Gw.d Ee* edit descriptors follow the rules
 7 for the *Aw* edit descriptor (10.7.4). When used to specify the output of character data, the *G0* and *G0.d* edit
 8 descriptors follow the rules for the *A* edit descriptor with no field width.

9 **10.7.6 User-defined derived-type editing**

10 1 The DT edit descriptor specifies that a user-provided procedure shall be used instead of the processor's default
 11 input/output formatting for processing a list item of derived type.

12 2 The DT edit descriptor may include a character literal constant. The character value "DT" concatenated with the
 13 character literal constant is passed to the [defined input/output](#) procedure as the *iotype* argument (9.6.4.8). The
 14 *v* values of the edit descriptor are passed to the [defined input/output](#) procedure as the *v_list* array argument.

NOTE 10.22

For the edit descriptor DT'Link List'(10, 4, 2), *iotype* is "DTLink List" and *v_list* is [10, 4, 2].

15 3 If a derived-type variable or value corresponds to a DT edit descriptor, there shall be an accessible [interface](#) to
 16 a corresponding [defined input/output](#) procedure for that derived type (9.6.4.8). A DT edit descriptor shall not
 17 correspond to a list item that is not of a derived type.

18 **10.8 Control edit descriptors**

19 **10.8.1 Position edit descriptors**

20 **10.8.1.1 Position editing**

21 1 The position edit descriptors T, TL, TR, and X, specify the position at which the next character will be transmit-
 22 ted to or from the record. If any character skipped by a position edit descriptor is of type nondefault character,
 23 and the *unit* is a default character [internal file](#) or an [external](#) non-Unicode file, the result of that position editing
 24 is processor dependent.

25 2 On input, if the position specified by a position edit descriptor is before the current position, portions of a record
 26 can be processed more than once, possibly with different editing.

27 3 On input, a position beyond the last character of the record may be specified if no characters are transmitted
 28 from such positions.

29 4 On output, a position edit descriptor does not by itself cause characters to be transmitted and therefore does not
 30 by itself affect the length of the record. If characters are transmitted to positions at or after the position specified
 31 by a position edit descriptor, positions skipped and not previously filled are filled with blanks. The result is as if
 32 the entire record were initially filled with blanks.

33 5 On output, a character in the record can be replaced. A position edit descriptor never directly causes a character

1 already placed in the record to be replaced, but it might result in positioning such that subsequent editing causes
2 a replacement.

3 **10.8.1.2 T, TL, and TR editing**

4 1 The left tab limit affects file positioning by the T and TL edit descriptors. Immediately prior to nonchild data
5 transfer (9.6.4.8.2), the left tab limit becomes defined as the character position of the current record or the current
6 position of the stream file. If, during data transfer, the file is positioned to another record, the left tab limit
7 becomes defined as character position one of that record.

8 2 The T n edit descriptor indicates that the transmission of the next character to or from a record is to occur at
9 the n th character position of the record, relative to the left tab limit. This position can be in either direction
10 from the current position.

11 3 The TL n edit descriptor indicates that the transmission of the next character to or from the record is to occur at
12 the character position n characters backward from the current position. However, if n is greater than the difference
13 between the current position and the left tab limit, the TL n edit descriptor indicates that the transmission of
14 the next character to or from the record is to occur at the left tab limit.

15 4 The TR n edit descriptor indicates that the transmission of the next character to or from the record is to occur
16 at the character position n characters forward from the current position.

17 **10.8.1.3 X editing**

18 1 The n X edit descriptor indicates that the transmission of the next character to or from a record is to occur at
19 the character position n characters forward from the current position.

NOTE 10.23

An n X edit descriptor has the same effect as a TR n edit descriptor.

20 **10.8.2 Slash editing**

21 1 The slash edit descriptor indicates the end of data transfer to or from the current record.

22 2 On input from a file connected for sequential or stream access, the remaining portion of the current record is
23 skipped and the file is positioned at the beginning of the next record. This record becomes the current record.
24 On output to a file connected for sequential or stream access, a new empty record is created following the current
25 record; this new record then becomes the last and current record of the file and the file is positioned at the
26 beginning of this new record.

27 3 For a file connected for direct access, the record number is increased by one and the file is positioned at the
28 beginning of the record that has that record number, if there is such a record, and this record becomes the
29 current record.

NOTE 10.24

A record that contains no characters can be written on output. If the file is an [internal file](#) or a file connected
for direct access, the record is filled with blank characters.

An entire record can be skipped on input.

30 4 The repeat specification is optional in the slash edit descriptor. If it is not specified, the default value is one.

31 **10.8.3 Colon editing**

32 1 The colon edit descriptor terminates format control if there are no more [effective items](#) in the input/output list
33 (9.6.3). The colon edit descriptor has no effect if there are more [effective items](#) in the input/output list.

10.8.4 SS, SP, and S editing

- 1 The SS, SP, and S edit descriptors temporarily change (9.5.2) the sign mode (9.5.6.17, 9.6.2.14) for the connection. The edit descriptors SS, SP, and S set the sign mode corresponding to the SIGN= specifier values SUPPRESS, PLUS, and PROCESSOR_DEFINED, respectively.
- 2 The sign mode controls optional plus characters in numeric output fields. When the sign mode is PLUS, the processor shall produce a plus sign in any position that normally contains an optional plus sign. When the sign mode is SUPPRESS, the processor shall not produce a plus sign in such positions. When the sign mode is PROCESSOR_DEFINED, the processor has the option of producing a plus sign or not in such positions, subject to 10.7.2(5).
- 3 The SS, SP, and S edit descriptors affect only I, F, E, EN, ES, D, and G editing during the execution of an output statement. The SS, SP, and S edit descriptors have no effect during the execution of an input statement.

10.8.5 P editing

- 1 The k P edit descriptor temporarily changes (9.5.2) the scale factor for the connection to k . The scale factor affects the editing done by the F, E, EN, ES, D, and G edit descriptors for numeric quantities.
- 2 The scale factor k affects the appropriate editing in the following manner.
 - On input, with F, E, EN, ES, D, and G editing (provided that no exponent exists in the field), the effect is that the externally represented number equals the internally represented number multiplied by 10^k ; the scale factor is applied to the external decimal value and then this is converted using the input/output rounding mode.
 - On input, with F, E, EN, ES, D, and G editing, the scale factor has no effect if there is an exponent in the field.
 - On output, with F output editing, the effect is that the externally represented number equals the internally represented number multiplied by 10^k ; the internal value is converted using the input/output rounding mode and then the scale factor is applied to the converted decimal value.
 - On output, with E and D editing, the effect is that the significand (R415) part of the quantity to be produced is multiplied by 10^k and the exponent is reduced by k .
 - On output, with G editing, the effect is suspended unless the magnitude of the datum to be edited is outside the range that permits the use of F editing. If the use of E editing is required, the scale factor has the same effect as with E output editing.
 - On output, with EN and ES editing, the scale factor has no effect.

10.8.6 BN and BZ editing

- 1 The BN and BZ edit descriptors temporarily change (9.5.2) the blank interpretation mode (9.5.6.6, 9.6.2.6) for the connection. The edit descriptors BN and BZ set the blank interpretation mode corresponding to the BLANK= specifier values NULL and ZERO, respectively.
- 2 The blank interpretation mode controls the interpretation of nonleading blanks in numeric input fields. Such blank characters are interpreted as zeros when the blank interpretation mode has the value ZERO; they are ignored when the blank interpretation mode has the value NULL. The effect of ignoring blanks is to treat the input field as if blanks had been removed, the remaining portion of the field right justified, and the blanks replaced as leading blanks. However, a field containing only blanks has the value zero.
- 3 The blank interpretation mode affects only numeric editing (10.7.2) and generalized numeric editing (10.7.5.2) on input. It has no effect on output.

10.8.7 RU, RD, RZ, RN, RC, and RP editing

- 1 The round edit descriptors temporarily change (9.5.2) the connection's input/output rounding mode (9.5.6.16, 9.6.2.13, 10.7.2.3.8). The round edit descriptors RU, RD, RZ, RN, RC, and RP set the input/output rounding

1 mode corresponding to the `ROUND= specifier` values UP, DOWN, ZERO, NEAREST, COMPATIBLE, and
2 `PROCESSOR_DEFINED`, respectively. The input/output rounding mode affects the conversion of real and
3 complex values in formatted input/output. It affects only D, E, EN, ES, F, and G editing.

4 **10.8.8 DC and DP editing**

5 1 The decimal edit descriptors temporarily change (9.5.2) the decimal edit mode (9.5.6.7, 9.6.2.7, 10.6) for the
6 connection. The edit descriptors DC and DP set the decimal edit mode corresponding to the `DECIMAL=`
7 `specifier` values COMMA and POINT, respectively.

8 2 The decimal edit mode controls the representation of the `decimal symbol` (10.6) during conversion of real and
9 complex values in formatted input/output. The decimal edit mode affects only D, E, EN, ES, F, and G editing.

10 **10.9 Character string edit descriptors**

11 1 A character string edit descriptor shall not be used on input.

12 2 The character string edit descriptor causes characters to be written from the enclosed characters of the edit
13 descriptor itself, including blanks. For a character string edit descriptor, the width of the field is the number of
14 characters between the delimiting characters. Within the field, two consecutive delimiting characters are counted
15 as a single character.

NOTE 10.25

A delimiter for a character string edit descriptor is either an apostrophe or quote.

16 **10.10 List-directed formatting**

17 **10.10.1 Purpose of list-directed formatting**

18 1 List-directed input/output allows data editing according to the type of the list item instead of by a format
19 specification. It also allows data to be free-field, that is, separated by commas (or semicolons) or blanks.

20 **10.10.2 Values and value separators**

21 1 The characters in one or more list-directed records constitute a sequence of values and value separators. The end
22 of a record has the same effect as a blank character, unless it is within a character constant. Any sequence of two
23 or more consecutive blanks is treated as a single blank, unless it is within a character constant.

24 2 Each value is either a null value, c , r^*c , or r^* , where c is a literal constant, optionally signed if integer or real,
25 or an undelimited character constant and r is an unsigned, nonzero, integer literal constant. Neither c nor r
26 shall have kind type parameters specified. The constant c is interpreted as though it had the same kind type
27 parameter as the corresponding list item. The r^*c form is equivalent to r successive appearances of the constant
28 c , and the r^* form is equivalent to r successive appearances of the null value. Neither of these forms may contain
29 embedded blanks, except where permitted within the constant c .

30 3 A value separator is

- 31 • a comma optionally preceded by one or more contiguous blanks and optionally followed by one or more
32 contiguous blanks, unless the decimal edit mode is COMMA, in which case a semicolon is used in place of
33 the comma,
- 34 • a slash optionally preceded by one or more contiguous blanks and optionally followed by one or more
35 contiguous blanks, or
- 36 • one or more contiguous blanks between two nonblank values or following the last nonblank value, where a
37 nonblank value is a constant, an r^*c form, or an r^* form.

NOTE 10.26

Although a slash encountered in an input record is referred to as a separator, it actually causes termination of list-directed and namelist [input statements](#); it does not actually separate two values.

NOTE 10.27

If no list items are specified in a list-directed input/output statement, one input record is skipped or one empty output record is written.

10.10.3 List-directed input

1 Input forms acceptable to edit descriptors for a given type are acceptable for list-directed formatting, except as noted below. If the form of the input value is not acceptable to the processor for the type of the next [effective item](#) in the list, an error condition occurs. Blanks are never used as zeros, and embedded blanks are not permitted in constants, except within character constants and complex constants as specified below.

2 For the r^*c form of an input value, the constant c is interpreted as an undelimited character constant if the first list item corresponding to this value is default, [ASCII](#), or [ISO 10646 character](#), there is a nonblank character immediately after r^* , and that character is not an apostrophe or a quotation mark; otherwise, c is interpreted as a literal constant.

NOTE 10.28

The end of a record has the effect of a blank, except when it appears within a character constant.

3 When the next [effective item](#) is of type integer, the value in the input record is interpreted as if an Iw edit descriptor with a suitable value of w were used.

4 When the next [effective item](#) is of type real, the input form is that of a numeric input field. A numeric input field is a field suitable for F editing ([10.7.2.3.2](#)) that is assumed to have no fractional digits unless a [decimal symbol](#) appears within the field.

5 When the next [effective item](#) is of type complex, the input form consists of a left parenthesis followed by an ordered pair of numeric input fields separated by a comma (if the decimal edit mode is POINT) or semicolon (if the decimal edit mode is COMMA), and followed by a right parenthesis. The first numeric input field is the real part of the complex constant and the second is the imaginary part. Each of the numeric input fields may be preceded or followed by any number of blanks and ends of records. The end of a record may occur after the real part or before the imaginary part.

6 When the next [effective item](#) is of type logical, the input form shall not include value separators among the optional characters permitted for L editing.

7 When the next [effective item](#) is of type character, the input form consists of a possibly delimited sequence of zero or more *rep-chars* whose kind type parameter is implied by the kind of the [effective item](#). Character sequences may be continued from the end of one record to the beginning of the next record, but the end of record shall not occur between a doubled apostrophe in an apostrophe-delimited character sequence, nor between a doubled quote in a quote-delimited character sequence. The end of the record does not cause a blank or any other character to become part of the character sequence. The character sequence may be continued on as many records as needed. The characters blank, comma, semicolon, and slash may appear in default, [ASCII](#), or [ISO 10646 character](#) sequences.

8 If the next [effective item](#) is default, [ASCII](#), or [ISO 10646 character](#) and

- the character sequence does not contain value separators,
- the character sequence does not cross a record boundary,
- the first nonblank character is not a quotation mark or an apostrophe,
- the leading characters are not *digits* followed by an asterisk, and

1 • the character sequence contains at least one character,
 2 the delimiting apostrophes or quotation marks are not required. If the delimiters are omitted, the character
 3 sequence is terminated by the first blank, comma (if the decimal edit mode is POINT), semicolon (if the decimal
 4 edit mode is COMMA), slash, or end of record; in this case apostrophes and quotation marks within the datum
 5 are not to be doubled.

6 9 Let *len* be the length of the next [effective item](#), and let *w* be the length of the character sequence. If *len* is less
 7 than or equal to *w*, the leftmost *len* characters of the sequence are transmitted to the next [effective item](#). If *len*
 8 is greater than *w*, the sequence is transmitted to the leftmost *w* characters of the next [effective item](#) and the
 9 remaining *len*−*w* characters of the next [effective item](#) are filled with blanks. The effect is as though the sequence
 10 were assigned to the next [effective item](#) in an [intrinsic assignment statement](#) (7.2.1.3).

11 10.10.3.1 Null values

12 1 A null value is specified by

- 13 • the *r** form,
- 14 • no characters between consecutive value separators, or
- 15 • no characters before the first value separator in the first record read by each execution of a list-directed
 16 [input statement](#).

NOTE 10.29

The end of a record following any other value separator, with or without separating blanks, does not specify a null value in list-directed input.

17 2 A null value has no effect on the definition status of the next [effective item](#). A null value shall not be used for
 18 either the real or imaginary part of a complex constant, but a single null value may represent an entire complex
 19 constant.

20 3 A slash encountered as a value separator during execution of a list-directed [input statement](#) causes termination
 21 of execution of that [input statement](#) after the transference of the previous value. Any characters remaining in the
 22 current record are ignored. If there are additional items in the input list, the effect is as if null values had been
 23 supplied for them. Any [do-variable](#) in the input list becomes defined as if enough null values had been supplied
 24 for any remaining input list items.

NOTE 10.30

All blanks in a list-directed input record are considered to be part of some value separator except for

- blanks embedded in a character sequence,
- embedded blanks surrounding the real or imaginary part of a complex constant, and
- leading blanks in the first record read by each execution of a list-directed [input statement](#), unless immediately followed by a slash or comma.

NOTE 10.31

List-directed input example:

```
INTEGER I; REAL X (8); CHARACTER (11) P;
COMPLEX Z; LOGICAL G
...
READ *, I, X, P, Z, G
...
```

The input data records are:

NOTE 10.31 (cont.)

```
12345,12345,,2*1.5,4*
ISN'T_BOB'S,(123,0),.TEXAS$
```

The results are:

Variable	Value
I	12345
X (1)	12345.0
X (2)	unchanged
X (3)	1.5
X (4)	1.5
X (5) – X (8)	unchanged
P	ISN'T_BOB'S
Z	(123.0,0.0)
G	true

10.10.4 List-directed output

- 1
- 2 1 The form of the values produced is the same as that required for input, except as noted otherwise. With the
3 exception of adjacent undelimited character sequences, the values are separated by one or more blanks or by a
4 comma, or a semicolon if the decimal edit mode is COMMA, optionally preceded by one or more blanks and
5 optionally followed by one or more blanks. Two undelimited character sequences are considered adjacent when
6 both were written using list-directed input/output, no intervening [data transfer](#) or [file positioning](#) operations on
7 that [unit](#) occurred, and both were written either by a single [data transfer statement](#), or during the execution of a
8 parent [data transfer statement](#) along with its child [data transfer statements](#). The form of the values produced by
9 [defined output \(9.6.4.8\)](#) is determined by the [defined output](#) procedure; this form need not be compatible with
10 list-directed input.
- 11 2 The processor may begin new records as necessary, but the end of record shall not occur within a constant except
12 as specified for complex constants and character sequences. The processor shall not insert blanks within character
13 sequences or within constants, except as specified for complex constants.
- 14 3 Logical output values are T for the value true and F for the value false.
- 15 4 Integer output constants are produced with the effect of an *Iw* edit descriptor.
- 16 5 Real constants are produced with the effect of either an F edit descriptor or an E edit descriptor, depending on
17 the magnitude x of the value and a range $10^{d_1} \leq x < 10^{d_2}$, where d_1 and d_2 are processor-dependent integers. If
18 the magnitude x is within this range or is zero, the constant is produced using *0PFw.d*; otherwise, *1PEw.d Ee* is
19 used.
- 20 6 For numeric output, reasonable processor-dependent values of *w*, *d*, and *e* are used for each of the numeric
21 constants output.
- 22 7 Complex constants are enclosed in parentheses with a separator between the real and imaginary parts, each
23 produced as defined above for real constants. The separator is a comma if the decimal edit mode is POINT; it
24 is a semicolon if the decimal edit mode is COMMA. The end of a record may occur between the separator and
25 the imaginary part only if the entire constant is as long as, or longer than, an entire record. The only embedded
26 blanks permitted within a complex constant are between the separator and the end of a record and one blank at
27 the beginning of the next record.
- 28 8 Character sequences produced when the delimiter mode has a value of NONE
- 29 • are not delimited by apostrophes or quotation marks,
 - 30 • are not separated from each other by value separators,

- 1 • have each internal apostrophe or quotation mark represented externally by one apostrophe or quotation
2 mark, and
 - 3 • have a blank character inserted by the processor at the beginning of any record that begins with the
4 continuation of a character sequence from the preceding record.
- 5 9 Character sequences produced when the delimiter mode has a value of QUOTE are delimited by quotes, are
6 preceded and followed by a value separator, and have each internal quote represented on the external medium by
7 two contiguous quotes.
- 8 10 Character sequences produced when the delimiter mode has a value of APOSTROPHE are delimited by apo-
9 strophes, are preceded and followed by a value separator, and have each internal apostrophe represented on the
10 external medium by two contiguous apostrophes.
- 11 11 If two or more successive values in an output record have identical values, the processor has the option of producing
12 a repeated constant of the form $r*c$ instead of the sequence of identical values.
- 13 12 Slashes, as value separators, and null values are not produced as output by list-directed formatting.
- 14 13 Except for new records created by explicit formatting within a [defined output](#) procedure or by continuation of
15 delimited character sequences, each output record begins with a blank character.

NOTE 10.32

The length of the output records is not specified and is processor dependent.

16 10.11 Namelist formatting

17 10.11.1 Purpose of namelist formatting

- 18 1 Namelist input/output allows data editing with name-value subsequences. This facilitates documentation of input
19 and output files and more flexibility on input.

20 10.11.2 Name-value subsequences

- 21 1 The characters in one or more namelist records constitute a sequence of name-value subsequences, each of which
22 consists of an [object designator](#) followed by an equals and followed by one or more values and value separators.
23 The equals may optionally be preceded or followed by one or more contiguous blanks. The end of a record has the
24 same effect as a blank character, unless it is within a character constant. Any sequence of two or more consecutive
25 blanks is treated as a single blank, unless it is within a character constant.
- 26 2 Each object designator shall begin with a name from the [namelist-group-object-list](#) (5.8) and shall follow the
27 syntax of [designator](#) (R601). It shall not contain a [vector subscript](#) or an [image-selector](#) and shall not designate a
28 zero-sized array, a zero-sized array section, or a zero-length character string. Each subscript, stride, and substring
29 range expression shall be an optionally signed integer literal constant with no [kind type parameter](#) specified. If
30 a section subscript list appears, the number of section subscripts shall be equal to the rank of the object. If
31 the namelist group object is of derived type, the designator in the input record may be either the name of the
32 variable or the designator of one of its components, indicated by qualifying the variable name with the appropriate
33 component name. Successive qualifications may be applied as appropriate to the shape and type of the variable
34 represented. Each designator may be preceded and followed by one or more optional blanks but shall not contain
35 embedded blanks.
- 36 3 A value separator for namelist formatting is the same as for list-directed formatting (10.10.2), or one or more
37 contiguous blanks between a nonblank value and the following [object designator](#) or namelist comment (10.11.3.6).

10.11.3 Namelist input

10.11.3.1 Overall syntax

1 Input for a namelist [input statement](#) consists of

- (1) optional blanks and namelist comments,
- (2) the character & followed immediately by the *namelist-group-name* as specified in the [NAMELIST statement](#),
- (3) one or more blanks,
- (4) a sequence of zero or more name-value subsequences separated by value separators, and
- (5) a slash to terminate the namelist input.

NOTE 10.33

A slash encountered in a namelist input record causes the [input statement](#) to terminate. A slash cannot be used to separate two values in a namelist [input statement](#).

2 The order of the name-value subsequences in the input records need not match the order of the *namelist-group-object-list*. The input records need not specify all objects in the *namelist-group-object-list*. They may specify a part of an object more than once.

3 A group name or object name is without regard to case.

10.11.3.2 Namelist input processing

1 The name-value subsequences are evaluated serially, in left-to-right order. A namelist group object [designator](#) may appear in more than one name-value subsequence. The definition status of an object that is not a subobject of a [designator](#) in any name-value subsequence remains unchanged.

2 When the [designator](#) in the input record represents an array variable or a variable of derived type, the effect is as if the variable represented were expanded into a sequence of scalar list items, in the same way that formatted input/output list items are expanded (9.6.3). The number of values following the equals shall not exceed the number of list items in the expanded sequence, but may be less; in the latter case, the effect is as if sufficient null values had been appended to match any remaining list items in the expanded sequence. Except as noted elsewhere in this subclause, if an input value is not acceptable to the processor for the type of the list item in the corresponding position in the expanded sequence, an error condition occurs.

NOTE 10.34

For example, if the designator in the input record designates an integer array of size 100, at most 100 values, each of which is either a digit string or a null value, can follow the equals; these values would then be assigned to the elements of the array in array element order.

3 A slash encountered as a value separator during the execution of a namelist [input statement](#) causes termination of execution of that [input statement](#) after transference of the previous value. If there are additional items in the namelist group object being transferred, the effect is as if null values had been supplied for them.

4 A namelist comment may appear after any value separator except a slash. A namelist comment is also permitted to start in the first nonblank position of an input record except within a character literal constant.

5 Successive namelist records are read by namelist input until a slash is encountered; the remainder of the record is ignored and need not follow the rules for namelist input values.

10.11.3.3 Namelist input values

1 Each value is either a null value (10.11.3.4), c , r^*c , or r^* , where c is a literal constant, optionally signed if integer or real, and r is an unsigned, nonzero, integer literal constant. A kind type parameter shall not be specified for c

- 1 or r . The constant c is interpreted as though it had the same kind type parameter as the corresponding [effective](#)
 2 [item](#). The r^*c form is equivalent to r successive appearances of the constant c , and the r^* form is equivalent to r
 3 successive null values. Neither of these forms may contain embedded blanks, except where permitted within the
 4 constant c .
- 5 2 The datum c ([10.11](#)) is any input value acceptable to format specifications for a given type, except for a restriction
 6 on the form of input values corresponding to list items of types logical, integer, and character as specified in this
 7 subclause. The form of a real or complex value is dependent on the decimal edit mode in effect ([10.6](#)). The form
 8 of an input value shall be acceptable for the type of the namelist group object list item. The number and forms
 9 of the input values that may follow the equals in a name-value subsequence depend on the shape and type of
 10 the object represented by the name in the input record. When the name in the input record is that of a scalar
 11 variable of an intrinsic type, the equals shall not be followed by more than one value. Blanks are never used
 12 as zeros, and embedded blanks are not permitted in constants except within character constants and complex
 13 constants as specified in this subclause.
- 14 3 When the next [effective item](#) is of type real, the input form of the input value is that of a numeric input field. A
 15 numeric input field is a field suitable for F editing ([10.7.2.3.2](#)) that is assumed to have no fractional digits unless
 16 a decimal symbol appears within the field.
- 17 4 When the next [effective item](#) is of type complex, the input form of the input value consists of a left parenthesis
 18 followed by an ordered pair of numeric input fields separated by a comma (if the decimal edit mode is POINT) or
 19 a semicolon (if the decimal edit mode is COMMA), and followed by a right parenthesis. The first numeric input
 20 field is the real part of the complex constant and the second field is the imaginary part. Each of the numeric
 21 input fields may be preceded or followed by any number of blanks and ends of records. The end of a record may
 22 occur between the real part and the comma or semicolon, or between the comma or semicolon and the imaginary
 23 part.
- 24 5 When the next [effective item](#) is of type logical, the input form of the input value shall not include equals or value
 25 separators among the optional characters permitted for L editing ([10.7.3](#)).
- 26 6 When the next [effective item](#) is of type integer, the value in the input record is interpreted as if an Iw edit
 27 descriptor with a suitable value of w were used.
- 28 7 When the next [effective item](#) is of type character, the input form consists of a delimited sequence of zero or more
 29 *rep-chars* whose kind type parameter is implied by the kind of the corresponding list item. Such a sequence
 30 may be continued from the end of one record to the beginning of the next record, but the end of record shall
 31 not occur between a doubled apostrophe in an apostrophe-delimited sequence, nor between a doubled quote in a
 32 quote-delimited sequence. The end of the record does not cause a blank or any other character to become part
 33 of the sequence. The sequence may be continued on as many records as needed. The characters blank, comma,
 34 semicolon, and slash may appear in such character sequences.

NOTE 10.35

A character sequence corresponding to a namelist input item of character type shall be delimited either with apostrophes or with quotes. The delimiter is required to avoid ambiguity between undelimited character sequences and object names. The value of the `DELIM= specifier`, if any, in the `OPEN statement` for an [external file](#) is ignored during namelist input ([9.5.6.8](#)).

- 35 8 Let len be the length of the next [effective item](#), and let w be the length of the character sequence. If len is less
 36 than or equal to w , the leftmost len characters of the sequence are transmitted to the next [effective item](#). If len
 37 is greater than w , the constant is transmitted to the leftmost w characters of the next [effective item](#) and the
 38 remaining $len-w$ characters of the next [effective item](#) are filled with blanks. The effect is as though the sequence
 39 were assigned to the next [effective item](#) in an [intrinsic assignment statement](#) ([7.2.1.3](#)).

10.11.3.4 Null values

- 40
 41 1 A null value is specified by
 42
 - the r^* form,

- 1 • blanks between two consecutive nonblank value separators following an equals,
- 2 • zero or more blanks preceding the first value separator and following an equals, or
- 3 • two consecutive nonblank value separators.

4 2 A null value has no effect on the definition status of the corresponding input list item. If the namelist group
 5 object list item is defined, it retains its previous value; if it is undefined, it remains undefined. A null value shall
 6 not be used as either the real or imaginary part of a complex constant, but a single null value may represent an
 7 entire complex constant.

NOTE 10.36

The end of a record following a value separator, with or without intervening blanks, does not specify a null value in namelist input.

8 10.11.3.5 Blanks

- 9 1 All blanks in a namelist input record are considered to be part of some value separator except for
- 10 • blanks embedded in a character constant,
 - 11 • embedded blanks surrounding the real or imaginary part of a complex constant,
 - 12 • leading blanks following the equals unless followed immediately by a slash or comma, or a semicolon if the
 13 decimal edit mode is COMMA, and
 - 14 • blanks between a name and the following equals.

15 10.11.3.6 Namelist comments

- 16 1 Except within a character literal constant, a “!” character after a value separator or in the first nonblank position
 17 of a namelist input record initiates a comment. The comment extends to the end of the record and may contain
 18 any graphic character in the processor-dependent character set. The comment is ignored. A slash within the
 19 namelist comment does not terminate execution of the namelist [input statement](#). Namelist comments are not
 20 allowed in stream input because comments depend on record structure.

NOTE 10.37

Namelist input example:

```
INTEGER I; REAL X (8); CHARACTER (11) P; COMPLEX Z; LOGICAL G
NAMELIST / TODAY / G, I, P, Z, X
READ (*, NML = TODAY)
```

The input data records are:

```
&TODAY I = 12345, X(1) = 12345, X(3:4) = 2*1.5, I=6, ! This is a comment.
P = ' 'ISN'T_BOB'S', Z = (123,0)/
```

The results stored are:

Variable	Value
I	6
X (1)	12345.0
X (2)	unchanged
X (3)	1.5
X (4)	1.5
X (5) – X (8)	unchanged
P	ISN'T_BOB'S
Z	(123.0,0.0)
G	unchanged

10.11.4 Namelist output

10.11.4.1 Form of namelist output

1 The form of the output produced by intrinsic namelist output shall be suitable for input, except for character output. The names in the output are in upper case. With the exception of adjacent undelimited character values, the values are separated by one or more blanks or by a comma, or a semicolon if the decimal edit mode is COMMA, optionally preceded by one or more blanks and optionally followed by one or more blanks. The form of the output produced by [defined output \(9.6.4.8\)](#) is determined by the [defined output](#) procedure; this form need not be compatible with namelist input.

2 Namelist output shall not include namelist comments.

3 The processor may begin new records as necessary. However, except for complex constants and character values, the end of a record shall not occur within a constant, character value, or name, and blanks shall not appear within a constant, character value, or name.

NOTE 10.38

The length of the output records is not specified exactly and is processor dependent.

10.11.4.2 Namelist output editing

1 Values in namelist output records are edited as for list-directed output ([10.10.4](#)).

NOTE 10.39

Namelist output records produced with a [DELIM= specifier](#) with a value of NONE and which contain a character sequence might not be acceptable as namelist input records.

10.11.4.3 Namelist output records

1 If two or more successive values for the same namelist group item in an output record produced have identical values, the processor has the option of producing a repeated constant of the form $r*c$ instead of the sequence of identical values.

2 The name of each namelist group object list item is placed in the output record followed by an equals and a list of values of the namelist group object list item.

3 An ampersand character followed immediately by a *namelist-group-name* will be produced by namelist formatting at the start of the first output record to indicate which particular group of data objects is being output. A slash is produced by namelist formatting to indicate the end of the namelist formatting.

4 A null value is not produced by namelist formatting.

5 Except for new records created by explicit formatting within a [defined output](#) procedure or by continuation of delimited character sequences, each output record begins with a blank character.

1

(Blank page)

11 Program units

11.1 Main program

- 1 A Fortran main program is a [program unit](#) that does not contain a [SUBROUTINE](#), [FUNCTION](#), [MODULE](#), [SUBMODULE](#), or [BLOCK DATA](#) statement as its first statement.

R1101 *main-program* **is** [*program-stmt*]
 [*specification-part*]
 [*execution-part*]
 [*internal-subprogram-part*]
 end-program-stmt

R1102 *program-stmt* **is** PROGRAM *program-name*

R1103 *end-program-stmt* **is** END [PROGRAM [*program-name*]]

- C1101 (R1101) The *program-name* may be included in the *end-program-stmt* only if the optional *program-stmt* is used and, if included, shall be identical to the *program-name* specified in the *program-stmt*.

NOTE 11.1

The program name is global to the program (16.2). For explanatory information about uses for the program name, see subclause C.8.1.

NOTE 11.2

An example of a main program is:

```
PROGRAM ANALYZE
  REAL A, B, C (10,10)      ! Specification part
  CALL FIND                 ! Execution part
CONTAINS
  SUBROUTINE FIND           ! Internal subprogram
  ...
  END SUBROUTINE FIND
END PROGRAM ANALYZE
```

- 2 The main program may be defined by means other than Fortran; in that case, the program shall not contain a *main-program program unit*.
- 3 A reference to a Fortran *main-program* shall not appear in any [program unit](#) in the program, including itself.

11.2 Modules

11.2.1 Module syntax and semantics

- 1 A [module](#) contains declarations, specifications, and definitions. Public identifiers of module entities are accessible to other [program units](#) by [use association](#) as specified in 11.2.2. A module that is provided as an inherent part of the processor is an intrinsic module. A nonintrinsic module is defined by a module [program unit](#) or a means other than Fortran.
- 2 Procedures and types defined in an intrinsic module are not themselves intrinsic.

1	R1104	<i>module</i>	is	<i>module-stmt</i>
2				[<i>specification-part</i>]
3				[<i>module-subprogram-part</i>]
4				<i>end-module-stmt</i>
5	R1105	<i>module-stmt</i>	is	MODULE <i>module-name</i>
6	R1106	<i>end-module-stmt</i>	is	END [MODULE [<i>module-name</i>]]
7	R1107	<i>module-subprogram-part</i>	is	<i>contains-stmt</i>
8				[<i>module-subprogram</i>] ...
9	R1108	<i>module-subprogram</i>	is	<i>function-subprogram</i>
10			or	<i>subroutine-subprogram</i>
11			or	<i>separate-module-subprogram</i>

12 C1102 (R1104) If the *module-name* is specified in the *end-module-stmt*, it shall be identical to the *module-name*
 13 specified in the *module-stmt*.

14 C1103 (R1104) A module *specification-part* shall not contain a *stmt-function-stmt*, an *entry-stmt*, or a *format-stmt*.

15 3 If a procedure declared in the *scoping unit* of a module has an *implicit interface*, it shall be given the **EXTERNAL**
 16 **attribute** in that *scoping unit*; if it is a function, its type and type parameters shall be explicitly declared in a
 17 *type declaration statement* in that *scoping unit*.

18 4 If an intrinsic procedure is declared in the *scoping unit* of a module, it shall explicitly be given the **INTRINSIC**
 19 **attribute** in that *scoping unit* or be used as an intrinsic procedure in that *scoping unit*.

NOTE 11.3

The module name is global to the program (16.2).

NOTE 11.4

Although *statement function definitions*, **ENTRY** statements, and **FORMAT** statements cannot appear in the specification part of a module, they can appear in the specification part of a module subprogram in the module.

NOTE 11.5

For a discussion of the impact of modules on dependent compilation, see subclause C.8.2.

NOTE 11.6

For examples of the use of modules, see subclause C.8.3.

20 11.2.2 The USE statement and use association

21 1 The USE statement specifies *use association*. A USE statement is a *reference* to the module it specifies. At the
 22 time a USE statement is processed, the public portions of the specified module shall be available. A module shall
 23 not reference itself, either directly or indirectly.

24 2 The USE statement provides the means by which a *scoping unit* accesses named data objects, derived types,
 25 procedures, *abstract interfaces*, *generic identifiers*, and namelist groups in a module. The entities in the *scoping*
 26 *unit* are use associated with the entities in the module. The accessed entities have the attributes specified in the
 27 module, except that a local entity may have a different *accessibility attribute*, it may have the **ASYNCHRONOUS**
 28 **attribute** even if the associated module entity does not, and if it is not a *coarray* it may have the **VOLATILE**
 29 **attribute** even if the associated module entity does not. The entities made accessible are identified by the names
 30 or *generic identifiers* used to identify them in the module. By default, the local entities are identified by the
 31 same identifiers in the *scoping unit* containing the USE statement, but it is possible to specify that different local

1 identifiers are used. A use-associated entity is considered to have been previously defined.

NOTE 11.7

The accessibility of module entities can be controlled by accessibility attributes (4.5.2.2, 5.5.2), and the ONLY option of the USE statement. Definability of module entities can be controlled by the PROTECTED attribute (5.5.15).

2 R1109 *use-stmt* is USE [[, *module-nature*] ::] *module-name* [, *rename-list*]
 3 or USE [[, *module-nature*] ::] *module-name* , ■
 4 ■ ONLY : [*only-list*]

5 R1110 *module-nature* is INTRINSIC
 6 or NON_INTRINSIC

7 R1111 *rename* is *local-name* => *use-name*
 8 or OPERATOR (*local-defined-operator*) => ■
 9 ■ OPERATOR (*use-defined-operator*)

10 R1112 *only* is *generic-spec*
 11 or *only-use-name*
 12 or *rename*

13 R1113 *only-use-name* is *use-name*

14 C1104 (R1109) If *module-nature* is INTRINSIC, *module-name* shall be the name of an intrinsic module.

15 C1105 (R1109) If *module-nature* is NON_INTRINSIC, *module-name* shall be the name of a nonintrinsic module.

16 C1106 (R1109) A *scoping unit* shall not access an intrinsic module and a nonintrinsic module of the same name.

17 C1107 (R1111) OPERATOR (*use-defined-operator*) shall not identify a *type-bound generic interface*.

18 C1108 (R1112) The *generic-spec* shall not identify a *type-bound generic interface*.

NOTE 11.8

Constraints C1107 and C1108 do not prevent accessing a *generic-spec* that is declared by an *interface block*, even if a *type-bound generic interface* has the same *generic-spec*.

19 C1109 (R1112) Each *generic-spec* shall be a public entity in the module.

20 C1110 (R1113) Each *use-name* shall be the name of a public entity in the module.

21 R1114 *local-defined-operator* is *defined-unary-op*
 22 or *defined-binary-op*

23 R1115 *use-defined-operator* is *defined-unary-op*
 24 or *defined-binary-op*

25 C1111 (R1115) Each *use-defined-operator* shall be a public entity in the module.

26 3 A *use-stmt* without a *module-nature* provides access either to an intrinsic or to a nonintrinsic module. If the
 27 *module-name* is the name of both an intrinsic and a nonintrinsic module, the nonintrinsic module is accessed.

28 4 The USE statement without the ONLY option provides access to all public entities in the specified module.

29 5 A USE statement with the ONLY option provides access only to those entities that appear as *generic-specs*,
 30 *use-names*, or *use-defined-operators* in the *only-list*.

31 6 More than one USE statement for a given module may appear in a specification part. If one of the USE statements

- 1 is without an **ONLY** option, all public entities in the module are accessible. If all the USE statements have **ONLY**
 2 options, only those entities in one or more of the *only-lists* are accessible.
- 3 7 An accessible entity in the referenced module has one or more local identifiers. These identifiers are
- 4 • the identifier of the entity in the referenced module if that identifier appears as an *only-use-name* or as the
 5 *defined-operator* of a *generic-spec* in any *only* for that module,
 - 6 • each of the *local-names* or *local-defined-operators* that the entity is given in any *rename* for that module,
 7 and
 - 8 • the identifier of the entity in the referenced module if that identifier does not appear as a *use-name* or
 9 *use-defined-operator* in any *rename* for that module.
- 10 8 Two or more accessible entities, other than **generic interfaces** or defined operators, may have the same local
 11 identifier only if the identifier is not used. **Generic interfaces** and defined operators are handled as described in
 12 12.4.3.5. Except for these cases, the local identifier of any entity given accessibility by a USE statement shall
 13 differ from the local identifiers of all other entities accessible to the **scoping unit**.

NOTE 11.9

There is no prohibition against a *use-name* or *use-defined-operator* appearing multiple times in one USE statement or in multiple USE statements involving the same module. As a result, it is possible for one use-associated entity to be accessible by more than one local identifier.

- 14 9 The local identifier of an entity made accessible by a USE statement shall not appear in any other nonexecutable
 15 statement that would cause any **attribute** (5.5) of the entity to be specified in the **scoping unit** that contains the
 16 USE statement, except that it may appear in a **PUBLIC** or **PRIVATE** statement in the **scoping unit** of a module
 17 and it may be given the **ASYNCHRONOUS** or **VOLATILE** attribute.
- 18 10 The appearance of such a local identifier in a **PUBLIC statement** in a module causes the entity accessible by
 19 the USE statement to be a public entity of that module. If the identifier appears in a **PRIVATE statement** in
 20 a module, the entity is not a public entity of that module. If the local identifier does not appear in either a
 21 **PUBLIC** or **PRIVATE** statement, it assumes the default accessibility attribute (5.6.1) of that **scoping unit**.

NOTE 11.10

The constraints in subclauses 5.9.1, 5.9.2, and 5.8 prohibit the *local-name* from appearing as a *common-block-object* in a **COMMON statement**, an *equivalence-object* in an **EQUIVALENCE statement**, or a *namelist-group-name* in a **NAMELIST statement**, respectively. There is no prohibition against the *local-name* appearing as a *common-block-name* or a *namelist-group-object*.

NOTE 11.11

For a discussion of the impact of the **ONLY** option and renaming on dependent compilation, see subclause C.8.2.1.

NOTE 11.12

Examples:

```
USE STATS_LIB
```

provides access to all public entities in the module STATS_LIB.

```
USE MATH_LIB; USE STATS_LIB, SPROD => PROD
```

makes all public entities in both MATH_LIB and STATS_LIB accessible. If MATH_LIB contains an entity called PROD, it is accessible by its own name while the entity PROD of STATS_LIB is accessible by the name SPROD.

NOTE 11.12 (cont.)

```
USE STATS_LIB, ONLY: YPROD; USE STATS_LIB, ONLY : PROD
```

makes public entities YPROD and PROD in STATS_LIB accessible.

```
USE STATS_LIB, ONLY : YPROD; USE STATS_LIB
```

makes all public entities in STATS_LIB accessible.

1 **11.2.3 Submodules**

2 1 A **submodule** is a **program unit** that extends a module or another submodule. The **program unit** that it extends
3 is its **host**, and is specified by the *parent-identifier* in the *submodule-stmt*.

4 2 A module or submodule is an ancestor program unit of all of its descendants, which are its submodules and their
5 descendants. The submodule identifier is the ordered pair whose first element is the ancestor module name and
6 whose second element is the submodule name; the submodule name by itself is not a local or global identifier.

NOTE 11.13

A module and its submodules stand in a tree-like relationship one to another, with the module at the root.
Therefore, a submodule has exactly one ancestor module and can have one or more ancestor submodules.

7 3 A submodule may provide implementations for separate module procedures (12.6.2.5), each of which is declared
8 (12.4.3.2) within that submodule or one of its ancestors, and declarations and definitions of other entities that
9 are accessible by **host association** in its **descendants**.

10 R1116 *submodule* **is** *submodule-stmt*
11 [*specification-part*]
12 [*module-subprogram-part*]
13 *end-submodule-stmt*

14 R1117 *submodule-stmt* **is** SUBMODULE (*parent-identifier*) *submodule-name*

15 R1118 *parent-identifier* **is** *ancestor-module-name* [: *parent-submodule-name*]

16 R1119 *end-submodule-stmt* **is** END [SUBMODULE [*submodule-name*]]

17 C1112 (R1116) A submodule *specification-part* shall not contain a *format-stmt*, *entry-stmt*, or *stmt-function-stmt*.

18 C1113 (R1118) The *ancestor-module-name* shall be the name of a nonintrinsic module; the *parent-submodule-*
19 *name* shall be the name of a **descendant** of that module.

20 C1114 (R1116) If a *submodule-name* appears in the *end-submodule-stmt*, it shall be identical to the one in the
21 *submodule-stmt*.

22 **11.3 Block data program units**

23 1 A block data program unit is used to provide initial values for data objects in named **common blocks**.

24 R1120 *block-data* **is** *block-data-stmt*
25 [*specification-part*]
26 *end-block-data-stmt*

27 R1121 *block-data-stmt* **is** BLOCK DATA [*block-data-name*]

28 R1122 *end-block-data-stmt* **is** END [BLOCK DATA [*block-data-name*]]

29 C1115 (R1120) The *block-data-name* shall be included in the *end-block-data-stmt* only if it was provided in the *block-data-stmt*
30 and, if included, shall be identical to the *block-data-name* in the *block-data-stmt*.

- 1 C1116 (R1120) A *block-data specification-part* shall contain only definitions of derived-type definitions and ASYNCHRONOUS,
2 BIND, COMMON, DATA, DIMENSION, EQUIVALENCE, IMPLICIT, INTRINSIC, PARAMETER, POINTER, SAVE,
3 TARGET, USE, VOLATILE, and type declaration statements.
- 4 C1117 (R1120) A type declaration statement in a *block-data specification-part* shall not contain ALLOCATABLE, EXTERNAL,
5 or BIND attribute specifiers.
- 6 2 If an object in a named common block is initially defined, all storage units in the common block storage sequence shall be specified
7 even if they are not all initially defined. More than one named common block may have objects initially defined in a single block
8 data program unit.
- 9 3 Only an object in a named common block may be initially defined in a block data program unit.
- 10 4 The same named common block shall not be specified in more than one block data program unit in a program.
- 11 5 There shall not be more than one unnamed block data program unit in a program.

12 Procedures

12.1 Concepts

- 1 The concept of a procedure was introduced in 2.2.3. This clause contains a complete description of procedures. The actions specified by a procedure are performed when the procedure is invoked by execution of a reference to it.
- 2 The sequence of actions encapsulated by a procedure has access to entities in the procedure reference by way of [argument association](#) (12.5.2). A name that appears as a *dummy-arg-name* in the `SUBROUTINE`, `FUNCTION`, or `ENTRY` statement in the declaration of a procedure (R1237) is a [dummy argument](#). [Dummy arguments](#) are also specified for intrinsic procedures and procedures in intrinsic modules in Clauses 13, 14, and 15.

12.2 Procedure classifications

12.2.1 Procedure classification by reference

- 1 The definition of a procedure specifies it to be a function or a subroutine. A reference to a function either appears explicitly as a primary within an expression, or is implied by a [defined operation](#) (7.1.6) within an expression. A reference to a subroutine is a [CALL statement](#), a [defined assignment](#) statement (7.2.1.4), the appearance of an object processed by [defined input/output](#) (9.6.4.8) in an input/output list, or [finalization](#) (4.5.6).
- 2 A procedure is classified as [elemental](#) if it is a procedure that may be referenced [elementally](#) (12.8).

12.2.2 Procedure classification by means of definition

12.2.2.1 Intrinsic procedures

- 1 A procedure that is provided as an inherent part of the processor is an intrinsic procedure.

12.2.2.2 External, internal, and module procedures

- 1 An [external procedure](#) is a procedure that is defined by an external subprogram or by a means other than Fortran.
- 2 An [internal procedure](#) is a procedure that is defined by an internal subprogram. Internal subprograms may appear in the main program, in an external subprogram, or in a module subprogram. Internal subprograms shall not appear in other internal subprograms. Internal subprograms are the same as external subprograms except that the name of the [internal procedure](#) is not a global identifier, an internal subprogram shall not contain an [ENTRY statement](#), and the internal subprogram has access to host entities by [host association](#).
- 3 A [module procedure](#) is a procedure that is defined by a module subprogram.
- 4 A subprogram defines a procedure for the `SUBROUTINE` or `FUNCTION` statement. If the subprogram has one or more [ENTRY statements](#), it also defines a procedure for each of them.

12.2.2.3 Dummy procedures

- 1 A [dummy argument](#) that is specified to be a procedure or appears as the procedure designator in a [procedure reference](#) is a [dummy procedure](#). A [dummy procedure](#) with the `POINTER` attribute is a [dummy procedure pointer](#).

1 12.2.2.4 Procedure pointers

2 1 A [procedure pointer](#) is a procedure that has the [EXTERNAL](#) and [POINTER](#) attributes; it may be [pointer](#)
3 [associated](#) with an [external procedure](#), an [internal procedure](#), an intrinsic procedure, a [module procedure](#), or a
4 [dummy procedure](#) that is not a [procedure pointer](#).

5 12.2.2.5 Statement functions

6 1 A function that is defined by a single statement is a statement function ([12.6.4](#)).

7 12.3 Characteristics

8 12.3.1 Characteristics of procedures

9 1 The [characteristics](#) of a procedure are the classification of the procedure as a function or subroutine, whether it
10 is pure, whether it is [elemental](#), whether it has the [BIND attribute](#), the [characteristics](#) of its [dummy arguments](#),
11 and the [characteristics](#) of its [function result](#) if it is a function.

12 12.3.2 Characteristics of dummy arguments

13 12.3.2.1 General

14 1 Each [dummy argument](#) has the [characteristic](#) that it is a [dummy data object](#), a [dummy procedure](#), or an asterisk
15 (alternate return indicator).

16 12.3.2.2 Characteristics of dummy data objects

17 1 The [characteristics](#) of a [dummy data object](#) are its type, its [type parameters](#) (if any), its shape (unless it is
18 [assumed-rank](#)), its [corank](#), its [codimensions](#), its intent ([5.5.10](#), [5.6.9](#)), whether it is optional ([5.5.12](#), [5.6.10](#)),
19 whether it is [allocatable](#) ([5.5.3](#)), whether it has the [ASYNCHRONOUS](#) ([5.5.4](#)), [CONTIGUOUS](#) ([5.5.7](#)), [VALUE](#)
20 ([5.5.18](#)), or [VOLATILE](#) ([5.5.19](#)) attributes, whether it is [polymorphic](#), and whether it is a [pointer](#) ([5.5.14](#), [5.6.12](#))
21 or a target ([5.5.17](#), [5.6.15](#)). If a [type parameter](#) of an object or a bound of an array is not a [constant expression](#),
22 the exact dependence on the entities in the expression is a characteristic. If a rank, shape, size, type, or type
23 parameter is assumed or [deferred](#), it is a characteristic.

24 12.3.2.3 Characteristics of dummy procedures

25 1 The [characteristics](#) of a [dummy procedure](#) are the explicitness of its [interface](#) ([12.4.2](#)), its [characteristics](#) as a
26 procedure if the [interface](#) is [explicit](#), whether it is a pointer, and whether it is optional ([5.5.12](#), [5.6.10](#)).

27 12.3.2.4 Characteristics of asterisk dummy arguments

28 1 An asterisk as a [dummy argument](#) has no [characteristics](#).

29 12.3.3 Characteristics of function results

30 1 The [characteristics](#) of a function result are its type, type parameters (if any), [rank](#), whether it is [polymorphic](#),
31 whether it is [allocatable](#), whether it is a [pointer](#), whether it has the [CONTIGUOUS attribute](#), and whether it is a
32 [procedure pointer](#). If a function result is an array that is not [allocatable](#) or a pointer, its shape is a characteristic.
33 If a type parameter of a function result or a bound of a function result array is not a [constant expression](#), the
34 exact dependence on the entities in the expression is a characteristic. If type parameters of a function result are
35 [deferred](#), which parameters are [deferred](#) is a characteristic. Whether the length of a character function result is assumed
36 is a characteristic.

12.4 Procedure interface

12.4.1 Interface and abstract interface

- 1 The **interface** of a procedure determines the forms of reference through which it may be invoked. The procedure's interface consists of its name, **binding label**, generic identifiers, characteristics, and the names of its dummy arguments. The **characteristics** and **binding label** of a procedure are fixed, but the remainder of the interface may differ in differing contexts, except that for a separate module procedure body (12.6.2.5), the **dummy argument** names and whether it is recursive shall be the same as in its corresponding module procedure interface body (12.4.3.2).
- 2 An **abstract interface** is a set of procedure **characteristics** with the **dummy argument** names.

12.4.2 Implicit and explicit interfaces

12.4.2.1 Interfaces and scopes

- 1 The interface of a procedure is either explicit or implicit. It is explicit if it is
 - an **internal procedure**, **module procedure**, or **intrinsic** procedure,
 - a subroutine, or a function with a separate result name, within the **scoping unit** that defines it, or
 - a procedure declared by a **procedure declaration statement** that specifies an explicit interface, or by an interface body.
 Otherwise, the interface of the identifier is implicit. The interface of a statement function is always implicit.

NOTE 12.1

For example, the subroutine LLS of C.8.3.4 has an **explicit interface**.

12.4.2.2 Explicit interface

- 1 Within the scope of a procedure identifier, the procedure shall have an **explicit interface** if it is not a statement function and
 - (1) a reference to the procedure appears
 - (a) with an **argument keyword** (12.5.2), or
 - (b) in a context that requires it to be pure,
 - (2) the procedure has a **dummy argument** that
 - (a) has the **ALLOCATABLE**, **ASYNCHRONOUS**, **OPTIONAL**, **POINTER**, **TARGET**, **VALUE**, or **VOLATILE** attribute,
 - (b) is an **assumed-shape** array,
 - (c) is **assumed-rank**,
 - (d) is a **coarray**,
 - (e) is of a parameterized derived type, or
 - (f) is **polymorphic**,
 - (3) the procedure has a result that
 - (a) is an array,
 - (b) is a **pointer** or is **allocatable**, or
 - (c) has a nonassumed type parameter value that is not a **constant expression**,
 - (4) the procedure is **elemental**, or
 - (5) the procedure has the **BIND** attribute.

12.4.3 Specification of the procedure interface

12.4.3.1 General

- 1 The interface for an [internal](#), [external](#), [module](#), or [dummy procedure](#) is specified by a [FUNCTION](#), [SUBROUTINE](#), or [ENTRY](#) statement and by specification statements for the [dummy arguments](#) and the result of a function. These statements may appear in the procedure definition, in an [interface body](#), or both, except that the [ENTRY statement](#) shall not appear in an [interface body](#).

NOTE 12.2

An [interface body](#) cannot be used to describe the interface of an [internal procedure](#), a [module procedure](#) that is not a separate [module procedure](#), or an intrinsic procedure because the interfaces of such procedures are already [explicit](#). However, the name of a procedure can appear in a [PROCEDURE statement](#) in an [interface block](#) (12.4.3.2).

12.4.3.2 Interface block

- | | | | |
|----|--------------------------------------|---|---|
| 8 | R1201 <i>interface-block</i> | is | <i>interface-stmt</i>
[<i>interface-specification</i>] ...
<i>end-interface-stmt</i> |
| 11 | R1202 <i>interface-specification</i> | is | <i>interface-body</i>
or <i>procedure-stmt</i> |
| 13 | R1203 <i>interface-stmt</i> | is | INTERFACE [<i>generic-spec</i>]
or ABSTRACT INTERFACE |
| 15 | R1204 <i>end-interface-stmt</i> | is | END INTERFACE [<i>generic-spec</i>] |
| 16 | R1205 <i>interface-body</i> | is | <i>function-stmt</i>
[<i>specification-part</i>]
<i>end-function-stmt</i>
or <i>subroutine-stmt</i>
[<i>specification-part</i>]
<i>end-subroutine-stmt</i> |
| 22 | R1206 <i>procedure-stmt</i> | is | [MODULE] PROCEDURE [::] <i>specific-procedure-list</i> |
| 23 | R1207 <i>specific-procedure</i> | is | <i>procedure-name</i> |
| 24 | R1208 <i>generic-spec</i> | is | <i>generic-name</i>
or OPERATOR (<i>defined-operator</i>)
or ASSIGNMENT (=)
or <i>defined-io-generic-spec</i> |
| 28 | R1209 <i>defined-io-generic-spec</i> | is | READ (FORMATTED)
or READ (UNFORMATTED)
or WRITE (FORMATTED)
or WRITE (UNFORMATTED) |
| 32 | C1201 (R1201) | An <i>interface-block</i> in a subprogram shall not contain an <i>interface-body</i> for a procedure defined by that subprogram. | |
| 34 | C1202 (R1201) | If the <i>end-interface-stmt</i> includes <i>generic-name</i> , the <i>interface-stmt</i> shall specify the same <i>generic-name</i> . If the <i>end-interface-stmt</i> includes ASSIGNMENT(=), the <i>interface-stmt</i> shall specify ASSIGNMENT(=). If the <i>end-interface-stmt</i> includes <i>defined-io-generic-spec</i> , the <i>interface-stmt</i> shall specify the same <i>defined-io-generic-spec</i> . If the <i>end-interface-stmt</i> includes OPERATOR(<i>defined-operator</i>), the <i>interface-stmt</i> shall specify the same <i>defined-operator</i> . If one <i>defined-operator</i> is .LT., .LE., .GT., .GE., .EQ., or .NE., the other is permitted to be the corresponding operator <, <=, >, >=, ==, or /=. | |

- 1 C1203 (R1203) If the *interface-stmt* is ABSTRACT INTERFACE, then the *function-name* in the *function-stmt*
 2 or the *subroutine-name* in the *subroutine-stmt* shall not be the same as a keyword that specifies an
 3 intrinsic type.
- 4 C1204 (R1202) A *procedure-stmt* is allowed only in an interface block that has a *generic-spec*.
- 5 C1205 (R1205) An *interface-body* of a pure procedure shall specify the intents of all *dummy arguments* except
 6 alternate return indicators, *dummy procedures*, and arguments with the POINTER or VALUE attribute.
- 7 C1206 (R1205) An *interface-body* shall not contain a *data-stmt*, *format-stmt*, *entry-stmt*, or *stmt-function-stmt*.
- 8 C1207 (R1206) If MODULE appears in a *procedure-stmt*, each *procedure-name* in that statement shall denote a
 9 *module procedure*.
- 10 C1208 (R1207) A *procedure-name* shall denote a nonintrinsic procedure that has an *explicit interface*.
- 11 C1209 (R1201) An *interface-specification* in a generic interface block shall not specify a procedure that was
 12 specified previously in any accessible interface with the same *generic identifier*.
- 13 1 An external or module subprogram specifies a *specific interface* for each procedure defined in that subprogram.
- 14 2 An interface block introduced by ABSTRACT INTERFACE is an *abstract interface block*. An interface body
 15 in an *abstract interface block* specifies an *abstract interface*. An interface block with a generic specification is
 16 a *generic interface block*. An interface block with neither ABSTRACT nor a generic specification is a *specific*
 17 *interface block*.
- 18 3 The name of the entity declared by an interface body is the *function-name* in the *function-stmt* or the *subroutine-*
 19 *name* in the *subroutine-stmt* that begins the interface body.
- 20 4 A module procedure interface body is an interface body whose initial statement contains the keyword MODULE.
 21 It specifies the interface for a separate *module procedure* (12.6.2.5). A separate *module procedure* is accessible
 22 by *use association* if and only if its interface body is declared in the specification part of a module and is public.
 23 If a corresponding (12.6.2.5) separate *module procedure* is not defined, the interface may be used to specify an
 24 explicit *specific interface* but the procedure shall not be used in any other way.
- 25 5 An interface body in a generic or specific interface block specifies the EXTERNAL attribute and an explicit
 26 specific interface for an *external procedure* or a *dummy procedure*. If the name of the declared procedure is that
 27 of a *dummy argument* in the subprogram containing the interface body, the procedure is a *dummy procedure*;
 28 otherwise, it is an *external procedure*.
- 29 6 An interface body specifies all of the *characteristics* of the explicit specific interface or *abstract interface*. The
 30 specification part of an interface body may specify attributes or define values for data entities that do not
 31 determine *characteristics* of the procedure. Such specifications have no effect.
- 32 7 If an explicit specific interface for an *external procedure* is specified by an interface body or a *procedure declaration*
 33 *statement* (12.4.3.7), the *characteristics* shall be consistent with those specified in the procedure definition, except
 34 that the interface may specify a procedure that is not pure even if the procedure is defined to be pure. An interface
 35 for a procedure defined by an ENTRY statement may be specified by using the entry name as the procedure name in the interface body.
 36 If an *external procedure* does not exist in the program, an interface body for it may be used to specify an explicit
 37 specific interface but the procedure shall not be used in any other way. A procedure shall not have more than
 38 one explicit specific interface in a given *scoping unit*, except that if the interface is accessed by *use association*,
 39 there may be more than one local name for the procedure. If a procedure is accessed by *use association*, each
 40 access shall be to the same procedure declaration or definition.

NOTE 12.3

<p>The <i>dummy argument</i> names in an interface body can be different from the corresponding <i>dummy argument</i> names in the procedure definition because the name of a <i>dummy argument</i> is not a characteristic.</p>
--

NOTE 12.4

An example of a specific interface block is:

```

INTERFACE
  SUBROUTINE EXT1 (X, Y, Z)
    REAL, DIMENSION (100, 100) :: X, Y, Z
  END SUBROUTINE EXT1
  SUBROUTINE EXT2 (X, Z)
    REAL X
    COMPLEX (KIND = 4) Z (2000)
  END SUBROUTINE EXT2
  FUNCTION EXT3 (P, Q)
    LOGICAL EXT3
    INTEGER P (1000)
    LOGICAL Q (1000)
  END FUNCTION EXT3
END INTERFACE

```

This interface block specifies [explicit interfaces](#) for the three [external procedures](#) EXT1, EXT2, and EXT3. Invocations of these procedures can use [argument keywords](#) (12.5.2); for example:

```
PRINT *, EXT3 (Q = P_MASK (N+1 : N+1000), P = ACTUAL_P)
```

1 **12.4.3.3 GENERIC statement**

2 1 A GENERIC statement specifies a generic identifier for one or more specific procedures, in the same way as a
3 generic interface block that does not contain interface bodies.

4 R1210 *generic-stmt* **is** GENERIC [, *access-spec*] :: *generic-spec* => *specific-procedure-list*

5 2 If *access-spec* appears, it specifies the accessibility (5.5.2) of *generic-spec*.

6 **12.4.3.4 IMPORT statement**

7 R1211 *import-stmt* **is** IMPORT [[::] *import-name-list*]
8 **or** IMPORT, ONLY : *import-name-list*
9 **or** IMPORT, NONE
10 **or** IMPORT, ALL

11 C1210 (R1211) An IMPORT statement shall not appear in the *specification-part* of a *main-program*, *external-*
12 *subprogram*, *module*, or *block-data*.

13 C1211 (R1211) Each *import-name* shall be the name of an entity in the [host scoping unit](#).

14 C1212 If any IMPORT statement in a [scoping unit](#) has an **ONLY** specifier, all IMPORT statements in that
15 [scoping unit](#) shall have an **ONLY** specifier.

16 C1213 IMPORT, NONE shall not appear in a submodule.

17 C1214 If an IMPORT, NONE or IMPORT, ALL statement appears in a [scoping unit](#), no other IMPORT
18 statement shall appear in that [scoping unit](#).

19 C1215 Within an interface body, an entity that is accessed by host association shall be accessible by host or use
20 association within the [host scoping unit](#), or explicitly declared prior to the interface body.

21 C1216 An entity whose name appears as an *import-name* or which is made accessible by an IMPORT, ALL
22 statement shall not appear in any context described in 16.5.1.4 that would cause the host entity of that
23 name to be inaccessible.

- 1 1 If the **ONLY** specifier appears on an **IMPORT** statement in a **scoping unit**, an entity is only accessible by host
2 association if its name appears as an *import-name* in that **scoping unit**.
- 3 2 An **IMPORT**, **NONE** statement in a **scoping unit** specifies that no entities in the **host scoping unit** are accessible
4 by host association in that **scoping unit**. This is the default for an interface body for an **external** or **dummy**
5 procedure.
- 6 3 An **IMPORT**, **ALL** statement in a **scoping unit** specifies that all entities from the **host scoping unit** are accessible
7 by host association in that **scoping unit**.
- 8 4 If an **IMPORT** statement with no *import-name-list* appears in a **scoping unit**, every entity in the **host scoping**
9 **unit** is accessible unless its name appears in a context described in 16.5.1.4 that causes it to be inaccessible. This
10 is the default for a nested scoping unit other than an interface body for an **external** or **dummy** procedure.
- 11 5 If an **IMPORT** statement with an *import-name-list* appears in a **scoping unit**, each named entity from the **host**
12 **scoping unit** is accessible by host association.

NOTE 12.5

The **IMPORT**, **NONE** statement can be used to prevent accidental host association:

```

SUBROUTINE s(x,n)
  IMPLICIT NONE
  IMPORT, NONE
  ...
  DO i=1,n ! Forces I to be locally declared.

```

NOTE 12.6

The **IMPORT**, **ALL** statement can be used to confirm the default rules and prevent accidental “shadowing” of host entities:

```

SUBROUTINE outer
  REAL x
  ...
  CONTAINS
  SUBROUTINE inner
    IMPORT, ALL
    ...
    x = x + 1 ! X was prevented from being locally declared...
              ! so must be the host X.

```

NOTE 12.7

The **IMPORT**, **ONLY** statement can be used to document deliberate access via host association whilst blocking accidental access:

```

SUBROUTINE sub
  IMPORT, ONLY :: x, y
  ...
  x = y + z ! X and Y imported, Z must be local.

```

NOTE 12.8

The **IMPORT** statement can be used to allow **module procedures** to have **dummy arguments** that are procedures with **assumed-shape** arguments of an opaque type. For example:

```

MODULE M

```

NOTE 12.8 (cont.)

```

TYPE T
  PRIVATE      ! T is an opaque type
  ...
END TYPE
CONTAINS
SUBROUTINE PROCESS(X,Y,RESULT,MONITOR)
  TYPE(T),INTENT(IN)  :: X(:,,:),Y(:,,:)
  TYPE(T),INTENT(OUT) :: RESULT(:,,:)
  INTERFACE
    SUBROUTINE MONITOR(ITERATION_NUMBER,CURRENT_ESTIMATE)
      IMPORT T
      INTEGER,INTENT(IN)  :: ITERATION_NUMBER
      TYPE(T),INTENT(IN)  :: CURRENT_ESTIMATE(:,,:)
    END SUBROUTINE
  END INTERFACE
  ...
END SUBROUTINE
END MODULE

```

The MONITOR [dummy procedure](#) requires an [explicit interface](#) because it has an [assumed-shape array](#) argument, but TYPE(T) would not be available inside the interface body without the IMPORT statement.

1 **12.4.3.5 Generic interfaces**2 **12.4.3.5.1 Generic identifiers**

3 1 A [generic interface block](#) specifies a [generic interface](#) for each of the procedures in the interface block. The
4 PROCEDURE statement lists [procedure pointers](#), [external procedures](#), [dummy procedures](#), or [module procedures](#)
5 that have this [generic interface](#). A [GENERIC statement](#) specifies a generic interface for each of the procedures
6 named in its [specific-procedure-list](#). A [generic interface](#) is always [explicit](#).

7 2 The [generic-spec](#) in an [interface-stmt](#) is a [generic identifier](#) for all the procedures in the interface block. The
8 [generic-spec](#) in a [GENERIC statement](#) is a [generic identifier](#) for all of the procedures named in its [specific-](#)
9 [procedure-list](#). The rules specifying how any two procedures with the same [generic identifier](#) shall differ are given
10 in [12.4.3.5.5](#). They ensure that any generic invocation applies to at most one specific procedure. If a specific
11 procedure in a [generic interface](#) has a function [dummy argument](#), that argument shall have its type and type
12 parameters explicitly declared in the [specific interface](#).

13 3 A generic name is a [generic identifier](#) that refers to all of the procedure names in the interface block. A generic
14 name may be the same as any one of the procedure names in the interface block, or the same as any accessible
15 generic name.

16 4 A generic name may be the same as a derived-type name, in which case all of the procedures in the interface
17 block shall be functions.

18 5 An [interface-stmt](#) having a [defined-io-generic-spec](#) is an interface for a [defined input/output](#) procedure ([9.6.4.8](#)).

NOTE 12.9

An example of a generic procedure interface is:

```

INTERFACE SWITCH
  SUBROUTINE INT_SWITCH (X, Y)
    INTEGER, INTENT (INOUT) :: X, Y
  END SUBROUTINE INT_SWITCH
  SUBROUTINE REAL_SWITCH (X, Y)

```

NOTE 12.9 (cont.)

```

REAL, INTENT (INOUT) :: X, Y
END SUBROUTINE REAL_SWITCH
SUBROUTINE COMPLEX_SWITCH (X, Y)
  COMPLEX, INTENT (INOUT) :: X, Y
  END SUBROUTINE COMPLEX_SWITCH
END INTERFACE SWITCH

```

Any of these three subroutines (INT_SWITCH, REAL_SWITCH, COMPLEX_SWITCH) can be referenced with the generic name SWITCH, as well as by its [specific name](#). For example, a reference to INT_SWITCH could take the form:

```
CALL SWITCH (MAX_VAL, LOC_VAL) ! MAX_VAL and LOC_VAL are of type INTEGER
```

NOTE 12.10

A [type-bound-generic-stmt](#) within a derived-type definition (4.5.5) specifies a [generic identifier](#) for a set of [type-bound procedures](#).

1 **12.4.3.5.2 Defined operations**

- 2 1 If **OPERATOR** is specified in a generic specification, all of the procedures specified in the [generic interface](#) shall
3 be functions that may be referenced as [defined operations](#) (7.1.6, 12.5). In the case of functions of two arguments,
4 infix binary operator notation is implied. In the case of functions of one argument, prefix operator notation is
5 implied. **OPERATOR** shall not be specified for functions with no arguments or for functions with more than two
6 arguments. The [dummy arguments](#) shall be nonoptional [dummy data objects](#) and shall have the **INTENT (IN)**
7 or **VALUE** attribute. The function result shall not have assumed character length. If the operator is an *intrinsic-operator*
8 (R308), the number of [dummy arguments](#) shall be consistent with the intrinsic uses of that operator, and the
9 types, kind type parameters, or [ranks](#) of the [dummy arguments](#) shall differ from those required for the intrinsic
10 operation (7.1.5).
- 11 2 A [defined operation](#) is treated as a reference to the function. For a unary [defined operation](#), the operand
12 corresponds to the function's [dummy argument](#); for a binary operation, the left-hand operand corresponds to the
13 first [dummy argument](#) of the function and the right-hand operand corresponds to the second [dummy argument](#).
14 All restrictions and constraints that apply to [actual arguments](#) in a [reference](#) to the function also apply to the
15 corresponding operands in the expression as if they were used as [actual arguments](#).
- 16 3 A given defined operator may, as with generic names, apply to more than one function, in which case it is generic
17 in exact analogy to generic procedure names. For intrinsic operator symbols, the generic properties include the
18 intrinsic operations they represent. Because both forms of each relational operator have the same interpretation
19 (7.1.6.2), extending one form (such as <=) has the effect of defining both forms (<= and **.LE.**).

NOTE 12.11

An example of the use of the **OPERATOR** generic specification is:

```

INTERFACE OPERATOR ( * )
  FUNCTION BOOLEAN_AND (B1, B2)
    LOGICAL, INTENT (IN) :: B1 (:), B2 (SIZE (B1))
    LOGICAL :: BOOLEAN_AND (SIZE (B1))
  END FUNCTION BOOLEAN_AND
END INTERFACE OPERATOR ( * )

```

This allows, for example

```
SENSOR (1:N) * ACTION (1:N)
```

NOTE 12.11 (cont.)

as an alternative to the function call

```
BOOLEAN_AND (SENSOR (1:N), ACTION (1:N)) ! SENSOR and ACTION are
                                           ! of type LOGICAL
```

1 **12.4.3.5.3 Defined assignments**

- 2 1 If **ASSIGNMENT** (=) is specified in a generic specification, all the procedures in the **generic interface** shall
 3 be subroutines that may be referenced as **defined assignments** (7.2.1.4, 7.2.1.5). **Defined assignment** may, as
 4 with generic names, apply to more than one subroutine, in which case it is generic in exact analogy to generic
 5 procedure names.
- 6 2 Each of these subroutines shall have exactly two **dummy arguments**. The **dummy arguments** shall be nonoptional
 7 **dummy data objects**. The first argument shall have **INTENT (OUT)** or **INTENT (INOUT)** and the second
 8 argument shall have the **INTENT (IN)** or **VALUE** attribute. Either the second argument shall be an array whose
 9 **rank** differs from that of the first argument, the **declared types** and **kind type parameters** of the arguments shall
 10 not conform as specified in Table 7.8, or the first argument shall be of derived type. A **defined assignment** is
 11 treated as a reference to the subroutine, with the left-hand side as the first argument and the right-hand side
 12 enclosed in parentheses as the second argument. All restrictions and constraints that apply to **actual arguments**
 13 in a reference to the subroutine also apply to the left-hand-side and to the right-hand-side enclosed in parentheses
 14 as if they were used as **actual arguments**. The **ASSIGNMENT** generic specification specifies that assignment is
 15 extended or redefined.

NOTE 12.12

An example of the use of the **ASSIGNMENT** generic specification is:

```
INTERFACE ASSIGNMENT ( = )

  SUBROUTINE LOGICAL_TO_NUMERIC (N, B)
    INTEGER, INTENT (OUT) :: N
    LOGICAL, INTENT (IN)  :: B
  END SUBROUTINE LOGICAL_TO_NUMERIC
  SUBROUTINE CHAR_TO_STRING (S, C)
    USE STRING_MODULE      ! Contains definition of type STRING
    TYPE (STRING), INTENT (OUT) :: S ! A variable-length string
    CHARACTER (*), INTENT (IN)  :: C
  END SUBROUTINE CHAR_TO_STRING
END INTERFACE ASSIGNMENT ( = )
```

Example assignments are:

```
KOUNT = SENSOR (J) ! CALL LOGICAL_TO_NUMERIC (KOUNT, (SENSOR (J)))
NOTE  = '89AB'    ! CALL CHAR_TO_STRING (NOTE, ('89AB'))
```

NOTE 12.13

A procedure whose second **dummy argument** has the **ALLOCATABLE** or **POINTER** attribute cannot be accessed via **defined assignment**, even if it given the **ASSIGNMENT** (=) generic identifier. This is because the **actual argument** associated with that **dummy argument** is the right-hand side of the assignment enclosed in parentheses, which makes the **actual argument** an expression that does not have the **ALLOCATABLE**, **POINTER**, or **TARGET** attribute.

12.4.3.5.4 Defined input/output procedure interfaces

- 1 All of the procedures specified in an interface block for a **defined input/output** procedure shall be subroutines that have interfaces as described in 9.6.4.8.3.

12.4.3.5.5 Restrictions on generic declarations

- 1 This subclause contains the rules that shall be satisfied by every pair of specific procedures that have the same **generic identifier** within the scope of the identifier. If a generic procedure is accessed from a module, the rules apply to all the specific versions even if some of them are inaccessible by their **specific names**.

NOTE 12.14

In most **scoping units**, the possible sources of procedures with a particular **generic identifier** are the accessible interface blocks and the generic **bindings** other than names for the accessible objects in that **scoping unit**. In a type definition, they are the generic **bindings**, including those from a **parent type**.

- 2 A **dummy argument** is type, kind, and **rank** compatible, or TKR compatible, with another **dummy argument** if the first is **type compatible** with the second, the kind type parameters of the first have the same values as the corresponding kind type parameters of the second, and both have the same **rank** or either is **assumed-rank**.

- 3 Two **dummy arguments** are distinguishable if

- one is a procedure and the other is a data object,
- they are both data objects or known to be functions, and neither is TKR compatible with the other,
- one has the **ALLOCATABLE attribute** and the other has the **POINTER attribute** and not the **INTENT (IN) attribute**, or
- one is a function with nonzero **rank** and the other is not known to be a function.

C1217 Within the scope of a generic operator, if two procedures with that identifier have the same number of arguments, one shall have a **dummy argument** that corresponds by position in the argument list to a **dummy argument** of the other that is distinguishable from it.

C1218 Within the scope of the generic **ASSIGNMENT (=)** identifier, if two procedures have that identifier, one shall have a **dummy argument** that corresponds by position in the argument list to a **dummy argument** of the other that is distinguishable from it.

C1219 Within the scope of a *defined-io-generic-spec*, if two procedures have that **generic identifier**, their **dtv arguments** (9.6.4.8.3) shall be distinguishable.

C1220 Within the scope of a generic name, each pair of procedures identified by that name shall both be subroutines or both be functions, and

- (1) there is a non-passed-object **dummy data object** in one or the other of them such that
 - (a) the number of **dummy data objects** in one that are nonoptional, are not passed-object, and with which that **dummy data object** is TKR compatible, possibly including that **dummy data object** itself, exceeds
 - (b) the number of non-passed-object **dummy data objects**, both optional and nonoptional, in the other that are not distinguishable from that **dummy data object**,
- (2) the number of nonoptional **dummy procedures** in one of them exceeds the number of **dummy procedures** in the other,
- (3) both have **passed-object dummy arguments** and the **passed-object dummy arguments** are distinguishable, or
- (4) at least one of them shall have both

- 1 (a) a nonoptional non-passed-object [dummy argument](#) at an effective position such that either
 2 the other procedure has no [dummy argument](#) at that effective position or the [dummy argu-
 3 ment](#) at that position is distinguishable from it, and
 4 (b) a nonoptional non-passed-object [dummy argument](#) whose name is such that either the other
 5 procedure has no [dummy argument](#) with that name or the [dummy argument](#) with that name
 6 is distinguishable from it,
 7 and the [dummy argument](#) that disambiguates by position shall either be the same as or occur
 8 earlier in the argument list than the one that disambiguates by name.

9 4 The effective position of a [dummy argument](#) is its position in the argument list after any [passed-object dummy
 10 argument](#) has been removed.

11 5 Within the scope of a generic name that is the same as the generic name of an intrinsic procedure, the intrinsic
 12 procedure is not accessible by its generic name if the procedures in the interface and the intrinsic procedure are
 13 not all functions or not all subroutines. If a generic invocation is consistent with both a specific procedure from
 14 an interface and an accessible intrinsic procedure, it is the specific procedure from the interface that is referenced.

NOTE 12.15

An extensive explanation of the application of these rules is in [C.9.6](#).

15 12.4.3.6 EXTERNAL statement

16 1 An EXTERNAL statement specifies the [EXTERNAL attribute](#) (5.5.9) for a list of names.

17 R1212 *external-stmt* is EXTERNAL [::] *external-name-list*

18 2 The appearance of the name of a [block data program unit](#) in an EXTERNAL statement confirms that the [block
 19 data program unit](#) is a part of the program.

NOTE 12.16

For explanatory information on potential portability problems with [external procedures](#), see subclause [C.9.1](#).

NOTE 12.17

An example of an EXTERNAL statement is:

EXTERNAL FOCUS

20 12.4.3.7 Procedure declaration statement

21 1 A procedure declaration statement declares [procedure pointers](#), [dummy procedures](#), and [external procedures](#). It
 22 specifies the [EXTERNAL attribute](#) (5.5.9) for all entities in the *proc-decl-list*.

23 R1213 *procedure-declaration-stmt* is PROCEDURE ([*proc-interface*]) ■
 24 ■ [[, *proc-attr-spec*] ... ::] *proc-decl-list*

25 R1214 *proc-interface* is *interface-name*
 26 or *declaration-type-spec*

27 R1215 *proc-attr-spec* is *access-spec*
 28 or *proc-language-binding-spec*
 29 or INTENT (*intent-spec*)
 30 or OPTIONAL
 31 or POINTER
 32 or PROTECTED
 33 or SAVE

1 R1216 *proc-decl* is *procedure-entity-name* [=> *proc-pointer-init*]

2 R1217 *interface-name* is *name*

3 R1218 *proc-pointer-init* is *null-init*
4 or *initial-proc-target*

5 R1219 *initial-proc-target* is *procedure-name*
6

7 C1221 (R1217) The *name* shall be the name of an **abstract interface** or of a procedure that has an **explicit interface**. If *name* is declared by a *procedure-declaration-stmt* it shall be previously declared. If *name* denotes an intrinsic procedure it shall be one that is listed in Table 13.2.
8
9

10 C1222 (R1217) The *name* shall not be the same as a keyword that specifies an intrinsic type.

11 C1223 (R1213) If a *proc-interface* describes an **elemental procedure**, each *procedure-entity-name* shall specify an **external procedure**.
12

13 C1224 (R1216) If => appears in *proc-decl*, the procedure entity shall have the **POINTER** attribute.

14 C1225 (R1219) The *procedure-name* shall be the name of a nonelemental **external** or **module procedure**, or a
15 specific intrinsic function listed in Table 13.2.

16 C1226 (R1213) If *proc-language-binding-spec* with a **NAME=** is specified, then *proc-decl-list* shall contain exactly
17 one *proc-decl*, which shall neither have the **POINTER** attribute nor be a **dummy procedure**.

18 C1227 (R1213) If *proc-language-binding-spec* is specified, the *proc-interface* shall appear, it shall be an *interface-*
19 *name*, and *interface-name* shall be declared with a *proc-language-binding-spec*.

20 2 If *proc-interface* appears and consists of *interface-name*, it specifies an explicit **specific interface** (12.4.3.2) for the
21 declared procedure entities. The **abstract interface** (12.4) is that specified by the interface named by *interface-*
22 *name*. The interface specified by *interface-name* shall not depend on any characteristic of a procedure identified
23 by a *procedure-entity-name* in the *proc-decl-list* of the same procedure declaration statement.

24 3 If *proc-interface* appears and consists of *declaration-type-spec*, it specifies that the declared procedure entities are
25 functions having **implicit interfaces** and the specified result type. If a type is specified for an external function,
26 its function definition (12.6.2.2) shall specify the same result type and type parameters.

27 4 If *proc-interface* does not appear, the procedure declaration statement does not specify whether the declared
28 procedure entities are subroutines or functions.

29 5 If a *proc-attr-spec* other than a *proc-language-binding-spec* appears, it specifies that the declared procedure entities
30 have that attribute. These attributes are described in 5.5. If a *proc-language-binding-spec* with **NAME=** appears,
31 it specifies a **binding label** or its absence, as described in 15.10.2. A *proc-language-binding-spec* without a **NAME=**
32 is allowed, but is redundant with the *proc-interface* required by C1227.

33 6 If => appears in a *proc-decl* in a *procedure-declaration-stmt* it specifies the initial association status of the
34 corresponding procedure entity, and implies the **SAVE** attribute, which may be confirmed by explicit specification.
35 If => *null-init* appears, the procedure entity is initially **disassociated**. If => *initial-proc-target* appears, the
36 procedure entity is initially associated with the **target**.

37 7 If *procedure-entity-name* has an **explicit interface**, its **characteristics** shall be the same as *initial-proc-target* except
38 that *initial-proc-target* may be pure even if *procedure-entity-name* is not pure and *initial-proc-target* may be an **elemental**
39 intrinsic procedure.

40 8 If the **characteristics** of *procedure-entity-name* or *initial-proc-target* are such that an **explicit interface** is required,
41 both *procedure-entity-name* and *initial-proc-target* shall have an **explicit interface**.

42 9 If *procedure-entity-name* has an **implicit interface** and is explicitly typed or referenced as a function, *initial-proc-*

- 1 *target* shall be a function. If *procedure-entity-name* has an **implicit interface** and is referenced as a subroutine,
 2 *initial-proc-target* shall be a subroutine.
- 3 10 If *initial-proc-target* and *procedure-entity-name* are functions, their results shall have the same **characteristics**.

NOTE 12.18

The following code illustrates procedure declaration statements. Note 7.46 illustrates the use of the P and BESSEL defined by this code.

```

ABSTRACT INTERFACE
  FUNCTION REAL_FUNC (X)
    REAL, INTENT (IN) :: X
    REAL :: REAL_FUNC
  END FUNCTION REAL_FUNC
END INTERFACE

INTERFACE
  SUBROUTINE SUB (X)
    REAL, INTENT (IN) :: X
  END SUBROUTINE SUB
END INTERFACE

!-- Some external or dummy procedures with explicit interface.
PROCEDURE (REAL_FUNC) :: BESSEL, GFUN
PROCEDURE (SUB) :: PRINT_REAL
!-- Some procedure pointers with explicit interface,
!-- one initialized to NULL().
PROCEDURE (REAL_FUNC), POINTER :: P, R => NULL()
PROCEDURE (REAL_FUNC), POINTER :: PTR_TO_GFUN
!-- A derived type with a procedure pointer component ...
TYPE STRUCT_TYPE
  PROCEDURE (REAL_FUNC), POINTER, NOPASS :: COMPONENT
END TYPE STRUCT_TYPE
!-- ... and a variable of that type.
TYPE(STRUCT_TYPE) :: STRUCT
!-- An external or dummy function with implicit interface
PROCEDURE (REAL) :: PSI

```

4 **12.4.3.8 INTRINSIC statement**

- 5 1 An INTRINSIC statement specifies the **INTRINSIC attribute** (5.5.11) for a list of names.

6 R1220 *intrinsic-stmt* is INTRINSIC [::] *intrinsic-procedure-name-list*

7 C1228 (R1220) Each *intrinsic-procedure-name* shall be the name of an intrinsic procedure.

8 **12.4.3.9 Implicit interface specification**

- 9 1 If the interface of a function is **implicit**, the type and type parameters of the function result are specified by an
 10 implicit or explicit type specification of the function name. The type, type parameters, and shape of the **dummy**
 11 **arguments** of a procedure invoked from where the interface of the procedure is **implicit** shall be such that each
 12 **actual argument** is consistent with the **characteristics** of the corresponding **dummy argument**.

12.5 Procedure reference

12.5.1 Syntax of a procedure reference

1 The form of a procedure reference is dependent on the [interface](#) of the procedure or [procedure pointer](#), but is independent of the means by which the procedure is defined. The forms of procedure references are as follows.

R1221 *function-reference* is *procedure-designator* ([*actual-arg-spec-list*])

C1229 (R1221) The *procedure-designator* shall designate a function.

C1230 (R1221) The *actual-arg-spec-list* shall not contain an *alt-return-spec*.

R1222 *call-stmt* is CALL *procedure-designator* [([*actual-arg-spec-list*])]

C1231 (R1222) The *procedure-designator* shall designate a subroutine.

R1223 *procedure-designator* is *procedure-name*
 or *proc-component-ref*
 or *data-ref* % *binding-name*

C1232 (R1223) A *procedure-name* shall be a generic name or the name of a procedure.

C1233 (R1223) A *binding-name* shall be a [binding name](#) (4.5.5) of the [declared type](#) of *data-ref*.

C1234 (R1223) A *data-ref* shall not be a [polymorphic](#) subobject of a [coindexed object](#).

C1235 (R1223) If *data-ref* is an array, the referenced [type-bound procedure](#) shall have the [PASS attribute](#).

2 The *data-ref* in a *procedure-designator* shall not be an unallocated [allocatable](#) variable or a pointer that is not associated.

3 Resolving references to [type-bound procedures](#) is described in 12.5.6.

4 A function may also be referenced as a [defined operation](#) (7.1.6). A subroutine may also be referenced as a [defined assignment](#) (7.2.1.4, 7.2.1.5), by [defined input/output](#) (9.6.4.8), or by [finalization](#) (4.5.6).

NOTE 12.19

When resolving [type-bound procedure](#) references, constraints on the use of [coindexed objects](#) ensure that the [coindexed object](#) (on the remote [image](#)) has the same [dynamic type](#) as the corresponding object on the local [image](#). Thus a processor can resolve the [type-bound procedure](#) using the [coarray](#) variable on its own [image](#) and pass the [coindexed object](#) as the [actual argument](#).

R1224 *actual-arg-spec* is [*keyword* =] *actual-arg*

R1225 *actual-arg* is *expr*
 or *variable*
 or *procedure-name*
 or *proc-component-ref*
 or *alt-return-spec*

R1226 *alt-return-spec* is * *label*

C1236 (R1224) The *keyword* = shall not appear if the [interface](#) of the procedure is [implicit](#).

C1237 (R1224) The *keyword* = shall not be omitted from an *actual-arg-spec* unless it has been omitted from each preceding *actual-arg-spec* in the argument list.

C1238 (R1224) Each *keyword* shall be the name of a [dummy argument](#) in the [explicit interface](#) of the procedure.

- 1 C1239 (R1225) A nonintrinsic [elemental procedure](#) shall not be used as an [actual argument](#).
- 2 C1240 (R1225) A *procedure-name* shall be the name of an [external](#), [internal](#), [module](#), or [dummy](#) procedure, a
3 specific intrinsic function listed in Table 13.2, or a [procedure pointer](#).
- 4 C1241 (R1225) *expr* shall not be a variable.
- 5 C1242 (R1226) The *label* shall be the [statement label](#) of a [branch target statement](#) that appears in the same [inclusive scope](#) as the
6 [call-stmt](#).
- 7 C1243 An actual argument that is a [coindexed object](#) shall not have a pointer ultimate component.

NOTE 12.20

Examples of procedure reference using [procedure pointers](#):

```
P => BESSEL
WRITE (*, *) P(2.5)      !-- BESSEL(2.5)

S => PRINT_REAL
CALL S(3.14)
```

NOTE 12.21

An [internal procedure](#) cannot be invoked using a [procedure pointer](#) from either Fortran or C after the [host instance](#) completes execution, because the pointer is then undefined. While the [host instance](#) is active, however, if an [internal procedure](#) was passed as an [actual argument](#) or is the [target](#) of a [procedure pointer](#), it could be invoked from outside of the host subprogram.

Assume there is a procedure with the following [interface](#) that calculates $\int_a^b f(x) dx$.

```
INTERFACE
  FUNCTION INTEGRATE(F, A, B) RESULT(INTEGRAL) BIND(C)
    USE ISO_C_BINDING
    INTERFACE
      FUNCTION F(X) BIND(C) ! Integrand
        USE ISO_C_BINDING
        REAL(C_FLOAT), VALUE :: X
        REAL(C_FLOAT) :: F
      END FUNCTION
    END INTERFACE
    REAL(C_FLOAT), VALUE :: A, B ! Bounds
    REAL(C_FLOAT) :: INTEGRAL
  END FUNCTION INTEGRATE
END INTERFACE
```

This procedure can be called from Fortran or C, and could be written in either Fortran or C. The argument *F* representing the mathematical function $f(x)$ can be written as an [internal procedure](#); this [internal procedure](#) will have access to any [host instance local variables](#) necessary to actually calculate $f(x)$. For example:

```
REAL FUNCTION MY_INTEGRATION(N, A, B) RESULT(INTEGRAL)
  ! Integrate f(x)=x^n over [a,b]
  USE ISO_C_BINDING
  INTEGER, INTENT(IN) :: N
  REAL, INTENT(IN) :: A, B

  INTEGRAL = INTEGRATE(MY_F, REAL(A, C_FLOAT), REAL(B, C_FLOAT))
  ! This will call the internal function MY_F to calculate f(x).
```

NOTE 12.21 (cont.)

! The above interface of INTEGRATE must be explicit and available.

CONTAINS

```
REAL(C_FLOAT) FUNCTION MY_F(X) BIND(C) ! Integrand
  REAL(C_FLOAT), VALUE :: X
  MY_F = X**N ! N is taken from the host instance of MY_INTEGRATION.
END FUNCTION
```

END FUNCTION MY_INTEGRATION

The function INTEGRATE cannot retain a function pointer to MY_F and use it after INTEGRATE has finished execution, because the [host instance](#) of MY_F might no longer exist, making the pointer undefined. If such a pointer is retained, then it can only be used to invoke MY_F during the execution of the [host instance](#) of MY_INTEGRATION called from INTEGRATE.

12.5.2 Actual arguments, dummy arguments, and argument association

12.5.2.1 Argument correspondence

- 1 In either a subroutine reference or a function reference, the [actual argument](#) list identifies the correspondence between the [actual arguments](#) and the [dummy arguments](#) of the procedure. This correspondence may be established either by keyword or by position. If an [argument keyword](#) appears, the [actual argument](#) corresponds to the [dummy argument](#) whose name is the same as the [argument keyword](#) (using the [dummy argument](#) names from the [interface](#) accessible by the [procedure reference](#)). In the absence of an [argument keyword](#), an [actual argument](#) corresponds to the [dummy argument](#) occupying the corresponding position in the reduced [dummy argument](#) list; that is, the first [actual argument](#) corresponds to the first [dummy argument](#) in the reduced list, the second [actual argument](#) corresponds to the second [dummy argument](#) in the reduced list, etc. The reduced [dummy argument](#) list is either the full [dummy argument](#) list or, if there is a [passed-object dummy argument](#) (4.5.4.5), the [dummy argument](#) list with the [passed-object dummy argument](#) omitted. Exactly one [actual argument](#) shall correspond to each nonoptional [dummy argument](#). At most one [actual argument](#) shall correspond to each optional [dummy argument](#). Each [actual argument](#) shall correspond to a [dummy argument](#).

NOTE 12.22

For example, the procedure defined by

```
SUBROUTINE SOLVE (FUNCT, SOLUTION, METHOD, STRATEGY, PRINT)
  INTERFACE
    FUNCTION FUNCT (X)
      REAL FUNCT, X
    END FUNCTION FUNCT
  END INTERFACE
  REAL SOLUTION
  INTEGER, OPTIONAL :: METHOD, STRATEGY, PRINT
  ...
```

can be invoked with

```
CALL SOLVE (FUN, SOL, PRINT = 6)
```

provided its [interface](#) is [explicit](#), and if the [interface](#) is specified by an [interface body](#), the name of the last argument is PRINT.

12.5.2.2 The passed-object dummy argument and argument correspondence

- 1 In a reference to a [type-bound procedure](#), or a [procedure pointer](#) component, that has a [passed-object dummy argument](#) (4.5.4.5), the *data-ref* of the *function-reference* or *call-stmt* corresponds, as an [actual argument](#), with the [passed-object dummy argument](#).

12.5.2.3 Argument association

- 1 Except in references to intrinsic [inquiry functions](#), a pointer [actual argument](#) that corresponds to a nonoptional nonpointer [dummy argument](#) shall be [pointer associated](#) with a [target](#).
- 2 If a nonpointer [dummy argument](#) without the [VALUE attribute](#) corresponds to a pointer [actual argument](#) that is [pointer associated](#) with a [target](#),
- if the [dummy argument](#) is [polymorphic](#), it becomes argument associated with that [target](#);
 - if the [dummy argument](#) is nonpolymorphic, it becomes argument associated with the [declared type](#) part of that [target](#).
- 3 If a present nonpointer [dummy argument](#) without the [VALUE attribute](#) corresponds to a nonpointer [actual argument](#),
- if the [dummy argument](#) is [polymorphic](#), it becomes argument associated with that [actual argument](#);
 - if the [dummy argument](#) is nonpolymorphic, it becomes argument associated with the [declared type](#) part of that [actual argument](#).
- 4 A present [dummy argument](#) with the [VALUE attribute](#) becomes argument associated with a [definable](#) anonymous data object whose initial value is the value of the [actual argument](#).
- 5 A present pointer [dummy argument](#) that corresponds to a pointer [actual argument](#) becomes argument associated with that [actual argument](#). A present pointer [dummy argument](#) that does not correspond to a pointer [actual argument](#) is not argument associated.
- 6 The entity that is argument associated with a [dummy argument](#) is called its [effective argument](#).
- 7 The [ultimate argument](#) is the [effective argument](#) if the [effective argument](#) is not a [dummy argument](#) or a subobject of a [dummy argument](#). If the [effective argument](#) is a dummy argument, the [ultimate argument](#) is the [ultimate argument](#) of that dummy argument. If the [effective argument](#) is a subobject of a dummy argument, the [ultimate argument](#) is the corresponding subobject of the [ultimate argument](#) of that dummy argument.

NOTE 12.23

For the sequence of subroutine calls

```

INTEGER :: X(100)
CALL SUBA (X)
...
SUBROUTINE SUBA(A)
  INTEGER :: A(:)
  CALL SUBB (A(1:5), A(5:1:-1))
  ...
SUBROUTINE SUBB(B, C)
  INTEGER :: B(:), C(:)

```

the [ultimate argument](#) of B is X(1:5). The [ultimate argument](#) of C is X(5:1:-1) and this is not the same object as the [ultimate argument](#) of B.

NOTE 12.24

Fortran [argument association](#) is usually similar to call by reference and call by value-result. If the [VALUE attribute](#) is specified, the effect is as if the [actual argument](#) is assigned to a temporary, and the temporary is

NOTE 12.24 (cont.)

then argument associated with the dummy argument. Subsequent changes to the value or definition status of the dummy argument do not affect the **actual argument**. The actual mechanism by which this happens is determined by the processor.

12.5.2.4 Ordinary dummy variables

- 1
- 2 1 The requirements in this subclause apply to **actual arguments** that correspond to nonallocatable nonpointer
3 dummy data objects.
- 4 2 The **dummy argument** shall be **type compatible** with the **actual argument**. If the **actual argument** is a **polymorphic
5 coindexed object**, the dummy argument shall not be **polymorphic**. If the **actual argument** is a **polymorphic
6 assumed-size array**, the **dummy argument** shall be **polymorphic**. If the **actual argument** is of a derived type that
7 has **type parameters**, **type-bound procedures**, or **final subroutines**, the **dummy argument** shall not be **assumed-
8 type**.
- 9 3 The **kind type parameter** values of the **actual argument** shall agree with the corresponding ones of the **dummy
10 argument**. The **length type parameter** values of a present **actual argument** shall agree with the corresponding
11 ones of the **dummy argument** that are not assumed, except for the case of the character length parameter of
12 an **actual argument** of type character with default kind or C character kind (15.2.2) associated with a **dummy
13 argument** that is not **assumed-shape** or **assumed-rank**.
- 14 4 If a present scalar **dummy argument** is of type character with default kind or C character kind, the length *len* of
15 the **dummy argument** shall be less than or equal to the length of the **actual argument**. The **dummy argument**
16 becomes associated with the leftmost *len* characters of the **actual argument**. If a present array **dummy argument**
17 is of type character with default kind or C character kind and is not **assumed-shape** or **assumed-rank**, it becomes
18 associated with the leftmost characters of the **actual argument** element sequence (12.5.2.11).
- 19 5 The values of **assumed type parameters** of a **dummy argument** are assumed from the corresponding type para-
20 meters of its **effective argument**.
- 21 6 If the **actual argument** is a **coindexed object** with an **allocatable ultimate component**, the dummy argument shall
22 have the **INTENT (IN)** or the **VALUE** attribute.

NOTE 12.25

If the **actual argument** is a **coindexed object**, a processor that uses distributed memory might create a copy on the executing **image** of the **actual argument**, including copies of any allocated **allocatable subobjects**, and associate the **dummy argument** with that copy. If necessary, on return from the procedure, the value of the copy would be copied back to the **actual argument**.

- 23 7 Except in references to intrinsic **inquiry functions**, if the dummy argument is nonoptional and the **actual argument**
24 is **allocatable**, the corresponding **actual argument** shall be allocated.
- 25 8 If the dummy argument does not have the **TARGET attribute**, any pointers associated with the **effective argument**
26 do not become associated with the corresponding dummy argument on invocation of the procedure. If such a
27 dummy argument is used as an **actual argument** that corresponds to a dummy argument with the **TARGET
28 attribute**, whether any pointers associated with the original **effective argument** become associated with the dummy
29 argument with the **TARGET attribute** is processor dependent.
- 30 9 If the dummy argument has the **TARGET attribute**, does not have the **VALUE attribute**, and either the **effective
31 argument** is **simply contiguous** or the **dummy argument** is scalar, **assumed-rank**, or **assumed-shape**, and does not
32 have the **CONTIGUOUS attribute**, and the **effective argument** has the **TARGET attribute** but is not a **coindexed
33 object** or an **array section** with a **vector subscript** then
- any pointers associated with the **effective argument** become associated with the corresponding dummy
34 argument on invocation of the procedure, and
35

- 1 • when execution of the procedure completes, any pointers that do not become undefined (16.5.2.5) and are
2 associated with the dummy argument remain associated with the **effective argument**.
- 3 10 If the dummy argument has the **TARGET attribute** and is an **explicit-shape array**, an **assumed-shape array** with
4 the **CONTIGUOUS attribute**, an **assumed-rank object** with the **CONTIGUOUS attribute**, or an **assumed-size**
5 **array**, and the **effective argument** has the **TARGET attribute** but is not **simply contiguous** and is not an **array**
6 **section** with a **vector subscript** then
- 7 • on invocation of the procedure, whether any pointers associated with the **effective argument** become asso-
8 ciated with the corresponding dummy argument is processor dependent, and
- 9 • when execution of the procedure completes, the **pointer association** status of any pointer that is **pointer**
10 **associated** with the **dummy argument** is processor dependent.
- 11 11 If the dummy argument has the **TARGET attribute** and the **effective argument** does not have the **TARGET**
12 **attribute** or is an **array section** with a **vector subscript**, any pointers associated with the dummy argument
13 become undefined when execution of the procedure completes.
- 14 12 If the **dummy argument** has the **TARGET attribute** and the **VALUE attribute**, any pointers associated with the
15 **dummy argument** become undefined when execution of the procedure completes.
- 16 13 If the **actual argument** is a **coindexed scalar**, the corresponding **dummy argument** shall be scalar. If the **actual**
17 **argument** is a noncoindexed scalar, the corresponding **dummy argument** shall be scalar unless the **actual argument**
18 is default character, of type character with the C character kind (15.2.2), or is an element or substring of an element
19 of an array that is not an **assumed-shape**, **pointer**, or **polymorphic array**. If the procedure is **nonelemental** and is
20 referenced by a generic name or as a defined operator or **defined assignment**, the **ranks** of the **actual arguments**
21 and corresponding **dummy arguments** shall agree.
- 22 14 If a dummy argument is an **assumed-shape array**, the **rank** of the **actual argument** shall be the same as the **rank**
23 of the dummy argument; the **actual argument** shall not be an **assumed-size array** (including an array element
24 **designator** or an array element substring **designator**).
- 25 15 An **actual argument** of any **rank** may correspond to an **assumed-rank** dummy argument. The **rank** and **shape**
26 of the dummy argument are the **rank** and **shape** of the corresponding **actual argument**. If the rank is nonzero,
27 the lower and upper bounds of the dummy argument are those that would be given by the intrinsic functions
28 **LBOUND** and **UBOUND** respectively if applied to the **actual argument**, except that when the **actual argument**
29 is **assumed-size**, the upper bound of the last dimension of the dummy argument is 2 less than the lower bound of
30 that dimension.
- 31 16 Except when a procedure reference is **elemental** (12.8), each element of an array **actual argument** or of a sequence
32 in a sequence association (12.5.2.11) is associated with the element of the dummy array that has the same position
33 in array element order (6.5.3.2).

NOTE 12.26

For default character sequence associations, the interpretation of element is provided in 12.5.2.11.

- 34 17 A scalar dummy argument of a **nonelemental** procedure shall correspond only to a scalar actual argument.
- 35 18 If a dummy argument has **INTENT (OUT)** or **INTENT (INOUT)**, the **actual argument** shall be **definable**. If a
36 dummy argument has **INTENT (OUT)**, the **effective argument** becomes undefined at the time the association is
37 established, except for **direct components** of an object of derived type for which **default initialization** has been
38 specified.
- 39 19 If the procedure is **nonelemental** and the **actual argument** is an **array section** having a **vector subscript**, the dummy
40 argument is not **definable** and shall not have the **ASYNCHRONOUS**, **INTENT (OUT)**, **INTENT (INOUT)**, or
41 **VOLATILE** attributes.

NOTE 12.27

Argument intent specifications serve several purposes. See Note 5.17.

NOTE 12.28

For more explanatory information on [targets](#) as dummy arguments, see subclause C.9.4.

- 1 C1244 An [actual argument](#) that is a [coindexed object](#) with the [ASYNCHRONOUS](#) or [VOLATILE](#) attribute shall
2 not correspond to a dummy argument that has either the [ASYNCHRONOUS](#) or [VOLATILE](#) attribute.
- 3 C1245 (R1225) If an [actual argument](#) is a nonpointer array that has the [ASYNCHRONOUS](#) or [VOLATILE](#)
4 attribute but is not [simply contiguous](#) (6.5.4), and the corresponding dummy argument has either the
5 [ASYNCHRONOUS](#) or [VOLATILE](#) attribute, that dummy argument shall be [assumed-shape](#) or [assumed-](#)
6 [rank](#) and shall not have the [CONTIGUOUS](#) attribute.
- 7 C1246 (R1225) If an [actual argument](#) is an array pointer that has the [ASYNCHRONOUS](#) or [VOLATILE](#)
8 attribute but does not have the [CONTIGUOUS](#) attribute, and the corresponding dummy argument has
9 either the [ASYNCHRONOUS](#) or [VOLATILE](#) attribute, that dummy argument shall be an array pointer,
10 an [assumed-shape](#) array without the [CONTIGUOUS](#) attribute, or an [assumed-rank entity](#) without the
11 [CONTIGUOUS](#) attribute.

NOTE 12.29

The constraints on an [actual argument](#) with the [ASYNCHRONOUS](#) or [VOLATILE](#) attribute that corresponds to a dummy argument with either the [ASYNCHRONOUS](#) or [VOLATILE](#) attribute are designed to avoid forcing a processor to use the so-called copy-in/copy-out argument passing mechanism. Making a copy of an [actual argument](#) whose value is likely to change due to an asynchronous input/output operation completing or in some unpredictable manner will cause the new value to be lost when a called procedure returns and the copy-out overwrites the [actual argument](#).

12 **12.5.2.5 Allocatable and pointer dummy variables**

- 13 1 The requirements in this subclause apply to an [actual argument](#) with the [ALLOCATABLE](#) or [POINTER](#) attribute
14 that corresponds to a [dummy argument](#) with the same attribute.
- 15 2 The [actual argument](#) shall be [polymorphic](#) if and only if the associated [dummy argument](#) is [polymorphic](#), and
16 either both the [actual](#) and [dummy](#) arguments shall be [unlimited polymorphic](#), or the [declared type](#) of the [actual](#)
17 [argument](#) shall be the same as the [declared type](#) of the [dummy argument](#).

NOTE 12.30

The [dynamic type](#) of a [polymorphic allocatable](#) or pointer dummy argument can change as a result of execution of an [ALLOCATE](#) statement or [pointer assignment](#) in the subprogram. Because of this the corresponding [actual argument](#) needs to be [polymorphic](#) and have a [declared type](#) that is the same as the [declared type](#) of the dummy argument or an [extension](#) of that type. However, type compatibility requires that the [declared type](#) of the dummy argument be the same as, or an [extension](#) of, the type of the [actual argument](#). Therefore, the dummy and [actual](#) arguments need to have the same [declared type](#).

[Dynamic type](#) information is not maintained for a nonpolymorphic [allocatable](#) or pointer dummy argument. However, allocating or pointer-assigning such a dummy argument would require maintenance of this information if the corresponding [actual argument](#) is [polymorphic](#). Therefore, the corresponding [actual argument](#) needs to be nonpolymorphic.

- 18 3 The [rank](#) of the [actual argument](#) shall be the same as that of the dummy argument, unless the dummy argument
19 is [assumed-rank](#). The type parameter values of the [actual argument](#) shall agree with the corresponding ones of
20 the dummy argument that are not [assumed](#) or [deferred](#).
- 21 4 The [actual argument](#) shall have [deferred](#) the same type parameters as the dummy argument.

5 If the **actual argument** is a **coindexed object**, the dummy argument shall have the **INTENT (IN)** attribute.

12.5.2.6 Allocatable dummy variables

The requirements in this subclause apply to **actual arguments** that correspond to **allocatable** dummy data objects.

The **actual argument** shall be **allocatable**. It is permissible for the **actual argument** to have an allocation status of unallocated.

The **corank** of the **actual argument** shall be the same as that of the **dummy argument**.

The values of **assumed type parameters** of a **dummy argument** are assumed from the corresponding type parameters of its **effective argument**.

If the **dummy argument** does not have the **TARGET attribute**, any pointers associated with the **actual argument** do not become associated with the corresponding **dummy argument** on invocation of the procedure. If such a **dummy argument** is used as an **actual argument** that is associated with a **dummy argument** with the **TARGET attribute**, whether any pointers associated with the original **actual argument** become associated with the **dummy argument** with the **TARGET attribute** is processor dependent.

If the dummy argument has the **TARGET attribute**, does not have the **INTENT (OUT)** or **VALUE** attribute, and the corresponding **actual argument** has the **TARGET attribute** then

- any pointers associated with the **actual argument** become associated with the corresponding dummy argument on invocation of the procedure, and
- when execution of the procedure completes, any pointers that do not become undefined (16.5.2.5) and are associated with the dummy argument remain associated with the **actual argument**.

If a dummy argument has **INTENT (OUT)** or **INTENT (INOUT)**, the **actual argument** shall be **definable**. If a dummy argument has **INTENT (OUT)** and its associated **actual argument** is allocated, the **actual argument** is deallocated on procedure invocation (6.7.3.2).

12.5.2.7 Pointer dummy variables

The requirements in this subclause apply to **actual arguments** that correspond to dummy data pointers.

C1247 The **actual argument** corresponding to a dummy pointer with the **CONTIGUOUS attribute** shall be **simply contiguous** (6.5.4).

C1248 The **actual argument** corresponding to a dummy pointer shall not be a **coindexed object**.

If the dummy argument does not have **INTENT (IN)**, the **actual argument** shall be a pointer. Otherwise, the **actual argument** shall be a pointer or a valid **target** for the dummy pointer in a **pointer assignment statement**. If the **actual argument** is not a pointer, the dummy pointer becomes **pointer associated** with the **actual argument**.

The **rank** of the **actual argument** shall be the same as that of the dummy argument. The type parameter values of the **actual argument** shall agree with the corresponding ones of the dummy argument that are not **assumed** or **deferred**. The values of **assumed type parameters** of a dummy argument are assumed from the corresponding type parameters of its **effective argument**.

If the dummy argument has **INTENT (OUT)**, the **pointer association** status of the **actual argument** becomes undefined on invocation of the procedure.

If the dummy argument is nonoptional and the **actual argument** is **allocatable**, the **actual argument** shall be allocated.

NOTE 12.31

For more explanatory information on pointers as dummy arguments, see subclause C.9.4.

1 **12.5.2.8 Coarray dummy variables**

- 2 1 If the **dummy argument** is a **coarray**, the corresponding **actual argument** shall be a **coarray** and shall have the
- 3 **VOLATILE attribute** if and only if the **dummy argument** has the **VOLATILE attribute**.
- 4 2 If the dummy argument is an array **coarray** that has the **CONTIGUOUS attribute** or is not of **assumed shape**,
- 5 the corresponding **actual argument** shall be **simply contiguous** or an element of a **simply contiguous array**.

NOTE 12.32

Consider the invocation of a procedure on a particular **image**. Each dummy **coarray** is associated with its **ultimate argument** on the **image**. In addition, during this execution of the procedure, this **image** can access the **coarray** corresponding to the **ultimate argument** on any other **image**. For example, consider

```
INTERFACE
  SUBROUTINE SUB(X)
    REAL :: X[*]
  END SUBROUTINE SUB
END INTERFACE
...
REAL :: A(1000)[*]
...
CALL SUB(A(10))
```

During execution of this invocation of SUB, the executing **image** has access through the syntax X[P] to A(10) on **image P**.

NOTE 12.33

Each invocation of a procedure with a nonallocatable **coarray dummy argument** establishes a dummy **coarray** for the **image** with its own bounds and **cobounds**. During this execution of the procedure, this **image** can use its own bounds and **cobounds** to access the **coarray** corresponding to the **ultimate argument** on any other **image**. For example, consider

```
INTERFACE
  SUBROUTINE SUB(X,N)
    INTEGER :: N
    REAL :: X(N,N)[N,*]
  END SUBROUTINE SUB
END INTERFACE
...
REAL :: A(1000)[*]
...
CALL SUB(A,10)
```

During execution of this invocation of SUB, the executing **image** has access through the syntax X(1,2)[3,4] to A(11) on the **image** with **image index 33**.

NOTE 12.34

The requirements on an **actual argument** that corresponds to a dummy **coarray** that is not of **assumed-shape** or has the **CONTIGUOUS attribute** are designed to avoid forcing a processor to use the so-called copy-in/copy-out argument passing mechanism.

12.5.2.9 Actual arguments associated with dummy procedure entities

- 1 If the **interface** of a **dummy procedure** is **explicit**, its **characteristics** as a procedure (12.3.1) shall be the same as those of its **effective argument**, except that a pure **effective argument** may be associated with a dummy argument that is not pure and an **elemental** intrinsic **actual** procedure may be associated with a **dummy procedure** (which cannot be **elemental**).
- 2 If the **interface** of a **dummy procedure** is **implicit** and either the dummy argument is explicitly typed or referenced as a function, it shall not be referenced as a subroutine and any corresponding **actual argument** shall be a function, function **procedure pointer**, or **dummy procedure**. If both the **actual argument** and **dummy argument** are known to be functions, they shall have the same type and type parameters. If only the **dummy argument** is known to be a function, the function that would be invoked by a reference to the **dummy argument** shall have the same type and type parameters, except that an external function with assumed character length may be associated with a dummy argument with explicit character length.
- 3 If the **interface** of a **dummy procedure** is **implicit** and a reference to it appears as a subroutine reference, any corresponding **actual argument** shall be a subroutine, subroutine **procedure pointer**, or **dummy procedure**.
- 4 If a dummy argument is a **dummy procedure** without the **POINTER** attribute, its **effective argument** shall be an **external**, **internal**, **module**, or **dummy** procedure, or a specific intrinsic procedure listed in Table 13.2. If the **specific name** is also a generic name, only the specific procedure is associated with the dummy argument.
- 5 If a dummy argument is a **procedure pointer**, the corresponding **actual argument** shall be a **procedure pointer**, a reference to a function that returns a **procedure pointer**, a reference to the intrinsic function **NULL**, or a valid **target** for the dummy pointer in a **pointer assignment statement**. If the **actual argument** is not a pointer, the dummy argument shall have **INTENT (IN)** and becomes **pointer associated** with the **actual argument**.
- 6 When the **actual argument** is a procedure, the **host instance** of the **dummy argument** is the **host instance** of the **actual argument** (12.6.2.4).
- 7 If an **external procedure** or a **dummy procedure** is used as an **actual argument**, its **interface** shall be **explicit** or it shall be explicitly declared to have the **EXTERNAL** attribute.

12.5.2.10 Actual arguments and alternate return indicators

- 1 If a dummy argument is an asterisk (12.6.2.3), the corresponding **actual argument** shall be an alternate return specifier (R1226).

12.5.2.11 Sequence association

- 1 An **actual argument** represents an element sequence if it is an array expression, an array element **designator**, a default character scalar, or a scalar of type character with the C character kind (15.2.2). If the **actual argument** is an array expression, the element sequence consists of the elements in array element order. If the **actual argument** is an array element **designator**, the element sequence consists of that array element and each element that follows it in array element order.
- 2 If the **actual argument** is default character or of type character with the C character kind, and is an array expression, array element, or array element substring **designator**, the element sequence consists of the **storage units** beginning with the first **storage unit** of the **actual argument** and continuing to the end of the array. The **storage units** of an array element substring **designator** are viewed as array elements consisting of consecutive groups of **storage units** having the character length of the dummy array.
- 3 If the **actual argument** is default character or of type character with the C character kind, and is a scalar that is not an array element or array element substring **designator**, the element sequence consists of the **storage units** of the **actual argument**.

NOTE 12.35

Some of the elements in the element sequence might consist of **storage units** from different elements of the original array.

1 4 An **actual argument** that represents an element sequence and corresponds to a dummy argument that is an array
2 is sequence associated with the dummy argument if the dummy argument is an **explicit-shape** or **assumed-size**
3 array. The **rank** and shape of the **actual argument** need not agree with the **rank** and shape of the dummy
4 argument, but the number of elements in the dummy argument shall not exceed the number of elements in the
5 element sequence of the **actual argument**. If the dummy argument is **assumed-size**, the number of elements in the
6 dummy argument is exactly the number of elements in the element sequence.

7 12.5.2.12 Argument presence and restrictions on arguments not present

8 1 A **dummy argument** or an entity that is **host associated** with a **dummy argument** is not present if the **dummy**
9 **argument**

- 10 • does not correspond to an **actual argument**,
- 11 • corresponds to an **actual argument** that is not present, or
- 12 • does not have the **ALLOCATABLE** or **POINTER** attribute, and corresponds to an **actual argument** that
 - 13 – has the **ALLOCATABLE** attribute and is not allocated, or
 - 14 – has the **POINTER** attribute and is **disassociated**;

15 otherwise, it is present.

16 2 A nonoptional **dummy argument** shall be present. If an optional nonpointer **dummy argument** corresponds to a
17 present pointer **actual argument**, the **pointer association** status of the **actual argument** shall not be undefined.

18 3 An optional dummy argument that is not present is subject to the following restrictions.

- 19 (1) If it is a data object, it shall not be referenced or be defined. If it is of a type that has default
20 initialization, the initialization has no effect.
- 21 (2) It shall not be used as the **data-target** or **proc-target** of a **pointer assignment**.
- 22 (3) If it is a procedure or **procedure pointer**, it shall not be invoked.
- 23 (4) It shall not be supplied as an **actual argument** corresponding to a nonoptional dummy argument
24 other than as the argument of the intrinsic function **PRESENT** or as an argument of a function
25 reference that is a **constant expression**.
- 26 (5) A **designator** with it as the **base object** and with one or more subobject selectors shall not be supplied
27 as an **actual argument**.
- 28 (6) If it is an array, it shall not be supplied as an **actual argument** to an **elemental procedure** unless an
29 array of the same **rank** is supplied as an **actual argument** corresponding to a nonoptional dummy
30 argument of that **elemental procedure**.
- 31 (7) If it is a pointer, it shall not be allocated, deallocated, nullified, pointer-assigned, or supplied as an
32 **actual argument** corresponding to an optional nonpointer dummy argument.
- 33 (8) If it is **allocatable**, it shall not be allocated, deallocated, or supplied as an **actual argument** corres-
34 ponding to an optional nonallocatable **dummy argument**.
- 35 (9) If it has length type parameters, they shall not be the subject of an inquiry.
- 36 (10) It shall not be used as the **selector** in an **ASSOCIATE**, **SELECT RANK**, or **SELECT TYPE** construct.
- 37 (11) It shall not be supplied as the **data-ref** in a **procedure-designator**.
- 38 (12) It shall not be supplied as the **scalar-variable** in a **proc-component-ref**.

39 4 Except as noted in the list above, it may be supplied as an **actual argument** corresponding to an optional dummy
40 argument, which is then also considered not to be present.

41 12.5.2.13 Restrictions on entities associated with dummy arguments

42 1 While an entity is associated with a dummy argument, the following restrictions hold.

- 43 (1) Action that affects the allocation status of the entity or a subobject thereof shall be taken through
44 the dummy argument.

- 1 (2) If the allocation status of the entity or a subobject thereof is affected through the dummy argument,
 2 then at any time during the invocation and execution of the procedure, either before or after the
 3 allocation or deallocation, it shall be referenced only through the dummy argument.
- 4 (3) Action that affects the value of the entity or any subobject of it shall be taken only through the
 5 dummy argument unless
- 6 (a) the dummy argument has the **POINTER attribute**,
- 7 (b) the dummy argument is a scalar, **assumed-shape**, or **assumed-rank** object, and has the **TAR-**
 8 **GET attribute** but not the **INTENT (IN)** or **CONTIGUOUS** attributes, and the **actual argu-**
 9 **ment** is a target other than an **array section** with a **vector subscript**, or
- 10 (c) the dummy argument is an **assumed-rank** object with the **TARGET attribute** and not the
 11 **INTENT (IN) attribute**, and the **actual argument** is a scalar target.
- 12 (4) If the value of the entity or any subobject of it is affected through the dummy argument, then at
 13 any time during the invocation and execution of the procedure, either before or after the definition,
 14 it may be referenced only through that dummy argument unless
- 15 (a) the dummy argument has the **POINTER attribute**,
- 16 (b) the dummy argument is a scalar, **assumed-shape**, or **assumed-rank** object, and has the **TAR-**
 17 **GET attribute** but not the **INTENT (IN)** or **CONTIGUOUS** attributes, and the **actual argu-**
 18 **ment** is a target other than an **array section** with a **vector subscript**, or
- 19 (c) the dummy argument is an **assumed-rank** object with the **TARGET attribute** and not the
 20 **INTENT (IN) attribute**, and the **actual argument** is a scalar target.

NOTE 12.36

In

```

SUBROUTINE OUTER
  REAL, POINTER :: A (:)
  ...
  ALLOCATE (A (1:N))
  ...
  CALL INNER (A)
  ...
CONTAINS
  SUBROUTINE INNER (B)
    REAL :: B (:)
    ...
  END SUBROUTINE INNER
  SUBROUTINE SET (C, D)
    REAL, INTENT (OUT) :: C
    REAL, INTENT (IN) :: D
    C = D
  END SUBROUTINE SET
END SUBROUTINE OUTER

```

an **assignment statement** such as

```
A (1) = 1.0
```

would not be permitted during the execution of **INNER** because this would be changing **A** without using **B**, but statements such as

```
B (1) = 1.0
```

or

NOTE 12.36 (cont.)

```
CALL SET (B (1), 1.0)
```

would be allowed. Similarly,

```
DEALLOCATE (A)
```

would not be allowed because this affects the allocation of B without using B. In this case,

```
DEALLOCATE (B)
```

also would not be permitted. If B were declared with the [POINTER attribute](#), either of the statements

```
DEALLOCATE (A)
```

and

```
DEALLOCATE (B)
```

would be permitted, but not both.

NOTE 12.37

If there is a partial or complete overlap between the [effective arguments](#) of two different dummy arguments of the same procedure and the dummy arguments have neither the [POINTER](#) nor [TARGET](#) attribute, the overlapped portions shall not be defined, redefined, or become undefined during the execution of the procedure. For example, in

```
CALL SUB (A (1:5), A (3:9))
```

A (3:5) shall not be defined, redefined, or become undefined through the first dummy argument because it is part of the argument associated with the second dummy argument and shall not be defined, redefined, or become undefined through the second dummy argument because it is part of the argument associated with the first dummy argument. A (1:2) remains [definable](#) through the first dummy argument and A (6:9) remains [definable](#) through the second dummy argument.

NOTE 12.38

This restriction applies equally to pointer targets. In

```
REAL, DIMENSION (10), TARGET :: A
```

```
REAL, DIMENSION (:), POINTER :: B, C
```

```
B => A (1:5)
```

```
C => A (3:9)
```

```
CALL SUB (B, C) ! The dummy arguments of SUB are neither pointers nor targets.
```

B (3:5) cannot be defined because it is part of the argument associated with the second dummy argument.

C (1:3) cannot be defined because it is part of the argument associated with the first dummy argument.

A (1:2) [which is B (1:2)] remains [definable](#) through the first dummy argument and A (6:9) [which is C (4:7)] remains [definable](#) through the second dummy argument.

NOTE 12.39

In

```
MODULE DATA
```

```
  REAL :: W, X, Y, Z
```

```
END MODULE DATA
```

NOTE 12.39 (cont.)

```

PROGRAM MAIN
  USE DATA
  ...
  CALL INIT (X)
  ...
END PROGRAM MAIN
SUBROUTINE INIT (V)
  USE DATA
  ...
  READ (*, *) V
  ...
END SUBROUTINE INIT

```

variable X cannot be directly referenced at any time during the execution of INIT because it is being defined through the dummy argument V. X can be (indirectly) referenced through V. W, Y, and Z can be directly referenced. X can, of course, be directly referenced once execution of INIT is complete.

NOTE 12.40

The restrictions on entities associated with dummy arguments are intended to facilitate a variety of optimizations in the translation of the subprogram, including implementations of [argument association](#) in which the value of an [actual argument](#) that is neither a pointer nor a target is maintained in a register or in local storage.

1 **12.5.3 Function reference**

2 1 A function is invoked during expression evaluation by a [function-reference](#) or by a defined operation (7.1.6).
3 When it is invoked, all [actual argument](#) expressions are evaluated, then the arguments are associated, and then
4 the function is executed. When execution of the function is complete, the value of the function result is available
5 for use in the expression that caused the function to be invoked. The [characteristics](#) of the function result (12.3.3)
6 are determined by the [interface](#) of the function. If a reference to an [elemental](#) function (12.8) is an [elemental](#)
7 [reference](#), all array arguments shall have the same shape.

8 **12.5.4 Subroutine reference**

9 1 A subroutine is invoked by execution of a [CALL statement](#), execution of a [defined assignment statement](#) (7.2.1.4),
10 [defined input/output](#) (9.6.4.8.2), or [finalization](#)(4.5.6). When a subroutine is invoked, all [actual argument](#) expres-
11 sions are evaluated, then the arguments are associated, and then the subroutine is executed. When the actions
12 specified by the subroutine are completed, the execution of the [CALL statement](#), the execution of the [defined](#)
13 [assignment statement](#), the processing of an input or output list item, or [finalization](#) of an object is also completed.
14 If a [CALL statement](#) includes one or more alternate return specifiers among its arguments, a branch to one of the statements indicated
15 might occur, depending on the action specified by the subroutine. If a reference to an [elemental](#) subroutine (12.8) is an
16 [elemental reference](#), at least one [actual argument](#) shall correspond to an [INTENT \(OUT\)](#) or [INTENT \(INOUT\)](#)
17 dummy argument, all such [actual arguments](#) shall be arrays, and all [actual arguments](#) shall be [conformable](#).

18 **12.5.5 Resolving named procedure references**19 **12.5.5.1 Establishment of procedure names**

20 1 The rules for interpreting a procedure reference depend on whether the procedure name in the reference is
21 established by the available declarations and specifications to be generic in the [scoping unit](#) containing the
22 reference, is established to be only specific in the [scoping unit](#) containing the reference, or is not established.

23 2 A procedure name is established to be generic in a [scoping unit](#)

- 1 (1) if that **scoping unit** contains an **interface block** with that name;
- 2 (2) if that **scoping unit** contains a **GENERIC statement** with a *generic-spec* that is that name;
- 3 (3) if that **scoping unit** contains an **INTRINSIC attribute** specification for that name and it is the generic
- 4 name of an intrinsic procedure;
- 5 (4) if that **scoping unit** contains a **USE statement** that makes that procedure name accessible and the
- 6 corresponding name in the module is established to be generic; or
- 7 (5) if that **scoping unit** contains no declarations of that name, that **scoping unit** has a **host scoping unit**,
- 8 and that name is established to be generic in the **host scoping unit**.

9 3 A procedure name is established to be only specific in a **scoping unit** if it is established to be specific and not
10 established to be generic. It is established to be specific

- 11 (1) if that **scoping unit** contains a **module subprogram**, **internal subprogram**, or **statement function statement**
- 12 that defines a procedure with that name;
- 13 (2) if that **scoping unit** is of a subprogram that defines a procedure with that name;
- 14 (3) if that **scoping unit** contains an **INTRINSIC attribute** specification for that name and it is the name of a specific
- 15 intrinsic procedure;
- 16 (4) if that **scoping unit** contains an explicit **EXTERNAL attribute** specification for that name;
- 17 (5) if that **scoping unit** contains a **USE statement** that makes that procedure name accessible and the
- 18 corresponding name in the module is established to be specific; or
- 19 (6) if that **scoping unit** contains no declarations of that name, that **scoping unit** has a **host scoping unit**,
- 20 and that name is established to be specific in the **host scoping unit**.

21 4 A procedure name is not established in a **scoping unit** if it is neither established to be generic nor established to
22 be specific.

23 12.5.5.2 Resolving procedure references to names established to be generic

- 24 1 If the reference is consistent with a **nonelemental reference** to one of the **specific interfaces** of a **generic interface**
- 25 that has that name and either is defined in the **scoping unit** in which the reference appears or is made accessible
- 26 by a **USE statement** in the **scoping unit**, the reference is to the specific procedure in the **interface block** that
- 27 provides that **interface**. The rules in 12.4.3.5.5 ensure that there can be at most one such specific procedure.
- 28 2 Otherwise, if the reference is consistent with an **elemental reference** to one of the **specific interfaces** of a **generic**
- 29 **interface** that has that name and either is defined in the **scoping unit** in which the reference appears or is made
- 30 accessible by a **USE statement** in the **scoping unit**, the reference is to the specific **elemental procedure** in the
- 31 **interface block** that provides that **interface**. The rules in 12.4.3.5.5 ensure that there can be at most one such
- 32 specific **elemental procedure**.
- 33 3 Otherwise, if the **scoping unit** contains either an **INTRINSIC attribute** specification for that name or a **USE**
- 34 **statement** that makes that name accessible from a module in which the corresponding name is specified to have
- 35 the **INTRINSIC attribute**, and if the reference is consistent with the **interface** of that **intrinsic** procedure, the
- 36 reference is to that **intrinsic** procedure.
- 37 4 Otherwise, if the **scoping unit** has a **host scoping unit**, the name is established to be generic in that **host scoping**
- 38 **unit**, and there is agreement between the **scoping unit** and the **host scoping unit** as to whether the name is a
- 39 function name or a subroutine name, the name is resolved by applying the rules in this subclause to the **host**
- 40 **scoping unit** as if the reference appeared there.
- 41 5 Otherwise, if the name is that of an intrinsic procedure and the reference is consistent with that intrinsic procedure,
- 42 the reference is to that intrinsic procedure.

NOTE 12.41

These rules allow particular specific procedures with the same [generic identifier](#) to be used for particular array [ranks](#) and a general [elemental](#) version to be used for other [ranks](#). For example, given an [interface block](#) such as:

```
INTERFACE RANF
  ELEMENTAL FUNCTION SCALAR_RANF(X)
    REAL, INTENT(IN) :: X
  END FUNCTION SCALAR_RANF
  FUNCTION VECTOR_RANDOM(X)
    REAL X(:)
    REAL VECTOR_RANDOM(SIZE(X))
  END FUNCTION VECTOR_RANDOM
END INTERFACE RANF
```

and a declaration such as:

```
REAL A(10,10), AA(10,10)
```

then the statement

```
A = RANF(AA)
```

is an [elemental reference](#) to SCALAR_RANF. The statement

```
A(6:10,2) = RANF(AA(6:10,2))
```

is a [nonelemental reference](#) to VECTOR_RANDOM.

NOTE 12.42

In the [USE statement](#) case, it is possible, because of the renaming facility, for the name in the reference to be different from the name of the intrinsic procedure.

1 **12.5.5.3 Resolving procedure references to names established to be only specific**

- 2 1 If the name has the [EXTERNAL attribute](#),
- 3 • if it is a [procedure pointer](#), the reference is to its target;
- 4 • if it is a [dummy procedure](#) that is not a [procedure pointer](#), the reference is to the [effective argument](#)
- 5 corresponding to that name;
- 6 • otherwise, the reference is to the [external procedure](#) with that name.
- 7 2 If the name is that of an accessible [external procedure](#), [internal procedure](#), [module procedure](#), [intrinsic procedure](#),
- 8 or statement function, the reference is to that procedure.

NOTE 12.43

Because of the renaming facility of the [USE statement](#), the name in the reference can be different from the original name of the procedure.

9 **12.5.5.4 Resolving procedure references to names not established**

- 10 1 If the name is the name of a dummy argument of the [scoping unit](#), the dummy argument is a [dummy procedure](#)
- 11 and the reference is to that [dummy procedure](#). That is, the procedure invoked by executing that reference is the
- 12 [effective argument](#) corresponding to that [dummy procedure](#).

- 1 2 Otherwise, if the name is the name of an intrinsic procedure, and if there is agreement between the reference and
 2 the status of the intrinsic procedure as being a function or subroutine, the reference is to that intrinsic procedure.
- 3 3 Otherwise, the reference is to an [external procedure](#) with that name.

4 12.5.6 Resolving type-bound procedure references

- 5 1 If the *binding-name* in a *procedure-designator* (R1223) is that of a specific [type-bound procedure](#), the procedure
 6 referenced is the one bound to that name in the [dynamic type](#) of the *data-ref*.
- 7 2 If the *binding-name* in a *procedure-designator* is that of a generic type bound procedure, the generic [binding](#) with
 8 that name in the [declared type](#) of the *data-ref* is used to select a specific [binding](#) using the following criteria.
- 9 • If the reference is consistent with one of the specific [bindings](#) of that generic [binding](#), that specific [binding](#)
 10 is selected.
 - 11 • Otherwise, the reference shall be consistent with an [elemental reference](#) to one of the specific [bindings](#) of
 12 that generic [binding](#); that specific [binding](#) is selected.
- 13 3 The reference is to the procedure bound to the same name as the selected specific [binding](#) in the [dynamic type](#)
 14 of the *data-ref*.

15 12.6 Procedure definition

16 12.6.1 Intrinsic procedure definition

- 17 1 Intrinsic procedures are defined as an inherent part of the processor. A standard-conforming processor shall
 18 include the intrinsic procedures described in Clause 13, but may include others. However, a standard-conforming
 19 program shall not make use of intrinsic procedures other than those described in Clause 13.

20 12.6.2 Procedures defined by subprograms

21 12.6.2.1 General

- 22 1 A procedure is defined by the initial [SUBROUTINE](#) or [FUNCTION](#) statement of a subprogram, and each [ENTRY](#)
 23 [statement](#) defines an additional procedure (12.6.2.6).
- 24 2 A subprogram is specified to be [elemental](#) (12.8), [pure](#) (12.7), [recursive](#), or a separate module subprogram
 25 (12.6.2.5) by a *prefix* in its initial [SUBROUTINE](#) or [FUNCTION](#) statement.

26 R1227 *prefix* is *prefix-spec* [*prefix-spec*] ...

27 R1228 *prefix-spec* is *declaration-type-spec*
 28 or ELEMENTAL
 29 or IMPURE
 30 or MODULE
 31 or NON_RECURSIVE
 32 or PURE
 33 or RECURSIVE

34 C1249 (R1227) A *prefix* shall contain at most one of each *prefix-spec*.

35 C1250 (R1227) A *prefix* shall not specify both PURE and IMPURE.

36 C1251 (R1227) A *prefix* shall not specify both NON_RECURSIVE and RECURSIVE.

37 C1252 An [elemental procedure](#) shall not have the [BIND attribute](#).

- 1 C1253 (R1227) **MODULE** shall appear only in the *function-stmt* or *subroutine-stmt* of a module subprogram or
2 of a nonabstract **interface body** that is declared in the **scoping unit** of a module or submodule.
- 3 C1254 (R1227) If **MODULE** appears in the *prefix* of a module subprogram, it shall have been declared to be a
4 separate **module procedure** in the containing program unit or an ancestor of that program unit.
- 5 C1255 (R1227) If **MODULE** appears in the *prefix* of a module subprogram, the subprogram shall specify the
6 same **characteristics** and dummy argument names as its corresponding module procedure **interface body**.
- 7 C1256 (R1227) If **MODULE** appears in the *prefix* of a module subprogram and a **binding label** is specified, it
8 shall be the same as the **binding label** specified in the corresponding module procedure **interface body**.
- 9 C1257 (R1227) If **MODULE** appears in the *prefix* of a module subprogram, **NON_RECURSIVE** shall appear
10 if and only if **NON_RECURSIVE** appears in the *prefix* in the corresponding module procedure **interface**
11 **body**.
- 12 3 The **NON_RECURSIVE** *prefix-spec* shall not appear if any procedure defined by the subprogram directly or
13 indirectly invokes itself or any other procedure defined by the subprogram.
- 14 4 If the *prefix-spec* **PURE** appears, or the *prefix-spec* **ELEMENTAL** appears and **IMPURE** does not appear, the
15 subprogram is a pure subprogram and shall meet the additional constraints of 12.7.
- 16 5 If the *prefix-spec* **ELEMENTAL** appears, the subprogram is an **elemental subprogram** and shall meet the additional
17 constraints of 12.8.1.

18 12.6.2.2 Function subprogram

- 19 1 A function subprogram is a subprogram that has a **FUNCTION** statement as its first statement.

20 R1229 *function-subprogram* **is** *function-stmt*
21 [*specification-part*]
22 [*execution-part*]
23 [*internal-subprogram-part*]
24 *end-function-stmt*

25 R1230 *function-stmt* **is** [*prefix*] **FUNCTION** *function-name* ■
26 ■ ([*dummy-arg-name-list*]) [*suffix*]

- 27 C1258 (R1230) If **RESULT** appears, *result-name* shall not be the same as *function-name* and shall not be the same
28 as the *entry-name* in any **ENTRY statement** in the subprogram.
- 29 C1259 (R1230) If **RESULT** appears, the *function-name* shall not appear in any specification statement in the
30 **scoping unit** of the function subprogram.
- 31 R1231 *proc-language-binding-spec* **is** *language-binding-spec*
- 32 C1260 (R1231) A *proc-language-binding-spec* with a **NAME= specifier** shall not be specified in the *function-stmt*
33 or *subroutine-stmt* of an **internal procedure**, or of an **interface body** for an **abstract interface** or a **dummy**
34 **procedure**.
- 35 C1261 If *proc-language-binding-spec* is specified for a procedure, each of its dummy arguments shall be an **inter-**
36 **operable** procedure (15.3.7) or a variable that is **interoperable** (15.3.5, 15.3.6), **assumed-shape**, **assumed-**
37 **rank**, **assumed-type**, of type **CHARACTER** with assumed length, or that has the **ALLOCATABLE** or
38 **POINTER** attribute.
- 39 C1262 If *proc-language-binding-spec* is specified for a function, the function result shall be an interoperable scalar
40 variable.
- 41 C1263 A variable that is a dummy argument of a procedure that has a *proc-language-binding-spec* shall not have
42 both the **OPTIONAL** and **VALUE** attributes.

- 1 C1264 A variable that is a dummy argument of a procedure that has a *proc-language-binding-spec* shall be
2 assumed-type or of interoperable type.
- 3 R1232 *dummy-arg-name* is *name*
- 4 C1265 (R1232) A *dummy-arg-name* shall be the name of a dummy argument.
- 5 R1233 *suffix* is *proc-language-binding-spec* [RESULT (*result-name*)]
6 or RESULT (*result-name*) [*proc-language-binding-spec*]
- 7 R1234 *end-function-stmt* is END [FUNCTION [*function-name*]]
- 8 C1266 (R1229) An internal function subprogram shall not contain an *internal-subprogram-part*.
- 9 C1267 (R1234) If a *function-name* appears in the *end-function-stmt*, it shall be identical to the *function-name*
10 specified in the *function-stmt*.
- 11 2 The name of the function is *function-name*.
- 12 3 The type and type parameters (if any) of the result of the function defined by a function subprogram may be
13 specified by a type specification in the FUNCTION statement or by the name of the **function result** appearing
14 in a **type declaration statement** in the specification part of the function subprogram. They shall not be specified
15 both ways. If they are not specified either way, they are determined by the implicit typing rules in effect within
16 the function subprogram. If the **function result** is an array, **allocatable**, or a pointer, this shall be specified by
17 specifications of the name of the **function result** within the function body. The specifications of the **function**
18 **result** attributes, the specification of dummy argument attributes, and the information in the procedure heading
19 collectively define the **characteristics** of the function (12.3.1).
- 20 4 If **RESULT** appears, the name of the **function result** of the function is *result-name* and all occurrences of the
21 function name in *execution-part* statements in its scope refer to the function itself. If **RESULT** does not appear,
22 the name of the **function result** is *function-name* and all occurrences of the function name in *execution-part*
23 statements in its scope are references to the **function result**. On completion of execution of the function, the value
24 returned is that of its **function result**. If the **function result** is a data pointer, the shape of the value returned by
25 the function is determined by the shape of the **function result** when the execution of the function is completed. If
26 the **function result** is not a pointer, its value shall be defined by the function. If the **function result** is a pointer,
27 on return the **pointer association** status of the **function result** shall not be undefined.

NOTE 12.44

The **function result** is similar to any other entity (variable or procedure pointer) local to a function subprogram. Its existence begins when execution of the function is initiated and ends when execution of the function is terminated. However, because the final value of this entity is used subsequently in the evaluation of the expression that invoked the function, an implementation might defer releasing the storage occupied by that entity until after its value has been used in expression evaluation.

NOTE 12.45

The following is an example of the declaration of an **interface body** with the **BIND attribute**, and a reference to the procedure declared.

```
USE, INTRINSIC :: ISO_C_BINDING
```

```
INTERFACE
```

```
  FUNCTION JOE (I, J, R) BIND(C,NAME="FrEd")
```

```
    USE, INTRINSIC :: ISO_C_BINDING
```

```
    INTEGER(C_INT) :: JOE
```

```
    INTEGER(C_INT), VALUE :: I, J
```

```
    REAL(C_FLOAT), VALUE :: R
```

```
  END FUNCTION JOE
```

NOTE 12.45 (cont.)

```
END INTERFACE
```

```
INT = JOE(1_C_INT, 3_C_INT, 4.0_C_FLOAT)
END PROGRAM
```

The invocation of the function JOE results in a reference to a function with a [binding label](#) "FrEd". FrEd could be a C function described by the C prototype

```
int FrEd(int n, int m, float x);
```

1 **12.6.2.3 Subroutine subprogram**

2 1 A subroutine subprogram is a subprogram that has a SUBROUTINE statement as its first statement.

3 R1235 *subroutine-subprogram* is *subroutine-stmt*
 4 [*specification-part*]
 5 [*execution-part*]
 6 [*internal-subprogram-part*]
 7 *end-subroutine-stmt*

8 R1236 *subroutine-stmt* is [*prefix*] SUBROUTINE *subroutine-name* ■
 9 ■ [([*dummy-arg-list*]) [*proc-language-binding-spec*]]

10 C1268 (R1236) The *prefix* of a *subroutine-stmt* shall not contain a *declaration-type-spec*.

11 R1237 *dummy-arg* is *dummy-arg-name*
 12 or *

13 R1238 *end-subroutine-stmt* is END [SUBROUTINE [*subroutine-name*]]

14 C1269 (R1235) An internal subroutine subprogram shall not contain an *internal-subprogram-part*.

15 C1270 (R1238) If a *subroutine-name* appears in the *end-subroutine-stmt*, it shall be identical to the *subroutine-*
 16 *name* specified in the *subroutine-stmt*.

17 2 The name of the subroutine is *subroutine-name*.

18 **12.6.2.4 Instances of a subprogram**

19 1 When a procedure defined by a subprogram is invoked, an instance of that subprogram is created. Each instance
 20 has an independent sequence of execution and an independent set of dummy arguments, [unsaved local variables](#),
 21 and [unsaved local procedure pointers](#). Saved local entities are shared by all instances of the subprogram.

22 2 When a statement function is invoked, an instance of that statement function is created.

23 3 When execution of an instance completes it ceases to exist.

24 4 The caller of an instance of a procedure is the instance of the main program, subprogram, or statement function
 25 that invoked it. The call sequence of an instance of a procedure is its caller, followed by the call sequence of its
 26 caller. The call sequence of the main program is empty. The [host instance](#) of an instance of a statement function
 27 or an [internal procedure](#) that is invoked by its name is the first element of the call sequence that is an instance
 28 of the host of the statement function or internal subprogram. The [host instance](#) of an [internal procedure](#) that is
 29 invoked via a [dummy procedure](#) or [procedure pointer](#) is the [host instance](#) of the [associating entity](#) from when the
 30 [argument association](#) or [pointer association](#) was established (16.5.5). The [host instance](#) of a [module procedure](#) is
 31 the module or submodule in which it is defined. A main program or external subprogram has no [host instance](#).

12.6.2.5 Separate module procedures

- 1 A separate module procedure is a **module procedure** defined by a *separate-module-subprogram*, by a *function-subprogram* whose initial statement contains the keyword **MODULE**, or by a *subroutine-subprogram* whose initial statement contains the keyword **MODULE**.

R1239 *separate-module-subprogram* **is** *mp-subprogram-stmt*
 [*specification-part*]
 [*execution-part*]
 [*internal-subprogram-part*]
 end-mp-subprogram-stmt

R1240 *mp-subprogram-stmt* **is** **MODULE PROCEDURE** *procedure-name*

R1241 *end-mp-subprogram-stmt* **is** **END** [**PROCEDURE** [*procedure-name*]]

C1271 (R1239) The *procedure-name* shall have been declared to be a separate **module procedure** in the containing **program unit** or an ancestor of that **program unit**.

C1272 (R1241) If a *procedure-name* appears in the *end-mp-subprogram-stmt*, it shall be identical to the *procedure-name* in the *mp-subprogram-stmt*.

- 2 A separate **module procedure** shall not be defined more than once.
- 3 The **interface** of a procedure defined by a *separate-module-subprogram* is explicitly declared by the *mp-subprogram-stmt* to be the same as its module procedure **interface body**. It is recursive if and only if it is declared to be recursive by the **interface body**, and if it is a function its result name is determined by the **FUNCTION statement** in the **interface body**.

NOTE 12.46

A separate **module procedure** can be accessed by **use association** only if its **interface body** is declared in the specification part of a module and is public.

12.6.2.6 ENTRY statement

- 1 An **ENTRY** statement permits a procedure reference to begin with a particular executable statement within the function or subroutine subprogram in which the **ENTRY** statement appears.

R1242 *entry-stmt* **is** **ENTRY** *entry-name* [([*dummy-arg-list*]) [*suffix*]]

C1273 (R1242) If **RESULT** appears, the *entry-name* shall not appear in any specification or **type declaration statement** in the **scoping unit** of the function program.

C1274 (R1242) An *entry-stmt* shall appear only in an *external-subprogram* or a *module-subprogram* that does not define a separate **module procedure**. An *entry-stmt* shall not appear within an *executable-construct*.

C1275 (R1242) **RESULT** shall appear only if the *entry-stmt* is in a function subprogram.

C1276 (R1242) A *dummy-arg* shall not be an alternate return indicator if the **ENTRY** statement is in a function subprogram.

C1277 (R1242) If **RESULT** appears, *result-name* shall not be the same as the *function-name* in the **FUNCTION statement** and shall not be the same as the *entry-name* in any **ENTRY** statement in the subprogram.

- 2 Optionally, a subprogram may have one or more **ENTRY** statements.
- 3 If the **ENTRY** statement is in a function subprogram, an additional function is defined by that subprogram. The name of the function is *entry-name* and the name of its **result** is *result-name* or is *entry-name* if no *result-name* is provided. The **dummy arguments** of the function are those specified in the **ENTRY** statement. If the **characteristics** of the result of the function named in the **ENTRY** statement are the same as the **characteristics** of the result of the function named in the **FUNCTION statement**, their **result** names identify the same entity, although their names need not be the same. Otherwise, they are **storage associated** and shall all be nonpointer, nonallocatable scalar variables that are default integer, default real, double precision real, default complex, or

- 1 default logical.
- 2 4 If the ENTRY statement is in a subroutine subprogram, an additional subroutine is defined by that subprogram. The name of the
3 subroutine is *entry-name*. The dummy arguments of the subroutine are those specified in the ENTRY statement.
- 4 5 The order, number, types, kind type parameters, and names of the dummy arguments in an ENTRY statement may differ from the
5 order, number, types, kind type parameters, and names of the dummy arguments in the FUNCTION or SUBROUTINE statement
6 in the containing subprogram.
- 7 6 Because an ENTRY statement defines an additional function or an additional subroutine, it is referenced in the same manner as any
8 other function or subroutine (12.5).
- 9 7 In a subprogram, a dummy argument specified in an ENTRY statement shall not appear in an executable statement preceding that
10 ENTRY statement, unless it also appears in a FUNCTION, SUBROUTINE, or ENTRY statement that precedes the executable
11 statement. A function result specified by a *result-name* in an ENTRY statement shall not appear in any executable statement that
12 precedes the first RESULT clause with that name.
- 13 8 In a subprogram, a dummy argument specified in an ENTRY statement shall not appear in the expression of a statement function
14 that precedes the first *dummy-arg* with that name in the subprogram. A function result specified by a *result-name* in an ENTRY
15 statement shall not appear in the expression of a statement function that precedes the first RESULT clause with that name.
- 16 9 If a dummy argument appears in an executable statement, the execution of the executable statement is permitted during the
17 execution of a reference to the function or subroutine only if the dummy argument appears in the dummy argument list of the
18 referenced procedure.
- 19 10 If a dummy argument is used in a specification expression to specify an array bound or character length of an object, the appearance
20 of the object in a statement that is executed during a procedure reference is permitted only if the dummy argument appears in the
21 dummy argument list of the referenced procedure and it is present (12.5.2.12).
- 22 11 The NON_RECURSIVE and RECURSIVE keywords are not used in an ENTRY statement. Instead, the presence or absence of
23 NON_RECURSIVE in the initial SUBROUTINE or FUNCTION statement controls whether the procedure defined by an ENTRY
24 statement is permitted to reference itself or another procedure defined by the subprogram.
- 25 12 The keywords PURE and IMPURE are not used in an ENTRY statement. Instead, the procedure defined by an ENTRY statement
26 is pure if and only if the subprogram is a pure subprogram.
- 27 13 The keyword ELEMENTAL is not used in an ENTRY statement. Instead, the procedure defined by an ENTRY statement is elemental
28 if and only if ELEMENTAL is specified in the SUBROUTINE or FUNCTION statement.

29 12.6.2.7 RETURN statement

30 R1243 *return-stmt* is RETURN [*scalar-int-expr*]

31 C1278 (R1243) The *return-stmt* shall be in the inclusive scope of a function or subroutine subprogram.

32 C1279 (R1243) The *scalar-int-expr* is allowed only in the inclusive scope of a subroutine subprogram.

- 33 1 Execution of the RETURN statement completes execution of the instance of the subprogram in which it appears.
34 If the expression appears and has a value n between 1 and the number of asterisks in the dummy argument list, the CALL statement
35 that invoked the subroutine branches (8.2) to the branch target statement identified by the n^{th} alternate return specifier in the actual
36 argument list of the referenced procedure. If the expression is omitted or has a value outside the required range, there is no transfer
37 of control to an alternate return.
- 38 2 Execution of an *end-function-stmt*, *end-mp-subprogram-stmt*, or *end-subroutine-stmt* is equivalent to execution
39 of a RETURN statement with no expression.

40 12.6.2.8 CONTAINS statement

41 R1244 *contains-stmt* is CONTAINS

1 1 The CONTAINS statement separates the body of a main program, module, submodule, or subprogram from any
 2 internal or module subprograms it might contain, or it introduces the type-bound procedure part of a derived-type
 3 definition (4.5.5). The CONTAINS statement is not executable.

4 12.6.3 Definition and invocation of procedures by means other than Fortran

5 1 A procedure may be defined by means other than Fortran. The [interface](#) of a procedure defined by means other
 6 than Fortran may be specified by an [interface body](#) or [procedure declaration statement](#). A reference to such a
 7 procedure is made as though it were defined by an external subprogram.

8 2 A procedure defined by means other than Fortran that is invoked by a Fortran procedure and does not cause
 9 [termination of execution](#) shall return to its caller.

NOTE 12.47

Examples of code that might cause a transfer of control that bypasses the normal return mechanism of a Fortran procedure are setjmp and longjmp in C and exception handling in other languages. No such behavior is permitted by this part of ISO/IEC 1539.

10 3 If the [interface](#) of a procedure has a [proc-language-binding-spec](#), the procedure is [interoperable](#) (15.10).

11 4 Interoperation with C functions is described in 15.10.

NOTE 12.48

For explanatory information on definition of procedures by means other than Fortran, see subclause C.9.2.

12 12.6.4 Statement function

13 1 A statement function is a function defined by a single statement.

14 R1245 *stmt-function-stmt* is *function-name* ([*dummy-arg-name-list*]) = *scalar-expr*

15 C1280 (R1245) Each [primary](#) in *scalar-expr* shall be a constant (literal or named), a reference to a variable, a reference to a
 16 function, or an expression in parentheses. Each operation shall be intrinsic. If *scalar-expr* contains a reference to a
 17 function, the reference shall not require an [explicit interface](#), the function shall not require an [explicit interface](#) unless it is
 18 an intrinsic function, the function shall not be a [transformational](#) intrinsic, and the result shall be scalar. If an argument to
 19 a function is an array, it shall be an array name. If a reference to a statement function appears in *scalar-expr*, its definition
 20 shall have been provided earlier in the [scoping unit](#) and shall not be the name of the statement function being defined.

21 C1281 (R1245) [Named constants](#) in *scalar-expr* shall have been declared earlier in the [scoping unit](#) or made accessible by use
 22 or [host](#) association. If array elements appear in *scalar-expr*, the array shall have been declared as an array earlier in the
 23 [scoping unit](#) or made accessible by use or [host](#) association.

24 C1282 (R1245) If a [dummy-arg-name](#), variable, function reference, or dummy function reference is typed by the implicit typing
 25 rules, its appearance in any subsequent [type declaration statement](#) shall confirm this implied type and the values of any
 26 implied type parameters.

27 C1283 (R1245) The *function-name* and each [dummy-arg-name](#) shall be specified, explicitly or implicitly, to be scalar.

28 C1284 (R1245) A given [dummy-arg-name](#) shall not appear more than once in any [dummy-arg-name-list](#).

29 2 The definition of a statement function with the same name as an accessible entity from the [host](#) shall be preceded by the declaration
 30 of its type in a [type declaration statement](#).

31 3 The dummy arguments have a scope of the statement function statement. Each dummy argument has the same type and type
 32 parameters as the entity of the same name in the [scoping unit](#) containing the statement function statement.

33 4 A statement function shall not be supplied as an actual argument.

34 5 Execution of a statement function consists of evaluating the expression using the values of the [actual arguments](#) for the values of the
 35 corresponding dummy arguments and, if necessary, converting the result to the [declared type](#) and type parameters of the function.

1 6 A function reference in the scalar expression shall not cause a dummy argument of the statement function to become redefined or
2 undefined.

3 12.7 Pure procedures

4 1 A **pure procedure** is

- 5 • a pure intrinsic procedure (13.1),
- 6 • a **module procedure** in an intrinsic module, if it is specified to be pure,
- 7 • defined by a pure subprogram,
- 8 • a **dummy procedure** that has been specified to be **PURE**, or
- 9 • a statement function that references only pure functions.

10 2 A pure subprogram is a subprogram that has the *prefix-spec* **PURE** or that has the *prefix-spec* **ELEMENTAL**
11 and does not have the *prefix-spec* **IMPURE**. The following additional constraints apply to pure subprograms.

12 C1285 The *specification-part* of a pure function subprogram shall specify that all its nonpointer dummy data
13 objects have the **INTENT (IN)** or the **VALUE** attribute.

14 C1286 The function result of a pure function shall not be such that **finalization** of a reference to the function
15 would reference an impure procedure.

16 C1287 A pure function shall not have a **polymorphic** allocatable result.

17 C1288 The *specification-part* of a pure subroutine subprogram shall specify the intents of all its nonpointer
18 dummy data objects that do not have the **VALUE** attribute.

19 C1289 An **INTENT (OUT) dummy argument** of a pure procedure shall not be such that **finalization** of the
20 actual argument would reference an impure procedure.

21 C1290 An **INTENT (OUT) dummy argument** of a pure procedure shall not be **polymorphic**.

22 C1291 A local variable of a pure subprogram, or of a **BLOCK construct** within a pure subprogram, shall not
23 have the **SAVE** attribute.

NOTE 12.49

Variable initialization in a *type-declaration-stmt* or a *data-stmt* implies the **SAVE** attribute; therefore, such initialization is also disallowed.

24 C1292 The *specification-part* of a pure subprogram shall specify that all its **dummy procedures** are pure.

25 C1293 If a procedure that is neither an intrinsic procedure nor a statement function is used in a context that requires
26 it to be pure, then its **interface** shall be **explicit** in the scope of that use. The **interface** shall specify that
27 the procedure is pure.

28 C1294 All internal subprograms in a pure subprogram shall be pure.

29 C1295 A *designator* of a variable with the **VOLATILE** attribute shall not appear in a pure subprogram.

30 C1296 In a pure subprogram any **designator** with a **base object** that is in common or accessed by **host** or **use**
31 association, is a **pointer dummy argument** of a pure function, is a **dummy argument** with the **INTENT**
32 **(IN) attribute**, is a **coindexed object**, or an object that is **storage associated** with any such variable, shall
33 not be used

- 34 (1) in a variable definition context (16.6.7),
- 35 (2) in a pointer association context (16.6.8),
- 36 (3) as the *data-target* in a *pointer-assignment-stmt*,

- 1 (4) as the *expr* corresponding to a component with the **POINTER attribute** in a *structure-constructor*,
 2 (5) as the *expr* of an **intrinsic assignment statement** in which the variable is of a derived type if the
 3 derived type has a pointer component at any level of component selection,
 4 (6) as the *source-expr* in a **SOURCE= specifier** if the designator is of a derived type that has a pointer
 5 component at any level of component selection,
 6 (7) as an **actual argument** corresponding to a dummy argument with the **POINTER attribute**, or
 7 (8) as the **actual argument** to the function **C_LOC** from the intrinsic module **ISO_C_BINDING**.

NOTE 12.50

Item 5 requires that processors be able to determine if entities with the **PRIVATE attribute** or with private components have a pointer component.

- 8 C1297 Any procedure referenced in a pure subprogram, including one referenced via a **defined operation**, **defined**
 9 **assignment**, **defined input/output**, or **finalization**, shall be pure.
 10 C1298 A statement that might result in the deallocation of a **polymorphic** entity is not permitted in a pure
 11 procedure.

NOTE 12.51

This includes **intrinsic assignment** to a variable that has a **potential subobject component** that is **polymorphic** and **allocatable**.

- 12 C1299 A pure subprogram shall not contain a *print-stmt*, *open-stmt*, *close-stmt*, *backspace-stmt*, *endfile-stmt*,
 13 *rewind-stmt*, *flush-stmt*, *wait-stmt*, or *inquire-stmt*.
 14 C12100 A pure subprogram shall not contain a *read-stmt* or *write-stmt* whose *io-unit* is a *file-unit-number* or *.
 15 C12101 A pure subprogram shall not contain an **image control statement** (8.5.1).

NOTE 12.52

The above constraints are designed to guarantee that a **pure procedure** is free from side effects (modifications of data visible outside the procedure), which means that it is safe to reference it in constructs such as **DO CONCURRENT** and **FORALL**, where there is no explicit order of evaluation.

The constraints on pure subprograms appear to be complicated, but it is not necessary for a programmer to be intimately familiar with them. From the programmer's point of view, these constraints can be summarized as follows: a pure subprogram shall not contain any operation that could conceivably result in an assignment or **pointer assignment** to a common variable, a variable accessed by use or **host** association, or an **INTENT (IN)** dummy argument; nor shall a pure subprogram contain any operation that could conceivably perform any **external file** input/output or **STOP** operation. Note the use of the word conceivably; it is not sufficient for a pure subprogram merely to be side-effect free in practice. For example, a function that contains an assignment to a global variable but in a block that is not executed in any invocation of the function is nevertheless not a pure function. The exclusion of functions of this nature is required if strict compile-time checking is to be used.

It is expected that most library procedures will conform to the constraints required of **pure procedures**, and so can be declared pure and referenced in **DO CONCURRENT** constructs, **FORALL** statements and constructs, and within user-defined **pure procedures**.

NOTE 12.53

Pure subroutines are included to allow subroutine calls from **pure procedures** in a safe way, and to allow *forall-assignment-stmts* to be **defined assignments**. The constraints for pure subroutines are based on the same principles as for pure functions, except that side effects to **INTENT (OUT)**, **INTENT (INOUT)**, and pointer dummy arguments are permitted.

12.8 Elemental procedures

12.8.1 Elemental procedure declaration and interface

1 An **elemental procedure** is an elemental intrinsic procedure or a procedure that is defined by an **elemental subprogram**. An **elemental procedure** has only **scalar dummy arguments**, but may have array **actual arguments**.

2 An **elemental subprogram** has the *prefix-spec* **ELEMENTAL**. An **elemental subprogram** is a pure subprogram unless it has the *prefix-spec* **IMPURE**. The following additional constraints apply to **elemental subprograms**.

C12102 All **dummy arguments** of an **elemental procedure** shall be scalar noncoarray dummy data objects and shall not have the **POINTER** or **ALLOCATABLE** attribute.

C12103 The **result** of an **elemental** function shall be scalar, and shall not have the **POINTER** or **ALLOCATABLE** attribute.

C12104 The *specification-part* of an **elemental subprogram** shall specify the intents of all of its **dummy arguments** that do not have the **VALUE** attribute.

C12105 In the *specification-expr* that specifies a **type parameter** value of the result of an elemental function, an **object designator** with a **dummy argument** of the function as the **base object** shall appear only as the subject of a specification inquiry (7.1.11), and that specification inquiry shall not depend on a property that is deferred.

3 In a reference to an elemental procedure, if any argument is an array, each **actual argument** that corresponds to an **INTENT (OUT)** or **INTENT (INOUT)** **dummy argument** shall be an array. All **actual arguments** shall be **conformable**. An array **actual argument** is considered to be associated with the scalar **dummy arguments** of the procedure throughout the entire execution of the elemental reference; thus, the restrictions on actions specified in 12.5.2.13 apply to the entirety of the **actual array argument**.

12.8.2 Elemental function actual arguments and results

1 If a generic name or a **specific name** is used to reference an **elemental** function, the shape of the result is the same as the shape of the **actual argument** with the greatest **rank**. If there are no **actual arguments** or the **actual arguments** are all scalar, the result is scalar. In the array case, the values of the elements, if any, of the result are the same as would have been obtained if the scalar function had been applied separately, in array element order, to corresponding elements of each array **actual argument**.

NOTE 12.54

An example of an **elemental reference** to the intrinsic function **MAX**:

if X and Y are arrays of shape (M, N),

MAX (X, 0.0, Y)

is an array expression of shape (M, N) whose elements have values

MAX (X(I, J), 0.0, Y(I, J)), I = 1, 2, ..., M, J = 1, 2, ..., N

12.8.3 Elemental subroutine actual arguments

1 In a reference to an elemental subroutine, if the **actual arguments** corresponding to **INTENT (OUT)** and **INTENT (INOUT)** **dummy arguments** are arrays, the values of the elements, if any, of the results are the same as would be obtained if the subroutine had been applied separately, in array element order, to corresponding elements of each array **actual argument**.

13 Intrinsic procedures and modules

13.1 Classes of intrinsic procedures

- 1 Intrinsic procedures are divided into seven classes: [inquiry functions](#), [elemental functions](#), [transformational functions](#), [elemental subroutines](#), [pure subroutines](#), [atomic subroutines](#), and (impure) subroutines.
- 2 An intrinsic [inquiry function](#) is one whose result depends on the properties of one or more of its arguments instead of their values; in fact, these argument values may be undefined. Unless the description of an intrinsic [inquiry function](#) states otherwise, these arguments are permitted to be unallocated [allocatable](#) variables or pointers that are undefined or [disassociated](#). An [elemental](#) intrinsic function is one that is specified for scalar arguments, but may be applied to array arguments as described in [12.8](#). All other intrinsic functions are [transformational functions](#); they almost all have one or more array arguments or an array result. All standard intrinsic functions are pure.
- 3 An [atomic subroutine](#) is an intrinsic subroutine that performs an atomic action. The semantics of atomic actions are described in [13.5](#).
- 4 The subroutine [MOVE_ALLOC](#) and the [elemental](#) subroutine [MVBITS](#) are [pure](#). No other standard intrinsic subroutine is pure.
- 5 [Generic names](#) of standard intrinsic procedures are listed in [13.6](#). In most cases, generic functions accept arguments of more than one type and the type of the result is the same as the type of the arguments. [Specific names](#) of standard intrinsic functions with corresponding generic names are listed in [13.7](#).
- 6 If an intrinsic procedure is used as an [actual argument](#) to a procedure, its [specific name](#) shall be used and it may be referenced in the called procedure only with scalar arguments. If an intrinsic procedure does not have a [specific name](#), it shall not be used as an [actual argument](#) ([12.5.2.9](#)).
- 7 [Elemental](#) intrinsic procedures behave as described in [12.8](#).

13.2 Arguments to intrinsic procedures

13.2.1 General rules

- 1 All intrinsic procedures may be invoked with either positional arguments or [argument keywords](#) ([12.5](#)). The descriptions in [13.6](#) through [13.8](#) give the [argument keyword](#) names and positional sequence for standard intrinsic procedures.
- 2 Many of the intrinsic procedures have optional arguments. These arguments are identified by the notation “optional” in the argument descriptions. In addition, the names of the optional arguments are enclosed in square brackets in description headings and in lists of procedures. The valid forms of reference for procedures with optional arguments are described in [12.5.2](#).

NOTE 13.1

The text `CMPLX (X [, Y, KIND])` indicates that `Y` and `KIND` are both optional arguments. Valid reference forms include `CMPLX(x)`, `CMPLX(x, y)`, `CMPLX(x, KIND=kind)`, `CMPLX(x, y, kind)`, and `CMPLX(KIND=kind, X=x, Y=y)`.

NOTE 13.2

Some intrinsic procedures impose additional requirements on their optional arguments. For example, `SELECTED_REAL_KIND` requires that at least one of its optional arguments be present, and `RANDOM_SEED` requires that at most one of its optional arguments be present.

3 The dummy arguments of the specific intrinsic procedures in 13.7 have `INTENT (IN)`. The dummy arguments of the intrinsic procedures in 13.8 have `INTENT (IN)` if the intent is not stated explicitly.

4 The **actual argument** corresponding to an intrinsic function dummy argument named `KIND` shall be a scalar integer **constant expression** and its value shall specify a representation method for the function result that exists on the processor.

5 Intrinsic subroutines that assign values to arguments of type character do so in accordance with the rules of intrinsic assignment (7.2.1.3).

6 In a reference to the intrinsic subroutine `MVBITS`, the **actual arguments** corresponding to the `TO` and `FROM` dummy arguments may be the same variable and may be associated scalar variables or associated array variables all of whose corresponding elements are associated. Apart from this, the **actual arguments** in a reference to an **intrinsic** subroutine shall be such that the execution of the intrinsic subroutine would satisfy the restrictions of 12.5.2.13.

7 An argument to an intrinsic procedure other than `ASSOCIATED`, `NULL`, or `PRESENT` shall be a data object.

13.2.2 The shape of array arguments

1 Unless otherwise specified, the intrinsic **inquiry functions** accept array arguments for which the shape need not be defined. The shape of array arguments to **transformational** and **elemental** intrinsic functions shall be defined.

13.2.3 Mask arguments

1 Some array intrinsic functions have an optional `MASK` argument of type logical that is used by the function to select the elements of one or more arguments to be operated on by the function. Any element not selected by the mask need not be defined at the time the function is invoked.

2 The `MASK` affects only the value of the function, and does not affect the evaluation, prior to invoking the function, of arguments that are array expressions.

13.2.4 DIM arguments and reduction functions

1 Some array intrinsic functions are “reduction” functions; that is, they reduce the rank of an array by collapsing one dimension (or all dimensions, usually producing a scalar result). These functions have a `DIM` argument that can specify the dimension to be reduced.

2 The process of reducing a dimension usually combines the selected elements with a simple operation such as addition or an intrinsic function such as `MAX`, but more sophisticated reductions are also provided, e.g. by `COUNT` and `MAXLOC`.

13.3 Bit model

13.3.1 General

1 The bit manipulation procedures are described in terms of a model for the representation and behavior of bits on a processor.

2 For the purposes of these procedures, a bit is defined to be a binary digit w located at position k of a nonnegative

integer scalar object based on a model nonnegative integer defined by

$$j = \sum_{k=0}^{z-1} w_k \times 2^k$$

1 and for which w_k may have the value 0 or 1. This defines a sequence of bits $w_{z-1} \dots w_0$, with w_{z-1} the leftmost
 2 bit and w_0 the rightmost bit. The positions of bits in the sequence are numbered from right to left, with the
 3 position of the rightmost bit being zero. The length of a sequence of bits is z . An example of a model number
 4 compatible with the examples used in 13.4 would have $z = 32$, thereby defining a 32-bit integer.

5 3 The interpretation of a negative integer as a sequence of bits is processor dependent.

6 4 The [inquiry function BIT_SIZE](#) provides the value of the parameter z of the model.

7 5 Effectively, this model defines an integer object to consist of z bits in sequence numbered from right to left from
 8 0 to $z - 1$. This model is valid only in the context of the use of such an object as the argument or result of an
 9 intrinsic procedure that interprets that object as a sequence of bits. In all other contexts, the model defined for
 10 an integer in 13.4 applies. In particular, whereas the models are identical for $r = 2$ and $w_{z-1} = 0$, they do not
 11 correspond for $r \neq 2$ or $w_{z-1} = 1$ and the interpretation of bits in such objects is processor dependent.

12 13.3.2 Bit sequence comparisons

13 1 When bit sequences of unequal length are compared, the shorter sequence is considered to be extended to the
 14 length of the longer sequence by padding with zero bits on the left.

15 2 Bit sequences are compared from left to right, one bit at a time, until unequal bits are found or all bits have been
 16 compared and found to be equal. If unequal bits are found, the sequence with zero in the unequal position is
 17 considered to be less than the sequence with one in the unequal position. Otherwise the sequences are considered
 18 to be equal.

19 13.3.3 Bit sequences as arguments to INT and REAL

20 1 When a *boz-literal-constant* is the argument A of the intrinsic function [INT](#) or [REAL](#),

- 21 • if the length of the sequence of bits specified by A is less than the size in bits of a scalar variable of the
 22 same type and kind type parameter as the result, the *boz-literal-constant* is treated as if it were extended
 23 to a length equal to the size in bits of the result by padding on the left with zero bits, and
- 24 • if the length of the sequence of bits specified by A is greater than the size in bits of a scalar variable of the
 25 same type and kind type parameter as the result, the *boz-literal-constant* is treated as if it were truncated
 26 from the left to a length equal to the size in bits of the result.

27 C1301 If a *boz-literal-constant* is truncated as an argument to the intrinsic function [REAL](#), the discarded bits
 28 shall all be zero.

NOTE 13.3

The result values of the intrinsic functions [CMPLX](#) and [DBLE](#) are defined by references to the intrinsic function [REAL](#) with the same arguments. Therefore, the padding and truncation of *boz-literal-constant* arguments to those intrinsic functions is the same as for the intrinsic function [REAL](#).

29 13.4 Numeric models

30 1 The numeric manipulation and [inquiry functions](#) are described in terms of a model for the representation and
 31 behavior of numbers on a processor. The model has parameters that are determined so as to make the model
 32 best fit the machine on which the program is executed.

2 The model set for integer i is defined by

$$i = s \times \sum_{k=0}^{q-1} w_k \times r^k$$

3 where r is an integer exceeding one, q is a positive integer, each w_k is a nonnegative integer less than r , and s is
4 +1 or -1 .

3 The model set for real x is defined by

$$x = \begin{cases} 0 \text{ or} \\ s \times b^e \times \sum_{k=1}^p f_k \times b^{-k}, \end{cases}$$

3 where b and p are integers exceeding one; each f_k is a nonnegative integer less than b , with f_1 nonzero; s is $+1$ or
4 -1 ; and e is an integer that lies between some integer maximum e_{\max} and some integer minimum e_{\min} inclusively.
5 For $x = 0$, its exponent e and digits f_k are defined to be zero. The integer parameters r and q determine the
6 set of model integers and the integer parameters b , p , e_{\min} , and e_{\max} determine the set of model floating-point
7 numbers.

8 4 The parameters of the integer and real models are available for each representation method of the integer and
9 real types. The parameters characterize the set of available numbers in the definition of the model. Intrinsic
10 functions provide the values of some parameters and other values related to the models.

11 5 There is also an extended model set for each kind of real x ; this extended model is the same as the ordinary
12 model except that there are no limits on the range of the exponent e .

NOTE 13.4

Examples of these functions in 13.8 use the models

$$i = s \times \sum_{k=0}^{30} w_k \times 2^k$$

and

$$x = 0 \text{ or } s \times 2^e \times \left(\frac{1}{2} + \sum_{k=2}^{24} f_k \times 2^{-k} \right), \quad -126 \leq e \leq 127$$

13 13.5 Atomic subroutines

14 1 An [atomic subroutine](#) is an intrinsic subroutine that performs an action on its ATOM argument, and if it has an
15 OLD argument, determination of the value to be assigned to that argument, atomically. Definition or evaluation
16 of any argument other than ATOM is not performed atomically.

17 2 For any two executions in unordered segments of atomic subroutines whose ATOM argument is the same object,
18 the effect is as if one of the executions is performed completely before the other execution begins. Which execution
19 is performed first is processor dependent. The sequence of [atomic](#) actions within ordered segments is specified in
20 2.3.5. If successive atomic subroutine invocations on image P redefine a variable atomically in segments P_i and
21 P_j , atomic references to that variable from image Q in a segment Q_k that is unordered relative to P_i and P_j may
22 observe the changes in the value of that variable in any order.

23 3 Atomic operations shall make asynchronous progress. If a variable X on image P is defined by an [atomic](#)
24 [subroutine](#) on image Q , image R repeatedly references $X [P]$ by an atomic subroutine in an unordered segment,

- 1 and no other image defines X [*P*] in an unordered segment, image *R* shall eventually receive the value assigned
 2 by image *Q*, even if none of the images *P*, *Q*, or *R* execute an [image control statement](#) until after the definition
 3 of X [*P*] by image *Q* and the reception of that value by image *R*.
- 4 4 If the STAT argument is present in an invocation of an atomic subroutine and no error condition occurs, it is
 5 assigned the value zero.
- 6 5 If the STAT argument is present in an invocation of an atomic subroutine and an error condition occurs, it
 7 is assigned a processor-dependent positive value, and any other argument that is not [INTENT \(IN\)](#) becomes
 8 undefined.
- 9 6 If the STAT argument is not present in an invocation of an atomic subroutine and an error condition occurs,
 10 [error termination](#) is initiated.

NOTE 13.5

The properties of atomic subroutines are intended to support custom synchronization mechanisms. The program will need to handle all possible orderings of sequences of atomic subroutine executions that can arise as a consequence of the above rules; note that the orderings can appear to be different on different images even in the same program execution.

11 13.6 Standard generic intrinsic procedures

- 12 1 For all of the standard intrinsic procedures, the arguments shown are the names that shall be used for [argument](#)
 13 [keywords](#) if the keyword form is used for [actual arguments](#).

NOTE 13.6

For example, a reference to CMPLX can be written in the form CMPLX (A, B, M) or in the form CMPLX (Y = B, KIND = M, X = A).

NOTE 13.7

Many of the [argument keywords](#) have names that are indicative of their usage. For example:

KIND	Describes the kind type parameter of the result
STRING, STRING_A	An arbitrary character string
BACK	Controls the direction of string scan (forward or backward)
MASK	A mask to be applied to the arguments
DIM	A selected dimension of an array argument

- 14 2 In the Class column of Table [13.1](#),
- 15 A indicates that the procedure is an [atomic subroutine](#),
- 16 E indicates that the procedure is an [elemental](#) function,
- 17 ES indicates that the procedure is an [elemental](#) subroutine,
- 18 I indicates that the procedure is an [inquiry function](#),
- 19 PS indicates that the procedure is a [pure](#) subroutine,
- 20 S indicates that the procedure is an impure subroutine, and
- 21 T indicates that the procedure is a [transformational function](#).

Table 13.1: **Standard generic intrinsic procedure summary**

Procedure	Arguments	Class	Description
ABS	(A)	E	Absolute value.
ACHAR	(I [, KIND])	E	Character from ASCII code value.
ACOS	(X)	E	Arccosine (inverse cosine) function.

Table 13.1: Standard generic intrinsic procedure summary (cont.)

Procedure	Arguments	Class	Description
ACOSH	(X)	E	Inverse hyperbolic cosine function.
ADJUSTL	(STRING)	E	Left-justified string value.
ADJUSTR	(STRING)	E	Right-justified string value.
AIMAG	(Z)	E	Imaginary part of a complex number.
AINT	(A [, KIND])	E	Truncation toward 0 to a whole number.
ALL	(MASK) or (MASK, DIM)	T	Array reduced by .AND. operator.
ALLOCATED	(ARRAY) or (SCALAR)	I	Allocation status of allocatable variable.
ANINT	(A [, KIND])	E	Nearest whole number.
ANY	(MASK) or (MASK, DIM)	T	Array reduced by .OR. operator.
ASIN	(X)	E	Arcsine (inverse sine) function.
ASINH	(X)	E	Inverse hyperbolic sine function.
ASSOCIATED	(POINTER [, TARGET])	I	Pointer association status inquiry.
ATAN	(X) or (Y, X)	E	Arctangent (inverse tangent) function.
ATAN2	(Y, X)	E	Arctangent (inverse tangent) function.
ATANH	(X)	E	Inverse hyperbolic tangent function.
ATOMIC_ADD	(ATOM, VALUE [, STAT])	A	Atomic addition.
ATOMIC_AND	(ATOM, VALUE [, STAT])	A	Atomic bitwise AND.
ATOMIC_CAS	(ATOM, OLD, COMPARE, VALUE [, STAT])	A	Atomic compare and swap.
ATOMIC_DEFINE	(ATOM, VALUE [, STAT])	A	Define a variable atomically.
ATOMIC_FETCH_ADD	(ATOM, VALUE, OLD [, STAT])	A	Atomic fetch and add.
ATOMIC_FETCH_AND	(ATOM, VALUE, OLD [, STAT])	A	Atomic fetch and bitwise AND.
ATOMIC_FETCH_OR	(ATOM, VALUE, OLD [, STAT])	A	Atomic fetch and bitwise OR.
ATOMIC_FETCH_XOR	(ATOM, VALUE, OLD [, STAT])	A	Atomic fetch and bitwise exclusive OR.
ATOMIC_OR	(ATOM, VALUE [, STAT])	A	Atomic bitwise OR.
ATOMIC_REF	(VALUE, ATOM [, STAT])	A	Reference a variable atomically.
ATOMIC_XOR	(ATOM, VALUE [, STAT])	A	Atomic bitwise exclusive OR.
BESSEL_J0	(X)	E	Bessel function of the 1 st kind, order 0.
BESSEL_J1	(X)	E	Bessel function of the 1 st kind, order 1.
BESSEL_JN	(N, X)	E	Bessel function of the 1 st kind, order N.
BESSEL_JN	(N1, N2, X)	T	Bessel functions of the 1 st kind.
BESSEL_Y0	(X)	E	Bessel function of the 2 nd kind, order 0.
BESSEL_Y1	(X)	E	Bessel function of the 2 nd kind, order 1.
BESSEL_YN	(N, X)	E	Bessel function of the 2 nd kind, order N.
BESSEL_YN	(N1, N2, X)	T	Bessel functions of the 2 nd kind.
BGE	(I, J)	E	Bitwise greater than or equal to.
BGT	(I, J)	E	Bitwise greater than.
BIT_SIZE	(I)	I	Number of bits in integer model 13.3 .
BLE	(I, J)	E	Bitwise less than or equal to.
BLT	(I, J)	E	Bitwise less than.
BTEST	(I, POS)	E	Test single bit in an integer.
CEILING	(A [, KIND])	E	Least integer greater than or equal to A.
CHAR	(I [, KIND])	E	Character from code value.
CMPLX	(X [, KIND]) or (X [, Y, KIND])	E	Conversion to complex type.
COMMAND_ARGUMENT_COUNT	()	T	Number of command arguments.
CONJG	(Z)	E	Conjugate of a complex number.
COS	(X)	E	Cosine function.

Table 13.1: Standard generic intrinsic procedure summary (cont.)

Procedure	Arguments	Class	Description
COSH	(X)	E	Hyperbolic cosine function.
COSHAPE	(COARRAY [, KIND])	I	Sizes of codimensions of a coarray.
COUNT	(MASK [, DIM, KIND])	T	Logical array reduced by counting true values.
CPU_TIME	(TIME)	S	Processor time used.
CSHIFT	(ARRAY, SHIFT [, DIM])	T	Circular shift of an array.
DATE_AND_TIME	([DATE, TIME, ZONE, VALUES])	S	Date and time.
DBLE	(A)	E	Conversion to double precision real.
DIGITS	(X)	I	Significant digits in numeric model.
DIM	(X, Y)	E	Maximum of X – Y and zero.
DOT_PRODUCT	(VECTOR_A, VECTOR_B)	T	Dot product of two vectors.
DPROD	(X, Y)	E	Double precision real product.
DSHIFTL	(I, J, SHIFT)	E	Combined left shift.
DSHIFTR	(I, J, SHIFT)	E	Combined right shift.
EOSHIFT	(ARRAY, SHIFT [, BOUNDARY, DIM])	T	End-off shift of the elements of an array.
EPSILON	(X)	I	Model number that is small compared to 1.
ERF	(X)	E	Error function.
ERFC	(X)	E	Complementary error function.
ERFC_SCALED	(X)	E	Scaled complementary error function.
EVENT_QUERY	(EVENT, COUNT [, STAT])	S	Query event count.
EXECUTE_COMMAND_LINE	(COMMAND [, WAIT, EXITSTAT, CMDSTAT, CMDMSG])	S	Execute a command line.
EXP	(X)	E	Exponential function.
EXPONENT	(X)	E	Exponent of floating-point number.
EXTENDS_TYPE_OF	(A, MOLD)	I	Dynamic type extension inquiry.
FINDLOC	(ARRAY, VALUE, DIM [, MASK, KIND, BACK]) or (ARRAY, VALUE [, MASK, KIND, BACK])	T	Location(s) of a specified value.
FLOOR	(A [, KIND])	E	Greatest integer less than or equal to A.
FRACTION	(X)	E	Fractional part of number.
GAMMA	(X)	E	Gamma function.
GET_COMMAND	([COMMAND, LENGTH, STATUS, ERRMSG])	S	Get program invocation command.
GET_COMMAND_ARGUMENT	(NUMBER [, VALUE, LENGTH, STATUS, ERRMSG])	S	Get program invocation argument.
GET_ENVIRONMENT_VARIABLE	(NAME [, VALUE, LENGTH, STATUS, TRIM_NAME, ERRMSG])	S	Get environment variable.
HUGE	(X)	I	Largest model number.
HYPOT	(X, Y)	E	Euclidean distance function.
IACHAR	(C [, KIND])	E	ASCII code value for character.
IALL	(ARRAY, DIM [, MASK]) or (ARRAY [, MASK])	T	Array reduced by IAND function.
IAND	(I, J)	E	Bitwise AND.
IANY	(ARRAY, DIM [, MASK]) or (ARRAY [, MASK])	T	Array reduced by IOR function.

Table 13.1: Standard generic intrinsic procedure summary (cont.)

Procedure	Arguments	Class	Description
IBCLR	(I, POS)	E	I with bit POS replaced by zero.
IBITS	(I, POS, LEN)	E	Specified sequence of bits.
IBSET	(I, POS)	E	I with bit POS replaced by one.
ICHAR	(C [, KIND])	E	Code value for character.
IEOR	(I, J)	E	Bitwise exclusive OR.
IMAGE_INDEX	(COARRAY, SUB)	I	Image index from cosubscripts .
INDEX	(STRING, SUBSTRING [, BACK, KIND])	E	Character string search.
INT	(A [, KIND])	E	Conversion to integer type.
IOR	(I, J)	E	Bitwise inclusive OR.
IPARITY	(ARRAY, DIM [, MASK]) or (ARRAY [, MASK])	T	Array reduced by IEOB function.
ISHFT	(I, SHIFT)	E	Logical shift.
ISHFTC	(I, SHIFT [, SIZE])	E	Circular shift of the rightmost bits.
IS_CONTIGUOUS	(ARRAY)	I	Array contiguity test (5.5.7).
IS_IOSTAT_END	(I)	E	IOSTAT value test for end of file.
IS_IOSTAT_EOR	(I)	E	IOSTAT value test for end of record.
KIND	(X)	I	Value of the kind type parameter of X.
LBOUND	(ARRAY [, DIM, KIND])	I	Lower bound(s).
LCBOUND	(COARRAY [, DIM, KIND])	I	Lower cobound (s) of a coarray .
LEADZ	(I)	E	Number of leading zero bits.
LEN	(STRING [, KIND])	I	Length of a character entity.
LEN_TRIM	(STRING [, KIND])	E	Length without trailing blanks.
LGE	(STRING_A, STRING_B)	E	ASCII greater than or equal.
LGT	(STRING_A, STRING_B)	E	ASCII greater than.
LLE	(STRING_A, STRING_B)	E	ASCII less than or equal.
LLT	(STRING_A, STRING_B)	E	ASCII less than.
LOG	(X)	E	Natural logarithm.
LOG_GAMMA	(X)	E	Logarithm of the absolute value of the gamma function.
LOG10	(X)	E	Common logarithm.
LOGICAL	(L [, KIND])	E	Conversion between kinds of logical.
MASKL	(I [, KIND])	E	Left justified mask.
MASKR	(I [, KIND])	E	Right justified mask.
MATMUL	(MATRIX_A, MATRIX_B)	T	Matrix multiplication.
MAX	(A1, A2 [, A3, ...])	E	Maximum value.
MAXEXPONENT	(X)	I	Maximum exponent of a real model.
MAXLOC	(ARRAY, DIM [, MASK, KIND, BACK]) or (ARRAY [, MASK, KIND, BACK])	T	Location(s) of maximum value.
MAXVAL	(ARRAY, DIM [, MASK]) or (ARRAY [, MASK])	T	Maximum value(s) of array.
MERGE	(TSOURCE, FSOURCE, MASK)	E	Expression value selection.
MERGE_BITS	(I, J, MASK)	E	Merge of bits under mask.
MIN	(A1, A2 [, A3, ...])	E	Minimum value.
MINEXPONENT	(X)	I	Minimum exponent of a real model.
MINLOC	(ARRAY, DIM [, MASK, KIND, BACK]) or (ARRAY [, MASK, KIND, BACK])	T	Location(s) of minimum value.
MINVAL	(ARRAY, DIM [, MASK]) or (ARRAY [, MASK])	T	Minimum value(s) of array.
MOD	(A, P)	E	Remainder function.

Table 13.1: Standard generic intrinsic procedure summary (cont.)

Procedure	Arguments	Class	Description
MODULO	(A, P)	E	Modulo function.
MOVE_ALLOC	(FROM, TO)	PS	Move an allocation.
MVBITS	(FROM, FROMPOS, LEN, TO, TOPOS)	ES	Copy a sequence of bits.
NEAREST	(X, S)	E	Adjacent machine number.
NEW_LINE	(A)	I	Newline character.
NINT	(A [, KIND])	E	Nearest integer.
NORM2	(X) or (X, DIM)	T	L_2 norm of an array.
NOT	(I)	E	Bitwise complement.
NULL	([MOLD])	T	Disassociated pointer or unallocated allocatable entity.
NUM_IMAGES	()	T	Number of images .
OUT_OF_RANGE	(X, MOLD [, ROUND])	E	Whether a value cannot be converted safely.
PACK	(ARRAY, MASK [, VECTOR])	T	Array packed into a vector.
PARITY	(MASK) or (MASK, DIM)	T	Array reduced by .NEQV. operator.
POPCNT	(I)	E	Number of one bits.
POPPAR	(I)	E	Parity expressed as 0 or 1.
PRECISION	(X)	I	Decimal precision of a real model.
PRESENT	(A)	I	Presence of optional argument.
PRODUCT	(ARRAY, DIM [, MASK]) or (ARRAY [, MASK])	T	Array reduced by multiplication.
RADIX	(X)	I	Base of a numeric model.
RANDOM_INIT	(REPEATABLE, IMAGE_- DISTINCT)	S	Initialise the pseudorandom number generator.
RANDOM_NUMBER	(HARVEST)	S	Generate pseudorandom number(s).
RANDOM_SEED	([SIZE, PUT, GET])	S	Restart or query the pseudorandom number generator.
RANGE	(X)	I	Decimal exponent range of a numeric model (13.4).
RANK	(A)	I	Rank of a data object.
REAL	(A [, KIND])	E	Conversion to real type.
REDUCE	(ARRAY, OPERATION, DIM [, MASK, IDENTITY, ORDERED]) or (ARRAY, OPERATION [, MASK, IDENTITY, ORDERED])	T	General reduction of array
REPEAT	(STRING, NCOPIES)	T	Repetitive string concatenation.
RESHAPE	(SOURCE, SHAPE [, PAD, ORDER])	T	Arbitrary shape array construction.
RRSPACING	(X)	E	Reciprocal of relative spacing of model numbers.
SAME_TYPE_AS	(A, B)	I	Dynamic type equality test.
SCALE	(X, I)	E	Real number scaled by radix power.
SCAN	(STRING, SET [, BACK, KIND])	E	Character set membership search.
SELECTED_CHAR_- KIND	(NAME)	T	Character kind selection.
SELECTED_INT_- KIND	(R)	T	Integer kind selection.
SELECTED_REAL_- KIND	([P, R, RADIX])	T	Real kind selection.

Table 13.1: Standard generic intrinsic procedure summary (cont.)

Procedure	Arguments	Class	Description
SET_EXPONENT	(X, I)	E	Real value with specified exponent.
SHAPE	(SOURCE [, KIND])	I	Shape of an array or a scalar.
SHIFTA	(I, SHIFT)	E	Right shift with fill.
SHIFTL	(I, SHIFT)	E	Left shift.
SHIFTR	(I, SHIFT)	E	Right shift.
SIGN	(A, B)	E	Magnitude of A with the sign of B.
SIN	(X)	E	Sine function.
SINH	(X)	E	Hyperbolic sine function.
SIZE	(ARRAY [, DIM, KIND])	I	Size of an array or one extent.
SPACING	(X)	E	Spacing of model numbers (13.4).
SPREAD	(SOURCE, DIM, NCOPIES)	T	Value replicated in a new dimension.
SQRT	(X)	E	Square root.
STORAGE_SIZE	(A [, KIND])	I	Storage size in bits.
SUM	(ARRAY, DIM [, MASK]) or (ARRAY [, MASK])	T	Array reduced by addition.
SYSTEM_CLOCK	([COUNT, COUNT_RATE, COUNT_MAX])	S	Query system clock.
TAN	(X)	E	Tangent function.
TANH	(X)	E	Hyperbolic tangent function.
THIS_IMAGE	()	T	Index of the invoking image .
THIS_IMAGE	(COARRAY) or (COAR- RAY, DIM)	T	Cosubscript(s) for this image .
TINY	(X)	I	Smallest positive model number.
TRAILZ	(I)	E	Number of trailing zero bits.
TRANSFER	(SOURCE, MOLD [, SIZE])	T	Transfer physical representation.
TRANSPOSE	(MATRIX)	T	Transpose of an array of rank two.
TRIM	(STRING)	T	String without trailing blanks.
UBOUND	(ARRAY [, DIM, KIND])	I	Upper bound(s).
UCOBOUND	(COARRAY [, DIM, KIND])	I	Upper cobound(s) of a coarray .
UNPACK	(VECTOR, MASK, FIELD)	T	Vector unpacked into an array.
VERIFY	(STRING, SET [, BACK, KIND])	E	Character set non-membership search.

- 1 3 The effect of calling [EXECUTE_COMMAND_LINE](#) on any [image](#) other than [image](#) 1 is processor dependent.
- 2 4 If [RANDOM_INIT](#) or [RANDOM_SEED](#) is called in a segment A, and [RANDOM_INIT](#), [RANDOM_SEED](#), or
3 [RANDOM_NUMBER](#) is called in segment B, then segments A and B shall be ordered. It is processor dependent
4 whether each [image](#) uses a separate random number generator, or if some or all [images](#) use common random
5 number generators.
- 6 5 The use of all other standard intrinsic procedures in unordered segments is subject only to their argument use
7 following the rules in [8.5.2](#).

8 13.7 Specific names for standard intrinsic functions

- 9 1 Except for AMAX0, AMIN0, MAX1, and MIN1, the result type of the specific function is the same that the result type of the
10 corresponding generic function reference would be if it were invoked with the same arguments as the specific function.
- 11 2 A function listed in Table 13.3 is not permitted to be used as an [actual argument](#) ([12.5.1](#), C1240), as a target in a procedure
12 [pointer assignment statement](#) ([7.2.2.2](#), C730), as an initial target in a [procedure declaration statement](#) ([12.4.3.7](#), C1225), or to specify
13 an interface ([12.4.3.7](#), C1221).

Table 13.2: Unrestricted specific intrinsic functions

Specific name	Generic name	Argument type and kind
ABS	ABS	default real
ACOS	ACOS	default real
AIMAG	AIMAG	default complex
AINIT	AINIT	default real
ALOG	LOG	default real
ALOG10	LOG10	default real
AMOD	MOD	default real
ANINT	ANINT	default real
ASIN	ASIN	default real
ATAN	ATAN (X)	default real
ATAN2	ATAN2	default real
CABS	ABS	default complex
CCOS	COS	default complex
CEXP	EXP	default complex
CLOG	LOG	default complex
CONJG	CONJG	default complex
COS	COS	default real
COSH	COSH	default real
CSIN	SIN	default complex
CSQRT	SQRT	default complex
DABS	ABS	double precision real
DACOS	ACOS	double precision real
DASIN	ASIN	double precision real
DATAN	ATAN	double precision real
DATAN2	ATAN2	double precision real
DCOS	COS	double precision real
DCOSH	COSH	double precision real
DDIM	DIM	double precision real
DEXP	EXP	double precision real
DIM	DIM	default real
DINT	AINIT	double precision real
DLOG	LOG	double precision real
DLOG10	LOG10	double precision real
DMOD	MOD	double precision real
DNINT	ANINT	double precision real
DPROD	DPROD	default real
DSIGN	SIGN	double precision real
DSIN	SIN	double precision real
DSINH	SINH	double precision real
DSQRT	SQRT	double precision real
DTAN	TAN	double precision real
DTANH	TANH	double precision real
EXP	EXP	default real
IABS	ABS	default integer
IDIM	DIM	default integer
IDNINT	NINT	double precision real
INDEX	INDEX	default character
ISIGN	SIGN	default integer
LEN	LEN	default character
MOD	MOD	default integer
NINT	NINT	default real
SIGN	SIGN	default real
SIN	SIN	default real
SINH	SINH	default real
SQRT	SQRT	default real
TAN	TAN	default real
TANH	TANH	default real

Table 13.3: Restricted specific intrinsic functions

Specific name	Generic name	Argument type and kind
AMAX0 (...)	REAL (MAX (...))	default integer
AMAX1	MAX	default real
AMIN0 (...)	REAL (MIN (...))	default integer
AMIN1	MIN	default real
CHAR	CHAR	default integer

Restricted specific intrinsic functions (cont.)

Specific name	Generic name	Argument type and kind
DMAX1	MAX	double precision real
DMIN1	MIN	double precision real
FLOAT	REAL	default integer
ICHAR	ICHAR	default character
IDINT	INT	double precision real
IFIX	INT	default real
INT	INT	default real
LGE	LGE	default character
LGT	LGT	default character
LLE	LLE	default character
LLT	LLT	default character
MAX0	MAX	default integer
MAX1 (...)	INT (MAX (...))	default real
MIN0	MIN	default integer
MIN1 (...)	INT (MIN (...))	default real
REAL	REAL	default integer
SNGL	REAL	double precision real

13.8 Specifications of the standard intrinsic procedures

13.8.1 General

- 1 Detailed specifications of the standard generic intrinsic procedures are provided in 13.8 in alphabetical order.
- 2 The types and type parameters of standard intrinsic procedure arguments and function results are determined by these specifications. The “Argument(s)” paragraphs specify requirements on the **actual arguments** of the procedures. The result **characteristics** are sometimes specified in terms of the **characteristics** of dummy arguments. A program shall not invoke an intrinsic procedure under circumstances where a value to be assigned to a subroutine argument or returned as a function result is not representable by objects of the specified type and type parameters.
- 3 If an IEEE infinity is assigned or returned by an intrinsic procedure, the intrinsic module `IEEE_ARITHMETIC` is accessible, and the actual arguments were finite numbers, the flag `IEEE_OVERFLOW` or `IEEE_DIVIDE_BY_ZERO` shall signal. If an IEEE NaN is assigned or returned, the actual arguments were finite numbers, the intrinsic module `IEEE_ARITHMETIC` is accessible, and the exception `IEEE_INVALID` is supported, the flag `IEEE_INVALID` shall signal. If no IEEE infinity or NaN is assigned or returned, these flags shall have the same status as when the intrinsic procedure was invoked.

13.8.2 ABS (A)

- 1 **Description.** Absolute value.
- 2 **Class.** `Elemental` function.
- 3 **Argument.** A shall be of type integer, real, or complex.
- 4 **Result Characteristics.** The same as A except that if A is complex, the result is real.
- 5 **Result Value.** If A is of type integer or real, the value of the result is $|A|$; if A is complex with value (x, y) , the result is equal to a processor-dependent approximation to $\sqrt{x^2 + y^2}$ computed without undue overflow or underflow.
- 6 **Example.** `ABS((3.0, 4.0))` has the value 5.0 (approximately).

13.8.3 ACHAR (I [, KIND])

1 **Description.** Character from ASCII code value.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 I shall be of type integer.

5 KIND (optional) shall be a scalar integer [constant expression](#).

6 **Result Characteristics.** Character of length one. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise, the kind type parameter is that of default character.

7 **Result Value.** If I has a value in the range $0 \leq I \leq 127$, the result is the character in position I of the [ASCII collating sequence](#), provided the processor is capable of representing that character in the character kind of the result; otherwise, the result is processor dependent. ACHAR (IACHAR (C)) shall have the value C for any character C capable of representation as a default character.

8 **Example.** ACHAR (88) has the value 'X'.

13.8.4 ACOS (X)

9 **Description.** Arccosine (inverse cosine) function.

10 **Class.** [Elemental](#) function.

11 **Argument.** X shall be of type real with a value that satisfies the inequality $|X| \leq 1$, or of type complex.

12 **Result Characteristics.** Same as X.

13 **Result Value.** The result has a value equal to a processor-dependent approximation to $\arccos(X)$. If it is real it is expressed in radians and lies in the range $0 \leq \text{ACOS}(X) \leq \pi$. If it is complex the real part is expressed in radians and lies in the range $0 \leq \text{REAL}(\text{ACOS}(X)) \leq \pi$.

14 **Example.** ACOS (0.54030231) has the value 1.0 (approximately).

13.8.5 ACOSH (X)

15 **Description.** Inverse hyperbolic cosine function.

16 **Class.** [Elemental](#) function.

17 **Argument.** X shall be of type real or complex.

18 **Result Characteristics.** Same as X.

19 **Result Value.** The result has a value equal to a processor-dependent approximation to the inverse hyperbolic cosine function of X. If the result is complex the imaginary part is expressed in radians and lies in the range $0 \leq \text{AIMAG}(\text{ACOSH}(X)) \leq \pi$

20 **Example.** ACOSH (1.5430806) has the value 1.0 (approximately).

13.8.6 ADJUSTL (STRING)

21 **Description.** Left-justified string value.

22 **Class.** [Elemental](#) function.

23 **Argument.** STRING shall be of type character.

1 4 **Result Characteristics.** Character of the same length and kind type parameter as STRING.

2 5 **Result Value.** The value of the result is the same as STRING except that any leading blanks have been deleted
3 and the same number of trailing blanks have been inserted.

4 6 **Example.** ADJUSTL (' WORD') has the value 'WORD '.

5 13.8.7 ADJUSTR (STRING)

6 1 **Description.** Right-justified string value.

7 2 **Class.** [Elemental](#) function.

8 3 **Argument.** STRING shall be of type character.

9 4 **Result Characteristics.** Character of the same length and kind type parameter as STRING.

10 5 **Result Value.** The value of the result is the same as STRING except that any trailing blanks have been deleted
11 and the same number of leading blanks have been inserted.

12 6 **Example.** ADJUSTR ('WORD ') has the value ' WORD'.

13 13.8.8 AIMAG (Z)

14 1 **Description.** Imaginary part of a complex number.

15 2 **Class.** [Elemental](#) function.

16 3 **Argument.** Z shall be of type complex.

17 4 **Result Characteristics.** Real with the same kind type parameter as Z.

18 5 **Result Value.** If Z has the value (x, y) , the result has the value y .

19 6 **Example.** AIMAG ((2.0, 3.0)) has the value 3.0.

20 13.8.9 AINT (A [, KIND])

21 1 **Description.** Truncation toward 0 to a whole number.

22 2 **Class.** [Elemental](#) function.

23 3 **Arguments.**

24 A shall be of type real.

25 KIND (optional) shall be a scalar integer [constant expression](#).

26 4 **Result Characteristics.** The result is of type real. If KIND is present, the kind type parameter is that specified
27 by the value of KIND; otherwise, the kind type parameter is that of A.

28 5 **Result Value.** If $|A| < 1$, AINT (A) has the value 0; if $|A| \geq 1$, AINT (A) has a value equal to the integer
29 whose magnitude is the largest integer that does not exceed the magnitude of A and whose sign is the same as
30 the sign of A.

31 6 **Examples.** AINT (2.783) has the value 2.0. AINT (-2.783) has the value -2.0.

32 13.8.10 ALL (MASK) or ALL (MASK, DIM)

33 1 **Description.** Array reduced by [.AND.](#) operator.

34 2 **Class.** [Transformational](#) function.

1 3 **Arguments.**

2 MASK shall be a logical array.

3 DIM shall be an integer scalar with value in the range $1 \leq \text{DIM} \leq n$, where n is the **rank** of MASK.4 4 **Result Characteristics.** The result is of type logical with the same kind type parameter as MASK. It is scalar
5 if DIM does not appear or $n = 1$; otherwise, the result has **rank** $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1},$
6 $\dots, d_n]$ where $[d_1, d_2, \dots, d_n]$ is the shape of MASK.7 5 **Result Value.**8 *Case (i):* The result of ALL (MASK) has the value true if all elements of MASK are true or if MASK has
9 size zero, and the result has value false if any element of MASK is false.10 *Case (ii):* If MASK has **rank** one, ALL (MASK, DIM) is equal to ALL (MASK). Otherwise, the value of
11 element $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of ALL (MASK, DIM) is equal to ALL (MASK $(s_1,$
12 $s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$).13 6 **Examples.**14 *Case (i):* The value of ALL ([.TRUE., .FALSE., .TRUE.]) is false.15 *Case (ii):* If B is the array $\begin{bmatrix} 1 & 3 & 5 \\ 2 & 4 & 6 \end{bmatrix}$ and C is the array $\begin{bmatrix} 0 & 3 & 5 \\ 7 & 4 & 8 \end{bmatrix}$ then ALL (B /= C, DIM = 1) is
16 [true, false, false] and ALL (B /= C, DIM = 2) is [false, false].17 **13.8.11 ALLOCATED (ARRAY) or ALLOCATED (SCALAR)**18 1 **Description.** Allocation status of allocatable variable.19 2 **Class.** [Inquiry function](#).20 3 **Arguments.**21 ARRAY shall be an **allocatable** array.22 SCALAR shall be an **allocatable** scalar.23 4 **Result Characteristics.** Default logical scalar.24 5 **Result Value.** The result has the value true if the argument (ARRAY or SCALAR) is allocated and has the
25 value false if the argument is unallocated.26 **13.8.12 ANINT (A [, KIND])**27 1 **Description.** Nearest whole number.28 2 **Class.** [Elemental function](#).29 3 **Arguments.**

30 A shall be of type real.

31 KIND (optional) shall be a scalar integer **constant expression**.32 4 **Result Characteristics.** The result is of type real. If KIND is present, the kind type parameter is that specified
33 by the value of KIND; otherwise, the kind type parameter is that of A.34 5 **Result Value.** The result is the integer nearest A, or if there are two integers equally near A, the result is
35 whichever such integer has the greater magnitude.36 6 **Examples.** ANINT (2.783) has the value 3.0. ANINT (-2.783) has the value -3.0.

13.8.13 ANY (MASK) or ANY (MASK, DIM)

1 **Description.** Array reduced by `.OR.` operator.

2 **Class.** Transformational function.

3 **Arguments.**

4 MASK shall be a logical array.

5 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the `rank` of MASK.

6 **Result Characteristics.** The result is of type logical with the same kind type parameter as MASK. It is scalar if DIM does not appear or $n = 1$; otherwise, the result has `rank` $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$ where $[d_1, d_2, \dots, d_n]$ is the shape of MASK.

7 **Result Value.**

8 *Case (i):* The result of ANY (MASK) has the value true if any element of MASK is true and has the value false if no elements are true or if MASK has size zero.

9 *Case (ii):* If MASK has `rank` one, ANY (MASK, DIM) is equal to ANY (MASK). Otherwise, the value of element $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of ANY (MASK, DIM) is equal to ANY (MASK $(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$).

10 **Examples.**

11 *Case (i):* The value of ANY (`[.TRUE., .FALSE., .TRUE.]`) is true.

12 *Case (ii):* If B is the array $\begin{bmatrix} 1 & 3 & 5 \\ 2 & 4 & 6 \end{bmatrix}$ and C is the array $\begin{bmatrix} 0 & 3 & 5 \\ 7 & 4 & 8 \end{bmatrix}$ then ANY (B /= C, DIM = 1) is `[true, false, true]` and ANY (B /= C, DIM = 2) is `[true, true]`.

13.8.14 ASIN (X)

1 **Description.** Arcsine (inverse sine) function.

2 **Class.** Elemental function.

3 **Argument.** X shall be of type real with a value that satisfies the inequality $|X| \leq 1$, or of type complex.

4 **Result Characteristics.** Same as X.

5 **Result Value.** The result has a value equal to a processor-dependent approximation to $\arcsin(X)$. If it is real it is expressed in radians and lies in the range $-\pi/2 \leq \text{ASIN}(X) \leq \pi/2$. If it is complex the real part is expressed in radians and lies in the range $-\pi/2 \leq \text{REAL}(\text{ASIN}(X)) \leq \pi/2$.

6 **Example.** ASIN (0.84147098) has the value 1.0 (approximately).

13.8.15 ASINH (X)

1 **Description.** Inverse hyperbolic sine function.

2 **Class.** Elemental function.

3 **Argument.** X shall be of type real or complex.

4 **Result Characteristics.** Same as X.

5 **Result Value.** The result has a value equal to a processor-dependent approximation to the inverse hyperbolic sine function of X. If the result is complex the imaginary part is expressed in radians and lies in the range $-\pi/2 \leq \text{AIMAG}(\text{ASINH}(X)) \leq \pi/2$.

6 **Example.** ASINH (1.1752012) has the value 1.0 (approximately).

13.8.16 ASSOCIATED (POINTER [, TARGET])

1 **Description.** [Pointer association](#) status inquiry.

2 **Class.** [Inquiry function](#).

3 **Arguments.**

4 POINTER shall be a pointer. It may be of any type or may be a procedure pointer. Its [pointer association](#)

5 status shall not be undefined.
6
7 TARGET (optional) shall be allowable as the [data-target](#) or [proc-target](#) in a [pointer assignment statement \(7.2.2\)](#)
8 in which POINTER is [data-pointer-object](#) or [proc-pointer-object](#). If TARGET is a pointer then its
9 [pointer association](#) status shall not be undefined.

10 **4 Result Characteristics.** Default logical scalar.

11 **5 Result Value.**

12 *Case (i):* If TARGET is absent, the result is true if and only if POINTER is associated with a target.

13 *Case (ii):* If TARGET is present and is a procedure, the result is true if and only if POINTER is associated
14 with TARGET.

15 *Case (iii):* If TARGET is present and is a procedure pointer, the result is true if and only if POINTER and
16 TARGET are associated with the same procedure.

17 *Case (iv):* If TARGET is present and is a scalar target, the result is true if and only if TARGET is not a zero-
18 sized [storage sequence](#) and POINTER is associated with a target that occupies the same [storage](#)
19 [units](#) as TARGET.

20 *Case (v):* If TARGET is present and is an array target, the result is true if and only if POINTER is associated
21 with a target that has the same shape as TARGET, is neither of size zero nor an array whose elements
22 are zero-sized [storage sequences](#), and occupies the same [storage units](#) as TARGET in array element
23 order.

24 *Case (vi):* If TARGET is present and is a scalar pointer, the result is true if and only if POINTER and
25 TARGET are associated, the targets are not zero-sized [storage sequences](#), and they occupy the
26 same [storage units](#).

27 *Case (vii):* If TARGET is present and is an [array pointer](#), the result is true if and only if POINTER and
28 TARGET are both associated, have the same shape, are neither of size zero nor arrays whose
29 elements are zero-sized [storage sequences](#), and occupy the same [storage units](#) in array element
30 order.

NOTE 13.8

The references to TARGET in the above cases are referring to properties that might be possessed by the actual argument, so the case of TARGET being a disassociated pointer will be covered by case *(iii)*, *(vi)*, or *(vii)*.

31 **6 Examples.** ASSOCIATED (CURRENT, HEAD) is true if CURRENT is associated with the target HEAD.

32 After the execution of

33 `A_PART => A (:N)`

34 ASSOCIATED (A_PART, A) is true if N is equal to UBOUND (A, DIM = 1). After the execution of

35 `NULLIFY (CUR); NULLIFY (TOP)`

36 ASSOCIATED (CUR, TOP) is false.

13.8.17 ATAN (X) or ATAN (Y, X)

38 **1 Description.** Arctangent (inverse tangent) function.

39 **2 Class.** [Elemental](#) function.

40 **3 Arguments.**

1 Y shall be of type real.
 2 X If Y appears, X shall be of type real with the same kind type parameter as Y. If Y has the value
 3 zero, X shall not have the value zero. If Y does not appear, X shall be of type real or complex.

4 4 **Result Characteristics.** Same as X.

5 5 **Result Value.** If Y appears, the result is the same as the result of `ATAN2 (Y,X)`. If Y does not appear, the
 6 result has a value equal to a processor-dependent approximation to $\arctan(X)$ whose real part is expressed in
 7 radians and lies in the range $-\pi/2 \leq \text{ATAN}(X) \leq \pi/2$.

8 6 **Example.** `ATAN (1.5574077)` has the value 1.0 (approximately).

9 13.8.18 ATAN2 (Y, X)

10 1 **Description.** Arctangent (inverse tangent) function.

11 2 **Class.** `Elemental` function.

12 3 **Arguments.**

13 Y shall be of type real.

14 X shall be of the same type and kind type parameter as Y. If Y has the value zero, X shall not have
 15 the value zero.

16 4 **Result Characteristics.** Same as X.

17 5 **Result Value.** The result has a value equal to a processor-dependent approximation to the principal value of
 18 the argument of the complex number (X, Y), expressed in radians. It lies in the range $-\pi \leq \text{ATAN2}(Y,X)$
 19 $\leq \pi$ and is equal to a processor-dependent approximation to a value of $\arctan(Y/X)$ if $X \neq 0$. If $Y > 0$, the
 20 result is positive. If $Y = 0$ and $X > 0$, the result is Y. If $Y = 0$ and $X < 0$, then the result is approximately
 21 π if Y is positive real zero or the processor does not distinguish between positive and negative real zero, and
 22 approximately $-\pi$ if Y is negative real zero. If $Y < 0$, the result is negative. If $X = 0$, the absolute value of the
 23 result is approximately $\pi/2$.

24 6 **Examples.** `ATAN2 (1.5574077, 1.0)` has the value 1.0 (approximately). If Y has the value $\begin{bmatrix} 1 & 1 \\ -1 & -1 \end{bmatrix}$ and X
 25 has the value $\begin{bmatrix} -1 & 1 \\ -1 & 1 \end{bmatrix}$, the value of `ATAN2 (Y, X)` is approximately $\begin{bmatrix} 3\pi/4 & \pi/4 \\ -3\pi/4 & -\pi/4 \end{bmatrix}$.

26 13.8.19 ATANH (X)

27 1 **Description.** Inverse hyperbolic tangent function.

28 2 **Class.** `Elemental` function.

29 3 **Argument.** X shall be of type real or complex.

30 4 **Result Characteristics.** Same as X.

31 5 **Result Value.** The result has a value equal to a processor-dependent approximation to the inverse hyperbolic
 32 tangent function of X. If the result is complex the imaginary part is expressed in radians and lies in the range
 33 $-\pi/2 \leq \text{AIMAG}(\text{ATANH}(X)) \leq \pi/2$.

34 6 **Example.** `ATANH (0.76159416)` has the value 1.0 (approximately).

13.8.20 ATOMIC_ADD (ATOM, VALUE [, STAT])

1 **Description.** Atomic addition.

2 **Class.** Atomic subroutine.

3 **Arguments.**

4 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind [ATOMIC_INT_KIND](#) from the intrinsic module [ISO_FORTRAN_ENV](#). It is an [INTENT \(INOUT\)](#) argument. If an error condition occurs, ATOM becomes undefined; otherwise, it becomes defined with the value of $ATOM + VALUE$.

5 VALUE shall be an integer scalar. It is an [INTENT \(IN\)](#) argument. The values of VALUE and $ATOM + VALUE$ shall be representable in [ATOMIC_INT_KIND](#).

6 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an [INTENT \(OUT\)](#) argument. It is assigned a value as specified in [13.5](#). If an error condition occurs and STAT is not present, [error termination](#) is initiated.

7 **Example.** CALL ATOMIC_ADD (I [3], 42) will cause I on [image 3](#) to become defined with the value 46 if the value of I [3] is 4 when the atomic operation is executed.

13.8.21 ATOMIC_AND (ATOM, VALUE [, STAT])

1 **Description.** Atomic bitwise AND.

2 **Class.** Atomic subroutine.

3 **Arguments.**

4 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind [ATOMIC_INT_KIND](#) from the intrinsic module [ISO_FORTRAN_ENV](#). It is an [INTENT \(INOUT\)](#) argument. If an error condition occurs, ATOM becomes undefined; otherwise, it becomes defined with the value of [IAND \(ATOM, INT \(VALUE, ATOMIC_INT_KIND\)\)](#).

5 VALUE shall be an integer scalar. It is an [INTENT \(IN\)](#) argument. The value of VALUE shall be representable in [ATOMIC_INT_KIND](#).

6 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an [INTENT \(OUT\)](#) argument. It is assigned a value as specified in [13.5](#). If an error condition occurs and STAT is not present, [error termination](#) is initiated.

7 **Example.** CALL ATOMIC_AND (I [3], 6) will cause I on [image 3](#) to become defined with the value 4 if the value of I [3] is 5 when the atomic operation is executed.

13.8.22 ATOMIC_CAS (ATOM, OLD, COMPARE, NEW [, STAT])

1 **Description.** Atomic compare and swap.

2 **Class.** Atomic subroutine.

3 **Arguments.**

4 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind [ATOMIC_INT_KIND](#) from the intrinsic module [ISO_FORTRAN_ENV](#), or of type logical with kind [ATOMIC_LOGICAL_KIND](#) from the intrinsic module [ISO_FORTRAN_ENV](#). It is an [INTENT \(INOUT\)](#) argument. If an error condition occurs, ATOM becomes undefined; otherwise, if ATOM is of type integer and equal to COMPARE, or of type logical and equivalent to COMPARE, it becomes defined with the value of NEW.

5 OLD shall be scalar and of the same type and kind as ATOM. It is an [INTENT \(OUT\)](#) argument. If an error condition occurs, it becomes undefined; otherwise, it becomes defined with the value that

1 ATOM had at the start of the atomic operation.
 2 COMPARE shall be scalar and of the same type and kind as ATOM. It is an [INTENT \(IN\)](#) argument.
 3 NEW shall be scalar and of the same type and kind as ATOM. It is an [INTENT \(IN\)](#) argument.
 4 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an [INTENT](#)
 5 [\(OUT\)](#) argument. It is assigned a value as specified in [13.5](#). If an error condition occurs and STAT
 6 is not present, [error termination](#) is initiated.

7 4 **Example.** If the value of I on [image 3](#) is equal to 13 at the beginning of the atomic operation performed by
 8 CALL ATOMIC_CAS (I [3], OLD, 0, 1), the value of I on [image 3](#) will be unchanged, and OLD will become
 9 defined with the value 13. If the value of I on [image 3](#) is equal to 0 at the beginning of the atomic operation
 10 performed by CALL ATOMIC_CAS (I [3], OLD, 0, 1), I on [image 3](#) will become defined with the value 1, and
 11 OLD will become defined with the value 0.

12 13.8.23 ATOMIC_DEFINE (ATOM, VALUE [, STAT])

13 1 **Description.** Define a variable atomically.

14 2 **Class.** [Atomic subroutine.](#)

15 3 **Arguments.**

16 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind [ATOMIC_INT_](#)
 17 [KIND](#) from the intrinsic module [ISO_FORTRAN_ENV](#), or of type logical with kind [ATOMIC_](#)
 18 [LOGICAL_KIND](#) from the intrinsic module [ISO_FORTRAN_ENV](#). It is an [INTENT \(OUT\)](#)
 19 argument. On successful execution, it becomes defined with the value of VALUE. If an error
 20 condition occurs, it becomes undefined.

21 VALUE shall be scalar and of the same type as ATOM. It is an [INTENT \(IN\)](#) argument.

22 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an [INTENT](#)
 23 [\(OUT\)](#) argument. It is assigned a value as specified in [13.5](#). If an error condition occurs and STAT
 24 is not present, [error termination](#) is initiated.

25 4 **Example.** CALL ATOMIC_DEFINE (I [3], 4) causes I on [image 3](#) to become defined with the value 4.

26 13.8.24 ATOMIC_FETCH_ADD (ATOM, VALUE, OLD [, STAT])

27 1 **Description.** Atomic fetch and add.

28 2 **Class.** [Atomic subroutine.](#)

29 3 **Arguments.**

30 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind [ATOMIC_INT_](#)
 31 [KIND](#) from the intrinsic module [ISO_FORTRAN_ENV](#). It is an [INTENT \(INOUT\)](#) argument. If
 32 an error condition occurs, ATOM becomes undefined; otherwise, it becomes defined with the value
 33 of ATOM + VALUE.

34 VALUE shall be an integer scalar. It is an [INTENT \(IN\)](#) argument. The values of VALUE and ATOM +
 35 VALUE shall be representable in [ATOMIC_INT_KIND](#).

36 OLD shall be scalar and of the same type and kind as ATOM. It is an [INTENT \(OUT\)](#) argument. If
 37 an error condition occurs, it becomes undefined; otherwise, it becomes defined with the value that
 38 ATOM had at the start of the atomic operation.

39 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an [INTENT](#)
 40 [\(OUT\)](#) argument. It is assigned a value as specified in [13.5](#). If an error condition occurs and STAT
 41 is not present, [error termination](#) is initiated.

42 4 **Example.** CALL ATOMIC_FETCH_ADD (I [3], 7, J) will cause I on [image 3](#) to become defined with the value
 43 12, and J to become defined with the value 5, if the value of I [3] is 5 when the atomic operation is executed.

13.8.25 ATOMIC_FETCH_AND (ATOM, VALUE, OLD [, STAT])

1 **Description.** Atomic fetch and bitwise AND.

2 **Class.** [Atomic subroutine](#).

3 **Arguments.**

4 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind [ATOMIC_INT_KIND](#) from the intrinsic module [ISO_FORTRAN_ENV](#). It is an [INTENT \(INOUT\)](#) argument. If
5 an error condition occurs, ATOM becomes undefined; otherwise, it becomes defined with the value
6 of [IAND](#) (ATOM, [INT](#) (VALUE, [ATOMIC_INT_KIND](#))).

7
8
9 VALUE shall be an integer scalar. It is an [INTENT \(IN\)](#) argument. The value of VALUE shall be representable in [ATOMIC_INT_KIND](#).

10
11 OLD shall be scalar and of the same type and kind as ATOM. It is an [INTENT \(OUT\)](#) argument. If
12 an error condition occurs, it becomes undefined; otherwise, it becomes defined with the value that
13 ATOM had at the start of the atomic operation.

14 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an [INTENT \(OUT\)](#)
15 argument. It is assigned a value as specified in [13.5](#). If an error condition occurs and STAT
16 is not present, [error termination](#) is initiated.

17 **Example.** CALL ATOMIC_FETCH_AND (I [3], 6, J) will cause I on [image 3](#) to become defined with the value
18 4, and J to become defined with the value 5, if the value of I [3] is 5 when the atomic operation is executed.

13.8.26 ATOMIC_FETCH_OR (ATOM, VALUE, OLD [, STAT])

19 **Description.** Atomic fetch and bitwise OR.

20 **Class.** [Atomic subroutine](#).

21 **Arguments.**

22 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind [ATOMIC_INT_KIND](#)
23 from the intrinsic module [ISO_FORTRAN_ENV](#). It is an [INTENT \(INOUT\)](#) argument. If
24 an error condition occurs, ATOM becomes undefined; otherwise, it becomes defined with the value
25 of [IOR](#) (ATOM, [INT](#) (VALUE, [ATOMIC_INT_KIND](#))).

26
27 VALUE shall be an integer scalar. It is an [INTENT \(IN\)](#) argument. The value of VALUE shall be representable in [ATOMIC_INT_KIND](#).

28
29 OLD shall be scalar and of the same type and kind as ATOM. It is an [INTENT \(OUT\)](#) argument. If
30 an error condition occurs, it becomes undefined; otherwise, it becomes defined with the value that
31 ATOM had at the start of the atomic operation.

32 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an [INTENT \(OUT\)](#)
33 argument. It is assigned a value as specified in [13.5](#). If an error condition occurs and STAT
34 is not present, [error termination](#) is initiated.

35 **Example.** CALL ATOMIC_FETCH_OR (I [3], 1, J) will cause I on [image 3](#) to become defined with the value
36 3, and J to become defined with the value 2, if the value of I [3] is 2 when the atomic operation is executed.

13.8.27 ATOMIC_FETCH_XOR (ATOM, VALUE, OLD [, STAT])

37 **Description.** Atomic fetch and bitwise exclusive OR.

38 **Class.** [Atomic subroutine](#).

39 **Arguments.**

40 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind [ATOMIC_INT_KIND](#)
41 from the intrinsic module [ISO_FORTRAN_ENV](#). It is an [INTENT \(INOUT\)](#) argument. If
42

1 an error condition occurs, ATOM becomes undefined; otherwise, it becomes defined with the value
 2 of IEOR (ATOM, INT (VALUE, ATOMIC_INT_KIND)).
 3 VALUE shall be an integer scalar. It is an INTENT (IN) argument. The value of VALUE shall be repres-
 4 entable in ATOMIC_INT_KIND.
 5 OLD shall be scalar and of the same type and kind as ATOM. It is an INTENT (OUT) argument. If
 6 an error condition occurs, it becomes undefined; otherwise, it becomes defined with the value that
 7 ATOM had at the start of the atomic operation.
 8 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an INTENT
 9 (OUT) argument. It is assigned a value as specified in 13.5. If an error condition occurs and STAT
 10 is not present, error termination is initiated.

11 4 **Example.** CALL ATOMIC_FETCH_XOR (I [3], 1, J) will cause I on [image 3](#) to become defined with the value
 12 2, and J to become defined with the value 3, if the value of I [3] is 3 when the atomic operation is executed.

13 13.8.28 ATOMIC_OR (ATOM, VALUE [, STAT])

14 1 **Description.** Atomic bitwise OR.

15 2 **Class.** [Atomic subroutine.](#)

16 3 **Arguments.**

17 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind ATOMIC_INT_
 18 KIND from the intrinsic module ISO_FORTRAN_ENV. It is an INTENT (INOUT) argument. If
 19 an error condition occurs, ATOM becomes undefined; otherwise, it becomes defined with the value
 20 of IOR (ATOM, INT (VALUE, ATOMIC_INT_KIND)).

21 VALUE shall be an integer scalar. It is an INTENT (IN) argument. The value of VALUE shall be repres-
 22 entable in ATOMIC_INT_KIND.

23 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an INTENT
 24 (OUT) argument. It is assigned a value as specified in 13.5. If an error condition occurs and STAT
 25 is not present, error termination is initiated.

26 4 **Example.** CALL ATOMIC_OR (I [3], 1) will cause I on [image 3](#) to become defined with the value 3 if the value
 27 of I [3] is 2 when the atomic operation is executed.

28 13.8.29 ATOMIC_REF (VALUE, ATOM [, STAT])

29 1 **Description.** Reference a variable atomically.

30 2 **Class.** [Atomic subroutine.](#)

31 3 **Arguments.**

32 VALUE shall be scalar and of the same type as ATOM. It is an INTENT (OUT) argument. On successful
 33 execution, it becomes defined with the value of ATOM. If an error condition occurs, it becomes
 34 undefined.

35 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind ATOMIC_INT_
 36 KIND from the intrinsic module ISO_FORTRAN_ENV, or of type logical with kind ATOMIC_LO-
 37 GICAL_KIND from the intrinsic module ISO_FORTRAN_ENV. It is an INTENT (IN) argument.

38 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an INTENT
 39 (OUT) argument. It is assigned a value as specified in 13.5. If an error condition occurs and STAT
 40 is not present, error termination is initiated.

41 4 **Example.** CALL ATOMIC_REF (VAL, I [3]) causes VAL to become defined with the value of I on [image 3](#).

13.8.30 ATOMIC_XOR (ATOM, VALUE [, STAT])

1 **Description.** Atomic bitwise exclusive OR.

2 **Class.** [Atomic subroutine](#).

3 **Arguments.**

4 ATOM shall be a scalar [coarray](#) or [coindexed object](#). It shall be of type integer with kind [ATOMIC_INT_KIND](#) from the intrinsic module [ISO_FORTRAN_ENV](#). It is an [INTENT \(INOUT\)](#) argument. If an error condition occurs, ATOM becomes undefined; otherwise, it becomes defined with the value of [IEOR \(ATOM, INT \(VALUE, ATOMIC_INT_KIND\)\)](#).

5 VALUE shall be an integer scalar. It is an [INTENT \(IN\)](#) argument. The value of VALUE shall be representable in [ATOMIC_INT_KIND](#).

6 STAT (optional) shall be a noncoindexed integer scalar with a decimal range of at least four. It is an [INTENT \(OUT\)](#) argument. It is assigned a value as specified in [13.5](#). If an error condition occurs and STAT is not present, [error termination](#) is initiated.

7 **Example.** CALL ATOMIC_XOR (I [3], 1) will cause I on [image 3](#) to become defined with the value 2 if the value of I [3] is 3 when the atomic operation is executed.

13.8.31 BESSEL_J0 (X)

1 **Description.** Bessel function of the 1st kind, order 0.

2 **Class.** [Elemental](#) function.

3 **Argument.** X shall be of type real.

4 **Result Characteristics.** Same as X.

5 **Result Value.** The result has a value equal to a processor-dependent approximation to the Bessel function of the first kind and order zero of X.

6 **Example.** BESSEL_J0 (1.0) has the value 0.765 (approximately).

13.8.32 BESSEL_J1 (X)

1 **Description.** Bessel function of the 1st kind, order 1.

2 **Class.** [Elemental](#) function.

3 **Argument.** X shall be of type real.

4 **Result Characteristics.** Same as X.

5 **Result Value.** The result has a value equal to a processor-dependent approximation to the Bessel function of the first kind and order one of X.

6 **Example.** BESSEL_J1 (1.0) has the value 0.440 (approximately).

13.8.33 BESSEL_JN (N, X) or BESSEL_JN (N1, N2, X)

1 **Description.** Bessel functions of the 1st kind.

2 **Class.**

3 *Case (i):* BESSEL_JN (N,X) is an [elemental](#) function.

4 *Case (ii):* BESSEL_JN (N1,N2,X) is a [transformational function](#).

1 3 **Arguments.**

- 2 N shall be of type integer and nonnegative.
 3 N1 an integer scalar with a nonnegative value.
 4 N2 an integer scalar with a nonnegative value.
 5 X shall be of type real; if the function is transformational, X shall be scalar.

6 4 **Result Characteristics.** Same type and kind as X.

- 7 *Case (i):* The result of BESSEL_JN (N, X) has the same shape as X.
 8 *Case (ii):* The result of BESSEL_JN (N1, N2, X) is a rank-one array with extent [MAX](#) (N2–N1+1, 0).

9 5 **Result Value.**

- 10 *Case (i):* The result value of BESSEL_JN (N, X) is a processor-dependent approximation to the Bessel
 11 function of the first kind and order N of X.
 12 *Case (ii):* Element *i* of the result value of BESSEL_JN (N1, N2, X) is a processor-dependent approximation
 13 to the Bessel function of the first kind and order $N1+i-1$ of X.

14 6 **Example.** BESSEL_JN (2, 1.0) has the value 0.115 (approximately).

15 **13.8.34 BESSEL_Y0 (X)**

16 1 **Description.** Bessel function of the 2^{nd} kind, order 0.

17 2 **Class.** [Elemental](#) function.

18 3 **Argument.** X shall be of type real. Its value shall be greater than zero.

19 4 **Result Characteristics.** Same as X.

20 5 **Result Value.** The result has a value equal to a processor-dependent approximation to the Bessel function of
 21 the second kind and order zero of X.

22 6 **Example.** BESSEL_Y0 (1.0) has the value 0.088 (approximately).

23 **13.8.35 BESSEL_Y1 (X)**

24 1 **Description.** Bessel function of the 2^{nd} kind, order 1.

25 2 **Class.** [Elemental](#) function.

26 3 **Argument.** X shall be of type real. Its value shall be greater than zero.

27 4 **Result Characteristics.** Same as X.

28 5 **Result Value.** The result has a value equal to a processor-dependent approximation to the Bessel function of
 29 the second kind and order one of X.

30 6 **Example.** BESSEL_Y1 (1.0) has the value -0.781 (approximately).

31 **13.8.36 BESSEL_YN (N, X) or BESSEL_YN (N1, N2, X)**

32 1 **Description.** Bessel functions of the 2^{nd} kind.

33 2 **Class.**

34 *Case (i):* BESSEL_YN (N, X) is an [elemental](#) function.

35 *Case (ii):* BESSEL_YN (N1, N2, X) is a [transformational function](#).

36 3 **Arguments.**

- 1 N shall be of type integer and nonnegative.
 2 N1 an integer scalar with a nonnegative value.
 3 N2 an integer scalar with a nonnegative value.
 4 X shall be of type real; if the function is transformational, X shall be scalar. Its value shall be greater
 5 than zero.

6 4 **Result Characteristics.** Same type and kind as X.

7 *Case (i):* The result of BESSEL_YN (N, X) has the same shape as X.

8 *Case (ii):* The result of BESSEL_YN (N1, N2, X) is a rank-one array with extent **MAX** (N2–N1+1, 0).

9 5 **Result Value.**

10 *Case (i):* The result value of BESSEL_YN (N, X) is a processor-dependent approximation to the Bessel
 11 function of the second kind and order N of X.

12 *Case (ii):* Element *i* of the result value of BESSEL_YN (N1, N2, X) is a processor-dependent approximation
 13 to the Bessel function of the second kind and order N1+i – 1 of X.

14 6 **Example.** BESSEL_YN (2, 1.0) has the value –1.651 (approximately).

15 13.8.37 BGE (I, J)

16 1 **Description.** Bitwise greater than or equal to.

17 2 **Class.** [Elemental](#) function.

18 3 **Arguments.**

19 I shall be of type integer or a *boz-literal-constant*.

20 J shall be of type integer or a *boz-literal-constant*.

21 4 **Result Characteristics.** Default logical.

22 5 **Result Value.** The result is true if the sequence of bits represented by I is greater than or equal to the sequence
 23 of bits represented by J, according to the method of bit sequence comparison in [13.3.2](#); otherwise the result is
 24 false.

25 6 The interpretation of a *boz-literal-constant* as a sequence of bits is described in [4.7](#). The interpretation of an
 26 integer value as a sequence of bits is described in [13.3](#).

27 7 **Example.** If BIT_SIZE (J) has the value 8, BGE (Z'FF', J) has the value true for any value of J. BGE (0, –1)
 28 has the value false.

29 13.8.38 BGT (I, J)

30 1 **Description.** Bitwise greater than.

31 2 **Class.** [Elemental](#) function.

32 3 **Arguments.**

33 I shall be of type integer or a *boz-literal-constant*.

34 J shall be of type integer or a *boz-literal-constant*.

35 4 **Result Characteristics.** Default logical.

36 5 **Result Value.** The result is true if the sequence of bits represented by I is greater than the sequence of bits
 37 represented by J, according to the method of bit sequence comparison in [13.3.2](#); otherwise the result is false.

38 6 The interpretation of a *boz-literal-constant* as a sequence of bits is described in [4.7](#). The interpretation of an
 39 integer value as a sequence of bits is described in [13.3](#).

1 7 **Example.** BGT (Z'FF', Z'FC') has the value true. BGT (0, -1) has the value false.

2 13.8.39 BIT_SIZE (I)

3 1 **Description.** Number of bits in integer model 13.3.

4 2 **Class.** Inquiry function.

5 3 **Argument.** I shall be of type integer. It may be a scalar or an array.

6 4 **Result Characteristics.** Scalar integer with the same kind type parameter as I.

7 5 **Result Value.** The result has the value of the number of bits z of the model integer defined for bit manipulation
8 contexts in 13.3.

9 6 **Example.** BIT_SIZE (1) has the value 32 if z of the model is 32.

10 13.8.40 BLE (I, J)

11 1 **Description.** Bitwise less than or equal to.

12 2 **Class.** Elemental function.

13 3 **Arguments.**

14 I shall be of type integer or a *boz-literal-constant*.

15 J shall be of type integer or a *boz-literal-constant*.

16 4 **Result Characteristics.** Default logical.

17 5 **Result Value.** The result is true if the sequence of bits represented by I is less than or equal to the sequence of
18 bits represented by J, according to the method of bit sequence comparison in 13.3.2; otherwise the result is false.

19 6 The interpretation of a *boz-literal-constant* as a sequence of bits is described in 4.7. The interpretation of an
20 integer value as a sequence of bits is described in 13.3.

21 7 **Example.** BLE (0, J) has the value true for any value of J. BLE (-1, 0) has the value false.

22 13.8.41 BLT (I, J)

23 1 **Description.** Bitwise less than.

24 2 **Class.** Elemental function.

25 3 **Arguments.**

26 I shall be of type integer or a *boz-literal-constant*.

27 J shall be of type integer or a *boz-literal-constant*.

28 4 **Result Characteristics.** Default logical.

29 5 **Result Value.** The result is true if the sequence of bits represented by I is less than the sequence of bits
30 represented by J, according to the method of bit sequence comparison in 13.3.2; otherwise the result is false.

31 6 The interpretation of a *boz-literal-constant* as a sequence of bits is described in 4.7. The interpretation of an
32 integer value as a sequence of bits is described in 13.3.

33 7 **Example.** BLT (0, -1) has the value true. BLT (Z'FF', Z'FC') has the value false.

13.8.42 BTEST (I, POS)

1 **Description.** Test single bit in an integer.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 I shall be of type integer.

5 POS shall be of type integer. It shall be nonnegative and be less than BIT_SIZE (I).

6 **Result Characteristics.** Default logical.

7 **Result Value.** The result has the value true if bit POS of I has the value 1 and has the value false if bit POS of I has the value 0. The model for the interpretation of an integer value as a sequence of bits is in [13.3](#).

8 **Examples.** BTEST (8, 3) has the value true. If A has the value $\begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix}$, the value of BTEST (A, 2) is
 9 $\begin{bmatrix} \text{false} & \text{false} \\ \text{false} & \text{true} \end{bmatrix}$ and the value of BTEST (2, A) is $\begin{bmatrix} \text{true} & \text{false} \\ \text{false} & \text{false} \end{bmatrix}$.

13.8.43 CEILING (A [, KIND])

1 **Description.** Least integer greater than or equal to A.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 A shall be of type real.

5 KIND (optional) shall be a scalar integer [constant expression](#).

6 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise, the kind type parameter is that of default integer type.

7 **Result Value.** The result has a value equal to the least integer greater than or equal to A.

8 **Examples.** CEILING (3.7) has the value 4. CEILING (-3.7) has the value -3.

13.8.44 CHAR (I [, KIND])

1 **Description.** Character from code value.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 I shall be of type integer with a value in the range $0 \leq I \leq n - 1$, where n is the number of characters in the [collating sequence](#) associated with the specified kind type parameter.

5 KIND (optional) shall be a scalar integer [constant expression](#).

6 **Result Characteristics.** Character of length one. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise, the kind type parameter is that of default character.

7 **Result Value.** The result is the character in position I of the [collating sequence](#) associated with the specified kind type parameter. ICHAR (CHAR (I, KIND (C))) shall have the value I for $0 \leq I \leq n - 1$ and CHAR (ICHAR (C), KIND (C)) shall have the value C for any character C capable of representation in the processor.

8 **Example.** CHAR (88) has the value 'X' on a processor using the [ASCII collating sequence](#) for default characters.

13.8.45 CMPLX (X [, KIND]) or CMPLX (X [, Y, KIND])

1 **Description.** Conversion to complex type.

2 **Class.** [Elemental](#) function.

3 **Arguments for CMPLX(X [, KIND]).**

4 X shall be of type complex.

5 KIND (optional) shall be a scalar integer [constant expression](#).

6 **Arguments for CMPLX(X [, Y, KIND]).**

7 X shall be of type integer or real, or a *boz-literal-constant*.

8 Y (optional) shall be of type integer or real, or a *boz-literal-constant*.

9 KIND (optional) shall be a scalar integer [constant expression](#).

10 **Result Characteristics.** The result is of type complex. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise, the kind type parameter is that of default real kind.

11 **Result Value.** If Y is absent and X is not complex, it is as if Y were present with the value zero. If KIND is absent, it is as if KIND were present with the value [KIND](#) (0.0). If X is complex, the result is the same as that of [CMPLX \(REAL \(X\), AIMAG \(X\), KIND\)](#). The result of [CMPLX \(X, Y, KIND\)](#) has the complex value whose real part is [REAL \(X, KIND\)](#) and whose imaginary part is [REAL \(Y, KIND\)](#).

12 **Example.** [CMPLX \(-3\)](#) has the value (-3.0, 0.0).

13.8.46 COMMAND_ARGUMENT_COUNT ()

1 **Description.** Number of command arguments.

2 **Class.** [Transformational function](#).

3 **Argument.** None.

4 **Result Characteristics.** Default integer scalar.

5 **Result Value.** The result value is equal to the number of command arguments available. If there are no command arguments available or if the processor does not support command arguments, then the result has the value zero. If the processor has a concept of a command name, the command name does not count as one of the command arguments.

6 **Example.** See [13.8.77](#).

13.8.47 CONJG (Z)

1 **Description.** Conjugate of a complex number.

2 **Class.** [Elemental](#) function.

3 **Argument.** Z shall be of type complex.

4 **Result Characteristics.** Same as Z.

5 **Result Value.** If Z has the value (x, y) , the result has the value $(x, -y)$.

6 **Example.** [CONJG \(\(2.0, 3.0\)\)](#) has the value (2.0, -3.0).

1 13.8.48 COS (X)

2 1 **Description.** Cosine function.

3 2 **Class.** [Elemental](#) function.

4 3 **Argument.** X shall be of type real or complex.

5 4 **Result Characteristics.** Same as X.

6 5 **Result Value.** The result has a value equal to a processor-dependent approximation to $\cos(X)$. If X is of type real, it is regarded as a value in radians. If X is of type complex, its real part is regarded as a value in radians.

8 6 **Example.** COS (1.0) has the value 0.54030231 (approximately).

9 13.8.49 COSH (X)

10 1 **Description.** Hyperbolic cosine function.

11 2 **Class.** [Elemental](#) function.

12 3 **Argument.** X shall be of type real or complex.

13 4 **Result Characteristics.** Same as X.

14 5 **Result Value.** The result has a value equal to a processor-dependent approximation to $\cosh(X)$. If X is of type complex its imaginary part is regarded as a value in radians.

16 6 **Example.** COSH (1.0) has the value 1.5430806 (approximately).

17 13.8.50 COSHAPE (COARRAY [, KIND])

18 1 **Description.** Sizes of [codimensions](#) of a [coarray](#).

19 2 **Class.** [Inquiry function](#).

20 3 **Arguments.**

21 COARRAY shall be a [coarray](#) of any type. It shall not be an unallocated [allocatable coarray](#).

22 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise the kind type parameter is that of default integer type. The result is an array of [rank](#) one whose size is equal to the [corank](#) of COARRAY.

25 5 **Result Value.** The result has a value whose i^{th} element is equal to the size of the i^{th} [codimension](#) of COARRAY, as given by $UCOBOUND(COARRAY, i) - LCOBOUND(COARRAY, i) + 1$.

27 6 **Example.**

28 The following code allocates the coarray D with the same size in each codimension as that of the coarray C, with
29 the lower cobound 1.

```
30     REAL, ALLOCATABLE :: C[:,:], D[:,:]
31     INTEGER, ALLOCATABLE :: COSHAPE_C(:)
32     ...
33     COSHAPE_C = COSHAPE(C)
34     ALLOCATE ( D[COSHAPE_C(1),*] )
```

13.8.51 COUNT (MASK [, DIM, KIND])

1 **Description.** Logical array reduced by counting true values.

2 **Class.** Transformational function.

3 **Arguments.**

4 MASK shall be a logical array.

5 DIM (optional) shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the rank of MASK.
6 The corresponding actual argument shall not be an optional dummy argument, a disassociated
7 pointer, or an unallocated allocatable.
8

9 KIND (optional) shall be a scalar integer constant expression.

10 **4 Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of
11 KIND; otherwise the kind type parameter is that of default integer type. The result is scalar if DIM is absent or
12 $n = 1$; otherwise, the result has rank $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$ where $[d_1, d_2, \dots, d_n]$
13 is the shape of MASK.

14 **5 Result Value.**

15 *Case (i):* If DIM is absent or MASK has rank one, the result has a value equal to the number of true elements
16 of MASK or has the value zero if MASK has size zero.

17 *Case (ii):* If DIM is present and MASK has rank $n > 1$, the value of element $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots,$
18 $s_n)$ of the result is equal to the number of true elements of MASK $(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1},$
19 $\dots, s_n)$.

20 **6 Examples.**

21 *Case (i):* The value of COUNT (.TRUE., .FALSE., .TRUE.) is 2.

22 *Case (ii):* If B is the array $\begin{bmatrix} 1 & 3 & 5 \\ 2 & 4 & 6 \end{bmatrix}$ and C is the array $\begin{bmatrix} 0 & 3 & 5 \\ 7 & 4 & 8 \end{bmatrix}$, COUNT (B /= C, DIM = 1) is
23 $[2, 0, 1]$ and COUNT (B /= C, DIM = 2) is $[1, 2]$.

13.8.52 CPU_TIME (TIME)

25 **1 Description.** Processor time used.

26 **2 Class.** Subroutine.

27 **3 Argument.** TIME shall be a real scalar. It is an INTENT (OUT) argument. If the processor cannot provide
28 a meaningful value for the time, it is assigned a processor-dependent negative value; otherwise, it is assigned a
29 processor-dependent approximation to the processor time in seconds. Whether the value assigned is an approx-
30 imation to the amount of time used by the invoking image, or the amount of time used by the whole program, is
31 processor dependent.

32 **4 Example.**

```
33     REAL T1, T2
34     ...
35     CALL CPU_TIME(T1)
36     ... ! Code to be timed.
37     CALL CPU_TIME(T2)
38     WRITE (*,*) 'Time taken by code was ', T2-T1, ' seconds'
```

39 writes the processor time taken by a piece of code.

NOTE 13.9

A processor for which a single result is inadequate (for example, a parallel processor) might choose to provide an additional version for which time is an array.

The exact definition of time is left imprecise because of the variability in what different processors are able to provide. The primary purpose is to compare different algorithms on the same processor or discover which parts of a calculation are the most expensive.

The start time is left imprecise because the purpose is to time sections of code, as in the example.

Most computer systems have multiple concepts of time. One common concept is that of time expended by the processor for a given program. This might or might not include system overhead, and has no obvious connection to elapsed “wall clock” time.

13.8.53 CSHIFT (ARRAY, SHIFT [, DIM])

1 Description. Circular shift of an array.

2 Class. Transformational function.

3 Arguments.

ARRAY may be of any type. It shall be an array.

SHIFT shall be of type integer and shall be scalar if ARRAY has **rank** one; otherwise, it shall be scalar or of **rank** $n - 1$ and of shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$ where $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

DIM (optional) shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the **rank** of ARRAY. If DIM is absent, it is as if it were present with the value 1.

4 Result Characteristics. The result is of the type and type parameters of ARRAY, and has the shape of ARRAY.

5 Result Value.

Case (i): If ARRAY has **rank** one, element i of the result is $\text{ARRAY}(1 + \text{MODULO}(i + \text{SHIFT} - 1, \text{SIZE}(\text{ARRAY})))$.

Case (ii): If ARRAY has **rank** greater than one, section $(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$ of the result has a value equal to $\text{CSHIFT}(\text{ARRAY}(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n), sh, 1)$, where sh is SHIFT or $\text{SHIFT}(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$.

6 Examples.

Case (i): If V is the array [1, 2, 3, 4, 5, 6], the effect of shifting V circularly to the left by two positions is achieved by $\text{CSHIFT}(V, \text{SHIFT} = 2)$ which has the value [3, 4, 5, 6, 1, 2]; $\text{CSHIFT}(V, \text{SHIFT} = -2)$ achieves a circular shift to the right by two positions and has the value [5, 6, 1, 2, 3, 4].

Case (ii): The rows of an array of **rank** two may all be shifted by the same amount or by different amounts.

If M is the array $\begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$, the value of

$\text{CSHIFT}(M, \text{SHIFT} = -1, \text{DIM} = 2)$ is $\begin{bmatrix} 3 & 1 & 2 \\ 6 & 4 & 5 \\ 9 & 7 & 8 \end{bmatrix}$, and the value of

$\text{CSHIFT}(M, \text{SHIFT} = [-1, 1, 0], \text{DIM} = 2)$ is $\begin{bmatrix} 3 & 1 & 2 \\ 5 & 6 & 4 \\ 7 & 8 & 9 \end{bmatrix}$.

13.8.54 DATE_AND_TIME ([DATE, TIME, ZONE, VALUES])

1 **Description.** Date and time.

2 **Class.** Subroutine.

3 **Arguments.**

4 DATE (optional) shall be a default character scalar. It is an **INTENT (OUT)** argument. It is assigned a value
5 of the form *CCYYMMDD*, where *CC* is the century, *YY* is the year within the century, *MM* is the
6 month within the year, and *DD* is the day within the month. If there is no date available, DATE
7 is assigned all blanks.

8 TIME (optional) shall be a default character scalar. It is an **INTENT (OUT)** argument. It is assigned a value
9 of the form *hhmmss.sss*, where *hh* is the hour of the day, *mm* is the minutes of the hour, and *ss.sss*
10 is the seconds and milliseconds of the minute. If there is no clock available, TIME is assigned all
11 blanks.

12 ZONE (optional) shall be a default character scalar. It is an **INTENT (OUT)** argument. It is assigned a value of
13 the form *+hhmm* or *-hhmm*, where *hh* and *mm* are the time difference with respect to Coordinated
14 Universal Time (UTC) in hours and minutes, respectively. If this information is not available,
15 ZONE is assigned all blanks.

16 VALUES (optional) shall be a rank-one array of type integer with a decimal exponent range of at least four. It
17 is an **INTENT (OUT)** argument. Its size shall be at least 8. The values assigned to VALUES are
18 as follows:

19 VALUES (1) the year, including the century (for example, 2008), or **-HUGE (VALUES)** if there is no date
20 available;

21 VALUES (2) the month of the year, or **-HUGE (VALUES)** if there is no date available;

22 VALUES (3) the day of the month, or **-HUGE (VALUES)** if there is no date available;

23 VALUES (4) the time difference with respect to Coordinated Universal Time (UTC) in minutes, or **-HUGE (VAL-**
24 **UES)** if this information is not available;

25 VALUES (5) the hour of the day, in the range of 0 to 23, or **-HUGE (VALUES)** if there is no clock;

26 VALUES (6) the minutes of the hour, in the range 0 to 59, or **-HUGE (VALUES)** if there is no clock;

27 VALUES (7) the seconds of the minute, in the range 0 to 60, or **-HUGE (VALUES)** if there is no clock;

28 VALUES (8) the milliseconds of the second, in the range 0 to 999, or **-HUGE (VALUES)** if there is no clock.

29
30 4 The date, clock, and time zone information might be available on some **images** and not others. If the date, clock,
31 or time zone information is available on more than one **image**, it is processor dependent whether or not those
32 **images** share the same information.

33 5 **Example.** If run in Geneva, Switzerland on April 12, 2008 at 15:27:35.5 with a system configured for the
34 local time zone, this example would have assigned the value 20080412 to **BIG_BEN (1)**, the value 152735.500 to
35 **BIG_BEN (2)**, the value +0100 to **BIG_BEN (3)**, and the value [2008, 4, 12, 60, 15, 27, 35, 500] to **DATE_TIME**.

36 INTEGER DATE_TIME (8)

37 CHARACTER (LEN = 10) BIG_BEN (3)

38 CALL DATE_AND_TIME (BIG_BEN (1), BIG_BEN (2), BIG_BEN (3), DATE_TIME)

NOTE 13.10

These forms are compatible with the representations defined in ISO 8601:2004. UTC is established by the International Bureau of Weights and Measures (BIPM, i.e. Bureau International des Poids et Mesures) and the International Earth Rotation Service (IERS).

1 13.8.55 DBLE (A)

2 1 **Description.** Conversion to double precision real.

3 2 **Class.** [Elemental](#) function.

4 3 **Argument.** A shall be of type integer, real, complex, or a *boz-literal-constant*.

5 4 **Result Characteristics.** Double precision real.

6 5 **Result Value.** The result has the value REAL (A, KIND (0.0D0)).

7 6 **Example.** DBLE (-3) has the value -3.0D0.

8 13.8.56 DIGITS (X)

9 1 **Description.** Significant digits in numeric model.

10 2 **Class.** [Inquiry](#) function.

11 3 **Argument.** X shall be of type integer or real. It may be a scalar or an array.

12 4 **Result Characteristics.** Default integer scalar.

13 5 **Result Value.** The result has the value q if X is of type integer and p if X is of type real, where q and p are as defined in [13.4](#) for the model representing numbers of the same type and kind type parameter as X.

14 6 **Example.** DIGITS (X) has the value 24 for real X whose model is as in Note [13.4](#).

15 13.8.57 DIM (X, Y)

16 1 **Description.** Maximum of X - Y and zero.

17 2 **Class.** [Elemental](#) function.

18 3 **Arguments.**

19 X shall be of type integer or real.

20 Y shall be of the same type and kind type parameter as X.

21 4 **Result Characteristics.** Same as X.

22 5 **Result Value.** The value of the result is the maximum of X - Y and zero.

23 6 **Example.** DIM (-3.0, 2.0) has the value 0.0.

24 13.8.58 DOT_PRODUCT (VECTOR_A, VECTOR_B)

25 1 **Description.** Dot product of two vectors.

26 2 **Class.** [Transformational](#) function.

27 3 **Arguments.**

28 VECTOR_A shall be of [numeric type](#) (integer, real, or complex) or of logical type. It shall be a rank-one array.

29 VECTOR_B shall be of [numeric type](#) if VECTOR_A is of [numeric type](#) or of type logical if VECTOR_A is of
30 type logical. It shall be a rank-one array. It shall be of the same size as VECTOR_A.

31 4 **Result Characteristics.** If the arguments are of [numeric type](#), the type and [kind type parameter](#) of the result
32 are those of the expression VECTOR_A * VECTOR_B determined by the types and kinds of the arguments
33

1 according to 7.1.9.3. If the arguments are of type logical, the result is of type logical with the kind type parameter
2 of the expression VECTOR_A .AND. VECTOR_B according to 7.1.9.3. The result is scalar.

3 5 Result Value.

4 *Case (i):* If VECTOR_A is of type integer or real, the result has the value SUM (VECTOR_A*VECTOR_-
5 B). If the vectors have size zero, the result has the value zero.

6 *Case (ii):* If VECTOR_A is of type complex, the result has the value SUM (CONJG (VECTOR_A)*VECTOR_-
7 B). If the vectors have size zero, the result has the value zero.

8 *Case (iii):* If VECTOR_A is of type logical, the result has the value ANY (VECTOR_A .AND. VECTOR_B).
9 If the vectors have size zero, the result has the value false.

10 6 **Example.** DOT_PRODUCT ([1, 2, 3], [2, 3, 4]) has the value 20.

11 13.8.59 DPROD (X, Y)

12 1 **Description.** Double precision real product.

13 2 **Class.** Elemental function.

14 3 Arguments.

15 X shall be default real.

16 Y shall be default real.

17 4 **Result Characteristics.** Double precision real.

18 5 **Result Value.** The result has a value equal to a processor-dependent approximation to the product of X and
19 Y. DPROD (X, Y) should have the same value as DBLE (X) * DBLE (Y).

20 6 **Example.** DPROD (-3.0, 2.0) has the value -6.0D0.

21 13.8.60 DSHIFTL (I, J, SHIFT)

22 1 **Description.** Combined left shift.

23 2 **Class.** Elemental function.

24 3 Arguments.

25 I shall be of type integer or a *boz-literal-constant*.

26 J shall be of type integer or a *boz-literal-constant*. If both I and J are of type integer, they shall have
27 the same kind type parameter. I and J shall not both be *boz-literal-constants*.

28 SHIFT shall be of type integer. It shall be nonnegative and less than or equal to BIT_SIZE (I) if I is of
29 type integer; otherwise, it shall be less than or equal to BIT_SIZE (J).

30 4 **Result Characteristics.** Same as I if I is of type integer; otherwise, same as J.

31 5 **Result Value.** If either I or J is a *boz-literal-constant*, it is first converted as if by the intrinsic function INT to
32 type integer with the kind type parameter of the other. The rightmost SHIFT bits of the result value are the same
33 as the leftmost bits of J, and the remaining bits of the result value are the same as the rightmost bits of I. This
34 is equal to IOR (SHIFTL (I, SHIFT), SHIFTR (J, BIT_SIZE (J)-SHIFT)). The model for the interpretation of
35 an integer value as a sequence of bits is in 13.3.

36 6 **Examples.** DSHIFTL (1, 2**30, 2) has the value 5 if default integer has 32 bits. DSHIFTL (I, I, SHIFT) has
37 the same result value as ISHFTC (I, SHIFT).

13.8.61 DSHIFTR (I, J, SHIFT)

1 **Description.** Combined right shift.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 I shall be of type integer or a *boz-literal-constant*.

5 J shall be of type integer or a *boz-literal-constant*. If both I and J are of type integer, they shall have
6 the same kind type parameter. I and J shall not both be *boz-literal-constants*.

7 SHIFT shall be of type integer. It shall be nonnegative and less than or equal to BIT_SIZE (I) if I is of
8 type integer; otherwise, it shall be less than or equal to BIT_SIZE (J).

9 **Result Characteristics.** Same as I if I is of type integer; otherwise, same as J.

10 **Result Value.** If either I or J is a *boz-literal-constant*, it is first converted as if by the intrinsic function [INT](#) to
11 type integer with the kind type parameter of the other. The leftmost SHIFT bits of the result value are the same
12 as the rightmost bits of I, and the remaining bits of the result value are the same as the leftmost bits of J. This
13 is equal to IOR (SHIFTL (I, BIT_SIZE (I)–SHIFT), SHIFTR (J, SHIFT)). The model for the interpretation of
14 an integer value as a sequence of bits is in [13.3](#).

15 **Examples.** DSHIFTR (1, 16, 3) has the value $2^{29} + 2$ if default integer has 32 bits. DSHIFTR (I, I, SHIFT) has
16 the same result value as ISHFTC (I,–SHIFT).

13.8.62 EOSHIFT (ARRAY, SHIFT [, BOUNDARY, DIM])

17 **Description.** End-off shift of the elements of an array.

18 **Class.** [Transformational](#) function.

19 **Arguments.**

20 ARRAY shall be an array be of any type.

21 SHIFT shall be of type integer and shall be scalar if ARRAY has [rank](#) one; otherwise, it shall be scalar or
22 of [rank](#) $n - 1$ and of shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$ where $[d_1, d_2, \dots, d_n]$ is the shape
23 of ARRAY.

24 BOUNDARY (optional) shall be of the same type and type parameters as ARRAY and shall be scalar if ARRAY
25 has [rank](#) one; otherwise, it shall be either scalar or of [rank](#) $n - 1$ and of shape $[d_1, d_2, \dots, d_{\text{DIM}-1},$
26 $d_{\text{DIM}+1}, \dots, d_n]$. BOUNDARY is permitted to be absent only for the types in [Table 13.4](#), and in
27 this case it is as if it were present with the scalar value shown, converted if necessary to the kind
28 type parameter value of ARRAY.

Table 13.4: Default BOUNDARY values for EOSHIFT

Type of ARRAY	Value of BOUNDARY
Integer	0
Real	0.0
Complex	(0.0, 0.0)
Logical	.FALSE.
Character (<i>len</i>)	<i>len</i> blanks

29 DIM (optional) shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of ARRAY.
30 If DIM is absent, it is as if it were present with the value 1.

31 **Result Characteristics.** The result has the type, type parameters, and shape of ARRAY.

32 **Result Value.** Element (s_1, s_2, \dots, s_n) of the result has the value ARRAY $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}} + sh,$

1 s_{DIM+1}, \dots, s_n) where sh is SHIFT or SHIFT ($s_1, s_2, \dots, s_{DIM-1}, s_{DIM+1}, \dots, s_n$) provided the inequality
 2 $LBOUND (ARRAY, DIM) \leq s_{DIM} + sh \leq UBOUND (ARRAY, DIM)$ holds and is otherwise BOUNDARY or
 3 BOUNDARY ($s_1, s_2, \dots, s_{DIM-1}, s_{DIM+1}, \dots, s_n$).

4 6 Examples.

5 *Case (i):* If V is the array [1, 2, 3, 4, 5, 6], the effect of shifting V end-off to the left by 3 positions is achieved
 6 by EOSHIFT (V, SHIFT = 3), which has the value [4, 5, 6, 0, 0, 0]; EOSHIFT (V, SHIFT = -2,
 7 BOUNDARY = 99) achieves an end-off shift to the right by 2 positions with the boundary value of
 8 99 and has the value [99, 99, 1, 2, 3, 4].

9 *Case (ii):* The rows of an array of **rank** two may all be shifted by the same amount or by different amounts

10 and the boundary elements can be the same or different. If M is the array $\begin{bmatrix} A & B & C \\ D & E & F \\ G & H & I \end{bmatrix}$, then the

11 value of EOSHIFT (M, SHIFT = -1, BOUNDARY = '*', DIM = 2) is $\begin{bmatrix} * & A & B \\ * & D & E \\ * & G & H \end{bmatrix}$, and the value

12 of EOSHIFT (M, SHIFT = [-1, 1, 0], BOUNDARY = ['*', '/', '?'], DIM = 2) is $\begin{bmatrix} * & A & B \\ E & F & / \\ G & H & I \end{bmatrix}$.

13 13.8.63 EPSILON (X)

14 1 **Description.** Model number that is small compared to 1.

15 2 **Class.** [Inquiry function](#).

16 3 **Argument.** X shall be of type real. It may be a scalar or an array.

17 4 **Result Characteristics.** Scalar of the same type and kind type parameter as X.

18 5 **Result Value.** The result has the value b^{1-p} where b and p are as defined in [13.4](#) for the model representing
 19 numbers of the same type and kind type parameter as X.

20 6 **Example.** EPSILON (X) has the value 2^{-23} for real X whose model is as in Note [13.4](#).

21 13.8.64 ERF (X)

22 1 **Description.** Error function.

23 2 **Class.** [Elemental function](#).

24 3 **Argument.** X shall be of type real.

25 4 **Result Characteristics.** Same as X.

26 5 **Result Value.** The result has a value equal to a processor-dependent approximation to the error function of X,
 27 $\frac{2}{\sqrt{\pi}} \int_0^X \exp(-t^2) dt$.

28 6 **Example.** ERF (1.0) has the value 0.843 (approximately).

29 13.8.65 ERFC (X)

30 1 **Description.** Complementary error function.

31 2 **Class.** [Elemental function](#).

32 3 **Argument.** X shall be of type real.

33 4 **Result Characteristics.** Same as X.

1 5 **Result Value.** The result has a value equal to a processor-dependent approximation to the complementary error
 2 function of X, $1 - \text{ERF}(X)$; this is equivalent to $\frac{2}{\sqrt{\pi}} \int_X^\infty \exp(-t^2) dt$.

3 6 **Example.** `ERFC(1.0)` has the value 0.157 (approximately).

4 13.8.66 `ERFC_SCALED(X)`

5 1 **Description.** Scaled complementary error function.

6 2 **Class.** [Elemental](#) function.

7 3 **Argument.** X shall be of type real.

8 4 **Result Characteristics.** Same as X.

9 5 **Result Value.** The result has a value equal to a processor-dependent approximation to the exponentially-scaled
 10 complementary error function of X, $\exp(X^2) \frac{2}{\sqrt{\pi}} \int_X^\infty \exp(-t^2) dt$.

11 6 **Example.** `ERFC_SCALED(20.0)` has the value 0.02817434874 (approximately).

NOTE 13.11

The complementary error function is asymptotic to $\exp(-X^2)/(X\sqrt{\pi})$. As such it underflows for $X > \approx 9$ when using ISO/IEC/IEEE 60559:2011 single precision arithmetic. The exponentially-scaled complementary error function is asymptotic to $1/(X\sqrt{\pi})$. As such it does not underflow until $X > \text{HUGE}(X)/\sqrt{\pi}$.

12 13.8.67 `EVENT_QUERY(EVENT, COUNT [, STAT])`

13 1 **Description.** Query event count.

14 2 **Class.** Subroutine.

15 3 **Arguments.**

16 `EVENT` shall be an [event variable](#) (13.9.2.9). It shall not be [coindexed](#). It is an [INTENT \(IN\)](#) argument. The
 17 `EVENT` argument is accessed atomically with respect to the execution of [EVENT POST statements](#)
 18 in unordered segments, in exact analogy to [atomic subroutines](#).

19 `COUNT` shall be an integer scalar with a decimal range no smaller than that of default integer. It is an
 20 [INTENT \(OUT\)](#) argument. If no error condition occurs, `COUNT` is assigned the value of the count
 21 of `EVENT`; otherwise, it is assigned the value -1 .

22 `STAT` (optional) shall be a noncoindexed integer scalar with a decimal exponent range of at least four. It is an
 23 [INTENT \(OUT\)](#) argument. If the `STAT` argument is present, it is assigned a processor-dependent
 24 positive value if an error condition occurs; otherwise it is assigned the value zero. If the `STAT`
 25 argument is not present and an error condition occurs, [error termination](#) is initiated.

26 4 **Example.** If `EVENT` is an [event variable](#) for which there have been no successful posts or waits in preceding
 27 segments, and for which there are no posts or waits in an unordered segment, after execution of

28 `CALL EVENT_QUERY (EVENT, COUNT)`

29 the integer variable `COUNT` will have the value zero. If there have been ten successful posts to `EVENT` and two
 30 successful waits without an [UNTIL_COUNT= specifier](#) in preceding segments, and for which there are no posts
 31 or waits in an unordered segment, after execution of

32 `CALL EVENT_QUERY (EVENT, COUNT)`

33 the variable `COUNT` will have the value eight.

NOTE 13.12

Execution of EVENT_QUERY does not imply any synchronization.
--

13.8.68 EXECUTE_COMMAND_LINE (COMMAND [, WAIT, EXITSTAT, CMDSTAT, CMDMSG])

1 **Description.** Execute a command line.

2 **Class.** Subroutine.

3 **Arguments.**

4 COMMAND shall be a default character scalar. It is an **INTENT (IN)** argument. Its value is the command line
5 to be executed. The interpretation is processor dependent.

6 WAIT (optional) shall be a logical scalar. It is an **INTENT (IN)** argument. If WAIT is present with the value
7 false, and the processor supports asynchronous execution of the command, the command is executed
8 asynchronously; otherwise it is executed synchronously.

9 EXITSTAT (optional) shall be a scalar of type integer with a decimal exponent range of at least nine. It is an
10 **INTENT (INOUT)** argument. If the command is executed synchronously, it is assigned the value
11 of the processor-dependent exit status. Otherwise, the value of EXITSTAT is unchanged.

12 CMDSTAT (optional) shall be a scalar of type integer with a decimal exponent range of at least four. It is an
13 **INTENT (OUT)** argument. It is assigned the value -1 if the processor does not support command
14 line execution, a processor-dependent positive value if an error condition occurs, or the value -2
15 if no error condition occurs but WAIT is present with the value false and the processor does not
16 support asynchronous execution. Otherwise it is assigned the value 0.

17 CMDMSG (optional) shall be a default character scalar. It is an **INTENT (INOUT)** argument. If an error condi-
18 tion occurs, it is assigned a processor-dependent explanatory message. Otherwise, it is unchanged.

19 4 If the processor supports command line execution, it shall support synchronous and may support asynchronous
20 execution of the command line.

21 5 When the command is executed synchronously, EXECUTE_COMMAND_LINE returns after the command line
22 has completed execution. Otherwise, EXECUTE_COMMAND_LINE returns without waiting.

23 6 If a condition occurs that would assign a nonzero value to CMDSTAT but the CMDSTAT variable is not present,
24 **error termination** is initiated.

25 13.8.69 EXP (X)

26 1 **Description.** Exponential function.

27 2 **Class.** **Elemental** function.

28 3 **Argument.** X shall be of type real or complex.

29 4 **Result Characteristics.** Same as X.

30 5 **Result Value.** The result has a value equal to a processor-dependent approximation to e^X . If X is of type
31 complex, its imaginary part is regarded as a value in radians.

32 6 **Example.** EXP (1.0) has the value 2.7182818 (approximately).

33 13.8.70 EXPONENT (X)

34 1 **Description.** Exponent of floating-point number.

35 2 **Class.** **Elemental** function.

1 3 **Argument.** X shall be of type real.

2 4 **Result Characteristics.** Default integer.

3 5 **Result Value.** The result has a value equal to the exponent e of the representation for the value of X in the
4 extended real model for the kind of X (13.4), provided X is nonzero and e is within the range for default integers.
5 If X has the value zero, the result has the value zero. If X is an IEEE infinity or NaN, the result has the value
6 HUGE (0).

7 6 **Examples.** EXPONENT (1.0) has the value 1 and EXPONENT (4.1) has the value 3 for reals whose model is
8 as in Note 13.4.

9 13.8.71 EXTENDS_TYPE_OF (A, MOLD)

10 1 **Description.** Dynamic type extension inquiry.

11 2 **Class.** Inquiry function.

12 3 **Arguments.**

13 A shall be an object of extensible declared type or unlimited polymorphic. If it is a polymorphic
14 pointer, it shall not have an undefined association status.

15 MOLD shall be an object of extensible declared type or unlimited polymorphic. If it is a polymorphic
16 pointer, it shall not have an undefined association status.

17 4 **Result Characteristics.** Default logical scalar.

18 5 **Result Value.** If MOLD is unlimited polymorphic and is either a disassociated pointer or unallocated allocatable
19 variable, the result is true; otherwise if A is unlimited polymorphic and is either a disassociated pointer or
20 unallocated allocatable variable, the result is false; otherwise if the dynamic type of A or MOLD is extensible, the
21 result is true if and only if the dynamic type of A is an extension type of the dynamic type of MOLD; otherwise
22 the result is processor dependent.

NOTE 13.13

The dynamic type of a disassociated pointer or unallocated allocatable variable is its declared type.

23 6 **Example.** Given the declarations and assignments

```
24         TYPE T1
25           REAL C
26         END TYPE
27         TYPE, EXTENDS(T1) :: T2
28         END TYPE
29         CLASS(T1), POINTER :: P, Q
30         ALLOCATE (P)
31         ALLOCATE (T2 :: Q)
```

32 the result of EXTENDS_TYPE_OF (P, Q) will be false, and the result of EXTENDS_TYPE_OF (Q, P) will
33 be true.

34 13.8.72 FINDLOC (ARRAY, VALUE, DIM [, MASK, KIND, BACK]) or FINDLOC (ARRAY, VALUE [, MASK, KIND, BACK])

35 1 **Description.** Location(s) of a specified value.

36 2 **Class.** Transformational function.

1 3 **Arguments.**

- 2 ARRAY shall be an array of intrinsic type.
- 3 VALUE shall be scalar and in type conformance with ARRAY, as specified in Table 7.2 for the operator ==
4 or the operator `.EQV.`.
- 5 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the `rank` of ARRAY.
- 6 MASK (optional) shall be of type logical and shall be `conformable` with ARRAY.
- 7 KIND (optional) shall be a scalar integer `constant expression`.
- 8 BACK (optional) shall be a logical scalar.

9 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of
10 KIND; otherwise the kind type parameter is that of default integer type. If DIM does not appear, the result is
11 an array of `rank` one and of size equal to the `rank` of ARRAY; otherwise, the result is of `rank` $n - 1$ and shape
12 $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$, where $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

13 5 **Result Value.**

14 *Case (i):* The result of `FINDLOC (ARRAY, VALUE)` is a rank-one array whose element values are the values
15 of the subscripts of an element of ARRAY whose value matches VALUE. If there is such a value,
16 the i^{th} element value is in the range 1 to e_i , where e_i is the extent of the i^{th} dimension of ARRAY.
17 If no elements match VALUE or ARRAY has size zero, all elements of the result are zero.

18 *Case (ii):* The result of `FINDLOC (ARRAY, VALUE, MASK = MASK)` is a rank-one array whose element
19 values are the values of the subscripts of an element of ARRAY, corresponding to a true element
20 of MASK, whose value matches VALUE. If there is such a value, the i^{th} element value is in the
21 range 1 to e_i , where e_i is the extent of the i^{th} dimension of ARRAY. If no elements match VALUE,
22 ARRAY has size zero, or every element of MASK has the value false, all elements of the result are
23 zero.

24 *Case (iii):* If ARRAY has `rank` one, the result of
25 `FINDLOC (ARRAY, VALUE, DIM=DIM [, MASK = MASK])` is a scalar whose value is equal to
26 that of the first element of `FINDLOC (ARRAY, VALUE [, MASK = MASK])`. Otherwise, the value
27 of element $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of the result is equal to `FINDLOC (ARRAY (s1,
28 s2, ..., sDIM-1, :, sDIM+1, ..., sn), VALUE, DIM=1 [, MASK = MASK (s1, s2, ..., sDIM-1, :,
29 sDIM+1, ..., sn))`.

30 6 If both ARRAY and VALUE are of type logical, the comparison is performed with the `.EQV.` operator; otherwise,
31 the comparison is performed with the `==` operator. If the value of the comparison is true, that element of ARRAY
32 matches VALUE.

33 7 If DIM is not present, more than one element matches VALUE, and BACK is absent or present with the value
34 false, the value returned indicates the first such element, taken in array element order. If DIM is not present and
35 BACK is present with the value true, the value returned indicates the last such element, taken in array element
36 order.

37 8 **Examples.**

38 *Case (i):* The value of `FINDLOC ([2, 6, 4, 6], VALUE=6)` is [2], and the value of `FINDLOC ([2, 6, 4, 6],
39 VALUE=6, BACK=.TRUE.)` is [4].

40 *Case (ii):* If A has the value $\begin{bmatrix} 0 & -5 & 7 & 7 \\ 3 & 4 & -1 & 2 \\ 1 & 5 & 6 & 7 \end{bmatrix}$, and M has the value $\begin{bmatrix} T & T & F & T \\ T & T & F & T \\ T & T & F & T \end{bmatrix}$, `FINDLOC (A, 7,
41 MASK = M)` has the value [1, 4] and `FINDLOC (A, 7, MASK = M, BACK = .TRUE.)` has the
42 value [3, 4]. This is independent of the declared lower bounds for A.

43 *Case (iii):* The value of `FINDLOC ([2, 6, 4], VALUE=6, DIM=1)` is 2. If B has the value
44 $\begin{bmatrix} 1 & 2 & -9 \\ 2 & 2 & 6 \end{bmatrix}$, `FINDLOC (B, VALUE=2, DIM=1)` has the value [2, 1, 0] and `FINDLOC (B,
45 VALUE=2, DIM=2)` has the value [2, 1]. This is independent of the declared lower bounds for B.

13.8.73 FLOOR (A [, KIND])

1 **Description.** Greatest integer less than or equal to A.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 A shall be of type real.

5 KIND (optional) shall be a scalar integer [constant expression](#).

6 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise, the kind type parameter is that of default integer type.

7 **Result Value.** The result has a value equal to the greatest integer less than or equal to A.

8 **Examples.** FLOOR (3.7) has the value 3. FLOOR (-3.7) has the value -4.

13.8.74 FRACTION (X)

1 **Description.** Fractional part of number.

2 **Class.** [Elemental](#) function.

3 **Argument.** X shall be of type real.

4 **Result Characteristics.** Same as X.

5 **Result Value.** The result has the value $X \times b^{-e}$, where b and e are as defined in [13.4](#) for the representation of X in the extended real model for the kind of X. If X has the value zero, the result is zero. If X is an [IEEE NaN](#), the result is that [NaN](#). If X is an IEEE infinity, the result is an [IEEE NaN](#).

6 **Example.** FRACTION (3.0) has the value 0.75 for reals whose model is as in Note [13.4](#).

13.8.75 GAMMA (X)

1 **Description.** Gamma function.

2 **Class.** [Elemental](#) function.

3 **Argument.** X shall be of type real. Its value shall not be a negative integer or zero.

4 **Result Characteristics.** Same as X.

5 **Result Value.** The result has a value equal to a processor-dependent approximation to the gamma function of X,

$$\Gamma(X) = \begin{cases} \int_0^{\infty} t^{X-1} \exp(-t) dt & X > 0 \\ \int_0^{\infty} t^{X-1} \left(\exp(-t) - \sum_{k=0}^n \frac{(-t)^k}{k!} \right) dt & -n - 1 < X < -n, n \text{ an integer } \geq 0 \end{cases}$$

6 **Example.** GAMMA (1.0) has the value 1.000 (approximately).

13.8.76 GET_COMMAND ([COMMAND, LENGTH, STATUS, ERRMSG])

1 **Description.** Get program invocation command.

2 **Class.** Subroutine.

3 **Arguments.**

1 COMMAND (optional) shall be a default character scalar. It is an **INTENT (OUT)** argument. It is assigned
 2 the entire command by which the program was invoked. If the command cannot be determined,
 3 COMMAND is assigned all blanks.

4 LENGTH (optional) shall be a scalar of type integer with a decimal exponent range of at least four. It is an
 5 **INTENT (OUT)** argument. It is assigned the significant length of the command by which the
 6 program was invoked. The significant length may include trailing blanks if the processor allows
 7 commands with significant trailing blanks. This length does not consider any possible truncation or
 8 padding in assigning the command to the COMMAND argument; in fact the COMMAND argument
 9 need not even be present. If the command length cannot be determined, a length of 0 is assigned.

10 STATUS (optional) shall be a scalar of type integer with a decimal exponent range of at least four. It is an
 11 **INTENT (OUT)** argument. It is assigned the value -1 if the COMMAND argument is present and
 12 has a length less than the significant length of the command. It is assigned a processor-dependent
 13 positive value if the command retrieval fails. Otherwise it is assigned the value 0.

14 ERRMSG (optional) shall be a default character scalar. It is an **INTENT (INOUT)** argument. It is assigned a
 15 processor-dependent explanatory message if the command retrieval fails. Otherwise, it is unchanged.

- 16 4 **Example.** If the program below is invoked with the command “example” on a processor that supports command
 17 retrieval, it will display “Hello example”.

```

18     PROGRAM hello
19         CHARACTER(:), ALLOCATABLE :: cmd
20         INTEGER :: cmdlen
21         CALL GET_COMMAND(LENGTH=cmdlen)
22         IF (cmdlen>0) THEN
23             ALLOCATE(CHARACTER(cmdlen) :: cmd)
24             CALL GET_COMMAND(cmd)
25             PRINT *, 'Hello ', cmd
26         END IF
27     END PROGRAM
  
```

28 13.8.77 GET_COMMAND_ARGUMENT (NUMBER [, VALUE, LENGTH, STATUS, ERRMSG])

29 1 **Description.** Get program invocation argument.

30 2 **Class.** Subroutine.

31 3 **Arguments.**

32 NUMBER shall be an integer scalar. It is an **INTENT (IN)** argument that specifies the number of the command
 33 argument that the other arguments give information about.

34 Command argument 0 always exists, and is the command name by which the program was invoked
 35 if the processor has such a concept; otherwise, the value of command argument 0 is processor
 36 dependent. The remaining command arguments are numbered consecutively from 1 to the argument
 37 count in an order determined by the processor.

38 VALUE (optional) shall be a default character scalar. It is an **INTENT (OUT)** argument. If the command
 39 argument specified by NUMBER exists, its value is assigned to VALUE; otherwise, VALUE is
 40 assigned all blanks.

41 LENGTH (optional) shall be a scalar of type integer with a decimal exponent range of at least four. It is an
 42 **INTENT (OUT)** argument. If the command argument specified by NUMBER exists, its significant
 43 length is assigned to LENGTH; otherwise, LENGTH is assigned the value zero. It is processor
 44 dependent whether the significant length includes trailing blanks. This length does not consider any

1 possible truncation or padding in assigning the command argument value to the VALUE argument;
 2 in fact the VALUE argument need not even be present.

3 STATUS (optional) shall be a scalar of type integer with a decimal exponent range of at least four. It is an
 4 **INTENT (OUT)** argument. If NUMBER is less than zero or greater than the argument count that
 5 would be returned by the intrinsic function **COMMAND_ARGUMENT_COUNT**, or command
 6 retrieval fails, STATUS is assigned a processor-dependent positive value. Otherwise, if VALUE is
 7 present and has a length less than the significant length of the specified command argument, it is
 8 assigned the value -1 . Otherwise it is assigned the value 0.

9 ERRMSG (optional) shall be a default character scalar. It is an **INTENT (INOUT)** argument. It is assigned
 10 a processor-dependent explanatory message if the optional argument STATUS is, or would be if
 11 present, assigned a positive value. Otherwise, it is unchanged.

12 4 **Example.** On a processor that supports command arguments, the following program displays the arguments of
 13 the command by which it was invoked.

```

14 PROGRAM show_arguments
15     INTEGER :: i
16     CHARACTER :: command*32, arg*128
17     CALL get_command_argument(0, command)
18     WRITE (*,*) "Command name is: ", command
19     DO i = 1, command_argument_count()
20         CALL get_command_argument(i, arg)
21         WRITE (*,*) "Argument ", i, " is ", arg
22     END DO
23 END PROGRAM show_arguments
  
```

24 13.8.78 GET_ENVIRONMENT_VARIABLE (NAME [, VALUE, LENGTH, STATUS, TRIM_NAME, ERRMSG])

25 1 **Description.** Get environment variable.

26 2 **Class.** Subroutine.

27 3 **Arguments.**

28 NAME shall be a default character scalar. It is an **INTENT (IN)** argument. The interpretation of case is
 29 processor dependent.

30 VALUE (optional) shall be a default character scalar. It is an **INTENT (OUT)** argument. It is assigned the value
 31 of the environment variable specified by NAME. VALUE is assigned all blanks if the environment
 32 variable does not exist or does not have a value or if the processor does not support environment
 33 variables.

34 LENGTH (optional) shall be a scalar of type integer with a decimal exponent range of at least four. It is an
 35 **INTENT (OUT)** argument. If the specified environment variable exists and has a value, LENGTH
 36 is set to the length of that value. Otherwise LENGTH is set to 0.

37 STATUS (optional) shall be a scalar of type integer with a decimal exponent range of at least four. It is an
 38 **INTENT (OUT)** argument. If the environment variable exists and either has no value, its value is
 39 successfully assigned to VALUE, or the VALUE argument is not present, STATUS is set to zero.
 40 STATUS is set to -1 if the VALUE argument is present and has a length less than the significant
 41 length of the environment variable. It is assigned the value 1 if the specified environment variable
 42 does not exist, or 2 if the processor does not support environment variables. Processor-dependent
 43 values greater than 2 may be assigned for other error conditions.

44 TRIM_NAME (optional) shall be a logical scalar. It is an **INTENT (IN)** argument. If TRIM_NAME is present
 45 with the value false then trailing blanks in NAME are considered significant if the processor sup-

1 ports trailing blanks in environment variable names. Otherwise trailing blanks in NAME are not
2 considered part of the environment variable's name.

3 ERRMSG (optional) shall be a default character scalar. It is an **INTENT (INOUT)** argument. It is assigned
4 a processor-dependent explanatory message if the optional argument STATUS is, or would be if
5 present, assigned a positive value. Otherwise, it is unchanged.

6 4 It is processor dependent whether an environment variable that exists on an **image** also exists on another **image**,
7 and if it does exist on both **images**, whether the values are the same or different.

8 5 **Example.** If the value of the environment variable DATAFILE is datafile.dat, executing the statement sequence
9 below will assign the value 'datafile.dat' to FILENAME.

```
10 CHARACTER(:),ALLOCATABLE :: FILENAME
11 INTEGER :: NAMELEN
12 CALL GET_ENVIRONMENT_VARIABLE ("DATAFILE", LENGTH=NAMELEN)
13 IF (LENGTH>0) THEN
14     ALLOCATE(CHARACTER(LENGTH) :: FILENAME)
15     CALL GET_ENVIRONMENT_VARIABLE("DATAFILE", FILENAME)
16 END IF
```

17 13.8.79 HUGE (X)

18 1 **Description.** Largest model number.

19 2 **Class.** **Inquiry function.**

20 3 **Argument.** X shall be of type integer or real. It may be a scalar or an array.

21 4 **Result Characteristics.** Scalar of the same type and kind type parameter as X.

22 5 **Result Value.** The result has the value $r^q - 1$ if X is of type integer and $(1 - b^{-p})b^{e_{\max}}$ if X is of type real,
23 where r , q , b , p , and e_{\max} are as defined in 13.4 for the model representing numbers of the same type and kind
24 type parameter as X.

25 6 **Example.** HUGE (X) has the value $(1 - 2^{-24}) \times 2^{127}$ for real X whose model is as in Note 13.4.

26 13.8.80 HYPOT (X, Y)

27 1 **Description.** Euclidean distance function.

28 2 **Class.** **Elemental function.**

29 3 **Arguments.**

30 X shall be of type real.

31 Y shall be of type real with the same kind type parameter as X.

32 4 **Result Characteristics.** Same as X.

33 5 **Result Value.** The result has a value equal to a processor-dependent approximation to the Euclidean distance,
34 $\sqrt{X^2 + Y^2}$, without undue overflow or underflow.

35 6 **Example.** HYPOT (3.0, 4.0) has the value 5.0 (approximately).

13.8.81 IACHAR (C [, KIND])

1 **Description.** ASCII code value for character.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 C shall be of type character and of length one.

5 KIND (optional) shall be a scalar integer [constant expression](#).

6 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise, the kind type parameter is that of default integer type.

7 **Result Value.** If C is in the [collating sequence](#) defined by the codes specified in ISO/IEC 646:1991 (International Reference Version), the result is the position of C in that sequence; it is nonnegative and less than or equal to 127. The value of the result is processor dependent if C is not in the [ASCII collating sequence](#). The results are consistent with the LGE, LGT, LLE, and LLT comparison functions. For example, if LLE (C, D) is true, IACHAR (C) <= IACHAR (D) is true where C and D are any two characters representable by the processor.

8 **Example.** IACHAR ('X') has the value 88.

13.8.82 IALL (ARRAY, DIM [, MASK]) or IALL (ARRAY [, MASK])

1 **Description.** Array reduced by IAND function.

2 **Class.** [Transformational](#) function.

3 **Arguments.**

4 ARRAY shall be an array of type integer.

5 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of ARRAY.

6 MASK (optional) shall be of type logical and shall be [conformable](#) with ARRAY.

7 **Result Characteristics.** The result is of the same type and kind type parameter as ARRAY. It is scalar if DIM does not appear or if ARRAY has [rank](#) one; otherwise, the result is an array of [rank](#) $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$ where $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

8 **Result Value.**

9 *Case (i):* If ARRAY has size zero the result value is equal to NOT (INT (0, KIND (ARRAY))). Otherwise, the result of IALL (ARRAY) has a value equal to the bitwise AND of all the elements of ARRAY.

10 *Case (ii):* The result of IALL (ARRAY, MASK=MASK) has a value equal to IALL (PACK (ARRAY, MASK)).

11 *Case (iii):* The result of IALL (ARRAY, DIM=DIM [, MASK=MASK]) has a value equal to that of IALL (ARRAY [, MASK=MASK]) if ARRAY has [rank](#) one. Otherwise, the value of element $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of the result is equal to IALL (ARRAY $(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$ [, MASK = MASK $(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$]).

12 **Examples.** IALL ([14, 13, 11]) has the value 8. IALL ([14, 13, 11], MASK=[.true., .false., .true]) has the value 10.

13.8.83 IAND (I, J)

1 **Description.** Bitwise AND.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

1 I shall be of type integer or a *boz-literal-constant*.
 2 J shall be of type integer or a *boz-literal-constant*. If both I and J are of type integer, they shall have
 3 the same kind type parameter. I and J shall not both be *boz-literal-constants*.

4 **4 Result Characteristics.** Same as I if I is of type integer; otherwise, same as J.

5 **5 Result Value.** If either I or J is a *boz-literal-constant*, it is first converted as if by the intrinsic function INT to
 6 type integer with the kind type parameter of the other. The result has the value obtained by combining I and J
 7 bit-by-bit according to the following truth table:

I	J	IAND (I, J)
1	1	1
1	0	0
0	1	0
0	0	0

8 6 The model for the interpretation of an integer value as a sequence of bits is in 13.3.

9 7 **Example.** IAND (1, 3) has the value 1.

10 **13.8.84 IANY (ARRAY, DIM [, MASK]) or IANY (ARRAY [, MASK])**

11 1 **Description.** Reduce array with bitwise OR operation.

12 2 **Class.** Transformational function.

13 3 **Arguments.**

14 ARRAY shall be of type integer. It shall be an array.

15 DIM shall be an integer scalar with a value in the range $1 \leq DIM \leq n$, where n is the rank of ARRAY.

16 MASK (optional) shall be of type logical and shall be conformable with ARRAY.

17 4 **Result Characteristics.** The result is of the same type and kind type parameter as ARRAY. It is scalar if
 18 DIM does not appear or if ARRAY has rank one; otherwise, the result is an array of rank $n - 1$ and shape $[d_1,$
 19 $d_2, \dots, d_{DIM-1}, d_{DIM+1}, \dots, d_n]$ where $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

20 5 **Result Value.**

21 *Case (i):* The result of IANY (ARRAY) is the bitwise OR of all the elements of ARRAY. If ARRAY has size
 22 zero the result value is equal to zero.

23 *Case (ii):* The result of IANY (ARRAY, MASK=MASK) has a value equal to
 24 IANY (PACK (ARRAY, MASK)).

25 *Case (iii):* The result of IANY (ARRAY, DIM=DIM [, MASK=MASK]) has a value equal to that of IANY (AR-
 26 RAY [, MASK=MASK]) if ARRAY has rank one. Otherwise, the value of element $(s_1, s_2, \dots,$
 27 $s_{DIM-1}, s_{DIM+1}, \dots, s_n)$ of the result is equal to IANY (ARRAY $(s_1, s_2, \dots, s_{DIM-1}, :, s_{DIM+1},$
 28 $\dots, s_n)$ [, MASK = MASK $(s_1, s_2, \dots, s_{DIM-1}, :, s_{DIM+1}, \dots, s_n)$]).

29 6 **Examples.** IANY ([14, 13, 8]) has the value 15. IANY ([14, 13, 8], MASK=[.true., .false., .true]) has the value
 30 14.

31 **13.8.85 IBCLR (I, POS)**

32 1 **Description.** I with bit POS replaced by zero.

33 2 **Class.** Elemental function.

34 3 **Arguments.**

1 I shall be of type integer.
2 POS shall be of type integer. It shall be nonnegative and less than BIT_SIZE (I).

3 4 **Result Characteristics.** Same as I.

4 5 **Result Value.** The result has the value of the sequence of bits of I, except that bit POS is zero. The model for
5 the interpretation of an integer value as a sequence of bits is in 13.3.

6 6 **Examples.** IBCLR (14, 1) has the value 12. If V has the value [1, 2, 3, 4], the value of IBCLR (POS = V, I = 31)
7 is [29, 27, 23, 15].

8 13.8.86 IBITS (I, POS, LEN)

9 1 **Description.** Specified sequence of bits.

10 2 **Class.** Elemental function.

11 3 **Arguments.**

12 I shall be of type integer.
13 POS shall be of type integer. It shall be nonnegative and POS + LEN shall be less than or equal to
14 BIT_SIZE (I).
15 LEN shall be of type integer and nonnegative.

16 4 **Result Characteristics.** Same as I.

17 5 **Result Value.** The result has the value of the sequence of LEN bits in I beginning at bit POS, right-adjusted
18 and with all other bits zero. The model for the interpretation of an integer value as a sequence of bits is in 13.3.

19 6 **Example.** IBITS (14, 1, 3) has the value 7.

20 13.8.87 IBSET (I, POS)

21 1 **Description.** I with bit POS replaced by one.

22 2 **Class.** Elemental function.

23 3 **Arguments.**

24 I shall be of type integer.
25 POS shall be of type integer. It shall be nonnegative and less than BIT_SIZE (I).

26 4 **Result Characteristics.** Same as I.

27 5 **Result Value.** The result has the value of the sequence of bits of I, except that bit POS is one. The model for
28 the interpretation of an integer value as a sequence of bits is in 13.3.

29 6 **Examples.** IBSET (12, 1) has the value 14. If V has the value [1, 2, 3, 4], the value of IBSET (POS = V, I = 0)
30 is [2, 4, 8, 16].

31 13.8.88 ICHAR (C [, KIND])

32 1 **Description.** Code value for character.

33 2 **Class.** Elemental function.

34 3 **Arguments.**

35 C shall be of type character and of length one. Its value shall be that of a character capable of
36 representation in the processor.

1 KIND (optional) shall be a scalar integer [constant expression](#).

2 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of
3 KIND; otherwise, the kind type parameter is that of default integer type.

4 5 **Result Value.** The result is the position of C in the processor [collating sequence](#) associated with the kind type
5 parameter of C; it is nonnegative and less than n , where n is the number of characters in the [collating sequence](#).
6 The [kind type parameter](#) of the result shall specify an integer kind that is capable of representing n . For any char-
7 acters C and D capable of representation in the processor, $C \leq D$ is true if and only if $\text{ICHAR}(C) \leq \text{ICHAR}(D)$
8 is true and $C == D$ is true if and only if $\text{ICHAR}(C) == \text{ICHAR}(D)$ is true.

9 6 **Example.** $\text{ICHAR}('X')$ has the value 88 on a processor using the [ASCII collating sequence](#) for default characters.

10 13.8.89 IEOR (I, J)

11 1 **Description.** Bitwise exclusive OR.

12 2 **Class.** [Elemental function](#).

13 3 **Arguments.**

14 I shall be of type integer or a [boz-literal-constant](#).

15 J shall be of type integer or a [boz-literal-constant](#). If both I and J are of type integer, they shall have
16 the same kind type parameter. I and J shall not both be [boz-literal-constants](#).

17 4 **Result Characteristics.** Same as I if I is of type integer; otherwise, same as J.

18 5 **Result Value.** If either I or J is a [boz-literal-constant](#), it is first converted as if by the intrinsic function [INT](#) to
19 type integer with the kind type parameter of the other. The result has the value obtained by combining I and J
20 bit-by-bit according to the following truth table:

I	J	IEOR (I, J)
1	1	0
1	0	1
0	1	1
0	0	0

21 6 The model for the interpretation of an integer value as a sequence of bits is in [13.3](#).

22 7 **Example.** $\text{IEOR}(1, 3)$ has the value 2.

23 13.8.90 IMAGE_INDEX (COARRAY, SUB)

24 1 **Description.** [Image index](#) from [cosubscripts](#).

25 2 **Class.** [Inquiry function](#).

26 3 **Arguments.**

27 COARRAY shall be a [coarray](#) of any type.

28 SUB shall be a rank-one integer array of size equal to the [corank](#) of COARRAY.

29 4 **Result Characteristics.** Default integer scalar.

30 5 **Result Value.** If the value of SUB is a valid sequence of [cosubscripts](#) for COARRAY, the result is the [index](#) of
31 the corresponding [image](#). Otherwise, the result is zero.

32 6 **Examples.** If A and B are declared as $A [0:*$] and $B (10, 20) [10, 0:9, 0:*$] respectively, $\text{IMAGE_INDEX}(A, [0])$

1 has the value 1 and IMAGE_INDEX (B, [3, 1, 2]) has the value 213 (on any [image](#)).

2 13.8.91 INDEX (STRING, SUBSTRING [, BACK, KIND])

3 1 **Description.** Character string search.

4 2 **Class.** Elemental function.

5 3 **Arguments.**

6 STRING shall be of type character.

7 SUBSTRING shall be of type character with the same [kind type parameter](#) as STRING.

8 BACK (optional) shall be of type logical.

9 KIND (optional) shall be a scalar integer [constant expression](#).

10 4 **Result Characteristics.** Integer. If KIND is present, the [kind type parameter](#) is that specified by the value of
11 KIND; otherwise the [kind type parameter](#) is that of default integer type.

12 5 **Result Value.**

13 *Case (i):* If $\text{STRING \% LEN} < \text{SUBSTRING \% LEN}$, the result has the value zero.

14 *Case (ii):* Otherwise, if there is an integer I in the range $1 \leq I \leq \text{STRING \% LEN} - \text{SUBSTRING \% LEN} + 1$, such that $\text{STRING}(I : I + \text{SUBSTRING \% LEN} - 1)$ is equal to SUBSTRING, the result has
15 the value of the smallest such I if BACK is absent or present with the value false, and the greatest
16 such I if BACK is present with the value true.

17 *Case (iii):* Otherwise, the result has the value zero.

19 6 **Examples.** INDEX ('FORTRAN', 'R') has the value 3.

20 INDEX ('FORTRAN', 'R', BACK = .TRUE.) has the value 5.

21 13.8.92 INT (A [, KIND])

22 1 **Description.** Conversion to integer type.

23 2 **Class.** [Elemental](#) function.

24 3 **Arguments.**

25 A shall be of type integer, real, or complex, or a [boz-literal-constant](#).

26 KIND (optional) shall be a scalar integer [constant expression](#).

27 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of
28 KIND; otherwise, the kind type parameter is that of default integer type.

29 5 **Result Value.**

30 *Case (i):* If A is of type integer, $\text{INT}(A) = A$.

31 *Case (ii):* If A is of type real, there are two cases: if $|A| < 1$, INT (A) has the value 0; if $|A| \geq 1$, INT (A)
32 is the integer whose magnitude is the largest integer that does not exceed the magnitude of A and
33 whose sign is the same as the sign of A.

34 *Case (iii):* If A is of type complex, $\text{INT}(A) = \text{INT}(\text{REAL}(A, \text{KIND}(A)))$.

35 *Case (iv):* If A is a [boz-literal-constant](#), the value of the result is the value whose bit sequence according to the
36 model in [13.3](#) is the same as that of A as modified by padding or truncation according to [13.3.3](#).
37 The interpretation of a bit sequence whose most significant bit is 1 is processor dependent.

38 6 **Example.** INT (-3.7) has the value -3.

1 **13.8.93 IOR (I, J)**

2 1 **Description.** Bitwise inclusive OR.

3 2 **Class.** [Elemental](#) function.

4 3 **Arguments.**

5 I shall be of type integer or a *boz-literal-constant*.

6 J shall be of type integer or a *boz-literal-constant*. If both I and J are of type integer, they shall have
7 the same kind type parameter. I and J shall not both be *boz-literal-constants*.

8 4 **Result Characteristics.** Same as I if I is of type integer; otherwise, same as J.

9 5 **Result Characteristics.** Same as I.

10 6 **Result Value.** If either I or J is a *boz-literal-constant*, it is first converted as if by the intrinsic function [INT](#) to
11 type integer with the kind type parameter of the other. The result has the value obtained by combining I and J
12 bit-by-bit according to the following truth table:

I	J	IOR (I, J)
1	1	1
1	0	1
0	1	1
0	0	0

13 7 The model for the interpretation of an integer value as a sequence of bits is in [13.3](#).

14 8 **Example.** IOR (5, 3) has the value 7.

15 **13.8.94 IPARITY (ARRAY, DIM [, MASK]) or IPARITY (ARRAY [, MASK])**

16 1 **Description.** Array reduced by IEOR function.

17 2 **Class.** [Transformational](#) function.

18 3 **Arguments.**

19 ARRAY shall be of type integer. It shall be an array.

20 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of ARRAY.

21 MASK (optional) shall be of type logical and shall be [conformable](#) with ARRAY.

22 4 **Result Characteristics.** The result is of the same type and kind type parameter as ARRAY. It is scalar if
23 DIM does not appear; otherwise, the result has [rank](#) $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$ where
24 $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

25 5 **Result Value.**

26 *Case (i):* The result of IPARITY (ARRAY) has a value equal to the bitwise exclusive OR of all the elements
27 of ARRAY. If ARRAY has size zero the result has the value zero.

28 *Case (ii):* The result of IPARITY (ARRAY, MASK=MASK) has a value equal to that of IPARITY (PACK
29 (ARRAY, MASK)).

30 *Case (iii):* The result of IPARITY (ARRAY, DIM=DIM [, MASK=MASK]) has a value equal to that of
31 IPARITY (ARRAY [, MASK=MASK]) if ARRAY has [rank](#) one. Otherwise, the value of element
32 $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of the result is equal to IPARITY (ARRAY $(s_1, s_2, \dots,$
33 $s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$ [, MASK = MASK $(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$]).

34 6 **Examples.** IPARITY ([14, 13, 8]) has the value 11. IPARITY ([14, 13, 8], MASK=[.true., .false., .true]) has the

1 value 6.

2 **13.8.95 ISHFT (I, SHIFT)**

3 1 **Description.** Logical shift.

4 2 **Class.** [Elemental](#) function.

5 3 **Arguments.**

6 I shall be of type integer.

7 SHIFT shall be of type integer. The absolute value of SHIFT shall be less than or equal to BIT_SIZE (I).

8 4 **Result Characteristics.** Same as I.

9 5 **Result Value.** The result has the value obtained by shifting the bits of I by SHIFT positions. If SHIFT is
10 positive, the shift is to the left; if SHIFT is negative, the shift is to the right; if SHIFT is zero, no shift is
11 performed. Bits shifted out from the left or from the right, as appropriate, are lost. Zeros are shifted in from the
12 opposite end. The model for the interpretation of an integer value as a sequence of bits is in [13.3](#).

13 6 **Example.** ISHFT (3, 1) has the value 6.

14 **13.8.96 ISHFTC (I, SHIFT [, SIZE])**

15 1 **Description.** Circular shift of the rightmost bits.

16 2 **Class.** [Elemental](#) function.

17 3 **Arguments.**

18 I shall be of type integer.

19 SHIFT shall be of type integer. The absolute value of SHIFT shall be less than or equal to SIZE.

20 SIZE (optional) shall be of type integer. The value of SIZE shall be positive and shall not exceed BIT_SIZE (I).

21 If SIZE is absent, it is as if it were present with the value of BIT_SIZE (I).

22 4 **Result Characteristics.** Same as I.

23 5 **Result Value.** The result has the value obtained by shifting the SIZE rightmost bits of I circularly by SHIFT
24 positions. If SHIFT is positive, the shift is to the left; if SHIFT is negative, the shift is to the right; and if SHIFT
25 is zero, no shift is performed. No bits are lost. The unshifted bits are unaltered. The model for the interpretation
26 of an integer value as a sequence of bits is in [13.3](#).

27 6 **Example.** ISHFTC (3, 2, 3) has the value 5.

28 **13.8.97 IS_CONTIGUOUS (ARRAY)**

29 1 **Description.** Array contiguity test ([5.5.7](#)).

30 2 **Class.** [Inquiry function](#).

31 3 **Argument.** ARRAY may be of any type. It shall be [assumed-rank](#) or an array. If it is a pointer it shall be
32 associated.

33 4 **Result Characteristics.** Default logical scalar.

34 5 **Result Value.** The result has the value true if ARRAY has rank zero or is [contiguous](#), and false otherwise.

35 6 **Example.** After the [pointer assignment](#) AP => TARGET (1:10:2), IS_CONTIGUOUS (AP) has the value
36 false.

13.8.98 IS_IOSTAT_END (I)

1 **Description.** IOSTAT value test for end of file.

2 **Class.** [Elemental](#) function.

3 **Argument.** I shall be of type integer.

4 **Result Characteristics.** Default logical.

5 **Result Value.** The result has the value true if and only if I is a value for the *scalar-int-variable* in an [IOSTAT=specifier](#) (9.11.5) that would indicate an end-of-file condition.

13.8.99 IS_IOSTAT_EOR (I)

1 **Description.** IOSTAT value test for end of record.

2 **Class.** [Elemental](#) function.

3 **Argument.** I shall be of type integer.

4 **Result Characteristics.** Default logical.

5 **Result Value.** The result has the value true if and only if I is a value for the *scalar-int-variable* in an [IOSTAT=specifier](#) (9.11.5) that would indicate an end-of-record condition.

13.8.100 KIND (X)

1 **Description.** Value of the kind type parameter of X.

2 **Class.** [Inquiry function](#).

3 **Argument.** X may be of any intrinsic type. It may be a scalar or an array.

4 **Result Characteristics.** Default integer scalar.

5 **Result Value.** The result has a value equal to the kind type parameter value of X.

6 **Example.** KIND (0.0) has the kind type parameter value of default real.

13.8.101 LBOUND (ARRAY [, DIM, KIND])

1 **Description.** Lower bound(s).

2 **Class.** [Inquiry function](#).

3 **Arguments.**

ARRAY shall be [assumed-rank](#) or an array. It shall not be an unallocated [allocatable](#) variable or a pointer that is not associated.

DIM (optional) shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of ARRAY. The corresponding [actual argument](#) shall not be an optional dummy argument, a disassociated pointer, or an unallocated allocatable.

KIND (optional) shall be a scalar integer [constant expression](#).

4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise the kind type parameter is that of default integer type. The result is scalar if DIM is present; otherwise, the result is an array of [rank](#) one and size n , where n is the [rank](#) of ARRAY.

5 **Result Value.**

- 1 *Case (i):* If DIM is present, ARRAY is a **whole array**, and either ARRAY is an **assumed-size array** of rank
 2 DIM or dimension DIM of ARRAY has nonzero extent, the result has a value equal to the lower
 3 bound for subscript DIM of ARRAY. Otherwise, if DIM is present, the result value is 1.
- 4 *Case (ii):* LBOUND (ARRAY) has a value whose i^{th} element is equal to LBOUND (ARRAY, i), for $i = 1, 2,$
 5 \dots, n , where n is the **rank** of ARRAY. LBOUND (ARRAY, KIND=KIND) has a value whose i^{th}
 6 element is equal to LBOUND (ARRAY, i , KIND), for $i = 1, 2, \dots, n$, where n is the **rank** of
 7 ARRAY.

NOTE 13.14

If ARRAY is **assumed-rank** and has rank zero, DIM cannot be present since it cannot satisfy the requirement $1 \leq \text{DIM} \leq 0$.

- 8 6 **Examples.** If A is declared by the statement
 9 7 REAL A (2:3, 7:10)
 10 8 then LBOUND (A) is [2, 7] and LBOUND (A, DIM=2) is 7.

13.8.102 LCOBOUND (COARRAY [, DIM, KIND])

- 12 1 **Description.** Lower **cobound(s)** of a **coarray**.
- 13 2 **Class.** **Inquiry function**.
- 14 3 **Arguments.**
 15 COARRAY shall be a **coarray** and may be of any type. It may be a scalar or an array. If it is **allocatable** it
 16 shall be allocated.
 17 DIM (optional) shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the **corank**
 18 of COARRAY. The corresponding **actual argument** shall not be an optional dummy argument, a
 19 disassociated pointer, or an unallocated allocatable.
 20 KIND (optional) shall be a scalar integer **constant expression**.
- 21 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of
 22 KIND; otherwise, the kind type parameter is that of default integer type. The result is scalar if DIM is present;
 23 otherwise, the result is an array of **rank** one and size n , where n is the **corank** of COARRAY.
- 24 5 **Result Value.**
 25 *Case (i):* If DIM is present, the result has a value equal to the lower **cobound** for **codimension** DIM of
 26 COARRAY.
 27 *Case (ii):* If DIM is absent, the result has a value whose i^{th} element is equal to the lower **cobound** for **codi-**
 28 **mension** i of COARRAY, for $i = 1, 2, \dots, n$, where n is the **corank** of COARRAY.
- 29 6 **Examples.** If A is allocated by the statement ALLOCATE (A [2:3, 7:*) then LCOBOUND (A) is [2, 7] and
 30 LCOBOUND (A, DIM=2) is 7.

13.8.103 LEADZ (I)

- 32 1 **Description.** Number of leading zero bits.
- 33 2 **Class.** **Elemental function**.
- 34 3 **Argument.** I shall be of type integer.
- 35 4 **Result Characteristics.** Default integer.
- 36 5 **Result Value.** If all of the bits of I are zero, the result has the value BIT_SIZE (I). Otherwise, the result has
 37 the value BIT_SIZE (I) $- 1 - k$, where k is the position of the leftmost 1 bit in I. The model for the interpretation

1 of an integer value as a sequence of bits is in 13.3.

2 6 **Examples.** LEADZ (1) has the value 31 if BIT_SIZE (1) has the value 32.

3 13.8.104 LEN (STRING [, KIND])

4 1 **Description.** Length of a character entity.

5 2 **Class.** Inquiry function.

6 3 **Arguments.**

7 STRING shall be of type character. If it is an unallocated allocatable variable or a pointer that is not
8 associated, its length type parameter shall not be deferred.

9 KIND (optional) shall be a scalar integer constant expression.

10 4 **Result Characteristics.** Integer scalar. If KIND is present, the kind type parameter is that specified by the
11 value of KIND; otherwise the kind type parameter is that of default integer type.

12 5 **Result Value.** The result has a value equal to the number of characters in STRING if it is scalar or in an
13 element of STRING if it is an array.

14 6 **Example.** If C is declared by the statement

15 7 CHARACTER (11) C (100)

16 8 LEN (C) has the value 11.

17 13.8.105 LEN_TRIM (STRING [, KIND])

18 1 **Description.** Length without trailing blanks.

19 2 **Class.** Elemental function.

20 3 **Arguments.**

21 STRING shall be of type character.

22 KIND (optional) shall be a scalar integer constant expression.

23 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of
24 KIND; otherwise the kind type parameter is that of default integer type.

25 5 **Result Value.** The result has a value equal to the number of characters remaining after any trailing blanks in
26 STRING are removed. If the argument contains no nonblank characters, the result is zero.

27 6 **Examples.** LEN_TRIM (' A B ') has the value 4 and LEN_TRIM (' ') has the value 0.

28 13.8.106 LGE (STRING_A, STRING_B)

29 1 **Description.** ASCII greater than or equal.

30 2 **Class.** Elemental function.

31 3 **Arguments.**

32 STRING_A shall be default character or ASCII character.

33 STRING_B shall be of type character with the same kind type parameter as STRING_A.

34 4 **Result Characteristics.** Default logical.

35 5 **Result Value.** If the strings are of unequal length, the comparison is made as if the shorter string were extended

1 on the right with blanks to the length of the longer string. If either string contains a character not in the [ASCII](#)
 2 [character](#) set, the result is processor dependent. The result is true if the strings are equal or if STRING_A follows
 3 STRING_B in the [ASCII collating sequence](#); otherwise, the result is false.

NOTE 13.15

The result is true if both STRING_A and STRING_B are of zero length.

4 6 **Example.** LGE ('ONE', 'TWO') has the value false.

13.8.107 LGT (STRING_A, STRING_B)

6 1 **Description.** ASCII greater than.

7 2 **Class.** [Elemental](#) function.

8 3 **Arguments.**

9 STRING_A shall be default character or [ASCII character](#).

10 STRING_B shall be of type character with the same kind type parameter as STRING_A.

11 4 **Result Characteristics.** Default logical.

12 5 **Result Value.** If the strings are of unequal length, the comparison is made as if the shorter string were extended
 13 on the right with blanks to the length of the longer string. If either string contains a character not in the [ASCII](#)
 14 [character](#) set, the result is processor dependent. The result is true if STRING_A follows STRING_B in the
 15 [ASCII collating sequence](#); otherwise, the result is false.

NOTE 13.16

The result is false if both STRING_A and STRING_B are of zero length.

16 6 **Example.** LGT ('ONE', 'TWO') has the value false.

13.8.108 LLE (STRING_A, STRING_B)

18 1 **Description.** ASCII less than or equal.

19 2 **Class.** [Elemental](#) function.

20 3 **Arguments.**

21 STRING_A shall be default character or [ASCII character](#).

22 STRING_B shall be of type character with the same kind type parameter as STRING_A.

23 4 **Result Characteristics.** Default logical.

24 5 **Result Value.** If the strings are of unequal length, the comparison is made as if the shorter string were extended
 25 on the right with blanks to the length of the longer string. If either string contains a character not in the [ASCII](#)
 26 [character](#) set, the result is processor dependent. The result is true if the strings are equal or if STRING_A
 27 precedes STRING_B in the [ASCII collating sequence](#); otherwise, the result is false.

NOTE 13.17

The result is true if both STRING_A and STRING_B are of zero length.

28 6 **Example.** LLE ('ONE', 'TWO') has the value true.

13.8.109 LLT (STRING_A, STRING_B)

1 **Description.** ASCII less than.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 STRING_A shall be default character or [ASCII character](#).

5 STRING_B shall be of type character with the same kind type parameter as STRING_A.

6 **Result Characteristics.** Default logical.

7 **Result Value.** If the strings are of unequal length, the comparison is made as if the shorter string were extended on the right with blanks to the length of the longer string. If either string contains a character not in the [ASCII character](#) set, the result is processor dependent. The result is true if STRING_A precedes STRING_B in the [ASCII collating sequence](#); otherwise, the result is false.

NOTE 13.18

The result is false if both STRING_A and STRING_B are of zero length.

8 **Example.** LLT ('ONE', 'TWO') has the value true.

13.8.110 LOG (X)

9 **Description.** Natural logarithm.

10 **Class.** [Elemental](#) function.

11 **Argument.** X shall be of type real or complex. If X is real, its value shall be greater than zero. If X is complex, its value shall not be zero.

12 **Result Characteristics.** Same as X.

13 **Result Value.** The result has a value equal to a processor-dependent approximation to $\log_e X$. A result of type complex is the principal value with imaginary part ω in the range $-\pi \leq \omega \leq \pi$. If the real part of X is less than zero and the imaginary part of X is zero, then the imaginary part of the result is approximately π if the imaginary part of X is positive real zero or the processor does not distinguish between positive and negative real zero, and approximately $-\pi$ if the imaginary part of X is negative real zero.

14 **Example.** LOG (10.0) has the value 2.3025851 (approximately).

13.8.111 LOG_GAMMA (X)

15 **Description.** Logarithm of the absolute value of the gamma function.

16 **Class.** [Elemental](#) function.

17 **Argument.** X shall be of type real. Its value shall not be a negative integer or zero.

18 **Result Characteristics.** Same as X.

19 **Result Value.** The result has a value equal to a processor-dependent approximation to the natural logarithm of the absolute value of the gamma function of X.

20 **Example.** LOG_GAMMA (3.0) has the value 0.693 (approximately).

13.8.112 LOG10 (X)

1 **Description.** Common logarithm.

2 **Class.** [Elemental](#) function.

3 **Argument.** X shall be of type real. The value of X shall be greater than zero.

4 **Result Characteristics.** Same as X.

5 **Result Value.** The result has a value equal to a processor-dependent approximation to $\log_{10}X$.

6 **Example.** LOG10 (10.0) has the value 1.0 (approximately).

13.8.113 LOGICAL (L [, KIND])

1 **Description.** Conversion between kinds of logical.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

L shall be of type logical.

KIND (optional) shall be a scalar integer [constant expression](#).

4 **Result Characteristics.** Logical. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise, the kind type parameter is that of default logical.

5 **Result Value.** The value is that of L.

6 **Example.** LOGICAL (L [.OR.](#) [.NOT.](#) L) has the value true and is default logical, regardless of the kind type parameter of the logical variable L.

13.8.114 MASKL (I [, KIND])

1 **Description.** Left justified mask.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

I shall be of type integer. It shall be nonnegative and less than or equal to the number of bits z of the model integer defined for bit manipulation contexts in [13.3](#) for the kind of the result.

KIND (optional) shall be a scalar integer [constant expression](#).

4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise, the kind type parameter is that of default integer type.

5 **Result Value.** The result value has its leftmost I bits set to 1 and the remaining bits set to 0. The model for the interpretation of an integer value as a sequence of bits is in [13.3](#).

6 **Example.** MASKL (3) has the value SHIFTL (7, BIT_SIZE (0) – 3).

13.8.115 MASKR (I [, KIND])

1 **Description.** Right justified mask.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

1 I shall be of type integer. It shall be nonnegative and less than or equal to the number of bits z of
 2 the model integer defined for bit manipulation contexts in 13.3 for the kind of the result.

3 KIND (optional) shall be a scalar integer [constant expression](#).

4 **4 Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of
 5 KIND; otherwise, the kind type parameter is that of default integer type.

6 **5 Result Value.** The result value has its rightmost I bits set to 1 and the remaining bits set to 0. The model for
 7 the interpretation of an integer value as a sequence of bits is in 13.3.

8 **6 Example.** MASKR (3) has the value 7.

9 **13.8.116 MATMUL (MATRIX_A, MATRIX_B)**

10 **1 Description.** Matrix multiplication.

11 **2 Class.** [Transformational function](#).

12 **3 Arguments.**

13 MATRIX_A shall be a rank-one or rank-two array of [numeric type](#) or logical type.

14 MATRIX_B shall be of [numeric type](#) if MATRIX_A is of [numeric type](#) and of logical type if MATRIX_A is of
 15 logical type. It shall be an array of [rank](#) one or two. MATRIX_A and MATRIX_B shall not both
 16 have [rank](#) one. The size of the first (or only) dimension of MATRIX_B shall equal the size of the
 17 last (or only) dimension of MATRIX_A.

18 **4 Result Characteristics.** If the arguments are of [numeric type](#), the type and kind type parameter of the result
 19 are determined by the types of the arguments as specified in 7.1.9.3 for the * operator. If the arguments are of
 20 type logical, the result is of type logical with the kind type parameter of the arguments as specified in 7.1.9.3 for
 21 the .AND. operator. The shape of the result depends on the shapes of the arguments as follows:

22 *Case (i):* If MATRIX_A has shape $[n, m]$ and MATRIX_B has shape $[m, k]$, the result has shape $[n, k]$.

23 *Case (ii):* If MATRIX_A has shape $[m]$ and MATRIX_B has shape $[m, k]$, the result has shape $[k]$.

24 *Case (iii):* If MATRIX_A has shape $[n, m]$ and MATRIX_B has shape $[m]$, the result has shape $[n]$.

25 **5 Result Value.**

26 *Case (i):* Element (i, j) of the result has the value SUM (MATRIX_A $(i, :)$ * MATRIX_B $(:, j)$) if the
 27 arguments are of [numeric type](#) and has the value ANY (MATRIX_A $(i, :)$.AND. MATRIX_B $(:, j)$) if the
 28 arguments are of logical type.

29 *Case (ii):* Element (j) of the result has the value SUM (MATRIX_A $(:)$ * MATRIX_B $(:, j)$) if the arguments
 30 are of [numeric type](#) and has the value ANY (MATRIX_A $(:)$.AND. MATRIX_B $(:, j)$) if the
 31 arguments are of logical type.

32 *Case (iii):* Element (i) of the result has the value SUM (MATRIX_A $(i, :)$ * MATRIX_B $(:)$) if the arguments
 33 are of [numeric type](#) and has the value ANY (MATRIX_A $(i, :)$.AND. MATRIX_B $(:)$) if the
 34 arguments are of logical type.

35 **6 Examples.** Let A and B be the matrices $\begin{bmatrix} 1 & 2 & 3 \\ 2 & 3 & 4 \end{bmatrix}$ and $\begin{bmatrix} 1 & 2 \\ 2 & 3 \\ 3 & 4 \end{bmatrix}$; let X and Y be the vectors $[1, 2]$ and
 36 $[1, 2, 3]$.

37 *Case (i):* The result of MATMUL (A, B) is the matrix-matrix product AB with the value $\begin{bmatrix} 14 & 20 \\ 20 & 29 \end{bmatrix}$.

38 *Case (ii):* The result of MATMUL (X, A) is the vector-matrix product XA with the value $[5, 8, 11]$.

39 *Case (iii):* The result of MATMUL (A, Y) is the matrix-vector product AY with the value $[14, 20]$.

13.8.117 MAX (A1, A2 [, A3, ...])

1 **Description.** Maximum value.

2 **Class.** [Elemental](#) function.

3 **Arguments.** The arguments shall all have the same type which shall be integer, real, or character and they shall all have the same kind type parameter.

4 **Result Characteristics.** The type and kind type parameter of the result are the same as those of the arguments. For arguments of character type, the length of the result is the length of the longest argument.

5 **Result Value.** The value of the result is that of the largest argument. For arguments of character type, the result is the value that would be selected by application of intrinsic relational operators; that is, the [collating sequence](#) for characters with the kind type parameter of the arguments is applied. If the selected argument is shorter than the longest argument, the result is extended with blanks on the right to the length of the longest argument.

6 **Examples.** MAX (-9.0, 7.0, 2.0) has the value 7.0, MAX ('Z', 'BB') has the value 'Z ', and MAX (['A', 'Z'], ['BB', 'Y ']) has the value ['BB', 'Z '].

13.8.118 MAXEXPONENT (X)

1 **Description.** Maximum exponent of a real model.

2 **Class.** [Inquiry](#) function.

3 **Argument.** X shall be of type real. It may be a scalar or an array.

4 **Result Characteristics.** Default integer scalar.

5 **Result Value.** The result has the value e_{\max} , as defined in [13.4](#) for the model representing numbers of the same type and kind type parameter as X.

6 **Example.** MAXEXPONENT (X) has the value 127 for real X whose model is as in Note [13.4](#).

13.8.119 MAXLOC (ARRAY, DIM [, MASK, KIND, BACK]) or MAXLOC (ARRAY [, MASK, KIND, BACK])

1 **Description.** Location(s) of maximum value.

2 **Class.** [Transformational](#) function.

3 **Arguments.**

ARRAY shall be an array of type integer, real, or character.

DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of ARRAY.

MASK (optional) shall be of type logical and shall be [conformable](#) with ARRAY.

KIND (optional) shall be a scalar integer [constant expression](#).

BACK (optional) shall be a logical scalar.

4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise the kind type parameter is that of default integer type. If DIM does not appear, the result is an array of [rank](#) one and of size equal to the [rank](#) of ARRAY; otherwise, the result is of [rank](#) $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$, where $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

5 **Result Value.**

Case (i): If DIM does not appear and MASK is absent, the result is a rank-one array whose element values are the values of the subscripts of an element of ARRAY whose value equals the maximum value of

all of the elements of ARRAY. The i^{th} subscript returned lies in the range 1 to e_i , where e_i is the extent of the i^{th} dimension of ARRAY. If ARRAY has size zero, all elements of the result are zero.

Case (ii): If DIM does not appear and MASK is present, the result is a rank-one array whose element values are the values of the subscripts of an element of ARRAY, corresponding to a true element of MASK, whose value equals the maximum value of all such elements of ARRAY. The i^{th} subscript returned lies in the range 1 to e_i , where e_i is the extent of the i^{th} dimension of ARRAY. If ARRAY has size zero or every element of MASK has the value false, all elements of the result are zero.

Case (iii): If ARRAY has [rank](#) one and DIM is specified, the result has a value equal to that of the first element of MAXLOC (ARRAY [, MASK = MASK, KIND = KIND, BACK = BACK]). Otherwise, if DIM is specified, the value of element $(s_1, s_2, \dots, s_{DIM-1}, s_{DIM+1}, \dots, s_n)$ of the result is equal to

$$\text{MAXLOC}(\text{ARRAY}(s_1, s_2, \dots, s_{DIM-1}, :, s_{DIM+1}, \dots, s_n), \\ \text{DIM} = 1 \\ [, \text{MASK} = \text{MASK}(s_1, s_2, \dots, s_{DIM-1}, :, s_{DIM+1}, \dots, s_n), \\ \text{KIND} = \text{KIND}, \\ \text{BACK} = \text{BACK}]).$$

If only one element has the maximum value, that element's subscripts are returned. Otherwise, if more than one element has the maximum value and BACK is absent or present with the value false, the element whose subscripts are returned is the first such element, taken in array element order. If BACK is present with the value true, the element whose subscripts are returned is the last such element, taken in array element order.

If ARRAY has type character, the result is the value that would be selected by application of intrinsic relational operators; that is, the [collating sequence](#) for characters with the kind type parameter of the arguments is applied.

8 Examples.

Case (i): The value of MAXLOC ([2, 6, 4, 6]) is [2] and the value of MAXLOC ([2, 6, 4, 6], BACK=.TRUE.) is [4].

Case (ii): If A has the value $\begin{bmatrix} 0 & -5 & 8 & -3 \\ 3 & 4 & -1 & 2 \\ 1 & 5 & 6 & -4 \end{bmatrix}$, MAXLOC (A, MASK = A < 6) has the value [3, 2]. This is independent of the declared lower bounds for A.

Case (iii): The value of MAXLOC ([5, -9, 3], DIM = 1) is 1. If B has the value $\begin{bmatrix} 1 & 3 & -9 \\ 2 & 2 & 6 \end{bmatrix}$, MAXLOC (B, DIM = 1) is [2, 1, 2] and MAXLOC (B, DIM = 2) is [2, 3]. This is independent of the declared lower bounds for B.

13.8.120 MAXVAL (ARRAY, DIM [, MASK]) or MAXVAL (ARRAY [, MASK])

1 **Description.** Maximum value(s) of array.

2 **Class.** [Transformational function](#).

3 **Arguments.**

ARRAY shall be an array of type integer, real, or character.

DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of ARRAY.

MASK (optional) shall be of type logical and shall be [conformable](#) with ARRAY.

4 **Result Characteristics.** The result is of the same type and type parameters as ARRAY. It is scalar if DIM does not appear; otherwise, the result has [rank](#) $n - 1$ and shape $[d_1, d_2, \dots, d_{DIM-1}, d_{DIM+1}, \dots, d_n]$ where $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

5 **Result Value.**

Case (i): The result of MAXVAL (ARRAY) has a value equal to the maximum value of all the elements of ARRAY if the size of ARRAY is not zero. If ARRAY has size zero and type integer or real, the result has the value of the negative number of the largest magnitude supported by the processor for numbers of the type and kind type parameter of ARRAY. If ARRAY has size zero and type

1 character, the result has the value of a string of characters of length LEN (ARRAY), with each
2 character equal to CHAR (0, KIND (ARRAY)).

3 *Case (ii):* The result of MAXVAL (ARRAY, MASK = MASK) has a value equal to that of MAXVAL (PACK
4 (ARRAY, MASK)).

5 *Case (iii):* The result of MAXVAL (ARRAY, DIM = DIM [,MASK = MASK]) has a value equal to that of
6 MAXVAL (ARRAY [,MASK = MASK]) if ARRAY has **rank** one. Otherwise, the value of element
7 ($s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n$) of the result is equal to

8
$$\text{MAXVAL} (\text{ARRAY} (s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$$

9
$$[, \text{MASK} = \text{MASK} (s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)]).$$

10 6 If ARRAY is of type character, the result is the value that would be selected by application of intrinsic relational
11 operators; that is, the **collating sequence** for characters with the kind type parameter of the arguments is applied.

12 7 Examples.

13 *Case (i):* The value of MAXVAL ([1, 2, 3]) is 3.

14 *Case (ii):* MAXVAL (C, MASK = C < 0.0) is the maximum of the negative elements of C.

15 *Case (iii):* If B is the array $\begin{bmatrix} 1 & 3 & 5 \\ 2 & 7 & 6 \end{bmatrix}$, MAXVAL (B, DIM = 1) is [2, 7, 6] and MAXVAL (B, DIM = 2) is
16 [5, 7].

17 13.8.121 MERGE (TSOURCE, FSOURCE, MASK)

18 1 **Description.** Expression value selection.

19 2 **Class.** **Elemental** function.

20 3 Arguments.

21 TSOURCE may be of any type.

22 FSOURCE shall be of the same type and type parameters as TSOURCE.

23 MASK shall be of type logical.

24 4 **Result Characteristics.** Same as TSOURCE.

25 5 **Result Value.** The result is TSOURCE if MASK is true and FSOURCE otherwise.

26 6 **Examples.** If TSOURCE is the array $\begin{bmatrix} 1 & 6 & 5 \\ 2 & 4 & 6 \end{bmatrix}$, FSOURCE is the array $\begin{bmatrix} 0 & 3 & 2 \\ 7 & 4 & 8 \end{bmatrix}$ and MASK is the
27 array $\begin{bmatrix} \text{T} & \cdot & \text{T} \\ \cdot & \cdot & \text{T} \end{bmatrix}$, where “T” represents true and “.” represents false, then MERGE (TSOURCE, FSOURCE,
28 MASK) is $\begin{bmatrix} 1 & 3 & 5 \\ 7 & 4 & 6 \end{bmatrix}$. The value of MERGE (1.0, 0.0, K > 0) is 1.0 for K = 5 and 0.0 for K = -2.

29 13.8.122 MERGE_BITS (I, J, MASK)

30 1 **Description.** Merge of bits under mask.

31 2 **Class.** **Elemental** function.

32 3 Arguments.

33 I shall be of type integer or a *boz-literal-constant*.

34 J shall be of type integer or a *boz-literal-constant*. If both I and J are of type integer they shall have
35 the same kind type parameter. I and J shall not both be *boz-literal-constants*.

36 MASK shall be of type integer or a *boz-literal-constant*. If MASK is of type integer, it shall have the same
37 kind type parameter as each other argument of type integer.

1 4 **Result Characteristics.** Same as I if I is of type integer; otherwise, same as J.

2 5 **Result Value.** If any argument is a *boz-literal-constant*, it is first converted as if by the intrinsic function
3 [INT](#) to the type and kind type parameter of the result. The result has the value of IOR (IAND (I, MASK),
4 IAND (J, NOT (MASK))).

5 6 **Example.** MERGE_BITS (13, 18, 22) has the value 4.

6 13.8.123 MIN (A1, A2 [, A3, ...])

7 1 **Description.** Minimum value.

8 2 **Class.** [Elemental function](#).

9 3 **Arguments.** The arguments shall all be of the same type which shall be integer, real, or character and they
10 shall all have the same kind type parameter.

11 4 **Result Characteristics.** The type and kind type parameter of the result are the same as those of the arguments.
12 For arguments of character type, the length of the result is the length of the longest argument.

13 5 **Result Value.** The value of the result is that of the smallest argument. For arguments of character type, the
14 result is the value that would be selected by application of intrinsic relational operators; that is, the [collating](#)
15 [sequence](#) for characters with the kind type parameter of the arguments is applied. If the selected argument is
16 shorter than the longest argument, the result is extended with blanks on the right to the length of the longest
17 argument.

18 6 **Examples.** MIN (-9.0, 7.0, 2.0) has the value -9.0, MIN ('A', 'YY') has the value 'A ', and
19 MIN (['Z', 'A'], ['YY', 'B ']) has the value ['YY', 'A '].

20 13.8.124 MINEXPONENT (X)

21 1 **Description.** Minimum exponent of a real model.

22 2 **Class.** [Inquiry function](#).

23 3 **Argument.** X shall be of type real. It may be a scalar or an array.

24 4 **Result Characteristics.** Default integer scalar.

25 5 **Result Value.** The result has the value e_{\min} , as defined in [13.4](#) for the model representing numbers of the same
26 type and kind type parameter as X.

27 6 **Example.** MINEXPONENT (X) has the value -126 for real X whose model is as in Note [13.4](#).

28 13.8.125 MINLOC (ARRAY, DIM [, MASK, KIND, BACK]) or MINLOC (ARRAY [, MASK, KIND, BACK])

29 1 **Description.** Location(s) of minimum value.

30 2 **Class.** [Transformational function](#).

31 3 **Arguments.**

32 ARRAY shall be an array of type integer, real, or character.

33 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of ARRAY.

34 MASK (optional) shall be of type logical and shall be [conformable](#) with ARRAY.

35 KIND (optional) shall be a scalar integer [constant expression](#).

36 BACK (optional) shall be a logical scalar.

1 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of
 2 KIND; otherwise the kind type parameter is that of default integer type. If DIM does not appear, the result is
 3 an array of [rank](#) one and of size equal to the [rank](#) of ARRAY; otherwise, the result is of [rank](#) $n - 1$ and shape
 4 $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$, where $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

5 5 **Result Value.**

6 *Case (i):* If DIM does not appear and MASK is absent the result is a rank-one array whose element values
 7 are the values of the subscripts of an element of ARRAY whose value equals the minimum value
 8 of all the elements of ARRAY. The i^{th} subscript returned lies in the range 1 to e_i , where e_i is the
 9 extent of the i^{th} dimension of ARRAY. If ARRAY has size zero, all elements of the result are zero.

10 *Case (ii):* If DIM does not appear and MASK is present, the result is a rank-one array whose element values
 11 are the values of the subscripts of an element of ARRAY, corresponding to a true element of MASK,
 12 whose value equals the minimum value of all such elements of ARRAY. The i^{th} subscript returned
 13 lies in the range 1 to e_i , where e_i is the extent of the i^{th} dimension of ARRAY. If ARRAY has size
 14 zero or every element of MASK has the value false, all elements of the result are zero.

15 *Case (iii):* If ARRAY has [rank](#) one and DIM is specified, the result has a value equal to that of the first element
 16 of MINLOC (ARRAY [, MASK = MASK, KIND = KIND, BACK = BACK]). Otherwise, if DIM
 17 is specified, the value of element $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of the result is equal to
 MINLOC (ARRAY $(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$,

DIM = 1

[, MASK = MASK $(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$,

KIND = KIND,

BACK = BACK]).

18 6 If only one element has the minimum value, that element's subscripts are returned. Otherwise, if more than one
 19 element has the minimum value and BACK is absent or present with the value false, the element whose subscripts
 20 are returned is the first such element, taken in array element order. If BACK is present with the value true, the
 21 element whose subscripts are returned is the last such element, taken in array element order.
 22

23 7 If ARRAY is of type character, the result is the value that would be selected by application of intrinsic relational
 24 operators; that is, the [collating sequence](#) for characters with the kind type parameter of the arguments is applied.

25 8 **Examples.**

26 *Case (i):* The value of MINLOC ([4, 3, 6, 3]) is [2] and the value of MINLOC ([4, 3, 6, 3], BACK = [.TRUE.](#))
 27 is [4].

28 *Case (ii):* If A has the value $\begin{bmatrix} 0 & -5 & 8 & -3 \\ 3 & 4 & -1 & 2 \\ 1 & 5 & 6 & -4 \end{bmatrix}$, MINLOC (A, MASK = A > -4) has the value [1, 4].
 29 This is independent of the declared lower bounds for A.

30 *Case (iii):* The value of MINLOC ([5, -9, 3], DIM = 1) is 2. If B has the value $\begin{bmatrix} 1 & 3 & -9 \\ 2 & 2 & 6 \end{bmatrix}$, MIN-
 31 LOC (B, DIM = 1) is [1, 2, 1] and MINLOC (B, DIM = 2) is [3, 1]. This is independent of
 32 the declared lower bounds for B.

33 13.8.126 MINVAL (ARRAY, DIM [, MASK]) or MINVAL (ARRAY [, MASK])

34 1 **Description.** Minimum value(s) of array.

35 2 **Class.** [Transformational function](#).

36 3 **Arguments.**

37 ARRAY shall be an array of type integer, real, or character.

38 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of ARRAY.

39 MASK (optional) shall be of type logical and shall be [conformable](#) with ARRAY.

40 4 **Result Characteristics.** The result is of the same type and type parameters as ARRAY. It is scalar if DIM

1 does not appear; otherwise, the result has **rank** $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$ where
 2 $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

3 5 Result Value.

4 *Case (i):* The result of MINVAL (ARRAY) has a value equal to the minimum value of all the elements of
 5 ARRAY if the size of ARRAY is not zero. If ARRAY has size zero and type integer or real, the
 6 result has the value of the positive number of the largest magnitude supported by the processor
 7 for numbers of the type and kind type parameter of ARRAY. If ARRAY has size zero and type
 8 character, the result has the value of a string of characters of length LEN (ARRAY), with each
 9 character equal to CHAR ($n - 1$, KIND (ARRAY)), where n is the number of characters in the
 10 **collating sequence** for characters with the kind type parameter of ARRAY.

11 *Case (ii):* The result of MINVAL (ARRAY, MASK = MASK) has a value equal to that of MINVAL (PACK
 12 (ARRAY, MASK)).

13 *Case (iii):* The result of MINVAL (ARRAY, DIM = DIM [, MASK = MASK]) has a value equal to that of
 14 MINVAL (ARRAY [, MASK = MASK]) if ARRAY has **rank** one. Otherwise, the value of element
 15 $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of the result is equal to

16
$$\text{MINVAL} (\text{ARRAY} (s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$$

 17
$$[, \text{MASK} = \text{MASK} (s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)]).$$

18 6 If ARRAY is of type character, the result is the value that would be selected by application of intrinsic relational
 19 operators; that is, the **collating sequence** for characters with the kind type parameter of the arguments is applied.

20 7 Examples.

21 *Case (i):* The value of MINVAL ([1, 2, 3]) is 1.

22 *Case (ii):* MINVAL (C, MASK = C > 0.0) is the minimum of the positive elements of C.

23 *Case (iii):* If B is the array $\begin{bmatrix} 1 & 3 & 5 \\ 2 & 4 & 6 \end{bmatrix}$, MINVAL (B, DIM = 1) is [1, 3, 5] and MINVAL (B, DIM = 2) is
 24 [1, 2].

25 13.8.127 MOD (A, P)

26 1 **Description.** Remainder function.

27 2 **Class.** **Elemental** function.

28 3 Arguments.

29 A shall be of type integer or real.

30 P shall be of the same type and kind type parameter as A. P shall not be zero.

31 4 **Result Characteristics.** Same as A.

32 5 **Result Value.** The value of the result is $A - \text{INT} (A/P) * P$.

33 6 **Examples.** MOD (3.0, 2.0) has the value 1.0 (approximately). MOD (8, 5) has the value 3. MOD (-8, 5) has
 34 the value -3. MOD (8, -5) has the value 3. MOD (-8, -5) has the value -3.

35 13.8.128 MODULO (A, P)

36 1 **Description.** Modulo function.

37 2 **Class.** **Elemental** function.

38 3 Arguments.

39 A shall be of type integer or real.

40 P shall be of the same type and kind type parameter as A. P shall not be zero.

1 4 **Result Characteristics.** Same as A.

2 5 **Result Value.**

3 *Case (i):* A is of type integer. MODULO (A, P) has the value R such that $A = Q \times P + R$, where Q is an
4 integer, the inequalities $0 \leq R < P$ hold if $P > 0$, and $P < R \leq 0$ hold if $P < 0$.

5 *Case (ii):* A is of type real. The value of the result is $A - \text{FLOOR}(A / P) * P$.

6 6 **Examples.** MODULO (8, 5) has the value 3. MODULO (-8, 5) has the value 2. MODULO (8, -5) has the
7 value -2. MODULO (-8, -5) has the value -3.

8 13.8.129 MOVE_ALLOC (FROM, TO)

9 1 **Description.** Move an allocation.

10 2 **Class.** Pure subroutine.

11 3 **Arguments.**

12 FROM may be of any type, rank, and corank. It shall be allocatable. It is an INTENT (INOUT) argument.

13 TO shall be type compatible (4.3.2.3) with FROM and have the same rank and corank. It shall be alloc-
14 atable. It shall be polymorphic if FROM is polymorphic. It is an INTENT (OUT) argument. Each
15 nondeferred parameter of the declared type of TO shall have the same value as the corresponding
16 parameter of the declared type of FROM.

17 4 The allocation status of TO becomes unallocated if FROM is unallocated on entry to MOVE_ALLOC. Otherwise,
18 TO becomes allocated with dynamic type, type parameters, bounds, cobounds, and value identical to those that
19 FROM had on entry to MOVE_ALLOC.

20 5 If TO has the TARGET attribute, any pointer associated with FROM on entry to MOVE_ALLOC becomes
21 correspondingly associated with TO. If TO does not have the TARGET attribute, the pointer association status
22 of any pointer associated with FROM on entry becomes undefined.

23 6 The allocation status of FROM becomes unallocated.

24 7 When a reference to MOVE_ALLOC is executed for which the FROM argument is a coarray, there is an implicit
25 synchronization of all images. On each image, execution of the segment (8.5.2) following the CALL statement is
26 delayed until all other images have executed the same statement the same number of times.

27 8 **Example.** The example below demonstrates reallocation of GRID to twice its previous size, with its previous
28 contents evenly distributed over the new elements so that intermediate points can be inserted.

```
29     REAL,ALLOCATABLE :: GRID(:),TEMPGRID(:)
30     ...
31     ALLOCATE(GRID(-N:N))          ! initial allocation of GRID
32     ...
33     ALLOCATE(TEMPGRID(-2*N:2*N)) ! allocate bigger grid
34     TEMPGRID(:,2)=GRID ! distribute values to new locations
35     CALL MOVE_ALLOC(TO=GRID,FROM=TEMPGRID)
```

36 The old grid is deallocated because TO is INTENT (OUT), and GRID then takes over the new grid allocation.

NOTE 13.19

It is expected that the implementation of allocatable objects will typically involve descriptors to locate the allocated storage; MOVE_ALLOC could then be implemented by transferring the contents of the descriptor for FROM to the descriptor for TO and clearing the descriptor for FROM.

13.8.130 MVBITS (FROM, FROMPOS, LEN, TO, TOPOS)

1 **Description.** Copy a sequence of bits.

2 **Class.** [Elemental](#) subroutine.

3 **Arguments.**

4 FROM shall be of type integer. It is an [INTENT \(IN\)](#) argument.

5 FROMPOS shall be of type integer and nonnegative. It is an [INTENT \(IN\)](#) argument. FROMPOS + LEN shall be less than or equal to [BIT_SIZE](#) (FROM). The model for the interpretation of an integer value as a sequence of bits is in [13.3](#).

6 LEN shall be of type integer and nonnegative. It is an [INTENT \(IN\)](#) argument.

7 TO shall be a variable of the same type and kind type parameter value as FROM and may be associated with FROM ([12.8.3](#)). It is an [INTENT \(INOUT\)](#) argument. TO is defined by copying the sequence of bits of length LEN, starting at position FROMPOS of FROM to position TOPOS of TO. No other bits of TO are altered. On return, the LEN bits of TO starting at TOPOS are equal to the value that the LEN bits of FROM starting at FROMPOS had on entry. The model for the interpretation of an integer value as a sequence of bits is in [13.3](#).

8 TOPOS shall be of type integer and nonnegative. It is an [INTENT \(IN\)](#) argument. TOPOS + LEN shall be less than or equal to [BIT_SIZE](#) (TO).

9 **Example.** If TO has the initial value 6, its value after the statement CALL MVBITS (7, 2, 2, TO, 0) is 5.

13.8.131 NEAREST (X, S)

1 **Description.** Adjacent machine number.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 X shall be of type real.

5 S shall be of type real and not equal to zero.

6 **Result Characteristics.** Same as X.

7 **Result Value.** The result has a value equal to the machine-representable number distinct from X and nearest to it in the direction of the ∞ with the same sign as S.

8 **Example.** NEAREST (3.0, 2.0) has the value $3 + 2^{-22}$ on a machine whose representation is that of the model in Note [13.4](#).

NOTE 13.20

Unlike other floating-point manipulation functions, NEAREST operates on machine-representable numbers rather than model numbers. On many systems there are machine-representable numbers that lie between adjacent model numbers.

13.8.132 NEW_LINE (A)

1 **Description.** Newline character.

2 **Class.** [Inquiry function](#).

3 **Argument.** A shall be of type character. It may be a scalar or an array.

4 **Result Characteristics.** Character scalar of length one with the same kind type parameter as A.

1 5 **Result Value.**

2 *Case (i):* If A is default character and the character in position 10 of the [ASCII collating sequence](#) is representable in the default character set, then the result is [ACHAR](#) (10).

4 *Case (ii):* If A is [ASCII character](#) or [ISO 10646 character](#), then the result is [CHAR](#) (10, [KIND](#) (A)).

5 *Case (iii):* Otherwise, the result is a processor-dependent character that represents a newline in output to files connected for formatted stream output if there is such a character.

7 *Case (iv):* Otherwise, the result is the blank character.

8 6 **Example.** If there is a suitable newline character, and unit 10 is connected for formatted stream output, the statement

```
10 WRITE (10, '(A)') 'New'//NEW_LINE('a')//'Line'
```

11 will write a record containing “New” and then a record containing “Line”.

12 **13.8.133 NINT (A [, KIND])**

13 1 **Description.** Nearest integer.

14 2 **Class.** [Elemental function](#).

15 3 **Arguments.**

16 A shall be of type real.

17 KIND (optional) shall be a scalar integer [constant expression](#).

18 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise, the kind type parameter is that of default integer type.

20 5 **Result Value.** The result is the integer nearest A, or if there are two integers equally near A, the result is whichever such integer has the greater magnitude.

22 6 **Example.** NINT (2.783) has the value 3.

23 **13.8.134 NORM2 (X) or NORM2 (X, DIM)**

24 1 **Description.** L_2 norm of an array.

25 2 **Class.** [Transformational function](#).

26 3 **Arguments.**

27 X shall be a real array.

28 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of X.

29 4 **Result Characteristics.** The result is of the same type and type parameters as X. It is scalar if DIM does not appear; otherwise the result has [rank](#) $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$, where n is the [rank](#) of X and $[d_1, d_2, \dots, d_n]$ is the shape of X.

32 5 **Result Value.**

33 *Case (i):* The result of NORM2 (X) has a value equal to a processor-dependent approximation to the generalized L_2 norm of X, which is the square root of the sum of the squares of the elements of X. If X has size zero, the result has the value zero.

36 *Case (ii):* The result of NORM2 (X, DIM=DIM) has a value equal to that of NORM2 (X) if X has [rank](#) one. Otherwise, the value of element $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of the result is equal to NORM2 (X($s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n$)).

39 6 It is recommended that the processor compute the result without undue overflow or underflow.

1 7 **Example.** The value of NORM2 ([3.0, 4.0]) is 5.0 (approximately). If X has the value $\begin{bmatrix} 1.0 & 2.0 \\ 3.0 & 4.0 \end{bmatrix}$ then the
 2 value of NORM2 (X, DIM=1) is [3.162, 4.472] (approximately) and the value of NORM2 (X, DIM=2) is [2.236,
 3 5.0] (approximately).

4 13.8.135 NOT (I)

5 1 **Description.** Bitwise complement.

6 2 **Class.** [Elemental](#) function.

7 3 **Argument.** I shall be of type integer.

8 4 **Result Characteristics.** Same as I.

9 5 **Result Value.** The result has the value obtained by complementing I bit-by-bit according to the following truth
 10 table:

I	NOT (I)
1	0
0	1

11 6 The model for the interpretation of an integer value as a sequence of bits is in [13.3](#).

12 7 **Example.** If I is represented by the string of bits 01010101, NOT (I) has the binary value 10101010.

13 13.8.136 NULL ([MOLD])

14 1 **Description.** [Disassociated](#) pointer or unallocated [allocatable](#) entity.

15 2 **Class.** [Transformational](#) function.

16 3 **Argument.** MOLD shall be a pointer or [allocatable](#). It may be of any type or may be a procedure pointer.
 17 If MOLD is a pointer its [pointer association](#) status may be undefined, [disassociated](#), or associated. If MOLD is
 18 [allocatable](#) its allocation status may be allocated or unallocated. It need not be defined with a value.

19 4 **Result Characteristics.** If MOLD is present, the [characteristics](#) are the same as MOLD. If MOLD has [deferred](#)
 20 [type parameters](#), those type parameters of the result are [deferred](#).

21 5 If MOLD is absent, the [characteristics](#) of the result are determined by the entity with which the reference is
 22 associated. See Table [13.5](#). MOLD shall not be absent in any other context. If any type parameters of the
 23 contextual entity are [deferred](#), those type parameters of the result are [deferred](#). If any type parameters of the
 24 contextual entity are assumed, MOLD shall be present.

25 6 If the context of the reference to NULL is an [actual argument](#) in a generic procedure reference, MOLD shall be
 26 present if the type, type parameters, or [rank](#) are required to resolve the generic reference.

Table 13.5: **Characteristics of the result of NULL ()**

Appearance of NULL ()	Type, type parameters, and rank of result:
right side of a pointer assignment	pointer on the left side
initialization for an object in a declaration	the object
default initialization for a component	the component
in a structure constructor	the corresponding component
as an actual argument	the corresponding dummy argument
in a DATA statement	the corresponding pointer object

1 7 **Result.** The result is a [disassociated](#) pointer or an unallocated [allocatable](#) entity.

2 8 **Examples.**

3 *Case (i):* REAL, POINTER, DIMENSION (:) :: VEC => NULL () defines the initial association status of
4 VEC to be [disassociated](#).

5 *Case (ii):* The MOLD argument is required in the following:

```
6     INTERFACE GEN
7         SUBROUTINE S1 (J, PI)
8             INTEGER J
9             INTEGER, POINTER :: PI
10        END SUBROUTINE S1
11        SUBROUTINE S2 (K, PR)
12            INTEGER K
13            REAL, POINTER :: PR
14        END SUBROUTINE S2
15    END INTERFACE
16    REAL, POINTER :: REAL_PTR
17    CALL GEN (7, NULL (REAL_PTR) )      ! Invokes S2
```

18 13.8.137 NUM_IMAGES ()

19 1 **Description.** Number of [images](#).

20 2 **Class.** [Transformational function](#).

21 3 **Argument.** None.

22 4 **Result Characteristics.** Default integer scalar.

23 5 **Result Value.** The number of [images](#).

24 6 **Example.** The following code uses [image 1](#) to read data and broadcast it to other [images](#).

```
25     REAL :: P[*]
26     IF (THIS_IMAGE()==1) THEN
27         READ (6,*) P
28         DO I = 2, NUM_IMAGES()
29             P[I] = P
30         END DO
31     END IF
32     SYNC ALL
```

33 13.8.138 OUT_OF_RANGE (X, MOLD, [, ROUND])

34 1 **Description.** Whether a value cannot be converted safely.

35 2 **Class.** [Elemental function](#).

36 3 **Arguments.**

37 X shall be of type integer or real.

38 MOLD shall be an integer or real scalar. If it is a variable, it need not be defined.

39 ROUND (optional) shall be a logical scalar. ROUND shall be present only if X is of type real and MOLD is of
40 type integer.

1 4 **Result Characteristics.** Default logical scalar.

2 5 **Result Value.**

3 *Case (i):* If MOLD is of type integer, and ROUND is absent or present with the value false, the result is true
4 if and only if the value of X is an IEEE infinity or NaN, or if the integer with largest magnitude
5 that lies between zero and X inclusive is not representable by objects with the type and kind of
6 MOLD.

7 *Case (ii):* If MOLD is of type integer, and ROUND is present with the value true, the result is true if and only
8 if the value of X is an IEEE infinity or NaN, or if the integer nearest X, or the integer of greater
9 magnitude if two integers are equally near to X, is not representable by objects with the type and
10 kind of MOLD.

11 *Case (iii):* Otherwise, the result is true if and only if the value of X is an IEEE infinity or NaN that is not
12 supported by objects of the type and kind of MOLD, or if X is a finite number and the result of
13 rounding the value of X (according to the IEEE rounding mode if appropriate) to the extended
14 model for the kind of MOLD has magnitude larger than that of the largest finite number with the
15 same sign as X that is representable by objects with the type and kind of MOLD.

16 6 **Examples.** If INT8 is the kind value for an 8-bit binary integer type, OUT_OF_RANGE (-128.5, 0_INT8)
17 will have the value false and OUT_OF_RANGE (-128.5, 0_INT8, .TRUE.) will have the value true.

18 13.8.139 PACK (ARRAY, MASK [, VECTOR])

19 1 **Description.** Array packed into a vector.

20 2 **Class.** [Transformational function](#).

21 3 **Arguments.**

22 ARRAY shall be an array of any type.

23 MASK shall be of type logical and shall be [conformable](#) with ARRAY.

24 VECTOR (optional) shall be of the same type and type parameters as ARRAY and shall have [rank](#) one. VEC-
25 TOR shall have at least as many elements as there are true elements in MASK. If MASK is scalar
26 with the value true, VECTOR shall have at least as many elements as there are in ARRAY.

27 4 **Result Characteristics.** The result is an array of [rank](#) one with the same type and type parameters as
28 ARRAY. If VECTOR is present, the result size is that of VECTOR; otherwise, the result size is the number t
29 of true elements in MASK unless MASK is scalar with the value true, in which case the result size is the size of
30 ARRAY.

31 5 **Result Value.** Element i of the result is the element of ARRAY that corresponds to the i^{th} true element of
32 MASK, taking elements in array element order, for $i = 1, 2, \dots, t$. If VECTOR is present and has size $n > t$,
33 element i of the result has the value VECTOR (i), for $i = t + 1, \dots, n$.

34 6 **Examples.** The nonzero elements of an array M with the value $\begin{bmatrix} 0 & 0 & 0 \\ 9 & 0 & 0 \\ 0 & 0 & 7 \end{bmatrix}$ can be “gathered” by the func-
35 tion PACK. The result of PACK (M, MASK = M /= 0) is [9, 7] and the result of PACK (M, M /= 0, VEC-
36 TOR = [2, 4, 6, 8, 10, 12]) is [9, 7, 6, 8, 10, 12].

37 13.8.140 PARITY (MASK) or PARITY (MASK, DIM)

38 1 **Description.** Array reduced by [.NEQV](#) operation.

39 2 **Class.** [Transformational function](#).

40 3 **Arguments.**

41 MASK shall be a logical array.

1 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of MASK.

2 4 **Result Characteristics.** The result is of type logical with the same kind type parameter as MASK. It is scalar
3 if DIM does not appear; otherwise, the result has [rank](#) $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$
4 where $[d_1, d_2, \dots, d_n]$ is the shape of MASK.

5 5 **Result Value.**

6 *Case (i):* The result of PARITY (MASK) has the value true if an odd number of the elements of MASK are
7 true, and false otherwise.

8 *Case (ii):* If MASK has [rank](#) one, PARITY (MASK, DIM) is equal to PARITY (MASK). Otherwise, the
9 value of element $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of PARITY (MASK, DIM) is equal to
10 PARITY (MASK $(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)$).

11 6 **Examples.**

12 *Case (i):* The value of PARITY ([T, T, T, F]) is true if T has the value true and F has the value false.

13 *Case (ii):* If B is the array $\begin{bmatrix} T & T & F \\ T & T & T \end{bmatrix}$, where T has the value true and F has the value false, then
14 PARITY (B, DIM=1) has the value [F, F, T] and PARITY (B, DIM=2) has the value [F, T].

15 13.8.141 POPCNT (I)

16 1 **Description.** Number of one bits.

17 2 **Class.** [Elemental](#) function.

18 3 **Argument.** I shall be of type integer.

19 4 **Result Characteristics.** Default integer.

20 5 **Result Value.** The result value is equal to the number of one bits in the sequence of bits of I. The model for
21 the interpretation of an integer value as a sequence of bits is in [13.3](#).

22 6 **Examples.** POPCNT ([1, 2, 3, 4, 5, 6]) has the value [1, 1, 2, 1, 2, 2].

23 13.8.142 POPPAR (I)

24 1 **Description.** Parity expressed as 0 or 1.

25 2 **Class.** [Elemental](#) function.

26 3 **Argument.** I shall be of type integer.

27 4 **Result Characteristics.** Default integer.

28 5 **Result Value.** POPPAR (I) has the value 1 if POPCNT (I) is odd, and 0 if POPCNT (I) is even.

29 6 **Examples.** POPPAR ([1, 2, 3, 4, 5, 6]) has the value [1, 1, 0, 1, 0, 0].

30 13.8.143 PRECISION (X)

31 1 **Description.** Decimal precision of a real model.

32 2 **Class.** [Inquiry function](#).

33 3 **Argument.** X shall be of type real or complex. It may be a scalar or an array.

34 4 **Result Characteristics.** Default integer scalar.

1 5 **Result Value.** The result has the value $\text{INT}((p-1) * \text{LOG10}(b)) + k$, where b and p are as defined in 13.4
 2 for the model representing real numbers with the same value for the kind type parameter as X, and where k is 1
 3 if b is an integral power of 10 and 0 otherwise.

4 6 **Example.** PRECISION (X) has the value $\text{INT}(23 * \text{LOG10}(2.)) = \text{INT}(6.92\dots) = 6$ for real X whose model
 5 is as in Note 13.4.

6 13.8.144 PRESENT (A)

7 1 **Description.** Presence of optional argument.

8 2 **Class.** Inquiry function.

9 3 **Argument.** A shall be the name of an optional dummy argument that is accessible in the subprogram in which
 10 the PRESENT function reference appears. There are no other requirements on A.

11 4 **Result Characteristics.** Default logical scalar.

12 5 **Result Value.** The result has the value true if A is present (12.5.2.12) and otherwise has the value false.

13 13.8.145 PRODUCT (ARRAY, DIM [, MASK]) or PRODUCT (ARRAY [, MASK])

14 1 **Description.** Array reduced by multiplication.

15 2 **Class.** Transformational function.

16 3 **Arguments.**

17 ARRAY shall be an array of numeric type.

18 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the rank of ARRAY.

19 MASK (optional) shall be of type logical and shall be conformable with ARRAY.

20 4 **Result Characteristics.** The result is of the same type and kind type parameter as ARRAY. It is scalar if
 21 DIM does not appear; otherwise, the result has rank $n-1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$ where
 22 $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

23 5 **Result Value.**

24 *Case (i):* The result of PRODUCT (ARRAY) has a value equal to a processor-dependent approximation to
 25 the product of all the elements of ARRAY or has the value one if ARRAY has size zero.

26 *Case (ii):* The result of PRODUCT (ARRAY, MASK = MASK) has a value equal to a processor-dependent
 27 approximation to the product of the elements of ARRAY corresponding to the true elements of
 28 MASK or has the value one if there are no true elements.

29 *Case (iii):* If ARRAY has rank one, PRODUCT (ARRAY, DIM = DIM [, MASK = MASK]) has a value equal
 30 to that of PRODUCT (ARRAY [, MASK = MASK]). Otherwise, the value of element $(s_1, s_2, \dots,$
 31 $s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of PRODUCT (ARRAY, DIM = DIM [, MASK = MASK]) is equal to

32 $\text{PRODUCT}(\text{ARRAY}(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n) [, \text{MASK} = \text{MASK}(s_1, s_2, \dots,$
 33 $s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n)])$.

34 6 **Examples.**

35 *Case (i):* The value of PRODUCT ([1, 2, 3]) is 6.

36 *Case (ii):* PRODUCT (C, MASK = C > 0.0) forms the product of the positive elements of C.

37 *Case (iii):* If B is the array $\begin{bmatrix} 1 & 3 & 5 \\ 2 & 4 & 6 \end{bmatrix}$, PRODUCT (B, DIM = 1) is [2, 12, 30] and PRODUCT (B, DIM = 2)
 38 is [15, 48].

13.8.146 RADIX (X)

1 **Description.** Base of a numeric model.

2 **Class.** Inquiry function.

3 **Argument.** X shall be of type integer or real. It may be a scalar or an array.

4 **Result Characteristics.** Default integer scalar.

5 **Result Value.** The result has the value r if X is of type integer and the value b if X is of type real, where r and b are as defined in 13.4 for the model representing numbers of the same type and kind type parameter as X.

6 **Example.** RADIX (X) has the value 2 for real X whose model is as in Note 13.4.

13.8.147 RANDOM_INIT (REPEATABLE, IMAGE_DISTINCT)

1 **Description.** Initialize the pseudorandom number generator.

2 **Class.** Subroutine.

3 **Arguments.**

REPEATABLE shall be a logical scalar. It is an **INTENT (IN)** argument. If it has the value true, the seed accessed by the pseudorandom number generator is set to a processor-dependent value that is the same each time RANDOM_INIT is called from the same **image**. If it has the value false, the seed is set to a processor-dependent, unpredictably different value on each call.

IMAGE_DISTINCT shall be a logical scalar. It is an **INTENT (IN)** argument. If it has the value true, the seed accessed by the pseudorandom number generator is set to a processor-dependent value that is distinct from the value that would be set by a call to RANDOM_INIT in another **image**. If it has the value false, the value to which the seed is set does not depend on which **image** calls RANDOM_INIT.

4 **Example.** The following statement initializes the pseudorandom number generator so that the seed is different on each call and that the sequence generated will differ from that of another image:

```
CALL RANDOM_INIT (REPEATABLE=.FALSE., IMAGE_DISTINCT=.TRUE.)
```

13.8.148 RANDOM_NUMBER (HARVEST)

1 **Description.** Generate pseudorandom number(s).

2 **Class.** Subroutine.

3 **Argument.** HARVEST shall be of type real. It is an **INTENT (OUT)** argument. It may be a scalar or an array. It is assigned pseudorandom numbers from the uniform distribution in the interval $0 \leq x < 1$. If **images** use a common generator, the interleaving of values assigned in unordered segments is processor dependent.

4 **Example.**

```
REAL X, Y (10, 10)
! Initialize X with a pseudorandom number
CALL RANDOM_NUMBER (HARVEST = X)
CALL RANDOM_NUMBER (Y)
! X and Y contain uniformly distributed random numbers
```

13.8.149 RANDOM_SEED ([SIZE, PUT, GET])

1 **Description.** Restart or query the pseudorandom number generator.

2 **Class.** Subroutine.

3 **Arguments.** There shall either be exactly one or no arguments present.

4 SIZE (optional) shall be a default integer scalar. It is an **INTENT (OUT)** argument. It is assigned the number
5 N of integers that the processor uses to hold the value of the seed.

6 PUT (optional) shall be a default integer array of **rank** one and size $\geq N$. It is an **INTENT (IN)** argument. It
7 is used in a processor-dependent manner to compute the seed value accessed by the pseudorandom
8 number generator.

9 GET (optional) shall be a default integer array of **rank** one and size $\geq N$. It is an **INTENT (OUT)** argument.
10 It is assigned the value of the seed.
11

12 4 If no argument is present, the processor assigns a processor-dependent value to the seed.

13 5 The pseudorandom number generator used by **RANDOM_NUMBER** maintains a seed that is updated during the
14 execution of **RANDOM_NUMBER** and that can be retrieved or changed by **RANDOM_SEED**. Computation
15 of the seed from the argument PUT is performed in a processor-dependent manner. The value assigned to GET
16 need not be the same as the value of PUT in an immediately preceding reference to **RANDOM_SEED**. For
17 example, following execution of the statements

```
18     CALL RANDOM_SEED (PUT=SEED1)
19     CALL RANDOM_SEED (GET=SEED2)
```

20 SEED2 need not equal SEED1. When the values differ, the use of either value as the PUT argument in a
21 subsequent call to **RANDOM_SEED** shall result in the same sequence of pseudorandom numbers being generated.
22 For example, after execution of the statements

```
23     CALL RANDOM_SEED (PUT=SEED1)
24     CALL RANDOM_SEED (GET=SEED2)
25     CALL RANDOM_NUMBER (X1)
26     CALL RANDOM_SEED (PUT=SEED2)
27     CALL RANDOM_NUMBER (X2)
```

28 X2 equals X1.

29 6 **Examples.**

```
30     CALL RANDOM_SEED                ! Processor initialization
31     CALL RANDOM_SEED (SIZE = K)      ! Puts size of seed in K
32     CALL RANDOM_SEED (PUT = SEED (1 : K)) ! Define seed
33     CALL RANDOM_SEED (GET = OLD (1 : K)) ! Read current seed
```

34 13.8.150 RANGE (X)

35 1 **Description.** Decimal exponent range of a numeric model (13.4).

36 2 **Class.** Inquiry function.

37 3 **Argument.** X shall be of type integer, real, or complex. It may be a scalar or an array.

38 4 **Result Characteristics.** Default integer scalar.

39 5 **Result Value.**

- 1 *Case (i):* If X is of type integer, the result has the value `INT (LOG10 (HUGE (X)))`.
 2 *Case (ii):* If X is of type real, the result has the value `INT (MIN (LOG10 (HUGE (X)), -LOG10 (TINY (X))))`.
 3 *Case (iii):* If X is of type complex, the result has the value `RANGE (REAL (X))`.

4 6 **Examples.** `RANGE (X)` has the value 38 for real X whose model is as in Note 13.4, because in this case
 5 `HUGE (X) = (1 - 2-24) × 2127` and `TINY (X) = 2-127`.

6 13.8.151 RANK (A)

7 1 **Description.** Rank of a data object.

8 2 **Class.** `Inquiry function`.

9 3 **Argument.** A shall be a data object of any type.

10 4 **Result Characteristics.** Default integer scalar.

11 5 **Result Value.** The value of the result is the rank of A.

12 6 **Example.** If X is an `assumed-rank` dummy argument and its associated `effective argument` is an array of rank
 13 3, `RANK(X)` has the value 3.

14 13.8.152 REAL (A [, KIND])

15 1 **Description.** Conversion to real type.

16 2 **Class.** `Elemental function`.

17 3 **Arguments.**

18 A shall be of type integer, real, or complex, or a `boz-literal-constant`.

19 KIND (optional) shall be a scalar integer `constant expression`.

20 4 **Result Characteristics.** Real.

21 *Case (i):* If A is of type integer or real and KIND is present, the kind type parameter is that specified by the
 22 value of KIND. If A is of type integer or real and KIND is not present, the kind type parameter is
 23 that of default real kind.

24 *Case (ii):* If A is of type complex and KIND is present, the kind type parameter is that specified by the value
 25 of KIND. If A is of type complex and KIND is not present, the kind type parameter is the kind
 26 type parameter of A.

27 *Case (iii):* If A is a `boz-literal-constant` and KIND is present, the kind type parameter is that specified by the
 28 value of KIND. If A is a `boz-literal-constant` and KIND is not present, the kind type parameter is
 29 that of default real kind.

30 5 **Result Value.**

31 *Case (i):* If A is of type integer or real, the result is equal to a processor-dependent approximation to A.

32 *Case (ii):* If A is of type complex, the result is equal to a processor-dependent approximation to the real part
 33 of A.

34 *Case (iii):* If A is a `boz-literal-constant`, the value of the result is the value whose internal representation as a
 35 bit sequence is the same as that of A as modified by padding or truncation according to 13.3.3. The
 36 interpretation of the bit sequence is processor dependent.

37 6 **Examples.** `REAL (-3)` has the value `-3.0`. `REAL (Z)` has the same kind type parameter and the same value
 38 as the real part of the complex variable Z.

1 **13.8.153 REDUCE (ARRAY, OPERATION [, MASK, IDENTITY, ORDERED])**
 or **REDUCE (ARRAY, OPERATION, DIM [, MASK, IDENTITY,**
ORDERED])

2 1 **Description.** General reduction of array.

3 2 **Class.** Transformational function.

4 3 **Arguments.**

5 ARRAY shall be an array of any type.

6 OPERATION shall be a pure function with two arguments of the same type and type parameters as ARRAY.
 7 Its result shall have the same type and type parameters as ARRAY. The arguments and result shall
 8 not be polymorphic. OPERATION should implement a mathematically associative operation. It
 9 need not be commutative.

10 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the rank of ARRAY.

11 MASK (optional) shall be of type logical and shall be conformable with ARRAY.

12 IDENTITY (optional) shall be scalar with the same type and type parameters as ARRAY.

13 ORDERED (optional) shall be a logical scalar.

14 4 **Result Characteristics.** The result is of the same type and type parameters as ARRAY. It is scalar if DIM
 15 does not appear; otherwise, the result has rank $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$ where
 16 $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

17 5 **Result Value.**

18 *Case (i):* The result of REDUCE (ARRAY, OPERATION [, IDENTITY = IDENTITY, ORDERED =
 19 ORDERED]) over the sequence of values in ARRAY is the result of an iterative process. The
 20 initial order of the sequence is array element order. While the sequence has more than one element,
 21 each iteration involves the execution of $r = \text{OPERATION}(x, y)$ for adjacent x and y in the sequence,
 22 with x immediately preceding y , and the subsequent replacement of x and y with r ; if ORDERED
 23 is present with the value true, x and y shall be the first two elements of the sequence. The process
 24 continues until the sequence has only one element which is the value of the reduction. If the initial
 25 sequence is empty, the result has the value IDENTITY if IDENTITY is present, and otherwise,
 26 error termination is initiated.

27 *Case (ii):* The result of REDUCE (ARRAY, OPERATION, MASK = MASK [, IDENTITY = IDENTITY,
 28 ORDERED = ORDERED]) is as for Case (i) except that the initial sequence is only those elements
 29 of ARRAY for which the corresponding elements of MASK is true.

30 *Case (iii):* If ARRAY has rank one, REDUCE (ARRAY, OPERATION, DIM = DIM [, MASK = MASK,
 31 IDENTITY = IDENTITY, ORDERED = ORDERED]) has a value equal to that of REDUCE (AR-
 32 RAY, OPERATION [, MASK = MASK, IDENTITY = IDENTITY, ORDERED = ORDERED]).
 33 Otherwise, the value of element $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1}, \dots, s_n)$ of REDUCE (ARRAY,
 34 DIM = DIM [, MASK = MASK, IDENTITY = IDENTITY]) is equal to

$$\begin{aligned} & \text{REDUCE (ARRAY (} s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n), \\ & \quad \text{OPERATION = OPERATION,} \\ & \quad \text{DIM=1} \\ & \quad [, \text{MASK = MASK (} s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n), \\ & \quad \text{IDENTITY = IDENTITY,} \\ & \quad \text{ORDERED = ORDERED]).} \end{aligned}$$

36 6 **Examples.** The following examples all use the function MY_MULT, which returns the product of its two integer
 37 arguments.

38 *Case (i):* The value of REDUCE ([1, 2, 3], MY_MULT) is 6.

39 *Case (ii):* REDUCE (C, MY_MULT, MASK= C > 0, IDENTITY=1) forms the product of the positive
 40 elements of C.

1 *Case (iii):* If B is the array $\begin{bmatrix} 1 & 3 & 5 \\ 2 & 4 & 6 \end{bmatrix}$, REDUCE (B, MY_MULT, DIM = 1) is [2, 12, 30] and REDUCE (B,
2 MY_MULT, DIM = 2) is [15, 48].

NOTE 13.21

If OPERATION is not computationally associative, REDUCE without ORDERED=.TRUE. with the same argument values might not always produce the same result, as the processor can apply the associative law to the evaluation.

3 **13.8.154 REPEAT (STRING, NCOPIES)**

4 1 **Description.** Repetitive string concatenation.

5 2 **Class.** Transformational function.

6 3 **Arguments.**

7 STRING shall be a character scalar.

8 NCOPIES shall be an integer scalar. Its value shall not be negative.

9 4 **Result Characteristics.** Character scalar of length NCOPIES times that of STRING, with the same kind type
10 parameter as STRING.

11 5 **Result Value.** The value of the result is the concatenation of NCOPIES copies of STRING.

12 6 **Examples.** REPEAT ('H', 2) has the value HH. REPEAT ('XYZ', 0) has the value of a zero-length string.

13 **13.8.155 RESHAPE (SOURCE, SHAPE [, PAD, ORDER])**

14 1 **Description.** Arbitrary shape array construction.

15 2 **Class.** Transformational function.

16 3 **Arguments.**

17 SOURCE shall be an array of any type. If PAD is absent or of size zero, the size of SOURCE shall be greater
18 than or equal to PRODUCT (SHAPE). The size of the result is the product of the values of the
19 elements of SHAPE.

20 SHAPE shall be a rank-one integer array. SIZE (x), where x is the actual argument corresponding to
21 SHAPE, shall be a constant expression whose value is positive and less than 16. It shall not have
22 an element whose value is negative.

23 PAD (optional) shall be an array of the same type and type parameters as SOURCE.

24 ORDER (optional) shall be of type integer, shall have the same shape as SHAPE, and its value shall be a
25 permutation of (1, 2, ..., n), where n is the size of SHAPE. If absent, it is as if it were present with
26 value (1, 2, ..., n).

27 4 **Result Characteristics.** The result is an array of shape SHAPE (that is, SHAPE (RESHAPE (SOURCE,
28 SHAPE, PAD, ORDER)) is equal to SHAPE) with the same type and type parameters as SOURCE.

29 5 **Result Value.** The elements of the result, taken in permuted subscript order ORDER (1), ..., ORDER (n), are
30 those of SOURCE in normal array element order followed if necessary by those of PAD in array element order,
31 followed if necessary by additional copies of PAD in array element order.

32 6 **Examples.** RESHAPE ([1, 2, 3, 4, 5, 6], [2, 3]) has the value $\begin{bmatrix} 1 & 3 & 5 \\ 2 & 4 & 6 \end{bmatrix}$.

33 RESHAPE ([1, 2, 3, 4, 5, 6], [2, 4], [0, 0], [2, 1]) has the value $\begin{bmatrix} 1 & 2 & 3 & 4 \\ 5 & 6 & 0 & 0 \end{bmatrix}$.

13.8.156 RRSPACING (X)

1 **Description.** Reciprocal of relative spacing of model numbers.

2 **Class.** [Elemental](#) function.

3 **Argument.** X shall be of type real.

4 **Result Characteristics.** Same as X.

5 **Result Value.** The result has the value $|Y \times b^{-e}| \times b^p = \text{ABS}(\text{FRACTION}(Y)) * \text{RADIX}(X) / \text{EPSILON}(X)$, where b , e , and p are as defined in 13.4 for Y, the value nearest to X in the model for real values whose kind type parameter is that of X; if there are two such values, the value of greater absolute value is taken. If X is an IEEE infinity, the result is an [IEEE NaN](#). If X is an [IEEE NaN](#), the result is that [NaN](#).

6 **Example.** RRSPACING (−3.0) has the value 0.75×2^{24} for reals whose model is as in Note 13.4.

13.8.157 SAME_TYPE_AS (A, B)

1 **Description.** [Dynamic type](#) equality test.

2 **Class.** [Inquiry](#) function.

3 **Arguments.**

A shall be an object of [extendible declared](#) type or [unlimited polymorphic](#). If it is a [polymorphic](#) pointer, it shall not have an undefined association status.

B shall be an object of [extendible declared](#) type or [unlimited polymorphic](#). If it is a [polymorphic](#) pointer, it shall not have an undefined association status.

4 **Result Characteristics.** Default logical scalar.

5 **Result Value.** If the [dynamic type](#) of A or B is [extendible](#), the result is true if and only if the [dynamic type](#) of A is the same as the [dynamic type](#) of B. If neither A nor B has [extendible dynamic](#) type, the result is processor dependent.

NOTE 13.22

The [dynamic type](#) of a [disassociated](#) pointer or unallocated [allocatable](#) variable is its [declared type](#). An [unlimited polymorphic](#) entity has no [declared type](#).

6 **Example.** Given the declarations and assignments

```

TYPE T1
  REAL C
END TYPE
TYPE, EXTENDS(T1) :: T2
END TYPE
CLASS(T1), POINTER :: P, Q, R
ALLOCATE(P, Q)
ALLOCATE(T2 :: R)

```

the value of SAME_TYPE_AS (P, Q) will be true, and the value of SAME_TYPE_AS (P, R) will be false.

13.8.158 SCALE (X, I)

1 **Description.** Real number scaled by radix power.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 X shall be of type real.

5 I shall be of type integer.

6 **Result Characteristics.** Same as X.

7 **Result Value.** The result has the value $X \times b^I$, where b is defined in [13.4](#) for model numbers representing values of X, provided this result is representable; if not, the result is processor dependent.

8 **Example.** SCALE (3.0, 2) has the value 12.0 for reals whose model is as in Note [13.4](#).

13.8.159 SCAN (STRING, SET [, BACK, KIND])

1 **Description.** Character set membership search.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 STRING shall be of type character.

5 SET shall be of type character with the same kind type parameter as STRING.

6 BACK (optional) shall be of type logical.

7 KIND (optional) shall be a scalar integer [constant expression](#).

8 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise the kind type parameter is that of default integer type.

9 **Result Value.**

10 *Case (i):* If BACK is absent or is present with the value false and if STRING contains at least one character that is in SET, the value of the result is the position of the leftmost character of STRING that is in SET.

11 *Case (ii):* If BACK is present with the value true and if STRING contains at least one character that is in SET, the value of the result is the position of the rightmost character of STRING that is in SET.

12 *Case (iii):* The value of the result is zero if no character of STRING is in SET or if the length of STRING or SET is zero.

13 **Examples.**

14 *Case (i):* SCAN ('FORTRAN', 'TR') has the value 3.

15 *Case (ii):* SCAN ('FORTRAN', 'TR', BACK = [.TRUE.](#)) has the value 5.

16 *Case (iii):* SCAN ('FORTRAN', 'BCD') has the value 0.

13.8.160 SELECTED_CHAR_KIND (NAME)

1 **Description.** Character kind selection.

2 **Class.** [Transformational function](#).

3 **Argument.** NAME shall be default character scalar.

4 **Result Characteristics.** Default integer scalar.

1 5 **Result Value.** If NAME has the value DEFAULT, then the result has a value equal to that of the kind type
 2 parameter of default character. If NAME has the value ASCII, then the result has a value equal to that of the
 3 kind type parameter of [ASCII character](#) if the processor supports such a kind; otherwise the result has the value
 4 -1 . If NAME has the value ISO_10646, then the result has a value equal to that of the kind type parameter of
 5 the [ISO 10646 character](#) kind (corresponding to UCS-4 as specified in ISO/IEC 10646) if the processor supports
 6 such a kind; otherwise the result has the value -1 . If NAME is a processor-defined name of some other character
 7 kind supported by the processor, then the result has a value equal to that kind type parameter value. If NAME is
 8 not the name of a supported character type, then the result has the value -1 . The NAME is interpreted without
 9 respect to case or trailing blanks.

10 6 **Examples.** SELECTED_CHAR_KIND ('ASCII') has the value 1 on a processor that uses 1 as the kind type
 11 parameter for the [ASCII character](#) set. The following subroutine produces a Japanese date stamp.

```

12     SUBROUTINE create_date_string(string)
13         INTRINSIC date_and_time,selected_char_kind
14         INTEGER,PARAMETER :: ucs4 = selected_char_kind("ISO_10646")
15         CHARACTER(1,UCS4),PARAMETER :: nen=CHAR(INT(Z'5e74'),UCS4), & !year
16             gatsu=CHAR(INT(Z'6708'),UCS4), & !month
17             nichi=CHAR(INT(Z'65e5'),UCS4) !day
18         CHARACTER(len= *, kind= ucs4) string
19         INTEGER values(8)
20         CALL date_and_time(values=values)
21         WRITE(string,1) values(1),nen,values(2),gatsu,values(3),nichi
22     1 FORMAT(IO,A,IO,A,IO,A)
23     END SUBROUTINE

```

24 13.8.161 SELECTED_INT_KIND (R)

25 1 **Description.** Integer kind selection.

26 2 **Class.** [Transformational function](#).

27 3 **Argument.** R shall be an integer scalar.

28 4 **Result Characteristics.** Default integer scalar.

29 5 **Result Value.** The result has a value equal to the value of the kind type parameter of an integer type that
 30 represents all values n in the range $-10^R < n < 10^R$, or if no such kind type parameter is available on the
 31 processor, the result is -1 . If more than one kind type parameter meets the criterion, the value returned is the
 32 one with the smallest decimal exponent range, unless there are several such values, in which case the smallest of
 33 these kind values is returned.

34 6 **Example.** Assume a processor supports two integer kinds, 32 with representation method $r = 2$ and $q = 31$,
 35 and 64 with representation method $r = 2$ and $q = 63$. On this processor SELECTED_INT_KIND (9) has the
 36 value 32 and SELECTED_INT_KIND (10) has the value 64.

37 13.8.162 SELECTED_REAL_KIND ([P, R, RADIX])

38 1 **Description.** Real kind selection.

39 2 **Class.** [Transformational function](#).

40 3 **Arguments.** At least one argument shall be present.

41 P (optional) shall be an integer scalar.

42 R (optional) shall be an integer scalar.

1 RADIX (optional) shall be an integer scalar.

2 4 **Result Characteristics.** Default integer scalar.

3 5 **Result Value.** If P or R is absent, the result value is the same as if it were present with the value zero. If
4 RADIX is absent, there is no requirement on the radix of the selected kind.

5 6 The result has a value equal to a value of the kind type parameter of a real type with decimal precision, as
6 returned by the function PRECISION, of at least P digits, a decimal exponent range, as returned by the function
7 RANGE, of at least R, and a radix, as returned by the function RADIX, of RADIX, if such a kind type parameter
8 is available on the processor.

9 7 Otherwise, the result is -1 if the processor supports a real type with radix RADIX and exponent range of at least
10 R but not with precision of at least P, -2 if the processor supports a real type with radix RADIX and precision of
11 at least P but not with exponent range of at least R, -3 if the processor supports a real type with radix RADIX
12 but with neither precision of at least P nor exponent range of at least R, -4 if the processor supports a real type
13 with radix RADIX and either precision of at least P or exponent range of at least R but not both together, and
14 -5 if the processor supports no real type with radix RADIX.

15 8 If more than one kind type parameter value meets the criteria, the value returned is the one with the smallest
16 decimal precision, unless there are several such values, in which case the smallest of these kind values is returned.

17 9 **Example.** SELECTED_REAL_KIND (6, 70) has the value KIND (0.0) on a machine that supports a default
18 real approximation method with $b = 16$, $p = 6$, $e_{\min} = -64$, and $e_{\max} = 63$ and does not have a less precise
19 approximation method.

20 13.8.163 SET_EXPONENT (X, I)

21 1 **Description.** Real value with specified exponent.

22 2 **Class.** [Elemental function](#).

23 3 **Arguments.**

24 X shall be of type real.

25 I shall be of type integer.

26 4 **Result Characteristics.** Same as X.

27 5 **Result Value.** If X has the value zero, the result has the same value as X. If X is an IEEE infinity, the result is
28 an [IEEE NaN](#). If X is an [IEEE NaN](#), the result is the same [NaN](#). Otherwise, the result has the value $X \times b^{I-e}$,
29 where b and e are as defined in [13.4](#) for the representation for the value of X in the extended real model for the
30 kind of X.

31 6 **Example.** SET_EXPONENT (3.0, 1) has the value 1.5 for reals whose model is as in Note [13.4](#).

32 13.8.164 SHAPE (SOURCE [, KIND])

33 1 **Description.** Shape of an array or a scalar.

34 2 **Class.** [Inquiry function](#).

35 3 **Arguments.**

36 SOURCE shall be a scalar or array of any type. It shall not be an unallocated [allocatable](#) variable or a pointer
37 that is not associated. It shall not be an [assumed-size array](#).

38 KIND (optional) shall be a scalar integer [constant expression](#).

39 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value
40 of KIND; otherwise the kind type parameter is that of default integer type. The result is an array of [rank](#) one

1 whose size is equal to the [rank](#) of SOURCE.

2 5 **Result Value.** The result has a value whose i^{th} element is equal to the extent of dimension i of SOURCE,
3 except that if SOURCE is [assumed-rank](#), and associated with an [assumed-size array](#), the last element is equal to
4 -1 .

5 6 **Examples.** The value of SHAPE (A (2:5, -1:1)) is [4, 3]. The value of SHAPE (3) is the rank-one array of size
6 zero.

7 **13.8.165 SHIFTA (I, SHIFT)**

8 1 **Description.** Right shift with fill.

9 2 **Class.** [Elemental](#) function.

10 3 **Arguments.**

11 I shall be of type integer.

12 SHIFT shall be of type integer. It shall be nonnegative and less than or equal to BIT_SIZE (I).

13 4 **Result Characteristics.** Same as I.

14 5 **Result Value.** The result has the value obtained by shifting the bits of I to the right SHIFT bits and replicating
15 the leftmost bit of I in the left SHIFT bits.

16 6 If SHIFT is zero the result is I. Bits shifted out from the right are lost. The model for the interpretation of an
17 integer value as a sequence of bits is in [13.3](#).

18 7 **Example.** SHIFTA (IBSET (0, BIT_SIZE (0) - 1), 2) is equal to SHIFTL (7, BIT_SIZE (0) - 3).

19 **13.8.166 SHIFTL (I, SHIFT)**

20 1 **Description.** Left shift.

21 2 **Class.** [Elemental](#) function.

22 3 **Arguments.**

23 I shall be of type integer.

24 SHIFT shall be of type integer. It shall be nonnegative and less than or equal to BIT_SIZE (I).

25 4 **Result Characteristics.** Same as I.

26 5 **Result Value.** The value of the result is ISHFT (I, SHIFT).

27 6 **Examples.** SHIFTL (3, 1) has the value 6.

28 **13.8.167 SHIFTR (I, SHIFT)**

29 1 **Description.** Right shift.

30 2 **Class.** [Elemental](#) function.

31 3 **Arguments.**

32 I shall be of type integer.

33 SHIFT shall be of type integer. It shall be nonnegative and less than or equal to BIT_SIZE (I).

34 4 **Result Characteristics.** Same as I.

35 5 **Result Value.** The value of the result is ISHFT (I, -SHIFT).

1 6 **Examples.** SHIFTR (3, 1) has the value 1.

2 13.8.168 SIGN (A, B)

3 1 **Description.** Magnitude of A with the sign of B.

4 2 **Class.** [Elemental](#) function.

5 3 **Arguments.**

6 A shall be of type integer or real.

7 B shall be of the same type as A.

8 4 **Result Characteristics.** Same as A.

9 5 **Result Value.**

10 *Case (i):* If $B > 0$, the value of the result is $|A|$.

11 *Case (ii):* If $B < 0$, the value of the result is $-|A|$.

12 *Case (iii):* If B is of type integer and $B=0$, the value of the result is $|A|$.

13 *Case (iv):* If B is of type real and is zero, then:

- 14 • if the processor does not distinguish between positive and negative real zero, or if B is positive
15 real zero, the value of the result is $|A|$;
- 16 • if the processor distinguishes between positive and negative real zero, and B is negative real
17 zero, the value of the result is $-|A|$.

18 6 **Example.** SIGN (-3.0, 2.0) has the value 3.0.

19 13.8.169 SIN (X)

20 1 **Description.** Sine function.

21 2 **Class.** [Elemental](#) function.

22 3 **Argument.** X shall be of type real or complex.

23 4 **Result Characteristics.** Same as X.

24 5 **Result Value.** The result has a value equal to a processor-dependent approximation to $\sin(X)$. If X is of type
25 real, it is regarded as a value in radians. If X is of type complex, its real part is regarded as a value in radians.

26 6 **Example.** SIN (1.0) has the value 0.84147098 (approximately).

27 13.8.170 SINH (X)

28 1 **Description.** Hyperbolic sine function.

29 2 **Class.** [Elemental](#) function.

30 3 **Argument.** X shall be of type real or complex.

31 4 **Result Characteristics.** Same as X.

32 5 **Result Value.** The result has a value equal to a processor-dependent approximation to $\sinh(X)$. If X is of type
33 complex its imaginary part is regarded as a value in radians.

34 6 **Example.** SINH (1.0) has the value 1.1752012 (approximately).

13.8.171 SIZE (ARRAY [, DIM, KIND])

1 **Description.** Size of an array or one extent.

2 **Class.** [Inquiry function](#).

3 **Arguments.**

4 ARRAY shall be [assumed-rank](#) or an array. It shall not be an unallocated [allocatable](#) variable or a pointer
5 that is not associated. If ARRAY is an [assumed-size array](#), DIM shall be present with a value less
6 than the [rank](#) of ARRAY.

7 DIM (optional) shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of ARRAY.

8 KIND (optional) shall be a scalar integer [constant expression](#).

9 **Result Characteristics.** Integer scalar. If KIND is present, the kind type parameter is that specified by the
10 value of KIND; otherwise the kind type parameter is that of default integer type.

11 **Result Value.** If DIM is present, the result has a value equal to the extent of dimension DIM of ARRAY, except
12 that if ARRAY is [assumed-rank](#) and associated with an [assumed-size array](#) and DIM is present with a value equal
13 to the rank of ARRAY, the value is -1 .

14 If DIM is absent and ARRAY is [assumed-rank](#), the result has a value equal to [PRODUCT](#)([SHAPE](#)(ARRAY,
15 KIND)). Otherwise, the result has a value equal to the total number of elements of ARRAY.

16 **Examples.** The value of SIZE (A (2:5, -1:1), DIM=2) is 3. The value of SIZE (A (2:5, -1:1)) is 12.

NOTE 13.23

If ARRAY is [assumed-rank](#) and has rank zero, DIM cannot be present since it cannot satisfy the requirement
17 $1 \leq \text{DIM} \leq 0$.

13.8.172 SPACING (X)

18 **Description.** Spacing of model numbers ([13.4](#)).

19 **Class.** [Elemental function](#).

20 **Argument.** X shall be of type real.

21 **Result Characteristics.** Same as X.

22 **Result Value.** If X does not have the value zero and is not an IEEE infinity or [NaN](#), the result has the value
23 $b^{\max(e-p, e_{\min}-1)}$, where b , e , and p are as defined in [13.4](#) for the value nearest to X in the model for real values
24 whose kind type parameter is that of X; if there are two such values the value of greater absolute value is taken.
25 If X has the value zero, the result is the same as that of TINY (X). If X is an IEEE infinity, the result is an IEEE
26 [NaN](#). If X is an IEEE NaN, the result is that [NaN](#).

27 **Example.** SPACING (3.0) has the value 2^{-22} for reals whose model is as in Note [13.4](#).

13.8.173 SPREAD (SOURCE, DIM, NCOPIES)

28 **Description.** Value replicated in a new dimension.

29 **Class.** [Transformational function](#).

30 **Arguments.**

31 SOURCE shall be a scalar or array of any type. The [rank](#) of SOURCE shall be less than 15.

32 DIM shall be an integer scalar with value in the range $1 \leq \text{DIM} \leq n + 1$, where n is the [rank](#) of SOURCE.

33 NCOPIES shall be an integer scalar.

1 4 **Result Characteristics.** The result is an array of the same type and type parameters as SOURCE and of [rank](#)
2 $n + 1$, where n is the [rank](#) of SOURCE.

3 *Case (i):* If SOURCE is scalar, the shape of the result is (MAX (NCOPIES, 0)).

4 *Case (ii):* If SOURCE is an array with shape $[d_1, d_2, \dots, d_n]$, the shape of the result is $[d_1, d_2, \dots, d_{\text{DIM}-1},$
5 $\text{MAX (NCOPIES, 0)}, d_{\text{DIM}}, \dots, d_n]$.

6 5 **Result Value.**

7 *Case (i):* If SOURCE is scalar, each element of the result has a value equal to SOURCE.

8 *Case (ii):* If SOURCE is an array, the element of the result with subscripts $(r_1, r_2, \dots, r_{n+1})$ has the value
9 SOURCE $(r_1, r_2, \dots, r_{\text{DIM}-1}, r_{\text{DIM}+1}, \dots, r_{n+1})$.

10 6 **Examples.** If A is the array [2, 3, 4], SPREAD (A, DIM=1, NCOPIES=NC) is the array $\begin{bmatrix} 2 & 3 & 4 \\ 2 & 3 & 4 \\ 2 & 3 & 4 \end{bmatrix}$ if NC
11 has the value 3 and is a zero-sized array if NC has the value 0.

12 13.8.174 SQRT (X)

13 1 **Description.** Square root.

14 2 **Class.** [Elemental](#) function.

15 3 **Argument.** X shall be of type real or complex. Unless X is complex, its value shall be greater than or equal to
16 zero.

17 4 **Result Characteristics.** Same as X.

18 5 **Result Value.** The result has a value equal to a processor-dependent approximation to the square root of X. A
19 result of type complex is the principal value with the real part greater than or equal to zero. When the real part
20 of the result is zero, the imaginary part has the same sign as the imaginary part of X.

21 6 **Example.** SQRT (4.0) has the value 2.0 (approximately).

22 13.8.175 STORAGE_SIZE (A [, KIND])

23 1 **Description.** Storage size in bits.

24 2 **Class.** [Inquiry function](#).

25 3 **Arguments.**

26 A shall be a data object of any type. If it is [polymorphic](#) it shall not be an undefined [pointer](#). If
27 it is [unlimited polymorphic](#) or has any [deferred type parameters](#), it shall not be an unallocated
28 [allocatable](#) variable or a [disassociated](#) or undefined pointer.

29 KIND (optional) shall be a scalar integer [constant expression](#).

30 4 **Result Characteristics.** Integer scalar. If KIND is present, the kind type parameter is that specified by the
31 value of KIND; otherwise, the kind type parameter is that of default integer type.

32 5 **Result Value.** The result value is the size expressed in bits for an element of an array that has the [dynamic](#)
33 [type](#) and type parameters of A. If the type and type parameters are such that [storage association \(16.5.3\)](#) applies,
34 the result is consistent with the [named constants](#) defined in the intrinsic module [ISO_FORTRAN_ENV](#).

NOTE 13.24

An array element might take more bits to store than an isolated scalar, since any hardware-imposed alignment requirements for array elements might not apply to a simple scalar variable.

NOTE 13.25

This is intended to be the size in memory that an object takes when it is stored; this might differ from the size it takes during expression handling (which might be the native register size) or when stored in a file. If an object is never stored in memory but only in a register, this function nonetheless returns the size it would take if it were stored in memory.

1 6 **Example.** STORAGE_SIZE (1.0) has the same value as the [named constant](#) NUMERIC_STORAGE_SIZE in
 2 the intrinsic module ISO_FORTRAN_ENV.

3 13.8.176 SUM (ARRAY, DIM [, MASK]) or SUM (ARRAY [, MASK])

4 1 **Description.** Array reduced by addition.

5 2 **Class.** [Transformational function](#).

6 3 **Arguments.**

7 ARRAY shall be an array of [numeric type](#).

8 DIM shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [rank](#) of ARRAY.

9 MASK (optional) shall be of type logical and shall be [conformable](#) with ARRAY.

10 4 **Result Characteristics.** The result is of the same type and kind type parameter as ARRAY. It is scalar if
 11 DIM does not appear; otherwise, the result has [rank](#) $n - 1$ and shape $[d_1, d_2, \dots, d_{\text{DIM}-1}, d_{\text{DIM}+1}, \dots, d_n]$ where
 12 $[d_1, d_2, \dots, d_n]$ is the shape of ARRAY.

13 5 **Result Value.**

14 *Case (i):* The result of SUM (ARRAY) has a value equal to a processor-dependent approximation to the sum
 15 of all the elements of ARRAY or has the value zero if ARRAY has size zero.

16 *Case (ii):* The result of SUM (ARRAY, MASK = MASK) has a value equal to a processor-dependent approx-
 17 imation to the sum of the elements of ARRAY corresponding to the true elements of MASK or has
 18 the value zero if there are no true elements.

19 *Case (iii):* If ARRAY has [rank](#) one, SUM (ARRAY, DIM = DIM [, MASK = MASK]) has a value equal to that
 20 of SUM (ARRAY [, MASK = MASK]). Otherwise, the value of element $(s_1, s_2, \dots, s_{\text{DIM}-1}, s_{\text{DIM}+1},$
 21 $\dots, s_n)$ of SUM (ARRAY, DIM = DIM [, MASK = MASK]) is equal to

22 $\text{SUM}(\text{ARRAY}(s_1, s_2, \dots, s_{\text{DIM}-1}, :, s_{\text{DIM}+1}, \dots, s_n) [, \text{MASK} = \text{MASK}(s_1, s_2, \dots, s_{\text{DIM}-1},$
 23 $:, s_{\text{DIM}+1}, \dots, s_n)])$.

24 6 **Examples.**

25 *Case (i):* The value of SUM ([1, 2, 3]) is 6.

26 *Case (ii):* SUM (C, MASK = C > 0.0) forms the sum of the positive elements of C.

27 *Case (iii):* If B is the array $\begin{bmatrix} 1 & 3 & 5 \\ 2 & 4 & 6 \end{bmatrix}$, SUM (B, DIM = 1) is [3, 7, 11] and SUM (B, DIM = 2) is [9, 12].

28 13.8.177 SYSTEM_CLOCK ([COUNT, COUNT_RATE, COUNT_MAX])

29 1 **Description.** Query system clock.

30 2 **Class.** Subroutine.

31 3 **Arguments.**

32 COUNT (optional) shall be an integer scalar. It is an [INTENT \(OUT\)](#) argument. It is assigned a processor-
 33 dependent value based on the value of a processor clock, or -HUGE (COUNT) if there is no clock
 34 for the invoking [image](#). The processor-dependent value is incremented by one for each clock count
 35 until the value COUNT_MAX is reached and is reset to zero at the next count. It lies in the range
 36 0 to COUNT_MAX if there is a clock.

1 COUNT_RATE (optional) shall be an integer or real scalar. It is an **INTENT (OUT)** argument. It is assigned
 2 a processor-dependent approximation to the number of processor clock counts per second, or zero
 3 if there is no clock for the invoking **image**.

4 COUNT_MAX (optional) shall be an integer scalar. It is an **INTENT (OUT)** argument. It is assigned the
 5 maximum value that COUNT can have, or zero if there is no clock for the invoking **image**.

6 4 Whether an **image** has no clock, has a single clock of its own, or shares a clock with another **image**, is processor
 7 dependent.

8 5 **Example.** If the processor clock is a 24-hour clock that registers time at approximately 18.20648193 ticks per
 9 second, at 11:30 A.M. the reference

10 CALL SYSTEM_CLOCK (COUNT = C, COUNT_RATE = R, COUNT_MAX = M)

11 defines $C = (11 \times 3600 + 30 \times 60) \times 18.20648193 = 753748$, $R = 18.20648193$, and $M = 24 \times 3600 \times 18.20648193 - 1 =$
 12 1573039 .

13 13.8.178 TAN (X)

14 1 **Description.** Tangent function.

15 2 **Class.** **Elemental** function.

16 3 **Argument.** X shall be of type real or complex.

17 4 **Result Characteristics.** Same as X.

18 5 **Result Value.** The result has a value equal to a processor-dependent approximation to $\tan(X)$. If X is of type
 19 real, it is regarded as a value in radians. If X is of type complex, its real part is regarded as a value in radians.

20 6 **Example.** TAN (1.0) has the value 1.5574077 (approximately).

21 13.8.179 TANH (X)

22 1 **Description.** Hyperbolic tangent function.

23 2 **Class.** **Elemental** function.

24 3 **Argument.** X shall be of type real or complex.

25 4 **Result Characteristics.** Same as X.

26 5 **Result Value.** The result has a value equal to a processor-dependent approximation to $\tanh(X)$. If X is of type
 27 complex its imaginary part is regarded as a value in radians.

28 6 **Example.** TANH (1.0) has the value 0.76159416 (approximately).

29 13.8.180 THIS_IMAGE () or THIS_IMAGE (COARRAY) or THIS_IMAGE (COARRAY, DIM)

30 1 **Description.** **Cosubscript(s)** for this **image**.

31 2 **Class.** **Transformational** function.

32 3 **Arguments.**

33 COARRAY shall be a **coarray** of any type. If it is **allocatable** it shall be allocated.

34 DIM shall be an integer scalar. Its value shall be in the range $1 \leq \text{DIM} \leq n$, where n is the **corank** of
 35 COARRAY.

36 4 **Result Characteristics.** Default integer. It is scalar if COARRAY does not appear or DIM appears; otherwise,

1 the result has [rank](#) one and its size is equal to the [corank](#) of COARRAY.

2 **5 Result Value.**

3 *Case (i):* The result of THIS_IMAGE () is a scalar with a value equal to the [index](#) of the invoking [image](#).

4 *Case (ii):* The result of THIS_IMAGE (COARRAY) is the sequence of [cosubscript](#) values for COARRAY
5 that would specify the invoking [image](#).

6 *Case (iii):* The result of THIS_IMAGE (COARRAY, DIM) is the value of [cosubscript](#) DIM in the sequence
7 of [cosubscript](#) values for COARRAY that would specify the invoking [image](#).

8 **6 Examples.** If A is declared by the statement

```
9 REAL A (10, 20) [10, 0:9, 0:*]
```

10 then on [image](#) 5, THIS_IMAGE () has the value 5 and THIS_IMAGE (A) has the value [5, 0, 0]. For the same
11 [coarray](#) on [image](#) 213, THIS_IMAGE (A) has the value [3, 1, 2].

12 7 The following code uses [image](#) 1 to read data. The other [images](#) then copy the data.

```
13 IF (THIS_IMAGE()==1) READ (*,*) P
14 SYNC ALL
15 P = P[1]
```

16 **13.8.181 TINY (X)**

17 1 **Description.** Smallest positive model number.

18 2 **Class.** [Inquiry function](#).

19 3 **Argument.** X shall be a real scalar or array.

20 4 **Result Characteristics.** Scalar with the same type and kind type parameter as X.

21 5 **Result Value.** The result has the value $b^{e_{\min}-1}$ where b and e_{\min} are as defined in [13.4](#) for the model representing
22 numbers of the same type and kind type parameter as X.

23 6 **Example.** TINY (X) has the value 2^{-127} for real X whose model is as in Note [13.4](#).

24 **13.8.182 TRAILZ (I)**

25 1 **Description.** Number of trailing zero bits.

26 2 **Class.** [Elemental function](#).

27 3 **Argument.** I shall be of type integer.

28 4 **Result Characteristics.** Default integer.

29 5 **Result Value.** If all of the bits of I are zero, the result value is BIT_SIZE (I). Otherwise, the result value is the
30 position of the rightmost 1 bit in I. The model for the interpretation of an integer value as a sequence of bits is
31 in [13.3](#).

32 6 **Examples.** TRAILZ (8) has the value 3.

33 **13.8.183 TRANSFER (SOURCE, MOLD [, SIZE])**

34 1 **Description.** Transfer physical representation.

35 2 **Class.** [Transformational function](#).

36 3 **Arguments.**

1 SOURCE shall be a scalar or array of any type.
 2 MOLD shall be a scalar or array of any type. If it is a variable, it need not be defined.
 3 SIZE (optional) shall be an integer scalar. The corresponding **actual argument** shall not be an optional dummy
 4 argument.

5 **4 Result Characteristics.** The result is of the same type and type parameters as MOLD.

6 *Case (i):* If MOLD is a scalar and SIZE is absent, the result is a scalar.

7 *Case (ii):* If MOLD is an array and SIZE is absent, the result is an array and of **rank** one. Its size is as small
 8 as possible such that its physical representation is not shorter than that of SOURCE.

9 *Case (iii):* If SIZE is present, the result is an array of **rank** one and size SIZE.

10 **5 Result Value.** If the physical representation of the result has the same length as that of SOURCE, the physical
 11 representation of the result is that of SOURCE. If the physical representation of the result is longer than that
 12 of SOURCE, the physical representation of the leading part is that of SOURCE and the remainder is processor
 13 dependent. If the physical representation of the result is shorter than that of SOURCE, the physical representation
 14 of the result is the leading part of SOURCE. If D and E are scalar variables such that the physical representation
 15 of D is as long as or longer than that of E, the value of TRANSFER (TRANSFER (E, D), E) shall be the value
 16 of E. IF D is an array and E is an array of **rank** one, the value of TRANSFER (TRANSFER (E, D), E, SIZE (E))
 17 shall be the value of E.

18 **6 Examples.**

19 *Case (i):* TRANSFER (1082130432, 0.0) has the value 4.0 on a processor that represents the values 4.0 and
 20 1082130432 as the string of binary digits 0100 0000 1000 0000 0000 0000 0000 0000.

21 *Case (ii):* TRANSFER ([1.1, 2.2, 3.3], [(0.0, 0.0)]) is a complex rank-one array of length two whose first
 22 element has the value (1.1, 2.2) and whose second element has a real part with the value 3.3. The
 23 imaginary part of the second element is processor dependent.

24 *Case (iii):* TRANSFER ([1.1, 2.2, 3.3], [(0.0, 0.0)], 1) is a complex rank-one array of length one whose only
 25 element has the value (1.1, 2.2).

26 13.8.184 TRANSPOSE (MATRIX)

27 **1 Description.** Transpose of an array of **rank** two.

28 **2 Class.** **Transformational function.**

29 **3 Argument.** MATRIX shall be a rank-two array of any type.

30 **4 Result Characteristics.** The result is an array of the same type and type parameters as MATRIX and with
 31 **rank** two and shape $[n, m]$ where $[m, n]$ is the shape of MATRIX.

32 **5 Result Value.** Element (i, j) of the result has the value $MATRIX(j + LBOUND(MATRIX, 1) - 1, i +$
 33 $LBOUND(MATRIX, 2) - 1)$.

34 **6 Example.** If A is the array $\begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$, then TRANSPOSE (A) has the value $\begin{bmatrix} 1 & 4 & 7 \\ 2 & 5 & 8 \\ 3 & 6 & 9 \end{bmatrix}$.

35 13.8.185 TRIM (STRING)

36 **1 Description.** String without trailing blanks.

37 **2 Class.** **Transformational function.**

38 **3 Argument.** STRING shall be a character scalar.

39 **4 Result Characteristics.** Character with the same kind type parameter value as STRING and with a length

1 that is the length of STRING less the number of trailing blanks in STRING. If STRING contains no nonblank
2 characters, the result has zero length.

3 5 **Result Value.** The value of the result is the same as STRING except any trailing blanks are removed.

4 6 **Example.** TRIM (' A B ') has the value ' A B'.

5 13.8.186 UBOUND (ARRAY [, DIM, KIND])

6 1 **Description.** Upper bound(s).

7 2 **Class.** Inquiry function.

8 3 **Arguments.**

9 ARRAY shall be **assumed-rank** or an array. It shall not be an unallocated **allocatable** array or a pointer that
10 is not associated. If ARRAY is an **assumed-size array**, DIM shall be present with a value less than
11 the **rank** of ARRAY.

12 DIM (optional) shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the **rank** of ARRAY.
13 The corresponding **actual argument** shall not be an optional dummy argument, a disassociated
14 pointer, or an unallocated allocatable.

15 KIND (optional) shall be a scalar integer **constant expression**.

16 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of
17 KIND; otherwise the kind type parameter is that of default integer type. The result is scalar if DIM is present;
18 otherwise, the result is an array of **rank** one and size n , where n is the **rank** of ARRAY.

19 5 **Result Value.**

20 *Case (i):* If DIM is present, ARRAY is a **whole array**, and dimension DIM of ARRAY has nonzero extent,
21 the result has a value equal to the upper bound for subscript DIM of ARRAY. Otherwise, if DIM
22 is present and ARRAY is **assumed-rank**, the value of the result is as if ARRAY were a **whole array**,
23 with the extent of the final dimension of ARRAY when ARRAY is associated with an **assumed-size**
24 **array** being considered to be -1 . Otherwise, if DIM is present, the result has a value equal to the
25 number of elements in dimension DIM of ARRAY.

26 *Case (ii):* If ARRAY has rank zero, UBOUND (ARRAY) has a value that is a zero-sized array. Otherwise,
27 UBOUND (ARRAY) has a value whose i^{th} element is equal to UBOUND (ARRAY, i), for $i = 1, 2,$
28 \dots, n , where n is the **rank** of ARRAY. UBOUND (ARRAY, KIND=KIND) has a value whose i^{th}
29 element is equal to UBOUND (ARRAY, i , KIND=KIND), for $i = 1, 2, \dots, n$, where n is the
30 **rank** of ARRAY.

31 6 **Examples.** If A is declared by the statement

32 REAL A (2:3, 7:10)

33 then UBOUND (A) is [3, 10] and UBOUND (A, DIM = 2) is 10.

NOTE 13.26

If ARRAY is **assumed-rank** and has rank zero, DIM cannot be present since it cannot satisfy the requirement $1 \leq \text{DIM} \leq 0$.

34 13.8.187 UCBOUND (COARRAY [, DIM, KIND])

35 1 **Description.** Upper **cobound**(s) of a **coarray**.

36 2 **Class.** Inquiry function.

1 3 **Arguments.**

2 COARRAY shall be a [coarray](#) of any type. It may be a scalar or an array. If it is [allocatable](#) it shall be allocated.
 3 DIM (optional) shall be an integer scalar with a value in the range $1 \leq \text{DIM} \leq n$, where n is the [corank](#)
 4 of COARRAY. The corresponding [actual argument](#) shall not be an optional dummy argument, a
 5 disassociated pointer, or an unallocated allocatable.
 6 KIND (optional) shall be a scalar integer [constant expression](#).

7 4 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of
 8 KIND; otherwise, the kind type parameter is that of default integer type. The result is scalar if DIM is present;
 9 otherwise, the result is an array of [rank](#) one and size n , where n is the [corank](#) of COARRAY.

10 5 **Result Value.** The final upper [cobound](#) is the final [cosubscript](#) in the [cosubscript](#) list for the [coarray](#) that selects
 11 the [image](#) with [index](#) NUM_IMAGES().

12 *Case (i):* If DIM is present, the result has a value equal to the upper [cobound](#) for [codimension](#) DIM of
 13 COARRAY.

14 *Case (ii):* If DIM is absent, the result has a value whose i^{th} element is equal to the upper [cobound](#) for
 15 [codimension](#) i of COARRAY, for $i = 1, 2, \dots, n$, where n is the [corank](#) of COARRAY.

16 6 **Examples.** If NUM_IMAGES() has the value 30 and A is allocated by the statement

17 ALLOCATE (A [2:3, 0:7, *])

18 then UCOBOUND (A) is [3, 7, 2] and UCOBOUND (A, DIM=2) is 7. Note that the [cosubscripts](#) [3, 7, 2] do
 19 not correspond to an actual [image](#).

20 **13.8.188 UNPACK (VECTOR, MASK, FIELD)**

21 1 **Description.** Vector unpacked into an array.

22 2 **Class.** [Transformational function](#).

23 3 **Arguments.**

24 VECTOR shall be a rank-one array of any type. Its size shall be at least t where t is the number of true
 25 elements in MASK.

26 MASK shall be a logical array.

27 FIELD shall be of the same type and type parameters as VECTOR and shall be [conformable](#) with MASK.

28 4 **Result Characteristics.** The result is an array of the same type and type parameters as VECTOR and the
 29 same shape as MASK.

30 5 **Result Value.** The element of the result that corresponds to the i^{th} true element of MASK, in array element
 31 order, has the value VECTOR (i) for $i = 1, 2, \dots, t$, where t is the number of true values in MASK. Each other
 32 element has a value equal to FIELD if FIELD is scalar or to the corresponding element of FIELD if it is an array.

33 6 **Examples.** Particular values can be “scattered” to particular positions in an array by using UNPACK. If M is the

34 array $\begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}$, V is the array [1, 2, 3], and Q is the logical mask $\begin{bmatrix} . & \text{T} & . \\ \text{T} & . & . \\ . & . & \text{T} \end{bmatrix}$, where “T” represents true

35 and “.” represents false, then the result of UNPACK (V, MASK = Q, FIELD = M) has the value $\begin{bmatrix} 1 & 2 & 0 \\ 1 & 1 & 0 \\ 0 & 0 & 3 \end{bmatrix}$

36 and the result of UNPACK (V, MASK = Q, FIELD = 0) has the value $\begin{bmatrix} 0 & 2 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 3 \end{bmatrix}$.

13.8.189 VERIFY (STRING, SET [, BACK, KIND])

1 **Description.** Character set non-membership search.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 STRING shall be of type character.

5 SET shall be of type character with the same kind type parameter as STRING.

6 BACK (optional) shall be of type logical.

7 KIND (optional) shall be a scalar integer [constant expression](#).

8 **4 Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise the kind type parameter is that of default integer type.

9 **5 Result Value.**

10 *Case (i):* If BACK is absent or has the value false and if STRING contains at least one character that is not in SET, the value of the result is the position of the leftmost character of STRING that is not in SET.

11 *Case (ii):* If BACK is present with the value true and if STRING contains at least one character that is not in SET, the value of the result is the position of the rightmost character of STRING that is not in SET.

12 *Case (iii):* The value of the result is zero if each character in STRING is in SET or if STRING has zero length.

13 **6 Examples.**

14 *Case (i):* VERIFY ('ABBA', 'A') has the value 2.

15 *Case (ii):* VERIFY ('ABBA', 'A', BACK = [.TRUE.](#)) has the value 3.

16 *Case (iii):* VERIFY ('ABBA', 'AB') has the value 0.

13.9 Standard intrinsic modules

13.9.1 General

1 This part of ISO/IEC 1539 defines five standard intrinsic modules: a Fortran environment module, a set of three modules to support floating-point exceptions and IEEE arithmetic, and a module to support interoperability with the C programming language.

2 The intrinsic modules IEEE_EXCEPTIONS, IEEE_ARITHMETIC, and IEEE_FEATURES are described in Clause 14. The intrinsic module ISO_C_BINDING is described in Clause 15. The [module procedures](#) described in 13.9.2 are [pure](#).

NOTE 13.27

The types and procedures defined in [standard intrinsic](#) modules are not themselves [intrinsic](#).

3 A processor may extend the [standard intrinsic](#) modules to provide public entities in them in addition to those specified in this part of ISO/IEC 1539.

13.9.2 The ISO_FORTRAN_ENV intrinsic module

13.9.2.1 General

1 The intrinsic module ISO_FORTRAN_ENV provides public entities relating to the Fortran environment.

1 2 The processor shall provide the [named constants](#), derived type, and procedures described in subclause [13.9.2](#). In
2 the detailed descriptions below, procedure names are generic and not specific.

3 13.9.2.2 ATOMIC_INT_KIND

4 1 The value of the default integer scalar constant `ATOMIC_INT_KIND` is the kind type parameter value of type
5 integer variables for which the processor supports atomic operations specified by atomic subroutines.

6 13.9.2.3 ATOMIC_LOGICAL_KIND

7 1 The value of the default integer scalar constant `ATOMIC_LOGICAL_KIND` is the kind type parameter value
8 of type logical variables for which the processor supports atomic operations specified by atomic subroutines.

9 13.9.2.4 CHARACTER_KINDS

10 1 The values of the elements of the default integer array constant `CHARACTER_KINDS` are the kind values
11 supported by the processor for variables of type character. The order of the values is processor dependent. The
12 rank of the array is one, its lower bound is one, and its size is the number of character kinds supported.

13 13.9.2.5 CHARACTER_STORAGE_SIZE

14 1 The value of the default integer scalar constant `CHARACTER_STORAGE_SIZE` is the size expressed in bits
15 of the [character storage unit](#) ([16.5.3.2](#)).

16 13.9.2.6 COMPILER_OPTIONS ()

17 1 **Description.** Processor-dependent string describing the options that controlled the program translation phase.

18 2 **Class.** [Transformational function](#).

19 3 **Argument.** None.

20 4 **Result Characteristics.** Default character scalar with processor-dependent length.

21 5 **Result Value.** A processor-dependent value which describes the options that controlled the translation phase of
22 program execution. This value should include relevant information that could be useful for diagnosing problems
23 at a later date.

24 6 **Example.** `COMPILER_OPTIONS ()` might have the value `'/OPTIMIZE /FLOAT=IEEE'`.

25 13.9.2.7 COMPILER_VERSION ()

26 1 **Description.** Processor-dependent string identifying the program translation phase.

27 2 **Class.** [Transformational function](#).

28 3 **Argument.** None.

29 4 **Result Characteristics.** Default character scalar with processor-dependent length.

30 5 **Result Value.** A processor-dependent value that identifies the name and version of the program translation
31 phase of the processor. This value should include relevant information that could be useful for diagnosing problems
32 at a later date.

33 6 **Example.** `COMPILER_VERSION ()` might have the value `'Fast KL-10 Compiler Version 7'`.

NOTE 13.28

Relevant information that could be useful for diagnosing problems at a later date might include compiler release and patch level, default compiler arguments, environment variable values, and run time library requirements. A processor might include this information in an object file automatically, without the user needing to save the result of this function in a variable.

1 **13.9.2.8 ERROR_UNIT**

2 1 The value of the default integer scalar constant `ERROR_UNIT` identifies the processor-dependent [preconnected](#)
 3 [external unit](#) used for the purpose of error reporting (9.5). This [unit](#) may be the same as `OUTPUT_UNIT`. The
 4 value shall not be `-1`.

5 **13.9.2.9 EVENT_TYPE**

6 1 `EVENT_TYPE` is a derived type with private components. It is an extensible type with no type parameters.
 7 Each nonallocatable component is fully default-initialized.

8 2 A scalar variable of type `EVENT_TYPE` is an [event variable](#). The value of an event variable includes its event
 9 count, which is updated by execution of a sequence of `EVENT POST` or `EVENT WAIT` statements. The effect
 10 of each change is as if the intrinsic subroutine `ATOMIC_ADD` were executed with a variable that stores the
 11 event count as its `ATOM` argument. A coarray that is of type `EVENT_TYPE` may be referenced or defined
 12 during execution of a segment that is unordered relative to the execution of another segment in which that
 13 coarray is defined. The event count is of type integer with kind `ATOMIC_INT_KIND` from the intrinsic module
 14 [ISO_FORTRAN_ENV](#). The initial value of the event count of an event variable is zero.

15 C1302 A named variable of type `EVENT_TYPE` shall be a coarray. A named variable with a noncoarray
 16 subcomponent of type `EVENT_TYPE` shall be a coarray.

17 C1303 An [event variable](#) shall not appear in a variable definition context except as the *event-variable* in an
 18 `EVENT POST` or `EVENT WAIT` statement, as an *allocate-object*, or as an [actual argument](#) in a reference
 19 to a procedure with an [explicit interface](#) if the corresponding [dummy argument](#) has `INTENT (INOUT)`.

20 C1304 A variable with a nonpointer subobject of type `EVENT_TYPE` shall not appear in a variable definition
 21 context except as an *allocate-object* in an `ALLOCATE` statement without a `SOURCE=` specifier, as an
 22 *allocate-object* in a `DEALLOCATE` statement, or as an [actual argument](#) in a reference to a procedure
 23 with an [explicit interface](#) if the corresponding [dummy argument](#) has `INTENT (INOUT)`.

NOTE 13.29

The restrictions against changing an [event variable](#) except via `EVENT POST` and `EVENT WAIT` statements ensure the integrity of its value and facilitate efficient implementation, particularly when special synchronization is needed for correct event handling.

NOTE 13.30

Updates to variables via atomic subroutines are coherent but not necessarily consistent, so a processor might have to use extra synchronization to obtain the consistency required for the segments ordered by `EVENT POST` and `EVENT WAIT` statements.

24 **13.9.2.10 FILE_STORAGE_SIZE**

25 1 The value of the default integer scalar constant `FILE_STORAGE_SIZE` is the size expressed in bits of the [file](#)
 26 [storage unit](#) (9.3.5).

1 13.9.2.11 INPUT_UNIT

2 1 The value of the default integer scalar constant INPUT_UNIT identifies the same processor-dependent [external](#)
3 [unit preconnected](#) for sequential formatted input as the one identified by an asterisk in a [READ statement](#); this
4 [unit](#) is the one used for a [READ statement](#) that does not contain an input/output control list (9.6.4.3). The
5 value shall not be -1 .

6 13.9.2.12 INT8, INT16, INT32, and INT64

7 1 The values of these default integer scalar constants shall be those of the [kind type parameters](#) that specify an
8 INTEGER type whose storage size expressed in bits is 8, 16, 32, and 64 respectively. If, for any of these constants,
9 the processor supports more than one kind of that size, it is processor dependent which kind value is provided. If
10 the processor supports no kind of a particular size, that constant shall be equal to -2 if the processor supports
11 a kind with larger size and -1 otherwise.

12 13.9.2.13 INTEGER_KINDS

13 1 The values of the elements of the default integer array constant INTEGER_KINDS are the kind values supported
14 by the processor for variables of type integer. The order of the values is processor dependent. The rank of the
15 array is one, its lower bound is one, and its size is the number of integer kinds supported.

16 13.9.2.14 IOSTAT_END

17 1 The value of the default integer scalar constant IOSTAT_END is assigned to the variable specified in an [IOSTAT=](#)
18 [specifier](#) (9.11.5) if an end-of-file condition occurs during execution of an [input statement](#) and no error condition
19 occurs. This value shall be negative.

20 13.9.2.15 IOSTAT_EOR

21 1 The value of the default integer scalar constant IOSTAT_EOR is assigned to the variable specified in an [IOSTAT=](#)
22 [specifier](#) (9.11.5) if an end-of-record condition occurs during execution of an [input statement](#) and no end-of-file
23 or error condition occurs. This value shall be negative and different from the value of IOSTAT_END.

24 13.9.2.16 IOSTAT_INQUIRE_INTERNAL_UNIT

25 1 The value of the default integer scalar constant IOSTAT_INQUIRE_INTERNAL_UNIT is assigned to the
26 variable specified in an [IOSTAT= specifier](#) in an [INQUIRE statement](#) (9.10) if a *file-unit-number* identifies an
27 [internal unit](#) in that statement.

NOTE 13.31

This can only occur when a [defined input/output](#) procedure is called by the processor as the result of
executing a parent [data transfer statement](#) (9.6.4.8.2) for an [internal unit](#).

28 13.9.2.17 LOCK_TYPE

29 1 LOCK_TYPE is a [derived type](#) with private components; no component is allocatable or a pointer. It is an
30 [extensible type](#) with no [type parameters](#). Therefore it does not have the [BIND attribute](#) and is not a [sequence](#)
31 [type](#). All components have default initialization.

32 2 A scalar variable of type LOCK_TYPE is a lock variable. A lock variable can have one of two states: locked and
33 unlocked. The unlocked state is represented by the one value that is the default value of a LOCK_TYPE variable;
34 this is the value specified by the [structure constructor](#) LOCK_TYPE (). The locked state is represented by all
35 other values. The value of a lock variable can be changed with the [LOCK](#) and [UNLOCK](#) statements (8.5.8).

36 C1305 A named variable of type LOCK_TYPE shall be a [coarray](#). A named variable with a noncoarray
37 [subcomponent](#) of type LOCK_TYPE shall be a [coarray](#).

- 1 C1306 A lock variable shall not appear in a variable definition context except as the *lock-variable* in a **LOCK** or
2 **UNLOCK** statement, as an *allocate-object*, or as an **actual argument** in a reference to a procedure with
3 an **explicit interface** where the corresponding **dummy argument** has **INTENT (INOUT)**.
- 4 C1307 A variable with a subobject of type **LOCK_TYPE** shall not appear in a variable definition context except
5 as an *allocate-object* or as an **actual argument** in a reference to a procedure with an **explicit interface**
6 where the corresponding **dummy argument** has **INTENT (INOUT)**.

NOTE 13.32

The restrictions against changing a lock variable except via the **LOCK** and **UNLOCK** statements ensure the integrity of its value and facilitate efficient implementation, particularly when special synchronization is needed for correct lock operation.

7 13.9.2.18 LOGICAL_KINDS

- 8 1 The values of the elements of the default integer array constant **LOGICAL_KINDS** are the kind values supported
9 by the processor for variables of type logical. The order of the values is processor dependent. The rank of the
10 array is one, its lower bound is one, and its size is the number of logical kinds supported.

11 13.9.2.19 NUMERIC_STORAGE_SIZE

- 12 1 The value of the default integer scalar constant **NUMERIC_STORAGE_SIZE** is the size expressed in bits of the
13 **numeric storage unit** (16.5.3.2).

14 13.9.2.20 OUTPUT_UNIT

- 15 1 The value of the default integer scalar constant **OUTPUT_UNIT** identifies the same processor-dependent **external**
16 **unit preconnected** for sequential formatted output as the one identified by an asterisk in a **WRITE statement**
17 (9.6.4.3). The value shall not be -1 .

18 13.9.2.21 REAL_KINDS

- 19 1 The values of the elements of the default integer array constant **REAL_KINDS** are the kind values supported by
20 the processor for variables of type real. The order of the values is processor dependent. The rank of the array is
21 one, its lower bound is one, and its size is the number of real kinds supported.

22 13.9.2.22 REAL32, REAL64, and REAL128

- 23 1 The values of these default integer scalar **named constants** shall be those of the kind type parameters that specify
24 a **REAL** type whose storage size expressed in bits is 32, 64, and 128 respectively. If, for any of these constants,
25 the processor supports more than one kind of that size, it is processor dependent which kind value is provided. If
26 the processor supports no kind of a particular size, that constant shall be equal to -2 if the processor supports
27 kinds of a larger size and -1 otherwise.

28 13.9.2.23 STAT_LOCKED

- 29 1 The value of the default integer scalar constant **STAT_LOCKED** is assigned to the variable specified in a **STAT=**
30 **specifier** (8.5.9) of a **LOCK statement** if the **lock variable** is locked by the executing **image**.

31 13.9.2.24 STAT_LOCKED_OTHER_IMAGE

- 32 1 The value of the default integer scalar constant **STAT_LOCKED_OTHER_IMAGE** is assigned to the variable
33 specified in a **STAT= specifier** (8.5.9) of an **UNLOCK statement** if the **lock variable** is locked by another **image**.

1 **13.9.2.25 STAT_STOPPED_IMAGE**

2 1 The value of the default integer scalar constant `STAT_STOPPED_IMAGE` is assigned to the variable specified
3 in a `STAT= specifier` (6.7.4, 8.5.9) if execution of the statement with that specifier or argument requires syn-
4 chronization with an image that has initiated `normal termination`. This value shall be positive and different from
5 the value of `IOSTAT_INQUIRE_INTERNAL_UNIT`.

6 **13.9.2.26 STAT_UNLOCKED**

7 1 The value of the default integer scalar constant `STAT_UNLOCKED` is assigned to the variable specified in a
8 `STAT= specifier` (8.5.9) of an `UNLOCK statement` if the `lock variable` is unlocked.

1

(Blank page)

14 Exceptions and IEEE arithmetic

14.1 General

- 1 The intrinsic modules IEEE_EXCEPTIONS, IEEE_ARITHMETIC, and IEEE_FEATURES provide support for the facilities defined by ISO/IEC/IEEE 60559:2011* Whether the modules are provided is processor dependent. If the module IEEE_FEATURES is provided, which of the named constants defined in this part of ISO/IEC 1539 are included is processor dependent. The module IEEE_ARITHMETIC behaves as if it contained a [USE statement](#) for IEEE_EXCEPTIONS; everything that is public in IEEE_EXCEPTIONS is public in IEEE_ARITHMETIC.

NOTE 14.1

The types and procedures defined in these modules are not themselves intrinsic.

- 2 If IEEE_EXCEPTIONS or IEEE_ARITHMETIC is accessible in a [scoping unit](#), the exceptions IEEE_OVERFLOW and IEEE_DIVIDE_BY_ZERO are supported in the [scoping unit](#) for all kinds of real and complex IEEE floating-point data. Which other exceptions are supported can be determined by the [inquiry function](#) IEEE_SUPPORT_FLAG (14.11.45); whether control of [halting](#) is supported can be determined by the [inquiry function](#) IEEE_SUPPORT_HALTING. The extent of support of the other exceptions may be influenced by the accessibility of the [named constants](#) IEEE_INEXACT_FLAG, IEEE_INVALID_FLAG, and IEEE_UNDERFLOW_FLAG of the module IEEE_FEATURES. If a [scoping unit](#) has access to IEEE_UNDERFLOW_FLAG of IEEE_FEATURES, within the [scoping unit](#) the processor shall support underflow and return true from IEEE_SUPPORT_FLAG (IEEE_UNDERFLOW, X) for at least one kind of real. Similarly, if IEEE_INEXACT_FLAG or IEEE_INVALID_FLAG is accessible, within the [scoping unit](#) the processor shall support the exception and return true from the corresponding [inquiry function](#) for at least one kind of real. If IEEE_HALTING is accessible, within the [scoping unit](#) the processor shall support control of [halting](#) and return true from IEEE_SUPPORT_HALTING (FLAG) for the flag.

NOTE 14.2

IEEE_INVALID is not required to be supported whenever IEEE_EXCEPTIONS is accessed. This is to allow a processor whose arithmetic does not conform to ISO/IEC/IEEE 60559:2011 to provide support for overflow and divide_by_zero. On a processor which does support ISO/IEC/IEEE 60559:2011, invalid is an equally serious condition.

- 3 If a [scoping unit](#) does not access IEEE_FEATURES, IEEE_EXCEPTIONS, or IEEE_ARITHMETIC, the level of support is processor dependent, and need not include support for any exceptions. If a flag is signaling on entry to such a [scoping unit](#), the processor ensures that it is signaling on exit. If a flag is quiet on entry to such a [scoping unit](#), whether it is signaling on exit is processor dependent.
- 4 Additional ISO/IEC/IEEE 60559:2011 facilities are available from the module IEEE_ARITHMETIC. The extent of support may be influenced by the accessibility of the [named constants](#) of the module IEEE_FEATURES. If a [scoping unit](#) has access to IEEE_DATATYPE of IEEE_FEATURES, within the [scoping unit](#) the processor shall support IEEE arithmetic and return true from IEEE_SUPPORT_DATATYPE (X) (14.11.42) for at least one kind of real. Similarly, if IEEE_DENORMAL, IEEE_DIVIDE, IEEE_INF, IEEE_NAN, IEEE_ROUNDING, IEEE_SQRT, or IEEE_SUBNORMAL is accessible, within the [scoping unit](#) the processor shall support the feature and return true from the corresponding [inquiry function](#) for at least one kind of real. In the case of IEEE_ROUNDING, it shall return true for the rounding modes IEEE_NEAREST, IEEE_TO_ZERO, IEEE_UP, and IEEE_DOWN; support for [IEEE_AWAY](#) is also required if there is at least one kind of real X for

* Because ISO/IEC/IEEE 60559:2011 was originally an IEEE standard, its facilities are widely known as “IEEE arithmetic”, and this terminology is used by this part of ISO/IEC 1539.

1 which `IEEE_SUPPORT_DATATYPE` (X) is true and `RADIX` (X) is equal to ten. Note that the effect of
 2 `IEEE_DENORMAL` is the same as that of `IEEE_SUBNORMAL`.

3 5 Execution might be slowed on some processors by the support of some features. If `IEEE_EXCEPTIONS` or
 4 `IEEE_ARITHMETIC` is accessed but `IEEE_FEATURES` is not accessed, the supported subset of features is
 5 processor dependent. The processor's fullest support is provided when all of `IEEE_FEATURES` is accessed as in

```
6 USE, INTRINSIC :: IEEE_ARITHMETIC; USE, INTRINSIC :: IEEE_FEATURES
```

7 but execution might then be slowed by the presence of a feature that is not needed. In all cases, the extent of
 8 support can be determined by the [inquiry functions](#).

9 14.2 Derived types and constants defined in the modules

10 1 The modules `IEEE_EXCEPTIONS`, `IEEE_ARITHMETIC`, and `IEEE_FEATURES` define five derived types,
 11 whose components are all private. No [direct component](#) of any of these types is [allocatable](#) or a pointer.

12 2 The module `IEEE_EXCEPTIONS` defines the following types.

- 13 • `IEEE_FLAG_TYPE` is for identifying a particular exception flag. Its only possible values are those of
 14 [named constants](#) defined in the module: `IEEE_INVALID`, `IEEE_OVERFLOW`, `IEEE_DIVIDE_BY_-`
 15 `ZERO`, `IEEE_UNDERFLOW`, and `IEEE_INEXACT`. The module also defines the array [named constants](#)
 16 `IEEE_USUAL` = [`IEEE_OVERFLOW`, `IEEE_DIVIDE_BY_ZERO`, `IEEE_INVALID`] and `IEEE_-`
 17 `ALL` = [`IEEE_USUAL`, `IEEE_UNDERFLOW`, `IEEE_INEXACT`].
- 18 • `IEEE_MODES_TYPE` is for representing the floating-point modes.
- 19 • `IEEE_STATUS_TYPE` is for representing the floating-point status.

20 3 The module `IEEE_ARITHMETIC` defines the following.

- 21 • The type `IEEE_CLASS_TYPE`, for identifying a class of floating-point values. Its only possible
 22 values are those of [named constants](#) defined in the module: `IEEE_SIGNALING_NAN`, `IEEE_QUI-`
 23 `ET_NAN`, `IEEE_NEGATIVE_INF`, `IEEE_NEGATIVE_NORMAL`, `IEEE_NEGATIVE_DENORMAL`,
 24 `IEEE_NEGATIVE_ZERO`, `IEEE_POSITIVE_ZERO`, `IEEE_POSITIVE_SUBNORMAL`, `IEEE_POS-`
 25 `ITIVE_NORMAL`, `IEEE_POSITIVE_INF`, and `IEEE_OTHER_VALUE`. The named constants `IEEE_-`
 26 `NEGATIVE_DENORMAL` and `IEEE_POSITIVE_DENORMAL` are defined with the same value as
 27 [IEEE_NEGATIVE_SUBNORMAL](#) and [IEEE_POSITIVE_SUBNORMAL](#) respectively.
- 28 • The type `IEEE_ROUND_TYPE`, for identifying a particular rounding mode. Its only possible values
 29 are those of [named constants](#) defined in the module: `IEEE_NEAREST`, `IEEE_TO_ZERO`, `IEEE_UP`,
 30 `IEEE_DOWN`, and [IEEE_AWAY](#) for the rounding modes specified in ISO/IEC/IEEE 60559:2011, and
 31 `IEEE_OTHER` for any other mode.
- 32 • The [elemental operator](#) `==` for two values of one of these types to return true if the values are the same
 33 and false otherwise.
- 34 • The [elemental operator](#) `/=` for two values of one of these types to return true if the values differ and false
 35 otherwise.

36 4 The module `IEEE_FEATURES` defines the type `IEEE_FEATURES_TYPE`, for expressing the need for particu-
 37 lar ISO/IEC/IEEE 60559:2011 features. Its only possible values are those of [named constants](#) defined in the mod-
 38 ule: `IEEE_DATATYPE`, `IEEE_DENORMAL`, `IEEE_DIVIDE`, `IEEE_HALTING`, `IEEE_INEXACT_FLAG`,
 39 `IEEE_INF`, `IEEE_INVALID_FLAG`, `IEEE_NAN`, `IEEE_ROUNDING`, `IEEE_SQRT`, `IEEE_SUBNORMAL`,
 40 and `IEEE_UNDERFLOW_FLAG`.

41 14.3 The exceptions

42 1 The exceptions are the following.

- 1 • IEEE_OVERFLOW occurs in an intrinsic real addition, subtraction, multiplication, division, or conversion
2 by the intrinsic function REAL, as specified by ISO/IEC/IEEE 60559:2011 if IEEE_SUPPORT_DATA-
3 TYPE is true for the operands of the operation or conversion, and as determined by the processor otherwise.
4 It occurs in an intrinsic real exponentiation as determined by the processor. It occurs in a complex op-
5 eration, or conversion by the intrinsic function CMPLX, if it is caused by the calculation of the real or
6 imaginary part of the result.
- 7 • IEEE_DIVIDE_BY_ZERO occurs in a real division as specified by ISO/IEC/IEEE 60559:2011 if IEEE_-
8 SUPPORT_DATATYPE is true for the operands of the division, and as determined by the processor
9 otherwise. It is processor-dependent whether it occurs in a real exponentiation with a negative exponent.
10 It occurs in a complex division if it is caused by the calculation of the real or imaginary part of the result.
- 11 • IEEE_INVALID occurs when a real or complex operation or assignment is invalid; possible examples are
12 SQRT (X) when X is real and has a nonzero negative value, and conversion to an integer (by assignment,
13 an intrinsic procedure, or a procedure defined in an intrinsic module) when the result is too large to
14 be representable. In a numeric relational operation $x_1 \text{ rel-op } x_2$, if $x_1 + x_2$ is of type real and IEEE_-
15 SUPPORT_NAN ($x_1 + x_2$) is true, IEEE_INVALID shall signal as specified by ISO/IEC/IEEE 60559:2011
16 for the compareSignaling{relation} operations; that is, if x_1 and x_2 are unordered.
- 17 • IEEE_UNDERFLOW occurs when the result for an intrinsic real operation or assignment has an absolute
18 value less than a processor-dependent limit and loss of accuracy is detected, or the real or imaginary part
19 of the result for an intrinsic complex operation or assignment has an absolute value less than a processor-
20 dependent limit and loss of accuracy is detected.
- 21 • IEEE_INEXACT occurs when the result of a real or complex operation or assignment is not exact.

- 22 2 Each exception has a flag whose value is either quiet or signaling. The value can be determined by the subroutine
23 IEEE_GET_FLAG. Its initial value is quiet and it signals when the associated exception occurs. Its status can
24 also be changed by the subroutine IEEE_SET_FLAG or the subroutine IEEE_SET_STATUS. Once signaling
25 within a procedure, it remains signaling unless set quiet by an invocation of the subroutine IEEE_SET_FLAG
26 or the subroutine IEEE_SET_STATUS.
- 27 3 If a flag is signaling on entry to a procedure other than IEEE_GET_FLAG or IEEE_GET_STATUS, the
28 processor will set it to quiet on entry and restore it to signaling on return.

NOTE 14.3

If a flag signals during execution of a procedure, the processor shall not set it to quiet on return.

- 29 4 Evaluation of a [specification expression](#) might cause an exception to signal.
- 30 5 In a [scoping unit](#) that has access to IEEE_EXCEPTIONS or IEEE_ARITHMETIC, if an intrinsic procedure
31 or a procedure defined in an intrinsic module executes normally, the values of the flags IEEE_OVERFLOW,
32 IEEE_DIVIDE_BY_ZERO, and IEEE_INVALID shall be as on entry to the procedure, even if one or more of
33 them signals during the calculation. If a real or complex result is too large for the procedure to handle, IEEE_-
34 OVERFLOW may signal. If a real or complex result is a NaN because of an invalid operation (for example,
35 LOG (-1.0)), IEEE_INVALID may signal. Similar rules apply to format processing and to intrinsic operations:
36 no signaling flag shall be set quiet and no quiet flag shall be set signaling because of an intermediate calculation
37 that does not affect the result.
- 38 6 In a sequence of statements that has no invocations of IEEE_GET_FLAG, IEEE_SET_FLAG, IEEE_GET_-
39 STATUS, IEEE_SET_HALTING_MODE, or IEEE_SET_STATUS, if the execution of an operation would
40 cause an exception to signal but after execution of the sequence no value of a variable depends on the operation,
41 whether the exception is signaling is processor dependent. For example, when Y has the value zero, whether the
42 code

```

43     X = 1.0/Y
44     X = 3.0

```

45 signals IEEE_DIVIDE_BY_ZERO is processor dependent. Another example is the following:

```

1      REAL, PARAMETER :: X=0.0, Y=6.0
2      IF (1.0/X == Y) PRINT *, 'Hello world'

```

3 where the processor is permitted to discard the [IF statement](#) because the logical expression can never be true
4 and no value of a variable depends on it.

5 7 An exception shall not signal if this could arise only during execution of an operation beyond those required or
6 permitted by the standard. For example, the statement

```

7      IF (F (X) > 0.0) Y = 1.0/Z

```

8 shall not signal IEEE_DIVIDE_BY_ZERO when both F (X) and Z are zero and the statement

```

9      WHERE (A > 0.0) A = 1.0/A

```

10 shall not signal IEEE_DIVIDE_BY_ZERO. On the other hand, when X has the value 1.0 and Y has the value
11 0.0, the expression

```

12      X>0.00001 .OR. X/Y>0.00001

```

13 is permitted to cause the signaling of IEEE_DIVIDE_BY_ZERO.

14 8 The processor need not support IEEE_INVALID, IEEE_UNDERFLOW, and IEEE_INEXACT. If an exception
15 is not supported, its flag is always quiet. The [inquiry function](#) IEEE_SUPPORT_FLAG can be used to inquire
16 whether a particular flag is supported.

17 14.4 The rounding modes

18 1 ISO/IEC/IEEE 60559:2011 specifies a binary rounding mode that affects floating-point arithmetic with radix
19 two, and a decimal rounding mode that affects floating-point arithmetic with radix ten. Unqualified references
20 to the rounding mode with respect to a particular arithmetic operation or operands refers to the mode for the
21 radix of the operation or operands, and other unqualified references to the rounding mode refers to both binary
22 and decimal rounding modes.

23 2 ISO/IEC/IEEE 60559:2011 specifies five possible modes for rounding:

- 24 • IEEE_NEAREST rounds the exact result to the nearest representable value;
- 25 • IEEE_TO_ZERO rounds the exact result towards zero to the next representable value;
- 26 • IEEE_UP rounds the exact result towards $+\infty$ to the next representable value;
- 27 • IEEE_DOWN rounds the exact result towards $-\infty$ to the next representable value;
- 28 • IEEE_AWAY rounds the exact result away from zero to the next representable value; ISO/IEC/IEEE
29 60559:2011 requires this mode for decimal floating-point, but it is optional for binary floating-point.

30 3 The subroutine [IEEE_GET_ROUNDING_MODE](#) can be used to get the rounding modes. The initial rounding
31 modes are processor dependent.

32 4 If the processor supports the alteration of the rounding modes during execution, the subroutine [IEEE_SET_-](#)
33 [ROUNDING_MODE](#) can be used to alter them. The [inquiry function](#) IEEE_SUPPORT_ROUNDING can be
34 used to inquire whether this facility is available for a particular mode. The [inquiry function](#) IEEE_SUPPORT_-
35 IO can be used to inquire whether rounding for base conversion in formatted input/output ([9.5.6.16](#), [9.6.2.13](#),
36 [10.7.2.3.8](#)) is as specified in ISO/IEC/IEEE 60559:2011.

37 5 In a procedure other than [IEEE_SET_ROUNDING_MODE](#) or [IEEE_SET_STATUS](#), the processor shall not
38 change the rounding modes on entry, and on return shall ensure that the rounding modes are the same as they
39 were on entry.

NOTE 14.4

Within a program, all literal constants that have the same form have the same value (4.1.4). Therefore, the value of a literal constant is not affected by the rounding modes.

14.5 Underflow mode

- 1 Some processors allow control during program execution of whether underflow produces a subnormal number in conformance with ISO/IEC/IEEE 60559:2011 (gradual underflow) or produces zero instead (abrupt underflow). On some processors, floating-point performance is typically better in abrupt underflow mode than in gradual underflow mode.
- 2 Control over the underflow mode is exercised by invocation of `IEEE_SET_UNDERFLOW_MODE`. The subroutine `IEEE_GET_UNDERFLOW_MODE` can be used to get the underflow mode. The [inquiry function](#) `IEEE_SUPPORT_UNDERFLOW_CONTROL` can be used to inquire whether this facility is available. The initial underflow mode is processor dependent. In a procedure other than `IEEE_SET_UNDERFLOW_MODE` or `IEEE_SET_STATUS`, the processor shall not change the underflow mode on entry, and on return shall ensure that the underflow mode is the same as it was on entry.
- 3 The underflow mode affects only floating-point calculations whose type is that of an X for which `IEEE_SUPPORT_UNDERFLOW_CONTROL` returns true.

14.6 Halting

- 1 Some processors allow control during program execution of whether to abort or continue execution after an exception. Such control is exercised by invocation of the subroutine `IEEE_SET_HALTING_MODE`. Halting is not precise and may occur any time after the exception has occurred. The [inquiry function](#) `IEEE_SUPPORT_HALTING` can be used to inquire whether this facility is available. The initial halting mode is processor dependent. In a procedure other than `IEEE_SET_HALTING_MODE` or `IEEE_SET_STATUS`, the processor shall not change the halting mode on entry, and on return shall ensure that the halting mode is the same as it was on entry.

14.7 The floating-point modes and status

- 1 The values of the rounding modes, [underflow mode](#), and [halting mode](#) are collectively called the floating-point modes. The values of all the supported flags for exceptions and the floating-point modes are collectively called the floating-point status. The floating-point modes can be stored in a scalar variable of type `IEEE_MODES_TYPE` with the subroutine `IEEE_GET_MODES` and restored with the subroutine `IEEE_SET_MODES`. The floating-point status can be stored in a scalar variable of type `IEEE_STATUS_TYPE` with the subroutine `IEEE_GET_STATUS` and restored with the subroutine `IEEE_SET_STATUS`. There are no facilities for finding the values of particular flags represented by such a variable.

NOTE 14.5

Each [image](#) has its own floating-point status (2.3.4).

NOTE 14.6

Some processors hold all these flags and modes in one or two status registers that can be obtained and set as a whole faster than all individual flags and modes can be obtained and set. These procedures are provided to exploit this feature.

NOTE 14.7

The processor is required to ensure that a call to a Fortran procedure does not change the floating-point status other than by setting exception flags to signaling.

14.8 Exceptional values

1 ISO/IEC/IEEE 60559:2011 specifies the following exceptional floating-point values.

- Subnormal values have very small absolute values and reduced precision.
- Infinite values (+infinity and -infinity) are created by overflow or division by zero.
- Not-a-Number (NaN) values are undefined values or values created by an invalid operation.

2 A value that does not fall into the above classes is called a normal number.

3 The functions IEEE_IS_FINITE, IEEE_IS_NAN, IEEE_IS_NEGATIVE, and IEEE_IS_NORMAL are provided to test whether a value is finite, NaN, negative, or normal. The function IEEE_VALUE is provided to generate an IEEE number of any class, including an infinity or a NaN. The inquiry functions IEEE_SUPPORT_SUBNORMAL, IEEE_SUPPORT_INF, and IEEE_SUPPORT_NAN are provided to determine whether these facilities are available for a particular kind of real.

14.9 IEEE arithmetic

1 The inquiry function IEEE_SUPPORT_DATATYPE can be used to inquire whether IEEE arithmetic is supported for a particular kind of real. Complete conformance with ISO/IEC/IEEE 60559:2011 is not required, but

- the normal numbers shall be exactly those of an ISO/IEC/IEEE 60559:2011 floating-point format,
- for at least one rounding mode, the intrinsic operations of addition, subtraction and multiplication shall conform whenever the operands and result specified by ISO/IEC/IEEE 60559:2011 are normal numbers,
- the IEEE function abs shall be provided by the intrinsic function ABS,
- the IEEE operation rem shall be provided by the function IEEE_REM, and
- the IEEE functions copysign, scalb, logb, nextafter, and unordered shall be provided by the functions IEEE_COPY_SIGN, IEEE_SCALB, IEEE_LOGB, IEEE_NEXT_AFTER, and IEEE_UNORDERED, respectively,

for that kind of real.

2 The inquiry function IEEE_SUPPORT_NAN is provided to inquire whether the processor supports IEEE NaNs. Where these are supported, the result of the intrinsic operations +, -, and *, and the functions IEEE_REM and IEEE_RINT from the intrinsic module IEEE_ARITHMETIC, shall conform to ISO/IEC/IEEE 60559:2011 when the result is an IEEE NaN.

3 The inquiry function IEEE_SUPPORT_INF is provided to inquire whether the processor supports IEEE infinities. Where these are supported, the result of the intrinsic operations +, -, and *, and the functions IEEE_REM and IEEE_RINT from the intrinsic module IEEE_ARITHMETIC, shall conform to ISO/IEC/IEEE 60559:2011 when exactly one operand or the result specified by ISO/IEC/IEEE 60559:2011 is an IEEE infinity.

4 The inquiry function IEEE_SUPPORT_SUBNORMAL is provided to inquire whether the processor supports subnormal numbers. Where these are supported, the result of the intrinsic operations +, -, and *, and the functions IEEE_REM and IEEE_RINT from the intrinsic module IEEE_ARITHMETIC, shall conform to ISO/IEC/IEEE 60559:2011 when the result specified by ISO/IEC/IEEE 60559:2011 is subnormal, or any operand is subnormal and either the result is not an IEEE infinity or IEEE_SUPPORT_INF is true.

5 The inquiry function IEEE_SUPPORT_DIVIDE is provided to inquire whether, on kinds of real for which IEEE_SUPPORT_DATATYPE returns true, the intrinsic division operation conforms to ISO/IEC/IEEE

- 1 60559:2011 when both operands and the result specified by ISO/IEC/IEEE 60559:2011 are normal numbers.
 2 If `IEEE_SUPPORT_NAN` is also true for a particular kind of real, the intrinsic division operation on that kind
 3 conforms to ISO/IEC/IEEE 60559:2011 when the result specified by ISO/IEC/IEEE 60559:2011 is a NaN. If
 4 `IEEE_SUPPORT_INF` is also true for a particular kind of real, the intrinsic division operation on that kind
 5 conforms to ISO/IEC/IEEE 60559:2011 when one operand or the result specified by ISO/IEC/IEEE 60559:2011
 6 is an IEEE infinity. If `IEEE_SUPPORT_SUBNORMAL` is also true for a particular kind of real, the intrinsic divi-
 7 sion operation on that kind conforms to ISO/IEC/IEEE 60559:2011 when the result specified by ISO/IEC/IEEE
 8 60559:2011 is subnormal, or when any operand is subnormal and either the result specified by ISO/IEC/IEEE
 9 60559:2011 is not an infinity or `IEEE_SUPPORT_INF` is true.
- 10 6 ISO/IEC/IEEE 60559:2011 specifies a square root function that returns negative real zero for the square root of
 11 negative real zero and has certain accuracy requirements. The [inquiry function](#) `IEEE_SUPPORT_SQRT` can
 12 be used to inquire whether the intrinsic function `SQRT` conforms to ISO/IEC/IEEE 60559:2011 for a particular
 13 kind of real. If `IEEE_SUPPORT_NAN` is also true for a particular kind of real, the intrinsic function `SQRT`
 14 on that kind conforms to ISO/IEC/IEEE 60559:2011 when the result specified by ISO/IEC/IEEE 60559:2011
 15 is a NaN. If `IEEE_SUPPORT_INF` is also true for a particular kind of real, the intrinsic function `SQRT` on
 16 that kind conforms to ISO/IEC/IEEE 60559:2011 when the result specified by ISO/IEC/IEEE 60559:2011 is an
 17 IEEE infinity. If `IEEE_SUPPORT_SUBNORMAL` is also true for a particular kind of real, the intrinsic function
 18 `SQRT` on that kind conforms to ISO/IEC/IEEE 60559:2011 when the argument is subnormal.
- 19 7 The [inquiry function](#) `IEEE_SUPPORT_STANDARD` is provided to inquire whether the processor supports all
 20 the ISO/IEC/IEEE 60559:2011 facilities defined in this part of ISO/IEC 1539 for a particular kind of real.

21 14.10 Summary of the procedures

- 22 1 For all of the procedures defined in the modules, the arguments shown are the names that shall be used for
 23 [argument keywords](#) if the keyword form is used for the [actual arguments](#).
- 24 2 A procedure classified in 14.10 as an [inquiry function](#) depends on the properties of one or more of its arguments
 25 instead of their values; in fact, these argument values may be undefined. Unless the description of one of these
 26 [inquiry functions](#) states otherwise, these arguments are permitted to be unallocated [allocatable](#) variables or
 27 pointers that are undefined or [disassociated](#). A procedure that is classified as a [transformational function](#) is
 28 neither an [inquiry function](#) nor [elemental](#).
- 29 3 In the Class column of Tables 14.1 and 14.2,
 30 E indicates that the procedure is an [elemental function](#),
 31 ES indicates that the procedure is an [elemental subroutine](#),
 32 I indicates that the procedure is an [inquiry function](#),
 33 PS indicates that the procedure is a [pure subroutine](#),
 34 S indicates that the procedure is an impure subroutine, and
 35 T indicates that the procedure is in a [transformational function](#).

Table 14.1: **IEEE_ARITHMETIC module procedure summary**

Procedure	Arguments	Class	Description
<code>IEEE_CLASS</code>	(X)	E	Classify number.
<code>IEEE_COPY_SIGN</code>	(X, Y)	E	Copy sign.
<code>IEEE_FMA</code>	(A, B, C)	E	Fused multiply-add operation.
<code>IEEE_GET_ROUNDING_MODE</code>	(ROUND_VALUE [, RADIX])	S	Get rounding mode.
<code>IEEE_GET_UNDERFLOW_- MODE</code>	(GRADUAL)	S	Get underflow mode .
<code>IEEE_INT</code>	(A, ROUND [, KIND])	E	Conversion to integer type.
<code>IEEE_IS_FINITE</code>	(X)	E	Whether a value is finite.
<code>IEEE_IS_NAN</code>	(X)	E	Whether a value is an IEEE NaN .

Table 14.1: IEEE_ARITHMETIC module procedure summary (cont.)

Procedure	Arguments	Class	Description
IEEE_IS_NEGATIVE	(X)	E	Whether a value is negative.
IEEE_IS_NORMAL	(X)	E	Whether a value is a normal number.
IEEE_LOGB	(X)	E	Exponent.
IEEE_MAX_NUM	(X, Y)	E	Maximum numeric value.
IEEE_MAX_NUM_MAG	(X, Y)	E	Maximum magnitude numeric value.
IEEE_MIN_NUM	(X, Y)	E	Minimum numeric value.
IEEE_MIN_NUM_MAG	(X, Y)	E	Minimum magnitude numeric value.
IEEE_NEXT_AFTER	(X, Y)	E	Adjacent machine number.
IEEE_NEXT_DOWN	(X)	E	Adjacent lower machine number.
IEEE_NEXT_UP	(X)	E	Adjacent higher machine number.
IEEE_QUIET_EQ	(A, B)	E	Quiet compares equal.
IEEE_QUIET_GE	(A, B)	E	Quiet compares greater than or equal.
IEEE_QUIET_GT	(A, B)	E	Quiet compares greater than.
IEEE_QUIET_LE	(A, B)	E	Quiet compares less than or equal.
IEEE_QUIET_LT	(A, B)	E	Quiet compares less than.
IEEE_QUIET_NE	(A, B)	E	Quiet compares not equal.
IEEE_REAL	(A [, KIND])	E	Conversion to real type.
IEEE_REM	(X, Y)	E	Exact remainder.
IEEE_RINT	(X)	E	Round to integer.
IEEE_SCALB	(X, I)	E	$X \times 2^I$.
IEEE_SELECTED_REAL_KIND	([P, R, RADIX])	T	IEEE kind type parameter value.
IEEE_SET_ROUNDING_MODE	(ROUND_VALUE [, RADIX])	S	Set rounding mode.
IEEE_SET_UNDERFLOW_- MODE	(GRADUAL)	S	Set underflow mode .
IEEE_SIGNBIT	(X)	E	Test sign bit.
IEEE_SUPPORT_DATATYPE	([X])	I	Query IEEE arithmetic support.
IEEE_SUPPORT_DENORMAL	([X])	I	Query subnormal number support.
IEEE_SUPPORT_DIVIDE	([X])	I	Query IEEE division support.
IEEE_SUPPORT_INF	([X])	I	Query IEEE infinity support.
IEEE_SUPPORT_IO	([X])	I	Query IEEE formatting support.
IEEE_SUPPORT_NAN	([X])	I	Query IEEE NaN support.
IEEE_SUPPORT_ROUNDING	(ROUND_VALUE [, X])	I	Query IEEE rounding support.
IEEE_SUPPORT_SQRT	([X])	I	Query IEEE square root support.
IEEE_SUPPORT_SUBNORMAL	([X])	I	Query subnormal number support.
IEEE_SUPPORT_STANDARD	([X])	I	Query IEEE standard support.
IEEE_SUPPORT_UNDER- FLOW_CONTROL	([X])	I	Query underflow control support.
IEEE_UNORDERED	(X, Y)	E	Whether two values are unordered.
IEEE_VALUE	(X, CLASS)	E	Return number in a class.

Table 14.2: IEEE_EXCEPTIONS module procedure summary

Procedure	Arguments	Class	Description
IEEE_GET_FLAG	(FLAG, FLAG_VALUE)	ES	Get an exception flag.
IEEE_GET_HALTING_MODE	(FLAG, HALTING)	ES	Get a halting mode .
IEEE_GET_MODES	(MODES)	S	Get floating-point modes.
IEEE_GET_STATUS	(STATUS_VALUE)	S	Get floating-point state.
IEEE_SET_FLAG	(FLAG, FLAG_VALUE)	PS	Set an exception flag.
IEEE_SET_HALTING_MODE	(FLAG, HALTING)	PS	Set a halting mode .
IEEE_SET_MODES	(MODES)	S	Set floating-point modes.
IEEE_SET_STATUS	(STATUS_VALUE)	S	Restore floating-point state.
IEEE_SUPPORT_FLAG	(FLAG [, X])	I	Query exception support.

Table 14.2: IEEE_EXCEPTIONS module procedure summary (cont.)

Procedure	Arguments	Class	Description
IEEE_SUPPORT_HALTING	(FLAG)	I	Query halting mode support.

1 4 In the intrinsic module IEEE_ARITHMETIC, the [elemental](#) functions listed are provided for all reals X and Y.

2 14.11 Specifications of the procedures

3 14.11.1 General

4 1 In the detailed descriptions in 14.11, procedure names are generic and are not specific. All the functions are pure.
5 All dummy arguments have [INTENT \(IN\)](#) if the intent is not stated explicitly. In the examples, it is assumed
6 that the processor supports IEEE arithmetic for default real.

7 2 For the [elemental](#) functions of IEEE_ARITHMETIC that return a floating-point result, if X or Y has a value
8 that is an infinity or a NaN, the result shall be consistent with the general rules in 6.1 and 6.2 of ISO/IEC/IEEE
9 60559:2011. For example, the result for an infinity shall be constructed as the limiting case of the result with a
10 value of arbitrarily large magnitude, if such a limit exists.

11 3 A program may contain statements that, if executed, would violate the requirements listed in a **Restriction**
12 paragraph.

NOTE 14.8

A program can avoid violating those requirements by using [IF constructs](#) to check whether particular features are supported. For example,

```

IF (IEEE_SUPPORT_DATATYPE (X)) THEN
  C = IEEE_CLASS (X)
ELSE
  ...
END IF

```

avoids invoking [IEEE_CLASS](#) except on a processor which supports that facility.

13 14.11.2 IEEE_CLASS (X)

14 1 **Description.** Classify number.

15 2 **Class.** [Elemental](#) function.

16 3 **Argument.** X shall be of type real.

17 4 **Restriction.** IEEE_CLASS (X) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) has the value false.

18 5 **Result Characteristics.** [IEEE_CLASS_TYPE](#).

19 6 **Result Value.** The result value shall be IEEE_SIGNALING_NAN or IEEE_QUIET_NAN if IEEE_SUP-
20 PORT_NAN (X) has the value true and the value of X is a signaling or quiet NaN, respectively. The result
21 value shall be IEEE_NEGATIVE_INF or IEEE_POSITIVE_INF if IEEE_SUPPORT_INF (X) has the value
22 true and the value of X is negative or positive infinity, respectively. The result value shall be [IEEE_NEG-](#)
23 [ATIVE_SUBNORMAL](#) or [IEEE_POSITIVE_SUBNORMAL](#) if [IEEE_SUPPORT_SUBNORMAL](#) (X) has the
24 value true and the value of X is a negative or positive subnormal value, respectively. The result value shall
25 be IEEE_NEGATIVE_NORMAL, IEEE_NEGATIVE_ZERO, IEEE_POSITIVE_ZERO, or IEEE_POSIT-

1 IVE_NORMAL if the value of X is negative normal, negative zero, positive zero, or positive normal, respectively.
 2 Otherwise, the result value shall be IEEE_OTHER_VALUE.

3 7 **Example.** IEEE_CLASS (−1.0) has the value IEEE_NEGATIVE_NORMAL.

NOTE 14.9

The result value IEEE_OTHER_VALUE is useful on systems that are almost IEEE-compatible, but do not implement all of it. For example, if a subnormal value is encountered on a system that does not support them.

4 14.11.3 IEEE_COPY_SIGN (X, Y)

5 1 **Description.** Copy sign.

6 2 **Class.** [Elemental](#) function.

7 3 **Arguments.** The arguments shall be of type real.

8 4 **Restriction.** IEEE_COPY_SIGN (X, Y) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) or
 9 IEEE_SUPPORT_DATATYPE (Y) has the value false.

10 5 **Result Characteristics.** Same as X.

11 6 **Result Value.** The result has the absolute value of X with the sign of Y. This is true even for IEEE special
 12 values, such as a NaN or an infinity (on processors supporting such values).

13 7 **Example.** The value of IEEE_COPY_SIGN (X, 1.0) is ABS (X) even when X is a NaN.

14 14.11.4 IEEE_FMA (A, B, C)

15 1 **Description.** Fused multiply-add operation.

16 2 **Class.** [Elemental](#) function.

17 3 **Arguments.**

18 A shall be of type real.

19 B shall be of the same type and kind type parameter as A.

20 C shall be of the same type and kind type parameter as A.

21 4 **Restriction.** IEEE_FMA (A, B, C) shall not be invoked if IEEE_SUPPORT_DATATYPE (A) has the value
 22 false.

23 5 **Result Characteristics.** Same as A.

24 6 **Result Value.** The result has the value specified by ISO/IEC/IEEE 60559:2011 for the fusedMultiplyAdd
 25 operation; that is, when the result is in range, its value is equal to the mathematical value of $(A \times B) + C$ rounded
 26 to the representation method of A according to the rounding mode. IEEE_OVERFLOW, IEEE_UNDERFLOW,
 27 and IEEE_INEXACT shall be signaled according to the final step in the calculation and not by any intermediate
 28 calculation.

29 7 **Example.** The value of IEEE_FMA (TINY (0.0), TINY (0.0), 1.0), when the rounding mode is IEEE_-
 30 NEAREST, is equal to 1.0; only the IEEE_INEXACT exception is signaled.

31 14.11.5 IEEE_GET_FLAG (FLAG, FLAG_VALUE)

32 1 **Description.** Get an exception flag.

33 2 **Class.** [Elemental](#) subroutine.

1 3 **Arguments.**

2 FLAG shall be of type `IEEE_FLAG_TYPE`. It specifies the exception flag to be obtained.
 3 FLAG_VALUE shall be of type logical. It is an **INTENT (OUT)** argument. If the value of FLAG is `IEEE_`
 4 `INVALID`, `IEEE_OVERFLOW`, `IEEE_DIVIDE_BY_ZERO`, `IEEE_UNDERFLOW`, or `IEEE_`
 5 `INEXACT`, FLAG_VALUE is assigned the value true if the corresponding exception flag is signaling
 6 and is assigned the value false otherwise.

7 4 **Example.** Following `CALL IEEE_GET_FLAG (IEEE_OVERFLOW, FLAG_VALUE)`, FLAG_VALUE is
 8 true if the `IEEE_OVERFLOW` flag is signaling and is false if it is quiet.

9 **14.11.6 IEEE_GET_HALTING_MODE (FLAG, HALTING)**

10 1 **Description.** Get a [halting mode](#).

11 2 **Class.** [Elemental](#) subroutine.

12 3 **Arguments.**

13 FLAG shall be of type `IEEE_FLAG_TYPE`. It specifies the exception flag. It shall have one of the val-
 14 ues `IEEE_INVALID`, `IEEE_OVERFLOW`, `IEEE_DIVIDE_BY_ZERO`, `IEEE_UNDERFLOW`,
 15 or `IEEE_INEXACT`.

16 HALTING shall be of type logical. It is an **INTENT (OUT)** argument. It is assigned the value true if the
 17 exception specified by FLAG will cause halting. Otherwise, it is assigned the value false.

18 4 **Example.** To store the [halting mode](#) for `IEEE_OVERFLOW`, do a calculation without halting, and restore the
 19 [halting mode](#) later:

```
20     USE, INTRINSIC :: IEEE_ARITHMETIC
21     LOGICAL HALTING
22     ...
23     CALL IEEE_GET_HALTING_MODE (IEEE_OVERFLOW, HALTING) ! Store halting mode
24     CALL IEEE_SET_HALTING_MODE (IEEE_OVERFLOW, .FALSE.) ! No halting
25     ... ! calculation without halting
26     CALL IEEE_SET_HALTING_MODE (IEEE_OVERFLOW, HALTING) ! Restore halting mode
```

27 **14.11.7 IEEE_GET_MODES (MODES)**

28 1 **Description.** Get floating-point modes.

29 2 **Class.** Subroutine.

30 3 **Argument.** MODES shall be a scalar of type `IEEE_MODES_TYPE`. It is an **INTENT (OUT)** argument that
 31 is assigned the value of the floating-point modes.

32 4 **Example.** To save the floating-point modes, do a calculation with specific rounding and [underflow](#) modes, and
 33 restore them later:

```
34     USE, INTRINSIC :: IEEE_ARITHMETIC
35     TYPE (IEEE_MODES_TYPE) SAVE_MODES
36     ...
37     CALL IEEE_GET_MODES (SAVE_MODES) ! Save all modes.
38     CALL IEEE_SET_ROUNDING_MODE (IEEE_TO_ZERO)
39     CALL IEEE_SET_UNDERFLOW_MODE (GRADUAL=.FALSE.)
40     ... ! calculation with abrupt round-to-zero.
41     CALL IEEE_SET_MODES (SAVE_MODES) ! Restore all modes.
```

14.11.8 IEEE_GET_ROUNDING_MODE (ROUND_VALUE [, RADIX])

1 **Description.** Get rounding mode.

2 **Class.** Subroutine.

3 **Arguments.**

4 ROUND_VALUE shall be a scalar of type `IEEE_ROUND_TYPE`. It is an `INTENT (OUT)` argument. It is
5 assigned the value `IEEE_NEAREST`, `IEEE_TO_ZERO`, `IEEE_UP`, `IEEE_DOWN`, or `IEEE_`
6 `AWAY` if the corresponding rounding mode is in operation and `IEEE_OTHER` otherwise.

7 RADIX (optional) shall be an integer scalar with the value two or ten. If RADIX is present with the value ten,
8 the rounding mode queried is the decimal rounding mode, otherwise it is the binary rounding mode.

9 **Example.** To save the binary rounding mode, do a calculation with round to nearest, and restore the rounding
10 mode later:

```
11      USE, INTRINSIC :: IEEE_ARITHMETIC
12      TYPE (IEEE_ROUND_TYPE) ROUND_VALUE
13      ...
14      CALL IEEE_GET_ROUNDING_MODE (ROUND_VALUE) ! Store the rounding mode
15      CALL IEEE_SET_ROUNDING_MODE (IEEE_NEAREST)
16      ... ! calculation with round to nearest
17      CALL IEEE_SET_ROUNDING_MODE (ROUND_VALUE) ! Restore the rounding mode
```

14.11.9 IEEE_GET_STATUS (STATUS_VALUE)

1 **Description.** Get floating-point state.

2 **Class.** Subroutine.

3 **Argument.** STATUS_VALUE shall be a scalar of type `IEEE_STATUS_TYPE`. It is an `INTENT (OUT)`
4 argument. It is assigned the value of the floating-point status.

5 **Example.** To store all the exception flags, do a calculation involving exception handling, and restore them later:

```
6      USE, INTRINSIC :: IEEE_ARITHMETIC
7      TYPE (IEEE_STATUS_TYPE) STATUS_VALUE
8      ...
9      CALL IEEE_GET_STATUS (STATUS_VALUE) ! Get the flags
10     CALL IEEE_SET_FLAG (IEEE_ALL, .FALSE.) ! Set the flags quiet.
11     ... ! calculation involving exception handling
12     CALL IEEE_SET_STATUS (STATUS_VALUE) ! Restore the flags
```

14.11.10 IEEE_GET_UNDERFLOW_MODE (GRADUAL)

1 **Description.** Get `underflow mode`.

2 **Class.** Subroutine.

3 **Argument.** GRADUAL shall be a logical scalar. It is an `INTENT (OUT)` argument. It is assigned the value
4 true if the `underflow mode` is gradual underflow, and false if the `underflow mode` is abrupt underflow.

5 **Restriction.** `IEEE_GET_UNDERFLOW_MODE` shall not be invoked unless `IEEE_SUPPORT_UNDER-`
6 `FLOW_CONTROL (X)` is true for some X.

1 5 **Example.** After CALL [IEEE_SET_UNDERFLOW_MODE \(.FALSE.\)](#), a subsequent CALL [IEEE_GET_UNDERFLOW_MODE \(GRADUAL\)](#) will set GRADUAL to false.

3 14.11.11 IEEE_INT (A, ROUND [, KIND])

4 1 **Description.** Conversion to integer type.

5 2 **Class.** [Elemental](#) function.

6 3 **Arguments.**

7 A shall be of type real.

8 ROUND shall be of type [IEEE_ROUND_TYPE](#).

9 KIND (optional) shall be a scalar integer constant expression.

10 4 **Restriction.** [IEEE_INT \(A, ROUND, KIND\)](#) shall not be invoked if [IEEE_SUPPORT_DATATYPE \(A\)](#) has the value false.

12 5 **Result Characteristics.** Integer. If KIND is present, the kind type parameter is that specified by the value of KIND; otherwise, the kind type parameter is that of default integer.

14 6 **Result Value.** The result has the value specified by ISO/IEC/IEEE 60559:2011 for the `convertToInteger{round}` or the `convertToIntegerExact{round}` operation; the processor shall consistently choose which operation it provides. That is, the value of A is converted to an integer according to the rounding mode specified by ROUND; if this value is representable in the representation method of the result, the result has this value, otherwise [IEEE_INVALID](#) is signaled and the result is processor dependent. If the processor provides the `convertToIntegerExact` operation, [IEEE_INVALID](#) did not signal, and the value of the result differs from that of A, [IEEE_INEXACT](#) will be signaled.

21 7 **Example.** The value of [IEEE_INT \(12.5, IEEE_UP\)](#) is 13; [IEEE_INEXACT](#) will be signaled if the processor provides the `convertToIntegerExact` operation.

23 14.11.12 IEEE_IS_FINITE (X)

24 1 **Description.** Whether a value is finite.

25 2 **Class.** [Elemental](#) function.

26 3 **Argument.** X shall be of type real.

27 4 **Restriction.** [IEEE_IS_FINITE \(X\)](#) shall not be invoked if [IEEE_SUPPORT_DATATYPE \(X\)](#) has the value false.

29 5 **Result Characteristics.** Default logical.

30 6 **Result Value.** The result has the value true if the value of X is finite, that is, [IEEE_CLASS \(X\)](#) has one of the values [IEEE_NEGATIVE_NORMAL](#), [IEEE_NEGATIVE_SUBNORMAL](#), [IEEE_NEGATIVE_ZERO](#), [IEEE_POSITIVE_ZERO](#), [IEEE_POSITIVE_SUBNORMAL](#), or [IEEE_POSITIVE_NORMAL](#); otherwise, the result has the value false.

34 7 **Example.** [IEEE_IS_FINITE \(1.0\)](#) has the value true.

35 14.11.13 IEEE_IS_NAN (X)

36 1 **Description.** Whether a value is an [IEEE NaN](#).

37 2 **Class.** [Elemental](#) function.

38 3 **Argument.** X shall be of type real.

1 4 **Restriction.** IEEE_IS_NAN (X) shall not be invoked if IEEE_SUPPORT_NAN (X) has the value false.

2 5 **Result Characteristics.** Default logical.

3 6 **Result Value.** The result has the value true if the value of X is an IEEE NaN; otherwise, it has the value false.

4 7 **Example.** IEEE_IS_NAN (SQRT (−1.0)) has the value true if IEEE_SUPPORT_SQRT (1.0) has the value
5 true.

6 14.11.14 IEEE_IS_NEGATIVE (X)

7 1 **Description.** Whether a value is negative.

8 2 **Class.** Elemental function.

9 3 **Argument.** X shall be of type real.

10 4 **Restriction.** IEEE_IS_NEGATIVE (X) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) has the
11 value false.

12 5 **Result Characteristics.** Default logical.

13 6 **Result Value.** The result has the value true if IEEE_CLASS (X) has one of the values IEEE_NEGATIVE_-
14 NORMAL, IEEE_NEGATIVE_SUBNORMAL, IEEE_NEGATIVE_ZERO or IEEE_NEGATIVE_INF; oth-
15 erwise, the result has the value false.

16 7 **Example.** IEEE_IS_NEGATIVE (0.0) has the value false.

17 14.11.15 IEEE_IS_NORMAL (X)

18 1 **Description.** Whether a value is a normal number.

19 2 **Class.** Elemental function.

20 3 **Argument.** X shall be of type real.

21 4 **Restriction.** IEEE_IS_NORMAL (X) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) has the
22 value false.

23 5 **Result Characteristics.** Default logical.

24 6 **Result Value.** The result has the value true if IEEE_CLASS (X) has one of the values IEEE_NEGATIVE_-
25 NORMAL, IEEE_NEGATIVE_ZERO, IEEE_POSITIVE_ZERO or IEEE_POSITIVE_NORMAL; otherwise,
26 the result has the value false.

27 7 **Example.** IEEE_IS_NORMAL (SQRT (−1.0)) has the value false if IEEE_SUPPORT_SQRT (1.0) has the
28 value true.

29 14.11.16 IEEE_LOGB (X)

30 1 **Description.** Exponent.

31 2 **Class.** Elemental function.

32 3 **Argument.** X shall be of type real.

33 4 **Restriction.** IEEE_LOGB (X) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) has the value false.

34 5 **Result Characteristics.** Same as X.

35 6 **Result Value.**

1 *Case (i):* If the value of X is neither zero, infinity, nor NaN, the result has the value of the unbiased exponent
2 of X. Note: this value is equal to `EXPONENT (X) - 1`.

3 *Case (ii):* If $X=0$, the result is $-\text{infinity}$ if `IEEE_SUPPORT_INF (X)` is true and $-\text{HUGE (X)}$ otherwise;
4 `IEEE_DIVIDE_BY_ZERO` signals.

5 *Case (iii):* If `IEEE_SUPPORT_INF (X)` is true and X is infinite, the result is $+\text{infinity}$.

6 *Case (iv):* If `IEEE_SUPPORT_NAN (X)` is true and X is a NaN, the result is a NaN.

7 7 **Example.** `IEEE_LOGB (-1.1)` has the value 0.0.

8 14.11.17 IEEE_MAX_NUM (X, Y)

9 1 **Description.** Maximum numeric value.

10 2 **Class.** `Elemental` function.

11 3 **Arguments.**

12 X shall be of type real.

13 Y shall be of the same type and kind type parameter as X.

14 4 **Restriction.** `IEEE_MAX_NUM` shall not be invoked if `IEEE_SUPPORT_DATATYPE (X)` has the value
15 false.

16 5 **Result Characteristics.** Same as X.

17 6 **Result Value.** The result has the value specified for the `maxNum` operation in ISO/IEC/IEEE 60559:2011;
18 that is,

- 19 • if $X < Y$ the result has the value of Y;
- 20 • if $Y < X$ the result has the value of X;
- 21 • if exactly one of X and Y is a quiet NaN the result has the value of the other argument;
- 22 • if both X and Y are quiet NaNs the result is either X or Y (processor dependent);
- 23 • if one or both of X and Y are signaling NaNs, `IEEE_INVALID` signals and the result is a NaN.

24 7 Except when X or Y is a signaling NaN, no exception is signaled.

25 8 **Example.** The value of `IEEE_MAX_NUM (1.5, IEEE_VALUE (IEEE_QUIET_NAN))` is 1.5.

26 14.11.18 IEEE_MAX_NUM_MAG (X, Y)

27 1 **Description.** Maximum magnitude numeric value.

28 2 **Class.** `Elemental` function.

29 3 **Arguments.**

30 X shall be of type real.

31 Y shall be of the same type and kind type parameter as X.

32 4 **Restriction.** `IEEE_MAX_NUM_MAG` shall not be invoked if `IEEE_SUPPORT_DATATYPE (X)` has the
33 value false.

34 5 **Result Characteristics.** Same as X.

35 6 **Result Value.** The result has the value specified for the `maxNumMag` operation in ISO/IEC/IEEE 60559:2011;
36 that is,

- 37 • if $\text{ABS (X)} < \text{ABS (Y)}$ the result has the value of Y;
- 38 • if $\text{ABS (Y)} < \text{ABS (X)}$ the result has the value of X;

- 1 • if exactly one of X and Y is a quiet NaN the result has the value of the other argument;
- 2 • if both X and Y are quiet NaNs the result is either X or Y (processor dependent);
- 3 • if one or both of X and Y are signaling NaNs, IEEE_INVALID signals and the result is a NaN.

4 7 Except when X or Y is a signaling NaN, no exception is signaled.

5 8 **Example.** The value of IEEE_MAX_NUM_MAG (1.5, -2.5) is -2.5.

6 **14.11.19 IEEE_MIN_NUM (X, Y)**

7 1 **Description.** Minimum numeric value.

8 2 **Class.** [Elemental](#) function.

9 3 **Arguments.**

10 X shall be of type real.

11 Y shall be of the same type and kind type parameter as X.

12 4 **Restriction.** IEEE_MIN_NUM shall not be invoked if [IEEE_SUPPORT_DATATYPE](#) (X) has the value false.

13 5 **Result Characteristics.** Same as X.

14 6 **Result Value.**

15 7 The result has the value specified for the minNum operation in ISO/IEC/IEEE 60559:2011; that is,

- 16 • if $X < Y$ the result has the value of X;
- 17 • if $Y < X$ the result has the value of Y;
- 18 • if exactly one of X and Y is a quiet NaN the result has the value of the other argument;
- 19 • if both X and Y are quiet NaNs the result is either X or Y (processor dependent);
- 20 • if one or both of X and Y are signaling NaNs, IEEE_INVALID signals and the result is a NaN.

21 8 Except when X or Y is a signaling NaN, no exception is signaled.

22 9 **Example.** The value of IEEE_MIN_NUM (1.5, [IEEE_VALUE](#) (IEEE_QUIET_NAN)) is 1.5.

23 **14.11.20 IEEE_MIN_NUM_MAG (X, Y)**

24 1 **Description.** Minimum magnitude numeric value.

25 2 **Class.** [Elemental](#) function.

26 3 **Arguments.**

27 X shall be of type real.

28 Y shall be of the same type and kind type parameter as X.

29 4 **Restriction.** IEEE_MIN_NUM_MAG shall not be invoked if [IEEE_SUPPORT_DATATYPE](#) (X) has the
30 value false.

31 5 **Result Characteristics.** Same as X.

32 6 **Result Value.** The result has the value specified for the minNumMag operation in ISO/IEC/IEEE 60559:2011;
33 that is,

- 34 • if $ABS(X) < ABS(Y)$ the result has the value of X;
- 35 • if $ABS(Y) < ABS(X)$ the result has the value of Y;
- 36 • if exactly one of X and Y is a quiet NaN the result has the value of the other argument;

- 1 • if both X and Y are quiet NaNs the result is either X or Y (processor dependent);
- 2 • if one or both of X and Y are signaling NaNs, IEEE_INVALID signals and the result is a NaN.

3 7 Except when X or Y is a signaling NaN, no exception is signaled.

4 8 **Example.** The value of IEEE_MIN_NUM_MAG (1.5, -2.5) is 1.5.

5 14.11.21 IEEE_NEXT_AFTER (X, Y)

6 1 **Description.** Adjacent machine number.

7 2 **Class.** Elemental function.

8 3 **Arguments.** The arguments shall be of type real.

9 4 **Restriction.** IEEE_NEXT_AFTER (X, Y) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) or
10 IEEE_SUPPORT_DATATYPE (Y) has the value false.

11 5 **Result Characteristics.** Same as X.

12 6 **Result Value.**

13 *Case (i):* If $X == Y$, the result is X and no exception is signaled.

14 *Case (ii):* If $X \neq Y$, the result has the value of the next representable neighbor of X in the direction of Y.
15 The neighbors of zero (of either sign) are both nonzero. IEEE_OVERFLOW is signaled when
16 X is finite but IEEE_NEXT_AFTER (X, Y) is infinite; IEEE_UNDERFLOW is signaled when
17 IEEE_NEXT_AFTER (X, Y) is subnormal; in both cases, IEEE_INEXACT signals.

18 7 **Example.** The value of IEEE_NEXT_AFTER (1.0, 2.0) is $1.0 + \text{EPSILON}(X)$.

19 14.11.22 IEEE_NEXT_DOWN (X)

20 1 **Description.** Adjacent lower machine number.

21 2 **Class.** Elemental function.

22 3 **Argument.** X shall be of type real.

23 4 **Restriction.** IEEE_NEXT_DOWN (X) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) has the
24 value false. IEEE_NEXT_DOWN (-HUGE (X)) shall not be invoked if IEEE_SUPPORT_INF (X) has the
25 value false.

26 5 **Result Characteristics.** Same as X.

27 6 **Result Value.** The result has the value specified for the nextDown operation in ISO/IEC/IEEE 60559:2011;
28 that is, it is the greatest value in the representation method of X that compares less than X, except when X is
29 equal to $-\infty$ the result has the value $-\infty$, and when X is a NaN the result is a NaN. If X is a signaling NaN,
30 IEEE_INVALID signals; otherwise, no exception is signaled.

31 7 **Example.** If IEEE_SUPPORT_SUBNORMAL (0.0) is true, the value of IEEE_NEXT_DOWN (+0.0) is the
32 negative subnormal number with least magnitude.

33 14.11.23 IEEE_NEXT_UP (X)

34 1 **Description.** Adjacent higher machine number.

35 2 **Class.** Elemental function.

36 3 **Argument.** X shall be of type real.

1 4 **Restriction.** IEEE_NEXT_UP (X) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) has the value
2 false. IEEE_NEXT_UP (HUGE (X)) shall not be invoked if IEEE_SUPPORT_INF (X) has the value false.

3 5 **Result Characteristics.** Same as X.

4 6 **Result Value.** The result has the value specified for the nextUp operation in ISO/IEC/IEEE 60559:2011; that
5 is, it is the least value in the representation method of X that compares greater than X, except when X is
6 equal to $+\infty$ the result has the value $+\infty$, and when X is a NaN the result is a NaN. If X is a signaling NaN,
7 IEEE_INVALID_signals; otherwise, no exception is signaled.

8 7 **Example.** If IEEE_SUPPORT_INF (X) is true, the value of IEEE_NEXT_UP (HUGE (X)) is $+\infty$.

9 14.11.24 IEEE_QUIET_EQ (A, B)

10 1 **Description.** Quiet compares equal.

11 2 **Class.** Elemental function.

12 3 **Arguments.**

13 A shall be of type real.

14 B shall have the same type and type parameters as A.

15 4 **Restriction.** IEEE_QUIET_EQ (A) shall not be invoked if IEEE_SUPPORT_DATATYPE (A) has the value
16 false.

17 5 **Result Characteristics.** Default logical.

18 6 **Result Value.** The result has the value specified for the compareQuietEqual operation in ISO/IEC/IEEE
19 60559:2011; that is, it is true if and only if A compares equal to B; if A or B is a NaN, the result will be false
20 and no exception will be signaled.

21 7 **Example.** IEEE_QUIET_EQ (1.0, IEEE_VALUE (IEEE_QUIET_NAN)) has the value false and no exception
22 is signaled.

23 14.11.25 IEEE_QUIET_GE (A, B)

24 1 **Description.** Quiet compares greater than or equal.

25 2 **Class.** Elemental function.

26 3 **Arguments.**

27 A shall be of type real.

28 B shall have the same type and type parameters as A.

29 4 **Restriction.** IEEE_QUIET_GE (A) shall not be invoked if IEEE_SUPPORT_DATATYPE (A) has the value
30 false.

31 5 **Result Characteristics.** Default logical.

32 6 **Result Value.** The result has the value specified for the compareQuietGreaterEqual operation in ISO/IEC/IEEE
33 60559:2011; that is, it is true if and only if A compares greater than or equal to B; if A or B is a NaN, the result
34 will be false and no exception will be signaled.

35 7 **Example.** IEEE_QUIET_GE (1.0, IEEE_VALUE (IEEE_QUIET_NAN)) has the value false and no exception
36 is signaled.

14.11.26 IEEE_QUIET_GT (A, B)

1 **Description.** Quiet compares greater than.

2 **Class.** [Elemental](#) function.

3 **Arguments.**

4 A shall be of type real.

5 B shall have the same type and type parameters as A.

6 **Restriction.** IEEE_QUIET_GT (A) shall not be invoked if [IEEE_SUPPORT_DATATYPE](#) (A) has the value false.

7 **Result Characteristics.** Default logical.

8 **Result Value.** The result has the value specified for the compareQuietGreater operation in ISO/IEC/IEEE 60559:2011; that is, it is true if and only if A compares greater than B; if A or B is a NaN, the result will be false and no exception will be signaled.

9 **Example.** IEEE_QUIET_GT (1.0, [IEEE_VALUE](#) (IEEE_QUIET_NAN)) has the value false and no exception is signaled.

14.11.27 IEEE_QUIET_LE (A, B)

10 **Description.** Quiet compares less than or equal.

11 **Class.** [Elemental](#) function.

12 **Arguments.**

13 A shall be of type real.

14 B shall have the same type and type parameters as A.

15 **Restriction.** IEEE_QUIET_LE (A) shall not be invoked if [IEEE_SUPPORT_DATATYPE](#) (A) has the value false.

16 **Result Characteristics.** Default logical.

17 **Result Value.** The result has the value specified for the compareQuietLessEqual operation in ISO/IEC/IEEE 60559:2011; that is, it is true if and only if A compares less than or equal to B; if A or B is a NaN, the result will be false and no exception will be signaled.

18 **Example.** IEEE_QUIET_LE (1.0, [IEEE_VALUE](#) (IEEE_QUIET_NAN)) has the value false and no exception is signaled.

14.11.28 IEEE_QUIET_LT (A, B)

19 **Description.** Quiet compares less than.

20 **Class.** [Elemental](#) function.

21 **Arguments.**

22 A shall be of type real.

23 B shall have the same type and type parameters as A.

24 **Restriction.** IEEE_QUIET_LT (A) shall not be invoked if [IEEE_SUPPORT_DATATYPE](#) (A) has the value false.

25 **Result Characteristics.** Default logical.

1 6 **Result Value.** The result has the value specified for the compareQuietLess operation in ISO/IEC/IEEE
2 60559:2011; that is, it is true if and only if A compares less than B; if A or B is a NaN, the result will be
3 false and no exception will be signaled.

4 7 **Example.** IEEE_QUIET_LT (1.0, IEEE_VALUE (IEEE_QUIET_NAN)) has the value false and no exception
5 is signaled.

6 14.11.29 IEEE_QUIET_NE (A, B)

7 1 **Description.** Quiet compares not equal.

8 2 **Class.** Elemental function.

9 3 **Arguments.**

10 A shall be of type real.

11 B shall have the same type and type parameters as A.

12 4 **Restriction.** IEEE_QUIET_NE (A) shall not be invoked if IEEE_SUPPORT_DATATYPE (A) has the value
13 false.

14 5 **Result Characteristics.** Default logical.

15 6 **Result Value.** The result has the value specified for the compareQuietNotEqual operation in ISO/IEC/IEEE
16 60559:2011; that is, it is true if and only if A compares not equal to B; if A or B is a NaN, the result will be true
17 and no exception will be signaled.

18 7 **Example.** IEEE_QUIET_NE (1.0, IEEE_VALUE (IEEE_QUIET_NAN)) has the value true and no exception
19 is signaled.

20 14.11.30 IEEE_REAL (A, [, KIND])

21 1 **Description.** Conversion to real type.

22 2 **Class.** Elemental function.

23 3 **Arguments.**

24 A shall be of type integer or real.

25 KIND (optional) shall be a scalar integer constant expression.

26 4 **Restriction.** IEEE_REAL shall not be invoked if A is of type real and IEEE_SUPPORT_DATATYPE (A)
27 has the value false, or if IEEE_SUPPORT_DATATYPE (IEEE_REAL (A, KIND)) has the value false.

28 5 **Result Characteristics.** Real. If KIND is present, the kind type parameter is that specified by the value of
29 KIND; otherwise, the kind type parameter is that of default real.

30 6 **Result Value.** The result has the same value as A if that value is representable in the representation method
31 of the result, and is rounded according to the rounding mode otherwise. This shall be consistent with the
32 specification of ISO/IEC/IEEE 60559:2011 for the convertFromInt operation when A is of type integer, and with
33 the convertFormat operation otherwise.

34 7 **Example.** The value of IEEE_REAL (123) is 123.0.

35 14.11.31 IEEE_REM (X, Y)

36 1 **Description.** Exact remainder.

37 2 **Class.** Elemental function.

1 3 **Arguments.** The arguments shall be of type real.

2 4 **Restriction.** IEEE_REM (X, Y) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) or IEEE_SUPPORT_DATATYPE (Y) has the value false.

4 5 **Result Characteristics.** Real with the kind type parameter of whichever argument has the greater precision.

5 6 **Result Value.** The result value, regardless of the rounding mode, shall be exactly $X - Y*N$, where N is the integer nearest to the exact value X/Y ; whenever $|N - X/Y| = \frac{1}{2}$, N shall be even. If the result value is zero, the sign shall be that of X. This function computes the remainder operation specified in ISO/IEC/IEEE 60559:2011.

8 7 **Examples.** The value of IEEE_REM (4.0, 3.0) is 1.0, the value of IEEE_REM (3.0, 2.0) is -1.0, and the value of IEEE_REM (5.0, 2.0) is 1.0.

10 14.11.32 IEEE_RINT (X [, ROUND])

11 1 **Description.** Round to integer.

12 2 **Class.** Elemental function.

13 3 **Arguments.**

14 X shall be of type real.

15 ROUND (optional) shall be of type IEEE_ROUND_TYPE.

16 4 **Restriction.** IEEE_RINT (X) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) has the value false.

17 5 **Result Characteristics.** Same as X.

18 6 **Result Value.** If ROUND is present, the value of the result is the value of X rounded to an integer according to the mode specified by ROUND; this is the ISO/IEC/IEEE 60559:2011 operation roundToInteger{rounding}. Otherwise, the value of the result is that specified for the operation roundIntegralToExact in ISO/IEC/IEEE 60559:2011; this is the value of X rounded to an integer according to the rounding mode. If the result has the value zero, the sign is that of X.

23 7 **Examples.** If the rounding mode is round to nearest, the value of IEEE_RINT (1.1) is 1.0. The value of IEEE_RINT (1.1, IEEE_UP) is 2.0.

25 14.11.33 IEEE_SCALB (X, I)

26 1 **Description.** $X \times 2^I$.

27 2 **Class.** Elemental function.

28 3 **Arguments.**

29 X shall be of type real.

30 I shall be of type integer.

31 4 **Restriction.** IEEE_SCALB (X) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) has the value false.

32 5 **Result Characteristics.** Same as X.

33 6 **Result Value.**

34 *Case (i):* If $X \times 2^I$ is representable as a normal number, the result has this value.

35 *Case (ii):* If X is finite and $X \times 2^I$ is too large, the IEEE_OVERFLOW exception shall occur. If IEEE_SUPPORT_INF (X) is true, the result value is infinity with the sign of X; otherwise, the result value is SIGN (HUGE (X), X).

1 *Case (iii):* If $X \times 2^I$ is too small and there is loss of accuracy, the IEEE_UNDERFLOW exception shall occur.
 2 The result is the representable number having a magnitude nearest to $|2^I|$ and the same sign as X.

3 *Case (iv):* If X is infinite, the result is the same as X; no exception signals.

4 7 **Example.** The value of IEEE_SCALB (1.0, 2) is 4.0.

5 14.11.34 IEEE_SELECTED_REAL_KIND ([P, R, RADIX])

6 1 **Description.** IEEE kind type parameter value.

7 2 **Class.** Transformational function.

8 3 **Arguments.** At least one argument shall be present.

9 P (optional) shall be an integer scalar.

10 R (optional) shall be an integer scalar.

11 RADIX (optional) shall be an integer scalar.

12 4 **Result Characteristics.** Default integer scalar.

13 5 **Result Value.** If P or R is absent, the result value is the same as if it were present with the value zero. If
 14 RADIX is absent, there is no requirement on the radix of the selected kind. The result has a value equal to a
 15 value of the kind type parameter of an ISO/IEC/IEEE 60559:2011 floating-point format with decimal precision,
 16 as returned by the intrinsic function PRECISION, of at least P digits, a decimal exponent range, as returned
 17 by the intrinsic function RANGE, of at least R, and a radix, as returned by the intrinsic function RADIX, of
 18 RADIX, if such a kind type parameter is available on the processor.

19 6 Otherwise, the result is -1 if the processor supports an IEEE real type with radix RADIX and exponent range
 20 of at least R but not with precision of at least P, -2 if the processor supports an IEEE real type with radix
 21 RADIX and precision of at least P but not with exponent range of at least R, -3 if the processor supports an
 22 IEEE real type with radix RADIX but with neither precision of at least P nor exponent range of at least R, -4 if
 23 the processor supports an IEEE real type with radix RADIX and either precision of at least P or exponent range
 24 of at least R but not both together, and -5 if the processor supports no IEEE real type with radix RADIX.

25 7 If more than one kind type parameter value meets the criteria, the value returned is the one with the smallest
 26 decimal precision, unless there are several such values, in which case the smallest of these kind values is returned.

27 8 **Example.** IEEE_SELECTED_REAL_KIND (6, 30) has the value KIND (0.0) on a machine that supports
 28 ISO/IEC/IEEE 60559:2011 single precision arithmetic for its default real approximation method.

29 14.11.35 IEEE_SET_FLAG (FLAG, FLAG_VALUE)

30 1 **Description.** Set an exception flag.

31 2 **Class.** Pure subroutine.

32 3 **Arguments.**

33 FLAG shall be a scalar or array of type IEEE_FLAG_TYPE. If a value of FLAG is IEEE_INVALID,
 34 IEEE_OVERFLOW, IEEE_DIVIDE_BY_ZERO, IEEE_UNDERFLOW, or IEEE_INEXACT,
 35 the corresponding exception flag is assigned a value. No two elements of FLAG shall have the same
 36 value.

37 FLAG_VALUE shall be a logical scalar or array. It shall be conformable with FLAG. If an element has the value
 38 true, the corresponding flag is set to be signaling; otherwise, the flag is set to be quiet.

39 4 **Example.** CALL IEEE_SET_FLAG (IEEE_OVERFLOW, .TRUE.) sets the IEEE_OVERFLOW flag to be
 40 signaling.

14.11.36 IEEE_SET_HALTING_MODE (FLAG, HALTING)

1 **Description.** Set a [halting mode](#).

2 **Class.** Pure subroutine.

3 **Arguments.**

4 FLAG shall be a scalar or array of type [IEEE_FLAG_TYPE](#). It shall have only the values [IEEE_INVALID](#), [IEEE_OVERFLOW](#), [IEEE_DIVIDE_BY_ZERO](#), [IEEE_UNDERFLOW](#), or [IEEE_INEXACT](#). No two elements of FLAG shall have the same value.

5 HALTING shall be a logical scalar or array. It shall be [conformable](#) with FLAG. If an element has the value true, the corresponding exception specified by FLAG will cause halting. Otherwise, execution will continue after this exception.

6 **Restriction.** [IEEE_SET_HALTING_MODE](#) (FLAG, HALTING) shall not be invoked if [IEEE_SUPPORT_HALTING](#) (FLAG) has the value false.

7 **Example.** CALL [IEEE_SET_HALTING_MODE](#) ([IEEE_DIVIDE_BY_ZERO](#), [.TRUE.](#)) causes halting after a [divide_by_zero](#) exception.

14.11.37 IEEE_SET_MODES (MODES)

1 **Description.** Set floating-point modes.

2 **Class.** Subroutine.

3 **Argument.** MODES shall be a scalar of type [IEEE_MODES_TYPE](#). Its value shall be one that was assigned by a previous invocation of [IEEE_GET_MODES](#) to its MODES argument. The floating-point modes ([14.7](#)) are restored to the state at that invocation.

4 **Example.**

To save the floating-point modes, do a calculation with specific rounding and [underflow](#) modes, and restore them later:

```

24     USE, INTRINSIC :: IEEE_ARITHMETIC
25     TYPE (IEEE\_MODES\_TYPE) SAVE_MODES
26     ...
27     CALL IEEE\_GET\_MODES (SAVE_MODES) ! Save all modes.
28     CALL IEEE\_SET\_ROUNDING\_MODE (IEEE\_TO\_ZERO)
29     CALL IEEE\_SET\_UNDERFLOW\_MODE (GRADUAL=.FALSE.)
30     ... ! calculation with abrupt round-to-zero.
31     CALL IEEE\_SET\_MODES (SAVE_MODES) ! Restore all modes.

```

14.11.38 IEEE_SET_ROUNDING_MODE (ROUND_VALUE [, RADIX])

1 **Description.** Set rounding mode.

2 **Class.** Subroutine.

3 **Arguments.**

4 ROUND_VALUE shall be a scalar of type [IEEE_ROUND_TYPE](#). It specifies the mode to be set.

5 RADIX (optional) shall be an integer scalar with the value two or ten. If RADIX is present with the value ten, the rounding mode set is the decimal rounding mode, otherwise it is the binary rounding mode.

6 **Restriction.** [IEEE_SET_ROUNDING_MODE](#) (ROUND_VALUE) shall not be invoked unless [IEEE_SUPPORT_ROUNDING](#) (ROUND_VALUE, X) is true for some X such that [IEEE_SUPPORT_DATATYPE](#) (X)

1 is true. IEEE_SET_ROUNDING_MODE (ROUND_VALUE, RADIX) shall not be invoked unless IEEE_
 2 SUPPORT_ROUNDING (ROUND_VALUE, X) is true for some X with radix RADIX such that IEEE_SUP-
 3 PORT_DATATYPE (X) is true.

4 5 **Example.** To save the binary rounding mode, do a calculation with round to nearest, and restore the rounding
 5 mode later:

```
6         USE, INTRINSIC :: IEEE_ARITHMETIC
7         TYPE (IEEE_ROUND_TYPE) ROUND_VALUE
8         ...
9         CALL IEEE_GET_ROUNDING_MODE (ROUND_VALUE) ! Store the rounding mode
10        CALL IEEE_SET_ROUNDING_MODE (IEEE_NEAREST)
11        ... ! calculation with round to nearest
12        CALL IEEE_SET_ROUNDING_MODE (ROUND_VALUE) ! Restore the rounding mode
```

13 14.11.39 IEEE_SET_STATUS (STATUS_VALUE)

14 1 **Description.** Restore floating-point state.

15 2 **Class.** Subroutine.

16 3 **Argument.** STATUS_VALUE shall be a scalar of type IEEE_STATUS_TYPE. Its value shall be one that was
 17 assigned by a previous invocation of IEEE_GET_STATUS to its STATUS_VALUE argument. The floating-
 18 point status (14.7 is restored to the state at that invocation).

19 4 **Example.** To store all the exceptions flags, do a calculation involving exception handling, and restore them
 20 later:

```
21        USE, INTRINSIC :: IEEE_EXCEPTIONS
22        TYPE (IEEE_STATUS_TYPE) STATUS_VALUE
23        ...
24        CALL IEEE_GET_STATUS (STATUS_VALUE) ! Store the flags
25        CALL IEEE_SET_FLAG (IEEE_ALL, .FALSE.) ! Set them quiet
26        ... ! calculation involving exception handling
27        CALL IEEE_SET_STATUS (STATUS_VALUE) ! Restore the flags
```

28 14.11.40 IEEE_SET_UNDERFLOW_MODE (GRADUAL)

29 1 **Description.** Set [underflow mode](#).

30 2 **Class.** Subroutine.

31 3 **Argument.** GRADUAL shall be a logical scalar. If it is true, the [underflow mode](#) is set to gradual underflow.
 32 If it is false, the [underflow mode](#) is set to abrupt underflow.

33 4 **Restriction.** IEEE_SET_UNDERFLOW_MODE shall not be invoked unless IEEE_SUPPORT_UNDER-
 34 FLOW_CONTROL (X) is true for some X.

35 5 **Example.** To perform some calculations with abrupt underflow and then restore the previous mode:

```
36        USE, INTRINSIC :: IEEE_ARITHMETIC
37        LOGICAL SAVE_UNDERFLOW_MODE
38        ...
```



```

1      CALL IEEE_GET_UNDERFLOW_MODE (SAVE_UNDERFLOW_MODE)
2      CALL IEEE_SET_UNDERFLOW_MODE (GRADUAL=.FALSE.)
3      ... ! Perform some calculations with abrupt underflow
4      CALL IEEE_SET_UNDERFLOW_MODE (SAVE_UNDERFLOW_MODE)

```

14.11.41 IEEE_SIGNBIT (X)

- 1 **Description.** Test sign bit.
- 2 **Class.** [Elemental function](#).
- 3 **Argument.** X shall be of type real.
- 4 **Restriction.** IEEE_SIGNBIT (X) shall not be invoked if [IEEE_SUPPORT_DATATYPE](#) (X) has the value false.
- 5 **Result Characteristics.** Default logical.
- 6 **Result Value.** The result has the value specified for the isSignMinus operation in ISO/IEC/IEEE 60559:2011; that is, it is true if and only if the sign bit of X is nonzero. No exception is signaled even if X is a signaling NaN.
- 7 **Example.** IEEE_SIGNBIT (−1.0) has the value true.

14.11.42 IEEE_SUPPORT_DATATYPE () or IEEE_SUPPORT_DATATYPE (X)

- 1 **Description.** Query IEEE arithmetic support.
- 2 **Class.** [Inquiry function](#).
- 3 **Argument.** X shall be of type real. It may be a scalar or an array.
- 4 **Result Characteristics.** Default logical scalar.
- 5 **Result Value.** The result has the value true if the processor supports IEEE arithmetic for all reals (X does not appear) or for real variables of the same kind type parameter as X; otherwise, it has the value false. Here, support is as defined in the first paragraph of [14.9](#).
- 6 **Example.** If default real kind conforms to ISO/IEC/IEEE 60559:2011 except that underflow values flush to zero instead of being subnormal, IEEE_SUPPORT_DATATYPE (1.0) has the value true.

14.11.43 IEEE_SUPPORT_DENORMAL () or IEEE_SUPPORT_DENORMAL (X)

- 1 **Description.** Query subnormal number support.
- 2 **Class.** [Inquiry function](#).
- 3 **Argument.** X shall be of type real. It may be a scalar or an array.
- 4 **Result Characteristics.** Default logical scalar.
- 5 **Result Value.**
- Case (i):* IEEE_SUPPORT_DENORMAL (X) has the value true if [IEEE_SUPPORT_DATATYPE](#) (X) has the value true and the processor supports arithmetic operations and assignments with subnormal numbers (biased exponent $e = 0$ and fraction $f \neq 0$, see subclause 3.2 of ISO/IEC/IEEE 60559:2011) for real variables of the same kind type parameter as X; otherwise, it has the value false.

1 *Case (ii):* IEEE_SUPPORT_DENORMAL () has the value true if IEEE_SUPPORT_DENORMAL (X) has
2 the value true for all real X; otherwise, it has the value false.

3 6 **Example.** IEEE_SUPPORT_DENORMAL (X) has the value true if the processor supports subnormal values
4 for X.

NOTE 14.10

A reference to IEEE_SUPPORT_DENORMAL will have the same result value as a reference to IEEE_SUPPORT_SUBNORMAL with the same argument list.

5 14.11.44 IEEE_SUPPORT_DIVIDE () or IEEE_SUPPORT_DIVIDE (X)

6 1 **Description.** Query IEEE division support.

7 2 **Class.** [Inquiry function](#).

8 3 **Argument.** X shall be of type real. It may be a scalar or an array.

9 4 **Result Characteristics.** Default logical scalar.

10 5 **Result Value.**

11 *Case (i):* IEEE_SUPPORT_DIVIDE (X) has the value true if the processor supports division with the
12 accuracy specified by ISO/IEC/IEEE 60559:2011 for real variables of the same kind type parameter
13 as X; otherwise, it has the value false.

14 *Case (ii):* IEEE_SUPPORT_DIVIDE () has the value true if IEEE_SUPPORT_DIVIDE (X) has the value
15 true for all real X; otherwise, it has the value false.

16 6 **Example.** IEEE_SUPPORT_DIVIDE (X) has the value true if division of operands with the same kind as X
17 conforms to ISO/IEC/IEEE 60559:2011.

18 14.11.45 IEEE_SUPPORT_FLAG (FLAG) or IEEE_SUPPORT_FLAG (FLAG, X)

19 1 **Description.** Query exception support.

20 2 **Class.** [Inquiry function](#).

21 3 **Arguments.**

22 FLAG shall be a scalar of type [IEEE_FLAG_TYPE](#). Its value shall be one of IEEE_INVALID, IEEE_
23 OVERFLOW, IEEE_DIVIDE_BY_ZERO, IEEE_UNDERFLOW, or IEEE_INEXACT.

24 X shall be of type real. It may be a scalar or an array.

25 4 **Result Characteristics.** Default logical scalar.

26 5 **Result Value.**

27 *Case (i):* IEEE_SUPPORT_FLAG (FLAG, X) has the value true if the processor supports detection of the
28 specified exception for real variables of the same kind type parameter as X; otherwise, it has the
29 value false.

30 *Case (ii):* IEEE_SUPPORT_FLAG (FLAG) has the value true if IEEE_SUPPORT_FLAG (FLAG, X) has
31 the value true for all real X; otherwise, it has the value false.

32 6 **Example.** IEEE_SUPPORT_FLAG (IEEE_INEXACT) has the value true if the processor supports the inexact
33 exception.

14.11.46 IEEE_SUPPORT_HALTING (FLAG)

1 **Description.** Query [halting mode](#) support.

2 **Class.** [Inquiry function](#).

3 **Argument.** FLAG shall be a scalar of type [IEEE_FLAG_TYPE](#). Its value shall be one of IEEE_INVALID,
4 IEEE_OVERFLOW, IEEE_DIVIDE_BY_ZERO, IEEE_UNDERFLOW, or IEEE_INEXACT.

5 **Result Characteristics.** Default logical scalar.

6 **Result Value.** The result has the value true if the processor supports the ability to control during program
7 execution whether to abort or continue execution after the exception specified by FLAG; otherwise, it has the
8 value false. Support includes the ability to change the mode by CALL [IEEE_SET_HALTING_MODE](#) (FLAG).

9 **Example.** IEEE_SUPPORT_HALTING (IEEE_OVERFLOW) has the value true if the processor supports
10 control of [halting](#) after an overflow.

14.11.47 IEEE_SUPPORT_INF () or IEEE_SUPPORT_INF (X)

11 **Description.** Query IEEE infinity support.

12 **Class.** [Inquiry function](#).

13 **Argument.** X shall be of type real. It may be a scalar or an array.

14 **Result Characteristics.** Default logical scalar.

15 **Result Value.**

16 *Case (i):* IEEE_SUPPORT_INF (X) has the value true if the processor supports IEEE infinities (positive
17 and negative) for real variables of the same kind type parameter as X; otherwise, it has the value
18 false.

19 *Case (ii):* IEEE_SUPPORT_INF () has the value true if IEEE_SUPPORT_INF (X) has the value true for
20 all real X; otherwise, it has the value false.

21 **Example.** IEEE_SUPPORT_INF (X) has the value true if the processor supports IEEE infinities for X.

14.11.48 IEEE_SUPPORT_IO () or IEEE_SUPPORT_IO (X)

22 **Description.** Query IEEE formatting support.

23 **Class.** [Inquiry function](#).

24 **Argument.** X shall be of type real. It may be a scalar or an array.

25 **Result Characteristics.** Default logical scalar.

26 **Result Value.**

27 *Case (i):* IEEE_SUPPORT_IO (X) has the value true if base conversion during formatted input/output
28 ([9.5.6.16](#), [9.6.2.13](#), [10.7.2.3.8](#)) conforms to ISO/IEC/IEEE 60559:2011 for the modes UP, DOWN,
29 ZERO, and NEAREST for real variables of the same kind type parameter as X; otherwise, it has
30 the value false.

31 *Case (ii):* IEEE_SUPPORT_IO () has the value true if IEEE_SUPPORT_IO (X) has the value true for all
32 real X; otherwise, it has the value false.

33 **Example.** IEEE_SUPPORT_IO (X) has the value true if formatted input/output base conversions conform to
34 ISO/IEC/IEEE 60559:2011.

14.11.49 IEEE_SUPPORT_NAN () or IEEE_SUPPORT_NAN (X)

1 **Description.** Query IEEE NaN support.

2 **Class.** Inquiry function.

3 **Argument.** X shall be of type real. It may be a scalar or an array.

4 **Result Characteristics.** Default logical scalar.

5 **Result Value.**

6 *Case (i):* IEEE_SUPPORT_NAN (X) has the value true if the processor supports IEEE NaNs for real variables of the same kind type parameter as X; otherwise, it has the value false.

7 *Case (ii):* IEEE_SUPPORT_NAN () has the value true if IEEE_SUPPORT_NAN (X) has the value true for all real X; otherwise, it has the value false.

8 **Example.** IEEE_SUPPORT_NAN (X) has the value true if the processor supports IEEE NaNs for X.

14.11.50 IEEE_SUPPORT_ROUNDING (ROUND_VALUE) or IEEE_SUPPORT_ROUNDING (ROUND_VALUE, X)

9 **Description.** Query IEEE rounding support.

10 **Class.** Inquiry function.

11 **Arguments.**

12 ROUND_VALUE shall be of type IEEE_ROUND_TYPE.

13 X shall be of type real. It may be a scalar or an array.

14 **Result Characteristics.** Default logical scalar.

15 **Result Value.**

16 *Case (i):* IEEE_SUPPORT_ROUNDING (ROUND_VALUE, X) has the value true if the processor supports the rounding mode defined by ROUND_VALUE for real variables of the same kind type parameter as X; otherwise, it has the value false. Support includes the ability to change the mode by CALL IEEE_SET_ROUNDING_MODE (ROUND_VALUE).

17 *Case (ii):* IEEE_SUPPORT_ROUNDING (ROUND_VALUE) has the value true if IEEE_SUPPORT_ROUNDING (ROUND_VALUE, X) has the value true for all real X; otherwise, it has the value false.

18 **Example.** IEEE_SUPPORT_ROUNDING (IEEE_TO_ZERO) has the value true if the processor supports rounding to zero for all reals.

14.11.51 IEEE_SUPPORT_SQRT () or IEEE_SUPPORT_SQRT (X)

19 **Description.** Query IEEE square root support.

20 **Class.** Inquiry function.

21 **Argument.** X shall be of type real. It may be a scalar or an array.

22 **Result Characteristics.** Default logical scalar.

23 **Result Value.**

24 *Case (i):* IEEE_SUPPORT_SQRT (X) has the value true if the intrinsic function SQRT conforms to ISO/IEC/IEEE 60559:2011 for real variables of the same kind type parameter as X; otherwise, it has the value false.

1 *Case (ii):* IEEE_SUPPORT_SQRT () has the value true if IEEE_SUPPORT_SQRT (X) has the value true
2 for all real X; otherwise, it has the value false.

3 6 **Example.** If IEEE_SUPPORT_SQRT (1.0) has the value true, SQRT (−0.0) will have the value −0.0.

4 14.11.52 IEEE_SUPPORT_STANDARD () or IEEE_SUPPORT_STANDARD (X)

5 1 **Description.** Query IEEE standard support.

6 2 **Class.** Inquiry function.

7 3 **Argument.** X shall be of type real. It may be a scalar or an array.

8 4 **Result Characteristics.** Default logical scalar.

9 5 **Result Value.**

10 *Case (i):* IEEE_SUPPORT_STANDARD (X) has the value true if the results of all the functions
11 IEEE_SUPPORT_DATATYPE (X), IEEE_SUPPORT_DIVIDE (X), IEEE_SUPPORT_
12 FLAG (FLAG, X) for valid FLAG, IEEE_SUPPORT_HALTING (FLAG) for valid
13 FLAG, IEEE_SUPPORT_INF (X), IEEE_SUPPORT_NAN (X), IEEE_SUPPORT_
14 ROUNDING (ROUND_VALUE, X) for valid ROUND_VALUE, IEEE_SUPPORT_SQRT
15 (X), and IEEE_SUPPORT_SUBNORMAL (X) are all true; otherwise, it has the value false.

16 *Case (ii):* IEEE_SUPPORT_STANDARD () has the value true if IEEE_SUPPORT_STANDARD (X) has
17 the value true for all real X; otherwise, it has the value false.

18 6 **Example.** IEEE_SUPPORT_STANDARD () has the value false if some but not all kinds of reals conform to
19 ISO/IEC/IEEE 60559:2011.

20 14.11.53 IEEE_SUPPORT_SUBNORMAL () or IEEE_SUPPORT_SUBNORMAL (X)

21 1 **Description.** Query subnormal number support.

22 2 **Class.** Inquiry function.

23 3 **Argument.** X shall be of type real. It may be a scalar or an array.

24 4 **Result Characteristics.** Default logical scalar.

25 5 **Result Value.**

26 *Case (i):* IEEE_SUPPORT_SUBNORMAL (X) has the value true if IEEE_SUPPORT_DATATYPE (X)
27 has the value true and the processor supports arithmetic operations and assignments with subnormal
28 numbers (biased exponent $e = 0$ and fraction $f \neq 0$, see subclause 3.2 of ISO/IEC/IEEE 60559:2011)
29 for real variables of the same kind type parameter as X; otherwise, it has the value false.

30 *Case (ii):* IEEE_SUPPORT_SUBNORMAL () has the value true if IEEE_SUPPORT_SUBNORMAL (X)
31 has the value true for all real X; otherwise, it has the value false.

32 6 **Example.** IEEE_SUPPORT_SUBNORMAL (X) has the value true if the processor supports subnormal values
33 for X.

NOTE 14.11

The subnormal numbers are not included in the 13.4 model for real numbers; they satisfy the inequality $ABS(X) < TINY(X)$. They usually occur as a result of an arithmetic operation whose exact result is less than $TINY(X)$. Such an operation causes IEEE_UNDERFLOW to signal unless the result is exact. IEEE_SUPPORT_SUBNORMAL (X) is false if the processor never returns a subnormal number as the result of an arithmetic operation.

14.11.54 IEEE_SUPPORT_UNDERFLOW_CONTROL () or IEEE_SUPPORT_UNDERFLOW_CONTROL (X)

1 **Description.** Query [underflow](#) control support.

2 **Class.** [Inquiry function](#).

3 **Argument.** X shall be of type real. It may be a scalar or an array.

4 **Result Characteristics.** Default logical scalar.

5 **Result Value.**

6 *Case (i):* IEEE_SUPPORT_UNDERFLOW_CONTROL (X) has the value true if the processor supports
7 control of the [underflow mode](#) for floating-point calculations with the same type as X, and false
8 otherwise.
9

10 *Case (ii):* IEEE_SUPPORT_UNDERFLOW_CONTROL () has the value true if the processor supports
11 control of the [underflow mode](#) for all floating-point calculations, and false otherwise.

12 **Example.** IEEE_SUPPORT_UNDERFLOW_CONTROL (2.5) has the value true if the processor supports
13 [underflow mode](#) control for default real calculations.

14.11.55 IEEE_UNORDERED (X, Y)

15 **Description.** Whether two values are unordered.

16 **Class.** [Elemental function](#).

17 **Arguments.** The arguments shall be of type real.

18 **Restriction.** IEEE_UNORDERED (X, Y) shall not be invoked if IEEE_SUPPORT_DATATYPE (X) or
19 IEEE_SUPPORT_DATATYPE (Y) has the value false.

20 **Result Characteristics.** Default logical.

21 **Result Value.** The result has the value true if X or Y is a NaN or both are NaNs; otherwise, it has the value
22 false.

23 **Example.** IEEE_UNORDERED (0.0, [SQRT](#) (-1.0)) has the value true if IEEE_SUPPORT_SQRT (1.0) has
24 the value true.

14.11.56 IEEE_VALUE (X, CLASS)

26 **Description.** Return number in a class.

27 **Class.** [Elemental function](#).

28 **Arguments.**

29 X shall be of type real.

30 CLASS shall be of type [IEEE_CLASS_TYPE](#). The value is permitted to be: IEEE_SIGNALING_NAN or
31 IEEE_QUIET_NAN if [IEEE_SUPPORT_NAN](#) (X) has the value true, IEEE_NEGATIVE_INF
32 or IEEE_POSITIVE_INF if [IEEE_SUPPORT_INF](#) (X) has the value true, IEEE_NEGATIVE_-
33 SUBNORMAL or IEEE_POSITIVE_SUBNORMAL if [IEEE_SUPPORT_SUBNORMAL](#) (X) has
34 the value true, IEEE_NEGATIVE_NORMAL, IEEE_NEGATIVE_ZERO, IEEE_POSITIVE_-
35 ZERO or IEEE_POSITIVE_NORMAL.

36 **Restriction.** IEEE_VALUE (X, CLASS) shall not be invoked if [IEEE_SUPPORT_DATATYPE](#) (X) has the
37 value false.

38 **Result Characteristics.** Same as X.

- 1 6 **Result Value.** The result value is an IEEE value as specified by CLASS. Although in most cases the value is
 2 processor dependent, the value shall not vary between invocations for any particular X kind type parameter and
 3 CLASS value.
- 4 7 **Example.** IEEE_VALUE (1.0, IEEE_NEGATIVE_INF) has the value $-\infty$.
- 5 8 Whenever IEEE_VALUE returns a signaling NaN, it is processor dependent whether or not invalid is raised and
 6 processor dependent whether or not the signaling NaN is converted into a quiet NaN.

NOTE 14.12

If the *expr* in an *assignment statement* is a reference to the IEEE_VALUE function that returns a signaling NaN and the *variable* is of the same type and kind as the function result, it is recommended that the signaling NaN be preserved.

7 **14.12 Examples****NOTE 14.13**

```

MODULE DOT
  ! Module for dot product of two real arrays of rank 1.
  ! The caller needs to ensure that exceptions do not cause halting.
  USE, INTRINSIC :: IEEE_EXCEPTIONS
  LOGICAL :: MATRIX_ERROR = .FALSE.
  INTERFACE OPERATOR(.dot.)
    MODULE PROCEDURE MULT
  END INTERFACE
CONTAINS
  REAL FUNCTION MULT (A, B)
    REAL, INTENT (IN) :: A(:), B(:)
    INTEGER I
    LOGICAL OVERFLOW
    IF (SIZE(A) /= SIZE(B)) THEN
      MATRIX_ERROR = .TRUE.
      RETURN
    END IF
    ! The processor ensures that IEEE_OVERFLOW is quiet.
    MULT = 0.0
    DO I = 1, SIZE (A)
      MULT = MULT + A(I)*B(I)
    END DO
    CALL IEEE_GET_FLAG (IEEE_OVERFLOW, OVERFLOW)
    IF (OVERFLOW) MATRIX_ERROR = .TRUE.
  END FUNCTION MULT
END MODULE DOT

```

This module provides a function that computes the dot product of two real arrays of **rank 1**. If the sizes of the arrays are different, an immediate return occurs with `MATRIX_ERROR` true. If overflow occurs during the actual calculation, the `IEEE_OVERFLOW` flag will signal and `MATRIX_ERROR` will be true.

NOTE 14.14

```

USE, INTRINSIC :: IEEE_EXCEPTIONS
USE, INTRINSIC :: IEEE_FEATURES, ONLY: IEEE_INVALID_FLAG
! The other exceptions of IEEE_USUAL (IEEE_OVERFLOW and
! IEEE_DIVIDE_BY_ZERO) are always available with IEEE_EXCEPTIONS
TYPE (IEEE_STATUS_TYPE) STATUS_VALUE
LOGICAL, DIMENSION(3) :: FLAG_VALUE
...
CALL IEEE_GET_STATUS (STATUS_VALUE)
CALL IEEE_SET_HALTING_MODE (IEEE_USUAL, .FALSE.) ! Needed in case the
!
! default on the processor is to halt on exceptions
CALL IEEE_SET_FLAG (IEEE_USUAL, .FALSE.)
! First try the "fast" algorithm for inverting a matrix:
MATRIX1 = FAST_INV (MATRIX) ! This shall not alter MATRIX.
CALL IEEE_GET_FLAG (IEEE_USUAL, FLAG_VALUE)
IF (ANY(FLAG_VALUE)) THEN
  ! "Fast" algorithm failed; try "slow" one:
  CALL IEEE_SET_FLAG (IEEE_USUAL, .FALSE.)
  MATRIX1 = SLOW_INV (MATRIX)
  CALL IEEE_GET_FLAG (IEEE_USUAL, FLAG_VALUE)
  IF (ANY (FLAG_VALUE)) THEN
    WRITE (*, *) 'Cannot invert matrix'
    STOP
  END IF
END IF
CALL IEEE_SET_STATUS (STATUS_VALUE)

```

In this example, the function FAST_INV might cause a condition to signal. If it does, another try is made with SLOW_INV. If this still fails, a message is printed and the program stops. Note, also, that it is important to set the flags quiet before the second try. The state of all the flags is stored and restored.

NOTE 14.15

```

USE, INTRINSIC :: IEEE_EXCEPTIONS
LOGICAL FLAG_VALUE
...
CALL IEEE_SET_HALTING_MODE (IEEE_OVERFLOW, .FALSE.)
! First try a fast algorithm for inverting a matrix.
CALL IEEE_SET_FLAG (IEEE_OVERFLOW, .FALSE.)
DO K = 1, N
  ...
  CALL IEEE_GET_FLAG (IEEE_OVERFLOW, FLAG_VALUE)
  IF (FLAG_VALUE) EXIT
END DO
IF (FLAG_VALUE) THEN
! Alternative code which knows that K-1 steps have executed normally.

```


NOTE 14.15 (cont.)

```
...  
END IF
```

Here the code for matrix inversion is in line and the transfer is made more precise by adding extra tests of the flag.

1

(Blank page)

15 Interoperability with C

15.1 General

- 1 Fortran provides a means of referencing procedures that are defined by means of the C programming language or procedures that can be described by C prototypes as defined in 6.7.6.3 of ISO/IEC 9899:2011, even if they are not actually defined by means of C. Conversely, there is a means of specifying that a procedure defined by a Fortran subprogram can be referenced from a function defined by means of C. In addition, there is a means of declaring global variables that are associated with C variables whose names have external linkage as defined in 6.2.2 of ISO/IEC 9899:2011.
- 2 The ISO_C_BINDING module provides access to [named constants](#) that represent [kind type parameters](#) of data representations compatible with C types. Fortran also provides facilities for defining derived types (4.5) and enumerations (4.6) that correspond to C types.
- 3 The source file `ISO_Fortran_binding.h` provides definitions and prototypes to enable a C function to interoperate with a Fortran procedure that has a dummy data object that is [allocatable](#), [assumed-shape](#), [assumed-rank](#), [pointer](#), or is of type character with an assumed length.

15.2 The ISO_C_BINDING intrinsic module

15.2.1 Summary of contents

- 1 The processor shall provide the intrinsic module ISO_C_BINDING. This module shall make accessible the following entities: the [named constants](#) `C_NULL_PTR` and `C_NULL_FUNPTR` and those with names listed in the first column of Table 15.1 and the second column of Table 15.2, and the types `C_PTR` and `C_FUNPTR`. A processor may provide other public entities in the ISO_C_BINDING intrinsic module in addition to those listed here.

15.2.2 Named constants and derived types in the module

- 1 The entities listed in the second column of Table 15.2 shall be default integer [named constants](#).
- 2 A Fortran [intrinsic type](#) whose [kind type parameter](#) is one of the values in the module shall have the same representation as the C type with which it interoperates, for each value that a variable of that type can have. For `C_BOOL`, the internal representation of `.TRUE._C_BOOL` and `.FALSE._C_BOOL` shall be the same as those of the C values `(_Bool)1` and `(_Bool)0` respectively.
- 3 The value of `C_INT` shall be a valid value for an integer kind parameter on the processor. The values of `C_SHORT`, `C_LONG`, `C_LONG_LONG`, `C_SIGNED_CHAR`, `C_SIZE_T`, `C_INT8_T`, `C_INT16_T`, `C_INT32_T`, `C_INT64_T`, `C_INT_LEAST8_T`, `C_INT_LEAST16_T`, `C_INT_LEAST32_T`, `C_INT_LEAST64_T`, `C_INT_FAST8_T`, `C_INT_FAST16_T`, `C_INT_FAST32_T`, `C_INT_FAST64_T`, `C_INTMAX_T`, and `C_INTPTR_T` shall each be a valid value for an integer [kind type parameter](#) on the processor or shall be `-1` if the [companion processor](#) defines the corresponding C type and there is no interoperating Fortran processor kind or `-2` if the C processor does not define the corresponding C type.
- 4 The values of `C_FLOAT`, `C_DOUBLE`, and `C_LONG_DOUBLE` shall each be a valid value for a real kind type parameter on the processor or shall be `-1` if the [companion processor](#)'s type does not have a precision equal to the precision of any of the Fortran processor's real kinds, `-2` if the [companion processor](#)'s type does not have a range equal to the range of any of the Fortran processor's real kinds, `-3` if the [companion processor](#)'s type

- 1 has neither the precision nor range of any of the Fortran processor's real kinds, and equal to -4 if there is no
 2 interoperating Fortran processor kind for other reasons. The values of `C_FLOAT_COMPLEX`, `C_DOUBLE_`
 3 `COMPLEX`, and `C_LONG_DOUBLE_COMPLEX` shall be the same as those of `C_FLOAT`, `C_DOUBLE`, and
 4 `C_LONG_DOUBLE`, respectively.
- 5 5 The value of `C_BOOL` shall be a valid value for a logical kind parameter on the processor or shall be -1 .
- 6 6 The value of `C_CHAR` shall be a valid value for a character [kind type parameter](#) on the processor or shall be -1 .
 7 If the value of `C_CHAR` is nonnegative, the character kind specified is the C character kind; otherwise, there is
 8 no C character kind.
- 9 7 The following entities shall be [named constants](#) of type character with a length parameter of one. The kind
 10 parameter value shall be equal to the value of `C_CHAR` unless `C_CHAR` = -1 , in which case the kind parameter
 11 value shall be the same as for default kind. The values of these constants are specified in Table 15.1. In the case
 12 that `C_CHAR` $\neq -1$ the value is specified using C syntax. The semantics of these values are explained in 5.2.1
 13 and 5.2.2 of ISO/IEC 9899:2011.

Table 15.1: Names of C characters with special semantics

Name	C definition	Value	
		<code>C_CHAR</code> = -1	<code>C_CHAR</code> $\neq -1$
<code>C_NULL_CHAR</code>	null character	<code>CHAR(0)</code>	'\0'
<code>C_ALERT</code>	alert	<code>ACHAR(7)</code>	'\a'
<code>C_BACKSPACE</code>	backspace	<code>ACHAR(8)</code>	'\b'
<code>C_FORM_FEED</code>	form feed	<code>ACHAR(12)</code>	'\f'
<code>C_NEW_LINE</code>	new line	<code>ACHAR(10)</code>	'\n'
<code>C_CARRIAGE_RETURN</code>	carriage return	<code>ACHAR(13)</code>	'\r'
<code>C_HORIZONTAL_TAB</code>	horizontal tab	<code>ACHAR(9)</code>	'\t'
<code>C_VERTICAL_TAB</code>	vertical tab	<code>ACHAR(11)</code>	'\v'

- 14 8 The entities `C_PTR` and `C_FUNPTR` are described in 15.3.3.
- 15 9 The entity `C_NULL_PTR` shall be a [named constant](#) of type `C_PTR`. The value of `C_NULL_PTR` shall be the
 16 same as the value `NULL` in C. The entity `C_NULL_FUNPTR` shall be a [named constant](#) of type `C_FUNPTR`.
 17 The value of `C_NULL_FUNPTR` shall be that of a null pointer to a function in C.

NOTE 15.1

The value of <code>NEW_LINE(C_NEW_LINE)</code> is <code>C_NEW_LINE</code> (13.8.132).

18 **15.2.3 Procedures in the module**19 **15.2.3.1 General**

- 20 1 In the detailed descriptions below, procedure names are generic and not specific. The `C_F_POINTER` subroutine
 21 is impure; all other procedures in the module are pure.

22 **15.2.3.2 C_ASSOCIATED (C_PTR_1 [, C_PTR_2])**

23 1 **Description.** Query C pointer status.

24 2 **Class.** [Inquiry function](#).

25 3 **Arguments.**

26 `C_PTR_1` shall be a scalar of type `C_PTR` or `C_FUNPTR`.

27 `C_PTR_2` (optional) shall be a scalar of the same type as `C_PTR_1`.

1 4 **Result Characteristics.** Default logical scalar.

2 5 **Result Value.**

3 *Case (i):* If C_PTR_2 is absent, the result is false if C_PTR_1 is a C null pointer and true otherwise.

4 *Case (ii):* If C_PTR_2 is present, the result is false if C_PTR_1 is a C null pointer. If C_PTR_1 is not a
5 C null pointer, the result is true if C_PTR_1 compares equal to C_PTR_2 in the sense of 6.3.2.3
6 and 6.5.9 of ISO/IEC 9899:2011, and false otherwise.

NOTE 15.2

The following example illustrates the use of C_LOC and C_ASSOCIATED.

```
USE, INTRINSIC :: ISO_C_BINDING, ONLY: C_PTR, C_FLOAT, C_ASSOCIATED, C_LOC
INTERFACE
  SUBROUTINE FOO(GAMMA) BIND(C)
    IMPORT C_PTR
    TYPE(C_PTR), VALUE :: GAMMA
  END SUBROUTINE FOO
END INTERFACE
REAL(C_FLOAT), TARGET, DIMENSION(100) :: ALPHA
TYPE(C_PTR) :: BETA
...
IF (.NOT. C_ASSOCIATED(BETA)) THEN
  BETA = C_LOC(ALPHA)
ENDIF
CALL FOO(BETA)
```

7 15.2.3.3 C_F_POINTER (CPTR, FPTR [, SHAPE])

8 1 **Description.** Associate a data pointer with the [target](#) of a C pointer and specify its shape.

9 2 **Class.** Subroutine.

10 3 **Arguments.**

11 CPTR shall be a scalar of type [C_PTR](#). It is an **INTENT (IN)** argument. Its value shall be

- 12 • the [C address](#) of an [interoperable](#) data entity,
- 13 • the result of a reference to [C_LOC](#) with a noninteroperable argument, or
- 14 • the [C address](#) of a storage sequence that is not in use by any other Fortran entity.

15 The value of CPTR shall not be the [C address](#) of a Fortran variable that does not have the **TARGET**
16 **attribute**.

17 FPTR shall be a pointer, shall not have a [deferred type parameter](#), and shall not be a [coindexed object](#).
18 It is an **INTENT (OUT)** argument. If FPTR is an array, its shape is specified by SHAPE and each
19 lower bound is equal to 1.

20 *Case (i):* If the value of CPTR is the [C address](#) of an [interoperable](#) data entity, FPTR
21 shall be a [data pointer](#) with type and [type parameter](#) values [interoperable](#)
22 with the type of the entity. If the target T of CPTR is scalar, FPTR becomes pointer
23 associated with T; if FPTR is an array, SHAPE shall specify a size of 1. If T is
24 an array, and FPTR is scalar, FPTR becomes associated with the first element of
25 T. If both T and FPTR are arrays, SHAPE shall specify a size that is less than or
26 equal to the size of T, and FPTR becomes associated with the first **PRODUCT**
27 (SHAPE) elements of T (this could be the entirety of T).

1 *Case (ii):* If the value of CPTR is the result of a reference to C_LOC with a noninter-
 2 operable **effective argument** X, FPTR shall be a nonpolymorphic pointer with
 3 the same type and type parameters as X. In this case, X shall not have been
 4 deallocated or have become undefined due to execution of a **RETURN** or **END**
 5 statement since the reference. If X is scalar, FPTR becomes **pointer associated**
 6 with X; if FPTR is an array, SHAPE shall specify a size of 1. If X is an array and
 7 FPTR is scalar, FPTR becomes associated with the first element of X. If both X
 8 and FPTR are arrays, SHAPE shall specify a size that is less than or equal to
 9 the size of X, and FPTR becomes associated with the first **PRODUCT** (SHAPE)
 10 elements of X (this could be the entirety of X).

11 *Case (iii):* If the value of CPTR is the **C address** of a storage sequence that is not in use by
 12 any other Fortran entity, FPTR becomes associated with that storage sequence.
 13 If FPTR is an array, its shape is specified by SHAPE and each lower bound
 14 is 1. The storage sequence shall be large enough to contain the target object
 15 described by FPTR and shall satisfy any other processor-dependent requirement
 16 for association.

17 SHAPE (optional) shall be a rank-one integer array. It is an **INTENT (IN)** argument. SHAPE shall be present
 18 if and only if FPTR is an array; its size shall be equal to the **rank** of FPTR.

19 4 Examples.

20 *Case (i):* extern double c_x;
 21 void *address_of_x (void)
 22 {
 23 return &c_x;
 24 }
 25
 26 ! Assume interface to "address_of_x" is available.
 27 Real (C_double), Pointer :: xp
 28 Call C_F_Pointer (address_of_x (), xp)

29 *Case (ii):* Type t
 30 Real, Allocatable :: v(:, :)
 31 End Type
 32 Type(t), Target :: x
 33 Type(C_ptr) :: xloc
 34 xloc = C_Loc (x)
 35 ...
 36 Type(t), Pointer :: y
 37 Call C_F_Pointer (xloc, y)

38 *Case (iii):* void *getmem (int nbits)
 39 {
 40 return malloc ((nbits+CHAR_BIT-1)/CHAR_BIT);
 41 }
 42
 43 ! Assume interface to "getmem" is available,
 44 ! and there is a derived type "mytype" accessible.
 45 Type(mytype), Pointer :: x
 46 Call C_F_Pointer (getmem (**Storage_Size** (x)), x)

47 The following statements illustrate the use of C_F_POINTER when the pointer to be set has a **deferred type**

```

1 parameter:
2     Character(42), Pointer :: C1
3     Character(:), Pointer :: C2
4     Call C_F_Pointer (CPTR, C1)
5     C2 => C1

```

6 This will associate C2 with the entity at the [C address](#) specified by CPTR, and specify its length to be the same
7 as that of C1.

NOTE 15.3

In the case of associating FPTR with a storage sequence, there might be processor-dependent requirements such as alignment of the memory address or placement in memory.

8 15.2.3.4 C_F_PROCPOINTER (CPTR, FPTR)

9 1 **Description.** Associate a procedure pointer with the [target](#) of a C function pointer.

10 2 **Class.** [Pure subroutine](#).

11 3 **Arguments.**

12 CPTR shall be a scalar of type [C_FUNPTR](#). It is an [INTENT \(IN\)](#) argument. Its value shall be the [C](#)
13 [address](#) of a procedure that is [interoperable](#), or the result of a reference to the function [C_FUNLOC](#)
14 from the intrinsic module [ISO_C_BINDING](#).

15 FPTR shall be a [procedure pointer](#), and shall not be a component of a [coindexed object](#). It is an [INTENT](#)
16 [\(OUT\)](#) argument. If the target of CPTR is [interoperable](#), the [interface](#) for FPTR shall be [interoper-](#)
17 [able](#) with the prototype that describes the [target](#) of CPTR; otherwise, the [interface](#) for FPTR shall
18 have the same characteristics as that target. FPTR becomes [pointer associated](#) with the [target](#) of
19 CPTR.

NOTE 15.4

The term “target” in the descriptions of [C_F_POINTER](#) and [C_F_PROCPOINTER](#) denotes the entity referenced by a C pointer, as described in 6.2.5 of ISO/IEC 9899:2011.

20 15.2.3.5 C_FUNLOC (X)

21 1 **Description.** [C address](#) of the argument.

22 2 **Class.** [Inquiry function](#).

23 3 **Argument.** X shall be a procedure; if it is a procedure pointer it shall be associated. It shall not be a [coindexed](#)
24 [object](#).

25 4 **Result Characteristics.** Scalar of type [C_FUNPTR](#).

26 5 **Result Value.** The result value is described using the result name FPTR. The result is determined as if [C_-](#)
27 [FUNPTR](#) were a derived type containing a procedure pointer component PX with an [implicit interface](#) and the
28 [pointer assignment](#) `FPTR%PX => X` were executed.

29 6 The result is a value that can be used as an [actual](#) FPTR argument in a call to [C_F_PROCPOINTER](#) where
30 FPTR has attributes that would allow the [pointer assignment](#) `FPTR => X`. Such a call to [C_F_PROCPOINTER](#)
31 shall have the effect of the pointer assignment `FPTR => X`.

1 **15.2.3.6 C_LOC (X)**

2 1 **Description.** C address of the argument.

3 2 **Class.** Inquiry function.

4 3 **Argument.** X shall have either the **POINTER** or **TARGET** attribute. It shall not be a **coindexed object**. It shall either be a variable with **interoperable** type and **kind type parameters**, or be a nonpolymorphic variable with no **length type parameters**. If it is **allocatable**, it shall be allocated. If it is a pointer, it shall be associated. If it is an array, it shall be **contiguous** and have nonzero size. It shall not be a zero-length string.

8 4 **Result Characteristics.** Scalar of type **C_PTR**.

9 5 **Result Value.** The result value is described using the result name **CPTR**.

10 6 If X is a scalar data entity, the result is determined as if **C_PTR** were a derived type containing a scalar pointer component **PX** of the type and type parameters of X and the **pointer assignment** **CPTR%PX => X** were executed.

12 7 If X is an array data entity, the result is determined as if **C_PTR** were a derived type containing a scalar pointer component **PX** of the type and type parameters of X and the **pointer assignment** of **CPTR%PX** to the first element of X were executed.

15 8 If X is a data entity that is **interoperable** or has **interoperable** type and type parameters, the result is the value that the C processor returns as the result of applying the unary “&” operator (as defined in ISO/IEC 9899:2011, 6.5.3.2) to the **target** of **CPTR%PX**.

18 9 The result is a value that can be used as an **actual** **CPTR** argument in a call to **C_F_POINTER** where **FPTR** has attributes that would allow the **pointer assignment** **FPTR => X**. Such a call to **C_F_POINTER** shall have the effect of the **pointer assignment** **FPTR => X**.

NOTE 15.5

Where the **actual argument** is of noninteroperable type or type parameters, the result of **C_LOC** provides an opaque “handle” for it. In an actual implementation, this handle might be the **C address** of the argument; however, only a C function that treats it as a void (generic) C pointer that cannot be dereferenced (6.5.3.2 in ISO/IEC 9899:2011) is likely to be portable.

21 **15.2.3.7 C_SIZEOF (X)**

22 1 **Description.** Size of X in bytes.

23 2 **Class.** Inquiry function.

24 3 **Argument.** X shall be an **interoperable** data entity that is not an **assumed-size array**.

25 4 **Result Characteristics.** Scalar integer of kind **C_SIZE_T** (15.3.2).

26 5 **Result Value.** If X is scalar, the result value is the value that the **companion processor** returns as the result of applying the **sizeof** operator (ISO/IEC 9899:2011, subclause 6.5.3.4) to an object of a type that interoperates with the type and type parameters of X.

29 6 If X is an array, the result value is the value that the **companion processor** returns as the result of applying the **sizeof** operator to an object of a type that interoperates with the type and type parameters of X, multiplied by the number of elements in X.

15.3 Interoperability between Fortran and C entities

15.3.1 General

- 1 Subclause 15.3 defines the conditions under which a Fortran entity is [interoperable](#). If a Fortran entity is [interoperable](#), an equivalent entity could be defined by means of C and the Fortran entity would interoperate with the C entity. There does not have to be such an interoperating C entity.

NOTE 15.6

A Fortran entity can be [interoperable](#) with more than one C entity.

15.3.2 Interoperability of intrinsic types

- 1 Table 15.2 shows the interoperability between Fortran intrinsic types and C types. A Fortran intrinsic type with particular type parameter values is [interoperable](#) with a C type if the type and [kind type parameter](#) value are listed in the table on the same row as that C type. If the type is character, the [length type parameter](#) is [interoperable](#) if and only if its value is one. A combination of Fortran type and type parameters that is [interoperable](#) with a C type listed in the table is also [interoperable](#) with any unqualified C type that is compatible with the listed C type.
- 2 The second column of the table refers to the [named constants](#) made accessible by the ISO_C_BINDING intrinsic module. If the value of any of these [named constants](#) is negative, there is no combination of Fortran type and type parameters [interoperable](#) with the C type shown in that row.
- 3 A combination of intrinsic type and type parameters is [interoperable](#) if it is [interoperable](#) with a C type. The C types mentioned in table 15.2 are defined in subclauses 6.2.5, 7.19, and 7.20.1 of ISO/IEC 9899:2011.

Table 15.2: Interoperability between Fortran and C types

Fortran type	Named constant from the ISO_C_BINDING module (kind type parameter if value is positive)	C type
INTEGER	C_INT	int
	C_SHORT	short int
	C_LONG	long int
	C_LONG_LONG	long long int
	C_SIGNED_CHAR	signed char unsigned char
	C_SIZE_T	size_t
	C_INT8_T	int8_t
	C_INT16_T	int16_t
	C_INT32_T	int32_t
	C_INT64_T	int64_t
	C_INT_LEAST8_T	int_least8_t
	C_INT_LEAST16_T	int_least16_t
	C_INT_LEAST32_T	int_least32_t
	C_INT_LEAST64_T	int_least64_t
	C_INT_FAST8_T	int_fast8_t
	C_INT_FAST16_T	int_fast16_t
	C_INT_FAST32_T	int_fast32_t
	C_INT_FAST64_T	int_fast64_t
	C_INTMAX_T	intmax_t

Interoperability between Fortran and C types

(cont.)

Fortran type	Named constant from the ISO_C_BINDING module (kind type parameter if value is positive)	C type
	C_INTPTR_T	intptr_t
	C_PTRDIFF_T	ptrdiff_t
REAL	C_FLOAT	float
	C_DOUBLE	double
	C_LONG_DOUBLE	long double
COMPLEX	C_FLOAT_COMPLEX	float _Complex
	C_DOUBLE_COMPLEX	double _Complex
	C_LONG_DOUBLE_COMPLEX	long double _Complex
LOGICAL	C_BOOL	_Bool
CHARACTER	C_CHAR	char

NOTE 15.7

For example, the type integer with a [kind type parameter](#) of C_SHORT is [interoperable](#) with the C type short or any C type derived (via typedef) from short.

NOTE 15.8

ISO/IEC 9899:2011 specifies that the representations for nonnegative signed integers are the same as the corresponding values of unsigned integers. Because Fortran does not provide direct support for unsigned kinds of integers, the ISO_C_BINDING module does not make accessible [named constants](#) for their [kind type parameter](#) values. A user can use the signed kinds of integers to interoperate with the unsigned types and all their qualified versions as well. This has the potentially surprising side effect that the C type unsigned char is [interoperable](#) with the type integer with a [kind type parameter](#) of C_SIGNED_CHAR.

1 15.3.3 Interoperability with C pointer types

- 2 1 C_PTR and C_FUNPTR shall be derived types with only private components. No [direct component](#) of either
3 of these types is [allocatable](#) or a pointer. C_PTR is [interoperable](#) with any C object pointer type. C_FUNPTR
4 is [interoperable](#) with any C function pointer type.

NOTE 15.9

This means that only a C processor with the same representation method for all C object pointer types, and the same representation method for all C function pointer types, can be the target of interoperability of a Fortran processor. ISO/IEC 9899:2011 does not require this to be the case.

NOTE 15.10

The function C_LOC can be used to return a value of type C_PTR that is the [C address](#) of an allocated [allocatable](#) variable. The function C_FUNLOC can be used to return a value of type C_FUNPTR that is the [C address](#) of a procedure. For C_LOC and C_FUNLOC the returned value is of an [interoperable](#) type and thus can be used in contexts where the procedure or [allocatable](#) variable is not directly allowed. For example, it could be passed as an [actual argument](#) to a C function.

Similarly, type C_FUNPTR or C_PTR can be used in a dummy argument or [structure component](#) and can have a value that is the [C address](#) of a procedure or [allocatable](#) variable, even in contexts where a procedure or [allocatable](#) variable is not directly allowed.

1 15.3.4 Interoperability of derived types and C struct types

- 2 1 Interoperability between a [derived type](#) in Fortran and a struct type in C is provided by the [BIND attribute](#) on
3 the Fortran type.
- 4 C1501 (R426) A [derived type](#) with the [BIND attribute](#) shall not have the [SEQUENCE attribute](#).
- 5 C1502 (R426) A [derived type](#) with the [BIND attribute](#) shall not have [type parameters](#).
- 6 C1503 (R426) A [derived type](#) with the [BIND attribute](#) shall not have the [EXTENDS attribute](#).
- 7 C1504 (R426) A *derived-type-def* that defines a [derived type](#) with the [BIND attribute](#) shall not have a *type-*
8 *bound-procedure-part*.
- 9 C1505 (R426) A [derived type](#) with the [BIND attribute](#) shall have at least one component.
- 10 C1506 (R426) Each component of a [derived type](#) with the [BIND attribute](#) shall be a nonpointer, nonallocatable
11 data component with [interoperable type](#) and [type parameters](#).

NOTE 15.11

The syntax rules and their constraints require that a [derived type](#) that is [interoperable](#) with a C struct type have components that are all data entities that are [interoperable](#). No component is permitted to be [allocatable](#) or a pointer, but the value of a component of type `C_FUNPTR` or `C_PTR` can be the C address of such an entity.

- 12 2 A [derived type](#) is [interoperable](#) with a C struct type if and only if the [derived type](#) has the [BIND attribute](#) (4.5.2),
13 the [derived type](#) and the C struct type have the same number of components, and the components of the [derived](#)
14 [type](#) would interoperate with corresponding components of the C struct type as described in 15.3.5 and 15.3.6 if
15 the components were variables. A component of a [derived type](#) and a component of a C struct type correspond
16 if they are declared in the same relative position in their respective type definitions.

NOTE 15.12

The names of the corresponding components of the [derived type](#) and the C struct type need not be the same.

- 17 3 There is no Fortran type that is [interoperable](#) with a C struct type that contains a bit field or that contains a
18 flexible array member. There is no Fortran type that is [interoperable](#) with a C union type.

NOTE 15.13

For example, the C type `myctype`, declared below, is [interoperable](#) with the Fortran type `myftype`, declared below.

```
typedef struct {
    int m, n;
    float r;
} myctype;

USE, INTRINSIC :: ISO_C_BINDING
TYPE, BIND(C) :: MYFTYPE
    INTEGER(C_INT) :: I, J
    REAL(C_FLOAT) :: S
END TYPE MYFTYPE
```

The names of the types and the names of the components are not significant for the purposes of determining whether a Fortran derived type is [interoperable](#) with a C struct type.

NOTE 15.14

ISO/IEC 9899:2011 requires the names and component names to be the same in order for the types to be compatible (ISO/IEC 9899:2011, subclause 6.2.7). This is similar to Fortran's rule describing when different derived type definitions describe the same [sequence type](#). This rule was not extended to determine whether a Fortran derived type is [interoperable](#) with a C struct type because the case of identifiers is significant in C but not in Fortran.

1 **15.3.5 Interoperability of scalar variables**

- 2 1 A named scalar Fortran variable is [interoperable](#) if and only if its type and type parameters are [interoperable](#), it
3 is not a [coarray](#), it has neither the [ALLOCATABLE](#) nor the [POINTER](#) attribute, and if it is of type character
4 its length is not assumed or declared by an expression that is not a [constant expression](#).
- 5 2 An [interoperable](#) scalar Fortran variable is [interoperable](#) with a scalar C entity if their types and type parameters
6 are [interoperable](#).

7 **15.3.6 Interoperability of array variables**

- 8 1 A Fortran variable that is a named array is [interoperable](#) if and only if its type and type parameters are [interop-](#)
9 [erable](#), it is not a [coarray](#), it is of explicit shape or assumed size, and if it is of type character its length is not
10 assumed or declared by an expression that is not a [constant expression](#).
- 11 2 An [explicit-shape](#) or [assumed-size](#) array of [rank](#) r , with a shape of $[e_1 \dots e_r]$ is [interoperable](#) with a C array
12 if its size is nonzero and
- 13 (1) either
- 14 (a) the array is [assumed-size](#), and the C array does not specify a size, or
- 15 (b) the array is an [explicit-shape array](#), and the extent of the last dimension (e_r) is the same as
16 the size of the C array, and
- 17 (2) either
- 18 (a) r is equal to one, and an element of the array is [interoperable](#) with an element of the C array,
19 or
- 20 (b) r is greater than one, and an [explicit-shape array](#) with shape of $[e_1 \dots e_{r-1}]$, with the
21 same type and type parameters as the original array, is [interoperable](#) with a C array of a type
22 equal to the element type of the original C array.

NOTE 15.15

An element of a multi-dimensional C array is an array type, so a Fortran array of [rank](#) one is not [interoperable](#) with a multidimensional C array.

NOTE 15.16

An [allocatable](#) array or [array pointer](#) is never [interoperable](#). Such an array does not meet the requirement of being an [explicit-shape](#) or [assumed-size](#) array.

NOTE 15.17

For example, a Fortran array declared as

```
INTEGER(C_INT) :: A(18, 3:7, *)
```

is [interoperable](#) with a C array declared as

```
int b[][5][18];
```

NOTE 15.18

The C programming language defines null-terminated strings, which are actually arrays of the C type char that have a C null character in them to indicate the last valid element. A Fortran array of type character with a **kind type parameter** equal to C_CHAR is **interoperable** with a C string.

Fortran's rules of sequence association (12.5.2.11) permit a character scalar **actual argument** to correspond to a dummy argument array. This makes it possible to argument associate a Fortran character string with a C string.

Note 15.22 has an example of interoperation between Fortran and C strings.

15.3.7 Interoperability of procedures and procedure interfaces

1 A Fortran procedure is **interoperable** if it has the **BIND attribute**, that is, if its **interface** is specified with a *proc-language-binding-spec*.

2 A Fortran procedure **interface** is **interoperable** with a C function prototype if

- (1) the **interface** has the **BIND attribute**,
- (2) either
 - (a) the **interface** describes a function whose **result** is a scalar variable that is **interoperable** with the result of the prototype or
 - (b) the **interface** describes a subroutine and the prototype has a result type of void,
- (3) the number of **dummy arguments** of the **interface** is equal to the number of formal parameters of the prototype,
- (4) any scalar dummy argument with the **VALUE attribute** is **interoperable** with the corresponding formal parameter of the prototype,
- (5) any dummy argument without the **VALUE attribute** corresponds to a formal parameter of the prototype that is of a pointer type, and either
 - the dummy argument is **interoperable** with an entity of the referenced type (ISO/IEC 9899:2011, 6.2.5, 7.19, and 7.20.1) of the formal parameter,
 - the dummy argument is a nonallocatable nonpointer variable of type CHARACTER with assumed character length and the formal parameter is a pointer to CFI_cdasc_t,
 - the dummy argument is **allocatable**, **assumed-shape**, **assumed-rank**, or a **pointer** without the **CONTIGUOUS attribute**, and the formal parameter is a pointer to CFI_cdasc_t, or
 - the dummy argument is **assumed-type** and not **allocatable**, **assumed-shape**, **assumed-rank**, or a **pointer**, and the formal parameter is a pointer to void,
- (6) each **allocatable** or **pointer** dummy argument of type CHARACTER has **deferred character length**, and
- (7) the prototype does not have variable arguments as denoted by the ellipsis (...).

NOTE 15.19

The **referenced type** of a C pointer type is the C type of the object that the C pointer type points to. For example, the referenced type of the pointer type `int *` is `int`.

NOTE 15.20

The C language allows specification of a C function that can take a variable number of arguments (ISO/IEC 9899:2011, 7.16). This part of ISO/IEC 1539 does not provide a mechanism for Fortran procedures to interoperate with such C functions.

3 A formal parameter of a C function prototype corresponds to a **dummy argument** of a Fortran **interface** if they are in the same relative positions in the C parameter list and the **dummy argument** list, respectively.

- 1 4 In a reference from C to a Fortran procedure with an interoperable [interface](#), a C actual argument shall be the
 2 address of a [C descriptor](#) for the intended [effective argument](#) if the corresponding [dummy argument](#) interoperates
 3 with a C formal parameter that is a pointer to `CFI_cdesc_t`. In this [C descriptor](#), the members other than
 4 `attribute` and `type` shall describe an object with the same characteristics as the intended [effective argument](#).
 5 The value of the `attribute` member of the [C descriptor](#) shall be compatible with the characteristics of the [dummy](#)
 6 [argument](#). The `type` member shall have a value that depends on the intended [effective argument](#) as follows:
- 7 • if the [dynamic type](#) of the intended [effective argument](#) is an interoperable type listed in Table 15.4, the
 8 corresponding value for that type;
 - 9 • if the [dynamic type](#) of the intended [effective argument](#) is an [intrinsic type](#) for which the processor defines
 10 a nonnegative type specifier value not listed in Table 15.4, that type specifier value;
 - 11 • otherwise, `CFI_type_other`.
- 12 5 When an interoperable Fortran procedure with a [simply contiguous dummy argument](#) is invoked from C and the
 13 actual argument is the address of a [C descriptor](#) for a discontinuous object, the Fortran processor shall handle
 14 the difference in contiguity.
- 15 6 When an interoperable C procedure whose Fortran interface has a [simply contiguous dummy argument](#) is invoked
 16 from Fortran and the [effective argument](#) is discontinuous, the Fortran processor shall ensure that the C procedure
 17 receives a descriptor for a contiguous object.
- 18 7 When an interoperable C procedure whose Fortran interface has a [simply contiguous dummy argument](#) is invoked
 19 from C, and the actual argument is the address of a [C descriptor](#) for a discontinuous object, the C code within
 20 the procedure shall be prepared to handle the discontinuous argument.
- 21 8 If an interoperable procedure defined by means other than Fortran has an optional [dummy argument](#), and the
 22 corresponding [actual argument](#) in a reference from Fortran is absent, the procedure is invoked with a null pointer
 23 for that argument. If an interoperable procedure defined by means of Fortran is invoked by a C function, an
 24 optional [dummy argument](#) is absent if and only if the corresponding argument in the invocation is a null pointer.

NOTE 15.21

For example, a Fortran procedure [interface](#) described by

```

INTERFACE
  FUNCTION FUNC(I, J, K, L, M) BIND(C)
    USE, INTRINSIC :: ISO_C_BINDING
    INTEGER(C_SHORT) :: FUNC
    INTEGER(C_INT), VALUE :: I
    REAL(C_DOUBLE) :: J
    INTEGER(C_INT) :: K, L(10)
    TYPE(C_PTR), VALUE :: M
  END FUNCTION FUNC
END INTERFACE

```

is [interoperable](#) with the C function prototype

```
short func(int i, double *j, int *k, int l[10], void *m);
```

A C pointer can correspond to a Fortran dummy argument of type `C_PTR` with the `VALUE` attribute or to a Fortran scalar that does not have the `VALUE` attribute. In the above example, the C pointers `j` and `k` correspond to the Fortran scalars `J` and `K`, respectively, and the C pointer `m` corresponds to the Fortran dummy argument `M` of type `C_PTR`.

NOTE 15.22

The interoperability of Fortran procedure [interfaces](#) with C function prototypes is only one part of invocation of a C function from Fortran. There are four pieces to consider in such an invocation: the procedure reference, the Fortran procedure [interface](#), the C function prototype, and the C function. Conversely, the invocation of a Fortran procedure from C involves the function reference, the C function prototype, the Fortran procedure [interface](#), and the Fortran procedure. In order to determine whether a reference is allowed, it is necessary to consider all four pieces.

For example, consider a C function that can be described by the C function prototype

```
void copy(char in[], char out[]);
```

Such a function can be invoked from Fortran as follows:

```
USE, INTRINSIC :: ISO_C_BINDING, ONLY: C_CHAR, C_NULL_CHAR
INTERFACE
  SUBROUTINE COPY(IN, OUT) BIND(C)
    IMPORT C_CHAR
    CHARACTER(KIND=C_CHAR), DIMENSION(*) :: IN, OUT
  END SUBROUTINE COPY
END INTERFACE

CHARACTER(LEN=10, KIND=C_CHAR) :: &
&   DIGIT_STRING = C_CHAR_'123456789' // C_NULL_CHAR
CHARACTER(KIND=C_CHAR) :: DIGIT_ARR(10)

CALL COPY(DIGIT_STRING, DIGIT_ARR)
PRINT '(1X, A1)', DIGIT_ARR(1:9)
END
```

The procedure reference has character string [actual arguments](#). These correspond to character array [dummy arguments](#) in the procedure [interface body](#) as allowed by Fortran's rules of sequence association ([12.5.2.11](#)). Those array [dummy arguments](#) in the procedure [interface](#) are [interoperable](#) with the formal parameters of the C function prototype. The C function is not shown here, but is assumed to be compatible with the C function prototype.

NOTE 15.23

The requirements on the Fortran processor when a discontinuous [actual argument](#) is being passed to a [simply contiguous dummy argument](#) are such that the C programmer has the same functionality (and safety) as the Fortran programmer, when either the calling or called procedure are Fortran procedures. The requirements on the C procedure, in the case when both the called and calling procedure are C procedures, effectively require that the C procedure not access memory through the descriptor that is not described by the descriptor; otherwise the program will not conform to this part of ISO/IEC 1539. A [dummy argument](#) is [simply contiguous](#) if it has the [CONTIGUOUS](#) attribute or is an array that is not [assumed-shape](#), [assumed-rank](#), or a [pointer](#).

1 15.4 C descriptors

- 2 1 A [C descriptor](#) is a C structure of type [CFI_cdesc_t](#). Together with library functions that have standard
3 prototypes, it provides a means for describing and manipulating Fortran data objects from within a C function.
4 This C structure is defined in the source file [ISO_Fortran_binding.h](#).

15.5 The source file ISO_Fortran_binding.h

15.5.1 Summary of contents

- 1 The source file ISO_Fortran_binding.h shall contain the C structure definitions, typedef declarations, macro definitions, and function prototypes specified in subclauses 15.5.2 to 15.5.5. The definitions and declarations in ISO_Fortran_binding.h can be used by a C function to interpret and manipulate a C descriptor. These provide a means to specify a C prototype that interoperates with a Fortran interface that has a non-interoperable dummy variable (15.3.7).
- 2 The source file ISO_Fortran_binding.h may be included in any order relative to the standard C headers, and may be included more than once in a given scope, with no effect different from being included only once, other than the effect on line numbers.
- 3 A C source file that includes the ISO_Fortran_binding.h header file shall not use any names starting with CFI_ that are not defined in the header, and shall not define any of the structure names defined in the header as macro names. All names other than structure member names defined in the header begin with CFI_ or an underscore character, or are defined by a standard C header that it includes.

15.5.2 The CFI_dim_t structure type

- 1 CFI_dim_t is a typedef name for a C structure. It is used to represent lower bound, extent, and memory stride information for one dimension of an array. The type CFI_index_t is described in 15.5.4. CFI_dim_t contains at least the following members in any order.

CFI_index_t lower_bound; The value is equal to the value of the lower bound for the dimension being described.

CFI_index_t extent; The value is equal to the number of elements in the dimension being described, or -1 for the final dimension of an assumed-size array.

CFI_index_t sm; The value is equal to the memory stride for a dimension; this is the difference in bytes between the addresses of successive elements in the dimension being described.

15.5.3 The CFI_cdesc_t structure type

- 1 CFI_cdesc_t is a typedef name for a C structure, which contains a flexible array member. It shall contain at least the members described in this subclause. The values of these members of a structure of type CFI_cdesc_t that is produced by the functions and macros specified in this part of ISO/IEC 1539, or received by a C function when invoked by a Fortran procedure, shall have the properties described in this subclause.

- 2 The first three members of the structure shall be **base_addr**, **elem_len**, and **version** in that order. The final member shall be **dim**. All other members shall be between **version** and **dim**, in any order. The types CFI_attribute_t, CFI_rank_t, and CFI_type_t are described in 15.5.4. The type CFI_dim_t is described in 15.5.2.

void * base_addr; If the object is an unallocated allocatable variable or a pointer that is disassociated, the value is a null pointer. If the object has zero size, the value is not a null pointer but is otherwise processor-dependent. Otherwise, the value is the base address of the object being described. The base address of a scalar is its C address. The base address of an array is the C address of the first element in Fortran array element order.

size_t elem_len; If the object is scalar, the value is the storage size in bytes of the object; otherwise, the value is the storage size in bytes of an element of the object.

int version; The value is equal to the value of CFI_VERSION in the source file ISO_Fortran_binding.h that defined the format and meaning of this C descriptor when the descriptor was established.

- 1 **CFI_rank_t rank**; The value is equal to the number of dimensions of the Fortran object being described; if
2 the object is scalar, the value is zero.
- 3 **CFI_type_t type**; The value is equal to the specifier for the type of the object. Each interoperable intrinsic C
4 type has a specifier. Specifiers are also provided to indicate that the type of the object is an interoperable
5 structure, or is unknown. The macros listed in Table 15.4 provide values that correspond to each specifier.
- 6 **CFI_attribute_t attribute**; The value is equal to the value of an attribute code that indicates whether the
7 object described is [allocatable](#), a [data pointer](#), or a nonallocatable nonpointer data object. The macros
8 listed in Table 15.3 provide values that correspond to each code.
- 9 **CFI_dim_t dim**; The number of elements in the `dim` array is equal to the rank of the object. Each element of
10 the array contains the lower bound, extent, and memory stride information for the corresponding dimension
11 of the Fortran object.
- 12 3 For a [C descriptor](#) of an array pointer or [allocatable](#) array, the value of the `lower_bound` member of each element
13 of the `dim` member of the descriptor is determined by argument association, allocation, or pointer association.
14 For a [C descriptor](#) of a nonallocatable nonpointer object, the value of the `lower_bound` member of each element
15 of the `dim` member of the descriptor is zero.
- 16 4 There shall be an ordering of the dimensions such that the absolute value of the `sm` member of the first dimension
17 is not less than the `elem_len` member of the [C descriptor](#) and the absolute value of the `sm` member of each
18 subsequent dimension is not less than the absolute value of the `sm` member of the previous dimension multiplied
19 by the extent of the previous dimension.
- 20 5 In a [C descriptor](#) of an [assumed-size array](#), the `extent` member of the last element of the `dim` member has the
21 value `-1`.

NOTE 15.24

The reason for the restriction on the absolute values of the `sm` members is to ensure that there is no overlap between the elements of the array that is being described, while allowing for the reordering of subscripts. Within Fortran, such a reordering can be achieved with the intrinsic function `TRANSPOSE` or the intrinsic function `RESHAPE` with the optional argument `ORDER`, and an optimizing compiler can accommodate it without making a copy by constructing the appropriate descriptor whenever it can determine that a copy is not needed.

NOTE 15.25

The value of `elem_len` for a Fortran `CHARACTER` object is equal to the character length times the number of bytes of a single character of that kind. If the kind is `C_CHAR`, this value will be equal to the character length.

22 **15.5.4 Macros and typedefs in ISO_Fortran_binding.h**

- 23 1 Except for `CFI_CDESC_T`, each macro defined in `ISO_Fortran_binding.h` expands to an integer constant
24 expression that is either a single token or a parenthesized expression that is suitable for use in `#if` preprocessing
25 directives.
- 26 2 `CFI_CDESC_T` is a function-like macro that takes one argument, which is the rank of the [C descriptor](#) to create,
27 and evaluates to an unqualified type of suitable size and alignment for defining a variable to use as a [C descriptor](#)
28 of that rank. The argument shall be an integer constant expression with a value that is greater than or equal to
29 zero and less than or equal to `CFI_MAX_RANK`. A pointer to a variable declared using `CFI_CDESC_T` can
30 be cast to `CFI_cdesc_t*`. A variable declared using `CFI_CDESC_T` shall not have an initializer.

NOTE 15.26

The `CFI_CDESC_T` macro provides the memory for a **C descriptor**. The address of an entity declared using the macro is not usable as an actual argument corresponding to a formal parameter of type `CFI_cdesc_t *` without an explicit cast. For example, the following code uses `CFI_CDESC_T` to declare a **C descriptor** of rank 5 and pass it to `CFI_deallocate` (15.5.5.4).

```
CFI_CDESC_T(5) object;
int ind;
... code to define and use C descriptor ...
ind = CFI_deallocate((CFI_cdesc_t *)&object);
```

- 1 3 `CFI_index_t` is a typedef name for a standard signed integer type capable of representing the result of subtracting
2 two pointers.
- 3 4 The `CFI_MAX_RANK` macro has a processor-dependent value equal to the largest rank supported. The value
4 shall be greater than or equal to 15. `CFI_rank_t` is a typedef name for a standard integer type capable of
5 representing the largest supported rank.
- 6 5 The `CFI_VERSION` macro has a processor-dependent value that encodes the version of the `ISO_Fortran_`
7 `binding.h` source file containing this macro. This value should be increased if a new version of the source file is
8 incompatible with the previous version.
- 9 6 The macros in Table 15.3 are for use as attribute codes. The values shall be nonnegative and distinct. `CFI_`
10 `attribute_t` is a typedef name for a standard integer type capable of representing the values of the attribute
11 codes.

Table 15.3: `ISO_Fortran_binding.h` macros for attribute codes

Macro name	Attribute
<code>CFI_attribute_pointer</code>	data pointer
<code>CFI_attribute_allocatable</code>	allocatable
<code>CFI_attribute_other</code>	nonallocatable nonpointer

- 12 7 `CFI_attribute_pointer` specifies a data object with the Fortran `POINTER` attribute. `CFI_attribute_allocatable`
13 specifies an object with the Fortran `ALLOCATABLE` attribute. `CFI_attribute_other` specifies a nonallocatable
14 nonpointer object.
- 15 8 The macros in Table 15.4 are for use as type specifiers. The value for `CFI_type_other` shall be negative and
16 distinct from all other type specifiers. `CFI_type_struct` specifies a C structure that is interoperable with a
17 Fortran derived type; its value shall be positive and distinct from all other type specifiers. If a C type is not
18 interoperable with a Fortran type and kind supported by the Fortran processor, its macro shall evaluate to a
19 negative value. Otherwise, the value for an intrinsic type shall be positive.
- 20 9 If the processor supports interoperability of a Fortran **intrinsic type** with a C type not listed in Table 15.4,
21 the processor shall define a type specifier value for that type which is positive and distinct from all other type
22 specifiers.
- 23 10 `CFI_type_t` is a typedef name for a standard integer type capable of representing the values for the supported
24 type specifiers.

Table 15.4: `ISO_Fortran_binding.h` macros for type codes

Macro name	C Type
<code>CFI_type_signed_char</code>	signed char
<code>CFI_type_short</code>	short int

ISO_Fortran_binding.h macros for type codes (cont.)

Macro name	C Type
CFI_type_int	int
CFI_type_long	long int
CFI_type_long_long	long long int
CFI_type_size_t	size_t
CFI_type_int8_t	int8_t
CFI_type_int16_t	int16_t
CFI_type_int32_t	int32_t
CFI_type_int64_t	int64_t
CFI_type_int_least8_t	int_least8_t
CFI_type_int_least16_t	int_least16_t
CFI_type_int_least32_t	int_least32_t
CFI_type_int_least64_t	int_least64_t
CFI_type_int_fast8_t	int_fast8_t
CFI_type_int_fast16_t	int_fast16_t
CFI_type_int_fast32_t	int_fast32_t
CFI_type_int_fast64_t	int_fast64_t
CFI_type_intmax_t	intmax_t
CFI_type_intptr_t	intptr_t
CFI_type_ptrdiff_t	ptrdiff_t
CFI_type_float	float
CFI_type_double	double
CFI_type_long_double	long double
CFI_type_float_Complex	float _Complex
CFI_type_double_Complex	double _Complex
CFI_type_long_double_Complex	long double _Complex
CFI_type_Bool	_Bool
CFI_type_char	char
CFI_type_cptr	void *
CFI_type_struct	interoperable C structure
CFI_type_other	Not otherwise specified

NOTE 15.27

The values for different C types can be the same; for example, CFI_type_int and CFI_type_int32_t might have the same value.

- 1 11 The macros in Table 15.5 are for use as error codes. The macro CFI_SUCCESS shall be defined to be the integer
 2 constant 0. The value of each macro other than CFI_SUCCESS shall be nonzero and shall be different from the
 3 values of the other macros specified in this subclause. Error conditions other than those listed in this subclause
 4 should be indicated by error codes different from the values of the macros named in this subclause.
- 5 12 The values of the macros in Table 15.5 indicate the error condition described.

Table 15.5: ISO_Fortran_binding.h macros for error codes

Macro name	Error condition
CFI_SUCCESS	No error detected.
CFI_ERROR_BASE_ADDR_NULL	The base address member of a C descriptor is a null pointer in a context that requires a non-null pointer value.
CFI_ERROR_BASE_ADDR_NOT_NULL	The base address member of a C descriptor is not a null pointer in a context that requires a null pointer value.
CFI_INVALID_ELEM_LEN	The value supplied for the element length member of a C descriptor is not valid.

ISO_Fortran_binding.h macros for error codes

(cont.)

Macro name	Error condition
CFI_INVALID_RANK	The value supplied for the rank member of a C descriptor is not valid.
CFI_INVALID_TYPE	The value supplied for the type member of a C descriptor is not valid.
CFI_INVALID_ATTRIBUTE	The value supplied for the attribute member of a C descriptor is not valid.
CFI_INVALID_EXTENT	The value supplied for the extent member of a CFI_dim_t structure is not valid.
CFI_INVALID_DESCRIPTOR	A C descriptor is invalid in some way.
CFI_ERROR_MEM_ALLOCATION	Memory allocation failed.
CFI_ERROR_OUT_OF_BOUNDS	A reference is out of bounds.

15.5.5 Functions declared in ISO_Fortran_binding.h

15.5.5.1 Arguments and results of the functions

1 Some of the functions described in 15.5.5 return an error indicator; this is an integer value that indicates whether an error condition was detected. The value zero indicates that no error condition was detected, and a nonzero value indicates which error condition was detected. Table 15.5 lists standard error conditions and macro names for their corresponding error codes. A processor is permitted to detect other error conditions. If an invocation of a function defined in 15.5.5 could detect more than one error condition and an error condition is detected, which error condition is detected is processor dependent.

2 In function arguments representing subscripts, bounds, extents, or strides, the ordering of the elements is the same as the ordering of the elements of the dim member of a C descriptor.

3 Prototypes for these functions, or equivalent macros, are provided in the ISO_Fortran_binding.h file as described in 15.5.5. It is unspecified whether the functions defined by this header are macros or identifiers declared with external linkage. If a macro definition is suppressed in order to access an actual function, the behavior is undefined.

NOTE 15.28

These functions are allowed to be macros to provide extra implementation flexibility. For example, CFI_ establish could include the value of CFI_VERSION in the header used to compile the call to CFI_ establish as an extra argument of the actual function used to establish the C descriptor.

15.5.5.2 The CFI_address function

1 **Synopsis.** C address of an object described by a C descriptor.

```
void *CFI_address(const CFI_cdesc_t *dv, const CFI_index_t subscripts[]);
```

2 **Formal Parameters.**

dv shall be the address of a C descriptor describing the object. The object shall not be an unallocated allocatable variable or a pointer that is not associated.

subscripts shall be a null pointer or the address of an array of type CFI_index_t. If the object is an array, **subscripts** shall be the address of an array of CFI_index_t with at least *n* elements, where *n* is the rank of the object. The value of **subscripts**[*i*] shall be within the bounds of dimension *i* specified by the **dim** member of the C descriptor.

3 **Result Value.** If the object is an array of rank *n*, the result is the C address of the element of the object that

1 the first n elements of the `subscripts` argument would specify if used as subscripts. If the object is scalar, the
2 result is its `C address`.

3 4 **Example.** If `dv` is the address of a `C descriptor` for the Fortran array `A` declared as

```
4 REAL(C_FLOAT) :: A(100, 100)
```

5 the following code calculates the `C address` of `A(5, 10)`:

```
6 CFI_index_t subscripts[2];
7 float *address;
8 subscripts[0] = 4;
9 subscripts[1] = 9;
10 address = (float *) CFI_address(dv, subscripts );
```

11 15.5.5.3 The `CFI_allocate` function

12 1 **Synopsis.** Allocate memory for an object described by a `C descriptor`.

```
13 int CFI_allocate(CFI_cdesc_t *dv, const CFI_index_t lower_bounds[],
14                const CFI_index_t upper_bounds[], size_t elem_len);
```

15 2 **Formal Parameters.**

16 `dv` shall be the address of a `C descriptor` specifying the rank and type of the object. The `base_`
17 `addr` member of the `C descriptor` shall be a null pointer. If the type is not a character type, the
18 `elem_len` member shall specify the element length. The `attribute` member shall have a value of
19 `CFI_attribute_allocatable` or `CFI_attribute_pointer`.

20 `lower_bounds` shall be the address of an array with at least `dv->rank` elements.

21 `upper_bounds` shall be the address of an array with at least `dv->rank` elements.

22 `elem_len` If the type specified in the `C descriptor` type is a Fortran character type, the value of `elem_len`
23 shall be the storage size in bytes of an element of the object; otherwise, `elem_len` is ignored.

24 3 **Description.** Successful execution of `CFI_allocate` allocates memory for the object described by the `C`
25 `descriptor` with the address `dv` using the same mechanism as the Fortran `ALLOCATE statement`, and assigns the
26 address of that memory to `dv->base_addr`. The first `dv->rank` elements of the `lower_bounds` and `upper_bounds`
27 arguments provide the lower and upper Fortran bounds, respectively, for each corresponding dimension of the
28 object. The supplied lower and upper bounds override any current dimension information in the `C descriptor`.
29 If the rank is zero, the `lower_bounds` and `upper_bounds` arguments are ignored. If the type specified in the `C`
30 `descriptor` is a character type, the supplied element length overrides the current element-length information in
31 the descriptor.

32 If an error is detected, the `C descriptor` is not modified.

33 4 **Result Value.** The result is an error indicator.

34 5 **Example.** If `dv` is the address of a `C descriptor` for the Fortran array `A` declared as

```
35 REAL, ALLOCATABLE :: A(:, :)
```

36 and the array is not allocated, the following code allocates it to be of shape `[100, 500]`:

```
37 CFI_index_t lower[2], upper[2];
38 int ind;
39 lower[0] = 1; lower[1] = 1;
40 upper[0] = 100; upper[1] = 500;
41 ind = CFI_allocate(dv, lower, upper, 0);
```

1 15.5.5.4 The CFI_deallocate function

2 1 **Synopsis.** Deallocate memory for an object described by a [C descriptor](#).

```
3 int CFI_deallocate(CFI_cdesc_t *dv);
```

4 2 **Formal Parameter.** `dv` shall be the address of a [C descriptor](#) describing the object. It shall have been allocated using the same mechanism as the Fortran [ALLOCATE statement](#). If the object is a pointer, it shall be associated with a target satisfying the conditions for successful deallocation by the Fortran [DEALLOCATE statement \(6.7.3\)](#).

8 3 **Description.** Successful execution of `CFI_deallocate` deallocates memory for the object using the same mechanism as the Fortran [DEALLOCATE statement](#), and the `base_addr` member of the [C descriptor](#) becomes a null pointer.

11 If an error is detected, the [C descriptor](#) is not modified.

12 4 **Result Value.** The result is an error indicator.

13 5 **Example.** If `dv` is the address of a [C descriptor](#) for the Fortran array `A` declared as

```
14 REAL, ALLOCATABLE :: A(:, :)
```

15 and the array is allocated, the following code deallocates it:

```
16 int ind;
17 ind = CFI_deallocate(dv);
```

18 15.5.5.5 The CFI_establish function

19 1 **Synopsis.** Establish a [C descriptor](#).

```
20 int CFI_establish(CFI_cdesc_t *dv, void *base_addr, CFI_attribute_t attribute,
21                 CFI_type_t type, size_t elem_len, CFI_rank_t rank,
22                 const CFI_index_t extents[]);
```

23 2 **Formal Parameters.**

24 `dv` shall be the address of a data object large enough to hold a [C descriptor](#) of the rank specified by `rank`. It shall not have the same value as either a C formal parameter that corresponds to a Fortran actual argument or a C actual argument that corresponds to a Fortran dummy argument. It shall not be the address of a [C descriptor](#) that describes an allocated allocatable object.

28 `base_addr` shall be a null pointer or the base address of the object to be described. If it is not a null pointer, it shall be the address of a contiguous storage sequence that is appropriately aligned (ISO/IEC 9899:2011 3.2) for an object of the type specified by `type`.

31 `attribute` shall be one of the attribute codes in Table 15.3. If it is `CFI_attribute_allocatable`, `base_addr` shall be a null pointer.

33 `type` shall be one of the type codes in Table 15.4.

34 `elem_len` If the type is equal to `CFI_type_struct`, `CFI_type_other`, or a Fortran character type code, `elem_len` shall be greater than zero and equal to the storage size in bytes of an element of the object. Otherwise, `type` will be ignored.

37 `rank` shall have a value in the range $0 \leq \text{rank} \leq \text{CFI_MAX_RANK}$. It specifies the rank of the object.

38 `extents` is ignored if `rank` is equal to zero or if `base_addr` is a null pointer. Otherwise, it shall be the address of an array with `rank` elements; the value of each element shall be nonnegative, and `extents[i]` specifies the extent of dimension i of the object.

1 3 **Description.** Successful execution of `CFI_establish` updates the object with the address `dv` to be an established
 2 **C descriptor** for a nonallocatable nonpointer data object of known shape, an unallocated allocatable object, or a
 3 data pointer. If `base_addr` is not a null pointer, it is for a nonallocatable entity that is a scalar or a contiguous
 4 array; if the `attribute` argument has the value `CFI_attribute_pointer`, the lower bounds of the object described
 5 by `dv` are set to zero. If `base_addr` is a null pointer, the established **C descriptor** is for an unallocated allocatable,
 6 a disassociated pointer, or is a **C descriptor** that has the `attribute` `CFI_attribute_other` but does not describe
 7 a data object. If `base_addr` is the **C address** of a Fortran data object, the `type` and `elem_len` arguments shall be
 8 consistent with the `type` and `type` parameters of the Fortran data object. The remaining properties of the object
 9 are given by the other arguments.

10 If an error is detected, the object with the address `dv` is not modified.

11 4 **Result Value.** The result is an error indicator.

NOTE 15.29

`CFI_establish` is used to initialize a **C descriptor** declared in C with `CFI_CDESC_T` before passing it to any other functions as an actual argument, in order to set the rank, attribute, type and element length.

NOTE 15.30

A **C descriptor** with `attribute` `CFI_attribute_other` and `base_addr` a null pointer can be used as the argument `result` in calls to `CFI_section` or `CFI_select_part`, which will produce a **C descriptor** for a nonallocatable nonpointer data object.

12 5 **Examples.**

13 *Case (i):* The following code fragment establishes a **C descriptor** for an unallocated rank-one allocatable array
 14 that can be passed to Fortran for allocation there.

```
15     CFI_rank_t rank;
16     CFI_CDESC_T(1) field;
17     int ind;
18     rank = 1;
19     ind = CFI_establish((CFI_cdesc_t *)&field, NULL, CFI_attribute_allocatable,
20                       CFI_type_double, 0, rank, NULL);
```

21 *Case (ii):* Given the Fortran type definition

```
22     TYPE, BIND(C) :: T
23         REAL(C_DOUBLE) :: X
24         COMPLEX(C_DOUBLE_COMPLEX) :: Y
25     END TYPE
```

26 and a Fortran subprogram that has an assumed-shape dummy argument of type T, the following
 27 code fragment creates a descriptor `a_fortran` for an array of size 100 that can be used as the actual
 28 argument in an invocation of the subprogram from C:

```
29     typedef struct {double x; double _Complex y;} t;
30     t a_c[100];
31     CFI_CDESC_T(1) a_fortran;
32     int ind;
33     CFI_index_t extent[1];
34
35     extent[0] = 100;
36     ind = CFI_establish((CFI_cdesc_t *)&a_fortran, a_c, CFI_attribute_other,
37                       CFI_type_struct, sizeof(t), 1, extent);
```

1 15.5.5.6 The CFI_is_contiguous function

2 1 **Synopsis.** Test contiguity of an array.

```
3 int CFI_is_contiguous(const CFI_cdesc_t * dv);
```

4 2 **Formal Parameter.** `dv` shall be the address of a [C descriptor](#) describing an array. The `base_addr` member of the [C descriptor](#) shall not be a null pointer.

6 3 **Result Value.** The value of the result is 1 if the array described by `dv` is contiguous, and 0 otherwise.

NOTE 15.31

[Assumed-size](#) and [allocatable](#) arrays are always contiguous, and therefore the result of `CFI_is_contiguous` on a [C descriptor](#) for such an array will be equal to 1.

7 15.5.5.7 The CFI_section function

8 1 **Synopsis.** Update a [C descriptor](#) for an array section for which each element is an element of a given array.

```
9 int CFI_section(CFI_cdesc_t *result, const CFI_cdesc_t *source,
10               const CFI_index_t lower_bounds[], const CFI_index_t upper_bounds[],
11               const CFI_index_t strides[]);
```

12 2 Formal Parameters.

13 **result** shall be the address of a [C descriptor](#) with rank equal to the rank of `source` minus the number of zero strides. The `attribute` member shall have the value `CFI_attribute_other` or `CFI_attribute_pointer`. If the value of `result` is the same as either a C formal parameter that corresponds to a Fortran actual argument or a C actual argument that corresponds to a Fortran dummy argument, the `attribute` member shall have the value `CFI_attribute_pointer`.

18 Successful execution of `CFI_section` updates the `base_addr` and `dim` members of the [C descriptor](#) with the address `result` to describe the array section determined by `source`, `lower_bounds`, `upper_bounds`, and `strides`, as follows.

21 The array section is equivalent to the Fortran array section `SOURCE(sectsub1, sectsub2, ... sectsubn)`, where `SOURCE` is the array described by `source`, n is the rank of that array, and `sectsubi` is the subscript `loweri` if `stridei` is zero, and the section subscript `loweri : upperi : stridei` otherwise. The value of `loweri` is the lower bound of dimension i of `SOURCE` if `lower_bounds` is a null pointer and `lower_bounds[i]` otherwise. The value of `upperi` is the upper bound of dimension i of `SOURCE` if `upper_bounds` is a null pointer and `upper_bounds[i]` otherwise. The value of `stridei` is 1 if `strides` is a null pointer and `strides[i]` otherwise. If `stridei` has the value zero, `loweri` shall have the same value as `upperi`.

29 If an error is detected, the [C descriptor](#) with the address `result` is not modified.

30 **source** shall be the address of a [C descriptor](#) that describes a nonallocatable nonpointer array, an allocated allocatable array, or an associated array pointer. The `elem_len` and `type` members of `source` shall have the same values as the corresponding members of `result`.

33 **lower_bounds** shall be a null pointer or the address of an array with at least `source->rank` elements. If it is not a null pointer, and `stridei` is zero or $(upper_i - lower_bounds[i] + stride_i)/stride_i > 0$, the value of `lower_bounds[i]` shall be within the bounds of dimension i of `SOURCE`.

36 **upper_bounds** shall be a null pointer or the address of an array with at least `source->rank` elements. If `source` describes an [assumed-size array](#), `upper_bounds` shall not be a null pointer. If it is not a null pointer and `stridei` is zero or $(upper_bounds[i] - lower_i + stride_i)/stride_i > 0$, the value of `upper_bounds[i]` shall be within the bounds of dimension i of `SOURCE`.

40 **strides** shall be a null pointer or the address of an array with at least `source->rank` elements.

1 3 **Result Value.** The result is an error indicator.

2 4 **Examples.**

3 *Case (i):* If `source` is already the address of a **C descriptor** for the rank-one Fortran array `A`, the lower
4 bounds of `A` are equal to 1, and the lower bounds in the **C descriptor** are equal to 0, the following
5 code fragment establishes a new **C descriptor** section and updates it to describe the array section
6 `A(3::5)`:

```
7     CFI_index_t lower[1], strides[1];
8     CFI_CDESC_T(1) section;
9     int ind;
10    lower[0] = 2;
11    strides[0] = 5;
12    ind = CFI_establish((CFI_cdesc_t *)&section, NULL, CFI_attribute_other,
13                      CFI_type_float, 0, 1, NULL);
14    ind = CFI_section((CFI_cdesc_t *)&section, source, lower, NULL, strides);
```

15 *Case (ii):* If `source` is already the address of a **C descriptor** for a rank-two Fortran assumed-shape array `A`
16 with lower bounds equal to 1, the following code fragment establishes a **C descriptor** and updates
17 it to describe the rank-one array section `A(:, 42)`.

```
18    CFI_index_t lower[2], upper[2], strides[2];
19    CFI_CDESC_T(1) section;
20    int ind;
21    lower[0] = source->dim[0].lower_bound;
22    upper[0] = source->dim[0].lower_bound + source->dim[0].extent - 1;
23    strides[0] = 1;
24    lower[1] = upper[1] = source->dim[1].lower_bound + 41;
25    strides[1] = 0;
26    ind = CFI_establish((CFI_cdesc_t *)&section, NULL, CFI_attribute_other,
27                      CFI_type_float, 0, 1, NULL);
28    ind = CFI_section((CFI_cdesc_t *)&section, source, lower, upper, strides);
```

29 15.5.5.8 The `CFI_select_part` function

30 1 **Synopsis.** Update a **C descriptor** for an array section for which each element is a part of the corresponding
31 element of an array.

```
32    int CFI_select_part(CFI_cdesc_t *result, const CFI_cdesc_t *source, size_t displacement,
33                      size_t elem_len);
```

34 2 **Formal Parameters.**

35 **result** shall be the address of a **C descriptor**; `result->rank` shall have the same value as `source->rank`
36 and `result->attribute` shall have the value `CFI_attribute_other` or `CFI_attribute_pointer`. If
37 the address specified by `result` is the value of a C formal parameter that corresponds to a For-
38 tran actual argument or of a C actual argument that corresponds to a Fortran dummy argument,
39 `result->attribute` shall have the value `CFI_attribute_pointer`. The value of `result->type` spe-
40 cifies the type of the array section.

41 **source** shall be the address of a **C descriptor** for a nonallocatable nonpointer array, an allocated allocatable
42 array, or an associated array pointer.

43 **displacement** shall have a value $0 \leq \text{displacement} \leq \text{source->elem_len} - 1$, and the sum of the displacement
44 and the size in bytes of an element of the array section shall be less than or equal to `source->elem_-`
45 `len`. The address `displacement` bytes greater than the value of `source->base_addr` is the base of

1 the array section and shall be appropriately aligned (ISO/IEC 9899:2011, 3.2) for an object of the
2 type of the array section.

3 `elem_len` shall have a value equal to the storage size in bytes of an element of the array section if `result->type`
4 specifies a Fortran character type; otherwise, `elem_len` is ignored.

5 **3 Description.** Successful execution of `CFI_select_part` updates the `base_addr`, `dim`, and `elem_len` members of
6 the **C descriptor** with the address `result` for an array section for which each element is a part of the corresponding
7 element of the array described by the **C descriptor** with the address `source`. The part shall be a component of a
8 structure, a substring, or the real or imaginary part of a complex value.

9 If an error is detected, the **C descriptor** with the address `result` is not modified.

10 **4 Result Value.** The result is an error indicator.

11 **5 Example.** If `source` is already the address of a **C descriptor** for the Fortran array `A` declared with

```
12     TYPE, BIND(C) :: T
13         REAL(C_DOUBLE) :: X
14         COMPLEX(C_DOUBLE_COMPLEX) :: Y
15     END TYPE
16     TYPE(T) A(100)
```

17 the following code fragment establishes a **C descriptor** for the array `A%Y`:

```
18     typedef struct {
19         double x; double _Complex y;
20     } t;
21     CFI_CDESC_T(1) component;
22     CFI_cdesc_t * comp_cdesc = (CFI_cdesc_t *)&component;
23     CFI_index_t extent[] = { 100 };
24     (void)CFI_establish(comp_cdesc, NULL, CFI_attribute_other, CFI_type_double_Complex,
25                         sizeof(double _Complex), 1, extent);
26     (void)CFI_select_part(comp_cdesc, source, offsetof(t,y), 0);
```

27 **15.5.5.9 The CFI_setpointer function**

28 **1 Synopsis.** Update a **C descriptor** for a Fortran pointer to be associated with the whole of a given object or to
29 be disassociated.

```
30     int CFI_setpointer(CFI_cdesc_t *result, CFI_cdesc_t *source,
31                       const CFI_index_t lower_bounds[]);
```

32 **2 Formal Parameters.**

33 `result` shall be the address of a **C descriptor** for a Fortran pointer. It is updated using information from
34 the `source` and `lower_bounds` arguments.

35 `source` shall be a null pointer or the address of a **C descriptor** for a nonallocatable nonpointer data object,
36 an allocated allocatable object, or a data pointer object. If `source` is not a null pointer, the corres-
37 ponding values of the `elem_len`, `rank`, and `type` members shall be the same in the **C descriptors**
38 with the addresses `source` and `result`.

39 `lower_bounds` If `source` is not a null pointer and `source->rank` is nonzero, `lower_bounds` shall be a null pointer
40 or the address of an array with at least `source->rank` elements.

1 3 **Result Value.** The result is an error indicator.

2 4 **Description.** Successful execution of `CFI_setpointer` updates the `base_addr` and `dim` members of the `C descriptor` with the address `result` as follows:

- 4 • if `source` is a null pointer or the address of a `C descriptor` for a disassociated pointer, the updated `C descriptor` describes a disassociated pointer;
- 5 • otherwise, the `C descriptor` with the address `result` becomes a `C descriptor` for the object described by the `C descriptor` with the address `source`, except that if `source->rank` is nonzero and `lower_bounds` is not a null pointer, the lower bounds are replaced by the values of the first `source->rank` elements of the `lower_bounds` array.

10 If an error is detected, the `C descriptor` with the address `result` is not modified.

11 5 **Example.** If `ptr` is already the address of a `C descriptor` for an array pointer of rank 1, the following code updates it to be a `C descriptor` for a pointer to the same array with lower bound 0.

```
13     CFI_index_t lower_bounds[1];
14     int ind;
15     lower_bounds[0] = 0;
16     ind = CFI_setpointer(ptr, ptr, lower_bounds);
```

17 15.6 Restrictions on C descriptors

18 1 A `C descriptor` shall not be initialized, updated, or copied other than by calling the functions specified in 15.5.5.

19 2 If the address of a `C descriptor` is a formal parameter that corresponds to a Fortran actual argument or a C actual argument that corresponds to a Fortran dummy argument,

- 21 • the `C descriptor` shall not be modified if either the corresponding dummy argument in the Fortran interface has the `INTENT (IN) attribute` or the `C descriptor` is for a nonallocatable nonpointer object, and
- 22 • the `base_addr` member of the `C descriptor` shall not be accessed before it is given a value if the corresponding dummy argument in the Fortran interface has the `POINTER` and `INTENT (OUT)` attributes.

NOTE 15.32

In this context, modification refers to any change to the location or contents of the `C descriptor`, including establishment and update. The intent of these restrictions is that `C descriptors` remain intact at all times they are accessible to an active Fortran procedure, so that the Fortran code is not required to copy them.

25 15.7 Restrictions on formal parameters

26 1 Within a C function, an `allocatable` object shall be allocated or deallocated only by execution of the `CFI_allocate` and `CFI_deallocate` functions. A Fortran pointer can become associated with a target by execution of the `CFI_allocate` function.

29 2 Calling `CFI_allocate` or `CFI_deallocate` for a `C descriptor` changes the allocation status of the Fortran variable it describes.

31 3 If the address of an object is the value of a formal parameter that corresponds to a nonpointer dummy argument in an interface with the `BIND attribute`, then

- 33 • if the dummy argument has the `INTENT (IN) attribute`, the object shall not be defined or become undefined, and

- 1 • if the dummy argument has the **INTENT (OUT) attribute**, the object shall not be referenced before it is
2 defined.

- 3 4 If a formal parameter that is a pointer to **CFI_cdesc_t** corresponds to a dummy argument in an interoperable
4 procedure interface, a pointer based on the **base_addr** in that **C descriptor** shall not be used to access memory
5 that is not part of the object described by the **C descriptor**.

6 15.8 Restrictions on lifetimes

- 7 1 A **C descriptor** of, or C pointer to, any part of a Fortran object becomes undefined under the same conditions
8 that the association status of a Fortran pointer associated with that object would become undefined, and any
9 further use of it is undefined behavior (ISO/IEC 9899:2011, 3.4.3).

- 10 2 A **C descriptor** whose address is a formal parameter that corresponds to a Fortran dummy argument becomes
11 undefined on return from a call to the function from Fortran. If the dummy argument does not have either the
12 **TARGET** or **ASYNCHRONOUS** attribute, all C pointers to any part of the object described by the **C descriptor**
13 become undefined on return from the call, and any further use of them is undefined behavior.

- 14 3 If the address of a **C descriptor** is passed as an actual argument to a Fortran procedure, the lifetime (ISO/IEC
15 9899:2011, 6.2.4) of the **C descriptor** shall not end before the return from the procedure call. If an object is passed
16 to a Fortran procedure as a nonallocatable, nonpointer dummy argument, its lifetime shall not end before the
17 return from the procedure call.

- 18 4 If the lifetime of a **C descriptor** for an allocatable object that was established by C ends before the program exits,
19 the object shall be unallocated at that time.

- 20 5 If a Fortran pointer becomes associated with a data object defined by the companion processor, the association
21 status of the Fortran pointer becomes undefined when the lifetime of that data object ends.

NOTE 15.33

The following example illustrates how a **C descriptor** becomes undefined upon returning from a call to a C function.

```
REAL, TARGET :: X(1000), B
INTERFACE
  REAL FUNCTION CFUN(ARRAY) BIND(C, NAME="Cfun")
    REAL ARRAY(:)
  END FUNCTION
END INTERFACE
B = CFUN(X)
```

Cfun is a C function. Before or during the invocation of **Cfun**, the processor will create a **C descriptor** for the array **x**. On return from **Cfun**, that **C descriptor** will become undefined. In addition, because the dummy argument **ARRAY** does not have the **TARGET** or **ASYNCHRONOUS** attribute, a C pointer whose value was set during execution of **Cfun** to be the address of any part of **X** will become undefined.

22 15.9 Interoperation with C global variables

23 15.9.1 General

- 24 1 A C variable whose name has external linkage may interoperate with a **common block** or with a variable declared in
25 the scope of a module. The **common block** or variable shall be specified to have the **BIND attribute**.

- 1 2 At most one variable that is associated with a particular C variable whose name has external linkage is permitted
 2 to be declared within all the Fortran **program units** of a program. A variable shall not be initially defined by
 3 more than one processor.
- 4 3 If a **common block** is specified in a **BIND statement**, it shall be specified in a **BIND statement** with the same **binding label** in each
 5 **scoping unit** in which it is declared. A C variable whose name has external linkage interoperates with a **common block** that has been
 6 specified in a **BIND statement** if
- 7 • the C variable is of a struct type and the variables that are members of the **common block** are **interoperable** with corresponding
 8 components of the struct type, or
 - 9 • the **common block** contains a single variable, and the variable is **interoperable** with the C variable.
- 10 4 There does not have to be an associated C entity for a Fortran entity with the **BIND attribute**.

NOTE 15.34

The following are examples of the usage of the **BIND attribute** for variables and for a **common block**. The Fortran variables, C_EXTERN and C2, interoperate with the C variables, c_extern and myVariable, respectively. The Fortran **common blocks**, COM and SINGLE, interoperate with the C variables, com and single, respectively.

```

MODULE LINK_TO_C_VARS
  USE, INTRINSIC :: ISO_C_BINDING
  INTEGER(C_INT), BIND(C) :: C_EXTERN
  INTEGER(C_LONG) :: C2
  BIND(C, NAME='myVariable') :: C2

  COMMON /COM/ R, S
  REAL(C_FLOAT) :: R, S, T
  BIND(C) :: /COM/, /SINGLE/
  COMMON /SINGLE/ T
END MODULE LINK_TO_C_VARS

/* Global variables. */
int c_extern;
long myVariable;
struct { float r, s; } com;
float single;

```

11 15.9.2 Binding labels for common blocks and variables

- 12 1 The **binding label** of a variable or **common block** is a default character value that specifies the name by which the
 13 variable or **common block** is known to the **companion processor**.
- 14 2 If a variable or **common block** has the **BIND attribute** with the NAME= specifier and the value of its expression,
 15 after discarding leading and trailing blanks, has nonzero length, the variable or **common block** has this as its **binding**
 16 **label**. The case of letters in the **binding label** is significant. If a variable or **common block** has the **BIND attribute**
 17 specified without a NAME= specifier, the **binding label** is the same as the name of the entity using lower case
 18 letters. Otherwise, the variable or **common block** has no **binding label**.
- 19 3 The **binding label** of a C variable whose name has external linkage is the same as the name of the C variable. A
 20 Fortran variable or **common block** with the **BIND attribute** that has the same **binding label** as a C variable whose
 21 name has external linkage is **linkage associated** (16.5.1.5) with that variable.

15.10 Interoperation with C functions

15.10.1 Definition and reference of interoperable procedures

- 1 A procedure that is [interoperable](#) may be defined either by means other than Fortran or by means of a Fortran subprogram, but not both.
- 2 If the procedure is defined by means other than Fortran, it shall
 - be describable by a C prototype that is [interoperable](#) with the [interface](#),
 - have a name that has external linkage as defined by 6.2.2 of ISO/IEC 9899:2011, and
 - have the same [binding label](#) as the [interface](#).
- 3 A reference to such a procedure causes the function described by the C prototype to be called as specified in ISO/IEC 9899:2011.
- 4 A reference in C to a procedure that has the [BIND attribute](#), has the same [binding label](#), and is defined by means of Fortran, causes the Fortran procedure to be invoked. A C function shall not invoke a function pointer whose value is the result of a reference to [C_FUNLOC](#) with a noninteroperable argument.
- 5 A procedure defined by means of Fortran shall not invoke setjmp or longjmp (ISO/IEC 9899:2011, 7.13). If a procedure defined by means other than Fortran invokes setjmp or longjmp, that procedure shall not cause any procedure defined by means of Fortran to be invoked. A procedure defined by means of Fortran shall not be invoked as a signal handler (ISO/IEC 9899:2011, 7.14.1).
- 6 If a procedure defined by means of Fortran and a procedure defined by means other than Fortran perform input/output operations on the same [external file](#), the results are processor dependent (9.5.4).
- 7 If the value of a C function pointer will be the result of a reference to [C_FUNLOC](#) with a noninteroperable argument, it is recommended that the C function pointer be declared to have the type `void (*)()`.

15.10.2 Binding labels for procedures

- 1 The [binding label](#) of a procedure is a default character value that specifies the name by which a procedure with the [BIND attribute](#) is known to the [companion processor](#).
- 2 If a procedure has the [BIND attribute](#) with the `NAME=` specifier and the value of its expression, after discarding leading and trailing blanks, has nonzero length, the procedure has this as its [binding label](#). The case of letters in the [binding label](#) is significant. If a procedure has the [BIND attribute](#) with no `NAME=` specifier, and the procedure is not a [dummy procedure](#), [internal procedure](#), or procedure pointer, then the [binding label](#) of the procedure is the same as the name of the procedure using lower case letters. Otherwise, the procedure has no [binding label](#).

C1507 A procedure defined in a submodule shall not have a [binding label](#) unless its [interface](#) is declared in the ancestor module.
- 3 The [binding label](#) for a C function whose name has external linkage is the same as the C function name.

NOTE 15.35

In the following sample, the [binding label](#) of `C_SUB` is `"c_sub"`, and the [binding label](#) of `C_FUNC` is `"C_funC"`.

```
SUBROUTINE C_SUB() BIND(C)
  ...
END SUBROUTINE C_SUB
```

NOTE 15.35 (cont.)

```

INTEGER(C_INT) FUNCTION C_FUNC() BIND(C, NAME="C_func")
  USE, INTRINSIC :: ISO_C_BINDING
  ...
END FUNCTION C_FUNC

```

ISO/IEC 9899:2011 permits functions to have names that are not permitted as Fortran names; it also distinguishes between names that would be considered as the same name in Fortran. For example, a C name can begin with an underscore, and C names that differ in case are distinct names.

The specification of a [binding label](#) allows a program to use a Fortran name to refer to a procedure defined by a [companion processor](#).

1 15.10.3 Exceptions and IEEE arithmetic procedures

- 2 1 A procedure defined by means other than Fortran shall not use signal (ISO/IEC 9899:2011, 7.14.1) to change the
3 [handling of any exception](#) that is being handled by the Fortran processor.
- 4 2 A procedure defined by means other than Fortran shall not alter the floating-point status ([14.7](#)) other than by
5 setting an exception flag to signaling.
- 6 3 The values of the floating-point exception flags on entry to a procedure defined by means other than Fortran are
7 processor dependent.

8 15.10.4 Asynchronous communication

- 9 1 Asynchronous communication for a Fortran variable occurs through the action of procedures defined by means
10 other than Fortran. It is initiated by execution of an asynchronous communication initiation procedure and
11 completed by execution of an asynchronous communication completion procedure. Between the execution of the
12 initiation and completion procedures, any variable of which any part is associated with any part of the asyn-
13 chronous communication variable is a pending communication affector. Whether a procedure is an asynchronous
14 communication initiation or completion procedure is processor dependent.
- 15 2 Asynchronous communication is either input communication or output communication. For input communication,
16 a pending communication affector shall not be referenced, become defined, become undefined, become associated
17 with a dummy argument that has the [VALUE attribute](#), or have its pointer association status changed. For
18 output communication, a pending communication affector shall not be redefined, become undefined, or have its
19 pointer association status changed. The restrictions for asynchronous input communication are the same as for
20 asynchronous input data transfer. The restrictions for asynchronous output communication are the same as for
21 asynchronous output data transfer.

NOTE 15.36

Asynchronous communication can be used for nonblocking MPI calls such as MPI_IRecv and MPI_ISEND. For example,

```

REAL :: BUF(100,100)
... ! Code that involves BUF
BLOCK
  ASYNCHRONOUS :: BUF
  CALL MPI_IRecv(BUF,...REQ,...)
  ... ! Code that does not involve BUF
  CALL MPI_WAIT(REQ,...)
END BLOCK

```

NOTE 15.36 (cont.)

... ! Code that involves BUF

In this example, there is asynchronous input communication and BUF is a pending communication affector between the two calls. MPI_IRecv can return while the communication (reading values into BUF) is still underway. The intent is that the code between MPI_IRecv and MPI_WAIT can execute without waiting for this communication to complete.

Similar code with the call of MPI_IRecv replaced by a call of MPI_ISEND is asynchronous output communication.

16 Scope, association, and definition

16.1 Scopes, identifiers, and entities

1 An entity is identified by an identifier.

2 The scope of

- a global identifier is a program (2.2.2),
- a local identifier is an [inclusive scope](#),
- an identifier of a [construct entity](#) is that construct (7.2.4, 8.1), and
- an identifier of a [statement entity](#) is that statement or part of that statement (3.3),

excluding any nested scope where the identifier is treated as the identifier of a different entity (16.3, 16.4).

3 An entity may be identified by

- an [image index](#) (1.3.87),
- a [name](#) (1.3.106),
- a [statement label](#) (1.3.138),
- an [external input/output unit](#) number (9.5),
- an identifier of a pending data transfer operation (9.6.2.9, 9.7),
- a submodule identifier (11.2.3),
- a [generic identifier](#) (1.3.81), or
- a [binding label](#) (1.3.16).

4 By means of association, an entity may be referred to by the same identifier or a different identifier in a different scope, or by a different identifier in the same scope.

16.2 Global identifiers

1 [Program units](#), [common blocks](#), [external procedures](#), entities with [binding labels](#), [external input/output units](#), pending data transfer operations, and [images](#) are global entities of a program. The name of a [common block](#) with no [binding label](#), [external procedure](#) with no [binding label](#), or [program unit](#) that is not a submodule is a global identifier. The submodule identifier of a submodule is a global identifier. A [binding label](#) of an entity of the program is a global identifier. An entity of the program shall not be identified by more than one [binding label](#).

2 The global identifier of an entity shall not be the same as the global identifier of any other entity. Furthermore, a [binding label](#) shall not be the same as the global identifier of any other global entity, ignoring differences in case. A processor may assign a global identifier to an entity that is not specified by this part of ISO/IEC 1539 to have a global identifier (such as an intrinsic procedure); in such a case, the processor shall ensure that this assigned global identifier differs from all other global identifiers in the program.

NOTE 16.1

An intrinsic module is not a [program unit](#), so a global identifier can be the same as the name of an intrinsic module.

NOTE 16.2

Submodule identifiers are global identifiers, but because they consist of a module name and a [descendant](#) submodule name, the name of a submodule can be the same as the name of another submodule so long as they do not have the same ancestor module.

16.3 Local identifiers**16.3.1 Classes of local identifiers**

1 Identifiers of entities in the classes

- (1) except for statement or [construct](#) entities ([16.4](#)), named variables, [named constants](#), named constructs, statement functions, [internal procedures](#), [module procedures](#), [dummy procedures](#), [intrinsic procedures](#), [external procedures](#) that have [binding labels](#), intrinsic modules, [abstract interfaces](#), [generic interfaces](#), derived types, namelist groups, [external procedures](#) accessed via USE, and statement labels,
- (2) type parameters, components, and [type-bound procedure bindings](#), in a separate class for each type,
- (3) [argument keywords](#), in a separate class for each procedure with an [explicit interface](#), and
- (4) common blocks that have [binding labels](#)

are local identifiers.

2 Within its scope, a local identifier of an entity of class (1) or class (4) shall not be the same as a global identifier used in that scope unless the global identifier

- is used only as the *use-name* of a [rename](#) in a [USE statement](#),
- is a [common block](#) name ([16.3.2](#)),
- is an [external procedure](#) name that is also a generic name, or
- is an external function name and the [inclusive scope](#) is its defining subprogram ([16.3.3](#)).

3 Within its scope, a local identifier of one class shall not be the same as another local identifier of the same class, except that a generic name may be the same as the name of a procedure as explained in [12.4.3.5](#) or the same as the name of a derived type ([4.5.10](#)). A local identifier of one class may be the same as a local identifier of another class.**NOTE 16.3**

An intrinsic procedure is inaccessible by its own name in a [scoping unit](#) that uses the same name as a local identifier of class (1) for a different entity. For example, in the program fragment

```

SUBROUTINE SUB
  ...
  A = SIN (K)
  ...
CONTAINS
  FUNCTION SIN (X)
    ...
  END FUNCTION SIN
END SUBROUTINE SUB

```

any reference to function SIN in subroutine SUB refers to the internal function SIN, not to the intrinsic function of the same name.

1 4 A local identifier identifies an entity in a scope and may be used to identify an entity in another scope except in
2 the following cases.

- 3 • The name that appears as a *subroutine-name* in a *subroutine-stmt* has limited use within the scope estab-
4 lished by the *subroutine-stmt*. It can be used to identify recursive references of the subroutine or to identify
5 a **common block** (the latter is possible only for internal and module subroutines).
- 6 • The name that appears as a *function-name* in a *function-stmt* has limited use within the scope established
7 by that *function-stmt*. It can be used to identify the **function result**, to identify recursive references of the
8 function, or to identify a **common block** (the latter is possible only for internal and module functions).
- 9 • The name that appears as an *entry-name* in an *entry-stmt* has limited use within the scope of the subprogram in which
10 the *entry-stmt* appears. It can be used to identify the **function result** if the subprogram is a function, to identify recursive
11 references, or to identify a **common block** (the latter is possible only if the *entry-stmt* is in a module subprogram).

12 16.3.2 Local identifiers that are the same as common block names

13 1 A name that identifies a **common block** in a **scoping unit** shall not be used to identify a constant or an intrinsic procedure in that
14 **scoping unit**. If a local identifier of class (1) is also the name of a **common block**, the appearance of that name in any context other
15 than as a **common block** name in a **BIND**, **COMMON**, or **SAVE** statement is an appearance of the local identifier.

16 16.3.3 Function results

17 1 For each **FUNCTION statement** or **ENTRY statement** in a function subprogram, there is a **function result**. If there is
18 no **RESULT** clause, the **function result** has the same name as the function being defined; otherwise, the **function**
19 **result** has the name specified in the **RESULT** clause.

20 16.3.4 Components, type parameters, and bindings

21 1 A component name has the scope of its derived-type definition. Outside the type definition, it may also appear
22 within a designator of a component of a structure of that type or as a **component keyword** in a **structure**
23 **constructor** for that type.

24 2 A type parameter name has the scope of its derived-type definition. Outside the derived-type definition, it may
25 also appear as a type parameter keyword in a *derived-type-spec* for the type or as the *type-param-name* of a
26 *type-param-inquiry*.

27 3 The **binding name** (4.5.5) of a **type-bound procedure** has the scope of its derived-type definition. Outside of the
28 derived-type definition, it may also appear as the *binding-name* in a procedure reference.

29 4 A generic **binding** for which the *generic-spec* is not a *generic-name* has a scope that consists of all **scoping units**
30 in which an entity of the type is accessible.

31 5 A component name or **binding name** may appear only in a scope in which it is accessible.

32 6 The accessibility of components and **bindings** is specified in 4.5.4.8 and 4.5.5.

33 16.3.5 Argument keywords

34 1 As an **argument keyword**, a **dummy argument** name in an **internal procedure**, **module procedure**, or an **interface**
35 **body** has a scope of the **scoping unit** of the **host** of the procedure or **interface body**. As an **argument keyword**,
36 the name of a **dummy argument** of a procedure declared by a **procedure declaration statement** that specifies an
37 **explicit interface** has a scope of the **scoping unit** containing the **procedure declaration statement**. It may appear
38 only in a procedure reference for the procedure of which it is a **dummy argument**. If the procedure is accessible

1 in another [scoping unit](#) by [use](#) or [host](#) association ([16.5.1.3](#), [16.5.1.4](#)), the [argument keyword](#) is accessible for
2 procedure references for that procedure in that [scoping unit](#).

3 2 A [dummy argument](#) name in an [intrinsic](#) procedure has a scope as an [argument keyword](#) of the [scoping unit](#)
4 in which the reference to the procedure occurs. As an [argument keyword](#), it may appear only in a procedure
5 reference for the procedure of which it is a [dummy argument](#).

6 16.4 Statement and construct entities

7 1 A variable that appears as a [data-i-do-variable](#) in a [DATA statement](#) or an [ac-do-variable](#) in an array constructor,
8 as a dummy argument in a [statement function statement](#), or as an [index-name](#) in a [FORALL statement](#) is a [statement entity](#).
9 A variable that appears as an [index-name](#) in a [FORALL](#) or [DO CONCURRENT](#) or as an [associate-name](#) in a
10 [SELECT TYPE](#) or [ASSOCIATE](#) construct is a [construct entity](#). A variable that has [LOCAL](#) or [LOCAL_INIT](#)
11 locality in a [DO CONCURRENT](#) construct is a [construct entity](#). An entity that is explicitly declared in the
12 specification part of a [BLOCK construct](#), other than only in [ASYNCHRONOUS](#) and [VOLATILE](#) statements, is
13 a [construct entity](#). Two [construct entities](#) of the same construct shall not have the same identifier.

14 2 Even if the name of a statement entity is the same as another identifier and the statement is in the scope of that
15 identifier, within the scope of the statement entity the name is interpreted as that of the statement entity.

16 3 The name of a statement entity shall not be the same as an accessible global identifier or local identifier of class
17 (1) ([16.3.1](#)), except for a [common block](#) name or a scalar variable name. Within the scope of a [statement entity](#),
18 another [statement entity](#) shall not have the same name.

19 4 The name of a [data-i-do-variable](#) in a [DATA statement](#) or an [ac-do-variable](#) in an array constructor has a scope
20 of its [data-implied-do](#) or [ac-implied-do](#). It is a scalar variable. If [integer-type-spec](#) appears in [data-implied-do](#) or
21 [ac-implied-do-control](#) it has the specified type and type parameters; otherwise it has the type and type parameters
22 that it would have if it were the name of a variable in the innermost executable construct or [scoping unit](#) that
23 includes the [DATA statement](#) or array constructor, and this type shall be integer type. It has no other attributes.
24 The appearance of a name as a [data-i-do-variable](#) of an implied DO in a [DATA statement](#) or an [ac-do-variable](#)
25 in an array constructor is not an implicit declaration of a variable whose scope is the [scoping unit](#) that contains
26 the statement.

27 5 The name of a variable that appears as an [index-name](#) in a [DO CONCURRENT](#) construct, [FORALL statement](#), or
28 [FORALL construct](#) has a scope of the statement or construct. It is a scalar variable. If [integer-type-spec](#) appears in
29 [concurrent-header](#) it has the specified type and type parameters; otherwise it has the type and type parameters
30 that it would have if it were the name of a variable in the innermost executable construct or [scoping unit](#) that
31 includes the [DO CONCURRENT](#) or [FORALL](#), and this type shall be integer type. It has no other attributes.
32 The appearance of a name as an [index-name](#) in a [DO CONCURRENT](#) construct, [FORALL statement](#), or [FORALL](#)
33 [construct](#) is not an implicit declaration of a variable whose scope is the [scoping unit](#) that contains the statement or
34 construct.

35 6 A variable that has [LOCAL](#) or [LOCAL_INIT](#) locality in a [DO CONCURRENT](#) construct has the scope of that
36 construct. Its attributes are specified in [8.1.6.5](#).

37 7 If [integer-type-spec](#) does not appear in a [concurrent-header](#), an [index-name](#) shall not be the same as an accessible
38 global identifier, local identifier, or identifier of an outer construct entity, except for a [common block](#) name or
39 a scalar variable name. An [index-name](#) of a contained [DO CONCURRENT](#) construct, [FORALL statement](#), or

- 1 **FORALL** construct shall not be the same as an *index-name* of any of its containing **DO CONCURRENT** or **FORALL**
2 constructs.
- 3 8 The **associate name** of a **SELECT TYPE** construct has a separate scope for each block of the construct. Within
4 each block, it has the **declared type**, **dynamic type**, type parameters, **rank**, and bounds specified in 8.1.10.2.
- 5 9 The **associate names** of an **ASSOCIATE** construct have the scope of the block. They have the **declared type**,
6 **dynamic type**, type parameters, **rank**, and bounds specified in 8.1.3.2.
- 7 10 The name of a variable that appears as a dummy argument in a **statement function statement** has a scope of the statement in which
8 it appears. It is a scalar that has the type and type parameters that it would have if it were the name of a variable in the **scoping**
9 **unit** that includes the **statement function**; it has no other attributes.

10 16.5 Association

11 16.5.1 Name association

12 16.5.1.1 Forms of name association

- 13 1 There are five forms of **name association**: **argument association**, **use association**, **host association**, **linkage asso-**
14 **ciation**, and **construct association**. **Argument**, **use**, and **host** association provide mechanisms by which entities
15 known in one scope may be accessed in another scope.

16 16.5.1.2 Argument association

- 17 1 The rules governing **argument association** are given in Clause 12. As explained in 12.5, execution of a procedure
18 reference establishes a correspondence between each dummy argument and an **actual argument** and thus an
19 association between each dummy argument and its **effective argument**. Argument association may be sequence
20 association (12.5.2.11).
- 21 2 The name of the dummy argument may be different from the name, if any, of its **effective argument**. The dummy
22 argument name is the name by which the **effective argument** is known, and by which it may be accessed, in the
23 referenced procedure.

NOTE 16.4

An **effective argument** can be a nameless data entity, such as the result of evaluating an expression that is not simply a variable or constant.

- 24 3 Upon termination of execution of a procedure reference, all **argument associations** established by that reference
25 are terminated. A dummy argument of that procedure may be associated with an entirely different **effective**
26 **argument** in a subsequent invocation of the procedure.

27 16.5.1.3 Use association

- 28 1 **Use association** is the association of names in different scopes specified by a **USE statement**. The rules governing
29 **use association** are given in 11.2.2. They allow for renaming of entities being accessed. **Use association** allows
30 access in one scope to entities defined or declared in another scope; it remains in effect throughout the execution
31 of the program.

16.5.1.4 Host association

1 A nested [scoping unit](#) has access to named entities from its host as specified in [12.4.3.4](#). In the case of an [internal subprogram](#), the access is to the entities in its [host instance](#). The accessed entities are identified by the same identifier and have the same attributes as in the [host](#), except that a local entity may have the [ASYNCHRONOUS attribute](#) even if the host entity does not, and a noncoarray local entity may have the [VOLATILE attribute](#) even if the host entity does not. The accessed entities are named data objects, derived types, [abstract interfaces](#), procedures, [generic identifiers](#), and namelist groups.

2 If an entity that is accessed by [use association](#) has the same nongeneric name as a host entity, the host entity is inaccessible by that name. The name of an [external procedure](#) that is given the [EXTERNAL attribute](#) ([5.5.9](#)) within the [scoping unit](#), or a name that appears within the [scoping unit](#) as a *module-name* in a *use-stmt* is a global identifier; any entity of the [host](#) that has this as its nongeneric name is inaccessible by that name. A name that appears in the [scoping unit](#) as

- (1) a *function-name* in a *stmt-function-stmt* or in an *entity-decl* in a *type-declaration-stmt*, unless it is a global identifier,
- (2) an *object-name* in an *entity-decl* in a *type-declaration-stmt*, in a *pointer-stmt*, in a *save-stmt*, in an *allocatable-stmt*, or in a *target-stmt*,
- (3) a *type-param-name* in a *derived-type-stmt*,
- (4) a *named-constant* in a *named-constant-def* in a *parameter-stmt*,
- (5) a *coarray-name* in a *codimension-stmt*,
- (6) an *array-name* in a *dimension-stmt*,
- (7) a *variable-name* in a *common-block-object* in a *common-stmt*,
- (8) a [procedure pointer](#) given the [EXTERNAL attribute](#) in the [scoping unit](#),
- (9) the name of a variable that is wholly or partially initialized in a *data-stmt*,
- (10) the name of an object that is wholly or partially equivalenced in an *equivalence-stmt*,
- (11) a *dummy-arg-name* in a *function-stmt*, in a *subroutine-stmt*, in an *entry-stmt*, or in a *stmt-function-stmt*,
- (12) a *result-name* in a *function-stmt* or in an *entry-stmt*,
- (13) the name of an entity declared by an [interface body](#), unless it is a global identifier,
- (14) an *intrinsic-procedure-name* in an *intrinsic-stmt*,
- (15) a *namelist-group-name* in a *namelist-stmt*,
- (16) a *generic-name* in a *generic-spec* in an *interface-stmt*, or
- (17) the name of a named construct

is a local identifier in the [scoping unit](#) and any entity of the [host](#) that has this as its nongeneric name is inaccessible by that name by [host association](#). If a [scoping unit](#) is the [host](#) of a derived-type definition or a subprogram that does not define a separate module procedure, the name of the derived type or of any procedure defined by the subprogram is a local identifier in the [scoping unit](#); any entity of the [host](#) that has this as its nongeneric name is inaccessible by that name. Local identifiers of a subprogram are not accessible to its [host](#).

NOTE 16.5

A name that appears in an [ASYNCHRONOUS](#) or [VOLATILE](#) statement is not necessarily the name of a local variable. In an [internal](#) or module procedure, if a variable that is accessible via [host association](#) is specified in an [ASYNCHRONOUS](#) or [VOLATILE](#) statement, that host variable is given the [ASYNCHRONOUS](#) or [VOLATILE](#) attribute in the local scope.

1 3 If a host entity is inaccessible only because a local variable with the same name is wholly or partially initialized
2 in a [DATA statement](#), the local variable shall not be referenced or defined prior to the [DATA statement](#).

3 4 If a derived-type name of a [host](#) is inaccessible, data entities of that type or subobjects of such data entities still
4 can be accessible.

NOTE 16.6

An [interface body](#) that is not a module procedure interface body accesses by [host association](#) only those entities made accessible by [IMPORT statements](#).

5 5 If an [external](#) or [dummy](#) procedure with an [implicit interface](#) is accessed via [host association](#), then it shall have
6 the [EXTERNAL attribute](#) in the [host scoping unit](#); if it is invoked as a function in the inner [scoping unit](#), its type
7 and type parameters shall be established in the [host scoping unit](#). The type and type parameters of a function
8 with the [EXTERNAL attribute](#) are established in a [scoping unit](#) if that [scoping unit](#) explicitly declares them,
9 invokes the function, accesses the function from a module, or accesses the function from its [host](#) where its type
10 and type parameters are established.

11 6 If an intrinsic procedure is accessed via [host association](#), then it shall be established to be intrinsic in the [host](#)
12 [scoping unit](#). An intrinsic procedure is established to be intrinsic in a [scoping unit](#) if that [scoping unit](#) explicitly
13 gives it the [INTRINSIC attribute](#), invokes it as an intrinsic procedure, accesses it from a module, or accesses it
14 from its [host](#) where it is established to be intrinsic.

NOTE 16.7

A host subprogram and an internal subprogram can contain the same and differing use-associated entities, as illustrated in the following example.

```

MODULE B; REAL BX, Q; INTEGER IX, JX; END MODULE B
MODULE C; REAL CX; END MODULE C
MODULE D; REAL DX, DY, DZ; END MODULE D
MODULE E; REAL EX, EY, EZ; END MODULE E
MODULE F; REAL FX; END MODULE F
MODULE G; USE F; REAL GX; END MODULE G
PROGRAM A
USE B; USE C; USE D
...
CONTAINS
  SUBROUTINE INNER_PROC (Q)
    USE C          ! Not needed
    USE B, ONLY: BX ! Entities accessible are BX, IX, and JX
                  ! if no other IX or JX
                  ! is accessible to INNER_PROC
                  ! Q is local to INNER_PROC,
                  ! because Q is a dummy argument
    USE D, X => DX ! Entities accessible are DX, DY, and DZ
                  ! X is local name for DX in INNER_PROC
                  ! X and DX denote same entity if no other
                  ! entity DX is local to INNER_PROC
    USE E, ONLY: EX ! EX is accessible in INNER_PROC, not in program A

```

NOTE 16.7 (cont.)

```

                                ! EY and EZ are not accessible in INNER_PROC
                                ! or in program A
USE G                            ! FX and GX are accessible in INNER_PROC
...
END SUBROUTINE INNER_PROC
END PROGRAM A

```

Because program A contains the statement

```
USE B
```

all of the entities in module B, except for Q, are accessible in INNER_PROC, even though INNER_PROC contains the statement

```
USE B, ONLY: BX
```

The [USE statement](#) with the [ONLY](#) option means that this particular statement brings in only the entity named, not that this is the only variable from the module accessible in this [scoping unit](#).

NOTE 16.8

For more examples of [host association](#), see subclause [C.12](#).

1 16.5.1.5 Linkage association

2 1 [Linkage association](#) occurs between a module variable that has the [BIND attribute](#) and the C variable with which
3 it interoperates, or between a Fortran [common block](#) and the C variable with which it interoperates ([15.9](#)). Such association
4 remains in effect throughout the execution of the program.

5 16.5.1.6 Construct association

6 1 Execution of a [SELECT TYPE statement](#) establishes an association between the selector and the [associate name](#)
7 of the construct. Execution of an [ASSOCIATE statement](#) establishes an association between each selector and
8 the corresponding [associate name](#) of the construct.

9 2 If the selector is [allocatable](#), it shall be allocated; the [associate name](#) is associated with the data object and does
10 not have the [ALLOCATABLE attribute](#).

11 3 If the selector has the [POINTER attribute](#), it shall be associated; the [associate name](#) is associated with the [target](#)
12 of the pointer and does not have the [POINTER attribute](#).

13 4 If the selector is a variable other than an [array section](#) having a [vector subscript](#), the association is with the data
14 object specified by the selector; otherwise, the association is with the value of the selector expression, which is
15 evaluated prior to execution of the block.

16 5 Each [associate name](#) remains associated with the corresponding selector throughout the execution of the executed
17 block. Within the block, each selector is known by and may be accessed by the corresponding [associate name](#).
18 On completion of execution of the construct, the association is terminated.

NOTE 16.9

The association between the [associate name](#) and a data object is established prior to execution of the block and is not affected by subsequent changes to variables that were used in subscripts or substring ranges in the [selector](#).

16.5.2 Pointer association**16.5.2.1 General**

- 1 [Pointer association](#) between a [pointer](#) and a [target](#) allows the [target](#) to be referenced by a reference to the pointer. At different times during the execution of a program, a pointer may be [undefined](#), associated with different [targets](#) on its own [image](#), or be [disassociated](#). If a pointer is associated with a [target](#), the definition status of the pointer is either defined or undefined, depending on the definition status of the [target](#). If the pointer has deferred [type parameters](#) or shape, their values are assumed from the [target](#). If the pointer is [polymorphic](#), its [dynamic type](#) is assumed from the [dynamic type](#) of the [target](#).

16.5.2.2 Pointer association status

- 1 A pointer may have a pointer association status of associated, [disassociated](#), or [undefined](#). Its association status may change during execution of a program. Unless a pointer is initialized ([explicitly](#) or by [default](#)), it has an initial association status of [undefined](#). A pointer may be initialized to have an association status of [disassociated](#) or associated.

NOTE 16.10

A pointer from a module [program unit](#) might be accessible in a subprogram via [use association](#). Such pointers have a lifetime that is greater than [targets](#) that are declared in the subprogram, unless such [targets](#) are [saved](#). Therefore, if such a pointer is associated with a local [target](#), there is the possibility that when a procedure defined by the subprogram completes execution, the [target](#) will cease to exist, leaving the pointer “dangling”. This part of ISO/IEC 1539 considers such pointers to have an undefined association status. They are neither associated nor [disassociated](#). They cannot be used again in the program until their status has been reestablished. A processor is not required to detect when a pointer [target](#) ceases to exist.

16.5.2.3 Events that cause pointers to become associated

- 1 A pointer becomes associated when any of the following events occur.
- (1) The pointer is allocated ([6.7.1](#)) as the result of the successful execution of an [ALLOCATE statement](#) referencing the pointer.
 - (2) The pointer is pointer-assigned to a [target](#) ([7.2.2](#)) that is associated or is specified with the [TARGET attribute](#) and, if [allocatable](#), is allocated.
 - (3) The pointer is a [subobject](#) of an object that is allocated by an [ALLOCATE statement](#) in which [SOURCE=](#) appears and the corresponding [subobject](#) of [source-expr](#) is associated.
 - (4) The pointer is a dummy argument and its corresponding [actual argument](#) is not a pointer.
 - (5) The pointer is a [default-initialized subcomponent](#) of an object, the corresponding initializer is not a reference to the intrinsic function [NULL](#), and
 - (a) a procedure is invoked with this object as an [actual argument](#) corresponding to a nonpointer nonallocatable dummy argument with [INTENT \(OUT\)](#),

- 1 (b) a procedure with this object as an **unsaved** nonpointer nonallocatable local variable is invoked,
2 (c) a **BLOCK construct** is entered and this object is an **unsaved** local nonpointer nonallocatable
3 local variable of the **BLOCK construct**,
4 or
5 (d) this object is allocated other than by an **ALLOCATE statement** in which **SOURCE=** appears.

6 **16.5.2.4 Events that cause pointers to become disassociated**

7 1 A pointer becomes **disassociated** when

- 8 (1) the pointer is nullified (6.7.2),
9 (2) the pointer is deallocated (6.7.3),
10 (3) the pointer is **pointer-assigned** (7.2.2) to a **disassociated** pointer,
11 (4) the pointer is a **subobject** of an object that is allocated by an **ALLOCATE statement** in which
12 **SOURCE=** appears and the corresponding **subobject** of *source-expr* is **disassociated**,
13 or
14 (5) the pointer is a **default-initialized subcomponent** of an object, the corresponding initializer is a
15 reference to the intrinsic function **NULL**, and
16 (a) a procedure is invoked with this object as an **actual argument** corresponding to a nonpointer
17 nonallocatable dummy argument with **INTENT (OUT)**,
18 (b) a procedure with this object as an **unsaved** nonpointer nonallocatable local variable is invoked,
19 (c) a **BLOCK construct** is entered and this object is an **unsaved** local nonpointer nonallocatable
20 local variable of the **BLOCK construct**,
21 or
22 (d) this object is allocated other than by an **ALLOCATE statement** in which **SOURCE=** appears.

23 **16.5.2.5 Events that cause the association status of pointers to become undefined**

24 1 The association status of a pointer becomes undefined when

- 25 (1) the pointer is pointer-assigned to a **target** that has an undefined association status,
26 (2) the pointer is pointer-assigned to a **target** on a different **image**,
27 (3) the **target** of the pointer is deallocated other than through the pointer,
28 (4) the **target** of the pointer is a data object defined by the companion processor and the lifetime of that
29 data object ends,
30 (5) the allocation transfer procedure (13.8.129) is executed, the pointer is associated with the argument
31 FROM, and an object without the **TARGET attribute** is pointer associated with the argument TO,
32 (6) completion of execution of an instance of a subprogram causes the pointer's **target** to become un-
33 defined (item (3) of 16.6.6),
34 (7) completion of execution of a **BLOCK construct** causes the pointer's **target** to become undefined (item
35 (22) of 16.6.6),
36 (8) execution of the **host instance** of a procedure pointer is completed,
37 (9) execution of an instance of a subprogram completes and the pointer is declared or accessed in the
38 subprogram that defines the procedure unless the pointer
39 (a) has the **SAVE attribute**,

- 1 (b) is in **blank common**,
- 2 (c) is in a named **common block** that is declared in at least one other **scoping unit** that is in execution,
- 3 (d) is accessed by **host association**, or
- 4 (e) is the return value of a function declared to have the **POINTER attribute**,
- 5 (10) execution of an instance of a subprogram completes, the pointer is associated with a **dummy argument**
- 6 of the procedure, and
- 7 (a) the **effective argument** does not have the **TARGET attribute** or is an **array section** with a
- 8 **vector subscript**, or
- 9 (b) the **dummy argument** has the **VALUE attribute**,
- 10 (11) a **BLOCK construct** completes execution and the pointer is an **unsaved construct entity** of that
- 11 **BLOCK construct**,
- 12 (12) a **DO CONCURRENT construct** is terminated and the pointer's association status was changed in
- 13 more than one iteration of the construct,
- 14 (13) the pointer is a **subcomponent** of an object that is allocated and either
- 15 (a) the pointer is not **default-initialized** and **SOURCE=** does not appear, or
- 16 (b) **SOURCE=** appears and the association status of the corresponding **subcomponent** of *source-*
- 17 *expr* is undefined,
- 18 (14) the pointer is a **subcomponent** of an object, the pointer is not **default-initialized**, and a procedure is
- 19 invoked with this object as an **actual argument** corresponding to a dummy argument with **INTENT**
- 20 **(OUT)**, or
- 21 (15) a procedure is invoked with the pointer as an **actual argument** corresponding to a pointer dummy
- 22 argument with **INTENT (OUT)**.

23 16.5.2.6 Other events that change the association status of pointers

- 24 1 When a pointer becomes associated with another pointer by **argument association**, **construct association**, or **host**
- 25 **association**, the effects on its association status are specified in 16.5.5.
- 26 2 While two pointers are **name associated**, **storage associated**, or **inheritance associated**, if the association status of
- 27 one pointer changes, the association status of the other changes accordingly.
- 28 3 The association status of a pointer object with the **VOLATILE attribute** might change by means not specified
- 29 by the program.

30 16.5.2.7 Pointer definition status

- 31 1 The definition status of an associated pointer is that of its **target**. If a pointer is associated with a **definable target**,
- 32 the definition status of the pointer may be defined or undefined according to the rules for a variable (16.6). The
- 33 definition status of a pointer that is not associated is undefined.

34 16.5.2.8 Relationship between association status and definition status

- 35 1 If the association status of a pointer is **disassociated** or undefined, the pointer shall not be referenced or deallocated.
- 36 Whatever its association status, a pointer always may be nullified, allocated, or pointer-assigned. A nullified
- 37 pointer is **disassociated**. When a pointer is allocated, it becomes associated but undefined. When a pointer is
- 38 pointer-assigned, its association and definition status become those of the specified **data-target** or **proc-target**.

16.5.3 Storage association

16.5.3.1 General

1 **Storage sequences** are used to describe relationships that exist among variables and **common blocks**. **Storage association** is the association of two or more data objects that occurs when two or more **storage sequences** share or are aligned with one or more **storage units**.

16.5.3.2 Storage sequence

1 A **storage sequence** is a sequence of **storage units**. The size of a **storage sequence** is the number of **storage units** in the **storage sequence**. A **storage unit** is a **character storage unit**, a **numeric storage unit**, a **file storage unit** (9.3.5), or an **unspecified storage unit**. The sizes of the **numeric storage unit**, the **character storage unit** and the **file storage unit** are the values of constants in the ISO_FORTRAN_ENV intrinsic module (13.9.2).

2 In a storage association context

- (1) a nonpointer scalar object that is default integer, default real, or default logical occupies a single **numeric storage unit**,
- (2) a nonpointer scalar object that is double precision real or default complex occupies two **contiguous numeric storage units**,
- (3) a default character nonpointer scalar object of character length *len* occupies *len* **contiguous character storage units**,
- (4) if C character kind is not the same as default character kind a nonpointer scalar object of type character with the C character kind (15.2.2) and character length *len* occupies *len* **contiguous unspecified storage units**,
- (5) a nonpointer scalar object of **sequence type** with no type parameters occupies a sequence of **storage sequences** corresponding to the sequence of its **ultimate components**,
- (6) a nonpointer scalar object of any type not specified in items (1)-(5) occupies a single **unspecified storage unit** that is different for each case and each set of type parameter values, and that is different from the **unspecified storage units** of item (4),
- (7) a nonpointer array occupies a sequence of **contiguous storage sequences**, one for each array element, in array element order (6.5.3.2), and
- (8) a **data pointer** occupies a single **unspecified storage unit** that is different from that of any nonpointer object and is different for each combination of type, type parameters, and **rank**. A **data pointer** that has the **CONTIGUOUS** attribute occupies a **storage unit** that is different from that of a **data pointer** that does not have the **CONTIGUOUS** attribute.

3 A sequence of **storage sequences** forms a **storage sequence**. The order of the **storage units** in such a composite **storage sequence** is that of the individual **storage units** in each of the constituent **storage sequences** taken in succession, ignoring any zero-sized constituent sequences.

4 Each **common block** has a **storage sequence** (5.9.2.2).

16.5.3.3 Association of storage sequences

1 Two nonzero-sized **storage sequences** s_1 and s_2 are storage associated if the i th **storage unit** of s_1 is the same as the j th **storage unit** of s_2 . This causes the $(i + k)$ th **storage unit** of s_1 to be the same as the $(j + k)$ th **storage**

1 **unit** of s_2 , for each integer k such that $1 \leq i + k \leq \text{size of } s_1$ and $1 \leq j + k \leq \text{size of } s_2$ where *size of* measures
2 the number of **storage units**.

3 2 Storage association also is defined between two zero-sized **storage sequences**, and between a zero-sized **storage**
4 **sequence** and a **storage unit**. A zero-sized **storage sequence** in a sequence of **storage sequences** is storage associated
5 with its successor, if any. If the successor is another zero-sized **storage sequence**, the two **sequences** are storage
6 associated. If the successor is a nonzero-sized **storage sequence**, the zero-sized **sequence** is storage associated with
7 the first **storage unit** of the successor. Two **storage units** that are each storage associated with the same zero-sized
8 **storage sequence** are the same **storage unit**.

9 **16.5.3.4 Association of scalar data objects**

10 1 Two scalar data objects are storage associated if their **storage sequences** are storage associated. Two scalar entities
11 are totally associated if they have the same **storage sequence**. Two scalar entities are partially associated if they
12 are associated without being totally associated.

13 2 The definition status and value of a data object affects the definition status and value of any storage associated
14 entity. An **EQUIVALENCE statement**, a **COMMON statement**, or an **ENTRY statement** can cause storage association of **storage**
15 **sequences**.

16 3 An **EQUIVALENCE statement** causes storage association of data objects only within one **scoping unit**, unless one of the equivalenced
17 entities is also in a **common block** (5.9.1.2, 5.9.2.2).

18 4 **COMMON statements** cause data objects in one **scoping unit** to become storage associated with data objects in another **scoping unit**.

19 5 A **common block** is permitted to contain a sequence of differing **storage units**. All **scoping units** that access named **common blocks**
20 with the same name shall specify an identical sequence of **storage units**. **Blank common blocks** may be declared with differing sizes
21 in different **scoping units**. For any two **blank common blocks**, the initial sequence of **storage units** of the longer **blank common**
22 shall be identical to the sequence of **storage units** of the shorter **common block**. If two **blank common blocks** are the same length,
23 they shall have the same sequence of **storage units**.

24 6 An **ENTRY statement** in a function subprogram causes storage association of the **function results** that are variables.

25 7 Partial association shall exist only between

- 26 • an object that is default character or of **character sequence type** and an object that is default character or
27 of **character sequence type**, or
- 28 • an object that is default complex, double precision real, or of **numeric sequence type** and an object that is
29 default integer, default real, default logical, double precision real, default complex, or of **numeric sequence**
30 **type**.

31 8 For noncharacter entities, partial association may occur only through the use of **COMMON**, **EQUIVALENCE**, or **ENTRY** statements.
32 For character entities, partial association may occur only through **argument association** or the use of **COMMON** or
33 **EQUIVALENCE** statements.

34 9 Partial association of character entities occurs when some, but not all, of the **storage units** of the entities are the
35 same.

36 10 A **storage unit** shall not be **explicitly initialized** more than once in a program. **Explicit initialization** overrides
37 **default initialization**, and **default initialization** for an object of derived type overrides **default initialization** for
38 a component of the object (4.5.4.6). **Default initialization** may be specified for a **storage unit** that is storage

1 associated provided the objects supplying the [default initialization](#) are of the same type and type parameters,
2 and supply the same value for the [storage unit](#).

3 **16.5.4 Inheritance association**

4 1 [Inheritance association](#) occurs between components of the [parent component](#) and components [inherited](#) by type
5 extension into an [extended type](#) (4.5.7.2). This association is persistent; it is not affected by the accessibility of
6 the [inherited](#) components.

7 **16.5.5 Establishing associations**

8 1 When an association is established between two entities by [argument association](#), [host association](#), or [construct](#)
9 [association](#), certain properties of the [associating entity](#) become those of the pre-existing entity.

10 2 For [argument association](#), the pre-existing entity is the [effective argument](#) and the [associating entity](#) is the dummy
11 argument.

12 3 For [host association](#), the [associating entity](#) is the entity in the contained [scoping unit](#). When a procedure is
13 invoked, the pre-existing entity that participates in the association is the one from its [host instance](#) (12.6.2.4).
14 Otherwise the pre-existing entity that participates in the association is the entity in the [host scoping unit](#).

15 4 For [construct association](#), the [associating entity](#) is identified by the [associate name](#) and the pre-existing entity is
16 the selector.

17 5 When an association is established by [argument association](#), [host association](#), or [construct association](#), the fol-
18 lowing applies.

- 19 • If the entities have the [POINTER attribute](#), the [pointer association](#) status of the [associating entity](#) becomes
20 the same as that of the pre-existing entity. If the pre-existing entity has a [pointer association](#) status of
21 associated, the [associating entity](#) becomes [pointer associated](#) with the same [target](#) and, if they are arrays,
22 the bounds of the [associating entity](#) become the same as those of the pre-existing entity.
- 23 • If the [associating entity](#) has the [ALLOCATABLE attribute](#), its allocation status becomes the same as that
24 of the pre-existing entity. If the pre-existing entity is allocated, the bounds (if it is an array), values of
25 [deferred type parameters](#), definition status, and value (if it is defined) become the same as those of the
26 pre-existing entity. If the [associating entity](#) is [polymorphic](#) and the pre-existing entity is allocated, the
27 [dynamic type](#) of the [associating entity](#) becomes the same as that of the pre-existing entity.
- 28 • If the [associating entity](#) is neither a pointer nor allocatable, its definition status, value (if it is defined), and
29 [dynamic type](#) (if it is [polymorphic](#)) become the same as those of the pre-existing entity. If the entities are
30 arrays and the association is not [argument association](#), the bounds of the [associating entity](#) become the
31 same as those of the pre-existing entity.
- 32 • If the [associating entity](#) is a pointer dummy argument and the pre-existing entity is a nonpointer [actual](#)
33 [argument](#) the [associating entity](#) becomes [pointer associated](#) with the pre-existing entity and, if the entities
34 are arrays, the bounds of the [associating entity](#) become the same as those of the pre-existing entity.

16.6 Definition and undefinition of variables

16.6.1 Definition of objects and subobjects

1 A variable may be defined or may be undefined and its definition status may change during execution of a
2 program. An action that causes a variable to become undefined does not imply that the variable was previously
3 defined. An action that causes a variable to become defined does not imply that the variable was previously
4 undefined.

5 Arrays, including sections, and variables of derived, character, or complex type are objects that consist of zero
6 or more subobjects. Associations may be established between variables and subobjects and between subobjects
7 of different variables. These subobjects may become defined or undefined.

8 An array is defined if and only if all of its elements are defined.

9 A derived-type scalar object is defined if and only if all of its nonpointer components are defined.

10 A complex or character scalar object is defined if and only if all of its subobjects are defined.

11 If an object is undefined, at least one (but not necessarily all) of its subobjects are undefined.

16.6.2 Variables that are always defined

12 Zero-sized arrays and zero-length strings are always defined.

16.6.3 Variables that are initially defined

13 The following variables are initially defined:

- 14 (1) variables specified to have initial values by [DATA statements](#);
- 15 (2) variables specified to have initial values by [type declaration statements](#);
- 16 (3) nonpointer [default-initialized subcomponents](#) of [saved](#) variables that do not have the [ALLOCAT-](#)
17 [ABLE](#) or [POINTER](#) attribute;
- 18 (4) pointers specified to be initially associated with a variable that is initially defined;
- 19 (5) variables that are always defined;
- 20 (6) variables with the [BIND attribute](#) that are initialized by means other than Fortran.

NOTE 16.11

Fortran code:

```
module mod
  integer, bind(c,name="blivet") :: foo
end module mod
```

C code:

```
int blivet = 123;
```

In the above example, the Fortran variable foo is initially defined to have the value 123 by means other than Fortran.

16.6.4 Variables that are initially undefined

1 All other variables are initially undefined.

16.6.5 Events that cause variables to become defined

1 Variables become defined by the following events.

- (1) Execution of an [intrinsic assignment statement](#) other than a [masked array assignment](#) or [FORALL assignment statement](#) causes the variable that precedes the equals to become defined.
- (2) Execution of a [masked array assignment](#) or [FORALL assignment statement](#) might cause some or all of the array elements in the [assignment statement](#) to become defined (7.2.3).
- (3) As execution of an [input statement](#) proceeds, each variable that is assigned a value from the input file becomes defined at the time that data are transferred to it. (See (4) in 16.6.6.) Execution of a [WRITE statement](#) whose [unit specifier](#) identifies an [internal file](#) causes each record that is written to become defined.
- (4) Execution of a [DO statement](#) causes the DO variable, if any, to become defined.
- (5) Beginning of execution of the action specified by an [io-implied-do](#) in a synchronous data transfer statement causes the [do-variable](#) to become defined.
- (6) A reference to a procedure causes the entire dummy argument data object to become defined if the dummy argument does not have [INTENT \(OUT\)](#) and the entire [effective argument](#) is defined.
A reference to a procedure causes a subobject of a dummy argument to become defined if the dummy argument does not have [INTENT \(OUT\)](#) and the corresponding subobject of the [effective argument](#) is defined.
- (7) Execution of an input/output statement containing an [IOSTAT= specifier](#) causes the specified integer variable to become defined.
- (8) Execution of a synchronous [input statement](#) containing a [SIZE= specifier](#) causes the specified integer variable to become defined.
- (9) Execution of a wait operation (9.7.1) corresponding to an asynchronous [input statement](#) containing a [SIZE= specifier](#) causes the specified integer variable to become defined.
- (10) Execution of an [INQUIRE statement](#) causes any variable that is assigned a value during the execution of the statement to become defined if no error condition exists.
- (11) If an error, end-of-file, or end-of-record condition occurs during execution of an input/output statement that has an [IOMSG= specifier](#), the [iomsg-variable](#) becomes defined.
- (12) When a [character storage unit](#) becomes defined, all associated [character storage units](#) become defined.
When a [numeric storage unit](#) becomes defined, all associated [numeric storage units](#) of the same type become defined. When an entity of double precision real type becomes defined, all totally associated entities of double precision real type become defined.
When an [unspecified storage unit](#) becomes defined, all associated [unspecified storage units](#) become defined.
- (13) When a default complex entity becomes defined, all partially associated default real entities become defined.
- (14) When both parts of a default complex entity become defined as a result of partially associated default real or default complex entities becoming defined, the default complex entity becomes defined.
- (15) When all components of a structure of a [numeric sequence type](#) or [character sequence type](#) become

- 1 defined as a result of partially associated objects becoming defined, the structure becomes defined.
- 2 (16) Execution of a statement with a **STAT= specifier** causes the variable specified by the **STAT= specifier**
- 3 to become defined.
- 4 (17) If an error condition occurs during execution of a statement that has an **ERRMSG= specifier**, the
- 5 variable specified by the **ERRMSG= specifier** becomes defined.
- 6 (18) Allocation of a zero-sized array causes the array to become defined.
- 7 (19) Allocation of an object that has a nonpointer **default-initialized subcomponent**, except by an **AL-**
- 8 **LOCATE statement** with a **SOURCE= specifier**, causes that **subcomponent** to become defined.
- 9 (20) Successful execution of an **ALLOCATE statement** with a **SOURCE= specifier** causes a subobject of
- 10 the allocated object to become defined if the corresponding subobject of the **SOURCE=** expression
- 11 is defined.
- 12 (21) Invocation of a procedure causes any **automatic object** of zero size in that procedure to become
- 13 defined.
- 14 (22) When a pointer becomes associated with a **target** that is defined, the pointer becomes defined.
- 15 (23) Invocation of a procedure that contains an **unsaved** nonpointer nonallocatable local variable causes
- 16 all nonpointer **default-initialized subcomponents** of the object to become defined.
- 17 (24) Invocation of a procedure that has a nonpointer nonallocatable **INTENT (OUT)** dummy argument
- 18 causes all nonpointer **default-initialized subcomponents** of the dummy argument to become defined.
- 19 (25) In a **DO CONCURRENT** or **FORALL** construct, the *index-name* becomes defined when the *index-*
- 20 *name* value set is evaluated.
- 21 (26) An object with the **VOLATILE attribute** that is changed by a means not specified by the program
- 22 might become defined (see 5.5.19).
- 23 (27) Execution of the **BLOCK statement** of a **BLOCK construct** that has an **unsaved** nonpointer non-
- 24 allocatable local variable causes all nonpointer **default-initialized subcomponents** of the variable to
- 25 become defined.
- 26 (28) Execution of an **OPEN statement** containing a **NEWUNIT= specifier** causes the specified integer
- 27 variable to become defined.
- 28 (29) Execution of a **LOCK statement** containing an **ACQUIRED_LOCK= specifier** causes the specified
- 29 logical variable to become defined. If the logical variable becomes defined with the value true, the
- 30 **lock variable** in the **LOCK statement** also becomes defined.
- 31 (30) Successful execution of a **LOCK statement** that does not contain an **ACQUIRED_LOCK= specifier**
- 32 causes the **lock variable** to become defined.
- 33 (31) Successful execution of an **UNLOCK statement** causes the **lock variable** to become defined.
- 34 (32) Successful execution of an **EVENT POST** or **EVENT WAIT** statement causes the **event variable** to
- 35 become defined.

36 16.6.6 Events that cause variables to become undefined

37 1 Variables become undefined by the following events.

- 38 (1) When a scalar variable of **intrinsic type** becomes defined, all totally associated variables of different type become
- 39 undefined. When a double precision scalar variable becomes defined, all partially associated scalar
- 40 variables become undefined. When a scalar variable becomes undefined, all partially associated double
- 41 precision scalar variables become undefined.
- 42 (2) If the evaluation of a function would cause a variable to become defined and if a reference to the

1 function appears in an expression in which the value of the function is not needed to determine the
2 value of the expression, the variable becomes undefined when the expression is evaluated.

- 3 (3) When execution of an instance of a subprogram completes,
4 (a) its **unsaved** local variables become undefined,
5 (b) **unsaved** variables in a named **common block** that appears in the subprogram become undefined if they have been
6 defined or redefined, unless another active **scoping unit** is referencing the **common block**, and
7 (c) a variable of type **C_PTR** from the intrinsic module **ISO_C_BINDING** whose value is the **C**
8 **address** of an **unsaved** local variable of the subprogram becomes undefined.
- 9 (4) When an error condition or end-of-file condition occurs during execution of an **input statement**, all of
10 the variables specified by the input list or namelist group of the statement become undefined.
- 11 (5) When an error condition occurs during execution of an **output statement** in which the **unit** is an **internal**
12 **file**, the **internal file** becomes undefined.
- 13 (6) When an error condition, end-of-file condition, or end-of-record condition occurs during execution of
14 an input/output statement and the statement contains any *io-implied-dos*, all of the *do-variables* in
15 the statement become undefined (9.11).
- 16 (7) Execution of a direct access **input statement** that specifies a record that has not been written previously
17 causes all of the variables specified by the input list of the statement to become undefined.
- 18 (8) Execution of an **INQUIRE statement** might cause the **NAME=**, **RECL=**, and **NEXTREC=** variables
19 to become undefined (9.10).
- 20 (9) When a **character storage unit** becomes undefined, all associated **character storage units** become un-
21 defined.
22 When a **numeric storage unit** becomes undefined, all associated **numeric storage units** become undefined
23 unless the undefinition is a result of defining an associated **numeric storage unit** of different type (see
24 (1) above).
25 When an entity of double precision real type becomes undefined, all totally associated entities of double
26 precision real type become undefined.
27 When an **unspecified storage unit** becomes undefined, all associated **unspecified storage units** become
28 undefined.
- 29 (10) When an **allocatable** entity is deallocated, it becomes undefined.
- 30 (11) When the allocation transfer procedure (13.8.129) causes the allocation status of an **allocatable** entity
31 to become unallocated, the entity becomes undefined.
- 32 (12) Successful execution of an **ALLOCATE statement** with no **SOURCE= specifier** causes a **subcomponent**
33 of an allocated object to become undefined if **default initialization** has not been specified for that
34 **subcomponent**.
- 35 (13) Successful execution of an **ALLOCATE statement** with a **SOURCE= specifier** causes a subobject of
36 the allocated object to become undefined if the corresponding subobject of the **SOURCE=** expression
37 is undefined.
- 38 (14) Execution of an **INQUIRE statement** causes all inquiry specifier variables to become undefined if an
39 error condition exists, except for any variable in an **IOSTAT=** or **IOMSG=** specifier.
- 40 (15) When a procedure is invoked
41 (a) an optional dummy argument that has no corresponding **actual argument** becomes undefined,
42 (b) a dummy argument with **INTENT (OUT)** becomes undefined except for any nonpointer **default-**
43 **initialized subcomponents** of the argument,

- 1 (c) an **actual argument** corresponding to a dummy argument with **INTENT (OUT)** becomes un-
 2 defined except for any nonpointer **default-initialized subcomponents** of the argument,
- 3 (d) a subobject of a dummy argument that does not have **INTENT (OUT)** becomes undefined if the
 4 corresponding subobject of the **effective argument** is undefined, and
- 5 (e) a variable that is the **function result** of that procedure becomes undefined except for any of its
 6 nonpointer **default-initialized subcomponents**.
- 7 (16) When the association status of a pointer becomes undefined or **disassociated** (16.5.2.4, 16.5.2.5), the
 8 pointer becomes undefined.
- 9 (17) When a **DO CONCURRENT construct** terminates, a variable that is defined or becomes undefined
 10 during more than one iteration of the construct becomes undefined.
- 11 (18) Execution of an asynchronous **READ statement** causes all of the variables specified by the input list or
 12 **SIZE= specifier** to become undefined. Execution of an asynchronous namelist **READ statement** causes
 13 any variable in the namelist group to become undefined if that variable will subsequently be defined
 14 during the execution of the **READ statement** or the corresponding wait operation (9.7.1).
- 15 (19) When a variable with the **TARGET attribute** is deallocated, a variable of type **C_PTR** from the
 16 intrinsic module **ISO_C_BINDING** becomes undefined if its value is the **C address** of any part of the
 17 variable that is deallocated.
- 18 (20) When a pointer is deallocated, a variable of type **C_PTR** from the intrinsic module **ISO_C_BINDING**
 19 becomes undefined if its value is the **C address** of any part of the **target** that is deallocated.
- 20 (21) Execution of the allocation transfer procedure (13.7.125) where an object without the **TARGET at-**
 21 **tribute** is **pointer associated** with the argument TO causes a variable of type **C_PTR** from the intrinsic
 22 module **ISO_C_BINDING** to become undefined if its value is the **C address** of any part of the argument
 23 FROM.
- 24 (22) When a **BLOCK construct** completes execution,
- 25 • its **unsaved** local variables become undefined, and
 - 26 • a variable of type **C_PTR** from the intrinsic module **ISO_C_BINDING**, whose value is the **C**
 27 **address** of an **unsaved** local variable of the **BLOCK construct**, becomes undefined.
- 28 (23) When execution of the **host instance** of the **target** of a variable of type **C_FUNPTR** from the intrinsic
 29 module **ISO_C_BINDING** is completed by execution of a **RETURN** or **END** statement, the variable
 30 becomes undefined.
- 31 (24) Execution of an intrinsic assignment of the type **C_PTR** or **C_FUNPTR** from the intrinsic module
 32 **ISO_C_BINDING** in which the variable and *expr* are not on the same **image** causes the variable to
 33 become undefined.
- 34 (25) An object with the **VOLATILE attribute** (5.5.19) might become undefined by means not specified by
 35 the program.
- 36 (26) When a pointer becomes associated with a target that is undefined, the pointer becomes undefined.

NOTE 16.12

Execution of a defined assignment statement could leave all or part of the variable undefined.

16.6.7 Variable definition context

- 37
- 38 1 Some variables are prohibited from appearing in a syntactic context that would imply definition or undefinition
 39 of the variable (5.5.10, 5.5.15, 12.7). The following are the contexts in which the appearance of a variable implies

1 such definition or undefinition of the variable:

- 2 (1) the *variable* of an *assignment-stmt*;
- 3 (2) a *do-variable* in a *do-stmt* or *io-implied-do*;
- 4 (3) an *input-item* in a *read-stmt*;
- 5 (4) a *variable-name* in a *namelist-stmt* if the *namelist-group-name* appears in a *NML= specifier* in a
- 6 *read-stmt*;
- 7 (5) an *internal-file-variable* in a *write-stmt*;
- 8 (6) an *IOSTAT=*, *SIZE=*, or *IOMSG=* specifier in an input/output statement;
- 9 (7) a specifier in an *INQUIRE statement* other than *FILE=*, *ID=*, and *UNIT=*;
- 10 (8) a *NEWUNIT=* specifier in an *OPEN statement*;
- 11 (9) a *stat-variable*, *allocate-object*, or *errmsg-variable*;
- 12 (10) an *actual argument* in a reference to a procedure with an *explicit interface* if the corresponding
- 13 *dummy argument* is not a pointer and has *INTENT (OUT)* or *INTENT (INOUT)*;
- 14 (11) a *variable* that is a *selector* in a *SELECT TYPE* or *ASSOCIATE* construct if the corresponding
- 15 *associate name* appears in a variable definition context;
- 16 (12) an *event-variable* in a *EVENT POST* or *EVENT WAIT* statement;
- 17 (13) a *lock-variable* in a *LOCK* or *UNLOCK* statement;
- 18 (14) a *scalar-logical-variable* in an *ACQUIRED_LOCK= specifier*.

- 19 2 If a reference to a function appears in a variable definition context the result of the function reference shall be a
20 pointer that is associated with a *definable target*. That *target* is the variable that becomes defined or undefined.

21 16.6.8 Pointer association context

- 22 1 Some pointers are prohibited from appearing in a syntactic context that would imply alteration of the *pointer*
23 *association* status (16.5.2.2, 5.5.10, 5.5.15, 12.7). The following are the contexts in which the appearance of a
24 pointer implies such alteration of its *pointer association* status:

- 25 • a *pointer-object* in a *nullify-stmt*;
- 26 • a *data-pointer-object* or *proc-pointer-object* in a *pointer-assignment-stmt*;
- 27 • an *allocate-object* in an *allocate-stmt* or *deallocate-stmt*;
- 28 • an *actual argument* in a reference to a procedure if the corresponding *dummy argument* is a pointer with
29 the *INTENT (OUT)* or *INTENT (INOUT)* attribute.

Annex A

(Informative)

Processor Dependencies

A.1 Unspecified Items

1 This part of ISO/IEC 1539 does not specify the following:

- 2 • the properties excluded in 1.1;
- 3 • a processor's error detection capabilities beyond those listed in 1.5;
- 4 • which additional intrinsic procedures or modules a processor provides (1.5);
- 5 • the number and kind of companion processors (2.5.7);
- 6 • the number of representation methods and associated kind type parameter values of the intrinsic types (4.4), except that there shall be at least two representation methods for type real, and a representation method of type complex that corresponds to each representation method for type real.

A.2 Processor Dependencies

1 According to this part of ISO/IEC 1539, the following are processor dependent:

- 2 • the order of evaluation of the specification expressions within the specification part of an invoked Fortran procedure (2.3.5);
- 3 • how soon an image terminates if another image initiates error termination (2.3.5);
- 4 • whether the processor supports a concept of process exit status, and if so, the process exit status on program termination (2.3.6);
- 5 • the mechanism of a companion processor, and the means of selecting between multiple companion processors (2.5.7);
- 6 • the processor character set (3.1);
- 7 • the means for specifying the source form of a program unit (3.3);
- 8 • the maximum number of characters allowed on a source line containing characters not of default kind (3.3.2, 3.3.3);
- 9 • the maximum depth of nesting of include lines (3.4);
- 10 • the interpretation of the *char-literal-constant* in the include line (3.4);
- 11 • the set of values supported by an intrinsic type, other than logical (4.1.3);
- 12 • the kind of a character length type parameter (4.4.4.1);
- 13 • the blank padding character for nondefault character kind (4.4.4.2)
- 14 • whether particular control characters can appear within a character literal constant in fixed source form (4.4.4.3);
- 15 • the collating sequence for each character set (4.4.4.4);
- 16 • the order of finalization of components of objects of derived type (4.5.6.2);
- 17 • the order of finalization when several objects are finalized as the consequence of a single event (4.5.6.2);

- 1 • whether and when an object is finalized if it is allocated by pointer allocation and it later becomes un-
2 reachable due to all pointers associated with the object having their pointer association status changed
3 (4.5.6.3);
- 4 • whether an object is finalized by a deallocation in which an error condition occurs (4.5.6.3);
- 5 • the kind type parameter of each enumeration and its enumerators (4.6);
- 6 • whether an array is contiguous, except as specified in 5.5.7;
- 7 • the set of error conditions that can occur in `ALLOCATE` and `DEALLOCATE` statements (6.7.1, 6.7.3);
- 8 • the allocation status of a variable after evaluation of an expression if the evaluation of a function would
9 change the allocation status of the variable and if a reference to the function appears in the expression in
10 which the value of the function is not needed to determine the value of the expression (6.7.1.3);
- 11 • the order of deallocation when several objects are deallocated by a `DEALLOCATE` statement (6.7.3);
- 12 • the order of deallocation when several objects are deallocated due to the occurrence of an event described
13 in 6.7.3.2;
- 14 • whether an allocated allocatable subobject is deallocated when an error condition occurs in the deallocation
15 of an object (6.7.3.2);
- 16 • the positive integer values assigned to the *stat-variable* in a `STAT= specifier` as the result of an error
17 condition (6.7.4, 8.5.9);
- 18 • the allocation status or pointer association status of an *allocate-object* if an error occurs during execution
19 of an `ALLOCATE` or `DEALLOCATE` statement (6.7.4);
- 20 • the value assigned to the *errmsg-variable* in an `ERRMSG= specifier` as the result of an error condition
21 (6.7.5, 8.5.9);
- 22 • the kind type parameter value of the result of a numeric intrinsic binary operation where
 - 23 – both operands are of type integer but with different kind type parameters, and the decimal exponent
24 ranges are the same,
 - 25 – one operand is of type real or complex and the other is of type real or complex with a different kind
26 type parameter, and the decimal precisions are the same,and for a logical intrinsic binary operation where the operands have different kind type parameters (7.1.9.3);
- 27 • the character assigned to the variable in an `intrinsic assignment statement` if the kind of the expression is
28 different and the character is not representable in the kind of the variable (7.2.1.3);
- 29 • the order of evaluation of the `specification expressions` within the specification part of a `BLOCK construct`
30 when the construct is executed (8.1.4);
- 31 • the pointer association status of a pointer that has its pointer association changed in more than one iteration
32 of a `DO CONCURRENT construct`, on termination of the construct (8.1.6);
- 33 • the ordering between records written by different iterations of a `DO CONCURRENT construct` if the records
34 are written to a file connected for sequential access by more than one iteration (8.1.6);
- 35 • the manner in which the stop code of a `STOP` or `ERROR STOP` statement is made available (8.4);
- 36 • the mechanisms available for creating dependencies for cooperative synchronization (8.5.5);
- 37 • the value of the count of the event variable in an `EVENT POST` or `EVENT WAIT` statement if an error
38 condition occurs (8.5.6, 8.5.7);
- 39 • the set of error conditions that can occur in `image control statements` (8.5.9);
- 40 • the relationship between the `file storage units` when viewing a file as a `stream file`, and the records when
41 viewing that file as a `record file` (9);
- 42 • whether particular control characters can appear in a formatted `record` or a formatted `stream file` (9.2.2);
- 43

- 1 • the form of values in an unformatted record (9.2.3);
- 2 • at any time, the set of allowed access methods, set of allowed forms, set of allowed actions, and set of
- 3 allowed record lengths for a [file](#) (9.3);
- 4 • the set of allowable names for a [file](#) (9.3);
- 5 • whether a named file on one [image](#) is the same as a file with the same name on another [image](#) (9.3.1);
- 6 • the set of [external files](#) that exist for a program (9.3.2);
- 7 • the relationship between positions of successive [file storage units](#) in an [external file](#) that is connected for
- 8 formatted stream access (9.3.3.4);
- 9 • the [external unit](#) preconnected for sequential formatted input and identified by an asterisk or the [named](#)
- 10 [constant](#) INPUT_UNIT of the ISO_FORTRAN_ENV intrinsic module (9.5);
- 11 • the [external unit](#) preconnected for sequential formatted output and identified by an asterisk or the [named](#)
- 12 [constant](#) OUTPUT_UNIT of the ISO_FORTRAN_ENV intrinsic module (9.5);
- 13 • the [external unit](#) preconnected for sequential formatted output and identified by the [named constant](#) ER-
- 14 ROR_UNIT of the ISO_FORTRAN_ENV intrinsic module, and whether this unit is the same as OUT-
- 15 PUT_UNIT (9.5);
- 16 • at any time, the set of [external units](#) that exist for an [image](#) (9.5.3);
- 17 • whether a [unit](#) can be connected to a file that is also connected to a C stream (9.5.4);
- 18 • whether a file can be connected to more than one [unit](#) at the same time (9.5.4);
- 19 • the result of performing input/output operations on a [unit](#) connected to a file that is also connected to a C
- 20 stream (9.5.4);
- 21 • whether the files connected to the [units](#) INPUT_UNIT, OUTPUT_UNIT, and ERROR_UNIT correspond
- 22 to the predefined C text streams standard input, standard output, and standard error, respectively (9.5.4);
- 23 • the results of performing input/output operations on an [external file](#) both from Fortran and from a procedure
- 24 defined by means other than Fortran (9.5.4);
- 25 • the default value for the [ACTION= specifier](#) on the [OPEN statement](#) (9.5.6.4);
- 26 • the encoding of a file opened with [ENCODING='DEFAULT'](#) (9.5.6.9);
- 27 • the file connected by an [OPEN statement](#) with [STATUS='SCRATCH'](#) (9.5.6.10);
- 28 • the interpretation of case in a file name (9.5.6.10, 9.10.2.2);
- 29 • the position of a file after executing an [OPEN statement](#) with a [POSITION= specifier](#) of ASIS, when the
- 30 file previously existed but was not connected (9.5.6.14);
- 31 • the default value for the [RECL= specifier](#) in an [OPEN statement](#) (9.5.6.15);
- 32 • the effect of [RECL=](#) on a record containing any nondefault characters (9.5.6.15);
- 33 • the default input/output rounding mode (9.5.6.16);
- 34 • the default sign mode (9.5.6.17);
- 35 • the file status when [STATUS='UNKNOWN'](#) is specified in an [OPEN statement](#) (9.5.6.18);
- 36 • the value assigned to the variable in the [ID= specifier](#) in an asynchronous [data transfer statement](#) when
- 37 execution of the statement is successfully completed (9.6.2.9);
- 38 • whether [POS=](#) is permitted with particular files, and whether [POS=](#) can position a particular file to a
- 39 position prior to its current position (9.6.2.11);
- 40 • the form in which a single value of derived type is treated in an unformatted input/output statement if the
- 41 [effective item](#) is not processed by a [defined input/output](#) procedure (9.6.3);
- 42 • the result of unformatted input when the value stored in the file has a different type or type parameters

1 from the input list item, as described in 9.6.4.5.2;

- 2 • the negative value of the `unit` argument to a `defined input/output` procedure if the parent `data transfer`
- 3 `statement` accesses an `internal file` (9.6.4.8.3);
- 4 • the manner in which the processor makes the value of the `iomsg` argument of a `defined input/output`
- 5 `procedure` available if the procedure assigns a nonzero value to the `iostat` argument and the processor
- 6 therefore `terminates execution` of the program (9.6.4.8.3);
- 7 • the action caused by the flush operation, whether the processor supports the flush operation for the specified
- 8 `unit`, and the negative value assigned to the `IOSTAT=` variable if the processor does not support the flush
- 9 operation for the specified `unit` (9.9);
- 10 • the case of characters assigned to the variable in a `NAME=` specifier in an `INQUIRE statement` (9.10.2.15);
- 11 • the value of the variable in a `POSITION=` specifier in an `INQUIRE statement` if the file has been repositioned
- 12 since connection (9.10.2.23);
- 13 • the relationship between file size and the data stored in records in a sequential or direct access file (9.10.2.30);
- 14 • the number of `file storage units` needed to store data in an unformatted file (9.10.3);
- 15 • the set of error conditions that can occur in input/output statements (9.11.1);
- 16 • when an input/output error condition occurs or is detected (9.11.1);
- 17 • the positive integer value assigned to the variable in an `IOSTAT=` specifier as the result of an error condition
- 18 (9.11.5);
- 19 • the value assigned to the variable in an `IOMSG=` specifier as the result of an error condition (9.11.6);
- 20 • the result of output of non-representable characters to a Unicode file (10.7.1);
- 21 • the interpretation of the optional non-blank characters within the parentheses of a real NaN input field
- 22 (10.7.2.3.2);
- 23 • the interpretation of a sign in a NaN input field (10.7.2.3.2);
- 24 • for output of an IEEE NaN, whether after the letters 'NaN', the processor produces additional alphanumeric
- 25 characters enclosed in parentheses (10.7.2.3.2);
- 26 • the effect of the input/output rounding mode `PROCESSOR_DEFINED` (10.7.2.3.8);
- 27 • which value is chosen if the input/output rounding mode is `NEAREST` and the value to be converted is
- 28 exactly halfway between the two nearest representable values in the result format (10.7.2.3.8);
- 29 • the field width, decimal part width, and exponent width used for the `G0` edit descriptor (10.7.5);
- 30 • the file position when position editing skips a character of nondefault kind in an `internal file` of default
- 31 character kind or an `external unit` that is not connected to a Unicode file (10.8.1.1);
- 32 • when the sign mode is `PROCESSOR_DEFINED`, whether a plus sign appears in a numeric output field
- 33 for a nonnegative value (10.8.4);
- 34 • the results of list-directed output (10.10.4);
- 35 • the results of namelist output (10.11.4);
- 36 • the interaction between `argument association` and pointer association, (12.5.2.4);
- 37 • the values returned by some intrinsic functions (13);
- 38 • how the sequences of atomic actions in unordered segments interleave (13.1);
- 39 • the effects of calling `COMMAND_ARGUMENT_COUNT`, `EXECUTE_COMMAND_LINE`, `GET_COM-`
- 40 `MAND`, and `GET_COMMAND_ARGUMENT` on any `image` other than `image 1` (13.6);
- 41 • whether each `image` uses a separate random number generator, or if some or all `images` use common random
- 42 number generators (13.6);

- 1 • whether the results returned from `CPU_TIME`, `DATE_AND_TIME` and `SYSTEM_CLOCK` are depend-
2 ent on which `image` calls them (13.6);
- 3 • the set of error conditions that can occur in some intrinsic subroutines (13.8);
- 4 • the value assigned to a `CMDSTAT`, `ERRMSG`, or `STATUS` argument to indicate a processor-dependent
5 error condition (13.8);
- 6 • the value assigned to the `TIME` argument by the intrinsic subroutine `CPU_TIME` (13.8.52);
- 7 • whether date, clock, and time zone information is available (13.8.54);
- 8 • whether date, clock, and time zone information on one `image` is the same as that on another `image` (13.8.54);
- 9 • the value of command argument zero, if the processor does not support the concept of a command name
10 (13.8.77);
- 11 • whether the significant length of a command argument includes trailing blanks (13.8.77);
- 12 • the interpretation of case for the `NAME` argument of the intrinsic subroutine `GET_ENVIRONMENT_-`
13 `VARIABLE` (13.8.78);
- 14 • whether an environment variable that exists on an `image` also exists on another `image`, and if it does exist
15 on both `images`, whether the values are the same or different (13.8.78);
- 16 • the value assigned to the pseudorandom number generator by the intrinsic subroutine `RANDOM_INIT`
17 (13.8.147);
- 18 • the computation of the seed value used by the pseudorandom number generator (13.8.149);
- 19 • on `images` that use a common random number generator, the interleaving of values assigned by `RANDOM_-`
20 `NUMBER` in unordered segments(13.6);
- 21 • the value assigned to the seed by the intrinsic subroutine `RANDOM_SEED` when no argument is present
22 (13.8.149);
- 23 • the values assigned to its arguments by the intrinsic subroutine `SYSTEM_CLOCK` (13.8.177);
- 24 • the values of the named constants in the intrinsic module `ISO_FORTRAN_ENV`(13.9.2);
- 25 • the values returned by the functions `COMPILER_OPTIONS` and `COMPILER_VERSION` in the intrinsic
26 module `ISO_FORTRAN_ENV`(13.9.2);
- 27 • the extent to which a processor supports IEEE arithmetic (14);
- 28 • the conditions under which `IEEE_OVERFLOW` is raised in a calculation involving non-ISO/IEC/IEEE
29 60559:2011 floating-point data;
- 30 • the conditions under which `IEEE_OVERFLOW` and `IEEE_DIVIDE_BY_ZERO` are raised in a floating-
31 point exponentiation operation;
- 32 • the conditions under which `IEEE_DIVIDE_BY_ZERO` is raised in a calculation involving non-ISO/IEC/IEEE
33 60559:2011 floating-point data;
- 34 • the initial rounding modes (14.4);
- 35 • the initial underflow mode (14.5);
- 36 • the initial halting mode (14.6);
- 37 • the order of the members of the `CFI_dim_t` structure defined in the source file `CFI_Fortran_binding.h`
38 (15.5.2);
- 39 • members of the `CFI_cdesc_t` structure defined in the source file `CFI_Fortran_binding.h` beyond the re-
40 quirements of 15.5.3;
- 41 • the value of `CFI_MAX_RANK` in the source file `CFI_Fortran_binding.h` (15.5.4);
- 42 • the value of `CFI_VERSION` in the source file `CFI_Fortran_binding.h` (15.5.4);

- 1 • which error condition is detected if more than one error condition is detected for an invocation of one of
- 2 the functions declared in the source file CFI_Fortran_binding.h (15.5.5.1);
- 3 • the values of the attribute specifier macros defined in the source file CFI_Fortran_binding.h (15.5.4);
- 4 • the values of the type specifier macros defined in the source file CFI_Fortran_binding.h;
- 5 • which additional type specifier values are defined in the source file CFI_Fortran_binding.h (15.5.4);
- 6 • the values of the error code macros other than CFI_SUCCESS that are defined in the source file CFI_-
- 7 Fortran_binding.h (15.5.4);
- 8 • the base address of a zero-sized array (15.5.3);
- 9 • the requirements on the storage sequence to be associated with the pointer FPTR by the C_F_POINTER
- 10 subroutine (15.2.3.4);
- 11 • the values of the floating-point exception flags on entry to a procedure defined by means other than Fortran
- 12 (15.10.3),
- 13 • whether a procedure defined by means other than Fortran is an asynchronous communication initiation or
- 14 completion procedure (15.10.4);
- 15 • the value assigned to a STAT argument in a reference to an atomic subroutine when an error condition
- 16 occurs (13.5).

Annex B

(Informative)

Deleted and obsolescent features

B.1 Deleted features from Fortran 90

1 These deleted features are those features of Fortran 90 that were redundant and considered largely unused.

2 The following Fortran 90 features are not required.

3 (1) Real and double precision DO variables.

4 In FORTRAN 77 and Fortran 90, a DO variable was allowed to be of type real or double precision
5 in addition to type integer; this has been deleted. A similar result can be achieved by using a **DO**
6 **construct** with no loop control and the appropriate exit test.

7 (2) Branching to an **END IF statement** from outside its block.

8 In FORTRAN 77 and Fortran 90, it was possible to to an **END IF statement** from outside the **IF**
9 **construct**; this has been deleted. A similar result can be achieved by branching to a **CONTINUE**
10 **statement** that is immediately after the **END IF statement**.

11 (3) PAUSE statement.

12 The PAUSE statement, provided in FORTRAN 66, FORTRAN 77, and Fortran 90, has been deleted.
13 A similar result can be achieved by writing a message to the appropriate **unit**, followed by reading
14 from the appropriate **unit**.

15 (4) ASSIGN and assigned GO TO statements and assigned format specifiers.

16 The ASSIGN statement and the related assigned GO TO statement, provided in FORTRAN 66,
17 FORTRAN 77, and Fortran 90, have been deleted. Further, the ability to use an assigned integer as a
18 format, provided in FORTRAN 77 and Fortran 90, has been deleted. A similar result can be achieved
19 by using other control constructs instead of the assigned GO TO statement and by using a default
20 character variable to hold a format specification instead of using an assigned integer.

21 (5) H edit descriptor.

22 In FORTRAN 77 and Fortran 90, there was an alternative form of character string edit descriptor,
23 which had been the only such form in FORTRAN 66; this has been deleted. A similar result can be
24 achieved by using a character string edit descriptor.

25 (6) Vertical format control.

26 In FORTRAN 66, FORTRAN 77, Fortran 90, and Fortran 95 formatted output to certain **units** resulted
27 in the first character of each record being interpreted as controlling vertical spacing. There was no
28 standard way to detect whether output to a **unit** resulted in this vertical format control, and no
29 way to specify that it should be applied; this has been deleted. The effect can be achieved by
30 post-processing a formatted file.

31 3 See ISO/IEC 1539:1991 for detailed rules of how these deleted features worked.

B.2 Deleted features from Fortran 2008

1 These deleted features are those features of Fortran 2008 that were redundant and considered largely unused.

2 The following Fortran 2008 features are not required.

(1) Arithmetic IF statement.

The arithmetic IF statement is incompatible with ISO/IEC/IEEE 60559:2011 and necessarily involves the use of [statement labels](#); [statement labels](#) can hinder optimization, and make code hard to read and maintain. Similar logic can be more clearly encoded using other conditional statements.

(2) Nonblock DO construct

The nonblock forms of the DO loop were confusing and hard to maintain. Shared termination and dual use of labeled action statements as do termination and branch targets were especially error-prone.

B.3 Obsolescent features

B.3.1 General

1 The obsolescent features are those features of Fortran 90 that were redundant and for which better methods were available in Fortran 90. Subclause [1.7.3](#) describes the nature of the obsolescent features. The obsolescent features in this part of ISO/IEC 1539 are the following.

(1) Alternate return — see [B.3.2](#).

(2) [Computed GO TO](#) — see [B.3.3](#).

(3) Statement functions — see [B.3.4](#).

(4) [DATA statements](#) amongst executable statements — see [B.3.5](#).

(5) Assumed length character functions — see [B.3.6](#).

(6) Fixed form source — see [B.3.7](#).

(7) CHARACTER* form of CHARACTER declaration — see [B.3.8](#).

(8) [ENTRY statements](#) — see [B.3.9](#).

(9) Label form of [DO statement](#) — see [B.3.10](#).

(10) [COMMON](#) and [EQUIVALENCE](#) statements, and the [block data program unit](#) — see [B.3.11](#).

(11) Specific names for intrinsic functions — see [B.3.12](#).

(12) [FORALL](#) construct and statement — see [B.3.13](#)

B.3.2 Alternate return

1 An alternate return introduces labels into an argument list to allow the called procedure to direct the execution of the caller upon return. The same effect can be achieved with a return code that is used in a [SELECT CASE construct](#) on return. This avoids an irregularity in the syntax and semantics of [argument association](#). For example,

```
CALL SUBR_NAME (X, Y, Z, *100, *200, *300)
```

can be replaced by

```
CALL SUBR_NAME (X, Y, Z, RETURN_CODE)
SELECT CASE (RETURN_CODE)
```

```
1      CASE (1)
2          ...
3      CASE (2)
4          ...
5      CASE (3)
6          ...
7      CASE DEFAULT
8          ...
9  END SELECT
```

10 **B.3.3 Computed GO TO statement**

11 1 The [computed GO TO statement](#) has been superseded by the [SELECT CASE construct](#), which is a generalized,
12 easier to use, and clearer means of expressing the same computation.

13 **B.3.4 Statement functions**

14 1 [Statement functions](#) are subject to a number of nonintuitive restrictions and are a potential source of error because
15 their syntax is easily confused with that of an assignment statement.

16 2 The internal function is a more generalized form of the [statement function](#) and completely supersedes it.

17 **B.3.5 DATA statements among executables**

18 1 The statement ordering rules allow [DATA statements](#) to appear anywhere in a [program unit](#) after the specific-
19 ation statements. The ability to position [DATA statements](#) amongst executable statements is very rarely used,
20 unnecessary, and a potential source of error.

21 **B.3.6 Assumed character length functions**

22 1 Assumed character length for functions is an irregularity in the language in that elsewhere in Fortran the philo-
23 sophy is that the attributes of a function result depend only on the [actual arguments](#) of the invocation and on
24 any data accessible by the function through host or use association. Some uses of this facility can be replaced
25 with an [automatic](#) character length function, where the length of the function result is declared in a [specification](#)
26 [expression](#). Other uses can be replaced by the use of a subroutine whose arguments correspond to the function
27 result and the function arguments.

28 2 Note that dummy arguments of a function can have assumed character length.

29 **B.3.7 Fixed form source**

30 1 Fixed form source was designed when the principal machine-readable input medium for new programs was punched
31 cards. Now that new and amended programs are generally entered via keyboards with screen displays, it is an
32 unnecessary overhead, and is potentially error-prone, to have to locate positions 6, 7, or 72 on a line. Free form
33 source was designed expressly for this more modern technology.

34 2 It is a simple matter for a software tool to convert from fixed to free form source.

1 **B.3.8 CHARACTER* form of CHARACTER declaration**

2 1 In addition to the CHARACTER**char-length* form introduced in FORTRAN 77, Fortran 90 provided the CHAR-
3 ACTER([LEN =] *type-param-value*) form. The older form (CHARACTER**char-length*) is redundant.

4 **B.3.9 ENTRY statements**

5 1 **ENTRY statements** allow more than one entry point to a subprogram, facilitating sharing of data items and
6 executable statements local to that subprogram.

7 2 This can be replaced by a module containing the (private) data items, with a module procedure for each entry
8 point and the shared code in a private module procedure.

9 **B.3.10 Label DO statement**

10 1 The label in the **DO statement** is redundant with the construct name. Furthermore, the label allows unrestricted
11 branches and, for its main purpose (the target of a conditional branch to skip the rest of the current iteration),
12 is redundant with the **CYCLE statement**, which is clearer.

13 **B.3.11 COMMON and EQUIVALENCE statements and the block data program unit**

14 1 **Common blocks** are error-prone and have largely been superseded by **modules**. **EQUIVALENCE** similarly is
15 error-prone. Whilst use of these statements was invaluable prior to Fortran 90 they are now redundant and
16 can inhibit performance. The **block data program unit** exists only to serve **common blocks** and hence is also
17 redundant.

18 **B.3.12 Specific names for intrinsic functions**

19 1 The **specific names of the intrinsic functions** are often obscure and hinder portability. They have been redundant
20 since Fortran 90. Use generic names for references to intrinsic procedures.

21 **B.3.13 FORALL construct and statement**

22 1 The **FORALL** construct and statement were added to the language in the expectation that they would enable
23 highly efficient execution, especially on parallel processors. However, experience indicates that they are too
24 complex and have too many restrictions for compilers to take advantage of them. They are redundant with the
25 **DO CONCURRENT construct**, and many of the manipulations for which they might be used can be done more
26 effectively using pointers, especially using pointer rank remapping.

Annex C

(Informative)

Extended notes

C.1 Clause 4 notes

C.1.1 Selection of the approximation methods (4.4.3.2)

1 One can select the real approximation method for an entire program through the use of a module and the parameterized real type. This is accomplished by defining a named integer constant to have a particular kind type parameter value and using that [named constant](#) in all real, complex, and derived-type declarations. For example, the specification statements

```

10     INTEGER, PARAMETER :: LONG_FLOAT = 8
11     REAL (LONG_FLOAT) X, Y
12     COMPLEX (LONG_FLOAT) Z

```

specify that the approximation method corresponding to a kind type parameter value of 8 is supplied for the data objects X, Y, and Z in the [program unit](#). The kind type parameter value LONG_FLOAT can be made available to an entire program by placing the INTEGER specification statement in a module and accessing the [named constant](#) LONG_FLOAT with a [USE statement](#). Note that by changing 8 to 4 once in the module, a different approximation method is selected.

2 To avoid the use of the processor-dependent values 4 or 8, replace 8 by [KIND \(0.0\)](#) or [KIND \(0.0D0\)](#). Another way to avoid these processor-dependent values is to select the kind value using the intrinsic function [SELECTED_REAL_KIND \(13.8.162\)](#). In the above specification statement, the 8 might be replaced by, for instance, [SELECTED_REAL_KIND \(10, 50\)](#), which requires an approximation method to be selected with at least 10 decimal digits of precision and a range from 10^{-50} to 10^{50} . There are no magnitude or ordering constraints placed on kind values, in order that implementers have flexibility in assigning such values and can add new kinds without changing previously assigned kind values.

3 As kind values have no portable meaning, a good practice is to use them in programs only through [named constants](#) as described above (for example, SINGLE, IEEE_SINGLE, DOUBLE, and QUAD), rather than using the kind values directly.

C.1.2 Type extension and component accessibility (4.5.2.2, 4.5.4)

1 The default accessibility of an [extended type](#) can be specified in the type definition. The accessibility of its components can be specified individually. For example:

```

31     module types
32         type base_type
33             private                !-- Sets default accessibility
34             integer :: i           !-- a private component
35             integer, private :: j !-- another private component

```

```

1         integer, public :: k    !-- a public component
2     end type base_type
3
4     type, extends(base_type) :: my_type
5         private                !-- Sets default for components declared in my_type
6         integer :: l            !-- A private component.
7         integer, public :: m    !-- A public component.
8     end type my_type
9
10    end module types
11
12    subroutine sub
13        use types
14        type (my_type) :: x
15
16        ...
17
18        call another_sub( &
19            x%base_type, & !-- ok because base_type is a public subobject of x
20            x%base_type%k, & !-- ok because x%base_type is ok and has k as a
21                                !-- public component.
22            x%k, & !-- ok because it is shorthand for x%base_type%k
23            x%base_type%i, & !-- Invalid because i is private.
24            x%i) !-- Invalid because it is shorthand for x%base_type%i
25    end subroutine sub

```

26 C.1.3 Generic type-bound procedures (4.5.5)

27 Example of a derived type with generic type-bound procedures:

28 1 The only difference between this example and the same thing rewritten to use generic [interface blocks](#) is that
29 with [type-bound procedures](#),

```
30         USE rational_numbers, ONLY: rational
```

31 does not block the [type-bound procedures](#); the user still gets access to the defined assignment and extended
32 operations.

```

33     MODULE rational_numbers
34     IMPLICIT NONE
35     PRIVATE
36     TYPE,PUBLIC :: rational
37     PRIVATE
38     INTEGER n,d
39     CONTAINS
40     ! ordinary type-bound procedure
41     PROCEDURE :: real => rat_to_real
42     ! specific type-bound procedures for generic support

```



```

1      PROCEDURE,PRIVATE :: rat_asgn_i, rat_plus_i, rat_plus_rat => rat_plus
2      PROCEDURE,PRIVATE,PASS(b) :: i_plus_rat
3      ! generic type-bound procedures
4      GENERIC :: ASSIGNMENT(=) => rat_asgn_i
5      GENERIC :: OPERATOR(+) => rat_plus_rat, rat_plus_i, i_plus_rat
6  END TYPE
7  CONTAINS
8      ELEMENTAL REAL FUNCTION rat_to_real(this) RESULT(r)
9          CLASS(rational),INTENT(IN) :: this
10         r = REAL(this%n)/this%d
11     END FUNCTION
12     ELEMENTAL SUBROUTINE rat_asgn_i(a,b)
13         CLASS(rational),INTENT(OUT) :: a
14         INTEGER,INTENT(IN) :: b
15         a%n = b
16         a%d = 1
17     END SUBROUTINE
18     ELEMENTAL TYPE(rational) FUNCTION rat_plus_i(a,b) RESULT(r)
19         CLASS(rational),INTENT(IN) :: a
20         INTEGER,INTENT(IN) :: b
21         r%n = a%n + b*a%d
22         r%d = a%d
23     END FUNCTION
24     ELEMENTAL TYPE(rational) FUNCTION i_plus_rat(a,b) RESULT(r)
25         INTEGER,INTENT(IN) :: a
26         CLASS(rational),INTENT(IN) :: b
27         r%n = b%n + a*b%d
28         r%d = b%d
29     END FUNCTION
30     ELEMENTAL TYPE(rational) FUNCTION rat_plus(a,b) RESULT(r)
31         CLASS(rational),INTENT(IN) :: a,b
32         r%n = a%n*b%d + b%n*a%d
33         r%d = a%d*b%d
34     END FUNCTION
35 END

```

36 C.1.4 Abstract types (4.5.7.1)

37 1 The following illustrates how an abstract type can be used as the basis for a collection of related types, and how
38 a non-abstract member of that collection can be created by type extension.

```

39     TYPE, ABSTRACT :: DRAWABLE_OBJECT
40         REAL, DIMENSION(3) :: RGB_COLOR = (/1.0,1.0,1.0/) ! White
41         REAL, DIMENSION(2) :: POSITION = (/0.0,0.0/) ! Centroid
42     CONTAINS
43         PROCEDURE(RENDER_X), PASS(OBJECT), DEFERRED :: RENDER
44     END TYPE DRAWABLE_OBJECT

```

```

1
2     ABSTRACT INTERFACE
3         SUBROUTINE RENDER_X(OBJECT, WINDOW)
4             IMPORT DRAWABLE_OBJECT, X_WINDOW
5             CLASS(DRAWABLE_OBJECT), INTENT(IN) :: OBJECT
6             CLASS(X_WINDOW), INTENT(INOUT) :: WINDOW
7         END SUBROUTINE RENDER_X
8     END INTERFACE
9
10    ...
11
12    TYPE, EXTENDS(DRAWABLE_OBJECT) :: DRAWABLE_TRIANGLE ! Not ABSTRACT
13        REAL, DIMENSION(2,3) :: VERTICES ! In relation to centroid
14    CONTAINS
15        PROCEDURE, PASS(OBJECT) :: RENDER=>RENDER_TRIANGLE_X
16    END TYPE DRAWABLE_TRIANGLE

```

17 2 The actual drawing procedure will draw a triangle in WINDOW with vertices at x and y coordinates at
18 OBJECT%POSITION(1)+OBJECT%VERTICES(1,1:3) and OBJECT%POSITION(2)+OBJECT%VERTICES(2,1:3):

```

19     SUBROUTINE RENDER_TRIANGLE_X(OBJECT, WINDOW)
20         CLASS(DRAWABLE_TRIANGLE), INTENT(IN) :: OBJECT
21         CLASS(X_WINDOW), INTENT(INOUT) :: WINDOW
22         ...
23     END SUBROUTINE RENDER_TRIANGLE_X

```

24 C.1.5 Structure constructors and generic names (4.5.10)

25 1 A generic name can be the same as a type name. This can be used to emulate user-defined [structure constructors](#)
26 for that type, even if the type has private components. For example:

```

27     MODULE mytype_module
28         TYPE mytype
29             PRIVATE
30             COMPLEX value
31             LOGICAL exact
32         END TYPE
33         INTERFACE mytype
34             MODULE PROCEDURE int_to_mytype
35         END INTERFACE
36         ! Operator definitions etc.
37         ...
38     CONTAINS
39         TYPE(mytype) FUNCTION int_to_mytype(i)
40             INTEGER, INTENT(IN) :: i
41             int_to_mytype%value = i
42             int_to_mytype%exact = .TRUE.

```

```

1      END FUNCTION
2      ! Procedures to support operators etc.
3      ...
4      END
5
6      PROGRAM example
7          USE mytype_module
8          TYPE(mytype) x
9          x = mytype(17)
10         END

```

11 2 The type name can still be used as a generic name if the type has type parameters. For example:

```

12     MODULE m
13         TYPE t(kind)
14             INTEGER, KIND :: kind
15             COMPLEX(kind) value
16         END TYPE
17         INTEGER, PARAMETER :: single = KIND(0.0), double = KIND(0d0)
18         INTERFACE t
19             MODULE PROCEDURE real_to_t1, dble_to_t2, int_to_t1, int_to_t2
20         END INTERFACE
21         ...
22     CONTAINS
23         TYPE(t(single)) FUNCTION real_to_t1(x)
24             REAL(single) x
25             real_to_t1%value = x
26         END FUNCTION
27         TYPE(t(double)) FUNCTION dble_to_t2(x)
28             REAL(double) x
29             dble_to_t2%value = x
30         END FUNCTION
31         TYPE(t(single)) FUNCTION int_to_t1(x,mold)
32             INTEGER x
33             TYPE(t(single)) mold
34             int_to_t1%value = x
35         END FUNCTION
36         TYPE(t(double)) FUNCTION int_to_t2(x,mold)
37             INTEGER x
38             TYPE(t(double)) mold
39             int_to_t2%value = x
40         END FUNCTION
41         ...
42     END
43
44     PROGRAM example
45         USE m

```

```

1      TYPE(t(single)) x
2      TYPE(t(double)) y
3      x = t(1.5)           ! References real_to_t1
4      x = t(17,mold=x)    ! References int_to_t1
5      y = t(1.5d0)        ! References dble_to_t2
6      y = t(42,mold=y)    ! References int_to_t2
7      y = t(kind(0d0)) ((0,1)) ! Uses the structure constructor for type t
8      END

```

9 C.1.6 Final subroutines (4.5.6, 4.5.6.2, 4.5.6.3, 4.5.6.4)

10 Example of a parameterized derived type with final subroutines:

```

11      MODULE m
12          TYPE t(k)
13              INTEGER, KIND :: k
14              REAL(k),POINTER :: vector(:) => NULL()
15          CONTAINS
16              FINAL :: finalize_t1s, finalize_t1v, finalize_t2e
17          END TYPE
18      CONTAINS
19          SUBROUTINE finalize_t1s(x)
20              TYPE(t(KIND(0.0))) x
21              IF (ASSOCIATED(x%vector)) DEALLOCATE(x%vector)
22          END SUBROUTINE
23          SUBROUTINE finalize_t1v(x)
24              TYPE(t(KIND(0.0))) x(:)
25              DO i=LBOUND(x,1),UBOUND(x,1)
26                  IF (ASSOCIATED(x(i)%vector)) DEALLOCATE(x(i)%vector)
27              END DO
28          END SUBROUTINE
29          ELEMENTAL SUBROUTINE finalize_t2e(x)
30              TYPE(t(KIND(0.0d0))),INTENT(INOUT) :: x
31              IF (ASSOCIATED(x%vector)) DEALLOCATE(x%vector)
32          END SUBROUTINE
33      END MODULE
34
35      SUBROUTINE example(n)
36          USE m
37          TYPE(t(KIND(0.0))) a,b(10),c(n,2)
38          TYPE(t(KIND(0.0d0))) d(n,n)
39          ...
40          ! Returning from this subroutine will effectively do
41          !   CALL finalize_t1s(a)
42          !   CALL finalize_t1v(b)
43          !   CALL finalize_t2e(d)
44          ! No final subroutine will be called for variable C because the user

```

```

1           ! omitted to define a suitable specific procedure for it.
2     END SUBROUTINE

```

3 **Example of extended types with final subroutines:**

```

4     MODULE m
5         TYPE t1
6             REAL a,b
7         END TYPE
8         TYPE,EXTENDS(t1) :: t2
9             REAL,POINTER :: c(:),d(:)
10        CONTAINS
11            FINAL :: t2f
12        END TYPE
13        TYPE,EXTENDS(t2) :: t3
14            REAL,POINTER :: e
15        CONTAINS
16            FINAL :: t3f
17        END TYPE
18        ...
19    CONTAINS
20        SUBROUTINE t2f(x) ! Finalizer for TYPE(t2)'s extra components
21            TYPE(t2) :: x
22            IF (ASSOCIATED(x%c)) DEALLOCATE(x%c)
23            IF (ASSOCIATED(x%d)) DEALLOCATE(x%d)
24        END SUBROUTINE
25        SUBROUTINE t3f(y) ! Finalizer for TYPE(t3)'s extra components
26            TYPE(t3) :: y
27            IF (ASSOCIATED(y%e)) DEALLOCATE(y%e)
28        END SUBROUTINE
29    END MODULE
30
31    SUBROUTINE example
32        USE m
33        TYPE(t1) x1
34        TYPE(t2) x2
35        TYPE(t3) x3
36        ...
37        ! Returning from this subroutine will effectively do
38        !     ! Nothing to x1; it is not finalizable
39        !     CALL t2f(x2)
40        !     CALL t3f(x3)
41        !     CALL t2f(x3%t2)
42    END SUBROUTINE

```

1 C.2 Clause 5 notes: The VOLATILE attribute (5.5.19)

2 1 The following example shows the use of a variable with the [VOLATILE attribute](#) to communicate with an
3 asynchronous process, in this case the operating system. The program detects a user keystroke on the terminal
4 and reacts at a convenient point in its processing.

5 2 The [VOLATILE attribute](#) is necessary to prevent an optimizing compiler from storing the communication variable
6 in a register or from doing flow analysis and deciding that the [EXIT statement](#) can never be executed.

```
7      SUBROUTINE TERMINATE_ITERATIONS
8          LOGICAL, VOLATILE :: USER_HIT_ANY_KEY
9
10         ! Have the OS start to look for a user keystroke and set the variable
11         ! "USER_HIT_ANY_KEY" to TRUE as soon as it detects a keystroke.
12         ! This call is operating system dependent.
13
14         CALL OS_BEGIN_DETECT_USER_KEYSTROKE( USER_HIT_ANY_KEY )
15         USER_HIT_ANY_KEY = .FALSE.      ! This will ignore any recent keystrokes.
16         PRINT *, " Hit any key to terminate iterations!"
17
18         DO I = 1,100
19             ...                        ! Compute a value for R.
20             PRINT *, I, R
21             IF (USER_HIT_ANY_KEY)      EXIT
22         ENDDO
23
24         ! Have the OS stop looking for user keystrokes.
25         CALL OS_STOP_DETECT_USER_KEYSTROKE
26
27     END SUBROUTINE TERMINATE_ITERATIONS
```

28 C.3 Clause 6 notes

29 C.3.1 Structure components (6.4.2)

30 1 Components of a structure are referenced by writing the components of successive levels of the structure hierarchy
31 until the desired component is described. For example,

```
32     TYPE ID_NUMBERS
33         INTEGER SSN
34         INTEGER EMPLOYEE_NUMBER
35     END TYPE ID_NUMBERS
36
37     TYPE PERSON_ID
38         CHARACTER (LEN=30) LAST_NAME
39         CHARACTER (LEN=1) MIDDLE_INITIAL
40         CHARACTER (LEN=30) FIRST_NAME
```

```

1         TYPE (ID_NUMBERS) NUMBER
2     END TYPE PERSON_ID
3
4     TYPE PERSON
5         INTEGER AGE
6         TYPE (PERSON_ID) ID
7     END TYPE PERSON
8
9     TYPE (PERSON) GEORGE, MARY
10
11    PRINT *, GEORGE % AGE           ! Print the AGE component
12    PRINT *, MARY % ID % LAST_NAME ! Print LAST_NAME of MARY
13    PRINT *, MARY % ID % NUMBER % SSN ! Print SSN of MARY
14    PRINT *, GEORGE % ID % NUMBER ! Print SSN and EMPLOYEE_NUMBER of GEORGE

```

- 15 2 A [structure component](#) can be a data object of intrinsic type as in the case of GEORGE % AGE or it can be
 16 of derived type as in the case of GEORGE % ID % NUMBER. The resultant component can be a scalar or an
 17 array of intrinsic or derived type.

```

18    TYPE LARGE
19        INTEGER ELT (10)
20        INTEGER VAL
21    END TYPE LARGE
22
23    TYPE (LARGE) A (5)           ! 5 element array, each of whose elements
24                                ! includes a 10 element array ELT and
25                                ! a scalar VAL.
26    PRINT *, A (1)              ! Prints 10 element array ELT and scalar VAL.
27    PRINT *, A (1) % ELT (3)    ! Prints scalar element 3
28                                ! of array element 1 of A.
29    PRINT *, A (2:4) % VAL      ! Prints scalar VAL for array elements
30                                ! 2 to 4 of A.

```

- 31 3 Components of an object of [extensible type](#) that are [inherited](#) from the [parent type](#) can be accessed as a whole
 32 by using the [parent component](#) name, or individually, either with or without qualifying them by the [parent](#)
 33 [component](#) name. For example:

```

34    TYPE POINT                   ! A base type
35        REAL :: X, Y
36    END TYPE POINT
37    TYPE, EXTENDS(POINT) :: COLOR_POINT ! An extension of TYPE(POINT)
38        ! Components X and Y, and component name POINT, inherited from parent
39        INTEGER :: COLOR
40    END TYPE COLOR_POINT
41
42    TYPE(POINT) :: PV = POINT(1.0, 2.0)
43    TYPE(COLOR_POINT) :: CPV = COLOR_POINT(POINT=PV, COLOR=3)

```

```

1
2     PRINT *, CPV%POINT           ! Prints 1.0 and 2.0
3     PRINT *, CPV%POINT%X, CPV%POINT%Y ! And this does, too
4     PRINT *, CPV%X, CPV%Y       ! And this does, too

```

5 C.3.2 Allocation with dynamic type (6.7.1)

6 1 The following example illustrates the use of allocation with the value and [dynamic type](#) of the allocated object
7 given by another object. The example copies a list of objects of any type. It copies the list starting at IN_LIST.
8 After copying, each element of the list starting at LIST_COPY has a polymorphic component, ITEM, for which
9 both the value and type are taken from the ITEM component of the corresponding element of the list starting at
10 IN_LIST.

```

11     TYPE :: LIST ! A list of anything
12     TYPE(LIST), POINTER :: NEXT => NULL()
13     CLASS(*), ALLOCATABLE :: ITEM
14     END TYPE LIST
15     ...
16     TYPE(LIST), POINTER :: IN_LIST, LIST_COPY => NULL()
17     TYPE(LIST), POINTER :: IN_WALK, NEW_TAIL
18     ! Copy IN_LIST to LIST_COPY
19     IF (ASSOCIATED(IN_LIST)) THEN
20         IN_WALK => IN_LIST
21         ALLOCATE(LIST_COPY)
22         NEW_TAIL => LIST_COPY
23         DO
24             ALLOCATE(NEW_TAIL%ITEM, SOURCE=IN_WALK%ITEM)
25             IN_WALK => IN_WALK%NEXT
26             IF (.NOT. ASSOCIATED(IN_WALK)) EXIT
27             ALLOCATE(NEW_TAIL%NEXT)
28             NEW_TAIL => NEW_TAIL%NEXT
29         END DO
30     END IF

```

31 C.4 Clause 7 notes

32 C.4.1 Evaluation of function references (7.1.7)

33 1 If more than one function reference appears in a statement, they can be executed in any order (subject to a
34 function result being evaluated after the evaluation of its arguments) and their values cannot depend on the order
35 of execution. This lack of dependence on order of evaluation enables parallel execution of the function references.

36 C.4.2 Pointers in expressions (7.1.9.2)

37 1 A pointer is considered to be like any other variable when it is used as a primary in an expression. If a pointer
38 is used as an operand to an operator that expects a value, the pointer will automatically deliver the value stored
39 in the space described by the pointer, that is, the value of the target object associated with the pointer.

1 C.4.3 Pointers in variable definition contexts (7.2.1.3, 16.6.7)

2 1 The appearance of a pointer in a context that requires its value is a reference to its target. Similarly, where a
3 pointer appears in a variable definition context the variable that is defined is the target of the pointer.

4 2 Executing the program fragment

```
5         REAL, POINTER :: A
6         REAL, TARGET :: B = 10.0
7         A => B
8         A = 42.0
9         PRINT '(F4.1)', B
```

10 produces “42.0” as output.

11 C.5 Clause 8 notes

12 C.5.1 The SELECT CASE construct (8.1.8)

13 1 At most one case block is selected for execution within a [SELECT CASE construct](#), and there is no fall-through
14 from one block into another block within a [SELECT CASE construct](#). Thus there is no requirement for the user
15 to exit explicitly from a block.

16 C.5.2 Loop control (8.1.6)

17 1 Fortran provides several forms of loop control:

- 18 (1) With an iteration count and a DO variable. This is the classic Fortran DO loop.
- 19 (2) Test a logical condition before each execution of the loop (DO WHILE).
- 20 (3) DO “forever”.

21 C.5.3 Examples of DO constructs (8.1.6)

22 1 The following are all valid examples of [DO constructs](#).

23 Example 1:

```
24         SUM = 0.0
25         READ (IUN) N
26         OUTER: DO L = 1, N           ! A DO with a construct name
27             READ (IUN) IQUAL, M, ARRAY (1:M)
28             IF (IQUAL < IQUAL_MIN) CYCLE OUTER ! Skip inner loop
29             INNER: DO 40 I = 1, M     ! A DO with a label and a name
30                 CALL CALCULATE (ARRAY (I), RESULT)
31                 IF (RESULT < 0.0) CYCLE
32                 SUM = SUM + RESULT
33                 IF (SUM > SUM_MAX) EXIT OUTER
34     40     END DO INNER
35         END DO OUTER
```

1 2 The outer loop has an iteration count of `MAX (N, 0)`, and will execute that number of times or until `SUM` exceeds
 2 `SUM_MAX`, in which case the `EXIT OUTER` statement terminates both loops. The inner loop is skipped by
 3 the first `CYCLE statement` if the quality flag, `IQUAL`, is too low. If `CALCULATE` returns a negative `RESULT`,
 4 the second `CYCLE statement` prevents it from being summed. Both loops have construct names and the inner
 5 loop also has a label. A construct name is required in the `EXIT statement` in order to terminate both loops, but
 6 is optional in the `CYCLE statements` because each belongs to its innermost loop.

7 **Example 2:**

```
8         N = 0
9         DO 50, I = 1, 10
10            J = I
11            DO K = 1, 5
12                L = K
13                N = N + 1 ! This statement executes 50 times
14            END DO      ! Nonlabeled DO inside a labeled DO
15 50 CONTINUE
```

16 3 After execution of the above program fragment, `I = 11`, `J = 10`, `K = 6`, `L = 5`, and `N = 50`.

17 **Example 3:**

```
18         N = 0
19         DO I = 1, 10
20            J = I
21            DO 60, K = 5, 1 ! This inner loop is never executed
22                L = K
23                N = N + 1
24 60 CONTINUE      ! Labeled DO inside a nonlabeled DO
25 END DO
```

26 4 After execution of the above program fragment, `I = 11`, `J = 10`, `K = 5`, `N = 0`, and `L` is not defined by these
 27 statements.

28 **C.5.4 Examples of invalid DO constructs (8.1.6)**

29 1 The following are all examples of invalid skeleton `DO constructs`:

30 **Example 1:**

```
31         DO I = 1, 10
32             ...
33         END DO LOOP ! No matching construct name
```

34 **Example 2:**

```
35         LOOP: DO 1000 I = 1, 10 ! No matching construct name
36             ...
37 1000 CONTINUE
```

1 **Example 3:**

```

2     LOOP1: DO
3         ...
4     END DO LOOP2    ! Construct names don't match

```

5 **Example 4:**

```

6     DO I = 1, 10    ! Label required or ...
7         ...
8     1010 CONTINUE ! ... END DO required

```

9 **Example 5:**

```

10     DO 1020 I = 1, 10
11         ...
12     1021 END DO    ! Labels don't match

```

13 **Example 6:**

```

14     FIRST: DO I = 1, 10
15         SECOND: DO J = 1, 5
16             ...
17         END DO FIRST    ! Improperly nested DOs
18     END DO SECOND

```

19 **C.5.5 Simple example using events**

- 20 1 A tree is a graph in which every node except one has a single “parent” node to which it is connected by an edge.
 21 The node without a parent is the “root” of the tree. The nodes that have a particular node as their parent are
 22 the “children” of that node. The root is at level 1, its children are at level 2, and so on.
- 23 2 A multifrontal code to solve a sparse set of linear equations involves a tree. Work at a node can start after all of
 24 its children’s work is complete and their data have been passed to it.
- 25 3 Here we assume that each node has been assigned to an image. Each image has a list of its nodes and these
 26 are ordered in decreasing tree level (all those at level L preceding those at level $L - 1$). For each node, array
 27 elements hold the number of children, details about the parent, and an event variable. This allows the processing
 28 to proceed asynchronously subject to the rule that a parent must wait for all its children.

29 **Outline of example code:**

```

30     PROGRAM TREE
31         USE, INTRINSIC :: ISO_FORTRAN_ENV
32         INTEGER, ALLOCATABLE :: NODE (:) ! Tree nodes that this image handles.
33         INTEGER, ALLOCATABLE :: NC (:)    ! NODE(I) has NC(I) children.
34         INTEGER, ALLOCATABLE :: PARENT (:), SUB (:)
35         ! The parent of NODE (I) is NODE (SUB (I)) [PARENT (I)].
36         TYPE (EVENT_TYPE), ALLOCATABLE :: DONE (:) [*]

```

```

1      INTEGER :: I, J, STATUS
2      ! Set up the tree, including allocation of all arrays.
3      DO I = 1, SIZE (NODE)
4          ! Wait for children to complete
5          IF (NC (I) > 0) THEN
6              EVENT WAIT (DONE (I), UNTIL_COUNT=NC (I), STAT=STATUS)
7              IF (STATUS/=0) EXIT
8          END IF
9
10         ! Process node, using data from children.
11         IF (PARENT (I)>0) THEN
12             ! Node is not the root.
13             ! Place result on image PARENT (I) for node NODE (SUB) [PARENT (I)]
14             ! Tell PARENT (I) that this has been done.
15             EVENT POST (DONE (SUB (I)) [PARENT (I)], STAT=STATUS)
16             IF (STATUS/=0) EXIT
17         END IF
18     END DO
19 END PROGRAM TREE

```

20 C.6 Clause 9 notes

21 C.6.1 External files (9.3)

22 1 This part of ISO/IEC 1539 accommodates, but does not require, file cataloging. To do this, several concepts are
23 introduced.

24 C.6.1.1 File existence (9.3.2)

25 1 Totally independent of the connection state is the property of existence, this being a file property. The processor
26 “knows” of a set of files that exist at a given time for a given program. This set would include tapes ready to
27 read, files in a catalog, a keyboard, a printer, etc. The set might exclude files inaccessible to the program because
28 of security, because they are already in use by another program, etc. This part of ISO/IEC 1539 does not specify
29 which files exist, hence wide latitude is available to a processor to implement security, locks, privilege techniques,
30 etc. Existence is a convenient concept to designate all of the files that a program can potentially process.

31 2 All four combinations of connection and existence can occur:

Connect	Exist	Examples
Yes	Yes	A card reader loaded and ready to be read
Yes	No	A printer before the first line is written
No	Yes	A file named 'JOAN' in the catalog
No	No	A file on a reel of tape, not known to the processor

32 3 Means are provided to create, delete, connect, and disconnect files.

1 C.6.1.2 File access (9.3.3)

2 1 This part of ISO/IEC 1539 does not address problems of security, protection, locking, and many other concepts
3 that might be part of the concept of “right of access”. Such concepts are considered to be in the province of an
4 operating system.

5 2 The [OPEN](#) and [INQUIRE](#) statements can be extended naturally to consider these things.

6 3 Possible access methods for a file are: sequential, stream and direct. The processor might implement three
7 different types of files, each with its own access method. It might instead implement one type of file with three
8 different access methods.

9 4 Direct access to files is of a simple and commonly available type, that is, fixed-length records. The key is a
10 positive integer.

11 C.6.1.3 File connection (9.5)

12 1 Before any input/output can be performed on a file, it needs to be connected to a [unit](#). The [unit](#) then serves as a
13 designator for that file as long as it is connected. To be connected does not imply that “buffers” have or have not
14 been allocated, that “file-control tables” have or have not been filled, or that any other method of implementation
15 has been used. Connection means that (barring some other fault) a [READ](#) or [WRITE](#) statement can be executed
16 on the [unit](#), hence on the file. Without a connection, a [READ](#) or [WRITE](#) statement cannot be executed.

17 C.6.1.4 File names (9.5.6.10)

18 1 A file can have a name. The form of a file name is not specified. If a system does not have some form of cataloging
19 or tape labeling for at least some of its files, all file names disappear at the [termination of execution](#). This is
20 a valid implementation. Nowhere does this part of ISO/IEC 1539 require names to survive for any period of
21 time longer than the execution time span of a program. Therefore, this part of ISO/IEC 1539 does not impose
22 cataloging as a prerequisite. The naming feature is intended to enable use of a cataloging system where one
23 exists.

24 C.6.2 Nonadvancing input/output (9.3.4.2)

25 1 [Data transfer statements](#) affect the positioning of an [external file](#). In FORTRAN 77, if no error or end-of-file
26 condition exists, the file is positioned after the record just read or written and that record becomes the preceding
27 record. This part of ISO/IEC 1539 contains the [ADVANCE= specifier](#) in a [data transfer statement](#) that provides
28 the capability of maintaining a position within the current record from one formatted [data transfer statement](#) to
29 the next [data transfer statement](#). The value NO provides this capability. The value YES positions the file after
30 the record just read or written. The default is YES.

31 2 The tab edit descriptor and the slash are still appropriate for use with this type of record access but the tab
32 cannot reposition before the left tab limit.

33 3 A [BACKSPACE](#) of a file that is positioned within a record causes the specified unit to be positioned before the
34 current record.

35 4 If the next input/output operation on a file after a nonadvancing write is a [rewind](#), [backspace](#), [end file](#) or [close](#)
36 operation, the file is positioned implicitly after the current record before an ENDFILE record is written to the
37 file, that is, a [REWIND](#), [BACKSPACE](#), or [ENDFILE](#) statement following a nonadvancing [WRITE statement](#)

1 causes the file to be positioned at the end of the current output record before the endfile record is written to the
2 file.

3 5 This part of ISO/IEC 1539 provides a [SIZE= specifier](#) to be used with nonadvancing [data transfer statements](#).
4 The variable in the [SIZE= specifier](#) is assigned the count of the number of characters that make up the sequence
5 of values read by the data edit descriptors in the [input statement](#).

6 6 The count is especially helpful if there is only one list item in the input list because it is the number of characters
7 that appeared for the item.

8 7 The [EOR= specifier](#) is provided to indicate when an EOR condition is encountered during a nonadvancing [data](#)
9 [transfer statement](#). The EOR condition is not an error condition. If this specifier appears, an input list item that
10 requires more characters than the record contained is padded with blanks if [PAD= 'YES'](#) is in effect. This means
11 that the input list item completed successfully. The file is positioned after the current record. If the [IOSTAT=](#)
12 [specifier](#) appears, the specified variable is defined with the value of the [named constant IOSTAT_EOR](#) from
13 the intrinsic module [ISO_FORTRAN_ENV](#) and the [data transfer statement](#) is terminated. Program execution
14 continues with the statement specified in the [EOR= specifier](#). The [EOR= specifier](#) gives the capability of taking
15 control of execution when the EOR condition is encountered. The *do-variables* in *io-implied-dos* retain their last
16 defined value and any remaining items in the *input-item-list* retain their definition status when an EOR condition
17 occurs. If the [SIZE= specifier](#) appears, the specified variable is assigned the number of characters read with the
18 data edit descriptors during the [READ statement](#).

19 8 For nonadvancing input, the processor is not required to read partial records. The processor could read the entire
20 record into an internal buffer and make successive portions of the record available to successive [input statements](#).

21 9 In an implementation of nonadvancing input/output in which a nonadvancing write to a terminal device causes
22 immediate display of the output, such a write can be used as a mechanism to output a prompt. In this case, the
23 statement

```
24 WRITE (*, FMT='(A)', ADVANCE='NO') 'CONTINUE?(Y/N): '
```

25 would result in the prompt

```
26 CONTINUE?(Y/N):
```

27 being displayed with no subsequent line feed.

28 10 The response, which might be read by a statement of the form

```
29 READ (*, FMT='(A)') ANSWER
```

30 can then be entered on the same line as the prompt as in

```
31 CONTINUE?(Y/N): Y
```

32 11 This part of ISO/IEC 1539 does not require that an implementation of nonadvancing input/output operate in this
33 manner. For example, an implementation of nonadvancing output in which the display of the output is deferred
34 until the current record is complete is also standard-conforming. Such an implementation will not, however, allow
35 a prompting mechanism of this kind to operate.

36 C.6.3 OPEN statement ([9.5.6](#))

37 1 A file can become connected to a [unit](#) either by preconnection or by execution of an [OPEN statement](#). Precon-
38 nection is performed prior to the beginning of execution of a program by means external to Fortran. For example,

- 1 it could be done by job control action or by processor-established defaults. Execution of an **OPEN statement** is
 2 not required in order to access preconnected files (9.5.5).
- 3 2 The **OPEN statement** provides a means to access existing files that are not preconnected. An **OPEN statement**
 4 can be used in either of two ways: with a file name (open-by-name) and without a file name (open-by-unit). A
 5 **unit** is given in either case. Open-by-name connects the specified file to the specified **unit**. Open-by-unit connects
 6 a processor-dependent default file to the specified **unit**. (The default file might or might not have a name.)
- 7 3 Therefore, there are three ways a file can become connected and hence processed: preconnection, open-by-name,
 8 and open-by-unit. Once a file is connected, there is no means in standard Fortran to determine how it became
 9 connected.
- 10 4 An **OPEN statement** can also be used to create a new file. In fact, any of the foregoing three connection methods
 11 can be performed on a file that does not exist. When a **unit** is preconnected, writing the first record creates the
 12 file. With the other two methods, execution of the **OPEN statement** creates the file.
- 13 5 When an **OPEN statement** is executed, the **unit** specified in the **OPEN** might or might not already be connected
 14 to a file. If it is already connected to a file (either through preconnection or by a prior **OPEN**), then omitting
 15 the **FILE= specifier** in the **OPEN statement** implies that the file is to remain connected to the **unit**. Such an
 16 **OPEN statement** can be used to change the values of the blank interpretation mode, decimal edit mode, pad
 17 mode, input/output rounding mode, delimiter mode, and sign mode.
- 18 6 If the value of the **ACTION= specifier** is WRITE, then a **READ statement** cannot refer to the connection.
 19 **ACTION = 'WRITE'** does not restrict positioning by a **BACKSPACE statement** or positioning specified by the
 20 **POSITION= specifier** with the value APPEND. However, a **BACKSPACE statement** or an **OPEN statement**
 21 containing **POSITION = 'APPEND'** might fail if the processor needs to read the file to achieve the positioning.
- 22 7 The following examples illustrate these rules. In the first example, **unit 10** is preconnected to a SCRATCH file;
 23 the **OPEN statement** changes the value of **PAD=** to YES.

```

24 CHARACTER (LEN = 20) CH1
25 WRITE (10, '(A)') 'THIS IS RECORD 1'
26 OPEN (UNIT = 10, STATUS = 'OLD', PAD = 'YES')
27 REWIND 10
28 READ (10, '(A20)') CH1 ! CH1 now has the value
29 ! 'THIS IS RECORD 1 '

```

- 30 8 In the next example, **unit 12** is first connected to a file named FRED, with a status of OLD. The second **OPEN**
 31 **statement** then opens **unit 12** again, retaining the connection to the file FRED, but changing the value of the
 32 **DELIM= specifier** to QUOTE.

```

33 CHARACTER (LEN = 25) CH2, CH3
34 OPEN (12, FILE = 'FRED', STATUS = 'OLD', DELIM = 'NONE')
35 CH2 = '"THIS STRING HAS QUOTES."'
36 ! Quotes in string CH2
37 WRITE (12, *) CH2 ! Written with no delimiters
38 OPEN (12, DELIM = 'QUOTE') ! Now quote is the delimiter
39 REWIND 12
40 READ (12, *) CH3 ! CH3 now has the value
41 ! 'THIS STRING HAS QUOTES. '

```

1 9 The next example is invalid because it attempts to change the value of the `STATUS= specifier`.

```
2 OPEN (10, FILE = 'FRED', STATUS = 'OLD')
3 WRITE (10, *) A, B, C
4 OPEN (10, STATUS = 'SCRATCH') ! Attempts to make FRED a SCRATCH file
```

5 10 The previous example could be made valid by closing the `unit` first, as in the next example.

```
6 OPEN (10, FILE = 'FRED', STATUS = 'OLD')
7 WRITE (10, *) A, B, C
8 CLOSE (10)
9 OPEN (10, STATUS = 'SCRATCH') ! Opens a different SCRATCH file
```

10 C.6.4 Connection properties (9.5.4)

11 1 When a `unit` becomes connected to a file, either by execution of an `OPEN statement` or by preconnection, the
12 following connection properties, among others, are established.

- 13 (1) An access method, which is sequential, direct, or stream, is established for the connection (9.5.6.3).
- 14 (2) A form, which is formatted or unformatted, is established for a connection to a file that exists or
15 is created by the connection. For a connection that results from execution of an `OPEN statement`,
16 a default form (which depends on the access method, as described in 9.3.3) is established if no
17 form is specified. For a preconnected file that exists, a form is established by preconnection. For a
18 preconnected file that does not exist, a form might be established, or the establishment of a form
19 might be delayed until the file is created (for example, by execution of a formatted or unformatted
20 `WRITE statement`) (9.5.6.11).
- 21 (3) A record length might be established. If the access method is direct, the connection establishes a
22 record length that specifies the length of each record of the file. A direct access file can only contain
23 records that are all of equal length.
- 24 (4) A sequential file can contain records of varying lengths. In this case, the record length established
25 specifies the maximum length of a record in the file (9.5.6.15).

26 2 A processor has wide latitude in adapting these concepts and actions to its own cataloging and job control
27 conventions. Some processors might need job control action to specify the set of files that exist or that will be
28 created by a program. Some processors might not need any job control action prior to execution. This part of
29 ISO/IEC 1539 enables processors to perform dynamic open, close, or file creation operations, but it does not
30 require such capabilities of the processor.

31 3 The meaning of “open” in contexts other than Fortran might include such things as mounting a tape, console
32 messages, spooling, label checking, security checking, etc. These actions might occur upon job control action
33 external to Fortran, upon execution of an `OPEN statement`, or upon execution of the first read or write of the
34 file. The `OPEN statement` describes properties of the connection to the file and might or might not cause physical
35 activities to take place.

36 C.6.5 Asynchronous input/output (9.6.2.5)

37 1 Rather than limit support for asynchronous input/output to what has been traditionally provided by facilities
38 such as `BUFFERIN/BUFFEROUT`, this part of ISO/IEC 1539 builds upon existing Fortran syntax. This permits

- 1 alternative approaches for implementing asynchronous input/output, and simplifies the task of adapting existing
2 standard-conforming programs to use asynchronous input/output.
- 3 2 Not all processors actually perform input/output asynchronously, nor will every processor that does be able to
4 handle **data transfer statements** with complicated input/output item lists in an asynchronous manner. Such
5 processors can still be standard-conforming.
- 6 3 This part of ISO/IEC 1539 allows for at least two different conceptual models for asynchronous input/output.
- 7 4 Model 1: the processor performs asynchronous input/output when the item list is simple (perhaps one contiguous
8 named array) and the input/output is unformatted. The implementation cost is reduced, and this is the scenario
9 most likely to be beneficial on traditional “big-iron” machines.
- 10 5 Model 2: The processor is free to do any of the following:
- 11 (1) on output, create a buffer inside the input/output library, completely formatted, and then start an
12 asynchronous write of the buffer, and immediately return to the next statement in the program. The
13 processor is free to wait for previously issued WRITES, or not, or
- 14 (2) pass the input/output list addresses to another processor/process, which processes the list items
15 independently of the processor that executes the user’s code. The addresses of the list items must be
16 computed before the asynchronous **READ/WRITE** statement completes. There is still an ordering
17 requirement on list item processing to handle things like **READ (...)** N,(a(i),i=1,N).
- 18 6 A program can issue a large number of asynchronous input/output requests, without waiting for any of them to
19 complete, and then wait for any or all of them. That does not constitute a requirement for the processor to keep
20 track of each individual request separately.
- 21 7 It is not necessary for all requests to be tracked by the runtime library. If an **ID= specifier** does not appear in on a
22 **READ** or **WRITE** statement, the runtime library can forget about this particular request once it has successfully
23 completed. If an error or end-of-file condition occurs for a request, the processor can report this during any
24 input/output operation to that **unit**. If an **ID= specifier** appears, the processor’s runtime input/output library
25 will need to keep track of any end-of-file or error conditions for that particular input/output request. However, if
26 the input/output request succeeds without any exceptional conditions occurring, then the runtime can forget that
27 **ID=** value. A runtime library might only keep track of the last request made, or perhaps a very few. Then, when
28 a user **WAITs** for a particular request, either the library will know about it (and does the right thing with respect
29 to error handling, etc.), or can assume it is a request that successfully completed and was forgotten about (and
30 will just return without signaling any end-of-file or error condition). A standard-conforming program can only
31 pass valid **ID=** values, but there is no requirement on the processor to detect invalid **ID=** values. There might
32 be a processor dependent limit on how many outstanding input/output requests that generate an end-of-file or
33 error condition can be handled before the processor runs out of memory to keep track of such conditions. The
34 restrictions on the **SIZE=** variables are designed to enable the processor to update such variables at any time
35 (after the request has been processed, but before the wait operation), and then forget about them. Only error and
36 end-of-file conditions are expected to be tracked by individual request by the runtime, and then only if an **ID=**
37 **specifier** appears. The **END=** and **EOR=** specifiers have not been added to all statements that can perform wait
38 operations. Instead, the **IOSTAT** variable can be queried after a wait operation to handle this situation. This
39 choice was made because the **WAIT statement** is expected to be the usual method of waiting for input/output
40 to complete (and **WAIT** does support the **END=** and **EOR=** specifiers). This particular choice is philosophical,
41 and was not based on significant technical difficulties.

1 8 The requirement to set the IOSTAT variable correctly means that a processor will need to remember which
2 input/output requests encountered an end-of-record condition, so that a subsequent wait operation can return
3 the correct IOSTAT value. Therefor there might be a processor defined limit on the number of outstanding
4 nonadvancing input/output requests that have encountered an end-of-record condition (constrained by available
5 memory to keep track of this information, similar to end-of-file and error conditions).

6 **C.7 Clause 10 notes**

7 **C.7.1 Number of records (10.4, 10.5, 10.8.2)**

8 1 The number of records read by an explicitly formatted advancing input statement can be determined from the
9 following rule: a record is read at the beginning of the format scan (even if the input list is empty unless the most
10 recently previous operation on the `unit` was not a nonadvancing read operation), at each slash edit descriptor
11 encountered in the format, and when a format rescan occurs at the end of the format.

12 2 The number of records written by an explicitly formatted advancing output statement can be determined from
13 the following rule: a record is written when a slash edit descriptor is encountered in the format, when a format
14 rescan occurs at the end of the format, and at completion of execution of an advancing `output statement` (even if
15 the output list is empty). Thus, the occurrence of n successive slashes between two other edit descriptors causes
16 $n - 1$ blank lines if the records are printed. The occurrence of n slashes at the beginning or end of a complete
17 format specification causes n blank lines if the records are printed. However, a complete format specification
18 containing n slashes ($n > 0$) and no other edit descriptors causes $n + 1$ blank lines if the records are printed. For
19 example, the statements

```
20 PRINT 3  
21 3 FORMAT (/)
```

22 will write two records that cause two blank lines if the records are printed.

23 **C.7.2 List-directed input (10.10.3)**

24 1 The following examples illustrate list-directed input. A blank character is represented by b.

25 2 **Example 1:**

26 **Program:**

```
27 J = 3  
28 READ *, I  
29 READ *, J
```

30 **Sequential input file:**

```
31 record 1: b1b,4bbbb  
32 record 2: ,2bbbbbbb
```

33 3 Result: $I = 1, J = 3$.

34 4 Explanation: The second `READ statement` reads the second record. The initial comma in the record designates
35 a null value; therefore, `J` is not redefined.

1 5 **Example 2:**

2 **Program:**

```
3 CHARACTER A *8, B *1
4 READ *, A, B
```

5 **Sequential input file:**

```
6 record 1: 'bbbbbbbb'
7 record 2: 'QXY'b'Z'
```

8 6 Result: A = 'bbbbbbbb', B = 'Q'

9 7 Explanation: In the first record, the rightmost apostrophe is interpreted as delimiting the constant (it cannot
10 be the first of a pair of embedded apostrophes representing a single apostrophe because this would involve
11 the prohibited “splitting” of the pair by the end of a record); therefore, A is assigned the character constant
12 'bbbbbbbb'. The end of a record acts as a blank, which in this case is a value separator because it occurs between
13 two constants.

14 **C.8 Clause 11 notes**

15 **C.8.1 Main program and block data program unit (11.1, 11.3)**

16 1 The name of the main program or of a block data program unit has no explicit use within the Fortran language.
17 It is available for documentation and for possible use by a processor.

18 2 A processor might implement an unnamed program unit by assigning it a global identifier that is not used
19 elsewhere in the program. This could be done by using a default name that does not satisfy the rules for Fortran
20 names.

21 **C.8.2 Dependent compilation (11.2)**

22 1 This part of ISO/IEC 1539, like its predecessors, is intended to enable the implementation of conforming processors
23 in which a program can be broken into multiple units, each of which can be separately translated in preparation
24 for execution. Such processors are commonly described as supporting separate compilation. There is an important
25 difference between the way separate compilation can be implemented under this part of ISO/IEC 1539 and the
26 way it could be implemented under the FORTRAN 77 International Standard. Under the FORTRAN 77 standard,
27 any information required to translate a [program unit](#) was specified in that [program unit](#). Each translation was
28 thus totally independent of all others. Under this part of ISO/IEC 1539, a [program unit](#) can use information
29 that was specified in a separate module and thus can be dependent on that module. The implementation of this
30 dependency in a processor might be that the translation of a [program unit](#) depends on the results of translating
31 one or more modules. Processors implementing the dependency this way are commonly described as supporting
32 dependent compilation.

33 2 The dependencies involved here are new only in the sense that the Fortran processor is now aware of them. The
34 same information dependencies existed under the FORTRAN 77 International Standard, but it was the program-
35 mer's responsibility to transport the information necessary to resolve them by making redundant specifications of

1 the information in multiple [program units](#). The availability of separate but dependent compilation offers several
2 potential advantages over the redundant textual specification of information.

- 3 (1) Specifying information at a single place in the program ensures that different [program units](#) using that
4 information are translated consistently. Redundant specification leaves the possibility that different
5 information can be erroneously be specified. Even if an INCLUDE line is used to ensure that the
6 text of the specifications is identical in all involved [program units](#), the presence of other specifications
7 (for example, an [IMPLICIT statement](#)) could change the interpretation of that text.
- 8 (2) During the revision of a program, it is possible for a processor to assist in determining whether differ-
9 ent [program units](#) have been translated using different (incompatible) versions of a module, although
10 there is no requirement that a processor provide such assistance. Inconsistencies in redundant textual
11 specification of information, on the other hand, tend to be much more difficult to detect.
- 12 (3) Putting information in a module provides a way of packaging it. Without modules, redundant spe-
13 cifications frequently are interleaved with other specifications in a [program unit](#), making convenient
14 packaging of such information difficult.
- 15 (4) Because a processor can be implemented such that the specifications in a module are translated once
16 and then repeatedly referenced, there is the potential for greater efficiency than when the processor
17 translates redundant specifications of information in multiple [program units](#).

- 18 3 The exact meaning of the requirement that the public portions of a module be available at the time of reference
19 is processor dependent. For example, a processor could consider a module to be available only after it has been
20 compiled and require that if the module has been compiled separately, the result of that compilation be identified
21 to the compiler when compiling [program units](#) that use it.

22 **C.8.2.1 USE statement and dependent compilation (11.2.2)**

- 23 1 Another benefit of the [USE statement](#) is its enhanced facilities for name management. If one needs to use only
24 selected entities in a module, one can do so without having to worry about the names of all the other entities
25 in that module. If one needs to use two different modules that happen to contain entities with the same name,
26 there are several ways to deal with the conflict. If none of the entities with the same name are to be used, they
27 can simply be ignored. If the name happens to refer to the same entity in both modules (for example, if both
28 modules obtained it from a third module), then there is no confusion about what the name denotes and the name
29 can be freely used. If the entities are different and one or both is to be used, the local renaming facility in the
30 [USE statement](#) makes it possible to give those entities different names in the [program unit](#) containing the [USE](#)
31 [statements](#).
- 32 2 A benefit of using the [ONLY](#) option consistently, as compared to [USE](#) without it, is that the module from which
33 each accessed entity is accessed is explicitly specified in each [program unit](#). This means that one need not search
34 other [program units](#) to find where each one is defined. This reduces maintenance costs.
- 35 3 A typical implementation of dependent but separate compilation might involve storing the result of translating a
36 module in a file whose name is derived from the name of the module. Note, however, that the name of a module
37 is limited only by the Fortran rules and not by the names allowed in the file system. Thus the processor might
38 have to provide a mapping between Fortran names and file system names.
- 39 4 The result of translating a module could reasonably either contain only the information textually specified in the
40 module (with “pointers” to information originally textually specified in other modules) or contain all information
41 specified in the module (including copies of information originally specified in other modules). Although the former
42 approach would appear to save on storage space, the latter approach can greatly simplify the logic necessary to

1 process a [USE statement](#) and can avoid the necessity of imposing a limit on the logical “nesting” of modules via
2 the [USE statement](#).

3 5 There is an increased potential for undetected errors in a [scoping unit](#) that uses both implicit typing and the
4 [USE statement](#). For example, in the program fragment

```
5         SUBROUTINE SUB
6             USE MY_MODULE
7             IMPLICIT INTEGER (I-N), REAL (A-H, O-Z)
8             X = F (B)
9             A = G (X) + H (X + 1)
10        END SUBROUTINE SUB
```

11 X could be either an implicitly typed real variable or a variable obtained from the module MY_MODULE and
12 might change from one to the other because of changes in MY_MODULE unrelated to the action performed by
13 SUB. Logic errors resulting from this kind of situation can be extremely difficult to locate. Thus, the use of these
14 features together is discouraged.

15 C.8.2.2 Accessibility attributes (5.5.2)

16 1 The [PUBLIC](#) and [PRIVATE](#) attributes, which can be declared only in modules, divide the entities in a module
17 into those that are actually relevant to a [scoping unit](#) referencing the module and those that are not. This
18 information might be used to improve the performance of a Fortran processor. For example, it might be possible
19 to discard much of the information about the private entities once a module has been translated, thus saving on
20 both storage and the time to search it. Similarly, it might be possible to recognize that two versions of a module
21 differ only in the private entities they contain and avoid retranslating [program units](#) that use that module when
22 switching from one version of the module to the other.

23 C.8.3 Examples of the use of modules (11.2.1)

24 C.8.3.1 Global data (11.2.1)

25 1 A module could contain only data objects, for example:

```
26        MODULE DATA_MODULE
27            SAVE
28            REAL A (10), B, C (20,20)
29            INTEGER :: I=0
30            INTEGER, PARAMETER :: J=10
31            COMPLEX D (J,J)
32        END MODULE DATA_MODULE
```

33 2 Data objects made global in this manner can have any combination of data types.

34 3 Access to some of these can be made by a [USE statement](#) with the [ONLY](#) option, such as:

```
35        USE DATA_MODULE, ONLY: A, B, D
```

36 and access to all of them can be made by the following [USE statement](#):

```
37        USE DATA_MODULE
```

1 4 Access to all of them with some renaming to avoid name conflicts can be made by, for example:

```
2     USE DATA_MODULE, AMODULE => A, DMODULE => D
```

3 C.8.3.2 Derived types (11.2.1)

4 1 A derived type can be defined in a module and accessed in a number of [program units](#). For example,

```
5     MODULE SPARSE
6         TYPE NONZERO
7             REAL A
8             INTEGER I, J
9         END TYPE NONZERO
10    END MODULE SPARSE
```

11 defines a type consisting of a real component and two integer components for holding the numerical value of a
12 nonzero matrix element and its row and column indices.

13 C.8.3.3 Global allocatable arrays (11.2.1)

14 1 Many programs need large global allocatable arrays whose sizes are not known before program execution. A
15 simple form for such a program is:

```
16     PROGRAM GLOBAL_WORK
17         CALL CONFIGURE_ARRAYS      ! Perform the appropriate allocations
18         CALL COMPUTE              ! Use the arrays in computations
19     END PROGRAM GLOBAL_WORK
20     MODULE WORK_ARRAYS           ! An example set of work arrays
21         INTEGER N
22         REAL, ALLOCATABLE :: A (:), B (:, :), C (:, :, :)
23     END MODULE WORK_ARRAYS
24     SUBROUTINE CONFIGURE_ARRAYS  ! Process to set up work arrays
25         USE WORK_ARRAYS
26         READ (*, *) N
27         ALLOCATE (A (N), B (N, N), C (N, N, 2 * N))
28     END SUBROUTINE CONFIGURE_ARRAYS
29     SUBROUTINE COMPUTE
30         USE WORK_ARRAYS
31         ... ! Computations involving arrays A, B, and C
32     END SUBROUTINE COMPUTE
```

33 2 Typically, many subprograms need access to the work arrays, and all such subprograms would contain the
34 statement

```
35     USE WORK_ARRAYS
```

36 C.8.3.4 Procedure libraries (11.2.2)

37 1 [Interface bodies](#) for [external procedures](#) in a library can be gathered into a module. An [interface body](#) specifies
38 an [explicit interface](#) (12.4.2.2).

1 2 An example is the following library module:

```

2      MODULE LIBRARY_LLS
3          INTERFACE
4              SUBROUTINE LLS (X, A, F, FLAG)
5                  REAL X (:, :)
6                  ! The SIZE in the next statement is an intrinsic function
7                  REAL, DIMENSION (SIZE (X, 2)) :: A, F
8                  INTEGER FLAG
9              END SUBROUTINE LLS
10             ...
11         END INTERFACE
12         ...
13     END MODULE LIBRARY_LLS

```

14 3 This module provides an [explicit interface](#) that is necessary for the subroutine LLS to be invoked. for example:

```

15         USE LIBRARY_LLS
16         ...
17         CALL LLS (X = ABC, A = D, F = XX, FLAG = IFLAG)
18         ...

```

19 4 Because [dummy argument](#) names in an [interface body](#) for an [external procedure](#) are not required to be the same as in the procedure definition, different versions can be constructed for different applications using [argument keywords](#) appropriate to each application.

22 C.8.3.5 Operator extensions (11.2.2)

23 1 In order to extend an intrinsic operator symbol to have an additional meaning, an [interface block](#) specifying that operator symbol in the [OPERATOR](#) option of the [INTERFACE statement](#) could be placed in a module.

25 2 For example, // can be extended to perform concatenation of two derived-type objects serving as varying length character strings and + can be extended to specify matrix addition for type MATRIX or interval arithmetic addition for type INTERVAL.

28 3 A module might contain several such [interface blocks](#). An operator can be defined by an external function (either in Fortran or some other language) and its procedure [interface](#) placed in the module.

30 C.8.3.6 Data abstraction (11.2.2)

31 1 In addition to providing a portable means of avoiding the redundant specification of information in multiple [program units](#), a module provides a convenient means of “packaging” related entities, such as the definitions of the representation and operations of an abstract data type. The following example of a module defines a data abstraction for a SET type where the elements of each set are of type integer. The usual set operations of UNION, INTERSECTION, and DIFFERENCE are provided. The CARDINALITY function returns the cardinality of (number of elements in) its set argument. Two functions returning logical values are included, ELEMENT and SUBSET. ELEMENT defines the operator .IN. and SUBSET extends the operator <=. ELEMENT determines if a given scalar integer value is an element of a given set, and SUBSET determines if a given set is a subset of

1 another given set. (Two sets can be checked for equality by comparing cardinality and checking that one is a
2 subset of the other, or checking to see if each is a subset of the other.)

3 2 The transfer function SETF converts a vector of integer values to the corresponding set, with duplicate values
4 removed. Thus, a vector of constant values can be used as set constants. An inverse transfer function VECTOR
5 returns the elements of a set as a vector of values in ascending order. In this SET implementation, set data
6 objects have a maximum cardinality of 200.

7 3 Here is the example module:

```

8     MODULE INTEGER_SETS
9         ! This module is intended to illustrate use of the module facility
10        ! to define a new type, along with suitable operators.
11
12        INTEGER, PARAMETER :: MAX_SET_CARD = 200
13
14        TYPE SET                                ! Define SET type
15            PRIVATE
16            INTEGER CARD
17            INTEGER ELEMENT (MAX_SET_CARD)
18        END TYPE SET
19
20        INTERFACE OPERATOR (.IN.)
21            MODULE PROCEDURE ELEMENT
22        END INTERFACE OPERATOR (.IN.)
23
24        INTERFACE OPERATOR (<=)
25            MODULE PROCEDURE SUBSET
26        END INTERFACE OPERATOR (<=)
27
28        INTERFACE OPERATOR (+)
29            MODULE PROCEDURE UNION
30        END INTERFACE OPERATOR (+)
31
32        INTERFACE OPERATOR (-)
33            MODULE PROCEDURE DIFFERENCE
34        END INTERFACE OPERATOR (-)
35
36        INTERFACE OPERATOR (*)
37            MODULE PROCEDURE INTERSECTION
38        END INTERFACE OPERATOR (*)
39
40        CONTAINS
41
42        INTEGER FUNCTION CARDINALITY (A)        ! Returns cardinality of set A
43            TYPE (SET), INTENT (IN) :: A
44            CARDINALITY = A % CARD
45        END FUNCTION CARDINALITY

```



```

1
2     LOGICAL FUNCTION ELEMENT (X, A)           ! Determines if
3         INTEGER, INTENT(IN) :: X           ! element X is in set A
4         TYPE (SET), INTENT(IN) :: A
5         ELEMENT = ANY (A % ELEMENT (1 : A % CARD) == X)
6     END FUNCTION ELEMENT
7
8     FUNCTION UNION (A, B)                     ! Union of sets A and B
9         TYPE (SET) UNION
10        TYPE (SET), INTENT(IN) :: A, B
11        INTEGER J
12        UNION = A
13        DO J = 1, B % CARD
14            IF (.NOT. (B % ELEMENT (J) .IN. A)) THEN
15                IF (UNION % CARD < MAX_SET_CARD) THEN
16                    UNION % CARD = UNION % CARD + 1
17                    UNION % ELEMENT (UNION % CARD) = B % ELEMENT (J)
18                ELSE
19                    ! Maximum set size exceeded . . .
20                END IF
21            END IF
22        END DO
23    END FUNCTION UNION
24
25    FUNCTION DIFFERENCE (A, B)                 ! Difference of sets A and B
26        TYPE (SET) DIFFERENCE
27        TYPE (SET), INTENT(IN) :: A, B
28        INTEGER J, X
29        DIFFERENCE % CARD = 0                 ! The empty set
30        DO J = 1, A % CARD
31            X = A % ELEMENT (J)
32            IF (.NOT. (X .IN. B)) DIFFERENCE = DIFFERENCE + SET (1, X)
33        END DO
34    END FUNCTION DIFFERENCE
35
36    FUNCTION INTERSECTION (A, B)              ! Intersection of sets A and B
37        TYPE (SET) INTERSECTION
38        TYPE (SET), INTENT(IN) :: A, B
39        INTERSECTION = A - (A - B)
40    END FUNCTION INTERSECTION
41
42    LOGICAL FUNCTION SUBSET (A, B)            ! Determines if set A is
43        TYPE (SET), INTENT(IN) :: A, B      ! a subset of set B
44        INTEGER I
45        SUBSET = A % CARD <= B % CARD
46        IF (.NOT. SUBSET) RETURN             ! For efficiency

```

```

1      DO I = 1, A % CARD
2          SUBSET = SUBSET .AND. (A % ELEMENT (I) .IN. B)
3      END DO
4  END FUNCTION SUBSET
5
6  TYPE (SET) FUNCTION SETF (V)      ! Transfer function between a vector
7      INTEGER V (:)                ! of elements and a set of elements
8      INTEGER J                    ! removing duplicate elements
9      SETF % CARD = 0
10     DO J = 1, SIZE (V)
11         IF (.NOT. (V (J) .IN. SETF)) THEN
12             IF (SETF % CARD < MAX_SET_CARD) THEN
13                 SETF % CARD = SETF % CARD + 1
14                 SETF % ELEMENT (SETF % CARD) = V (J)
15             ELSE
16                 ! Maximum set size exceeded . . .
17             END IF
18         END IF
19     END DO
20 END FUNCTION SETF
21
22 FUNCTION VECTOR (A)              ! Transfer the values of set A
23     TYPE (SET), INTENT (IN) :: A ! into a vector in ascending order
24     INTEGER, POINTER :: VECTOR (:)
25     INTEGER I, J, K
26     ALLOCATE (VECTOR (A % CARD))
27     VECTOR = A % ELEMENT (1 : A % CARD)
28     DO I = 1, A % CARD - 1        ! Use a better sort if
29         DO J = I + 1, A % CARD    ! A % CARD is large
30             IF (VECTOR (I) > VECTOR (J)) THEN
31                 K = VECTOR (J); VECTOR (J) = VECTOR (I); VECTOR (I) = K
32             END IF
33         END DO
34     END DO
35 END FUNCTION VECTOR
36
37 END MODULE INTEGER_SETS

```

38 4 Examples of using INTEGER_SETS (A, B, and C are variables of type SET; X is an integer variable):

```

39     ! Check to see if A has more than 10 elements
40     IF (CARDINALITY (A) > 10) ...
41
42     ! Check for X an element of A but not of B
43     IF (X .IN. (A - B)) ...
44
45     ! C is the union of A and the result of B intersected

```

```

1         ! with the integers 1 to 100
2         C = A + B * SETF ([[I, I = 1, 100]])
3
4         ! Does A have any even numbers in the range 1:100?
5         IF (CARDINALITY (A * SETF ([[I, I = 2, 100, 2]])) > 0) ...
6
7         PRINT *, VECTOR (B) ! Print out the elements of set B, in ascending order

```

8 C.8.3.7 Public entities renamed (11.2.2)

- 9 1 At times it might be necessary to rename entities that are accessed with [USE statements](#).
- 10 2 The following example illustrates renaming features of the [USE statement](#).

```

11         MODULE J; REAL JX, JY, JZ; END MODULE J
12         MODULE K
13             USE J, ONLY : KX => JX, KY => JY
14             ! KX and KY are local names to module K
15             REAL KZ          ! KZ is local name to module K
16             REAL JZ          ! JZ is local name to module K
17         END MODULE K
18         PROGRAM RENAME
19             USE J; USE K
20             ! Module J's entity JX is accessible under names JX and KX
21             ! Module J's entity JY is accessible under names JY and KY
22             ! Module K's entity KZ is accessible under name KZ
23             ! Module J's entity JZ and K's entity JZ are different entities
24             ! and cannot be referenced
25             ...
26         END PROGRAM RENAME

```

27 C.8.4 Modules with submodules (11.2.3)

- 28 1 Each submodule specifies that it is the child of exactly one parent module or submodule. Therefore, a module and all of its descendant submodules stand in a tree-like relationship one to another.
- 30 2 A separate module procedure that is declared in a module to have public accessibility can be accessed by use association even if it is defined in a submodule. No other entity in a submodule can be accessed by use association. Each [program unit](#) that references a module by use association depends on it, and each submodule depends on its ancestor module. Therefore, if one changes a separate module procedure body in a submodule but does not change its corresponding module procedure interface, a tool for automatic program translation would not need to reprocess [program units](#) that reference the module by use association. This is so even if the tool exploits the relative modification times of files as opposed to comparing the result of translating the module to the result of a previous translation.
- 38 3 By constructing taller trees, one can put entities at intermediate levels that are shared by submodules at lower levels; changing these entities cannot change the interpretation of anything that is accessible from the module by use association. Developers of modules that embody large complicated concepts can exploit this possibility

1 to organize components of the concept into submodules, while preserving the privacy of entities that are shared
 2 by the submodules and that ought not to be exposed to users of the module. Putting these shared entities at an
 3 intermediate level also prevents cascades of reprocessing and testing if some of them are changed.

4 4 The following example illustrates a module, `color_points`, with a submodule, `color_points_a`, that in turn has
 5 a submodule, `color_points_b`. Public entities declared within `color_points` can be accessed by use association.
 6 The submodules `color_points_a` and `color_points_b` can be changed without causing retranslation of [program](#)
 7 [units](#) that reference the module `color_points`.

8 5 The module `color_points` does not have a [module-subprogram-part](#), but a [module-subprogram-part](#) is not pro-
 9 hibited. The module could be published as definitive specification of the interface, without revealing trade secrets
 10 contained within `color_points_a` or `color_points_b`. Of course, a similar module without the module prefix in
 11 the interface bodies would serve equally well as documentation – but the procedures would be [external procedures](#).
 12 It would make little difference to the consumer, but the developer would forfeit all of the advantages of modules.

```

13     module color_points
14
15         type color_point
16             private
17                 real :: x, y
18                 integer :: color
19         end type color_point
20
21         interface                ! Interfaces for procedures with separate
22                                 ! bodies in the submodule color_points_a
23             module subroutine color_point_del ( p ) ! Destroy a color_point object
24                 type(color_point), allocatable :: p
25             end subroutine color_point_del
26             ! Distance between two color_point objects
27             real module function color_point_dist ( a, b )
28                 type(color_point), intent(in) :: a, b
29             end function color_point_dist
30             module subroutine color_point_draw ( p ) ! Draw a color_point object
31                 type(color_point), intent(in) :: p
32             end subroutine color_point_draw
33             module subroutine color_point_new ( p ) ! Create a color_point object
34                 type(color_point), allocatable :: p
35             end subroutine color_point_new
36         end interface
37
38     end module color_points
  
```

39 6 The only entities within `color_points_a` that can be accessed by use association are the separate module
 40 procedures that were declared in `color_points`. If the procedures are changed but their interfaces are not, the
 41 interface from [program units](#) that access them by use association is unchanged. If the module and submodule are
 42 in separate files, utilities that examine the time of modification of a file would notice that changes in the module
 43 could affect the translation of its submodules or of [program units](#) that reference the module by use association,

1 but that changes in submodules could not affect the translation of the parent module or [program units](#) that
2 reference it by use association.

3 7 The variable `instance_count` in the following example is not accessible by use association of `color_points`, but
4 is accessible within `color_points_a`, and its submodules.

```

5     submodule ( color_points ) color_points_a ! Submodule of color_points
6
7     integer :: instance_count = 0
8
9     interface
10         ! Interface for a procedure with a separate
11         ! body in submodule color_points_b
12     module subroutine inquire_palette ( pt, pal )
13         use palette_stuff      ! palette_stuff, especially submodules
14         ! thereof, can reference color_points by use
15         ! association without causing a circular
16         ! dependence during translation because this
17         ! use is not in the module. Furthermore,
18         ! changes in the module palette_stuff do not
19         ! affect the translation of color_points.
20         type(color_point), intent(in) :: pt
21         type(palette), intent(out) :: pal
22     end subroutine inquire_palette
23
24     end interface
25
26     contains ! Invisible bodies for public separate module procedures
27         ! declared in the module
28
29     module subroutine color_point_del ( p )
30         type(color_point), allocatable :: p
31         instance_count = instance_count - 1
32         deallocate ( p )
33     end subroutine color_point_del
34
35     real module function color_point_dist ( a, b ) result ( dist )
36         type(color_point), intent(in) :: a, b
37         dist = sqrt( (b%x - a%x)**2 + (b%y - a%y)**2 )
38     end function color_point_dist
39
40     module subroutine color_point_new ( p )
41         type(color_point), allocatable :: p
42         instance_count = instance_count + 1
43         allocate ( p )
44     end subroutine color_point_new
45
46     end submodule color_points_a

```

47 8 The subroutine `inquire_palette` is accessible within `color_points_a` because its interface is declared therein.

1 It is not, however, accessible by use association, because its interface is not declared in the module, `color_points`.
 2 Since the interface is not declared in the module, changes in the interface cannot affect the translation of `program`
 3 `units` that reference the module by use association.

```

4     module palette_stuff
5         type :: palette ; ... ; end type palette
6     contains
7         subroutine test_palette ( p )
8             ! Draw a color wheel using procedures from the color_points module
9             use color_points ! This does not cause a circular dependency because
10                ! the "use palette_stuff" that is logically within
11                ! color_points is in the color_points_a submodule.
12             type(palette), intent(in) :: p
13             ...
14         end subroutine test_palette
15     end module palette_stuff

16
17     submodule ( color_points:color_points_a ) color_points_b ! Subsidiary**2 submodule
18
19     contains
20         ! Invisible body for interface declared in the ancestor module
21         module subroutine color_point_draw ( p )
22             use palette_stuff, only: palette
23             type(color_point), intent(in) :: p
24             type(palette) :: MyPalette
25             ...; call inquire_palette ( p, MyPalette ); ...
26         end subroutine color_point_draw
27
28         ! Invisible body for interface declared in the parent submodule
29         module procedure inquire_palette
30             ... implementation of inquire_palette
31         end procedure inquire_palette
32
33         subroutine private_stuff ! not accessible from color_points_a
34             ...
35         end subroutine private_stuff
36
37     end submodule color_points_b
  
```

38 9 There is a `use palette_stuff` in `color_points_a`, and a `use color_points` in `palette_stuff`. The `use`
 39 `palette_stuff` would cause a circular reference if it appeared in `color_points`. In this case, it does not cause
 40 a circular dependence because it is in a submodule. Submodules cannot be referenced by use association, and
 41 therefore what would be a circular appearance of `use palette_stuff` is not accessed.

```

42     program main
43         use color_points
44         ! "instance_count" and "inquire_palette" are not accessible here
  
```

```

1      ! because they are not declared in the "color_points" module.
2      ! "color_points_a" and "color_points_b" cannot be referenced by
3      ! use association.
4      interface draw                ! just to demonstrate it's possible
5          module procedure color_point_draw
6      end interface
7      type(color_point) :: C_1, C_2
8      real :: RC
9      ...
10     call color_point_new (c_1)    ! body in color_points_a, interface in color_points
11     ...
12     call draw (c_1)              ! body in color_points_b, specific interface
13                                 ! in color_points, generic interface here.
14     ...
15     rc = color_point_dist (c_1, c_2) ! body in color_points_a, interface in color_points
16     ...
17     call color_point_del (c_1)    ! body in color_points_a, interface in color_points
18     ...
19 end program main

```

20 10 A multilevel submodule system can be used to package and organize a large and interconnected concept without
 21 exposing entities of one subsystem to other subsystems.

22 11 Consider a **Plasma** module from a Tokamak simulator. A plasma simulation requires attention at least to fluid
 23 flow, thermodynamics, and electromagnetism. Fluid flow simulation requires simulation of subsonic, supersonic,
 24 and hypersonic flow. This problem decomposition can be reflected in the submodule structure of the **Plasma**
 25 module:

Plasma module				
Flow submodule			Thermal submodule	Electromagnetics submodule
Subsonic submodule	Supersonic submodule	Hypersonic submodule		

27 12 Entities can be shared among the **Subsonic**, **Supersonic**, and **Hypersonic** submodules by putting them within
 28 the **Flow** submodule. One then need not worry about accidental use of these entities by use association or by the
 29 **Thermal** or **Electromagnetics** submodules, or the development of a dependency of correct operation of those
 30 subsystems upon the representation of entities of the **Flow** subsystem as a consequence of maintenance. Since
 31 these entities are not accessible by use association, if any of them are changed, the new values cannot be accessed
 32 in **program units** that reference the **Plasma** module by use association; the answer to the question “where are
 33 these entities used” is therefore confined to the set of descendant submodules of the **Flow** submodule.

1 C.9 Clause 12 notes

2 C.9.1 Portability problems with external procedures (12.4.3.6)

- 3 1 There is a potential portability problem in a [scoping unit](#) that references an [external procedure](#) without explicitly
 4 declaring it to have the [EXTERNAL attribute](#) (5.5.9). On a different processor, the name of that procedure might
 5 be the name of a [nonstandard intrinsic](#) procedure and in such a case the processor would interpret those procedure
 6 references as references to that intrinsic procedure. (On that processor, the program would also be viewed as
 7 not conforming to this part of ISO/IEC 1539 because of the references to the [nonstandard intrinsic](#) procedure.)
 8 Declaration of the [EXTERNAL attribute](#) causes the references to be to the [external procedure](#) regardless of the
 9 availability of an intrinsic procedure with the same name. Note that declaration of the type of a procedure is not
 10 enough to make it [external](#), even if the type is inconsistent with the type of the result of an intrinsic procedure
 11 of the same name.

12 C.9.2 Procedures defined by means other than Fortran (12.6.3)

- 13 1 A processor is not required to provide any means other than Fortran for defining [external procedures](#). Among the
 14 means that might be supported are the machine assembly language, other high level languages, the Fortran lan-
 15 guage extended with nonstandard features, and the Fortran language as supported by another Fortran processor
 16 (for example, a previously existing FORTRAN 77 processor). The means other than Fortran for defining [external](#)
 17 [procedures](#), including any restrictions on the structure for organization of those procedures, are not specified by
 18 this part of ISO/IEC 1539.
- 19 2 A Fortran processor might limit its support of procedures defined by means other than Fortran such that these
 20 procedures can affect entities in the Fortran environment only on the same basis as procedures written in Fortran.
 21 For example, it might not support the value of a local variable from being changed by a procedure reference unless
 22 that variable were one of the arguments to the procedure.

23 C.9.3 Abstract interfaces and procedure pointer components (12.4, 4.5)

- 24 1 This is an example of a library module providing lists of callbacks that the user can register and invoke.

```

25     MODULE callback_list_module
26         !
27         ! Type for users to extend with their own data, if they so desire
28         !
29         TYPE callback_data
30     END TYPE
31     !
32     ! Abstract interface for the callback procedures
33     !
34     ABSTRACT INTERFACE
35         SUBROUTINE callback_procedure(data)
36             IMPORT callback_data
37             CLASS(callback_data),OPTIONAL :: data
38         END SUBROUTINE
39     END INTERFACE
40     !
  
```



```

1      ! The callback list type.
2      !
3      TYPE callback_list
4          PRIVATE
5          CLASS(callback_record),POINTER :: first => NULL()
6      END TYPE
7      !
8      ! Internal: each callback registration creates one of these
9      !
10     TYPE,PRIVATE :: callback_record
11         PROCEDURE(callback_procedure),POINTER,NOPASS :: proc
12         CLASS(callback_record),POINTER :: next
13         CLASS(callback_data),POINTER :: data => NULL();
14     END TYPE
15     PRIVATE invoke,forward_invoke
16 CONTAINS
17     !
18     ! Register a callback procedure with optional data
19     !
20     SUBROUTINE register_callback(list, entry, data)
21         TYPE(callback_list),INTENT(INOUT) :: list
22         PROCEDURE(callback_procedure) :: entry
23         CLASS(callback_data),OPTIONAL :: data
24         TYPE(callback_record),POINTER :: new,last
25         ALLOCATE(new)
26         new%proc => entry
27         IF (PRESENT(data)) ALLOCATE(new%data,SOURCE=data)
28         new%next => list%first
29         list%first => new
30     END SUBROUTINE
31     !
32     ! Internal: Invoke a single callback and destroy its record
33     !
34     SUBROUTINE invoke(callback)
35         TYPE(callback_record),POINTER :: callback
36         IF (ASSOCIATED(callback%data) THEN
37             CALL callback%proc(list%first%data)
38             DEALLOCATE(callback%data)
39         ELSE
40             CALL callback%proc
41         END IF
42         DEALLOCATE(callback)
43     END SUBROUTINE
44     !
45     ! Call the procedures in reverse order of registration
46     !

```

```

1      SUBROUTINE invoke_callback_reverse(list)
2          TYPE(callback_list),INTENT(INOUT) :: list
3          TYPE(callback_record),POINTER :: next,current
4          current => list%first
5          NULLIFY(list%first)
6          DO WHILE (ASSOCIATED(current))
7              next => current%next
8              CALL invoke(current)
9              current => next
10         END DO
11     END SUBROUTINE
12     !
13     ! Internal: Forward mode invocation
14     !
15     SUBROUTINE forward_invoke(callback)
16         IF (ASSOCIATED(callback%next)) CALL forward_invoke(callback%next)
17         CALL invoke(callback)
18     END SUBROUTINE
19     !
20     ! Call the procedures in forward order of registration
21     !
22     SUBROUTINE invoke_callback_forward(list)
23         TYPE(callback_list),INTENT(INOUT) :: list
24         IF (ASSOCIATED(list%first)) CALL forward_invoke(list%first)
25     END SUBROUTINE
26 END

```

27 C.9.4 Pointers and targets as arguments (12.5.2.4, 12.5.2.6, 12.5.2.7)

28 1 If a dummy argument is declared to be a pointer the corresponding **actual argument** could be a pointer, or could
29 be a nonpointer variable. Consider the two cases separately.

30 *Case (i):* The **actual argument** is a pointer. When procedure execution commences the pointer association
31 status of the dummy argument becomes the same as that of the **actual argument**. If the pointer
32 association status of the dummy argument is changed, the pointer association status of the **actual**
33 **argument** changes in the same way.

34 *Case (ii):* The **actual argument** is not a pointer. This only occurs when the **actual argument** has the **TARGET**
35 **attribute** and the dummy argument has the **INTENT (IN) attribute**. The dummy argument becomes
36 pointer associated with the **actual argument**.

37 2 When execution of a procedure completes, any pointer that remains defined and that is associated with a dummy
38 argument that has the **TARGET attribute** and is either a scalar or an **assumed-shape array**, remains associated
39 with the corresponding **actual argument** if the **actual argument** has the **TARGET attribute** and is not an array
40 section with a **vector subscript**.

41 3 For example, consider:

```
42     REAL, POINTER      :: PBEST
```

```

1      REAL, TARGET      :: B (10000)
2      CALL BEST (PBEST, B)          ! Upon return PBEST is associated
3      ...                          ! with the 'best' element of B
4      CONTAINS
5          SUBROUTINE BEST (P, A)
6              REAL, POINTER, INTENT (OUT)  :: P
7              REAL, TARGET, INTENT (IN)    :: A (:)
8              ...                          ! Find the 'best' element A(I)
9              P => A (I)
10             RETURN
11         END SUBROUTINE BEST
12     END

```

13 When procedure BEST completes, the pointer PBEST is associated with an element of B.

14 4 An [actual argument](#) without the [TARGET attribute](#) can become associated with a dummy argument with the
15 [TARGET attribute](#). This enables a pointer to become associated with the dummy argument during execution of
16 the procedure that contains the dummy argument. For example:

```

17     INTEGER LARGE(100,100)
18     CALL SUB (LARGE)
19     ...
20     CALL SUB ()
21     CONTAINS
22         SUBROUTINE SUB(ARG)
23             INTEGER, TARGET, OPTIONAL :: ARG(100,100)
24             INTEGER, POINTER, DIMENSION(:,:) :: PARG
25             IF (PRESENT(ARG)) THEN
26                 PARG => ARG
27             ELSE
28                 ALLOCATE (PARG(100,100))
29                 PARG = 0
30             ENDIF
31             ... ! Code with lots of references to PARG
32             IF (.NOT. PRESENT(ARG)) DEALLOCATE(PARG)
33         END SUBROUTINE SUB
34     END

```

35 Within subroutine SUB the pointer PARG is either associated with the dummy argument ARG or it is associated
36 with an allocated target. The bulk of the code can reference PARG without further calls to the intrinsic function
37 [PRESENT](#).

38 5 If a nonpointer dummy argument has the [TARGET attribute](#) and the corresponding [actual argument](#) does not,
39 any pointers that become associated with the dummy argument, and therefore with the [actual argument](#), during
40 execution of the procedure, become undefined when execution of the procedure completes.

1 C.9.5 Polymorphic Argument Association (12.5.2.9)

- 2 1 The following example illustrates the polymorphic [argument association](#) rules using the derived types defined in
3 Note [4.55](#).

```

4     TYPE(POINT) :: T2
5     TYPE(COLOR_POINT) :: T3
6     CLASS(POINT) :: P2
7     CLASS(COLOR_POINT) :: P3
8     ! Dummy argument is polymorphic and actual argument is of fixed type
9     SUBROUTINE SUB2 ( X2 ); CLASS(POINT) :: X2; ...
10    SUBROUTINE SUB3 ( X3 ); CLASS(COLOR_POINT) :: X3; ...
11
12    CALL SUB2 ( T2 ) ! Valid -- The declared type of T2 is the same as the
13                    !           declared type of X2.
14    CALL SUB2 ( T3 ) ! Valid -- The declared type of T3 is extended from
15                    !           the declared type of X2.
16    CALL SUB3 ( T2 ) ! Invalid -- The declared type of T2 is neither the
17                    !           same as nor extended from the declared type
18                    !           type of X3.
19    CALL SUB3 ( T3 ) ! Valid -- The declared type of T3 is the same as the
20                    !           declared type of X3.
21    ! Actual argument is polymorphic and dummy argument is of fixed type
22    SUBROUTINE TUB2 ( D2 ); TYPE(POINT) :: D2; ...
23    SUBROUTINE TUB3 ( D3 ); TYPE(COLOR_POINT) :: D3; ...
24
25    CALL TUB2 ( P2 ) ! Valid -- The declared type of P2 is the same as the
26                    !           declared type of D2.
27    CALL TUB2 ( P3 ) ! Invalid -- The declared type of P3 differs from the
28                    !           declared type of D2.
29    CALL TUB2 ( P3%POINT ) ! Valid alternative to the above
30    CALL TUB3 ( P2 ) ! Invalid -- The declared type of P2 differs from the
31                    !           declared type of D3.
32    SELECT TYPE ( P2 ) ! Valid conditional alternative to the above
33    CLASS IS ( COLOR_POINT ) ! Works if the dynamic type of P2 is the same
34        CALL TUB3 ( P2 )     ! as the declared type of D3, or a type
35                               ! extended therefrom.
36    CLASS DEFAULT
37                               ! Cannot work if not.
38    END SELECT
39    CALL TUB3 ( P3 ) ! Valid -- The declared type of P3 is the same as the
40                    !           declared type of D3.
41    ! Both the actual and dummy arguments are of polymorphic type.
42    CALL SUB2 ( P2 ) ! Valid -- The declared type of P2 is the same as the
43                    !           declared type of X2.
44    CALL SUB2 ( P3 ) ! Valid -- The declared type of P3 is extended from
45                    !           the declared type of X2.

```

```

1      CALL SUB3 ( P2 ) ! Invalid -- The declared type of P2 is neither the
2          !           same as nor extended from the declared
3          !           type of X3.
4      SELECT TYPE ( P2 ) ! Valid conditional alternative to the above
5      CLASS IS ( COLOR_POINT ) ! Works if the dynamic type of P2 is the
6          CALL SUB3 ( P2 )     ! same as the declared type of X3, or a
7          ! type extended therefrom.
8      CLASS DEFAULT
9          ! Cannot work if not.
10     END SELECT
11     CALL SUB3 ( P3 ) ! Valid -- The declared type of P3 is the same as the
12         !           declared type of X3.

```

13 C.9.6 Rules ensuring unambiguous generics (12.4.3.5.5)

14 1 The rules in 12.4.3.5.5 are intended to ensure

- 15 • that it is possible to reference each specific procedure or binding in the generic collection,
- 16 • that for any valid generic procedure reference, the determination of the specific procedure referenced is unambiguous, and
- 17 • that the determination of the specific procedure or binding referenced can be made before execution of the program begins (during compilation).

20 2 Interfaces of specific procedures or bindings are distinguished by fixed properties of their arguments, specifically type, kind type parameters, [rank](#), and whether the dummy argument has the [POINTER](#) or [ALLOCATABLE](#) attribute. A valid reference to one procedure in a generic collection will differ from another because it has an argument that the other cannot accept, because it is missing an argument that the other requires, or because one of these fixed properties is different.

25 3 Although the declared type of a data entity is a fixed property, polymorphic variables allow for a limited degree of type mismatch between dummy arguments and [actual arguments](#), so the requirement for distinguishing two dummy arguments is type incompatibility, not merely different types. (This is illustrated in the [BAD6](#) example later in this note.)

29 4 That same limited type mismatch means that two dummy arguments that are not type incompatible can be distinguished on the basis of the values of the kind type parameters they have in common; if one of them has a kind type parameter that the other does not, that is irrelevant in distinguishing them.

32 5 [Rank](#) is a fixed property, but some forms of array dummy arguments allow [rank](#) mismatches when a procedure is referenced by its specific name. In order to allow [rank](#) to always be usable in distinguishing generics, such [rank](#) mismatches are disallowed for those arguments when the procedure is referenced as part of a generic. Additionally, the fact that elemental procedures can accept array arguments is not taken into account when applying these rules, so apparent ambiguity between elemental and nonelemental procedures is possible; in such cases, the reference is interpreted as being to the nonelemental procedure.

38 6 For procedures referenced as operators or defined-assignment, syntactically distinguished arguments are mapped to specific positions in the argument list, so the rule for distinguishing such procedures is that it be possible to distinguish the arguments at one of the argument positions.

1 7 For [defined input/output](#) procedures, only the `dtv` argument corresponds to something explicitly written in the
 2 program, so it is the `dtv` that is required to be distinguished. Because `dtv` arguments are required to be scalar,
 3 they cannot differ in [rank](#). Thus this rule effectively involves only type and kind type parameters.

4 8 For generic procedure names, the rules are more complicated because optional arguments can be omitted and
 5 because arguments can be specified either positionally or by name.

6 9 In the special case of type-bound procedures with [passed-object dummy arguments](#), the passed-object argument
 7 is syntactically distinguished in the reference, so rule (3) in [12.4.3.5.5](#) can be applied. The type of passed-object
 8 arguments is constrained in ways that prevent passed-object arguments in the same [scoping unit](#) from being type
 9 incompatible. Thus this rule effectively involves only kind type parameters and [rank](#).

10 10 The primary means of distinguishing named generics is rule (4). The most common application of that rule is a
 11 single argument satisfying both (4a) and (4b):

```
12     INTERFACE GOOD1
13         FUNCTION F1A(X)
14             REAL :: F1A,X
15         END FUNCTION F1A
16         FUNCTION F1B(X)
17             INTEGER :: F1B,X
18         END FUNCTION F1B
19     END INTERFACE GOOD1
```

20 11 Whether one writes `GOOD1(1.0)` or `GOOD1(X=1.0)`, the reference is to `F1A` because `F1B` would require an integer
 21 argument whereas these references provide the real constant 1.0.

22 12 This example and those that follow are expressed using interface bodies, with type as the distinguishing property.
 23 This was done to make it easier to write and describe the examples. The principles being illustrated are equally
 24 applicable when the procedures get their explicit interfaces in some other way or when kind type parameters or
 25 [rank](#) are the distinguishing property.

26 13 Another common variant is the argument that satisfies (4a) and (4b) by being required in one specific and
 27 completely missing in the other:

```
28     INTERFACE GOOD2
29         FUNCTION F2A(X)
30             REAL :: F2A,X
31         END FUNCTION F2A
32         FUNCTION F2B(X,Y)
33             COMPLEX :: F2B
34             REAL :: X,Y
35         END FUNCTION F2B
36     END INTERFACE GOOD2
```

37 14 Whether one writes `GOOD2(0.0,1.0)`, `GOOD2(0.0,Y=1.0)`, or `GOOD2(Y=1.0,X=0.0)`, the reference is to `F2B`,
 38 because `F2A` has no argument in the second position or with the name `Y`. This approach is used as an alternative
 39 to optional arguments when one wants a function to have different result type, kind type parameters, or [rank](#),
 40 depending on whether the argument is present. In many of the intrinsic functions, the `DIM` argument works this
 41 way.

1 15 It is possible to construct cases where different arguments are used to distinguish positionally and by name:

```

2      INTERFACE GOOD3
3          SUBROUTINE S3A(W,X,Y,Z)
4              REAL :: W,Y
5              INTEGER :: X,Z
6          END SUBROUTINE S3A
7          SUBROUTINE S3B(X,W,Z,Y)
8              REAL :: W,Z
9              INTEGER :: X,Y
10         END SUBROUTINE S3B
11     END INTERFACE GOOD3

```

12 16 If one writes GOOD3(1.0,2,3.0,4) to reference S3A, then the third and fourth arguments are consistent with a
13 reference to S3B, but the first and second are not. If one switches to writing the first two arguments as keyword
14 arguments in order for them to be consistent with a reference to S3B, the latter two arguments must also be written
15 as keyword arguments, GOOD3(X=2,W=1.0,Z=4,Y=3.0), and the named arguments Y and Z are distinguished.

16 17 The ordering requirement in rule (4) is critical:

```

17     INTERFACE BAD4 ! this interface is invalid !
18         SUBROUTINE S4A(W,X,Y,Z)
19             REAL :: W,Y
20             INTEGER :: X,Z
21         END SUBROUTINE S4A
22         SUBROUTINE S4B(X,W,Z,Y)
23             REAL :: X,Y
24             INTEGER :: W,Z
25         END SUBROUTINE S4B
26     END INTERFACE BAD4

```

27 18 In this example, the positionally distinguished arguments are Y and Z, and it is W and X that are distinguished by
28 name. In this order it is possible to write BAD4(1.0,2,Y=3.0,Z=4), which is a valid reference for both S4A and
29 S4B.

30 19 Rule (1) can be used to distinguish some cases that are not covered by rule (4):

```

31     INTERFACE GOOD5
32         SUBROUTINE S5A(X)
33             REAL :: X
34         END SUBROUTINE S5A
35         SUBROUTINE S5B(Y,X)
36             REAL :: Y,X
37         END SUBROUTINE S5B
38     END INTERFACE GOOD5

```

39 20 In attempting to apply rule (4), position 2 and name Y are distinguished, but they are in the wrong order, just like
40 the BAD4 example. However, when we try to construct a similarly ambiguous reference, we get GOOD5(1.0,X=2.0),

1 which can't be a reference to S5A because it would be attempting to associate two different **actual arguments**
 2 with the dummy argument X. Rule (4) catches this case by recognizing that S5B requires two real arguments, and
 3 S5A cannot possibly accept more than one.

4 21 The application of rule (1) becomes more complicated when **extensible types** are involved. If FRUIT is an **extensible**
 5 **type**, PEAR and APPLE are **extensions** of FRUIT, and BOSCO is an **extension** of PEAR, then

```
6         INTERFACE BAD6 ! this interface is invalid !
7           SUBROUTINE S6A(X,Y)
8             CLASS(PEAR) :: X,Y
9           END SUBROUTINE S6A
10          SUBROUTINE S6B(X,Y)
11            CLASS(FRUIT) :: X
12            CLASS(BOSC) :: Y
13          END SUBROUTINE S6B
14        END INTERFACE BAD6
```

15 might, at first glance, seem distinguishable this way, but because of the limited type mismatching allowed,
 16 BAD6(A_PEAR,A_BOSC) is a valid reference to both S6A and S6B.

17 22 It is important to try rule (1) for each type that appears:

```
18        INTERFACE GOOD7
19          SUBROUTINE S7A(X,Y,Z)
20            CLASS(PEAR) :: X,Y,Z
21          END SUBROUTINE S7A
22          SUBROUTINE S7B(X,Z,W)
23            CLASS(FRUIT) :: X
24            CLASS(BOSC) :: Z
25            CLASS(APPLE),OPTIONAL :: W
26          END SUBROUTINE S7B
27        END INTERFACE GOOD7
```

28 23 Looking at the most general type, S7A has a minimum and maximum of 3 FRUIT arguments, while S7B has a
 29 minimum of 2 and a maximum of three. Looking at the most specific, S7A has a minimum of 0 and a maximum
 30 of 3 BOSCO arguments, while S7B has a minimum of 1 and a maximum of 2. However, when we look at the
 31 intermediate, S7A has a minimum and maximum of 3 PEAR arguments, while S7B has a minimum of 1 and a
 32 maximum of 2. Because S7A's minimum exceeds S7B's maximum, they can be distinguished.

33 24 In identifying the minimum number of arguments with a particular set of properties, we exclude optional argu-
 34 ments and test TKR compatibility, so the corresponding **actual arguments** are required to have those properties.
 35 In identifying the maximum number of arguments with those properties, we include the optional arguments and
 36 test not distinguishable, so we include **actual arguments** which could have those properties but are not required
 37 to have them.

38 25 These rules are sufficient to ensure that references to procedures that meet them are unambiguous, but there
 39 remain examples that fail to meet these rules but which can be shown to be unambiguous:

```
40 26        INTERFACE BAD8 ! this interface is invalid !
```



```

1           ! despite the fact that it is unambiguous !
2     SUBROUTINE S8A(X,Y,Z)
3         REAL,OPTIONAL :: X
4         INTEGER :: Y
5         REAL :: Z
6     END SUBROUTINE S8A
7     SUBROUTINE S8B(X,Z,Y)
8         INTEGER,OPTIONAL :: X
9         INTEGER :: Z
10        REAL :: Y
11    END SUBROUTINE S8B
12    END INTERFACE BAD8

```

13 27 This interface fails rule (4) because there are no required arguments that can be distinguished from the positionally
14 corresponding argument, but in order for the mismatch of the optional arguments not to be relevant, the later
15 arguments must be specified as keyword arguments, so distinguishing by name does the trick. This interface is
16 nevertheless invalid so a standard-conforming Fortran processor is not required to do such reasoning. The rules
17 to cover all cases are too complicated to be useful.

18 28 The real data objects that would be valid arguments for S9A are entirely disjoint from procedures that are valid
19 arguments to S9B and S9C, and the procedures that valid arguments for S9B are disjoint from the procedures
20 that are valid arguments to S9C because the former are required to accept real arguments and the latter in-
21 teger arguments. Again, this interface is invalid, so a standard-conforming Fortran processor need not examine
22 such properties when deciding whether a generic collection is valid. Again, the rules to cover all cases are too
23 complicated to be useful.

24 29 If one dummy argument has the [POINTER attribute](#) and a corresponding argument in the other interface body
25 has the [ALLOCATABLE attribute](#) the [generic interface](#) is not ambiguous. If one dummy argument has either the
26 [POINTER](#) or [ALLOCATABLE](#) attribute and a corresponding argument in the other interface body has neither
27 attribute, the [generic interface](#) might be ambiguous.

28 C.10 Clause 13 notes

29 C.10.1 Atomic memory consistency

30 C.10.1.1 Relaxed memory model

31 1 Parallel programs sometimes have apparently impossible behavior because data transfers and other messages can
32 be delayed, reordered and even repeated, by hardware, communication software, and caching and other forms of
33 optimization. Requiring processors to deliver globally consistent behavior is incompatible with performance on
34 many systems. This part of ISO/IEC 1539 specifies that all ordered actions will be consistent (2.3.5 and 8.5), but
35 all consistency between unordered segments is deliberately left processor dependent. Depending on the hardware,
36 this can be observed even when only two images and one mechanism are involved.

37 C.10.1.2 Examples with atomic operations

38 1 When variables are being referenced (atomically) from segments that are unordered with respect to the segment
39 that is atomically defining or redefining the variables, the results are processor dependent. This supports use

1 of so-called “relaxed memory model” architectures, which can enable more efficient execution on some hardware
2 implementations.

3 2 The following examples assume these declarations:

```
4     MODULE EXAMPLE
5     USE, INTRINSIC :: ISO_FORTRAN_ENV
6     INTEGER(ATOMIC_INT_KIND) :: X [*] = 0, Y [*] = 0
```

7 3 Example 1

8 4 With $X [j]$ and $Y [j]$ still in their initial state (both zero), image j executes the following sequence of statements:

```
9     CALL ATOMIC_DEFINE (X, 1)
10    CALL ATOMIC_DEFINE (Y, 1)
```

11 and a different image, k , executes the following sequence of statements:

```
12    DO
13    CALL ATOMIC_REF (TMP, Y [j])
14    IF (TMP==1) EXIT
15    END DO
16    CALL ATOMIC_REF (TMP, X [j])
17    PRINT *, TMP
```

18 5 The final value of TMP on image k can be either 0 or 1. That is, even though image j thinks that it defined $X [j]$
19 $[j]$ before it defined $Y [j]$, this ordering is not guaranteed to be observed on image k . There are many aspects of
20 hardware and software implementation that can cause this effect, but conceptually this example can be thought
21 of as the change in the value of Y propagating faster through the inter-image connections than the change in the
22 value of X .

23 6 Even if image j executed the sequence

```
24    CALL ATOMIC_DEFINE (X, 1)
25    SYNC MEMORY
26    CALL ATOMIC_DEFINE (Y, 1)
```

27 the same effect can be seen. That is because even though X and Y are defined in ordered segments, the references
28 from image k are both from a segment that is unordered with respect to image j .

29 7 Only if the reference on image k to $Y [j]$ is in a segment that is ordered after the segment on image j that defined
30 Y , will TMP be guaranteed to have the value 1.

31 8 Example 2:

32 With the initial state of X and Y on image j (i.e. $X [j]$ and $Y [j]$) still being zero, execution of

```
33    CALL ATOMIC_REF (TMP, X [j])
34    CALL ATOMIC_DEFINE (Y [j], 1)
35    PRINT *, TMP
```

36 on image k_1 , and execution of

```

1      CALL ATOMIC_REF (TMP, Y [j])
2      CALL ATOMIC_DEFINE (X [j], 1)
3      PRINT *, TMP

```

4 on image k_2 , in unordered segments, might print the value 1 both times.

5 9 This can happen by such mechanisms as “load buffering”; one might imagine that what is happening is that
6 the definitions (`ATOMIC_DEFINE`) are overtaking the references (`ATOMIC_REF`). On some processors it is
7 possible that insertion of `SYNC MEMORY` statements between the calls to `ATOMIC_REF` and `ATOMIC_-`
8 `DEFINE` might be sufficient to make the output print the value 1 at most one time (or even exactly one time),
9 but this is still processor dependent unless the `SYNC MEMORY` statement executions cause the relevant segments
10 on images k_1 and k_2 to be ordered.

11 C.10.2 EVENT_QUERY example

12 1 The following example illustrates the use of events via a program in which image 1 acts as the master image,
13 distributing work items to the other images. Only one work item at a time can be active on a worker image, and
14 each deals with the result (e.g. via input/output) without directly feeding data back to the master image.

15 2 Because the work items are not expected to be balanced, the master keeps cycling through all images to find one
16 that is waiting for work.

17 3 An event is posted by each worker to indicate that it has completed its work item. Since the corresponding
18 variables are needed only on the master, we place them in an allocatable array component of a coarray. An event
19 on each worker is needed for the master to post the fact that it has made a work item available for it.

20 Example code:

```

21      PROGRAM work_share
22          USE, INTRINSIC :: ISO_FORTRAN_ENV, ONLY: EVENT_TYPE
23          USE :: mod_work, ONLY:
24              work, & ! Module that creates work items
25              create_work_item, & ! Type for holding a work item
26              process_item, & ! Function that creates work item
27              work_done & ! Function that processes an item
28              ! Logical function that returns true
29              ! if all work has been done.
30
31          TYPE :: worker_type
32              TYPE (EVENT_TYPE), ALLOCATABLE :: free (:)
33          END TYPE
34
35          TYPE (EVENT_TYPE) :: submit [*] ! Post when work ready for a worker
36          TYPE (worker_type) :: worker [*] ! Post when worker is free
37          TYPE (work) :: work_item [*] ! Holds the data for a work item
38          INTEGER :: count, i, nbusy [*]
39
40          IF (THIS_IMAGE ()==1) THEN
41              ! Get started
42              ALLOCATE (worker%free (2:NUM_IMAGES ()))
43              nbusy = 0 ! This holds the number of workers working

```

```

1      DO i = 2, NUM_IMAGES () ! Start the workers working
2          IF (work_done ()) EXIT
3          nbusy = nbusy + 1
4          work_item [i] = create_work_item ()
5          EVENT POST (submit [i])
6      END DO
7      ! Main work distribution loop
8  master: DO
9      image: DO i = 2, NUM_IMAGES ()
10         CALL EVENT_QUERY (worker%free (i), count)
11         IF (count==0) CYCLE image ! Worker is not free
12         EVENT WAIT (worker%free (i))
13         nbusy = nbusy - 1
14         IF (work_done ()) CYCLE
15         nbusy = nbusy + 1
16         work_item [i] = create_work_item ()
17         EVENT POST (submit [i])
18     END DO image
19     IF (nbusy==0) THEN
20         ! All done. Exit on all images.
21         DO i = 2, NUM_IMAGES ()
22             EVENT POST (submit [i])
23         END DO
24         EXIT master
25     END IF
26 END DO master
27 ELSE
28     ! Work processing loop
29  worker: DO
30         EVENT WAIT (submit)
31         IF (nbusy[1] == 0) EXIT
32         CALL process_item (work_item)
33         EVENT POST (worker [1]%free (THIS_IMAGE ()))
34     END DO worker
35 END IF
36 END PROGRAM work_share

```

37 C.11 Clause 15 notes

38 C.11.1 Runtime environments (15.1)

- 39 1 This part of ISO/IEC 1539 allows programs to contain procedures defined by means other than Fortran. That
40 raises the issues of initialization of and interaction between the runtime environments involved.
- 41 2 Implementations are free to solve these issues as they see fit, provided that
- 42 • heap allocation/deallocation (e.g., (DE)ALLOCATE in a Fortran subprogram and malloc/free in a C func-
43 tion) can be performed without interference,

- 1 • input/output to and from [external files](#) can be performed without interference, as long as procedures defined
- 2 by different means do not do input/output with the same [external file](#),
- 3 • input/output preconnections exist as required by the respective standards, and
- 4 • initialized data are initialized according to the respective standards.

5 C.11.2 Example of Fortran calling C (15.3)

6 C Function Prototype:

```
7 int C_Library_Function(void* sendbuf, int sendcount, int *recvcounts);
```

8 Fortran Module:

```
9 MODULE CLIBFUN_INTERFACE
10 INTERFACE
11 INTEGER (C_INT) FUNCTION C_LIBRARY_FUNCTION (SENDBUF, SENDCOUNT, RECVCOUNTS) &
12 BIND(C, NAME='C_Library_Function')
13 USE, INTRINSIC :: ISO_C_BINDING
14 IMPLICIT NONE
15 TYPE (C_PTR), VALUE :: SENDBUF
16 INTEGER (C_INT), VALUE :: SENDCOUNT
17 INTEGER (C_INT) :: RECVCOUNTS(*)
18 END FUNCTION C_LIBRARY_FUNCTION
19 END INTERFACE
20 END MODULE CLIBFUN_INTERFACE
```

- 21 1 The module CLIBFUN_INTERFACE contains the declaration of the Fortran dummy arguments, which corres-
 22 pond to the C formal parameters. The [NAME=](#) is used in the [BIND attribute](#) in order to handle the case-sensitive
 23 name change between Fortran and C from “c_library_function” to “C_Library_Function”.
- 24 2 The first C formal parameter is the pointer to void `sendbuf`, which corresponds to the Fortran dummy argument
 25 `SENDBUF`, which has the type [C_PTR](#) and the [VALUE attribute](#).
- 26 3 The second C formal parameter is the int `sendcount`, which corresponds to the Fortran dummy argument
 27 `SENDCOUNT`, which has the type `INTEGER (C_INT)` and the [VALUE attribute](#).
- 28 4 The third C formal parameter is the pointer to int `recvcounts`, which corresponds to the Fortran dummy
 29 argument `RECVCOUNTS`, which is an [assumed-size array](#) of type `INTEGER (C_INT)`.
- 30 5 This example show how `C_Library_Function` might be referenced in a Fortran [program unit](#):

```
31 USE, INTRINSIC :: ISO_C_BINDING, ONLY: C_INT, C_FLOAT, C_LOC
32 USE CLIBFUN_INTERFACE
33 ...
34 REAL (C_FLOAT), TARGET :: SEND(100)
35 INTEGER (C_INT) :: SENDCOUNT, RET
36 INTEGER (C_INT), ALLOCATABLE :: RECVCOUNTS(:)
37 ...
38 ALLOCATE( RECVCOUNTS(100) )
```

```

1      ...
2      RET = C_LIBRARY_FUNCTION(C_LOC(SEND), SENDCOUNT, RECVCOUNTS)
3      ...

```

6 The first Fortran actual argument is a reference to the function `C_LOC` which returns the value of the C address of its argument, `SEND`. This value becomes the value of the first formal parameter, the pointer `sendbuf`, in `C_Library_Function`.

7 The second Fortran actual argument is `SENDCOUNT` of type `INTEGER (C_INT)`. Its value becomes the initial value of the second formal parameter, the int `sendcount`, in `C_Library_Function`.

8 The third Fortran actual argument is the allocatable array `RECVCOUNTS` of type `INTEGER (C_INT)`. The base C address of this array becomes the value of the third formal parameter, the pointer `recvcounts`, in `C_Library_Function`. Note that interoperability is based on the characteristics of the dummy arguments in the specified interface and not on those of the actual arguments. Thus, the fact that the actual argument is allocatable is not relevant here.

14 C.11.3 Example of C calling Fortran (15.3)

15 Fortran Code:

```

16      SUBROUTINE SIMULATION(ALPHA, BETA, GAMMA, DELTA, ARRAYS) BIND(C)
17          USE, INTRINSIC :: ISO_C_BINDING
18          IMPLICIT NONE
19          INTEGER (C_LONG), VALUE                :: ALPHA
20          REAL (C_DOUBLE), INTENT(INOUT)        :: BETA
21          INTEGER (C_LONG), INTENT(OUT)         :: GAMMA
22          REAL (C_DOUBLE), DIMENSION(*), INTENT(IN) :: DELTA
23          TYPE, BIND(C) :: PASS
24              INTEGER (C_INT) :: LENC, LENF
25              TYPE (C_PTR)   :: C, F
26          END TYPE PASS
27          TYPE (PASS), INTENT(INOUT) :: ARRAYS
28          REAL (C_FLOAT), ALLOCATABLE, TARGET, SAVE :: ETA(:)
29          REAL (C_FLOAT), POINTER :: C_ARRAY(:)
30          ...
31          ! Associate C_ARRAY with an array allocated in C
32          CALL C_F_POINTER (ARRAYS%C, C_ARRAY, [ ARRAYS%LENC ])
33          ...
34          ! Allocate an array and make it available in C
35          ARRAYS%LENF = 100
36          ALLOCATE (ETA(ARRAYS%LENF))
37          ARRAYS%F = C_LOC(ETA)
38          ...
39      END SUBROUTINE SIMULATION

```

40 C Struct Declaration:

```

1      struct pass {
2          int lenc, lenf;
3          float *c, *f;
4      };

```

5 C Function Prototype:

```

6      void simulation(long alpha, double *beta, long *gamma, double delta[],
7                      struct pass *arrays);

```

8 C Calling Sequence:

```

9      simulation(alpha, beta, gamma, delta, arrays);

```

10 1 The above-listed Fortran code specifies a subroutine SIMULATION. This subroutine corresponds to the C void
11 function simulation.

12 2 The Fortran subroutine references the intrinsic module ISO_C_BINDING.

13 3 The first Fortran dummy argument of the subroutine is ALPHA, which has the type INTEGER(C_LONG) and
14 the [VALUE attribute](#). This dummy argument corresponds to the C formal parameter alpha, which is a long.
15 The C actual argument is also a long.

16 4 The second Fortran dummy argument of the subroutine is BETA, which has the type REAL(C_DOUBLE) and
17 the [INTENT \(INOUT\) attribute](#). This dummy argument corresponds to the C formal parameter beta, which is
18 a pointer to double. An address is passed as the C actual argument.

19 5 The third Fortran dummy argument of the subroutine is GAMMA, which has the type INTEGER(C_LONG)
20 and the [INTENT \(OUT\) attribute](#). This dummy argument corresponds to the C formal parameter gamma, which
21 is a pointer to long. An address is passed as the C actual argument.

22 6 The fourth Fortran dummy argument is the [assumed-size array](#) DELTA, which has the type REAL (C_DOUBLE)
23 and the [INTENT \(IN\) attribute](#). This dummy argument corresponds to the C formal parameter delta, which is
24 a double array. The C actual argument is also a double array.

25 7 The fifth Fortran dummy argument is ARRAYS, which is a structure for accessing an array allocated in C and
26 an array allocated in Fortran. The lengths of these arrays are held in the components LENC and LENF; their [C](#)
27 [addresses](#) are held in components C and F.

28 C.11.4 Example of calling C functions with noninteroperable data (15.10)

29 1 Many Fortran processors support 16-byte real numbers, which might not be supported by the C processor.
30 Assume a Fortran programmer wants to use a C procedure from a message passing library for an array of these
31 reals. The C prototype of this procedure is

```

32      void ProcessBuffer(void *buffer, int n_bytes);

```

33 with the corresponding Fortran interface

```

34      USE, INTRINSIC :: ISO_C_BINDING

```

```

1      INTERFACE
2          SUBROUTINE PROCESS_BUFFER(BUFFER,N_BYTES) BIND(C,NAME="ProcessBuffer")
3              IMPORT :: C_PTR, C_INT
4              TYPE(C_PTR), VALUE :: BUFFER ! The 'C address' of the array buffer
5              INTEGER (C_INT), VALUE :: N_BYTES ! Number of bytes in buffer
6          END SUBROUTINE PROCESS_BUFFER
7      END INTERFACE

```

8 2 This can be done using `C_LOC` if the particular Fortran processor specifies that `C_LOC` returns an appropriate
9 address:

```

10         REAL(R_QUAD), DIMENSION(:), ALLOCATABLE, TARGET :: QUAD_ARRAY
11         ...
12         CALL PROCESS_BUFFER(C_LOC(QUAD_ARRAY), INT(16*SIZE(QUAD_ARRAY),C_INT))
13         ! One quad real takes 16 bytes on this processor

```

14 C.11.5 Example of opaque communication between C and Fortran (15.3)

15 1 The following example demonstrates how a Fortran processor can make a modern object-oriented random number
16 generator written in Fortran available to a C program.

```

17         USE, INTRINSIC :: ISO_C_BINDING
18         ! Assume this code is inside a module
19
20         TYPE RANDOM_STREAM
21         ! A (uniform) random number generator (URNG)
22     CONTAINS
23         PROCEDURE(RANDOM_UNIFORM), DEFERRED, PASS(STREAM) :: NEXT
24         ! Generates the next number from the stream
25     END TYPE RANDOM_STREAM
26
27     ABSTRACT INTERFACE
28         ! Abstract interface of Fortran URNG
29         SUBROUTINE RANDOM_UNIFORM(STREAM, NUMBER)
30             IMPORT :: RANDOM_STREAM, C_DOUBLE
31             CLASS(RANDOM_STREAM), INTENT(INOUT) :: STREAM
32             REAL(C_DOUBLE), INTENT(OUT) :: NUMBER
33         END SUBROUTINE RANDOM_UNIFORM
34     END INTERFACE

```

35 2 A polymorphic object with declared type `RANDOM_STREAM` is not [interoperable](#) with C. However, we can
36 make such a random number generator available to C by packaging it inside another nonpolymorphic, nonpara-
37 meterized derived type:

```

38         TYPE :: URNG_STATE ! No BIND(C), as this type is not interoperable
39         CLASS(RANDOM_STREAM), ALLOCATABLE :: STREAM
40     END TYPE URNG_STATE

```


1 3 The following two procedures will enable a C program to use our Fortran uniform random number generator:

```

2      ! Initialize a uniform random number generator:
3      SUBROUTINE INITIALIZE_URNG(STATE_HANDLE, METHOD) &
4          BIND(C, NAME="InitializeURNG")
5          TYPE(C_PTR), INTENT(OUT) :: STATE_HANDLE
6          ! An opaque handle for the URNG
7          CHARACTER(C_CHAR), DIMENSION(*), INTENT(IN) :: METHOD
8          ! The algorithm to be used
9
10         TYPE(URNG_STATE), POINTER :: STATE
11         ! An actual URNG object
12
13         ALLOCATE(STATE)
14         ! There needs to be a corresponding finalization
15         ! procedure to avoid memory leaks, not shown in this example
16         ! Allocate STATE%STREAM with a dynamic type depending on METHOD
17         ...
18         STATE_HANDLE=C_LOC(STATE)
19         ! Obtain an opaque handle to return to C
20     END SUBROUTINE INITIALIZE_URNG
21
22     ! Generate a random number:
23     SUBROUTINE GENERATE_UNIFORM(STATE_HANDLE, NUMBER) &
24         BIND(C, NAME="GenerateUniform")
25         TYPE(C_PTR), INTENT(IN), VALUE :: STATE_HANDLE
26         ! An opaque handle: Obtained via a call to INITIALIZE_URNG
27         REAL(C_DOUBLE), INTENT(OUT) :: NUMBER
28
29         TYPE(URNG_STATE), POINTER :: STATE
30         ! A pointer to the actual URNG
31
32         CALL C_F_POINTER(CPTR=STATE_HANDLE, FPTR=STATE)
33         ! Convert the opaque handle into a usable pointer
34         CALL STATE%STREAM%NEXT(NUMBER)
35         ! Use the type-bound procedure NEXT to generate NUMBER
36     END SUBROUTINE GENERATE_UNIFORM

```

37 C.11.6 Using assumed type to interoperate with C

38 C.11.6.1 Overview

39 1 The mechanism for handling [unlimited polymorphic](#) entities whose [dynamic type](#) is interoperable with C is
40 designed to handle the following two situations:

- 41 (1) A formal parameter that is a C pointer to void. This is an address, and no further information
42 about the entity is provided. The formal parameter corresponds to a dummy argument that is a
43 nonallocatable nonpointer scalar or is an [assumed-size array](#).

1 (2) A formal parameter that is the address of a [C descriptor](#). Additional information on the status, type,
 2 size, and shape is implicitly provided. The formal parameter corresponds to a dummy argument that
 3 is [assumed-shape](#) or [assumed-rank](#).

4 2 In the first situation, it is the programmer's responsibility to explicitly provide any information needed on the
 5 status, type, size, and shape of the entity.

6 **C.11.6.2 Mapping of interfaces with void * C parameters to Fortran**

7 1 A C interface for message passing or input/output functionality could be provided in the form

```
8         int EXAMPLE_send(const void *buffer, size_t buffer_size, const HANDLE_t *handle);
```

9 where the `buffer_size` argument is given in units of bytes, and the `handle` argument (which is of a type aliased
 10 to `int`) provides information about the target the buffer is to be transferred to. In this example, type resolution
 11 is not required.

12 2 The first method provides a thin binding; a call to `EXAMPLE_send` from Fortran directly invokes the C function.

```
13         INTERFACE
14             INTEGER (C_INT) FUNCTION example_send(buffer, buffer_size, handle) &
15             BIND(C, NAME='EXAMPLE_send')
16             USE, INTRINSIC :: ISO_C_BINDING
17             TYPE(*), INTENT (IN) :: buffer(*)
18             INTEGER (C_SIZE_T), VALUE :: buffer_size
19             INTEGER (C_INT), INTENT (IN) :: handle
20         END FUNCTION
21     END INTERFACE
```

22 3 It is assumed that this interface is declared in the specification part of the module `MOD_EXAMPLE_OLD`. An
 23 example of its use follows:

```
24         USE, INTRINSIC :: ISO_C_BINDING
25         USE MOD_EXAMPLE_OLD
26
27         REAL(C_FLOAT) :: x(100)
28         INTEGER(C_INT) :: y(10,10)
29         REAL(C_DOUBLE) :: z
30         INTEGER(C_INT) :: status, handle
31         ...
32         ! Assign values to x, y, z and initialize handle.
33         ...
34         ! Send values in x, y, and z using EXAMPLE_send.
35         status = example_send(x, C_SIZEOF(x), handle)
36         status = example_send(y, C_SIZEOF(y), handle)
37         status = example_send([ z ], C_SIZEOF(z), handle)
```

38 4 In those invocations, `x` and `y` are passed directly with sequence association, but it is necessary to make an array
 39 expression containing the value of `z` to pass it.

1 5 The second method provides a Fortran interface which is easier to use, but requires writing a separate C wrapper
 2 routine. With this method, a C descriptor is created because the buffer is assumed-rank in the Fortran interface;
 3 the use of an optional argument is also demonstrated.

```

4     INTERFACE
5         SUBROUTINE example_send(buffer, handle, status) BIND(C, NAME="EG_send_fortran")
6             USE, INTRINSIC :: ISO_C_BINDING
7             TYPE(*), CONTIGUOUS, INTENT (IN) :: buffer(..)
8             INTEGER (C_INT), INTENT (IN) :: handle
9             INTEGER (C_INT), INTENT(OUT), OPTIONAL :: status
10        END SUBROUTINE
11    END INTERFACE

```

12 6 It is assumed that this interface is declared in the specification part of a module MOD_EXAMPLE_NEW.
 13 Example invocations from Fortran are then

```

14        USE, INTRINSIC :: iso_c_binding
15        USE mod_example_new
16
17        TYPE, BIND(C) :: my_derived
18            INTEGER(C_INT) :: len_used
19            REAL(C_FLOAT) :: stuff(100)
20        END TYPE
21        TYPE(my_derived) :: w(3)
22        REAL(C_FLOAT) :: x(100)
23        INTEGER(C_INT) :: y(10,10)
24        REAL(C_DOUBLE) :: z
25        INTEGER(C_INT) :: status, handle
26        ...
27        ! Assign values to w, x, y, z and initialize handle.
28        ...
29        ! Send values in w, x, y, and z using example_send.
30        CALL example_send(w, handle, status)
31        CALL example_send(x, handle)
32        CALL example_send(y, handle)
33        CALL example_send(z, handle)
34        CALL example_send(y(:,5), handle) ! Fifth column of y.
35        CALL example_send(y(1,5), handle) ! Scalar y(1,5) passed by descriptor.

```

36 7 The wrapper routine can be written in C as follows.

```

37        #include "ISO_Fortran_binding.h"
38
39        void EXAMPLE_send_fortran(const CFI_cdesc_t *buffer, const HANDLE_t *handle,
40                                int *status)
41        {
42            int status_local;
43            size_t buffer_size;

```

```

1         int i;
2
3         buffer_size = buffer->elem_len;
4         for (i=0; i<buffer->rank; i++) {
5             buffer_size *= buffer->dim[i].extent;
6         }
7         status_local = EXAMPLE_send(buffer->base_addr,buffer_size, handle);
8         if (status != NULL) *status = status_local;
9     }

```

10 C.11.7 Using assumed-type variables in Fortran

11 1 An [assumed-type](#) dummy argument in a Fortran procedure can be used as an actual argument corresponding to an
12 [assumed-type](#) dummy in a call to another procedure. In the following example, the Fortran subroutine SIMPLE_
13 SEND serves as a wrapper to hide the complications associated with calls to a C function named ACTUAL_Send.
14 Module COMM_INFO contains node and address information for the current data transfer operations.

```

15     SUBROUTINE SIMPLE_SEND(buffer, nbytes)
16         USE comm_info, ONLY: my_node, r_node, r_addr
17         USE, INTRINSIC :: ISO_C_BINDING
18         IMPLICIT NONE
19
20         TYPE(*), INTENT (IN) :: buffer(*)
21         INTEGER                :: nbytes, ierr
22
23         INTERFACE
24             SUBROUTINE actual_Send(buffer, nbytes, node, addr, ierr) &
25             BIND(C, NAME="ACTUAL_Send")
26                 IMPORT :: C_SIZE_T, C_INT, C_INTPTR_T
27                 TYPE(*), INTENT (IN)                :: buffer(*)
28                 INTEGER(C_SIZE_T), VALUE            :: nbytes
29                 INTEGER(C_INT), VALUE                :: node
30                 INTEGER(C_INTPTR_T), VALUE          :: addr
31                 INTEGER(C_INT), INTENT(OUT)         :: ierr
32             END SUBROUTINE actual_Send
33         END INTERFACE
34
35         CALL actual_Send(buffer, INT(nbytes, C_SIZE_T), r_node, r_addr, ierr)
36
37         IF (ierr /= 0) THEN
38             PRINT *, "Error sending from node", my_node, "to node", r_node
39             PRINT *, "Program Aborting" ! Or call a recovery procedure
40             ERROR STOP                  ! Omit in the recovery case
41         END IF
42     END SUBROUTINE simple_Send

```

1 C.11.8 Simplifying interfaces for arbitrary rank procedures

2 1 There are situations where an [assumed-rank](#) dummy argument can be useful in Fortran, although a Fortran
3 procedure cannot itself access its value. For example, the IEEE inquiry functions in Clause 14 could be written
4 using an [assumed-rank](#) dummy argument instead of writing 16 separate specific routines, one for each possible
5 rank.

6 2 In particular, the specific procedures for the IEEE_SUPPORT_DIVIDE function could possibly be implemented
7 in Fortran as follows:

```
8     INTERFACE ieee_support_divide
9         MODULE PROCEDURE ieee_support_divide_noarg, ieee_support_divide_onearg_r, &
10             ieee_support_divide_onearg_d
11     END INTERFACE ieee_support_divide
12
13     ...
14
15     LOGICAL FUNCTION ieee_support_divide_noarg ()
16         ieee_support_divide_noarg = .TRUE.
17     END FUNCTION ieee_support_divide_noarg
18
19     LOGICAL FUNCTION ieee_support_divide_onearg_r (x)
20         REAL, INTENT (IN) :: x(..)
21         ieee_support_divide_onearg_r4 = .TRUE.
22     END FUNCTION ieee_support_divide_onearg_r
23
24     LOGICAL FUNCTION ieee_support_divide_onearg_d (x)
25         DOUBLE PRECISION, INTENT (IN) :: x(..)
26         ieee_support_divide_onearg_r8 = .TRUE.
27     END FUNCTION ieee_support_divide_onearg_d
```

28 C.11.9 Processing assumed-shape arrays in C

29 1 The example shown below calculates the product of individual elements of arrays A and B and returns the result
30 in array C. The Fortran interface of `elemental_mult` will accept arguments of any type and rank. However, the
31 C function will return an error code if any argument is not a two-dimensional `int` array. Note that the arguments
32 are permitted to be array sections, so the C function does not assume that any argument is contiguous.

33 2 The Fortran interface is:

```
34     INTERFACE
35         FUNCTION elemental_mult(a, b, c) BIND(C, NAME="elemental_mult_c") RESULT(err)
36             USE, INTRINSIC :: ISO_C_BINDING
37             INTEGER(C_INT) :: err
38             TYPE(*), DIMENSION(..) :: a, b, c
39         END FUNCTION elemental_mult
40     END INTERFACE
```

41 3 The definition of the C function is:

```
1      #include "ISO_Fortran_binding.h"
2
3      int elemental_mult_c(CFI_cdesc_t * a_desc, CFI_cdesc_t * b_desc, CFI_cdesc_t * c_desc)
4      {
5          size_t i, j, ni, nj;
6
7          int err = 1; /* this error code represents all errors */
8
9          char * a_col = (char*) a_desc->base_addr;
10         char * b_col = (char*) b_desc->base_addr;
11         char * c_col = (char*) c_desc->base_addr;
12         char *a_elt, *b_elt, *c_elt;
13
14         /* Only support int. */
15         if (a_desc->type != CFI_type_int || b_desc->type != CFI_type_int ||
16             c_desc->type != CFI_type_int) {
17             return err;
18         }
19
20         /* Only support two dimensions. */
21         if (a_desc->rank != 2 || b_desc->rank != 2 || c_desc->rank != 2) {
22             return err;
23         }
24
25         ni = a_desc->dim[0].extent;
26         nj = a_desc->dim[1].extent;
27
28         /* Ensure the shapes conform. */
29         if (ni != b_desc->dim[0].extent || ni != c_desc->dim[0].extent) return err;
30         if (nj != b_desc->dim[1].extent || nj != c_desc->dim[1].extent) return err;
31
32         /* Multiply the elements of the two arrays. */
33         for (j = 0; j < nj; j++) {
34             a_elt = a_col;
35             b_elt = b_col;
36             c_elt = c_col;
37             for (i = 0; i < ni; i++) {
38                 *(int*)a_elt = *(int*)b_elt * *(int*)c_elt;
39                 a_elt += a_desc->dim[0].sm;
40                 b_elt += b_desc->dim[0].sm;
41                 c_elt += c_desc->dim[0].sm;
42             }
43             a_col += a_desc->dim[1].sm;
44             b_col += b_desc->dim[1].sm;
45             c_col += c_desc->dim[1].sm;
46         }
```

```

1         return 0;
2     }

```

3 C.11.10 Creating a contiguous copy of an array

4 1 A C function might need to create a contiguous copy of an array section, for example, to pass the array section
5 as an actual argument corresponding to a dummy argument with the CONTIGUOUS attribute. The following
6 example provides functions that can be used to copy an array described by a `CFI_cdesc_t` descriptor to a
7 contiguous buffer. The input array need not be contiguous.

8 2 The C functions are:

```

9         #include "ISO_Fortran_binding.h"
10        /* Other necessary includes omitted. */
11
12        /*
13         * Returns the number of elements in the object described by desc.
14         * If it is an array, it need not be contiguous.
15         * (The number of elements could be zero).
16         */
17        size_t numElements(const CFI_cdesc_t * desc)
18        {
19            CFI_rank_t r;
20            size_t num = 1;
21
22            for (r = 0; r < desc->rank; r++) {
23                num *= desc->dim[r].extent;
24            }
25            return num;
26        }
27
28        /*
29         * Auxiliary recursive function to copy an array of a given rank.
30         * Recursion is useful because an array of rank n is composed of an
31         * ordered set of arrays of rank n-1.
32         */
33        static void *_copyToContiguous (const CFI_cdesc_t *vald, void *output,
34                                       const void *input, CFI_rank_t rank)
35        {
36            CFI_index_t e;
37
38            if (rank == 0) {
39                /* Copy scalar element. */
40                memcpy (output, input, vald->elem_len);
41                output = (void *)((char *)output + vald->elem_len);
42            }
43            else {
44                for (e = 0; e < vald->dim[rank-1].extent; e++) {

```

```

1         /* Recurse on subarrays of lesser rank. */
2         output = _copyToContiguous (vald, output, input, rank-1);
3         input = (void *) ((char *)input + vald->dim[rank].sm);
4     }
5 }
6     return output;
7 }
8
9 /*
10  * General routine to copy the elements in the array described by vald
11  * to buffer, as done by sequence association.  The array itself can
12  * be non-contiguous.  This is not the most efficient approach.
13  */
14 void copyToContiguous (void * buffer, const CFI_cdesc_t * vald) {
15     _copyToContiguous (vald, buffer, vald->base_addr, vald->rank);
16 }

```

17 C.11.11 Changing the attributes of an array

18 1 A C programmer might want to call more than one Fortran procedure and the attributes of an array involved
19 might differ between the procedures. In this case, it is necessary to set up more than one **C descriptor** for the
20 array. For example, this code fragment initializes the first **C descriptor** for an allocatable entity of rank 2, calls
21 a procedure that allocates the array described by the first **C descriptor**, constructs the second **C descriptor** by
22 invoking `CFI_section` with the value `CFI_attribute_other` for the `attribute` parameter, then calls a procedure
23 that expects an **assumed-shape array**.

```

24     CFI_CDESC_T(2) loc_alloc, loc_assum;
25     CFI_cdesc_t * desc_alloc = (CFI_cdesc_t *)&loc_alloc,
26         * desc_assum = (CFI_cdesc_t *)&loc_assum;
27     CFI_index_t extents[2];
28     CFI_rank_t rank = 2;
29     int flag;
30
31     flag = CFI_establish(desc_alloc,
32         NULL,
33         CFI_attribute_allocatable,
34         CFI_type_double,
35         sizeof(double),
36         rank,
37         NULL);
38
39     Fortran_factor (desc_alloc, ...); /* Allocates array described by desc_alloc. */
40
41     /* Extract extents from descriptor. */
42     extents[0] = desc_alloc->dim[0].extent;
43     extents[1] = desc_alloc->dim[1].extent;
44

```



```

1         flag = CFI_establish(desc_assum,
2                               desc_alloc->base_addr,
3                               CFI_attribute_other,
4                               CFI_type_double,
5                               sizeof(double),
6                               rank,
7                               extents);
8
9         Fortran_solve (desc_assum, ...); /* Uses array allocated in Fortran_factor. */

```

10 2 After invocation of the second CFI_establish, the lower bounds stored in the dim member of desc_assum will
11 have the value 0 even if the corresponding entries in desc_alloc have different values.

12 C.11.12 Creating an array section in C using CFI_section

13 1 The C function set_odd sets every second element of an array to a specific value, beginning with the first element.
14 If does this by making an array section descriptor for the elements to be set, and calling a Fortran subroutine
15 SET_ALL that sets every element of an assumed-shape array to a specific value. An interface block for set_odd
16 permits it to be also called from Fortran.

```

17         SUBROUTINE set_all(int_array, val) BIND(C)
18             INTEGER(C_INT) :: int_array(:)
19             INTEGER(C_INT), VALUE :: val
20             int_array = val
21         END SUBROUTINE
22
23         INTERFACE
24             SUBROUTINE set_odd(int_array, val) BIND(C)
25                 USE, INTRINSIC :: ISO_C_BINDING, ONLY : C_INT
26                 INTEGER(C_INT) :: int_array(:)
27                 INTEGER(C_INT), VALUE :: val
28             END SUBROUTINE
29         END INTERFACE
30
31         #include "ISO_Fortran_binding.h"
32
33         void set_odd(CFI_cdesc_t *int_array, int val)
34         {
35             CFI_index_t lower_bound[1], upper_bound[1], stride[1];
36             CFI_CDESC_T(1) array;
37             int status;
38             /* Create a new descriptor which will contain the section. */
39             status = CFI_establish((CFI_cdesc_t *)&array,
40                                   NULL,
41                                   CFI_attribute_other,
42                                   int_array->type,
43                                   int_array->elem_len,

```

```

1           /* rank */ 1,
2           /* extents is ignored */NULL);
3
4     lower_bound[0] = int_array->dim[0].lower_bound;
5     upper_bound[0] = lower_bound[0] + (int_array->dim[0].extent - 1);
6     stride[0] = 2;
7
8     status = CFI_section((CFI_cdesc_t *)&array,
9                          int_array,
10                         lower_bound,
11                         upper_bound,
12                         stride);
13
14     set_all( (CFI_cdesc_t *) &array, val);
15
16     /* Here one could make use of int_array and access all its data. */
17 }

```

18 2 The `set_odd` procedure can be called from Fortran as follows:

```

19     INTEGER(C_INT) :: d(5)
20     d = (/ 1, 2, 3, 4, 5 /)
21     CALL set_odd(d, -1)
22     PRINT *, d

```

23 3 This program will print something like:

```

24     -1    2    -1    4    -1

```

25 4 During execution of the subroutine `SET_ALL`, its dummy argument `INT_ARRAY` would have size (and upper bound) 3.

27 5 It is also possible to invoke `set_odd()` from C. However, it would be the C programmer's responsibility to make sure that all members of the [C descriptor](#) have the correct value on entry to the function. Inserting additional checking into the function could alleviate this problem.

30 6 Following is an example C function that dynamically generates a [C descriptor](#) for an [assumed-shape array](#) and calls `set_odd`.

```

32     #include <stdio.h>
33     #include <stdlib.h>
34     #include "ISO_Fortran_binding.h"
35
36     #define ARRAY_SIZE 5
37
38     void example_of_calling_set_odd(void)
39     {
40         CFI_CDESC_T(1) d;

```

```

1      CFI_index_t extent[1];
2      CFI_index_t subscripts[1];
3      void *base;
4      int i, status;
5
6      base = malloc(ARRAY_SIZE*sizeof(int));
7      extent[0] = ARRAY_SIZE;
8      status = CFI_establish((CFI_cdesc_t *)&d,
9                             base,
10                            CFI_attribute_other,
11                            CFI_type_int,
12                            /* element length is ignored */ 0,
13                            /* rank */ 1,
14                            extent);
15
16      set_odd((CFI_cdesc_t *)&d, -1);
17
18      for (i=0; i<ARRAY_SIZE; i++) {
19          subscripts[0] = i;
20          printf(" %d",*((int *)CFI_address((CFI_cdesc_t *)&d, subscripts)));
21      }
22      putc(10, stdout);
23      free(base);
24  }

```

25 The above C function will print similar output to that of the preceding Fortran program.

26 C.11.13 Use of CFI_setpointer

27 1 The C function `change_target` modifies a pointer to an integer variable to become associated with a global
28 variable defined inside C:

```

29      #include "ISO_Fortran_binding.h"
30
31      int y = 2;
32
33      void change_target(CFI_cdesc_t *ip) {
34          CFI_CDESC_T(0) yp;
35          int status;
36          /* Make local yp point at y. */
37          status = CFI_establish((CFI_cdesc_t *)&yp,
38                                 &y,
39                                 CFI_attribute_pointer,
40                                 CFI_type_int,
41                                 /* elem_len is ignored */ sizeof(int),
42                                 /* rank */ 0,
43                                 /* extents are ignored */ NULL);
44          /* Pointer-associate ip with (the target of) yp. */

```

```

1         status = CFI_setpointer(ip, (CFI_cdesc_t *)&yp, NULL);
2         if (status != CFI_SUCCESS) {
3             ... report run time error...
4         }
5     }

```

6 2 The restrictions on the use of CFI_establish prohibit direct modification of the incoming pointer entity `ip` by
7 invoking that function on it.

8 3 The following program illustrates the usage of `change_target` from Fortran.

```

9     PROGRAM change_target_example
10        USE, INTRINSIC :: ISO_C_BINDING
11        INTERFACE
12            SUBROUTINE change_target(ip) BIND(C)
13                IMPORT :: C_INT
14                INTEGER(C_INT), POINTER :: ip
15            END SUBROUTINE
16        END INTERFACE
17        INTEGER(C_INT), TARGET :: it = 1
18        INTEGER(C_INT), POINTER :: it_ptr
19        it_ptr => it
20        WRITE (*,*) it_ptr
21        CALL change_target(it_ptr)
22        WRITE (*,*) it_ptr

```

23 4 This will print something similar to

```

24         1
25         2

```

26 C.11.14 Mapping of MPI interfaces to Fortran

27 1 The Message Passing Interface (MPI) specifies procedures for exchanging data between MPI processes. This
28 example shows the usage of `MPI_Send` and is similar to the second variant of `EXAMPLE_Send` in [C.11.6.2](#). It also
29 shows the usage of assumed-length character dummy arguments and optional dummy arguments.

30 2 `MPI_Send` has the C prototype:

```

31         int MPI_Send(void *buf, int count, MPI_Datatype datatype, int dest, int tag,
32                     MPI_Comm comm);

```

33 where `MPI_Datatype` and `MPI_Comm` are opaque handles. Most MPI C functions return an error code, which in
34 Fortran is the last dummy argument to the corresponding subroutine and can be made optional. Thus, the use
35 of a Fortran subroutine requires a wrapper function, declared as

```

36         void MPI_Send_f(CFI_cdesc_t *buf, int count, MPI_Datatype_f datatype, int dest,
37                       int tag, MPI_Datatype_f comm, int *ierror);

```

1 3 This wrapper function will convert MPI_Datatype_f and MPI_Comm_f to MPI_Datatype and MPI_Comm, and pro-
 2 duce a contiguous void * buffer from CFI_cdesc_t *buf (if necessary).

3 4 Similarly, the wrapper function for MPI_Comm_set_name could have the C prototype:

```
4 void MPI_Comm_set_name_f(MPI_Comm comm, CFI_cdesc_t *comm_name, int *ierror);
```

5 5 The Fortran handle types and interfaces are defined in the module MPI_F08. For example,

```
6 MODULE mpi_f08
7   ...
8   TYPE, BIND(C) :: mpi_comm
9   PRIVATE
10  INTEGER(C_INT) :: mpi_val
11  END TYPE mpi_comm
12
13  INTERFACE
14    SUBROUTINE MPI_SEND(buf,count,datatype,dest,tag,comm,ierror) &
15    BIND(C, NAME='MPI_Send_f')
16    USE, INTRINSIC :: ISO_C_BINDING
17    IMPORT :: MPI_Datatype, MPI_Comm
18    TYPE(*), DIMENSION(..), INTENT (IN) :: buf
19    INTEGER(C_INT), VALUE, INTENT (IN) :: count, dest, tag
20    TYPE(mpi_datatype), INTENT (IN) :: datatype
21    TYPE(mpi_comm), INTENT (IN) :: comm
22    INTEGER(C_INT), OPTIONAL, INTENT (OUT) :: ierror
23  END SUBROUTINE mpi_send
24
25    SUBROUTINE mpi_comm_set_name(comm,comm_name,ierror) &
26    BIND(C, NAME='MPI_Comm_set_name_f')
27    USE, INTRINSIC :: ISO_C_BINDING
28    IMPORT :: mpi_comm
29    TYPE(mpi_comm), INTENT (IN) :: comm
30    CHARACTER(KIND=C_CHAR, LEN=*), INTENT (IN) :: comm_name
31    INTEGER(C_INT), OPTIONAL, INTENT (OUT) :: ierror
32  END SUBROUTINE mpi_comm_set_name
33  END INTERFACE
34  ...
35  END MODULE mpi_f08
```

36 6 Some examples of invocation from Fortran are:

```
37 USE, INTRINSIC :: ISO_C_BINDING
38 USE :: MPI_f08
39
40 TYPE(mpi_comm) :: comm
41 REAL :: x(100)
42 INTEGER :: y(10,10)
```

```

1      REAL(KIND(1.0d0)) :: z
2      INTEGER :: dest, tag, ierror
3      ...
4      ! Assign values to x, y, z and initialize MPI variables.
5      ...
6
7      ! Set the name of the communicator.
8      CALL mpi_comm_set_name(comm, "Communicator Name", ierror)
9
10     ! Send values in x, y, and z.
11     CALL mpi_send(x, 100, MPI_REAL, dest, tag, comm, ierror)
12     IF (ierror/=0) PRINT *, 'WARNING: X send error', ierror
13     CALL mpi_send(y(3,:), 10, MPI_INTEGER, dest, tag, comm)
14     CALL mpi_send(z, 1, MPI_DOUBLE_PRECISION, dest, tag, comm)

```

15 7 The first example sends the entire array X and includes the optional error argument return value. The second
16 example sends a noncontiguous subarray (the third row of Y) and the third example sends a scalar Z. Note the
17 differences between the calls in this example and those in [C.11.6.2](#).

18 C.12 Clause 16 notes : Examples of host association (16.5.1.4)

19 1 The first two examples are examples of valid [host association](#). The third example is an example of invalid [host](#)
20 [association](#).

21 Example 1:

```

22     PROGRAM A
23         INTEGER I, J
24         ...
25     CONTAINS
26         SUBROUTINE B
27             INTEGER I ! Declaration of I hides
28                     ! program A's declaration of I
29             ...
30             I = J     ! Use of variable J from program A
31                     ! through host association
32         END SUBROUTINE B
33     END PROGRAM A

```

34 Example 2:

```

35     PROGRAM A
36         TYPE T
37         ...
38     END TYPE T
39     ...
40     CONTAINS

```

```
1          SUBROUTINE B
2              IMPLICIT TYPE (T) (C) ! Refers to type T declared below
3                                      ! in subroutine B, not type T
4                                      ! declared above in program A
5              ...
6              TYPE T
7              ...
8              END TYPE T
9              ...
10             END SUBROUTINE B
11         END PROGRAM A
```

12 **Example 3:**

```
13         PROGRAM Q
14             REAL (KIND = 1) :: C
15             ...
16         CONTAINS
17             SUBROUTINE R
18                 REAL (KIND = KIND (C)) :: D ! Invalid declaration
19                                             ! See below
20                 REAL (KIND = 2) :: C
21                 ...
22             END SUBROUTINE R
23         END PROGRAM Q
```

24 2 In the declaration of D in subroutine R, the use of C would refer to the declaration of C in subroutine R, not
25 program Q. However, it is invalid because the declaration of C is required to occur before it is used in the
26 declaration of D (7.1.12).

(Blank page)

Index

In the index, entries in *italics* denote BNF terms, and page numbers in **bold face** denote primary text or definitions.

Symbols

–, 145
 <, 149
 <=, 149
 >, 149
 >=, 149
 *, 49, 52, 54, 59, 95, 99, 109, 130, 145, 226, 227, 257, 269, 274, 299, 318
 **, 145
 +, 145
 -*stmt*, 17
 .AND., 140, 141, 144, **148**, 148, 338
 .EQ., 139, 141, 144, 148, **149**, 149, 151, 288
 .EQV., 140, 141, 144, **148**, 148
 .FALSE., **62**, 457
 .GE., 139, 141, 144, 148, **149**, 151, 288
 .GT., 139, 141, 144, 148, **149**, 151, 288
 .LE., 139, 141, 144, 148, **149**, 151, 288
 .LT., 139, 141, 144, 148, **149**, 151, 288
 .NE., 139, 141, 144, 148, **149**, 149, 151, 288
 .NEQV., 140, 141, 144, **148**, 148, 394
 .NOT., 140, 141, 144, **148**, 148
 .OR., 140, 141, 144, **148**, 148, 340
 .TRUE., **62**, 457
 /, 145
 / edit descriptor, 267
 //, 147
 /=, 149
 : edit descriptor, 267
 ;;, 48
 ==, 149
 &, 48, 274

A

A edit descriptor, 264
 ABS, **336**, 428

ABSTRACT, **63**, 63, 79, **288**, 289
 ABSTRACT attribute, 19, 63, **79**
 abstract interface, **2**, 12, 280, **287**, 289, 297, 316, 488, 492
 abstract interface block, **12**, 12, 289
 abstract type, **19**, 53, 76, **79**, 79, 82, 123, 130
ac-do-variable (R476), **87**, 87, 154, 156, 490
ac-implied-do (R474), **87**, 87, 143, 490
ac-implied-do-control (R475), **87**, 87, 143, 154–156, 490
ac-spec (R470), 86, **87**
ac-value (R473), **87**, 87
access-id (R528), **106**, 106
access-name, 106
access-spec (R507), 63, 68, 69, 74–77, 89, **92**, 92, 106, 290, 296
access-stmt (R527), 30, 92, **106**, 106
 ACCESS= specifier, 212, **214**, 240, **241**
 accessibility attribute, **92**, 106, 280
 accessibility statement, 106
 ACHAR, 62, 160, **337**
 ACOS, **337**
 ACOSH, **337**
 ACQUIRED_LOCK= specifier, **200**, 503, 506
 action, 204
action-stmt (R215), 4, **31**, 31, 143, 184, 192
 ACTION= specifier, 213, **214**, 240, **241**, 509, 533
 actual argument, **2**, 13, 25, 38, 40, 54, 56, 66, 78, 79, 84, 98–103, 123, 125, 133, 135, 143, 152, 153, 232, 293, 294, 298–310, 312, 320, 321, 323–326, 329, 334, 336, 354, 376, 377, 392, 401, 413–415, 418, 429, 461, 462, 464, 467–469, 491, 495–497, 500, 504–506, 515, 552, 553, 555, 558
actual-arg (R1225), **299**, 299
actual-arg-spec (R1224), 82, **299**, 299
add-op (R709), 45, **138**, 138

- add-operand* (R705), **138**, 138, 141, 142
- ADJUSTL, **337**
- ADJUSTR, **338**
- ADVANCE= specifier, 218, 219, **220**, 230, 531
- advancing input/output statement, 207
- AIMAG, **338**
- AINT, **338**
- ALL, **290**, **338**
- alloc-opt* (R627), **130**, 130, 131
- allocatable, **2**, 2, 17, 39, 40, 52, 54, 65, 70, 71, 73, 78, 81, 83, 84, 90, 95, 98–101, 105, 108, 116, 118, 123, 124, 130–136, 153, 155, 157–160, 162, 163, 181, 195, 223, 224, 229, 286, 287, 299, 303, 305, 306, 309, 317, 323, 325, 339, 353, 363, 376–378, 389, 392, 393, 402, 405, 408, 409, 411, 414, 415, 424, 429, 457, 462, 464–466, 471, 478, 481, 494, 495, 504
- ALLOCATABLE attribute, **2**, 52–54, **62**, **68**, **69**, **92**, **93**, 93–95, 98, 103, 105, 107, 123, 126, 188, 284, 287, 294, 295, 305, 309, 316, 324, 466, 494, 500, 501, 555, 559
- ALLOCATABLE statement, **107**
- allocatable-decl* (R530), **107**, 107
- allocatable-stmt* (R529), **30**, **107**, 492
- ALLOCATE statement, 52, 53, 60, 93, 96, 98, **130**, 136, 162, 194, 418, 475, 476, 495, 496, 503, 504, 508
- allocate-coarray-spec* (R636), **130**, 130
- allocate-coshape-spec* (R637), **130**, 130
- allocate-object* (R632), **60**, **130**, 130–132, 134–136, 194, 418, 420, 506, 508
- allocate-shape-spec* (R633), **130**, 130, 132
- allocate-stmt* (R626), **31**, **130**, 506
- ALLOCATED, **68**, **69**, 133, 136, **339**
- allocation* (R631), **130**, 130, 132
- alphanumeric-character* (R301), **43**, 43, 44
- alt-return-spec* (R1226), **4**, 192, **299**, 299
- ancestor component, **80**
- ancestor-module-name*, 283
- and-op* (R719), 45, **140**, 140
- and-operand* (R714), **140**, 140
- ANINT, **339**
- ANY, **340**
- arg-name*, **69**, 71, 76
- argument
- dummy, **304**
- argument association, **3**, 3, 20, 52, 60, 70, 71, 95, 98, 105, 106, 134, 136, 285, 301, 302, 312, 318, 491, 497, 499, 500, 510, 514, 554
- argument keyword, **9**, **13**, 40, 287, 290, 301, 325, 329, 429, 488, **489**, **490**, 541
- arithmetic IF statement, **514**
- array, **2**, 4, 10, 17, 39, 97–99, 125–128
- assumed-shape, **2**, 54, 96, 98, 129, 287, 291, 292, 303–305, 307, 310, 316, 457, 467, 469, 552, 568, 574, 576
 - assumed-size, **2**, 99, 100, 105, 116, 125, 126, 137, 154, 157, 177, 188, 189, 223, 303, 304, 309, 377, 405, 406, 408, 414, 462, 466, 471, 478, 563, 565, 567
 - deferred-shape, **2**, 98
 - explicit-shape, **2**, 54, 70, 95, 98, 157, 304, 309, 466
- array bound, **4**, 69, 72, 91
- array constructor, **86**, 86
- array element, **2**, 39, 126
- array element order, 126–127
- array pointer, **2**, 96, 98, 99, 153, 341, 466
- array section, **2**, 96, 108, 109, 124, 126–129, 173, 209, 303, 304, 310, 494, 497
- array-constructor* (R469), **86**, 87, 137
- array-element* (R617), 108, 109, 116, 121, 122, **125**
- array-name*, 110, 492
- array-section* (R618), **2**, 121, **125**, 126, 127
- array-spec* (R515), 23, 89–91, **97**, 97–100, 107, 110, 112, 118
- ASCII character, **3**, **59**, **62**, 157, 209, 210, 224, 256, 270, 337, 351, 369, 372, 378–380, 391, 404
- ASCII collating sequence, **62**, 337, 351, 369, 372, 379, 380, 391
- ASIN, **340**
- ASINH, **340**
- ASSIGN statement, **513**
- assigned format, **513**
- assigned GO TO statement, **513**
- ASSIGNMENT, 75, 161, **288**, 288, 294, 295
- assignment, 157–169
- defined, 75, 161, 294
 - elemental, **9**, 161
 - elemental array (FORALL), 167
 - masked array (WHERE), 165
 - pointer, **161**
- assignment statement, 14, 38, 52, 78, **157**, 169, 453, 502
- assignment-stmt* (R732), **31**, **157**, 157, 165, 168, 506

- ASSOCIATE construct, **172**, 309, 490, 491, 506
- associate name, **3**, 3, 20, 52, 54, 82, 134, 172, 173, 190, 491, 494, 495, 500, 506
- ASSOCIATE statement, **172**, 494
- associate-construct* (R802), 31, **172**, 172
- associate-construct-name*, 172
- associate-name*, 172, 187, 188, 190, 192, 490
- associate-stmt* (R803), 4, **172**, 172, 192
- ASSOCIATED, 68, 69, 133, 136, 326, **341**
- associating entity, **3**, 60, 172, 173, 191, 318, **500**, 500
- association, **3**
- argument, **3**, 3, 20, 52, 60, 70, 71, 95, 98, 105, 106, 134, 136, 285, 301, 302, 312, 318, 491, 497, 499, 500, 510, 514, 554
 - common, 119
 - construct, **3**, 3, 134, 136, 491, **494**, 497, 500
 - equivalence, 117
 - host, **3**, 3, 33, 53, 60, 93, 106, 108, 113, 119, 154, 155, 163, 283, 285, 309, 321–323, 490–494, 497, 500, 580
 - inheritance, **3**, 3, 6, 80, 82, 497, 500
 - linkage, **3**, 3, 483, 491, **494**, 494
 - name, **3**, 3, **491**, 497
 - pointer, **3**, 3, 9, 19, 20, 38, 79, 81, 83, 96, 101, 103, 105, 106, 123, 134, 136, 161, 163, 164, 181, 195, 198, 226, 286, 302, 304, 306, 308, 309, 317, 318, 330, 341, 392, 460, 461, 495–497, 500, 505, 506
 - sequence, 308
 - storage, **3**, 3, 40, 116–118, 319, 322, 409, 497–500
 - use, **3**, 3, 33, 41, 60, 80, 93, 104, 106, 113, 116–118, 155, 163, **280**, 279–283, 289, 319, 322, 490–492, 495
- association* (R804), **172**, 172
- assumed type parameter, **20**, 20, 52, 303, 305, 306
- assumed-implied-spec* (R521), **99**, 99, 100
- assumed-rank dummy data object, **4**, 54, 96, 97, 129, 187, 188, 286, 287, 295, 303–305, 310, 316, 375–377, 399, 406, 408, 414, 457, 467, 469, 568, 569, 571
- assumed-rank-spec* (R525), 97, **100**
- assumed-shape array, **2**, 54, 96, 98, 129, 287, 291, 292, 303–305, 307, 310, 316, 457, 467, 469, 552, 568, 574, 576
- assumed-shape-spec* (R519), 97, **98**, 98
- assumed-size array, **2**, 99, 100, 105, 116, 125, 126, 137, 154, 157, 177, 188, 189, 223, 303, 304, 309, 377, 405, 406, 408, 414, 462, 466, 471, 478, 563, 565, 567
- assumed-size-spec* (R522), 97, **99**, 99
- assumed-type, **4**, 53, 54, 303, 316, 467, 570
- ASYNCHRONOUS attribute, **93**, 93, 94, 107, 173, 221, 280, 282, 286, 287, 304, 305, 482, 492
- asynchronous communication, 93, **485**
- asynchronous input/output, 93, 212, 214, 216, 220–222, 225, 226, 233, 236, 237, 239, 241, 243, 244
- ASYNCHRONOUS statement, **107**, 174, 284, 490, 492
- asynchronous-stmt* (R531), 31, **107**
- ASYNCHRONOUS= specifier, 213, **214**, 218, 219, **220**, 240, **241**
- ATAN, **341**
- ATAN2, 26, **342**
- ATANH, **342**
- atomic subroutine, **19**, 194, 195, 325, 328, 329, 343–347, 361
- ATOMIC_ADD, **343**, 418
- ATOMIC_AND, **343**
- ATOMIC_CAS, **343**
- ATOMIC_DEFINE, **344**, 560, 561
- ATOMIC_FETCH_ADD, **344**
- ATOMIC_FETCH_AND, **345**
- ATOMIC_FETCH_OR, **345**
- ATOMIC_FETCH_XOR, **345**
- ATOMIC_INT_KIND, 343–347, **417**
- ATOMIC_LOGICAL_KIND, 343, 344, 346, **417**
- ATOMIC_OR, **346**
- ATOMIC_REF, **346**, 560, 561
- ATOMIC_XOR, **347**
- attr-spec* (R502), **89**, 89, 91, 112
- attribute, **4**, 53, 62, 66, 89, 91–106, 282
- ABSTRACT, 19, 63, **79**
 - accessibility, **92**, 106, 280
 - ALLOCATABLE, 2, 52–54, 62, 68, 69, 92, **93**, 93–95, 98, 103, 105, 107, 123, 126, 188, 284, 287, 294, 295, 305, 309, 316, 324, 466, 494, 500, 501, 555, 559
 - ASYNCHRONOUS, **93**, 93, 94, 107, 173, 221, 280, 282, 286, 287, 304, 305, 482, 492
 - BIND, 3, 4, 37, 63–65, 79, **84**, **94**, 94, 107, 116, 118, 162, 163, 190, 284, 286, 287, 315, 317, 419, 465, 467, 481–484, 494, 501, 563
 - CODIMENSION, 54, 69, 90, **94**, 94, 100, 108
 - CONTIGUOUS, 69, 71, **96**, 96, 97, 108, 128, 129,

- 163, 286, 303–307, 310, 467, 469, 498
- DEFERRED, **75**, **76**, **79**
- DIMENSION, **69**, **90**, **97**, **97**, **110**, **118**
- EXTENDS, **19**, **79**, **79**, **465**
- EXTERNAL, **14**, **24**, **25**, **100**, **100**, **103**, **111**, **113**,
115, **163**, **280**, **284**, **286**, **289**, **296**, **308**, **313**,
314, **492**, **493**, **550**
- INTENT, **100**, **100–102**, **110**
- INTENT (IN), **100**, **101**, **102**, **105**, **177**, **293–295**,
303, **306**, **308**, **310**, **322**, **323**, **326**, **343–347**, **361**,
362, **366**, **367**, **390**, **397**, **398**, **431**, **459–461**, **481**,
552, **565**
- INTENT (INOUT), **100**, **101**, **102**, **105**, **294**, **304**,
306, **312**, **323**, **324**, **343–347**, **362**, **366–368**, **389**,
390, **418**, **420**, **506**, **565**
- INTENT (OUT), **26**, **54**, **77**, **78**, **99**, **100**, **100–102**,
105, **135**, **154**, **294**, **304**, **306**, **312**, **322–324**,
343–347, **354**, **356**, **361**, **362**, **366**, **367**, **389**,
397, **398**, **410**, **411**, **433**, **434**, **459**, **461**, **481**,
482, **495–497**, **502–506**, **565**
- INTRINSIC, **100**, **102**, **102**, **103**, **280**, **298**, **313**, **493**
- NON_OVERRIDABLE, **75**, **76**
- OPTIONAL, **103**, **103**, **111**, **154**, **173**, **177**, **287**, **316**
- PARAMETER, **7**, **37**, **85**, **91**, **103**, **103**, **111**, **122**
- PASS, **69**, **71**, **76**, **299**
- POINTER, **2**, **14**, **52–54**, **62**, **68–70**, **90**, **92**, **98**, **100**,
103, **103**, **105**, **110**, **111**, **123**, **126**, **134**, **162**,
173, **188**, **285–287**, **289**, **294**, **295**, **297**, **305**,
308–311, **316**, **323**, **324**, **462**, **466**, **481**, **494**, **497**,
500, **501**, **555**, **559**
- PRIVATE, **65**, **80**, **92**, **92**, **93**, **106**, **116**, **323**, **539**
- PROTECTED, **104**, **104**, **112**, **117**, **281**
- PUBLIC, **80**, **92**, **92**, **93**, **106**, **116**, **539**
- SAVE, **16**, **21**, **27**, **72**, **79**, **91**, **94**, **95**, **104**, **104**, **105**,
108, **112**, **117**, **119**, **135**, **297**, **322**, **496**
- SEQUENCE, **16**, **63**, **64**, **65**, **66**, **79**, **118**, **162**, **163**,
190, **465**
- TARGET, **3**, **19**, **72**, **103**, **105**, **105**, **112**, **117**, **119**,
133, **134**, **162**, **173**, **188**, **287**, **294**, **303**, **304**, **306**,
310, **311**, **389**, **459**, **462**, **482**, **495–497**, **505**, **552**,
553
- VALUE, **54**, **71**, **77**, **100**, **105**, **105**, **112**, **226**, **286**,
287, **289**, **293**, **294**, **302–304**, **306**, **316**, **322**, **324**,
467, **468**, **485**, **497**, **563**, **565**
- VOLATILE, **105**, **105**, **106**, **113**, **162**, **163**, **173**, **280**,
282, **286**, **287**, **304**, **305**, **307**, **492**, **497**, **503**, **505**,
524
- attribute specification statements, **106–120**
- automatic data object, **4**, **91**, **95**, **105**, **515**
- automatic object, **4**, **91**, **108**, **116**, **118**, **503**
- ## B
- B edit descriptor, **263**
- BACKSPACE statement, **204**, **207**, **233**, **236**, **237**, **238**,
531, **533**
- backspace-stmt* (R924), **31**, **237**, **323**
- base object, **4**, **93**, **96**, **116**, **123**, **129**, **154**, **221**, **309**, **322**,
324
- BESSEL_J0, **347**
- BESSEL_J1, **347**
- BESSEL_JN, **347**
- BESSEL_Y0, **348**
- BESSEL_Y1, **348**
- BESSEL_YN, **348**
- BGE, **349**
- BGT, **349**
- binary-constant* (R465), **86**, **86**
- BIND (C), *see* BIND attribute
- BIND attribute, **3**, **4**, **37**, **63–65**, **79**, **84**, **94**, **94**, **107**,
116, **118**, **162**, **163**, **190**, **284**, **286**, **287**, **315**,
317, **419**, **465**, **467**, **481–484**, **494**, **501**, **563**
- BIND statement, **107**, **284**, **483**, **489**
- bind-entity* (R533), **107**, **107**
- bind-stmt* (R532), **31**, **107**
- binding, **4**, **75**, **76**, **76**, **80**, **81**, **150**, **161**, **230**, **235**, **295**,
315, **488**, **489**
- binding label, **4**, **94**, **287**, **297**, **316**, **318**, **483–485**, **487**,
488
- binding name, **4**, **75**, **76**, **80**, **299**, **489**
- binding-attr* (R452), **75**, **76**, **76**
- binding-name*, **75**, **76**, **299**, **315**, **489**
- binding-private-stmt* (R447), **75**, **75**, **77**
- bit model, **327**
- BIT_SIZE, **327**, **350**, **390**
- blank common, **6**, **90**, **108**, **118**, **119**, **497**, **499**
- blank interpretation mode, **214**
- blank-interp-edit-desc* (R1018), **253**, **254**
- BLANK= specifier, **213**, **214**, **218**, **219**, **221**, **233**, **240**,
241, **268**
- BLE, **350**
- block, **4**
- interface, **281**

- block* (R801), 4, **171**, 172, 173, 175–179, 182, 183, 185, 187, 190
- BLOCK construct, 16, 35, 37, 78, 91, 93, 96, 98, 104, 106, 113, 115, 134, 154, **173**, 322, 490, 496, 497, 503, 505, 508
- block data program unit, **283**
- BLOCK DATA statement, 47, 279, **283**
- block scoping unit, 12, **16**
- BLOCK statement, 91, 96, 98, **173**, 503
- block-construct* (R807), 31, **173**, 174
- block-construct-name*, 173, 174
- block-data* (R1120), 29, **283**, 284, 290
- block-data-name*, 283
- block-data-stmt* (R1121), 29, **283**, 283
- block-specification-part* (R809), 17, 173, **174**, 174
- block-stmt* (R808), 4, **173**, 173, 174, 192
- BLT, **350**
- BN edit descriptor, 268
- bound, 2, 4, 4, 39, 40, 68, 69, 81, 84, 98, 130, 131, 136, 163, 389
- bounds, 97–100, 125–128
- bounds-remapping* (R736), 161, **162**, 162–164
- bounds-spec* (R735), 161, **162**, 162, 164
- boz-literal-constant* (R464), 45, **86**, 86, 110, 263, 327, 349, 350, 352, 357–359, 370, 372–374, 385, 386, 399
- branch, **192**, 320, 513
- branch target statement, 4, 34, 46, 166, 180, **192**, 192, 193, 213, 217, 218, 236, 237, 239, 241, 300, 320
- BTEST, **351**
- BZ edit descriptor, 268
- C**
- C address, 5, 459–462, 464, 465, 470, 474, 475, 477, 504, 505, 565
- C descriptor, 5, 135, 468–482
- C_ALERT, **458**
- C_ASSOCIATED, **458**
- C_BACKSPACE, **458**
- C_BOOL, **457**, **458**
- C_CARRIAGE_RETURN, **458**
- C_CHAR, **458**
- C_DOUBLE, **457**
- C_DOUBLE_COMPLEX, **458**
- C_F_POINTER, 458, **459**
- C_F_PROCPOINTER, **461**
- C_FLOAT, **457**
- C_FLOAT_COMPLEX, **458**
- C_FORM_FEED, **458**
- C_FUNLOC, **461**, 461, 484
- C_FUNPTR, 68, 79, 94, 123, 131, 160, 457, 458, 461, 464, 465, 505
- C_HORIZONTAL_TAB, **458**
- C_INT, **457**
- C_INT16_T, **457**
- C_INT32_T, **457**
- C_INT64_T, **457**
- C_INT8_T, **457**
- C_INT_FAST16_T, **457**
- C_INT_FAST32_T, **457**
- C_INT_FAST64_T, **457**
- C_INT_FAST8_T, **457**
- C_INT_LEAST16_T, **457**
- C_INT_LEAST32_T, **457**
- C_INT_LEAST64_T, **457**
- C_INT_LEAST8_T, **457**
- C_INTMAX_T, **457**
- C_INTPTR_T, **457**
- C_LOC, 54, 100, 323, **462**
- C_LONG, **457**
- C_LONG_DOUBLE, **457**
- C_LONG_DOUBLE_COMPLEX, **458**
- C_LONG_LONG, **457**
- C_NEW_LINE, **458**
- C_NULL_CHAR, **458**
- C_NULL_FUNPTR, 457, **458**
- C_NULL_PTR, 457, **458**
- C_PTR, 68, 79, 94, 123, 131, 160, 457–459, 462, **464**, 465, 468, 504, 505, 563
- C_SHORT, **457**
- C_SIGNED_CHAR, **457**
- C_SIZE_T, **457**
- C_SIZEOF, 154, **462**
- C_VERTICAL_TAB, **458**
- CALL statement, 19, 192, 194, 285, **299**, 312, 320, 389
- call-stmt* (R1222), 31, **299**, 300, 302
- CASE statement, **185**
- case-construct* (R835), 31, **185**, 185
- case-construct-name*, 185
- case-expr* (R839), **185**, 185
- case-selector* (R840), **185**, 185
- case-stmt* (R837), **185**, 185
- case-value* (R842), **185**, 185

- case-value-range* (R841), **185**, 185
- CEILING, **351**
- CFI_address, **474**
- CFI_allocate, **475**, 481
- CFI_cdesc_t, **5**, 467–469, **470**, 470–472, 474–480, 482
- CFI_deallocate, **472**, **476**, 481
- CFI_establish, **476**
- CFI_is_contiguous, **478**
- CFI_section, **478**
- CFI_select_part, **479**
- CFI_setpointer, **480**
- changeable mode, 210
- CHAR, **61**, **351**
- char-length* (R423), **59**, 59, 60, 68, 69, 89–91, 516
- char-literal-constant* (R424), 45, 49, 50, **60**, 232, 253, 254, 507
- char-selector* (R421), 55, **59**, 60
- char-string-edit-desc* (R1021), 252, **254**
- char-variable* (R605), **121**, 121, 209, 210
- character context, **5**, 43, 47–49, 61
- character literal constant, **60**
- character sequence type, **17**, **65**, 117, 119, 499, 502
- character set, 43
- character storage unit, **18**, 18, 99, 117, 119, 417, 498, 502, 504
- character string edit descriptor, **252**, 269
- character type, 59–62
- CHARACTER_KINDS, **417**
- CHARACTER_STORAGE_SIZE, **417**
- characteristics, **5**, 80, 164, 230, 231, 286, 287, 289, 297, 298, 308, 312, 316, 317, 319, 336, 392
- dummy argument, 286
- procedure, 286
- child data transfer statement, 208, 209, 220–222, 225, 229, 229–233, 248, 272
- CLASS, **53**, 53, 54, 230
- CLASS DEFAULT statement, **190**
- CLASS IS statement, **190**
- CLOSE statement, 204, 205, 209, 211, 212, **216**, 216, 233, 236, 531
- close-spec* (R909), **217**, 217
- close-stmt* (R908), 31, **217**, 323
- CMPLX, 159, 327, **352**, 425
- coarray, **5**, 5, 7, 35, 39, 40, 64, 68, 70, 78, 94–96, 101, 103, 105, 106, 116, 118, 129–132, 135, 136, 157, 160, 162, 163, 173, 177, 194, 195, 199, 280, 287, 299, 307, 332, 334, 343–347, 353, 372, 377, 389, 411, 412, 414, 415, 419, 466
- coarray-name*, 108, 492
- coarray-spec* (R509), 68–70, 89, 90, **94**, 94, 95, 107, 108, 112
- cobound, **5**, 39, 40, 94–96, 129, 132, 173, 307, 332, 334, 377, 389, 414, 415
- codimension, **5**, 5, 7, 39, 96, 129, 173, 286, 353, 377, 415
- CODIMENSION attribute, 54, 69, 90, **94**, 94, 100, 108
- codimension-decl* (R535), 107, **108**
- codimension-stmt* (R534), 31, **107**, 492
- coindexed object, **5**, 39, 108, 123, 129, 157, 160, 162, 163, 172, 200, 299, 300, 303–306, 322, 343–347, 361, 459, 461, 462
- coindexed-named-object* (R614), 121, 122, **124**, 124
- collating sequence, **5**, 61, 62, 149, 256, 337, 351, 369, 372, 379, 380, 383–388, 391, 507
- COMMAND_ARGUMENT_COUNT, 156, **352**, 367
- comment, **48**, **49**, 276
- common association, **119**
- common block, **6**, 27, 32, 37, 90, 91, 94, 104, 105, 107, 108, 116, 118–120, 154, 283, 284, 482, 483, 487–490, 494, 497–499, 504, 516
- common block storage sequence, **119**
- COMMON statement, 6, **118**, 118–120, 174, 282, 284, 489, 499, 514
- common-block-name*, 107, 112, 118, 174, 282
- common-block-object* (R573), **118**, 118, 282, 492
- common-stmt* (R572), 31, **118**, 492
- companion processor, 4, **5**, **6**, 12, 35, 41, 63, 85, 94, 457, 462, 483–485, 507
- compatibility
- FORTTRAN 77, 26
 - Fortran 2003, 25
 - Fortran 2008, 25
 - Fortran 90, 26
 - Fortran 95, 26
- COMPILER_OPTIONS, 154, **417**
- COMPILER_VERSION, 154, **417**
- completion step, 35, 217
- complex part designator, **8**, 37, 124
- complex type, 58
- complex-literal-constant* (R418), 45, **58**
- complex-part-designator* (R615), 121, **124**, 124, 125, 129
- component, **6**, 8, 12, 13, 17, 18, 63–65, **68**, 113, 489

- direct, **6**, **6**, **62**, **63**, **72**, **304**, **424**, **464**
- parent, **3**, **6**, **74**, **78**, **80**, **83**, **500**, **525**
- potential subobject, **6**, **62–64**, **323**
- ultimate, **6**, **62–64**, **68**, **94**, **96**, **99**, **100**, **105**, **116**, **118**, **131**, **133**, **156**, **229**, **303**, **498**
- component definition statement, **68**
- component keyword, **13**, **40**, **74**, **82**, **83**, **489**
- component order, **6**, **74**, **83**, **224**
- component-array-spec* (R440), **68**, **68**, **69**
- component-attr-spec* (R438), **68**, **68–70**, **72**
- component-data-source* (R458), **82**, **82**, **83**
- component-decl* (R439), **60**, **68**, **68–70**, **72**
- component-def-stmt* (R436), **6**, **68**, **68**, **69**
- component-initialization* (R443), **68**, **71**, **71**, **72**
- component-name*, **68**, **72**
- component-part* (R435), **63**, **68**, **74**, **77**
- component-spec* (R457), **82**, **82**, **155**
- computed GO TO statement, **4**, **192**, **193**, **514**, **515**
- computed-goto-stmt* (R853), **32**, **193**, **193**
- concat-op* (R711), **45**, **139**, **139**
- CONCURRENT, **176**
- concurrent-control* (R821), **167**, **169**, **176**, **177**, **177**, **178**
- concurrent-header* (R820), **168**, **169**, **176**, **176**, **177**, **490**
- concurrent-limit* (R822), **143**, **169**, **177**, **177**, **178**
- concurrent-locality* (R824), **176**, **177**
- concurrent-step* (R823), **143**, **169**, **177**, **177**, **178**
- conformable, **6**, **38**, **132**, **143**, **150**, **157**, **161**, **312**, **324**, **364**, **369**, **370**, **374**, **383**, **384**, **386**, **387**, **394**, **396**, **410**, **415**, **444**, **445**
- CONJG, **352**
- connect-spec* (R905), **212**, **212**, **213**
- connected, **6**, **10**, **13**, **15**, **204–208**, **211–213**, **215–217**, **222**, **226**, **228**, **229**
- connection mode, **210**
- constant, **6**, **37**, **38**, **45**, **51**
 - integer, **55**
 - named, **111**
- constant* (R304), **45**, **45**, **109**, **122**, **137**
- constant expression, **4**, **7**, **20**, **26**, **51**, **52**, **60**, **67**, **69**, **70**, **72**, **87**, **91**, **96**, **98**, **99**, **108**, **109**, **111**, **117**, **154**, **155**, **156**, **156**, **220**, **286**, **287**, **309**, **326**, **337–339**, **351**, **352**, **354**, **364**, **365**, **369**, **372**, **373**, **376–378**, **381–383**, **386**, **391**, **399**, **401**, **403**, **405**, **408**, **409**, **414–416**, **466**
- constant-expr* (R729), **20**, **52**, **71**, **72**, **90**, **91**, **99**, **100**, **103**, **111**, **156**, **156**, **185**
- constant-subobject* (R547), **109**, **109**
- construct
 - ASSOCIATE, **171**, **172**, **187**, **309**, **490**, **491**, **506**
 - BLOCK, **xvii**, **12**, **16**, **17**, **35**, **37**, **78**, **91**, **93**, **96**, **98**, **104**, **106**, **113**, **115**, **134**, **154**, **171**, **173**, **322**, **490**, **496**, **497**, **503**, **505**, **508**
 - CRITICAL, **171**, **175**, **175**, **179**, **192**
 - DO, **35**, **46**, **87**, **171**, **176**, **192**, **224**, **513**, **527**, **528**
 - DO CONCURRENT, **xvi**, **78**, **176**, **179**, **183**, **192**, **323**, **490**, **491**, **497**, **503**, **505**, **508**, **516**
 - FORALL, **167**, **323**, **490**, **491**, **503**, **514**, **516**
 - IF, **35**, **171**, **183**, **431**, **513**
 - nonblock DO, **xvi**, **514**
 - SELECT CASE, **35**, **171**, **185**, **514**, **515**, **527**
 - SELECT RANK, **xvi**, **35**, **99**, **100**, **171**, **187**, **309**
 - SELECT TYPE, **35**, **52**, **53**, **171**, **189**, **309**, **490**, **491**, **506**
 - WHERE, **14**, **165**
- construct association, **3**, **3**, **134**, **136**, **491**, **494**, **497**, **500**
- construct entity, **3**, **7**, **106**, **172**, **174**, **181**, **189**, **487**, **488**, **490**, **497**
- construct-name*, **192**
- constructor
 - array, **86**
 - derived-type, **82**
 - structure, **82**
- CONTAINS statement, **33**, **34**, **75**, **320**
- contains-stmt* (R1244), **30**, **75**, **280**, **320**
- contiguous, **7**, **17**, **65**, **71**, **96**, **122**, **129**, **163**, **165**, **173**, **221**, **228**, **375**, **462**, **498**
- CONTIGUOUS attribute, **69**, **71**, **96**, **96**, **97**, **108**, **128**, **129**, **163**, **286**, **303–307**, **310**, **467**, **469**, **498**
- CONTIGUOUS statement, **108**
- contiguous-stmt* (R536), **31**, **108**
- continuation, **48**, **49**
- CONTINUE statement, **193**, **513**
- continue-stmt* (R854), **31**, **177**, **193**
- control character, **43**, **60**, **203**, **206**
- control edit descriptor, **252**, **266–269**
- control information list, **218**
- control mask, **166**
- control-edit-desc* (R1013), **252**, **253**
- conversion
 - numeric, **159**
- corank, **7**, **39**, **40**, **70**, **94**, **95**, **97**, **123**, **129**, **130**, **137**, **173**, **286**, **306**, **353**, **372**, **377**, **389**, **411**, **412**, **415**

- COS, **353**
 COSH, **353**
 COSHAPE, **353**
 cosubscript, **7**, **39**, **96**, **129**, **332**, **334**, **372**, **411**, **412**, **415**
cosubscript (R625), **123**, **129**, **129**
 COUNT, **326**, **354**
 CPU_TIME, **354**
 CRITICAL construct, **175**, **179**, **192**
 CRITICAL statement, **151**, **175**, **194**
critical-construct (R811), **31**, **175**, **175**
critical-construct-name, **175**
critical-stmt (R812), **4**, **175**, **175**, **192**
 CSHIFT, **355**
 current record, **207**
 CYCLE statement, **172**, **176**, **179**, **180**, **516**
cycle-stmt (R828), **31**, **179**, **179**
- ## D
- d* (R1010), **253**, **253**, **258–262**, **265**, **266**, **272**
 D edit descriptor, **259**
 data edit descriptor, **252**, **256–266**
 data entity, **5**, **6**, **7**, **14–16**, **21**, **37–39**
 data object, **4–6**, **7**, **7–9**, **16**, **18**, **21**, **32–34**, **37**, **38**, **40**
 data object designator, **9**, **16**, **38**, **121**
 data object reference, **16**, **38**, **40**
 data pointer, **14**, **14**, **39**, **459**, **471**, **498**
 DATA statement, **27**, **34**, **86**, **91**, **108**, **119**, **284**, **392**,
490, **493**, **501**, **514**, **515**
 data transfer, **227**
 data transfer input statement, **217**
 data transfer output statement, **217**
 data transfer statement, **27**, **46**, **203–209**, **211**, **217**, **222**,
225–227, **232**, **236**, **238**, **246–249**, **251**, **252**, **263**,
268, **270–272**, **274**, **276**, **419**, **502**, **504**, **509**, **510**,
531, **532**, **535**, **536**
 data type, **19**, *see* type
data-component-def-stmt (R437), **68**, **68–70**
data-edit-desc (R1007), **252**, **253**
data-i-do-object (R541), **108**, **108**, **109**
data-i-do-variable (R542), **108**, **108**, **109**, **156**, **490**
data-implied-do (R540), **108**, **108**, **109**, **156**, **490**
data-pointer-component-name, **162**
 data-pointer-initialization compatible, **71**
data-pointer-object (R734), **161**, **162**, **162**, **163**, **168**,
341, **506**
data-ref (R611), **4**, **122**, **123–125**, **162**, **221**, **299**, **302**,
309, **315**
data-stmt (R537), **30**, **108**, **289**, **322**, **492**
data-stmt-constant (R545), **86**, **109**, **109**, **110**
data-stmt-object (R539), **108**, **108–110**
data-stmt-repeat (R544), **109**, **109**
data-stmt-set (R538), **108**, **108**
data-stmt-value (R543), **108**, **109**, **109**
data-target (R737), **82**, **83**, **104**, **161**, **162**, **162**, **163**, **168**,
309, **322**, **341**, **497**
 DATE_AND_TIME, **356**
 DBLE, **327**, **357**
 DC edit descriptor, **269**
dealloc-opt (R641), **134**, **134**, **135**
 DEALLOCATE statement, **134**, **136**, **194**, **418**, **476**, **508**
deallocate-stmt (R640), **31**, **134**, **506**
 decimal edit descriptor, **269**
 decimal edit mode, **214**
 decimal symbol, **7**, **214**, **221**, **241**, **256–262**, **269**, **270**
decimal-edit-desc (R1020), **253**, **254**
 DECIMAL= specifier, **213**, **214**, **218**, **219**, **221**, **233**,
240, **241**, **269**
 declaration, **7**, **33**, **89–120**
declaration-construct (R207), **30**, **30**, **174**
declaration-type-spec (R403), **53**, **53**, **60**, **68**, **69**, **89**, **91**,
113, **154**, **296**, **297**, **315**, **318**
 declared type, **19**, **54**, **71**, **83**, **87**, **123**, **124**, **131**, **134**, **150**,
152, **157**, **160–163**, **172**, **190**, **191**, **235**, **294**, **299**,
302, **305**, **315**, **321**, **363**, **389**, **402**, **491**
 DEFAULT, **177**, **185**, **190**
 default character, **59**
 default complex, **58**
 default initialization, **7**, **8**, **70–73**, **82–84**, **91**, **99**, **100**,
108, **117**, **118**, **120**, **304**, **392**, **495**, **499**, **500**,
504
 default real, **57**
default-char-constant-expr (R730), **94**, **156**, **156**, **218**,
219
default-char-expr (R725), **152**, **152**, **156**, **193**, **212–222**
default-char-variable (R606), **121**, **121**, **130**, **213**, **240–**
245
 default-initialized, **8**, **72**, **92**, **101**, **495–497**, **501**, **503–505**
 DEFERRED attribute, **75**, **76**, **79**
 deferred type parameter, **20**, **20**, **52**, **60**, **84**, **103**, **119**,
124, **130**, **131**, **133**, **136**, **157**, **158**, **163**, **286**, **305**,
306, **378**, **392**, **409**, **459**, **461**, **467**, **495**, **500**
deferred-coshape-spec (R510), **68**, **94**, **95**, **95**
 deferred-shape array, **2**, **98**

- deferred-shape-spec* (R520), 2, 68, 97, **98**, 98, 111
- definable, **8**, 101–104, 128, 158, 173, 223, 302, 304, 306, 311, 497, 506
- defined, **8**, 8, 21, 38, 40
- defined assignment, **8**, 19, 157, 160, 161, 165, 169, 285, 294, 299, 304, 323
- defined assignment statement, **161**, 312, 505
- defined input/output, **8**, 210, 215, 223–225, **229**, **229**, **229**, **229**, **230**, **230**, **231**, **232**, **233**, 229–235, 246, 266, 272, 273, 277, 285, 292, 295, 299, 312, 323, 419, 509, 510, 556
- defined operation, **8**, 141, **150**, 151–153, 177, 285, 293, 299, 312, 323
- defined-binary-op* (R723), 14, 46, **140**, 140, 141, 150, 281
- defined-io-generic-spec* (R1209), 8, 76, 229–231, 235, **288**, 288, 292, 295
- defined-operator* (R309), **46**, 75, 282, 288
- defined-unary-op* (R703), 14, 46, **138**, 138, 141, 150, 281
- definition, **8**, 8
- definition of variables, 501
- deleted features, 24, 26, 27, 513, 514
- DELIM= specifier, 213, **214**, 218, 219, **221**, 233, 240, **242**, 275, 277, 533
- delimiter mode, 214
- derived type, 8, 18, **19**, 36, 40, 51, 62–84, 87, 465
- derived type definition statement, *see* TYPE statement
- derived type determination, 65
- derived-type type specifier, 53
- derived-type-def* (R426), 30, 53, **63**, 64, 67, 465
- derived-type-spec* (R454), 20, 53, 60, **81**, 82, 190, 230, 489
- derived-type-stmt* (R427), **63**, 63, 64, 67, 92, 492
- descendant, **8**, 33, 64, 74, 75, 77, 104, 283, 488
- designator, 5, **8**, 9, 40, 99, 100, 105, 108, 116, 118, **125**, 125, 154, 155, 274, 304, 308, 309, 322, 324
 - data object, 121
- designator* (R601), 71, 72, 108, 109, **121**, 121, 123–125, 137, 162, 172, 273, 322
- designator*, 137
- digit*, 22, **43**, 43, 46, 56, 86, 270
- digit-string* (R411), 55, **56**, 56, 57, 257, 258, 264
- digit-string*, 56
- DIGITS, **357**
- DIM, **357**
- DIMENSION attribute, 69, 90, **97**, 97, 110, 118
- DIMENSION statement, **110**, 284
- dimension-spec* (R514), **97**
- dimension-stmt* (R548), 31, **110**, 492
- direct access, **205**
- direct access data transfer statement, **222**
- direct component, **6**, 6, 62, 63, 72, 304, 424, 464
- DIRECT= specifier, 240, **242**
- disassociated, 8, **9**, 21, 39, 54, 71–73, 91, 98, 110, 133–136, 153, 161, 163, 297, 309, 325, 333, 363, 392, 393, 402, 409, 429, 495–497, 505
- distinguishable, **295**
- DO CONCURRENT construct, 78, **176**, 179, 183, 192, 323, 490, 491, 497, 503, 505, 508, 516
- DO CONCURRENT statement, 168, **176**
- DO construct, 35, 46, 87, **176**, 192, 224, 513, 527, 528
- DO statement, **176**, 502, 514, 516
- DO WHILE statement, **176**
- do-construct* (R814), 31, **176**, 177, 179, 192
- do-construct-name*, 176, 177, 179
- do-stmt* (R815), 4, **176**, 176, 177, 192, 506
- do-variable* (R819), 87, 108, **176**, 176, 178, 223, 246–249, 271, 502, 504, 506, 532
- DOT_PRODUCT, **357**
- DOUBLE PRECISION, 47, 55, **57**, 63
- DP edit descriptor, 269
- DPROD, **358**
- DSHIFTL, **358**
- DSHIFTR, **359**
- DT edit descriptor, 266
- dtv-type-spec* (R921), **230**
- dummy argument, 2, 3, 5, **9**, 9, 13–15, 20, 21, 40, 44, 52–54, 59, 60, 66, 69, 71, 76–78, 80, 82, 84, 90, 92, 94, 95, 98–103, 105, 108, 110–112, 116, 118, 130, 132, 133, 135, 150, 153, 154, 161, 195, 226, 231–233, 285–289, 291–296, 298, 299, 301–309, 319, 320, 322, 324, 418, 467–469, 489, 490, 497, 506, 541
 - characteristics of, 286
 - restrictions, 309
- dummy data object, 4, 5, **9**, 54, 71, 91, 99–101, 105, 286, 293–295
 - assumed-rank, 4, 54, 96, 97, 129, 187, 188, 286, 287, 295, 303–305, 310, 316, 375–377, 399, 406, 408, 414, 457, 467, 469, 568, 569, 571
- dummy function, **9**, 60, 90
- dummy procedure, 5, **9**, 11, **15**, 100, 113, 155, 163, 285,

286, 288, 289, 291, 292, 295–297, 300, 308, 314,
316, 318, 322, 484, 488, 493
dummy-arg (R1237), **318**, 318–320
dummy-arg-name (R1232), 110–112, 285, 316, **317**, 317,
318, 321, 492
dynamic type, 14, **19**, 21, 54, 78, 79, 81, 84, 87, 105,
131, 132, 134, 136, 150, 152, 158, 160, 161,
163, 173, 189, 190, 198, 235, 299, 305, 315,
333, 363, 389, 402, 409, 468, 491, 495, 500,
526, 567

E

e (R1011), **253**, 253, 259–262, 265, 266, 272

E edit descriptor, 259

edit descriptor, **252**

/, 267

;, 267

A, 264

B, 263

BN, 268

BZ, 268

character string, **252**, 269

control, **252**, 266–269

D, 259

data, **252**, 256–266

DC, 269

decimal, 269

DP, 269

DT, 266

E, 259

EN, 260

ES, 261

EX, 262

F, 258

G, 264, 265

H, **513**

I, 257

L, 264

O, 263

P, 268

position, 266

RC, 268

RD, 268

RN, 268

round, 268

RP, 268

RU, 268

RZ, 268

S, 268

SP, 268

SS, 268

T, 267

TL, 267

TR, 267

X, 267

Z, 263

effective argument, 2–4, **9**, 20, 52, 54, 60, 96–101, 195,
302–304, 306, 308, 311, 314, 399, 460, 468, 491,
497, 500, 502, 505

effective item, **9**, 224, 227, 228, 232, 233, 235, 247, 254,
255, 267, 270, 271, 275, 509

effective position, **296**

element sequence, **308**

ELEMENTAL, 10, **315**, 316, 320, 322, 324

elemental, **9**, 19, 38, 60, 78, 80, 150, 156, 161, 164, 165,
167, 285–287, 297, 304, 308, 312, 314, 320, 324,
325, 329, 347, 348, 390, 429, 431

elemental array assignment (FORALL), 167

elemental assignment, **9**, 161

elemental operation, **10**, 143, 153, 167

elemental operator, **10**, 143, 424

elemental procedure, **10**, 39, 153, 163, 297, 300, 309,
313, 315, **324**, 324–326

elemental reference, **10**, 167, 304, 312–315, 324

elemental subprogram, **10**, 315, 316, 324

ELSE IF statement, 47, **183**

ELSE statement, **183**

else-if-stmt (R831), **183**, 183, 184

else-stmt (R832), **183**, 183, 184

ELSEWHERE statement, 47, **165**

elsewhere-stmt (R748), **165**, 165, 166

EN edit descriptor, 260

ENCODING= specifier, 213, **214**, 240, **242**, 509

END ASSOCIATE statement, 47, **172**

END BLOCK DATA statement, 47, **283**

END BLOCK statement, 47, 135, **174**

END CRITICAL statement, 47, 151, **175**, 194

END DO statement, 47, **177**

END ENUM statement, 47, **84**

END FORALL statement, 47, **168**

END FUNCTION statement, 47, **317**

END IF statement, 47, **184**, 513

END INTERFACE statement, 47, **288**

- END MODULE statement, [47](#), [280](#)
- END PROCEDURE statement, [47](#), [319](#)
- END PROGRAM statement, [47](#), [279](#)
- END SELECT statement, [47](#), [185](#), [190](#)
- END statement, [10](#), [34](#), [34](#), [35](#), [47](#), [49](#), [78](#), [79](#), [104](#), [119](#), [134](#), [135](#), [194](#), [460](#), [505](#)
- END SUBMODULE statement, [47](#), [283](#)
- END SUBROUTINE statement, [47](#), [318](#)
- END TYPE statement, [47](#), [64](#)
- END WHERE statement, [47](#), [165](#)
- end-associate-stmt* (R806), [4](#), [172](#), [172](#), [192](#)
- end-block-data-stmt* (R1122), [10](#), [30](#), [34](#), [283](#), [283](#)
- end-block-stmt* (R810), [4](#), [173](#), [174](#), [174](#), [192](#)
- end-critical-stmt* (R813), [4](#), [175](#), [175](#), [192](#)
- end-do* (R826), [176](#), [177](#), [177](#), [179](#)
- end-do-stmt* (R827), [4](#), [177](#), [177](#), [192](#)
- end-enum-stmt* (R463), [84](#), [84](#)
- end-forall-stmt* (R754), [168](#), [168](#)
- end-function-stmt* (R1234), [10](#), [29](#), [31](#), [32](#), [34](#), [184](#), [288](#), [316](#), [317](#), [317](#), [320](#)
- end-if-stmt* (R833), [4](#), [183](#), [184](#), [184](#), [192](#)
- end-interface-stmt* (R1204), [288](#), [288](#)
- end-module-stmt* (R1106), [10](#), [29](#), [34](#), [280](#), [280](#)
- end-mp-subprogram-stmt* (R1241), [10](#), [30–32](#), [34](#), [184](#), [319](#), [319](#), [320](#)
- end-program-stmt* (R1103), [10](#), [29](#), [31](#), [32](#), [34](#), [35](#), [79](#), [184](#), [193](#), [279](#), [279](#)
- end-select-rank-stmt* (R846), [4](#), [187](#), [188](#), [188](#), [192](#)
- end-select-stmt* (R838), [4](#), [185](#), [185](#), [186](#), [192](#)
- end-select-type-stmt* (R850), [4](#), [190](#), [190–192](#)
- end-submodule-stmt* (R1119), [10](#), [29](#), [34](#), [283](#), [283](#)
- end-subroutine-stmt* (R1238), [10](#), [29](#), [31](#), [32](#), [34](#), [184](#), [288](#), [318](#), [318](#), [320](#)
- end-type-stmt* (R430), [63](#), [64](#)
- end-where-stmt* (R749), [165](#), [165](#), [166](#)
- END= specifier, [4](#), [192](#), [218](#), [219](#), [226](#), [236](#), [237](#), [247](#), [535](#)
- endfile record, [204](#)
- ENDFILE statement, [47](#), [204](#), [205](#), [207](#), [214](#), [233](#), [236](#), [238](#), [531](#)
- endfile-stmt* (R925), [31](#), [237](#), [323](#)
- entity-decl* (R503), [60](#), [69](#), [89](#), [90](#), [90](#), [91](#), [155](#), [156](#), [492](#)
- entity-name*, [107](#), [112](#)
- ENTRY statement, [9](#), [34](#), [150](#), [161](#), [280](#), [285](#), [289](#), [315](#), [316](#), [319](#), [489](#), [499](#), [514](#), [516](#)
- entry-name*, [316](#), [319](#), [320](#), [489](#)
- entry-stmt* (R1242), [30](#), [280](#), [283](#), [289](#), [319](#), [319](#), [489](#), [492](#)
- ENUM statement, [84](#)
- enum-def* (R459), [30](#), [84](#), [85](#)
- enum-def-stmt* (R460), [84](#), [84](#)
- enumeration, [84](#)
- enumerator, [84](#)
- enumerator* (R462), [84](#), [84](#)
- ENUMERATOR statement, [84](#)
- enumerator-def-stmt* (R461), [84](#), [84](#)
- EOR= specifier, [4](#), [192](#), [218](#), [219](#), [226](#), [236](#), [237](#), [247](#), [247](#), [532](#), [535](#)
- EOSHIFT, [359](#)
- EPSILON, [360](#)
- equiv-op* (R721), [45](#), [140](#), [140](#)
- equiv-operand* (R716), [140](#), [140](#)
- equivalence association, [117](#)
- EQUIVALENCE statement, [116](#), [116–120](#), [174](#), [282](#), [284](#), [499](#), [514](#), [516](#)
- equivalence-object* (R571), [116](#), [116–118](#), [282](#)
- equivalence-set* (R570), [116](#), [116](#), [117](#)
- equivalence-stmt* (R569), [31](#), [116](#), [492](#)
- ERF, [360](#)
- ERFC, [360](#)
- ERFC_SCALED, [361](#)
- ERR= specifier, [4](#), [192](#), [212](#), [213](#), [217–219](#), [226](#), [236](#), [237](#), [239–241](#), [246](#)
- errmsg-variable* (R629), [130](#), [130](#), [131](#), [134](#), [136](#), [196](#), [506](#), [508](#)
- ERRMSG= specifier, [130](#), [133](#), [134](#), [136](#), [196](#), [202](#), [503](#), [508](#)
- error indicator, [474](#)
- ERROR STOP statement, [35](#), [36](#), [193](#), [508](#)
- error termination, [35](#), [79](#), [132](#), [134](#), [193](#), [202](#), [232](#), [246](#), [247](#), [329](#), [343–347](#), [361](#), [362](#), [400](#), [507](#), [510](#)
- error-stop-stmt* (R856), [31](#), [79](#), [193](#)
- ERROR_UNIT, [210](#), [211](#), [215](#), [418](#)
- ES edit descriptor, [261](#)
- evaluation
- operations, [143](#)
 - optional, [151](#)
 - parentheses, [152](#)
- EVENT POST statement, [194](#), [199](#), [200](#), [202](#), [361](#), [418](#), [503](#), [506](#), [508](#)
- event variable, [21](#), [195](#), [199](#), [200](#), [361](#), [418](#), [503](#)
- EVENT WAIT statement, [194](#), [199](#), [200](#), [202](#), [418](#), [503](#),

- 506, 508
 - event-post-stmt* (R863), 31, **199**
 - event-variable* (R864), **199**, 199, 200, 418, 506
 - event-wait-spec* (R866), **200**, 200
 - event-wait-stmt* (R865), 31, **200**, 200
 - EVENT_QUERY, xvii, **361**, 562
 - EVENT_TYPE, 64, 101, 131, 199, **418**
 - EX edit descriptor, 262
 - executable construct, 171
 - executable statement, **17**, 17, 33
 - executable-construct* (R214), 17, 30, **31**, 319
 - EXECUTE_COMMAND_LINE, 334, **362**
 - execution control, 171
 - execution-part* (R209), 29, **30**, 30, 32, 279, 316–319
 - execution-part-construct* (R210), **30**, 30, 171
 - exist, 204, 211
 - EXIST= specifier, 240, **242**
 - EXIT statement, 172, 180, **192**
 - exit-stmt* (R851), 31, **192**, 192
 - EXP, **362**
 - explicit formatting, 251–269
 - explicit initialization, **10**, 72, 73, 90, 91, 108, 495, 499, 501
 - explicit interface, **10**, 25, 71, 75, 164, 286–290, 292, 297, 299, 301, 308, 321, 322, 488, 489, 506, 540
 - explicit-coshape-spec* (R511), 94, **95**, 95
 - explicit-shape array, **2**, 54, 70, 95, 98, 157, 304, 309, 466
 - explicit-shape-spec* (R516), **2**, 68, 69, 91, **97**, 97–99, 118
 - EXPONENT, **362**, 437
 - exponent* (R417), **57**, 57
 - exponent-letter* (R416), **57**, 57
 - expr* (R722), 23, 78, 82, 83, 87, 130, 137, **140**, 140, 152, 156–163, 167, 168, 172, 185, 222, 299, 300, 321, 323, 453, 505
 - expression, **137**, 137–157
 - constant, **4**, **7**, 20, 26, 51, 52, 60, 67, 69, 70, 72, 87, 91, 96, 98, 99, 108, 109, 111, 117, 154, **155**, **156**, 156, 220, 286, 287, 309, 326, 337–339, 351, 352, 354, 364, 365, 369, 372, 373, 376–378, 381–383, 386, 391, 399, 401, 403, 405, 408, 409, 414–416, 466
 - specification, **17**, 20, 35, 67–69, 78, 93, 125, **154**, **155**, 155, 174, 320, 425, 507, 508, 515
 - extended real model, 328
 - extended type, 3, 6, 12, **19**, 20, 67, 74, 78–80, 500, 517, 523
 - extended-intrinsic-op* (R310), **46**, 46
 - EXTENDS attribute, 19, **79**, 79, 465
 - EXTENDS_TYPE_OF, 68, 69, **363**
 - extensible type, **19**, 53, 63, 71, 79, 230, 363, 402, 525, 558
 - extension operation, 141
 - extension type, **20**, 54, 79, 81, 190, 191, 305, 363, 558
 - extent, **10**, 38
 - EXTERNAL attribute, 14, 24, 25, **100**, 100, 103, 111, 113, 115, 163, 280, 284, 286, 289, 296, 308, 313, 314, 492, 493, 550
 - external file, **10**, 10, 26, 203–208, 210–212, 216, 220, 239, 256, 266, 275, 323, 484, 509, 531, 563
 - external input/output unit, **10**, 487
 - external linkage, 94, **457**, 482–484
 - external procedure, **15**, 24, 32, 75, 100, 113, 163, 199, 285, 286, 288–292, 296, 297, 300, 308, 314, 315, 487, 488, 492, 493, 540, 541, 546, 550
 - EXTERNAL statement, 100, **296**
 - external subprogram, 15, **19**, 32, 285
 - external unit, **10**, 210–212, 226, 232, 233, 243, 248, 418–420, 509, 510
 - external-name*, 296
 - external-stmt* (R1212), 31, **296**
 - external-subprogram* (R203), **29**, 29, 290, 319
- ## F
- F edit descriptor, 258
 - field, **254**
 - file
 - connected, 211
 - external, **10**, 10, 26, 203–208, 210–212, 216, 220, 239, 256, 266, 275, 323, 484, 509, 531, 563
 - internal, **13**, 13, 203, 209, 210, 212, 220, 224, 227, 229, 232, 233, 246, 248, 266, 267, 502, 504, 510
 - file access method, 204–206
 - file connection, 209–217
 - file inquiry statement, **239**
 - file position, 204, 207
 - file positioning statement, 204, **237**
 - file storage unit, **10**, 18, 203, 206–209, 215, 220, 222, 228, 238, 244–246, 418, 498, 508–510
 - file-name-expr* (R906), **213**, 213, 215, 240–242
 - file-unit-number* (R902), **209**, 209, 210, 212, 213, 217, 219, 231, 236, 237, 239–245, 323, 419
 - FILE= specifier, 213, **215**, 240, **241**, 241, 506, 533
 - FILE_STORAGE_SIZE, **418**

- FINAL statement, [10](#), [77](#)
- final subroutine, [4](#), [10](#), [11](#), [25](#), [76–79](#), [128](#), [154](#), [303](#), [522](#), [523](#)
- final-procedure-stmt* (R453), [75](#), [77](#)
- final-subroutine-name*, [77](#)
- finalizable, [11](#), [25](#), [77](#), [78](#), [99](#), [100](#), [135](#)
- finalization, [11](#), [16](#), [77–79](#), [128](#), [168](#), [285](#), [299](#), [312](#), [322](#), [323](#), [507](#)
- FINDLOC, [363](#)
- fixed source form, [48](#), [48](#)
- FLOOR, [365](#)
- FLUSH statement, [205](#), [236](#), [239](#), [248](#)
- flush-spec* (R929), [239](#), [239](#)
- flush-stmt* (R928), [31](#), [239](#), [323](#)
- FMT= specifier, [218](#), [219](#), [248](#)
- FORALL construct, [167](#), [323](#), [490](#), [491](#), [503](#), [514](#), [516](#)
- FORALL statement, [143](#), [169](#), [490](#), [502](#)
- forall-assignment-stmt* (R753), [143](#), [168](#), [168](#), [169](#), [323](#)
- forall-body-construct* (R752), [168](#), [168](#), [169](#)
- forall-construct* (R750), [31](#), [167](#), [168](#), [169](#)
- forall-construct-name*, [168](#)
- forall-construct-stmt* (R751), [4](#), [167](#), [168](#), [168](#), [192](#)
- forall-stmt* (R755), [32](#), [168](#), [169](#), [169](#), [192](#)
- FORM= specifier, [213](#), [215](#), [240](#), [242](#)
- format* (R915), [217](#), [218](#), [219](#), [219](#), [220](#), [227](#), [251](#), [252](#)
- format control, [254](#)
- format descriptor, *see* edit descriptor
- FORMAT statement, [24](#), [34](#), [46](#), [220](#), [251](#), [251](#), [280](#)
- format-item* (R1004), [252](#), [252](#)
- format-items* (R1003), [251](#), [252](#), [252](#)
- format-specification* (R1002), [251](#), [251](#)
- format-stmt* (R1001), [30](#), [251](#), [251](#), [280](#), [283](#), [289](#)
- FORMATTED, [230](#), [231](#), [288](#)
- formatted data transfer, [228](#)
- formatted input/output statement, [203](#), [219](#)
- formatted record, [203](#)
- FORMATTED= specifier, [240](#), [242](#)
- formatting
- explicit, [251–269](#)
 - list-directed, [229](#), [269–273](#)
 - namelist, [229](#), [273–277](#)
- forms, [204](#)
- Fortran 2003 compatibility, [25](#)
- Fortran 2008 compatibility, [25](#)
- FORTRAN 77 compatibility, [26](#)
- Fortran 90 compatibility, [26](#)
- Fortran 95 compatibility, [26](#)
- Fortran character set, [43](#), [59](#)
- FRACTION, [365](#)
- free source form, [47](#), [47](#)
- function, [11](#)
- intrinsic, [325](#)
 - intrinsic elemental, [325](#)
 - intrinsic inquiry, [325](#)
- function reference, [16](#), [37](#), [38](#), [312](#)
- function result, [11](#), [25](#), [60](#), [89](#), [113](#), [116](#), [118](#), [134](#), [286](#), [317](#), [319](#), [324](#), [467](#), [489](#), [499](#), [505](#)
- FUNCTION statement, [9](#), [53](#), [113](#), [150](#), [154](#), [279](#), [315](#), [316](#), [319](#), [320](#), [489](#)
- function-name*, [90](#), [289](#), [316](#), [317](#), [319](#), [321](#), [489](#), [492](#)
- function-reference* (R1221), [82](#), [90](#), [121](#), [137](#), [299](#), [302](#), [312](#)
- function-stmt* (R1230), [29](#), [288](#), [289](#), [316](#), [316](#), [317](#), [489](#), [492](#)
- function-subprogram* (R1229), [18](#), [29](#), [30](#), [280](#), [316](#), [319](#)
- ## G
- G edit descriptor, [264](#), [265](#)
- GAMMA, [365](#)
- generic identifier, [11](#), [12](#), [280](#), [289](#), [292](#), [293](#), [295](#), [314](#), [325](#), [487](#), [492](#)
- generic interface, [12](#), [76](#), [77](#), [80](#), [84](#), [102](#), [150](#), [161](#), [235](#), [281](#), [282](#), [292](#), [292–294](#), [313](#), [488](#), [559](#)
- generic interface block, [12](#), [12](#), [289](#), [292](#)
- generic procedure reference, [295](#)
- GENERIC statement, [75](#), [76](#), [290](#), [292](#), [313](#)
- generic-name*, [75](#), [76](#), [288](#), [489](#), [492](#)
- generic-spec* (R1208), [12](#), [75–77](#), [80](#), [106](#), [150](#), [161](#), [281](#), [282](#), [288](#), [288–290](#), [292](#), [313](#), [489](#), [492](#)
- generic-stmt* (R1210), [30](#), [290](#)
- GET_COMMAND, [365](#)
- GET_COMMAND_ARGUMENT, [366](#)
- GET_ENVIRONMENT_VARIABLE, [367](#), [511](#)
- global entity, [487](#)
- global identifier, [487](#)
- GO TO statement, [4](#), [47](#), [192](#), [193](#)
- goto-stmt* (R852), [31](#), [193](#), [193](#)
- graphic character, [43](#), [60](#), [276](#)
- ## H
- halting mode, [423](#), [427](#), [427](#), [430](#), [431](#), [433](#), [445](#), [449](#), [485](#), [511](#)
- hex-constant* (R467), [86](#), [86](#)

- hex-digit* (R468), **86**, 86, 264
hex-digit-string (R1022), **264**, 264
 host, **11**, 12, 32, 283, 321, 489, 492, 493
 host association, **3**, 3, 14, 33, 53, 60, 93, 106, 108, 113, 119, 154, 155, 163, 283, 285, 309, 321–323, 490–494, 497, 500, 580
 host instance, **11**, 164, 300, 301, 308, 318, 492, 496, 500, 505
 host scoping unit, **11**, 32, 113, 290, 291, 313, 493, 500
 HUGE, **368**
 HYPOT, **368**
- ## I
- I edit descriptor, 257
 IACHAR, 62, 160, **369**
 IALL, **369**
 IAND, 343, **369**
 IANY, **370**
 IBCLR, **370**
 IBITS, **371**
 IBSET, **371**
 ICHAR, 61, **371**
id-variable (R914), **218**, 218
 ID= specifier, 218, 219, **221**, 233, **236**, 240, 241, **242**, 248, 506, 509, 535
 IEEE infinity, **11**
 IEEE NaN, **11**
 IEEE_ALL, **424**
 IEEE_ARITHMETIC, 154, 156, 336, 423–453
 IEEE_AWAY, **426**, 434
 IEEE_CLASS, **431**, 431
 IEEE_CLASS_TYPE, **424**, 431, 452
 IEEE_COPY_SIGN, 428, **432**
 IEEE_DATATYPE, **424**
 IEEE_DENORMAL, **424**
 IEEE_DIVIDE, **424**
 IEEE_DIVIDE_BY_ZERO, **424**
 IEEE_DOWN, **424**, **426**
 IEEE_EXCEPTIONS, 154, 180, 423–453
 IEEE_FEATURES, 423–424
 IEEE_FEATURES_TYPE, **424**
 IEEE_FLAG_TYPE, **424**, 433, 444, 445, 448, 449
 IEEE_FMA, **432**
 IEEE_GET_FLAG, 180, **432**, 453, 454
 IEEE_GET_HALTING_MODE, 180, **433**, 433
 IEEE_GET_MODES, 427, **433**, 433, 445
 IEEE_GET_ROUNDING_MODE, 426, **434**, 434, 446
 IEEE_GET_STATUS, **434**, 434, 446, 454
 IEEE_GET_UNDERFLOW_MODE, **434**, 447
 IEEE_HALTING, **424**
 IEEE_INEXACT, **424**
 IEEE_INEXACT_FLAG, **424**
 IEEE_INF, **424**
 IEEE_INT, **435**
 IEEE_INVALID, **424**
 IEEE_INVALID_FLAG, **424**
 IEEE_IS_FINITE, **435**
 IEEE_IS_NAN, **435**
 IEEE_IS_NEGATIVE, **436**
 IEEE_IS_NORMAL, **436**
 IEEE_LOGB, 428, **436**
 IEEE_MAX_NUM, **437**
 IEEE_MAX_NUM_MAG, **437**
 IEEE_MIN_NUM, **438**
 IEEE_MIN_NUM_MAG, **438**
 IEEE_MODES_TYPE, **424**, 427, 433, 445
 IEEE_NAN, **424**
 IEEE_NEAREST, **424**, **426**
 IEEE_NEGATIVE_DENORMAL, **424**
 IEEE_NEGATIVE_INF, **424**
 IEEE_NEGATIVE_NORMAL, **424**
 IEEE_NEGATIVE_SUBNORMAL, **424**, 424, 431, 435, 436
 IEEE_NEGATIVE_ZERO, **424**
 IEEE_NEXT_AFTER, 428, **439**
 IEEE_NEXT_DOWN, **439**, 439
 IEEE_NEXT_UP, **439**
 IEEE_OTHER, **424**
 IEEE_OTHER_VALUE, **424**
 IEEE_OVERFLOW, **424**
 IEEE_POSITIVE_DENORMAL, **424**
 IEEE_POSITIVE_INF, **424**
 IEEE_POSITIVE_NORMAL, **424**
 IEEE_POSITIVE_SUBNORMAL, **424**, 424, 431, 435
 IEEE_POSITIVE_ZERO, **424**
 IEEE_QUIET_EQ, **440**
 IEEE_QUIET_GE, **440**
 IEEE_QUIET_GT, **441**
 IEEE_QUIET_LE, **441**
 IEEE_QUIET_LT, **441**
 IEEE_QUIET_NAN, **424**
 IEEE_QUIET_NE, **442**
 IEEE_REAL, **442**

- IEEE_REM, 428, 442
- IEEE_RINT, 428, 443
- IEEE_ROUND_TYPE, 424, 434, 435, 443, 445, 446, 450
- IEEE_ROUNDING, 424
- IEEE_SCALB, 428, 443
- IEEE_SELECTED_REAL_KIND, 444
- IEEE_SET_FLAG, 434, 444, 446, 454
- IEEE_SET_HALTING_MODE, 180, 433, 445, 449, 454
- IEEE_SET_MODES, 427, 433, 445, 445
- IEEE_SET_ROUNDING_MODE, 426, 433, 434, 445, 445, 446
- IEEE_SET_STATUS, 426, 434, 446, 446, 454
- IEEE_SET_UNDERFLOW_MODE, 433, 435, 445, 446
- IEEE_SIGNALING_NAN, 424
- IEEE_SIGNBIT, 447
- IEEE_SQRT, 424
- IEEE_STATUS_TYPE, 424, 427, 434, 446, 454
- IEEE_SUBNORMAL, 424
- IEEE_SUPPORT_DATATYPE, 424, 425, 431, 432, 435, 437–443, 445, 446, 447, 447, 451, 452
- IEEE_SUPPORT_DENORMAL, 447
- IEEE_SUPPORT_DIVIDE, 448, 451
- IEEE_SUPPORT_FLAG, 448, 451
- IEEE_SUPPORT_HALTING, 449, 451
- IEEE_SUPPORT_INF, 428, 439, 440, 449, 451, 452
- IEEE_SUPPORT_IO, 449
- IEEE_SUPPORT_NAN, 425, 428, 450, 451, 452
- IEEE_SUPPORT_ROUNDING, 445, 446, 450, 451
- IEEE_SUPPORT_SQRT, 450, 451
- IEEE_SUPPORT_STANDARD, 451
- IEEE_SUPPORT_SUBNORMAL, 428, 429, 431, 439, 448, 451, 451, 452
- IEEE_SUPPORT_UNDERFLOW_CONTROL, 452
- IEEE_TO_ZERO, 424, 426
- IEEE_UNDERFLOW, 424
- IEEE_UNDERFLOW_FLAG, 424
- IEEE_UNORDERED, 428, 452
- IEEE_UP, 424, 426
- IEEE_USUAL, 424
- IEEE_VALUE, 437, 438, 452
- IEOR, 347, 372
- IF construct, 35, 183, 513
- IF statement, 143, 184
- if-construct* (R829), 31, 183, 184
- if-construct-name*, 183, 184
- if-stmt* (R834), 31, 184, 184
- if-then-stmt* (R830), 4, 183, 183, 184, 192
- imag-part* (R420), 58, 58
- image, 1, 11, 11, 34–36, 39, 95, 129, 131, 132, 135, 136, 160, 162, 163, 175, 193–202, 204, 205, 210, 211, 299, 303, 307, 333, 334, 343–347, 354, 356, 368, 372, 373, 389, 393, 397, 410–412, 415, 420, 427, 487, 495, 496, 505
- image control statement, 11, 35, 151, 175, 180, 194, 194–196, 198, 202, 323, 329
- image index, 11, 34, 39, 129, 196, 204, 307, 332, 334, 372, 412, 415, 487
- image-selector* (R624), 5, 7, 123, 124, 129, 273
- image-set* (R861), 196, 196
- IMAGE_INDEX, 372
- imaginary part, 58
- implicit interface, 11, 69, 164, 280, 297–299, 308, 461, 493
- IMPLICIT NONE statement, 113
- IMPLICIT statement, 34, 113, 116, 284
- implicit-none-spec* (R566), 113, 113
- implicit-part* (R205), 30, 30, 174
- implicit-part-stmt* (R206), 30, 30
- implicit-spec* (R564), 113, 113
- implicit-stmt* (R563), 30, 113
- implied-shape array, 99
- implied-shape-or-assumed-size-spec* (R523), 97, 99, 99, 100
- implied-shape-spec* (R524), 97, 100, 100
- IMPORT statement, 34, 290, 493
- import-name*, 290, 291
- import-stmt* (R1211), 30, 174, 290
- IMPURE, 315, 316, 320, 322, 324
- IN, 101
- INCLUDE line, 47, 49
- inclusive scope, 12, 113, 174, 192, 193, 213, 217, 218, 220, 236, 237, 239, 241, 300, 320, 487, 488
- INDEX, 373
- index-name*, 168, 169, 176–179, 490, 491, 503
- inherit, 3, 6, 12, 63, 76, 78–81, 500, 525
- inheritance association, 3, 3, 6, 80, 82, 497, 500
- initial-data-target* (R444), 71, 71, 72, 90, 91, 109, 110
- initial-proc-target* (R1219), 72, 297, 297, 298
- initialization, 91

- default, **7**, **8**, 70–73, 82–84, 91, 99, 100, 108, 117, 118, 120, 304, 495, 499, 500, 504
- explicit, **10**, 72, 73, 90, 91, 108, 495, 499, 501
- initialization* (R505), **90**, 90, 91, 156
- INOUT, **47**, **101**
- input statement, **217**
- input-item* (R916), 217, 218, **222**, 223, 235, 248, 249, 506
- input/output editing, 251–277
- input/output list, 222
- input/output statement, 502
- input/output statements, 203–248
- input/output unit, 13, **21**, 34
- INPUT_UNIT, 210, 211, 215, 232, **419**
- INQUIRE statement, 26, 205, 206, 208, 209, 211, 212, 221, 222, 232, 233, 236, **239**, 248, 249, 419, 502, 504, 506, 510, 531
- inquire-spec* (R931), **240**, 240, 241, 248, 249
- inquire-stmt* (R930), 31, **240**, 323
- inquiry function, **12**, 19, 95, 98, 100, 123, 133, 154, 302, 303, 325–327, 329, 339, 341, 350, 353, 357, 360, 363, 368, 372, 375–378, 383, 386, 390, 395–399, 402, 405, 408, 409, 412, 414, 423, 424, 426–429, 447–452, 458, 461, 462
- inquiry, type parameter, 124
- instance, 318
- INT, **110**, 159, 327, 358, 359, 370, 372, **373**, 374, 386
- int-constant* (R307), **45**, 45, 109
- int-constant-expr* (R731), 55, 59, 66, 67, 84, 85, 108, **156**, 156, 188
- int-constant-name*, 56
- int-constant-subobject* (R546), **109**, 109
- int-expr* (R726), 34, 52, 87, 122, 125, 126, 129, 130, 143, **152**, 152, 154–156, 176–178, 193, 196, 200, 209, 210, 213, 218, 223, 225, 236, 240, 320
- int-literal-constant* (R408), 45, **55**, 55, 59, 252, 253
- int-variable* (R607), **121**, 121, 130, 213, 217–219, 236, 237, 239, 240, 243–247
- int-variable-name*, 176
- INT16, **419**
- INT32, **419**
- INT64, **419**
- INT8, **419**
- integer constant, 55
- integer editing, 257
- integer model, 328
- integer type, 55–56
- integer-type-spec* (R405), **55**, 55, 66, 87, 108, 176, 490
- INTEGER_KINDS, **419**
- INTENT (IN) attribute, **100**, 101, 102, 105, 177, 293–295, 303, 306, 308, 310, 322, 323, 326, 343–347, 361, 362, 366, 367, 390, 397, 398, 431, 459–461, 481, 552, 565
- INTENT (INOUT) attribute, **100**, 101, 102, 105, 294, 304, 306, 312, 323, 324, 343–347, 362, 366–368, 389, 390, 418, 420, 506, 565
- INTENT (OUT) attribute, 26, 54, 77, 78, 99, **100**, 100–102, 105, 135, 154, 294, 304, 306, 312, 322–324, 343–347, 354, 356, 361, 362, 366, 367, 389, 397, 398, 410, 411, 433, 434, 459, 461, 481, 482, 495–497, 502–506, 565
- INTENT attribute, **100**, 100–102, 110
- INTENT statement, **110**, 174
- intent-spec* (R526), 89, **101**, 110, 296
- intent-stmt* (R549), 31, **110**
- interface, **12**, 12, 33, 38, 40, 69, 75, 76, 102, 230, 231, 266, 286, **287**, 299, 308, 312, 313, 319, 321, 322, 467–469, 484, 541
 - abstract, 280, **287**, 289, 297, 316, 488, 492
 - explicit, **10**, 25, 71, 75, 164, 286–290, 292, 297, 299, 301, 308, 321, 322, 488, 489, 506, 540
 - generic, **12**, 76, 77, 80, 84, 102, 150, 161, 235, 281, 282, **292**, 292–294, 313, 488
 - implicit, **11**, 69, 164, 280, 297–299, 308, 461, 493
 - procedure, 287
 - specific, **12**, 235, **289**, 289, 292, 297, 313
- interface block, **12**, 33, 230, 235, 281, 288–292, 313, 541
- interface body, 12, 16, 34, 96, 98, 100, 113, 154, **288**, 288, 316, 319, 321, 469, 489, 492, 541
- INTERFACE statement, **288**, 541
- interface-block* (R1201), 30, **288**, 288
- interface-body* (R1205), **288**, 288, 289
- interface-name* (R1217), 75, 76, 296, **297**, 297
- interface-specification* (R1202), **288**, 288, 289
- interface-stmt* (R1203), **288**, 288, 289, 292, 492
- internal file, **13**, 13, 203, 209, 210, 212, 220, 224, 227, 229, 232, 233, 246, 248, 266, 267, 502, 504, 510
- internal procedure, 11, **15**, 32, 163, 285–288, 300, 308, 314, 316, 318, 484, 488, 489, 492
- internal subprogram, **19**, 32, 34, 113, 285, 313, 492
- internal unit, **13**, 13, 210, 212, 226, 232, 241, 248, 419

- internal-file-variable* (R903), **209**, 209, 210, 219, 248, 506
- internal-subprogram* (R212), **30**, 30
- internal-subprogram-part* (R211), 29, **30**, 30, 279, 316–319
- interoperable, **12**, 84, 85, 94, 316, 321, 459, 461–469, 483, 484
- interoperate, **463**
- intrinsic, 6, 9–12, **13**, 14, 19, 36–39, 41, 52, 54, 78, 86, 100, 287, 313, 314, 416, 488, 490
- intrinsic assignment statement, 83, 93, 135, 136, 153, **157**, 161, 163, 202, 239, 248, 271, 275, 323, 502, 508
- INTRINSIC attribute, 100, **102**, 102, 103, 280, 298, 313, 493
- intrinsic function, **325**
- intrinsic operation, 143–150
- intrinsic procedure, 325–416
- INTRINSIC statement, 284, **298**
- intrinsic subroutines, **325**
- intrinsic type, 6, **20**, 36, 51, 55–62, 468, 472
- intrinsic-operator* (R308), 14, **45**, 46, 138, 140, 143, 144, 150, 293
- intrinsic-procedure-name*, 298, 492
- intrinsic-stmt* (R1220), 31, **298**, 492
- intrinsic-type-spec* (R404), 53, **55**, 60
- io-control-spec* (R913), 217, **218**, 218, 219, 222, 232, 248, 249
- io-implied-do* (R918), 222, **223**, 223, 224, 227, 248, 249, 502, 504, 506, 532
- io-implied-do-control* (R920), **223**, 223, 225
- io-implied-do-object* (R919), **223**, 223, 227
- io-unit* (R901), 21, **209**, 209, 210, 218, 219, 323
- IOLENGTH= specifier, 208, 239, **246**
- iormsg-variable* (R907), **213**, 213, 217, 218, 236, 237, 239, 240, 246–248, 502
- IOMSG= specifier, 212, 213, 217–219, 226, 236, 237, 239–241, 246, 247, **248**, 248, 249, 502, 504, 506, 510
- IOR, **346**, **374**
- IOSTAT= specifier, 25, 212, 213, 217–219, 226, 232, 236, 237, 239–241, 246, **247**, 247–249, 376, 419, 502, 506, 532
- IOSTAT_END, 232, 248, **419**
- IOSTAT_EOR, 232, 248, **419**
- IOSTAT_INQUIRE_INTERNAL_UNIT, 232, 248, **419**, 421
- IPARITY, **374**
- IS_CONTIGUOUS, 54, **375**
- IS_IOSTAT_END, **376**
- IS_IOSTAT_EOR, **376**
- ISHFT, **375**
- ISHFTC, **375**
- ISO 10646 character, **13**, **59**, **62**, 157, 209, 210, 214, 224, 256, 270, 391, 404
- ISO_C_BINDING, 54, 68, 79, 94, 100, 123, 131, 154, 160, 323, 416, 457–464, 504, 505
- ISO_Fortran_binding.h, 469
- ISO_FORTRAN_ENV, 21, 25, 64, 101, 131, 136, 154, 193, 198–200, 202, 208, 210, 215, 226, 231, 232, 248, 343–347, 409, 410, 416–421, 511, 532
- ## K
- k* (R1014), **253**, 253, 260, 265, 268
- keyword, **13**
- argument, 9, **13**, 40, 287, 290, 301, 325, 329, 429, 488, **489**, **490**, 541
 - component, **13**, 40, 74, 82, 83, 489
 - statement, **13**, 40
 - type parameter, **13**, 40, 82
- keyword* (R216), **40**, 40, 81, 82, 299
- KIND, 55–59, 62, 85, 125, 159, 160, **376**
- kind type parameter, **20**, 24, 36, 52, 55–60, 62, 67, 77, 78, 85, 87, 155–157, 159, 273, 294, 303, 357, 419, 457, 458, 463
- kind-param* (R409), **55**, 55–57, 59, 60, 62
- kind-selector* (R406), 23, **55**, 55, 62
- ## L
- L edit descriptor, 264
- label, *see* statement label
- label* (R311), 4, **46**, 46, 176, 177, 193, 213, 217–220, 236, 237, 239–241, 247, 299, 300
- label-do-stmt* (R816), **176**, 176, 177
- language-binding-spec* (R508), 89, **94**, 107, 316
- LBOUND, 54, 158, 164, 173, 188, 304, **376**
- lbracket* (R471), 68, 86, **87**, 89, 90, 107, 108, 112, 129, 130
- LCOBOUND, **377**
- LEADZ, **377**
- left tab limit, **267**
- LEN, 125, **378**
- LEN_TRIM, **378**

- length type parameter, **20**, 20, 36, 52, 71, 87, 103, 158, 303, 378, 462, 463
 - length-selector* (R422), 23, **59**, 59, 60
 - letter*, **43**, 43, 44, 46, 113, 138, 140
 - letter-spec* (R565), **113**, 113
 - level-1-expr* (R702), **138**, 138, 141
 - level-2-expr* (R706), **138**, 138, 139, 141, 142
 - level-3-expr* (R710), **139**, 139
 - level-4-expr* (R712), **139**, 139, 140
 - level-5-expr* (R717), **140**, 140
 - lexical token, 11, **13**, 21, 44, 46
 - LGE, 62, **378**
 - LGT, 62, **379**
 - line, **13**, 47–50
 - linkage association, **3**, 3, 483, 491, **494**, 494
 - list-directed formatting, 229, 269–273
 - list-directed input/output statement, **220**
 - literal constant, **7**, 37, 122
 - literal-constant* (R305), **45**, 45
 - LLE, 62, **379**
 - LLT, 62, **380**
 - LOCAL, 78, **177**, 180, 183, 490
 - local identifier, **487**, 488
 - local procedure pointer, **14**, 318
 - local variable, **14**, **21**, 37, 91, 93, 96, 106, 133, 134, 154, 300, 318
 - local-defined-operator* (R1114), **281**, 281, 282
 - local-name*, 281, 282
 - LOCAL_INIT, 78, **177**, 180, 490
 - locality, 78, **180**, 490
 - locality-spec* (R825), **177**, 177
 - LOCK statement, 194, **200**, 202, 419, 420, 503, 506
 - lock variable, **21**, 202, 419–421, 503
 - lock-stat* (R869), **200**, 200
 - lock-stmt* (R868), 31, **200**
 - lock-variable* (R871), **200**, 200, 420, 506
 - LOCK_TYPE, 64, 101, 131, 200, **419**
 - LOG, 26, **380**
 - LOG10, **381**
 - LOG_GAMMA, **380**
 - LOGICAL, **381**
 - logical intrinsic operation, 147
 - logical type, 62
 - logical-expr* (R724), **152**, 152, 165, 176, 178–180, 183, 184, 193
 - logical-literal-constant* (R425), 45, **62**, 138, 140
 - logical-variable* (R604), **121**, 121, 200, 240, 242, 243, 506
 - LOGICAL_KINDS, **420**
 - loop-control* (R818), **176**, 176, 178, 179, 182
 - lower-bound* (R517), **97**, 97–100
 - lower-bound-expr* (R634), **130**, 130, 162
 - lower-cobound* (R512), 95, **96**, 96
- ## M
- m* (R1009), **253**, 253, 257, 258, 263, 264
 - main program, **13**, 15, 19, 32, 35, 37
 - main-program* (R1101), 29, 32, **279**, 279, 290
 - mask-expr* (R746), **165**, 165–169, 176–179
 - masked array assignment, **14**, **165**, 502
 - masked array assignment (WHERE), 165
 - masked-elsewhere-stmt* (R747), **165**, 165, 166, 169
 - MASKL, **381**
 - MASKR, **381**
 - MATMUL, **382**
 - MAX, 324, 326, **383**
 - MAXEXPONENT, **383**
 - MAXLOC, 326, **383**
 - MAXVAL, **384**
 - MERGE, **385**
 - MERGE_BITS, **385**
 - MIN, **386**
 - MINEXPONENT, **386**
 - MINLOC, **386**
 - MINVAL, **387**
 - MOD, 26, **388**
 - mode
 - blank interpretation, 214
 - changeable, 210
 - connection, 210
 - decimal edit, 214
 - delimiter, 214
 - halting, **423**, **427**, 427, 430, 431, 433, 445, 449, 485, 511
 - IEEE rounding, 423, 424, **426**, 427, 428
 - input/output rounding, 210, 216, 222, 245, **263**, 268, 449
 - pad, 215
 - sign, 216, 268
 - underflow, **427**, 427, 430, 434, 446, 452, 511
 - model
 - bit, 327
 - extended real, 328

- integer, 328
 - real, 328
 - MODULE, 288, 289, 315, 316, 319
 - module, 13, 14, 15, 16, 18, 19, 32, 33, 37, 279
 - module* (R1104), 29, 280, 290
 - module procedure, 15, 163, 285–289, 291, 292, 297, 300, 308, 314, 316, 318, 319, 322, 416, 488, 489
 - module procedure interface body, 289, 291
 - module reference, 16, 280
 - MODULE statement, 279, 280
 - module subprogram, 19, 32, 34, 113, 313
 - module-name*, 280, 281, 492
 - module-nature* (R1110), 281, 281
 - module-stmt* (R1105), 29, 280, 280
 - module-subprogram* (R1108), 30, 280, 280, 319
 - module-subprogram-part* (R1107), 29, 77, 81, 280, 280, 283, 546
 - MODULO, 26, 388
 - MOLD= specifier, 130, 132
 - MOVE_ALLOC, 133, 194, 325, 389
 - mp-subprogram-stmt* (R1240), 30, 319, 319
 - mult-op* (R708), 45, 138, 138
 - mult-operand* (R704), 138, 138, 141
 - MVBITS, 325, 326, 390
- ## N
- n* (R1016), 253, 253, 254, 267
 - name, 14, 40, 44, 487
 - name* (R303), 23, 40, 44, 44, 45, 90, 112, 121, 190, 227, 297, 317
 - name association, 3, 3, 491, 497
 - name-value subsequence, 273, 274
 - NAME= specifier, 89, 94, 107, 240, 241, 242, 297, 297, 316, 483, 563
 - named constant, 7, 20, 37, 38, 40, 44, 52, 56, 58–60, 99, 100, 103, 106, 109, 111, 116, 122, 202, 321
 - named-constant* (R306), 45, 45, 49, 58, 84, 111, 492
 - named-constant-def* (R552), 111, 111, 492
 - NAMED= specifier, 240, 243
 - namelist formatting, 229, 273–277
 - namelist input/output statement, 220
 - NAMELIST statement, 115, 174, 274, 282
 - namelist-group-name*, 116, 218–220, 226–228, 251, 274, 277, 282, 492, 506
 - namelist-group-object* (R568), 116, 116, 227, 229, 235, 249, 273, 274, 282
 - namelist-stmt* (R567), 31, 116, 492, 506
 - NaN, 14, 258–262, 265, 336, 363, 365, 402, 405, 408, 425, 428, 431, 432, 435, 436, 450
 - NEAREST, 390
 - NEW_LINE, 264, 265, 390
 - NEWUNIT= specifier, 210, 213, 215, 232, 503, 506
 - NEXTREC= specifier, 240, 243
 - NINT, 391
 - NML= specifier, 218, 220, 506
 - NON_INTRINSIC, 281
 - NON_OVERRIDABLE attribute, 75, 76
 - NON_RECURSIVE, 315, 316
 - nonadvancing input/output statement, 207
 - nonblock DO construct, 514
 - NONE, 113, 177, 290
 - nonexecutable statement, 17, 33
 - nonlabel-do-stmt* (R817), 176, 176, 177
 - nonstandard intrinsic, xvi, 13, 24, 550
 - NOPASS, 69, 71, 76
 - NOPASS attribute, *see* PASS attribute
 - NORM2, 391
 - normal number, 428
 - normal termination, 34, 35, 79, 136, 193, 202, 204, 216, 217, 421
 - NOT, 392
 - not-op* (R718), 45, 140, 140
 - NULL, 84, 90, 153, 155, 156, 308, 326, 392, 495, 496
 - null-init* (R506), 71, 72, 90, 90, 91, 109, 110, 297
 - NULLIFY statement, 133
 - nullify-stmt* (R638), 31, 134, 506
 - NUM_IMAGES, 156, 393, 415
 - NUMBER= specifier, 240, 243
 - numeric conversion, 159
 - numeric editing, 257
 - numeric intrinsic operation, 144
 - numeric sequence type, 17, 65, 117, 119, 499, 502
 - numeric storage unit, 18, 18, 119, 420, 498, 502, 504
 - numeric type, 20, 55–58, 144–146, 148, 152, 159, 357, 382, 396, 410
 - numeric-expr* (R727), 152, 152
 - NUMERIC_STORAGE_SIZE, 420
- ## O
- O edit descriptor, 263
 - object, 7, 7, 36–38
 - object designator, 9, 37, 105, 108, 122, 154, 273
 - object-name* (R504), 90, 90, 107, 108, 111–113, 121, 128, 129, 492

- obsolescent feature, 23, 24, 27, 514–516
- octal-constant* (R466), 86, 86
- ONLY, 281, 281, 282, 290, 290, 291, 494, 538, 539
- only* (R1112), 281, 281, 282
- only-use-name* (R1113), 281, 281, 282
- OPEN statement, 27, 204, 205, 209–211, 212, 212, 216, 220, 228, 229, 233, 242, 246, 263, 275, 503, 506, 509, 531–534
- open-stmt* (R904), 31, 212, 323
- OPENED= specifier, 240, 243
- operand, 14
- operation, 51
 - defined, 8, 75, 141, 150, 151–153, 177, 285, 293, 299, 312, 323
 - elemental, 10, 143, 153, 167
 - intrinsic, 143–150
 - logical, 147
 - numeric, 144
 - relational, 148
- OPERATOR, 51, 75, 150, 281, 288, 288, 293, 541
- operator, 14, 45
 - character, 139
 - defined binary, 140
 - defined unary, 138
 - elemental, 10, 143, 424
 - logical, 140
 - numeric, 138
 - relational, 139
- operator precedence, 141
- OPTIONAL attribute, 103, 103, 111, 154, 173, 177, 287, 316
- optional dummy argument, 309
- OPTIONAL statement, 111, 174
- optional-stmt* (R550), 31, 111
- or-op* (R720), 45, 140, 140
- or-operand* (R715), 140, 140
- other-specification-stmt* (R213), 30, 30
- OUT, 101
- OUT_OF_RANGE, 393
- output statement, 217
- output-item* (R917), 217, 218, 222, 223, 235, 240
- OUTPUT_UNIT, 210, 211, 215, 231, 420
- override, 72, 80, 89, 90, 113, 229, 257, 499
- pad mode, 215
- PAD= specifier, 26, 27, 213, 215, 218, 219, 221, 233, 240, 243, 532, 533
- padding, 327, 327, 373, 399
- PARAMETER attribute, 7, 37, 85, 91, 103, 103, 111, 122
- PARAMETER statement, 34, 111, 113, 284
- parameter-stmt* (R551), 30, 111, 492
- parent component, 3, 6, 74, 78, 80, 83, 500, 525
- parent data transfer statement, 222, 229, 229–233, 248, 272
- parent type, 6, 20, 64, 67, 74, 78–80, 295, 525
- parent-identifier* (R1118), 283, 283
- parent-string* (R609), 96, 122, 122
- parent-submodule-name*, 283
- parent-type-name*, 63
- parentheses, 152
- PARITY, 394
- part-name*, 4, 123–125, 129
- part-ref* (R612), 96, 108, 109, 116, 122, 123, 123–125, 127, 129
- partially associated, 499
- PASS attribute, 69, 71, 76, 299
- passed-object dummy argument, 14, 71, 75, 76, 80, 295, 296, 301, 302, 556
- PAUSE statement, 513
- pending affector, 93, 221, 226, 485, 486
- PENDING= specifier, 240, 241, 243
- pointer, 3, 8, 9, 14, 17, 19, 21, 39, 65, 70, 129, 133, 134, 136, 156, 286, 287, 304, 322, 409, 457, 469, 495
 - procedure, 461
- pointer assignment, 14, 98, 100, 133, 160, 161, 162, 309, 496
- pointer assignment statement, 14, 19, 52, 71, 83, 153, 161, 163, 169, 334, 341
- pointer association, 3, 3, 9, 19, 20, 38, 79, 81, 83, 96, 101, 103, 105, 106, 123, 134, 136, 161, 163, 164, 181, 195, 198, 226, 286, 302, 304, 306, 308, 309, 317, 318, 330, 341, 392, 460, 461, 495–497, 500, 505, 506
- pointer association context, 101, 104, 322, 506
- pointer association status, 495
- POINTER attribute, 2, 14, 52–54, 62, 68–70, 90, 92, 98, 100, 103, 103, 105, 110, 111, 123, 126, 134, 162, 173, 188, 285–287, 289, 294, 295, 297, 305, 308–311, 316, 323, 324, 462, 466, 481, 494, 497,

- 500, 501, 555, 559
- POINTER statement, **111**, 284
- pointer-assignment-stmt* (R733), 31, 104, **161**, 168, 322, 506
- pointer-decl* (R554), **111**, 111
- pointer-object* (R639), **134**, 134, 506
- pointer-stmt* (R553), 31, **111**, 492
- polymorphic, **14**, 25, 26, 54, 71, 99, 100, 123, 134, 152, 157, 158, 163, 172, 173, 190, 191, 223, 229, 286, 287, 299, 302–305, 322, 323, 363, 389, 400, 402, 409, 495, 500
- POPCNT, **395**
- POPPAR, **395**
- POS= specifier, 206–208, 218, 219, **222**, 222, 233, 240, **244**
- position edit descriptor, 266
- position-edit-desc* (R1015), **253**, 253
- position-spec* (R927), **237**, 237
- POSITION= specifier, 213, **215**, 240, **244**, 509, 510, 533
- positional arguments, 325
- potential subobject component, **6**, 62–64, 323
- power-op* (R707), 45, **138**, 138
- pre-existing, **500**
- precedence of operators, 141
- PRECISION, 56, **395**, 444
- preconnected, **15**, 205, 210–213, 220, 226, 418–420
- preconnection, **212**
- prefix* (R1227), **315**, 315, 316, 318
- prefix-spec* (R1228), **315**, 315, 316, 322, 324
- PRESENT, 54, 68, 69, 103, 154, 309, 326, **396**, 553
- present, **309**
- primary, 137
- primary* (R701), **137**, 137, 138, 321
- PRINT statement, 205, 214, **217**, 226, 231, 233, 236
- print-stmt* (R912), 32, **218**, 323
- PRIVATE attribute, 65, 80, **92**, 92, 93, 106, 116, 323, 539
- PRIVATE statement, **74**, **75**, 77, **106**, 282
- private-components-stmt* (R445), 64, **74**, 74
- private-or-sequence* (R429), 63, **64**, 64
- proc-attr-spec* (R1215), **296**, 296, 297
- proc-component-attr-spec* (R442), **69**, 69
- proc-component-def-stmt* (R441), 68, **69**, 69
- proc-component-ref* (R739), **162**, 162, 163, 299, 309
- proc-decl* (R1216), 69, 72, 296, **297**, 297
- proc-entity-name*, 111
- proc-interface* (R1214), 69, **296**, 296, 297
- proc-language-binding-spec* (R1231), 92, 94, 296, 297, **316**, 316–318, 321, 467
- proc-pointer-init* (R1218), **297**, 297
- proc-pointer-name* (R558), **112**, 112, 134, 162
- proc-pointer-object* (R738), 161, **162**, 163, 168, 341, 506
- proc-target* (R740), 82–84, 104, 161, **162**, 163, 168, 309, 341, 497
- PROCEDURE, **69**, **75**, **296**, **319**
- procedure, 8, **15**, 16, 41, 103, 288
 - characteristics of, 286
 - dummy, 5, 9, 11, **15**, 100, 113, 155, 163, 285, 286, 288, 289, 291, 292, 295–297, 300, 308, 314, 316, 322, 484, 488, 493
 - elemental, **10**, 39, 153, 163, 297, 300, 309, 313, 315, **324**, 324–326
 - external, **15**, 24, 32, 75, 100, 113, 163, 199, 285, 286, 288–292, 296, 297, 300, 308, 314, 315, 487, 488, 492, 493, 540, 541, 546, 550
 - internal, 11, **15**, 32, 163, 285–288, 300, 308, 314, 316, 318, 484, 488, 489, 492
 - intrinsic, 325–416
 - module, **15**, 163, 285–289, 291, 292, 297, 300, 308, 314, 316, 318, 319, 322, 416, 488, 489
 - non-Fortran, 321
 - pure, **15**, 25, 26, 168, 177, **322**, **323**, 325, 329, 389, 400, 416, 429, 461
 - type-bound, 4, 12, 14, **15**, 62–64, 71, **76**, 76, 77, 79, 80, 160, 235, 281, 293, 299, 302, 303, 315, 488, 489
- procedure declaration statement, 34, 100, 287, 289, **296**, 321, 334, 489
- procedure designator, **9**, 16, 38
- procedure interface, 287
- procedure pointer, 5, 11, **14**, 14, 32, 90, 100, 103, 118, 163, 164, 285, 286, 292, 296, 300, 302, 308, 309, 314, 318, 461, 492
- procedure reference, 2, **16**, 25, 38, 103, 125, 232, 285, 293, 299, 301
 - generic, 295
 - resolving, 312
 - type-bound, 315
- PROCEDURE statement, 288, **292**
- procedure-component-name*, 162
- procedure-declaration-stmt* (R1213), 30, **296**, 297

- procedure-designator* (R1223), **299**, 299, 309, 315
- procedure-entity-name*, 297, **298**
- procedure-name*, 75, 76, 163, 164, 288, 289, 297, 299, 300, 319
- procedure-stmt* (R1206), **288**, 288, 289
- processor, **15**, 23, 24, 41
- processor dependent, **15**, 24, 41, 507–512
- PRODUCT, **396**
- program, **15**, 23, 24, 32
- program* (R201), **29**
- PROGRAM statement, **279**
- program unit, 13, 14, **15**, 15, 16, 18, 23, 24, 29, 32–35, 40, 43, 44, 46–49, 66, 104, 113, 210, 216, 279, 283, 483, 487, 495, 507, 515, 517, 537–541, 545–549, 563
- program-name*, 279
- program-stmt* (R1102), 29, **279**, 279
- program-unit* (R202), 23, **29**, 29, 32
- PROTECTED attribute, **104**, 104, 112, 117, 281
- PROTECTED statement, **112**
- protected-stmt* (R555), 31, **112**
- PUBLIC attribute, 80, **92**, 92, 93, 106, 116, 539
- PUBLIC statement, **106**, 282
- PURE, **315**, 316, 320, 322
- pure procedure, **15**, 25, 26, 168, 177, **322**, **323**, 325, 329, 389, 400, 416, 429, 461
- ## Q
- QUIET= specifier, **193**
- ## R
- r* (R1006), **252**, 252–254
- RADIX, 56, **397**, 424, 444
- RANDOM_INIT, 334, **397**, 511
- RANDOM_NUMBER, 334, **397**, 398
- RANDOM_SEED, 326, 334, **398**
- RANGE, 55, 56, **398**, 444
- RANK, 54, **399**
- rank, **15**, 17, 37–40, 69, 71, 77, 78, 82, 84, 89, 94, 96–100, 111, 119, 123–127, 129–132, 150, 152, 153, 157–159, 161–163, 165, 173, 196, 286, 293–295, 304–306, 309, 314, 324, 334, 339, 340, 353–355, 359, 360, 364, 369, 370, 374, 376, 377, 382–389, 391, 392, 394–396, 398, 400, 405, 406, 408–410, 412–415, 453, 460, 466, 491, 498, 555, 556
- RANK (*), 99, **188**
- RANK DEFAULT, 100, **188**
- rbracket* (R472), 68, 86, **87**, 89, 90, 107, 108, 112, 129, 130
- RC edit descriptor, 268
- RD edit descriptor, 268
- READ (FORMATTED), 230, **288**
- READ (UNFORMATTED), 230, **288**
- READ statement, 27, 38, 206, 210, 214, **217**, 226, 232, 233, 236, 239, 246, 505, 531–533, 535, 536
- read-stmt* (R910), 32, **217**, 218, 323, 506
- READ= specifier, 240, **244**
- READWRITE= specifier, 240, **244**
- REAL, 26, 159, 327, **399**, 425
- real and complex editing, 258
- real model, 328
- real part, **58**
- real type, 56–57, 58
- real-literal-constant* (R414), 45, **57**, 57
- real-part* (R419), **58**, 58
- REAL128, **420**
- REAL32, **420**
- REAL64, **420**
- REAL_KINDS, **420**
- REC= specifier, 207, 218, 219, **222**, 233
- RECL= specifier, 213, **215**, 228, 229, 240, **244**, 246, 504, 509
- record, **15**, 203
- record file, 10, **16**, **203**, 205, 207–209, 508
- record number, **205**
- RECURSIVE, **315**
- recursive input/output statement, **248**
- REDUCE, **400**
- reference, **16**, 38
- procedure, 25
- rel-op* (R713), 45, **139**, 139, 149, 425
- relational intrinsic operation, 148
- rename* (R1111), **281**, 281, 282, 488
- rep-char*, **60**, 60, 254, 270, 275
- REPEAT, **401**
- repeat specification, **252**
- representation method, 55, 56, 59, 62
- RESHAPE, 87, 88, **401**
- resolving procedure reference, 312
- resolving procedure references
- defined input/output, 235
- restricted expression, **154**
- RESULT, 316, **317**, 317, 319, 320, 489

- result-name*, 316, 317, 319, 320, 492
- RETURN statement, 35, 79, 104, 119, 134, 135, 175, 180, **320**, 460, 505
- return-stmt* (R1243), 32, 34, **320**, 320
- REWIND statement, 204, 205, 207, 233, 236, **238**, 238, 531
- rewind-stmt* (R926), 32, **237**, 323
- RN edit descriptor, 268
- round edit descriptor, 268
- round-edit-desc* (R1019), 253, **254**
- ROUND= specifier, 213, **216**, 218, 219, **222**, 233, 240, **245**, 269
- rounding mode
- IEEE, 423, 424, **426**, 427, 428, 434, 443, 445, 450
 - input/output, 210, 216, 222, 245, **263**, 268, 449
- RP edit descriptor, 268
- RRSPACING, **402**
- RU edit descriptor, 268
- RZ edit descriptor, 268
- ## S
- S edit descriptor, 268
- SAME_TYPE_AS, 68, 69, **402**
- SAVE attribute, 16, 21, 27, 72, 79, 91, 94, 95, **104**, 104, 105, 108, 112, 117, 119, 135, 297, 322, 496
- SAVE statement, **112**, 174, 284, 489
- save-stmt* (R556), 31, **112**, 492
- saved, **16**, 495, 501
- saved-entity* (R557), **112**, 112, 174
- scalar, **16**, 16, 18, 324
- scalar-xyz* (R103), **23**, 23
- SCALE, **403**
- scale factor, **253**, 268
- SCAN, **403**
- scoping unit, 3, 11, 12, **16**, 21, 32, 34, 35, 37, 40, 41, 60, 65, 66, 75, 78, 82, 91, 93, 94, 100, 102, 105, 106, 112, 113, 116, 118, 119, 135, 155, 163, 174, 177, 181, 221, 224, 280–282, 287, 289–291, 295, 312–314, 316, 319, 321, 423, 425, 483, 488–494, 497, 499, 500, 504, 539, 550, 556
- section subscript, 127
- section-subscript* (R620), 21, 123, **125**, 125, 127–129
- segment, **194**
- SELECT CASE construct, 35, **185**, 515, 527
- SELECT CASE statement, 47, **185**
- SELECT RANK construct, 35, 99, 100, **187**, 309
- SELECT RANK statement, 100, **187**
- SELECT TYPE construct, 35, 52, 53, **189**, 309, 490, 491, 506
- SELECT TYPE statement, 47, **190**, 494
- select-case-stmt* (R836), 4, **185**, 185, 192
- select-construct-name*, 187, 188, 190
- select-rank-case-stmt* (R845), 187, **188**, 188
- select-rank-construct* (R843), 31, **187**, 188
- select-rank-stmt* (R844), 4, **187**, 187, 188, 192
- select-type-construct* (R847), 31, **190**, 190
- select-type-stmt* (R848), 4, **190**, 190, 192
- SELECTED_CHAR_KIND, 59, **403**
- SELECTED_INT_KIND, 55, **404**
- SELECTED_REAL_KIND, 56, 326, **404**, 517
- selector, 172
- selector* (R805), **172**, 172, 173, 187, 190, 191, 309, 495, 506
- separate module procedure, **319**
- separate module subprogram statement, **319**
- separate-module-subprogram* (R1239), 30, 280, **319**, 319
- sequence, **16**
- sequence association, 308
- SEQUENCE attribute, 16, 63, **64**, 65, 66, 79, 118, 162, 163, 190, 465
- SEQUENCE statement, **64**
- sequence structure, **16**
- sequence type, **16**, 16, 25, 63, **65**, 65, 116, 117, 419, 466, 498
- character, **17**, **65**, 117, 119, 499, 502
 - numeric, **17**, **65**, 117, 119, 499, 502
- sequence-stmt* (R431), **64**, 64
- sequential access, **205**
- sequential access data transfer statement, **222**
- SEQUENTIAL= specifier, 240, **245**
- SET_EXPONENT, **405**
- SHAPE, 54, **405**
- shape, **17**, 38, 304
- SHARED, **177**, 180
- SHIFTA, **406**
- SHIFTL, **406**
- SHIFTR, **406**
- SIGN, 26, 27, 57, **407**
- sign* (R412), 55, **56**, 56, 57, 258
- sign mode, 216, 257, **268**
- sign-edit-desc* (R1017), 253, **254**
- SIGN= specifier, 213, **216**, 218, 219, **222**, 240, **245**, 268

- signed-digit-string* (R410), **56**, **57**, 257–259
- signed-int-literal-constant* (R407), **55**, **55**, **58**, **109**, **253**
- signed-real-literal-constant* (R413), **57**, **58**, **109**
- significand* (R415), **57**, **57**
- simply contiguous, **17**, **128**, **129**, **129**, **163**, **303–307**, **468**, **469**
- SIN, **407**
- SINH, **407**
- SIZE, **54**, **408**
- size, **17**, **38**
- size of a common block, **119**
- SIZE= specifier, **xvi**, **218**, **222**, **240**, **245**, **246–249**, **502**, **505**, **506**, **532**, **535**
- source-expr* (R630), **130**, **130–133**, **323**, **495–497**
- SOURCE= specifier, **130**, **131–133**, **323**, **418**, **495–497**, **503**, **504**
- SP edit descriptor, **268**
- SPACING, **408**
- special character, **43**
- specific interface, **12**, **235**, **289**, **289**, **292**, **297**, **313**
- specific interface block, **12**, **12**, **289**
- specific name, **17**
- specific-procedure* (R1207), **288**, **288**, **290**, **292**
- specification, **89–120**
- specification expression, **17**, **20**, **35**, **67–69**, **78**, **93**, **125**, **154**, **155**, **155**, **174**, **320**, **425**, **507**, **508**, **515**
- specification function, **155**
- specification inquiry, **154**
- specification-construct* (R208), **30**, **30**, **174**
- specification-expr* (R728), **4**, **53**, **59**, **91**, **96**, **97**, **154**, **154**, **324**
- specification-part* (R204), **29**, **30**, **30**, **35**, **75**, **92**, **93**, **106**, **155**, **156**, **279**, **280**, **283**, **284**, **288**, **290**, **316**, **318**, **319**, **322**, **324**
- SPREAD, **408**
- SQRT, **26**, **409**, **429**, **450**, **451**
- SS edit descriptor, **268**
- standard intrinsic, **xvi**, **13**, **24**, **416**
- standard-conforming program, **17**, **23**, **24**
- stat-variable* (R628), **130**, **130**, **131**, **134**, **136**, **196**, **506**, **508**
- STAT= specifier, **130**, **132–134**, **136**, **196**, **202**, **420**, **421**, **503**, **508**
- STAT_LOCKED, **202**, **420**
- STAT_LOCKED_OTHER_IMAGE, **202**, **420**
- STAT_STOPPED_IMAGE, **136**, **202**, **421**
- STAT_UNLOCKED, **202**, **421**
- statement, **17**, **47**
- accessibility, **106**
 - ALLOCATABLE, **107**
 - ALLOCATE, **52**, **53**, **60**, **93**, **96**, **98**, **130**, **136**, **162**, **194**, **418**, **475**, **476**, **495**, **496**, **503**, **504**, **508**
 - arithmetic IF, **514**
 - ASSIGN, **513**
 - assigned GO TO, **513**
 - assignment, **14**, **38**, **52**, **78**, **157**, **169**, **453**, **502**
 - ASSOCIATE, **172**, **494**
 - ASYNCHRONOUS, **107**, **174**, **284**, **490**, **492**
 - attribute specification, **106–120**
 - BACKSPACE, **204**, **207**, **233**, **236**, **237**, **238**, **531**, **533**
 - BIND, **107**, **284**, **483**, **489**
 - BLOCK, **91**, **96**, **98**, **173**, **503**
 - BLOCK DATA, **47**, **279**, **283**
 - CALL, **19**, **192**, **194**, **285**, **299**, **312**, **320**, **389**
 - CASE, **185**
 - CLASS DEFAULT, **190**
 - CLASS IS, **190**
 - CLOSE, **204**, **205**, **209**, **211**, **212**, **216**, **216**, **233**, **236**, **531**
 - COMMON, **6**, **118**, **118–120**, **174**, **282**, **284**, **489**, **499**, **514**
 - component definition, **68**
 - computed GO TO, **4**, **192**, **193**, **514**, **515**
 - CONTAINS, **33**, **34**, **75**, **320**
 - CONTIGUOUS, **108**
 - CONTINUE, **193**, **513**
 - CRITICAL, **151**, **175**, **194**
 - CYCLE, **172**, **176**, **179**, **180**, **516**
 - DATA, **27**, **34**, **86**, **91**, **108**, **119**, **284**, **392**, **490**, **493**, **501**, **514**, **515**
 - data transfer, **27**, **46**, **203–209**, **211**, **217**, **222**, **225–227**, **232**, **236**, **238**, **246–249**, **251**, **252**, **263**, **268**, **270–272**, **274**, **276**, **419**, **502**, **504**, **509**, **510**, **531**, **532**, **535**, **536**
 - DEALLOCATE, **134**, **136**, **194**, **418**, **476**, **508**
 - defined assignment, **161**, **161**, **312**, **505**
 - derived type definition, *see* statement, TYPE
 - DIMENSION, **110**, **284**
 - DO, **176**, **502**, **514**, **516**
 - DO CONCURRENT, **168**, **176**
 - DO WHILE, **176**

ELSE, **183**
 ELSE IF, **47, 183**
 ELSEWHERE, **47, 165**
 END, **10, 34, 104, 119, 134, 135, 194, 460, 505**
 END ASSOCIATE, **47, 172**
 END BLOCK, **47, 135, 174**
 END BLOCK DATA, **47, 283**
 END CRITICAL, **47, 151, 175, 194**
 END DO, **47, 177**
 END ENUM, **47, 84**
 END FORALL, **47, 168**
 END FUNCTION, **47, 317**
 END IF, **47, 184, 513**
 END INTERFACE, **47, 288**
 END MODULE, **47, 280**
 END PROCEDURE, **47, 319**
 END PROGRAM, **47, 279**
 END SELECT, **47, 185, 190**
 END SUBMODULE, **47, 283**
 END SUBROUTINE, **47, 318**
 END TYPE, **47, 64**
 END WHERE, **47, 165**
 ENDFILE, **47, 204, 205, 207, 214, 233, 236, 238, 531**
 ENTRY, **9, 34, 150, 161, 280, 285, 289, 315, 316, 319, 489, 499, 514, 516**
 ENUM, **84**
 ENUMERATOR, **84**
 EQUIVALENCE, **116, 116–120, 174, 282, 284, 499, 514, 516**
 ERROR STOP, **35, 36, 193, 508**
 EVENT POST, **194, 199, 200, 202, 361, 418, 503, 506, 508**
 EVENT WAIT, **194, 199, 200, 202, 418, 503, 506, 508**
 executable, **17, 17, 33**
 EXIT, **172, 180, 192**
 EXTERNAL, **100, 296**
 file inquiry, **239**
 file positioning, **204, 237**
 FINAL, **10, 77**
 FLUSH, **205, 236, 239, 248**
 FORALL, **143, 169, 490, 502**
 FORMAT, **24, 34, 46, 220, 251, 251, 280**
 formatted input/output, **203, 219**
 FUNCTION, **9, 53, 113, 150, 154, 279, 315, 316, 319, 320, 489**
 GENERIC, **75, 76, 290, 292, 313**
 GO TO, **4, 47, 192, 193**
 IF, **143, 184**
 IMPLICIT, **34, 113, 116, 284**
 IMPLICIT NONE, **113**
 IMPORT, **34, 290, 493**
 input/output, **203–248, 502**
 INQUIRE, **26, 205, 206, 208, 209, 211, 212, 221, 222, 232, 233, 236, 239, 248, 249, 419, 502, 504, 506, 510, 531**
 INTENT, **110, 174**
 INTERFACE, **288, 541**
 INTRINSIC, **284, 298**
 intrinsic assignment, **83, 93, 135, 136, 153, 157, 161, 163, 202, 239, 248, 271, 275, 323, 502, 508**
 list-directed input/output, **220**
 LOCK, **194, 200, 202, 419, 420, 503, 506**
 MODULE, **279, 280**
 NAMELIST, **115, 174, 274, 282**
 namelist input/output, **220**
 nonexecutable, **17, 33**
 NULLIFY, **133**
 OPEN, **27, 204, 205, 209–211, 212, 212, 216, 220, 228, 229, 233, 242, 246, 263, 275, 503, 506, 509, 531–534**
 OPTIONAL, **111, 174**
 PARAMETER, **34, 111, 113, 284**
 PAUSE, **513**
 POINTER, **111, 284**
 pointer assignment, **14, 19, 52, 71, 83, 153, 161, 163, 169, 334, 341**
 PRINT, **205, 214, 217, 226, 231, 233, 236**
 PRIVATE, **74, 75, 77, 106, 282**
 PROCEDURE, **288, 292**
 procedure declaration, **34, 100, 287, 289, 296, 321, 334, 489**
 PROGRAM, **279**
 PROTECTED, **112**
 PUBLIC, **106, 282**
 READ, **27, 38, 206, 210, 214, 217, 226, 232, 233, 236, 239, 246, 505, 531–533, 535, 536**
 RETURN, **35, 79, 104, 119, 134, 135, 175, 180, 320, 460, 505**
 REWIND, **204, 205, 207, 233, 236, 238, 238, 531**

- SAVE, **112**, 174, 284, 489
- SELECT CASE, 47, **185**
- SELECT RANK, 100, **187**
- SELECT TYPE, 47, **190**, 494
- separate module subprogram, **319**
- SEQUENCE, **64**
- statement function, 9, 34, 60, 174, 280, 313, 320, **321**, 490, 491, 515
- STOP, 35, **193**, 194, 508
- SUBMODULE, 279, **283**
- SUBROUTINE, 9, 161, 279, 315, **318**, 320
- SYNC ALL, 194, **195**, 197, 202
- SYNC IMAGES, 194, **196**, 202
- SYNC MEMORY, 194, **198**, 202, 561
- TARGET, **112**, 284
- TYPE, **63**, 67, 92, 492
- type declaration, 34, 53, 72, **89**, 89–91, 100, 113, 116, 119, 155, 280, 284, 317, 319, 321, 501
- type guard, 60, **190**
- TYPE IS, **190**
- type parameter definition, **66**
- type-bound procedure, **75**, **76**
- unformatted input/output, 204, **219**
- UNLOCK, 194, **200**, 202, 419–421, 503, 506
- USE, 3, 16, 34, 66, 106, **280**, 284, 313, 314, 488, 491, 494, 538, 539, 545
- VALUE, **112**, 174
- VOLATILE, **113**, 174, 284, 490, 492
- WAIT, 211, 221, **236**, 236, 535
- WHERE, 14, 143, **165**
- WRITE, 205, 210, 214, **217**, 226, 231, 233, 236, 248, 502, 531, 534, 535
- statement entity, **18**, 487, 490
- statement function, 321–322, 515
- statement function statement, 9, 34, 60, 174, 280, 313, 320, **321**, 490, 491, 515
- statement keyword, **13**, 40
- statement label, 4, **18**, **46**, 46–49, 300, 487
- statement order, **33**
- STATUS= specifier, 212, 213, **216**, **217**, 217, 509, 534
- stmt-function-stmt* (R1245), 30, 280, 283, 289, **321**, 492
- STOP statement, 35, **193**, 194, 508
- stop-code* (R857), **193**, 193, 194
- stop-stmt* (R855), 32, 79, **193**
- storage association, **3**, 3, 40, 116–120, 319, 322, 409, 497–500
- storage sequence, **18**, 63, 65, 117–120, 284, 341, **498**, 498, 499
- storage unit, **18**, 18, 116–120, 221, 225, 233, 236, 284, 308, 341, 498–500
 - character, **18**, 18, 99, 117, 119, 417, 498, 502, 504
 - file, **10**, 18, 203, 206–209, 215, 220, 222, 228, 238, 244–246, 418, 498, 508–510
 - numeric, **18**, 18, 119, 420, 498, 502, 504
 - unspecified, **18**, 18, 498, 502, 504
- STORAGE_SIZE, 86, **409**
- stream access, **206**
- stream access data transfer statement, **222**
- stream file, **10**, **18**, **203**, 206, 208, 246, 508
- STREAM= specifier, 240, **245**
- stride* (R622), **126**, 126–128, 225
- structure, 6, **18**, 36, 37, 63
- structure component, **18**, 109, 122, 123, 125, 464, 525
- structure constructor, 6, 13, **18**, 36, 40, 51, 74, 82, 83, 109, 110, 152, 154, 155, 392, 419, 489, 520
- structure-component* (R613), 108, 109, 121, 122, **123**, 129, 130, 134
- structure-constructor* (R456), 18, **82**, 82, 109, 137, 323
- subcomponent, 6, 8, 72, 82, 162, 495–497, 501, 503–505
- submodule, 13, 15, **18**, 18, 19, 32, 33, 37, **283**
- submodule* (R1116), 29, **283**
- submodule identifier, **283**
- SUBMODULE statement, 279, **283**
- submodule-name*, 283
- submodule-stmt* (R1117), 29, **283**, 283
- subobject, 2, 6, 7, **18**, 37–39, 101, **123**, 303, 495, 496
- subprogram, 13, **18**, 32, 34, 35, 37, 113
 - elemental, **10**, 315, 316, 324
 - external, 15, **19**, 32, 285
 - internal, **19**, 32, 34, 285, 492
 - module, **19**, 32, 34
- subroutine, **19**
 - atomic, **19**, 194, 195, 325, 328, 329, 343–347, 361
- subroutine reference, 312
- SUBROUTINE statement, 9, 161, 279, 315, **318**, 320
- subroutine-name*, 289, 318, 489
- subroutine-stmt* (R1236), 29, 288, 289, 316, **318**, 318, 489, 492
- subroutine-subprogram* (R1235), 18, 29, 30, 280, **318**, 319
- subroutines
 - intrinsic, 325

- subscript, **125**
 - section, **127**
- subscript* (R619), **109, 125, 125, 126, 128, 225**
- subscript triplet, **127**
- subscript-triplet* (R621), **125, 126, 126–128**
- substring, **122**
- substring* (R608), **116, 117, 121, 122**
- substring ending point., **122**
- substring starting point, **122**
- substring-range* (R610), **96, 122, 122, 124–126, 129, 225**
- suffix* (R1233), **316, 317, 319**
- SUM, **410**
- SYNC ALL statement, **194, 195, 197, 202**
- SYNC IMAGES statement, **194, 196, 202**
- SYNC MEMORY statement, **194, 198, 202, 561**
- sync-all-stmt* (R858), **32, 195**
- sync-images-stmt* (R860), **32, 196**
- sync-memory-stmt* (R862), **32, 198**
- sync-stat* (R859), **195, 196, 196, 198–200**
- synchronous input/output, **214, 220, 222, 225**
- SYSTEM_CLOCK, **410**
- T**
- T edit descriptor, **267**
- TAN, **411**
- TANH, **411**
- target, **9, 19, 38, 39, 54, 71–73, 78, 84, 91, 95, 96, 98, 100–104, 109, 110, 121, 123, 130, 132–136, 152, 153, 158, 161, 162, 164, 168, 169, 223, 227, 229, 297, 300, 302, 305, 306, 308, 459, 461, 462, 494–497, 500, 503, 505, 506**
- TARGET attribute, **3, 19, 72, 103, 105, 105, 112, 117, 119, 133, 134, 162, 173, 188, 287, 294, 303, 304, 306, 310, 311, 389, 459, 462, 482, 495–497, 505, 552, 553**
- TARGET statement, **112, 284**
- target-decl* (R560), **112, 112**
- target-stmt* (R559), **31, 112, 492**
- THEN, **183**
- THIS_IMAGE, **156, 411**
- TINY, **412**
- TKR compatible, **295**
- TL edit descriptor, **267**
- totally associated, **499**
- TR edit descriptor, **267**
- TRAILZ, **412**
- TRANSFER, **156, 412**
- transfer of control, **171, 192, 247**
- transformational function, **19, 156, 321, 325, 325, 326, 329, 347, 348, 417, 429**
- TRANSPPOSE, **413**
- TRIM, **413**
- truncation, **327, 373, 399**
- TYPE, **53**
- type, **19, 36, 51–87**
 - abstract, **19, 53, 76, 79, 79, 82, 123, 130**
 - character, **59–62**
 - complex, **58**
 - declared, **19, 54, 71, 83, 87, 123, 124, 131, 134, 150, 152, 157, 160–163, 172, 190, 191, 235, 294, 299, 302, 305, 315, 321, 363, 389, 402, 491**
 - derived, **8, 18, 19, 36, 40, 51, 62–84, 87, 465**
 - dynamic, **14, 19, 21, 54, 78, 79, 81, 84, 87, 105, 131, 132, 134, 136, 150, 152, 158, 160, 161, 163, 173, 189, 190, 198, 235, 299, 305, 315, 333, 363, 389, 402, 409, 491, 495, 500, 526, 567**
 - expression, **152**
 - extended, **3, 6, 12, 19, 20, 67, 74, 78–80, 500, 517, 523**
 - extensible, **19, 53, 63, 71, 79, 230, 363, 402, 525, 558**
 - extension, **20, 54, 79, 81, 190, 191, 305, 363, 558**
 - integer, **55–56**
 - intrinsic, **6, 20, 36, 51, 55–62**
 - logical, **62**
 - numeric, **20, 55–58, 144–146, 148, 152, 159, 357, 382, 396, 410**
 - operation, **153**
 - parent, **6, 20, 64, 67, 74, 78–80, 295, 525**
 - primary, **152**
 - real, **56–57, 58**
- type compatible, **20, 54, 71, 130, 131, 157, 162, 295, 303, 389**
- type conformance, **157**
- type declaration statement, **34, 53, 72, 89, 89–91, 100, 113, 116, 119, 155, 280, 284, 317, 319, 321, 501**
- type equality, **65**
- type guard statement, **60, 190**
- TYPE IS statement, **190**
- type parameter, **2, 4, 12, 13, 17, 20, 25, 36, 52, 54, 55, 65, 67, 71, 87, 90, 91, 111, 119, 157, 173, 286, 303, 324, 389, 459, 465, 489**

- type parameter definition statement, **66**
 - type parameter inquiry, **20, 124, 152, 154**
 - type parameter keyword, **13, 40, 82**
 - type parameter order, **20, 67**
 - type specifier, **53**
 - CHARACTER, **59**
 - CLASS, **54**
 - COMPLEX, **58**
 - derived type, **53**
 - DOUBLE PRECISION, **57**
 - INTEGER, **55**
 - LOGICAL, **62**
 - REAL, **57**
 - TYPE, **53**
 - TYPE statement, **63, 67, 92, 492**
 - type-attr-spec* (R428), **63, 63, 79**
 - type-bound procedure, **4, 12, 14, 15, 62–64, 71, 76, 76, 77, 79, 80, 160, 235, 281, 293, 299, 302, 303, 315, 488, 489**
 - type-bound procedure statement, **75, 76**
 - type-bound-generic-stmt* (R451), **75, 75, 293**
 - type-bound-proc-binding* (R448), **75, 75**
 - type-bound-proc-decl* (R450), **75, 75**
 - type-bound-procedure-part* (R446), **63, 65, 75, 77, 465**
 - type-bound-procedure-stmt* (R449), **75, 75**
 - type-declaration-stmt* (R501), **30, 60, 89, 89, 322, 492**
 - type-guard-stmt* (R849), **190, 190**
 - type-name*, **63, 64, 66, 76, 81**
 - type-param-attr-spec* (R434), **66, 67, 67**
 - type-param-decl* (R433), **66, 66, 67**
 - type-param-def-stmt* (R432), **63, 66, 67**
 - type-param-inquiry* (R616), **20, 124, 125, 137, 489**
 - type-param-name*, **63, 66, 67, 69, 124, 137, 489, 492**
 - type-param-spec* (R455), **81, 81, 82**
 - type-param-value* (R401), **20, 52, 52, 53, 59, 60, 69, 81, 82, 130, 132, 516**
 - type-spec* (R402), **53, 53, 60, 87, 130–132, 190**
- ## U
- UBOUND, **54, 188, 304, 414**
 - UCOBOUND, **414**
 - ultimate argument, **21, 132, 135, 302, 307**
 - ultimate component, **6, 62–64, 68, 94, 96, 99, 100, 105, 116, 118, 131, 133, 156, 229, 303, 498**
 - undefined, **9, 21, 38, 134, 495, 496, 501, 502**
 - undefinition of variables, **501**
 - underflow mode, **427, 427, 430, 434, 446, 452, 511**
 - underscore* (R302), **43, 43**
 - UNFORMATTED, **230, 231, 288**
 - unformatted data transfer, **228**
 - unformatted input/output statement, **204, 219**
 - unformatted record, **203**
 - UNFORMATTED= specifier, **240, 245**
 - Unicode file, **214**
 - unit, **6, 15, 21, 204–206, 209, 209–217, 221, 222, 225–227, 229, 231, 232, 236, 237, 239, 241–245, 248, 266, 272, 418, 419, 502, 504, 510, 531–536**
 - UNIT= specifier, **212, 217, 218, 236, 237, 239, 240**
 - unlimited polymorphic, **21, 54, 54, 87, 118, 130, 162, 190, 305, 363, 402, 409, 567**
 - unlimited-format-item* (R1005), **251, 252, 252, 255**
 - UNLOCK statement, **194, 200, 202, 419–421, 503, 506**
 - unlock-stmt* (R870), **32, 200**
 - unordered segments, **194, 195, 328, 334, 361, 397**
 - UNPACK, **415**
 - unsaved, **21, 133, 134, 318, 496, 497, 503–505**
 - unspecified storage unit, **18, 18, 498, 502, 504**
 - until-spec* (R867), **200, 200**
 - UNTIL_COUNT= specifier, **200, 361**
 - upper-bound* (R518), **97, 97, 98**
 - upper-bound-expr* (R635), **130, 130, 162**
 - upper-cobound* (R513), **95, 96, 96**
 - use association, **3, 3, 14, 33, 41, 60, 80, 93, 104, 106, 113, 116–118, 155, 163, 280, 279–283, 289, 319, 322, 490–492, 495**
 - USE statement, **3, 16, 34, 66, 106, 280, 284, 313, 314, 488, 491, 494, 538, 539, 545**
 - use-defined-operator* (R1115), **281, 281, 282**
 - use-name*, **281, 282, 488**
 - use-stmt* (R1109), **30, 174, 281, 281, 492**
- ## V
- v* (R1012), **232, 253, 253, 266**
 - VALUE attribute, **54, 71, 77, 100, 105, 105, 112, 226, 286, 287, 289, 293, 294, 302–304, 306, 316, 322, 324, 467, 468, 485, 497, 563, 565**
 - value separator, **269**
 - VALUE statement, **112, 174**
 - value-stmt* (R561), **31, 112**
 - variable, **7, 18, 21, 37, 40, 44, 103**
 - definition & undefinition, **501**
 - variable* (R602), **83, 108, 121, 121, 129, 157–160, 162, 167–169, 172, 190, 200, 222, 299, 309, 453, 506**

- variable-name* (R603), 116, 118, **121**, 121, 122, 130, 134, 162, 177, 492, 506
- vector subscript, **21**, 39, 72, 96, 123, 127, 128, 172, 190, 209, 273, 303, 304, 310, 494, 497, 552
- vector-subscript* (R623), **126**, 126, 127
- VERIFY, **416**
- VOLATILE attribute, **105**, 105, 106, 113, 162, 163, 173, 280, 282, 286, 287, 304, 305, 307, 492, 497, 503, 505, 524
- VOLATILE statement, **113**, 174, 284, 490, 492
- volatile-stmt* (R562), 31, **113**
- ## W
- w* (R1008), **253**, 253, 257–266, 270, 272, 275
- wait operation, 212, 216, 222, 225, 226, **236**, 236–237, 239, 243, 244, 246, 247
- WAIT statement, 211, 221, **236**, 236, 535
- wait-spec* (R923), **236**, 236
- wait-stmt* (R922), 32, **236**, 323
- WHERE construct, 14, **165**
- WHERE statement, 14, 143, **165**
- where-assignment-stmt* (R745), 143, **165**, 165–167, 169
- where-body-construct* (R744), **165**, 165–167
- where-construct* (R742), 31, **165**, 165, 166, 168, 169
- where-construct-name*, 165, 166
- where-construct-stmt* (R743), 4, **165**, 165, 166, 169, 192
- where-stmt* (R741), 32, **165**, 165, 166, 168, 169
- WHILE, **176**, 178, 179
- whole array, **21**, **125**, 125, 126, 377, 414
- WRITE (FORMATTED), 230, 231, **288**
- WRITE (UNFORMATTED), 230, 231, **288**
- WRITE statement, 205, 210, 214, **217**, 226, 231, 233, 236, 248, 502, 531, 534, 535
- write-stmt* (R911), 32, **217**, 218, 323, 506
- WRITE= specifier, 240, **245**
- ## X
- X edit descriptor, 267
- xyz-list* (R101), **23**
- xyz-name* (R102), **23**
- ## Z
- Z edit descriptor, 263
- zero-size array, 38, 98, 109
- ZZZUTI013, 92
- ZZZUTI014, 92
- ZZZUTI015, 180